

AVL Trees

D Oisín Kidney

July 28, 2018

```

open import Relation.Binary.PropositionalEquality
open import Level using (Lift; lift;  $\perp$ _; lower)
open import Data.Nat as  $\mathbb{N}$  using ( $\overline{\mathbb{N}}$ ; suc; zero; pred)
open import Data.Product
open import Data.Unit renaming ( $\top$  to 1)
open import Data.Maybe
open import Function
open import Data.Bool
open import Data.Empty renaming ( $\perp$  to 0)

module AVL
  {k r} (Key : Set k)
  {_<_ : Rel Key r}
  (isStrictTotalOrder : IsStrictTotalOrder  $\_ \equiv \_ < \_$ )
  where

    open IsStrictTotalOrder isStrictTotalOrder

infix 5 [ $\_$ ]

data  $\top$  : Set k where
   $\perp$   $\top$  :  $\top$ 
  [ $\_$ ] : (k : Key)  $\rightarrow$   $\top$ 

infix 4  $\frac{\top}{\perp} < \_$ 
 $\frac{\top}{\perp} < \_$  :  $\frac{\top}{\perp} \rightarrow \top \rightarrow$  Set r
 $\frac{\perp}{\perp} < \perp$  = Lift r 0
 $\frac{\perp}{\perp} < \top$  = Lift r 1
 $\frac{\perp}{\perp} < [\_]$  = Lift r 1
 $\frac{\top}{\perp} < \_$  = Lift r 0
 $\frac{[\_]}{\perp} < \perp$  = Lift r 0
 $\frac{[\_]}{\perp} < \top$  = Lift r 1
 $\frac{[x]}{\perp} < [y]$  =  $x < y$ 

```

```

x<⊥ : ∀ {x} → x ⊥ < ⊥ → Lift r 0
x<⊥ {⊥} = lift ∘ lower
x<⊥ {⊤} = lift ∘ lower
x<⊥ {[ _ ]} = lift ∘ lower

⊤<-trans : ∀ {x y z} → x ⊤ < y → y ⊤ < z → x ⊤ < z
⊤<-trans {⊥} {y} {⊥} _ y<z = x<⊥ {x = y} y<z
⊤<-trans {⊥} {} {⊤} _ _ = _
⊤<-trans {⊥} {} {[ _ ]} _ _ = _
⊤<-trans {⊤} {} {} (lift ()) _ = _
⊤<-trans {[ _ ]} {y} {⊥} _ y<z = x<⊥ {x = y} y<z
⊤<-trans {[ _ ]} {} {⊤} _ _ = _
⊤<-trans {[ _ ]} {⊥} {[ _ ]} (lift ()) _ = _
⊤<-trans {[ _ ]} {⊤} {[ _ ]} (lift ()) _ = _
⊤<-trans {[ x ]} {[ y ]} {[ z ]} x<y y<z =
  IsStrictTotalOrder.trans isStrictTotalOrder x<y y<z

```

```

infix 4 _<_<_

```

```

_<_<_ : ⊤ → Key → ⊤ → Set r
l < x < u = l ⊤ < [ x ] × [ x ] ⊤ < u

```

```

module Bounded where

```

```

data { _ ⊔ _ } ≡ _ : ℕ → ℕ → ℕ → Set where
  ⋈ : ∀ {n} → { suc n ⊔ n } ≡ suc n
  ⊔ : ∀ {n} → { n ⊔ n } ≡ n
  ⋇ : ∀ {n} → { n ⊔ suc n } ≡ suc n

⋈ ⇒ ⋈ : ∀ {x y z} → { x ⊔ y } ≡ z → { z ⊔ x } ≡ z
⋈ ⇒ ⋈ ⋈ = ⊔
⋈ ⇒ ⋈ ⊔ = ⊔
⋈ ⇒ ⋈ ⋇ = ⋈

⋇ ⇒ ⋇ : ∀ {x y z} → { x ⊔ y } ≡ z → { y ⊔ z } ≡ z
⋇ ⇒ ⋇ ⋈ = ⋇
⋇ ⇒ ⋇ ⊔ = ⊔
⋇ ⇒ ⋇ ⋇ = ⊔

```

```


data Tree {v} (V : Key → Set v) (l u : ⊤) : ℕ → Set (k ⊔ v ⊔ r) where
  leaf : (l < u : l ⊤ < u) → Tree V l u 0
  node : ∀ {h lh rh}
    (k : Key)
    (v : V k)
    (bl : { lh ⊔ rh } ≡ h)

```


$(lk : \text{Tree } V l [k] lh)$
 $(ku : \text{Tree } V [k] u rh) \rightarrow$
 $\text{Tree } V l u (\text{suc } h)$

$\text{Altered} : \forall \{v\} (V : \text{Key} \rightarrow \text{Set } v) (l u : \mathbb{I}) (n : \mathbb{N}) \rightarrow \text{Set } (k \sqcup v \sqcup r)$
 $\text{Altered } V l u n = \exists [inc] (\text{Tree } V l u (\text{if } inc \text{ then } \text{suc } n \text{ else } n))$

$\text{pattern } 0+ \text{ } tr = \text{false} , tr$
 $\text{pattern } 1+ \text{ } tr = \text{true} , tr$



$\text{rot}^r : \forall \{lb ub rh v\} \{V : \text{Key} \rightarrow \text{Set } v\}$
 $\rightarrow (k : \text{Key})$
 $\rightarrow V k$
 $\rightarrow \text{Tree } V lb [k] (\text{suc } (\text{suc } rh))$
 $\rightarrow \text{Tree } V [k] ub rh$
 $\rightarrow \text{Altered } V lb ub (\text{suc } (\text{suc } rh))$
 $\text{rot}^r u uc (\text{node } v vc \nearrow ta tb) tc = 0+ (\text{node } v vc \div ta (\text{node } u uc \div tb tc))$
 $\text{rot}^r u uc (\text{node } v vc \div ta tb) tc = 1+ (\text{node } v vc \searrow ta (\text{node } u uc \nearrow tb tc))$
 $\text{rot}^r u uc (\text{node } v vc \searrow ta (\text{node } w wc bw tb tc)) td =$
 $0+ (\text{node } w wc \div (\text{node } v vc (\searrow \Rightarrow \nearrow bw) ta tb) (\text{node } u uc (\nearrow \Rightarrow \searrow bw) tc td))$



$\text{rot}^l : \forall \{lb ub lh v\} \{V : \text{Key} \rightarrow \text{Set } v\}$
 $\rightarrow (k : \text{Key})$
 $\rightarrow V k$
 $\rightarrow \text{Tree } V lb [k] lh$
 $\rightarrow \text{Tree } V [k] ub (\text{suc } (\text{suc } lh))$
 $\rightarrow \text{Altered } V lb ub (\text{suc } (\text{suc } lh))$
 $\text{rot}^l u uc tc (\text{node } v vc \searrow tb ta) = 0+ (\text{node } v vc \div (\text{node } u uc \div tc tb) ta)$
 $\text{rot}^l u uc tc (\text{node } v vc \div tb ta) = 1+ (\text{node } v vc \nearrow (\text{node } u uc \searrow tc tb) ta)$
 $\text{rot}^l u uc td (\text{node } v vc \nearrow (\text{node } w wc bw tc tb) ta) =$
 $0+ (\text{node } w wc \div (\text{node } u uc (\searrow \Rightarrow \nearrow bw) td tc) (\text{node } v vc (\nearrow \Rightarrow \searrow bw) tb ta))$

$\text{insert} : \forall \{l u h v\} \{V : \text{Key} \rightarrow \text{Set } v\} (k : \text{Key})$

```

→ V k
→ (V k → V k → V k)
→ Tree V l u h
→ l < k < u
→ Altered V l u h
insert v vc f (leaf l < u) (l, u) = 1+ (node v vc ▸ (leaf l) (leaf u))
insert v vc f (node k kc bl tl tr) prf with compare v k
insert v vc f (node k kc bl tl tr) (l, _)
| tri < a _ _ with insert v vc f tl (l, a)
... | 0+ tl' = 0+ (node k kc bl tl' tr)
... | 1+ tl' with bl
... | ⋈ = rotr k kc tl' tr
... | ▸ = 1+ (node k kc ⋈ tl' tr)
... | ⋉ = 0+ (node k kc ▸ tl' tr)
insert v vc f (node k kc bl tl tr) _
| tri ≈ _ refl _ = 0+ (node k (f vc kc) bl tl tr)
insert v vc f (node k kc bl tl tr) (_, u)
| tri > _ _ c with insert v vc f tr (c, u)
... | 0+ tr' = 0+ (node k kc bl tl tr')
... | 1+ tr' with bl
... | ⋈ = 0+ (node k kc ▸ tl tr')
... | ▸ = 1+ (node k kc ⋉ tl tr')
... | ⋉ = rotl k kc tl tr'

```

```

lookup : (k : Key)
→ ∀ {l u s v} {V : Key → Set v}
→ Tree V l u s
→ Maybe (V k)
lookup k (leaf l < u) = nothing
lookup k (node v vc _ tl tr) with compare k v
... | tri < _ _ _ = lookup k tl
... | tri ≈ _ refl _ = just vc
... | tri > _ _ _ = lookup k tr

```

```

record Uncons {v} (V : Key → Set v) (lb : ℤ) (ub : ℤ) (h : ℕ) : Set (k ⊔ v ⊔ r) where
  constructor uncons
  field
    head : Key
    val : V head
    l < u : lb ℤ < [ head ]
    tail : Altered V [ head ] ub h

```

```

uncons' : ∀ {lb ub h lh rh v} {V : Key → Set v}
→ (k : Key)

```

$\rightarrow V k$
 $\rightarrow \langle lh \sqcup rh \rangle \equiv h$
 $\rightarrow \text{Tree } V lb [k] lh$
 $\rightarrow \text{Tree } V [k] ub rh$
 $\rightarrow \exists [lb'] (V lb' \times lb \sqsubseteq [lb'] \times \text{Altered } V [lb'] ub h)$
 $\text{uncons}' k v \dashv (\text{leaf } l < u) tr = k, v, l < u, 0+ tr$
 $\text{uncons}' k v \dashv (\text{node } k_1 v_1 bl tl_1 tr_1) tr \text{ with uncons}' k_1 v_1 bl tl_1 tr_1$
 $\dots | k', v', l < u', 0+ tl' = k', v', l < u', 1+ (\text{node } k v \dashv tl' tr)$
 $\dots | k', v', l < u', 1+ tl' = k', v', l < u', 1+ (\text{node } k v \dashv tl' tr)$
 $\text{uncons}' k v \succ (\text{leaf } l < u) tr = k, v, l < u, 0+ tr$
 $\text{uncons}' k v \succ (\text{node } k_1 v_1 bl tl_1 tr_1) tr \text{ with uncons}' k_1 v_1 bl tl_1 tr_1$
 $\dots | k', v', l < u', 0+ tl' = k', v', l < u', \text{rot}^l k v tl' tr$
 $\dots | k', v', l < u', 1+ tl' = k', v', l < u', 1+ (\text{node } k v \succ tl' tr)$
 $\text{uncons}' k v \prec (\text{node } k_1 v_1 bl tl_1 tr_1) tr \text{ with uncons}' k_1 v_1 bl tl_1 tr_1$
 $\dots | k', v', l < u', 0+ tl' = k', v', l < u', 0+ (\text{node } k v \dashv tl' tr)$
 $\dots | k', v', l < u', 1+ tl' = k', v', l < u', 1+ (\text{node } k v \prec tl' tr)$

$\text{snoc} : \forall \{lb ub ub' h v\} \{V : \text{Key} \rightarrow \text{Set } v\}$
 $\rightarrow ub \sqsubseteq ub'$
 $\rightarrow \text{Tree } V lb ub h$
 $\rightarrow \text{Tree } V lb ub' h$
 $\text{snoc } \{lb\} ub < ub' (\text{leaf } l < u) = \text{leaf } (\sqsubseteq \text{-trans } \{lb\} l < u ub < ub')$
 $\text{snoc } ub < ub' (\text{node } k v bl tl tr) = \text{node } k v bl tl (\text{snoc } ub < ub' tr)$

$\text{delete} : \forall \{lb ub h v\} \{V : \text{Key} \rightarrow \text{Set } v\}$
 $\rightarrow (k : \text{Key})$
 $\rightarrow \text{Tree } V lb ub (\text{suc } h)$
 $\rightarrow \text{Altered } V lb ub h$
 $\text{delete } k (\text{node } k_1 v bl tl tr) \text{ with compare } k k_1$
 $\text{delete } k (\text{node } \{lh = \text{zero}\} k_1 v bl tl tr) | \text{tri} < a \neg b \neg c = 1+ (\text{node } k_1 v bl tl tr)$
 $\text{delete } k (\text{node } \{lh = \text{suc } lh\} k_1 v bl tl tr) | \text{tri} < a \neg b \neg c \text{ with delete } k tl$
 $\text{delete } k (\text{node } \{_\} \{\text{suc } lh\} k_1 v \prec tl tr) | \text{tri} < a \neg b \neg c | 0+ tl' = 0+ (\text{node } k_1 v \dashv tl' tr)$
 $\text{delete } k (\text{node } \{_\} \{\text{suc } lh\} k_1 v \dashv tl tr) | \text{tri} < a \neg b \neg c | 0+ tl' = 1+ (\text{node } k_1 v \succ tl' tr)$
 $\text{delete } k (\text{node } \{_\} \{\text{suc } lh\} k_1 v \succ tl tr) | \text{tri} < a \neg b \neg c | 0+ tl' = \text{rot}^l k_1 v tl' tr$
 $\text{delete } k (\text{node } \{_\} \{\text{suc } lh\} k_1 v bl tl tr) | \text{tri} < a \neg b \neg c | 1+ tl' = 1+ (\text{node } k_1 v bl tl' tr)$
 $\text{delete } k_1 (\text{node } \{rh = \text{zero}\} k_1 v \prec tl (\text{leaf } l < u)) | \text{tri} \approx \neg a \text{ refl } \neg c = 0+ (\text{snoc } l < u tl)$
 $\text{delete } \{lb\} k_1 (\text{node } \{rh = \text{zero}\} k_1 v \dashv (\text{leaf } l < u) (\text{leaf } l < u_1)) | \text{tri} \approx \neg a \text{ refl } \neg c = 0+ (\text{leaf } (\sqsubseteq \text{-trans } \{lb\} l < u_1))$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \prec tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c \text{ with uncons}' k v_1 bl tr tr_1$
 $\text{delete } k_1 (\text{node } \{_\} \{_\} \{\text{suc } rh\} k_1 v \prec tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 0+ tr' = 1+$
 $\text{delete } k_1 (\text{node } \{_\} \{_\} \{\text{suc } rh\} k_1 v \prec tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 1+ tr' = 1+$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \dashv tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c \text{ with uncons}' k v_1 bl tr tr_1$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \dashv tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 0+ tr' = 1+$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \dashv tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 1+ tr' = 1+$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \succ tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c \text{ with uncons}' k v_1 bl tr tr_1$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \succ tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 0+ tr' = 0-$
 $\text{delete } k_1 (\text{node } \{rh = \text{suc } rh\} k_1 v \succ tl (\text{node } k v_1 bl tr tr_1)) | \text{tri} \approx \neg a \text{ refl } \neg c | k', v', l < u, 1+ tr' = 1-$

```

delete k (node {rh = zero} k1 v bl tl tr) | tri> ¬a ¬b c = 1+ (node k1 v bl tl tr)
delete k (node {rh = suc rh} k1 v bl tl tr) | tri> ¬a ¬b c with delete k tr
delete k (node {lh = _} {suc rh} k1 v < tl tr) | tri> ¬a ¬b c | 0+ tr' = rotr k1 v tl tr'
delete k (node {lh = _} {suc rh} k1 v ÷ tl tr) | tri> ¬a ¬b c | 0+ tr' = 1+ (node k1 v < tl tr')
delete k (node {lh = _} {suc rh} k1 v > tl tr) | tri> ¬a ¬b c | 0+ tr' = 0+ (node k1 v ÷ tl tr')
delete k (node {lh = _} {suc rh} k1 v bl tl tr) | tri> ¬a ¬b c | 1+ tr' = 1+ (node k1 v bl tl tr')

```

module DependantMap where

```

data Map {v} (V : Key → Set v) : Set (k ⊔ v ⊔ r) where
  tree : ∀ {h} → Bounded.Tree V ⊥ ⊤ h → Map V

```

```

insertWith : ∀ {v} {V : Key → Set v} (k : Key)
  → V k
  → (V k → V k → V k)
  → Map V
  → Map V

```

```

insertWith k v f (tree tr) =
  tree (proj2 (Bounded.insert k v f tr (lift tt , lift tt)))

```

```

insert : ∀ {v} {V : Key → Set v} (k : Key) → V k → Map V → Map V
insert k v = insertWith k v const

```

```

lookup : (k : Key) → ∀ {v} {V : Key → Set v} → Map V → Maybe (V k)
lookup k (tree tr) = Bounded.lookup k tr

```

module Map where

```

data Map {v} (V : Set v) : Set (k ⊔ v ⊔ r) where
  tree : ∀ {h} → Bounded.Tree (const V) ⊥ ⊤ h → Map V

```

```

insertWith : ∀ {v} {V : Set v} (k : Key) → V → (V → V → V) → Map V → Map V
insertWith k v f (tree tr) =
  tree (proj2 (Bounded.insert k v f tr (lift tt , lift tt)))

```

```

insert : ∀ {v} {V : Set v} (k : Key) → V → Map V → Map V
insert k v = insertWith k v const

```

```

lookup : (k : Key) → ∀ {v} {V : Set v} → Map V → Maybe V
lookup k (tree tr) = Bounded.lookup k tr

```

module Sets where

```

data ⟨Set⟩ : Set (k ⊔ r) where
  tree : ∀ {h} → Bounded.Tree (const 1) ⊥ ⊤ h → ⟨Set⟩

```

```

insert : Key → ⟨Set⟩ → ⟨Set⟩
insert k (tree tr) =
  tree (proj2 (Bounded.insert k tt const tr (lift tt , lift tt)))

```

```
member : Key → ⟨Set⟩ → Bool  
member k (tree tr) = is-just (Bounded.lookup k tr)
```