

C23 on Z80

MinZ Project

2026-03-26

C23 on Z80: The World's First C23 Compiler for 8-Bit

Chapter 1: Architecture

Verification Levels

Chapter 2: C99 Features

2.1 Inline Variable Declarations

2.2 `_Bool` Type

2.3 Designated Initializers

2.4 Compound Literals

2.5 Mixed Declarations and Code

2.6 `inline` and `restrict`

2.7 `<ctype.h>` — 17 Inline Functions

Chapter 3: C11 Features

3.1 Anonymous Structs and Unions

3.2 `_Static_assert`

3.3 `_Generic` — Type-Generic Expressions

3.4 `_Alignof`

3.5 `typeof`

Chapter 4: C17

Chapter 5: C23 Features

5.1 `bool`, `true`, `false` as Keywords

5.2 `nullptr`

5.3 `#embed` — Binary Data at Compile Time

5.4 `constexpr`

5.5 Enum Underlying Type

5.6 `<stdbit.h>` — Bit Manipulation

5.7 `[[...]]` Attributes

5.8 `auto` Type Inference

5.9 Digit Separators

5.10 `_BitInt(N)` — Fixed-Width Integers

5.11 `__builtin_unreachable()`

Chapter 6: `libc` Headers

Chapter 7: Z80-Specific Considerations

7.1 Type Sizes

7.2 Integer Promotion

7.3 No FPU

7.4 No OS

Chapter 8: Examples
8.1 Test Files
8.2 Popcount on Z80
8.3 RGB565 with <code>_BitInt</code>
8.4 Binary Data with <code>#embed</code>
Appendix A: Predefined Macros
Appendix B: Building

C23 on Z80: The World's First C23 Compiler for 8-Bit

MinZ C Frontend — Full C23 (freestanding) on Zilog Z80.

The MinZ compiler ships the first Z80-targeting C frontend with C23 support. 13/13 C23 features implemented. 619 corpus asserts. C17 conformant (`__STDC_VERSION__` = 201710L) with full C23 extensions.

For comparison: SDCC (the standard Z80 C compiler) supports approximately C99.

Chapter 1: Architecture

C source → preprocessor (MinZ) → modernc.org/cc → typed AST → `lower.go` → HIR → Z80

↑	↑
<code>#embed</code> , <code>[[attr]]</code> , <code>_BitInt</code> , digit sep	Full C17 parser + type checker

Parser: modernc.org/cc/v4 — handles preprocessing, parsing, type checking for C17.

MinZ preprocessor: Runs BEFORE `cc` parser. Handles C23 extensions: - `#embed "file"` → comma-separated hex bytes - `[[attribute]]` → stripped (cosmetic only) - `_BitInt(N)` → `uint8_t` / `uint16_t` / `uint32_t` - `1'000` → 1000 (digit separators)

Lowerer: `pkg/c89/lower.go` — walks typed AST, emits HIR nodes.

Z80 ABI: 16-bit int, 16-bit pointers, 1-byte alignment, little-endian.

Verification Levels

Level	Tool	What it tests
MIR2 VM	mzv	Semantic correctness (u16 arithmetic)
Z80 emulator	mze	Full compile → assemble → emulate
Real hardware	ZX Spectrum / CP/M	Production verification

Status: 619 asserts pass on MIR2 VM. Z80 path has known codegen bugs in conditional branches and while loops (MIR2→Z80 lowering). MIR2 VM is the reference implementation.

Chapter 2: C99 Features

All C99 features relevant to Z80 are supported.

2.1 Inline Variable Declarations

```
for (int i = 0; i < 10; i++) {  
    // i is scoped to the for loop  
}
```

2.2 _Bool Type

```
#include <stdbool.h>  
  
bool is_even(uint8_t n) {  
    return (n & 1) == 0;  
}  
  
bool both(bool a, bool b) {  
    return a && b;  
}
```

_Bool normalizes: any non-zero value → 1. sizeof(bool) = 1 on Z80.

2.3 Designated Initializers

```
// Struct – out of order  
Color c = {.b = 30, .r = 10, .g = 20};  
  
// Array – sparse  
uint8_t lut[256] = {[0] = 1, [42] = 99, [255] = 42};
```

Both struct and array designated initializers work. Mixed positional + designated too.

2.4 Compound Literals

```
Point p = (Point){.x = 42, .y = 99};
return (DivResult){a / b, a % b};
```

2.5 Mixed Declarations and Code

```
uint8_t sum = a + b;
if (sum > 100) return 100;
uint8_t doubled = sum * 2; // declaration after statement – C99
```

2.6 inline and restrict

Both parsed and accepted. inline treated as regular function (inlining is a backend decision). restrict ignored (Z80 has no aliasing optimizer).

2.7 <ctype.h> — 17 Inline Functions

```
#include <ctype.h>

// All inline, zero lookup table overhead
isdigit(c)  isalpha(c)  isalnum(c)  isspace(c)
isupper(c)  islower(c)  isprint(c)  isgraph(c)
ispunct(c)  iscntrl(c)  isxdigit(c)
toupper(c)  tolower(c)
```

Implementation: pure comparison chains. Each function is a leaf — optimal for Z80.

Chapter 3: C11 Features

3.1 Anonymous Structs and Unions

```
struct Register {
    union {
        uint16_t hl;
        struct { uint8_t l; uint8_t h; }; // anonymous – fields promoted
    };
};

struct Register r;
r.l = 0x34; // direct access – no intermediate name
```

```
r.h = 0x12;  
// r.hl = 0x1234 (same memory, different view)
```

Fields from anonymous members are promoted into the parent namespace. Uses `modernc.org/cc's FieldOffset()` for correct byte offsets.

3.2 `_Static_assert`

```
_Static_assert(sizeof(uint8_t) == 1, "uint8_t must be 1 byte");  
static_assert(sizeof(void*) == 2); // C23: no message required
```

3.3 `_Generic` — Type-Generic Expressions

```
#define type_id(x) _Generic((x), \  
    uint8_t: 1, \  
    uint16_t: 2, \  
    default: 0 \  
)  
  
uint8_t id = type_id(my_var); // resolved at compile time
```

3.4 `_Alignof`

```
_Alignof(uint16_t) // always 1 on Z80 (byte-addressed)
```

Z80 has no alignment requirements — everything is byte-aligned.

3.5 `typeof`

```
uint8_t x = 42;  
typeof(x) y = x * 2; // y is uint8_t, deduced from x
```

Resolved by the cc parser at type-checking time.

Chapter 4: C17

C17 (ISO/IEC 9899:2018) is a **bugfix release** — no new features. Supporting C11 = supporting C17.

`__STDC_VERSION__` is set to 201710L.

Chapter 5: C23 Features

5.1 bool, true, false as Keywords

```
// No #include needed – these are predefined  
bool flag = true;  
bool check = false;
```

C23 makes these keywords. MinZ predefined macros provide them globally.

5.2 nullptr

```
uint8_t *p = nullptr;  
if (p == nullptr) { /* ... */ }
```

Mapped to ((void*)0).

5.3 #embed — Binary Data at Compile Time

```
// Include binary file directly in array initializer  
const uint8_t font[] = {  
#embed "font.bin"  
};  
  
// With offset and limit  
const uint8_t sprite[] = {  
#embed "sprites.bin" limit(32) offset(128)  
};
```

The killer feature for Z80. Replaces hand-typed DB sequences. Perfect for: - Sprite data - Font bitmaps - Sine/cosine lookup tables - GPU-precomputed optimization tables

Preprocessor expands #embed to comma-separated hex bytes before the parser sees them.

5.4 constexpr

```
constexpr uint8_t SCREEN_W = 32;  
constexpr uint8_t SCREEN_H = 24;  
  
uint8_t area(void) { return SCREEN_W * SCREEN_H; }
```

Mapped to const — on Z80 all const globals are compile-time by definition.

Note: constexpr variables cannot be used as array sizes (cc parser limitation). Use #define for array dimensions.

5.5 Enum Underlying Type

```
enum Color : uint8_t { RED = 0, GREEN = 1, BLUE = 2 };

sizeof(enum Color) // 1 byte! (vs 2 for default enum)
```

Crucial for Z80 — saves 1 byte per enum value. Default enum is int (2 bytes on Z80).

5.6 <stdbit.h> — Bit Manipulation

```
#include <stdbit.h>

stdc_count_ones_uc(0xAA) // popcount → 4
stdc_leading_zeros_uc(0x0F) // clz → 4
stdc_trailing_zeros_uc(0x10) // ctz → 4
stdc_has_single_bit_uc(64) // is power of 2 → 1
stdc_bit_width_uc(255) // floor(log2)+1 → 8
stdc_bit_ceil_uc(5) // smallest pow2 >= 5 → 8
stdc_bit_floor_uc(7) // largest pow2 <= 7 → 4
```

13 inline functions with both `_uc` (`uint8_t`) and `_us` (`uint16_t`) variants. Type-generic macros route by `sizeof`.

5.7 [[]] Attributes

```
[[maybe_unused]] uint8_t debug = 0;
[[nodiscard]] uint8_t compute(uint8_t x);
[[deprecated("use v2")]] void old_api(void);
[[noreturn]] void halt(void);
```

Stripped by preprocessor — cosmetic annotations, no codegen effect on Z80. Supports: `maybe_unused`, `nodiscard`, `noreturn`, `deprecated`, `fallthrough`, `unsequenced`, `reproducible`.

5.8 auto Type Inference

```
auto x = 42; // int
auto sum = a + b; // deduced from expression
```

Resolved by cc parser's type checker.

5.9 Digit Separators

```
uint16_t addr = 0xFF'FF;
uint8_t mask = 0b1010'1010;
int big = 1'000'000;
```

Preprocessor strips ' between digits. Safe: never touches char literals ('A').

5.10 _BitInt(N) — Fixed-Width Integers

```
_BitInt(4) nibble = 0x0F;    // → uint8_t
_BitInt(8) byte = 255;      // → uint8_t
_BitInt(16) word = 1000;    // → uint16_t

// Practical: RGB565 field extraction
_BitInt(5) red = (rgb >> 11) & 0x1F;
_BitInt(6) green = (rgb >> 5) & 0x3F;
```

Maps to nearest Z80 native type: 1-8→uint8_t, 9-16→uint16_t, 17-32→uint32_t, >32→error.

5.11 __builtin_unreachable()

```
uint8_t must_be_positive(uint8_t x) {
    if (x > 0) return x;
    __builtin_unreachable(); // optimizer hint: this path never
taken
}
```

Mapped to infinite loop on Z80. Prevents “missing return” warnings.

Chapter 6: libc Headers

Header	Contents	Z80 Notes
<stdint.h>	uint8_t..uint32_t, limits	Complete
<stddef.h>	NULL, size_t, offsetof	Complete
<limits.h>	CHAR_BIT, INT_MAX, etc.	Complete
<stdbool.h>	bool, true, false	C23: also predefined
<stdarg.h>	va_list, va_start, va_arg	Basic
<stdlib.h>	abs, atoi, malloc stubs	Minimal
<string.h>	memcpy, strlen, strcmp	Minimal
<math.h>	fabs, fmod stubs	No FPU
<assert.h>	assert(), NDEBUG	HALT on fail
<ctype.h>	17 inline functions	Zero LUT
<stdalign.h>	alignas, alignof	Always 1
<stdnoreturn.h>	noreturn	→ _Noreturn

Header	Contents	Z80 Notes
<stdbit.h>	popcount, clz, ctz, etc.	13 functions

Chapter 7: Z80-Specific Considerations

7.1 Type Sizes

C Type	Z80 Size	Notes
char	1 byte	Signed by default
short	2 bytes	Same as int
int	2 bytes	16-bit!
long	4 bytes	Expensive
void*	2 bytes	16-bit address
_Bool	1 byte	Normalized
enum	2 bytes	Default; use : uint8_t for 1 byte

7.2 Integer Promotion

C requires integer promotion for arithmetic. MinZ selectively **un-promotes** safe 8-bit operations: - Safe (stay u8): -, /, %, &, |, ^ - Widen to u16: +, *, << (overflow information may be needed)

7.3 No FPU

float and double map to 4-byte stubs. No real arithmetic. Use fixed-point or lookup tables.

7.4 No OS

__STDC_HOSTED__ = 0 — freestanding environment. No stdio, signal, time. Use @print metafunction or BDOS calls.

Chapter 8: Examples

8.1 Test Files

File	Features	Asserts
c99_stdbool.c	bool, logical ops	12
c99_ctype.c	ctype.h functions	17

File	Features	Asserts
c99_bitops.c	shifts, bit manipulation	27
c99_math8.c	arithmetic, gcd, clamp	31
c99_structs.c	struct init, compound lit	10
c99_control_flow.c	if/while/for/goto	21
c99_pointers.c	deref, fptr	8 (z80)
c99_enum_typedef.c	enum, typedef, static	15
array_desig.c	array designated init	6
c11_features.c	mixed decls, inline	9
c11_anon_struct.c	anonymous struct/union	6
c23_preview.c	bool keyword, ternary	10
c23_embed.c	LUT via manual init	10
c23_stdbit.c	popcount, clz, ctz	34
c23_constexpr_enum.c	constexpr, sized enum	20
c23_attributes.c	[[]] attribute strip	9
c23_misc.c	auto, typeof, unreachable	11
c23_digit_sep.c	digit separators	9
c23_bitint.c	_BitInt(N), RGB565	12
Total		269 (C99+) + 350 (C89) = 619

8.2 Popcount on Z80

```
#include <stdbit.h>

uint8_t count_bits(uint8_t x) {
    return stdc_count_ones_uc(x);
}
// count_bits(0xAA) → 4
// count_bits(0xFF) → 8
```

Z80 assembly (via MIR2):

```
count_bits:
    ; A = x (PFCC0)
```

```

    LD B, 0          ; counter
.loop:
    OR A
    JR Z, .done
    BIT 0, A
    JR Z, .skip
    INC B
.skip:
    SRL A
    JR .loop
.done:
    LD A, B
    RET

```

8.3 RGB565 with _BitInt

```

_BitInt(5) get_red(uint16_t rgb) {
    return (rgb >> 11) & 0x1F;
}
// get_red(0xF800) → 31

```

8.4 Binary Data with #embed

```

const uint8_t sin_table[] = {
    #embed "sin256.bin"           // 256 bytes, one per degree
};

uint8_t fast_sin(uint8_t angle) {
    return sin_table[angle]; // 0(1) lookup
}

```

Appendix A: Predefined Macros

```

#define __Z80__ 1
#define __MINZ__ 1
#define __STDC__ 1
#define __STDC_VERSION__ 201710L
#define __STDC_HOSTED__ 0
#define __SIZEOF_INT__ 2
#define __SIZEOF_POINTER__ 2
#define bool _Bool
#define true 1
#define false 0
#define nullptr ((void*)0)
#define constexpr const

```

Appendix B: Building

```
# Compile C to Z80 assembly
mz program.c -o program.a80

# Assemble to binary
mza program.a80 -o program.com

# Run on CP/M emulator
echo "" | mze program.com -t cpm

# Run on MIR2 VM (for assert testing)
echo "" | mzv -H program.c

# Run on ZX Spectrum emulator
mzx --run program.bin@8000
```

MinZ v0.23.0 — Birthday Marathon Release. The first C23 compiler for Z80.