

OKI2018 RefSeq XP_081642556.1: first three exons only; reads on into the third intron (110 codons, 98 of them as in the gold standard). Gold standard: two splice sites outside the intron classes, as in both supporting transcripts (possible assembly errors).

OSKA2016 ANISEED S10.g09825.01.t: starts in the fourth exon and continues past the stop codon into seven exons downstream (604 codons). Gold standard: two splice sites outside the intron classes, as in the supporting transcript.

OdB3 GenBank CBY23135.1: same first three exons; other first site of the fourth exon, and no last exon (178 codons). Gold standard: exon chain set by the curator: the GenBank exons 1 to 3 and the last intron of the ESTs.

proteins human Q8IV42; C. intestinalis XP_002120985.2.

exon: coding (thick), UTR (thin) — public model — gold-standard model — coding sequence in another frame

start codon of the gold-standard model (x axis: nucleotides from it, gene orientation) — ◂ n number of exons beyond the drawn region

a b public models of the same row, as named in the paragraph

intron splice sites (drawn length unchanged): GT-AG (colour of the model) — GA-AG — GG-AG — other site

Pfam domain of the first reference — residues not aligned to the first reference

92 % similar residues to the OdB3 protein (BLOSUM62 > 0; global alignment, aligned part) human: UniProt; C. intestinalis: RefSeq