



SKILLPILLS

Skill Pill: Julia

Lecture 2: Data Processing and Plotting


Juan Polo { material
taken/based on
Ankur Dhar &
James Schloss }

juan.polo@oist.jp

ankurd@oist.jp

james.schloss@oist.jp

February 24th, 2021



OIST

1 Arrays

2 Data Handling

3 Plotting

Arrays in Julia are defined very similarly to arrays in Matlab, using square brackets to denote them. By default arrays are row vectors, but can be transposed to column vectors.

Arrays in Julia are defined very similarly to arrays in Matlab, using square brackets to denote them. By default arrays are row vectors, but can be transposed to column vectors.

In addition, sequences of numbers can be generated using the `:` operator (**start:step:end**). To see all these values expanded out you will need to print them manually or use the `collect` function.

Arrays in Julia are defined very similarly to arrays in Matlab, using square brackets to denote them. By default arrays are row vectors, but can be transposed to column vectors.

In addition, sequences of numbers can be generated using the `:` operator (**start:step:end**). To see all these values expanded out you will need to print them manually or use the `collect` function.

```
x = [1 2 3 4]           # 1x4 Array{Int64,2}
y = collect(1:4)        # 4-element Array{Int64,1}
z = [1, 2, 3, 4]        # 4-element Array{Int64,1}
m = [1 2; 3 4]          # 2x2 Array{Int64,2}
w=x'                    # 4x1 {Int64,Array{Int64,2}}
array = Int64[]         # 0-element Array{Int64,1}
```

Arrays in Julia are defined very similarly to arrays in Matlab, using square brackets to denote them. By default arrays are row vectors, but can be transposed to column vectors.

In addition, sequences of numbers can be generated using the `:` operator (**start:step:end**). To see all these values expanded out you will need to print them manually or use the `collect` function.

```
x = [1 2 3 4]           # 1x4 Array{Int64,2}
y = collect(1:4)         # 4-element Array{Int64,1}
z = [1, 2, 3, 4]         # 4-element Array{Int64,1}
m = [1 2; 3 4]           # 2x2 Array{Int64,2}
w=x'                     # 4x1 {Int64,Array{Int64,2}}
array = Int64[]          # 0-element Array{Int64,1}
```

Please try to create a vector from 0 to 0.9 in steps of 0.1

`zeros(S)` Makes an array of size S filled with zeros

`ones(S)` Makes an array of size S filled with ones

`repeat(A,c,r)` Repeats array A column-wise c times and row-wise r times

`rand(S)` Generates array of size S with random numbers between 0 and 1

`Type[]` Creates empty array of type `Type`

Arrays can be indexed by using square brackets after the array. For multidimensional arrays, the first dimension is the row, followed by column and so on. Output of indexing arrays is by default a column. This is crucial when it comes to multiplying arrays by each other.

Arrays can be indexed by using square brackets after the array. For multidimensional arrays, the first dimension is the row, followed by column and so on. Output of indexing arrays is by default a column. This is crucial when it comes to multiplying arrays by each other.

```
data = rand(50,50)
data[1,:]
data[:,1]
inner = x*y
outer = y*x
square = x .* x
```

To execute scalar operations on an array, **you can use a `.` to the operator**. This is also applicable to functions as well.

Arrays can be indexed by using square brackets after the array. For multidimensional arrays, the first dimension is the row, followed by column and so on. Output of indexing arrays is by default a column. This is crucial when it comes to multiplying arrays by each other.

```
data = rand(50,50)
data[1,:]
data[:,1]
inner = x*y
outer = y*x
square = x .* x
```

To execute scalar operations on an array, **you can use a `.` to the operator**. This is also applicable to functions as well.

Multiply all elements of "x" by a constant "2" (careful with spaces)

Arrays can be indexed by using square brackets after the array. For multidimensional arrays, the first dimension is the row, followed by column and so on. Output of indexing arrays is by default a column. This is crucial when it comes to multiplying arrays by each other.

```
data = rand(50,50)
data[1,:]
data[:,1]
inner = x*y
outer = y*x
square = x .* x
```

To execute scalar operations on an array, **you can use a `.` to the operator**. This is also applicable to functions as well.

Multiply all elements of "x" by a constant "2" (careful with spaces)

2 .* x

It is sometimes useful to perform element-by-element binary operations on arrays of different sizes. Dotted operators such as `.+` and `.*` are equivalent to broadcast calls

```
data = collect(0:.1:1)
round.(data)
f(x) = x+2
f.(data)
```

It is sometimes useful to perform element-by-element binary operations on arrays of different sizes. Dotted operators such as `.+` and `.*` are equivalent to broadcast calls

```
data = collect(0:.1:1)
round.(data)
f(x) = x+2
f.(data)
```

Create a vector of `dim = 2` (e.g. elements `(1, 2)`) and add it to `m` of `dim = 2x2`

It is sometimes useful to perform element-by-element binary operations on arrays of different sizes. Dotted operators such as `.+` and `.*` are equivalent to broadcast calls

```
data = collect(0:.1:1)
round.(data)
f(x) = x+2
f.(data)
```

Create a vector of `dim = 2` (e.g. elements (1, 2)) and add it to `m` of `dim = 2x2`

```
v = [1, 2]
m = [1 2; 3 4]
v .+ m
```

It is sometimes useful to perform element-by-element binary operations on arrays of different sizes. Dotted operators such as `.+` and `.*` are equivalent to broadcast calls

```
data = collect(0:.1:1)
round.(data)
f(x) = x+2
f.(data)
```

Create a vector of `dim = 2` (e.g. elements `(1, 2)`) and add it to `m` of `dim = 2x2`

```
v = [1, 2]
m = [1 2; 3 4]
v .+ m
```

Extra cool things

```
data[data .< 0.5]
```

Data Handling

To begin working with files, you must know where your working directory is. When launching Julia from an application menu (Windows/MacOS), the default directory is predefined. For Linux it will be the home directory.

```
pwd()  
# cd("C:\\Users\\M\\Documents\\JuliaStuff")  
readdir()
```

You can use `pwd()` to print your working directory, and `cd()` to change it to whichever new directory you would like. Once you are in the directory you want, you can list the files within using `readdir()`.

The simplest data files are often delimited text files or CSV files, which can be manipulated like any other variable in Julia. To load any general delimited file, load the `DelimitedFiles` package. Reading in these files will automatically generate 1D or 2D arrays depending on the data being read in.

```
julia> using DelimitedFiles
julia> data = rand(50,50)
julia> writedlm("Random.txt",data)
julia> randData = readdlm("Random.txt")
```

Similarly, any 1D or 2D can be written to a file, with the actual delimiter being based on the file extension used (txt for space and csv for comma).

Typical CSV files are a bit more complex than standard delimited files, with headers or labels. For this use case the CSV package is recommended. When reading in a file, the first row will be taken as the header row, but this can be explicitly defined.

```
using CSV, DataFrames
data =
    DataFrame(CSV.File("simplemaps-worldcities-basic.csv"))
names(data)
populations = data[:, :pop]
populations = data.pop
data[5677, :]
```

Small trick, you can write "data." and press "TAB" twice to see the available columns

```
data[data.city .== "Barcelona",:]
findall(x->x=="Barcelona", data.city)
```

Exercise 1

Creates a file `squares.txt` consisting of the first 5 square numbers

Exercise 2

Write a script which creates a new file called `large_cities.txt`. The file should contain one line for each of the cities which have a population larger than 10,000,000., formatted as follows:

Buenos Aires, Argentina: population 11862073

Sao Paulo, Brazil: population 14433147.5

...

Fast way to look at data using Dataframes `data[data.pop .> 107,:]`


Plots

To start with, let's add and load the general Plots package

```
# inside pkg>
add Plots
# inside REPL
using Plots
# plot(Plots.fakedata(50))
```

This will let us call the general Plot commands, in this case plot plots 1D data as a line plot.

More information can be found at <https://docs.juliaplots.org/latest/>



`scatter(X,Y)` Scatter plot data with XY coordinates

`bar(x,y)` Bar plot following similar rules to plot

`histogram(x,bins=n)` Plots histogram of 1D data in n bins.

`plot(θ ,r,proj=:polar)` Polar plot of data following r and θ

`heatmap(x,y,z)` Plots heatmap following XY axes with intensity array z

`fakedata(L,S)` Generates random S numbers of series data of length L


`savefig(filename)` Saves a generated plot as an image file

There are a couple of additional options for plotting 3D data:


`surface(x,y,z)` Draws surface in 3D space

`contour(x,y,z)` Draws contours on 2D plane

The plotting commands `plot`, `scatter`, `bar`, and `heatmap` also can accept 3D data.




```
using Plots
x = y = collect(-1:0.01:1)
#surface(x,y,(x,y)->x^2+y^2)
#heatmap(x,y,(x,y)->x^2+y^2)
f(x,y) = x^2 + y^2
surface(x,y,f.(x,y'))
contour(x,y,f.(x,y'))
```




For vector data the current option is
quiver:

```
help?> quiver  
search: quiver quiver!
```

```
quiver(x,y,quiver=(u,v))  
quiver!(x,y,quiver=(u,v))
```

Make a quiver (vector field)
plot. The i th vector
extends from $(x[i], y[i])$
to $(x[i] + u[i], y[i] + v[i])$.



These commands are agnostic to the plotting backend, meaning they will work with a number of plotting engines in similar fashion. Each backend has pros and cons, but most commonly used are **GR** and **PyPlot**.




Figure: PyPlot
using PyPlot; PyPlot.plot(rand(10))




Figure: PGFPlots





Figure: UnicodePlots
using UnicodePlots; UnicodePlots.lineplot(rand(10))
UnicodePlots.histogram(randn(1000), nbins=15, closed=:left)



Each of these commands can be expressed in-line with the plotting command or beforehand within a call to the plotting backend.

`font(fontname,size)` Defines a Font object with a given size

`size=(X,Y)` Sets size of plot to X by Y pixels

`xlabel=string` Sets X-Y labels to string, also `ylabel`

`title=string` Sets title to string, also `colorbar_title` for heatmap.

`xtickfont=font` Sets the font of x tick marks, also `ytickfont`, `titlefont`, `guidelfont`

`left_margin=length` Sets margin for left side of plot, also `top_margin`, `bottom_margin`, and `right_margin`

`xscale=:log10` Sets x scale to log10, also `yscale`

Exercise 3

Read data.txt given in the Public Folder and plot the results. What do you see?

Exercise 4

Plot a histogram of the longitudes of the world's cities. What is the mean and median longitude?

using Plots, DataFrames, CSV

```
data = DataFrame(CSV.File("simplemaps-worldcities-basic.csv"))
```

```
using Plots, Images, ImageMagick, DataFrames, CSV

data =
    DataFrame(CSV.File("simplemaps-worldcities-basic.csv"))

histogram(data.lng, bins=200)
histogram(data.lat)
```

```
using Plots, Images, ImageMagick, DataFrames, CSV, Shapefile

data =
    DataFrame(CSV.File("simplemaps-worldcities-basic.csv"))

shp =
    Shapefile.shapes(Shapefile.Table("ne_110m_coastline.shp"));

p3 = histogram(data.lng, bins=200, xticks = (-200:25:200));
p2 = plot(shp, xlim=(-200,200), ylim=(-100,100));
p2_size = p2.attr.explicit[:size];

p1 = histogram(data.lat, bins=200, ylim = (-100,100),
    orientation=:horizontal, aspect_ratio=p2_size[1]/p2_size[2]);

plot(p1,p2,p3,p3,
    layout= layout=@layout [[a{0.2w} b{0.8h}]; [c d]])
```

Last Session Problem Sets with James

Also next week Advanced Topics with Valentin!