

# Shiprocket API

Welcome to Shiprocket's API Documentation. We've designed this document to help developers and Shiprocket users fully understand and integrate our API for a seamless and easy deployment. These APIs enable you to utilize most of your Shiprocket account's panel features fully.

We've listed all the APIs, their required parameters, and their example requests and responses on the right for easy understanding. The easiest way to start using the Shiprocket APIs is by clicking the **Run in Postman** button above. The **Postman** is a free tool that helps developers run and debug API requests.

Our APIs are based around **REST** architecture and use the basic **HTTP** request methods. Our APIs accept **JSON** - encoded body requests and return data in the same form.

Read through the following sections for the integration process.

## Getting Started

First, you need to register with ShipRocket and create an account. Click on this [link](#) to complete the sign-up process.

After the sign-up process is complete, follow the steps listed below to create an API user:

1. Log in to your Shiprocket account.
2. From the left-hand menu, go to:  
**Settings → API → Add New API User**
3. Click on "Create API User."
4. In the pop-up form:
  - . Enter a **unique email address** (must be different from the one used for your main Shiprocket login).
  - . Under **Modules to Access**, select the relevant **API modules** you want your user to access.
  - . Under **Buyer's Details Access**, choose either "**Allowed**" or "**Not Allowed**" based on your requirement.
5. Click on "**Create User**."
6. The password for the API user will be sent to your registered email address (not the API user email ID).

Once created, you can proceed to generate an auth token using the Authentication API for further integration.

## Document and API Usage Guidelines

- Our APIs use the basic HTTP request codes: *POST*, *GET*, *PATCH*, & *PUT*.
- You can select the required response and request code language by selecting it from the drop-down menu on the top.
- You can import and test all our full API collection in the Postman app by clicking on the '**Run in Postman**' button.
- **Note:** Any requests made using the valid API credentials will affect the real-time data in your Shiprocket account.
- Authorization: Bearer
- All the APIs are provided with their appropriate example requests and responses for successful and failed calls. The

example definitions are:

- **Successful Call:** The API call was correct.
- **Invalid Data:** The data entered was incorrect.
- **Missing Fields:** Some of the required fields are missing.
- **Wrong Format:** There is a syntax error in the code.
- **Note:** The `order_id` defined by you at the time of order creation is your reference order id. The `order_id` returned in the API response is the *Shiprocket order id*. All our APIs will use this Shiprocket order id to access your created order unless stated otherwise.

## Errors and Response codes

While using Shiprocket's APIs, you may run into some standard response and error codes. The most common ones are listed along with their descriptions as follows:

| RESPONSE CODE                                                                             | DESCRIPTION                                                                                                                         |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>200</code> & <code>202</code> - OK & Accepted                                       | Everything worked as expected, and you'll get a response. Some APIs may respond with an error message if data is invalid.           |
| <code>400</code> - Bad Request                                                            | The request was invalid or cannot be otherwise served.                                                                              |
| <code>401</code> - Unauthorized                                                           | There is some error during validation. You need to check your token or credentials.                                                 |
| <code>404</code> - Not Found                                                              | The URI requested is invalid or the resource requested does not exist.                                                              |
| <code>405</code> - Method Not Allowed                                                     | The API was accessed using the wrong method. Check your HTTP method.                                                                |
| <code>422</code> - Unprocessable Entity                                                   | It means the request contains incorrect syntax or cannot be fulfilled. Try checking your code for errors.                           |
| <code>429</code> - Too Many Requests                                                      | You have exceeded the API call rate limit.                                                                                          |
| <code>500</code> , <code>502</code> , <code>503</code> , <code>504</code> - Server Errors | Some server error has occurred. Some APIs may show this due to syntax or parameter errors. Try contacting support if this persists. |

## Webhooks

You can set up a webhook with Shiprocket to get tracking updates. We will proactively notify your system whenever there is a new tracking event for an order.

### Setup:

- Log in to your Shiprocket account
- Go to Settings > API > Webhooks
- Add the webhook URL
- Enable the toggle

- Add the security token (not mandatory)

When we get a new tracking event, a POST request is made to the callback URL you added to your Shiprocket account.

#### Webhook Specifications:

- Method: POST
- The `Content-Type` header should be set to `application/json`
- Please do not use keywords like shiprocket, kartrocket, sr, or kr in your webhook URL
- Security token should be an `x-api-key`
- The URL should be set to send only code 200 in response.

#### Sample Body:

json

```
{
  "awb": "19041424751540",
  "courier_name": "Delhivery Surface",
  "current_status": "IN TRANSIT",
  "current_status_id": 20,
  "shipment_status": "IN TRANSIT",
  "shipment_status_id": 18,
  "current_timestamp": "23 05 2023 11:43:52",
```

## Sense

Businesses can enhance their internal and customer-facing applications using Sense intelligence through our API products. For more information, please visit <https://www.console.shiprocket.in>

#### Product Offerings:

1. Sense RTO Score API - Predicts return-to-origin (RTO) events
2. SenseAddress API - Provides address standardization and validation

#### Use Cases for RTO Score API:

- Online retail platforms
- Logistics or delivery apps/journeys
- E-commerce customer service tools

#### Use Cases for Sense Address API:

- Operational efficiency
- Delivery success
- Address quality and accuracy

## Applications:

- **BFSI:** Doorstep banking, KYC processes
- **Retail:** Enhancing customer experiences
- **FinTech:** Improving service accuracy
- **E-commerce:** Ensuring delivery accuracy
- **Location Intelligence:** Various industry applications

## API Details:

- **Address Score API:** Evaluates and scores addresses for overall quality and suitability.
- **Address Verification API:** Validates and ensures accuracy by comparing addresses with past entries.
- **RTO Prediction API:** Uses machine learning, historical data, and key parameters to forecast if an order will return to its origin efficiently.

## Support:

- All the required information on integration is in this document. Please read it thoroughly.
- For any integration and API-related support, you can feel free to drop us an email at [integration@shiprocket.com](mailto:integration@shiprocket.com). For any other issues, please email us at: [support@shiprocket.com](mailto:support@shiprocket.com).
- The Shiprocket terms of service are listed here: [Terms Of Service](#)

# Shiprocket MCP Server

A Model Context Protocol (MCP) server that enables AI clients (like Claude or Cursor) to interact with Shiprocket's logistics platform through natural language. Using this AI, clients can create conversational requests into authenticated API calls, covering shipping rates, order creation, tracking, cancellations, pickups, and label generation

## Key Features:

- Get real-time shipping rates for any pincode, city, or state with a simple command.
- Create or update orders instantly with details like dimensions, weight, and address.
- Assign couriers and schedule pickups effortlessly—just tell it what, where, and when.
- Generate shipping labels for your orders in one step.
- Cancel orders or shipments before they're dispatched.
- Track shipments live using AWB, Shiprocket Order ID, or your source order ID.
- Manage your entire order workflow—from creation to delivery—through natural prompts.

## List of Tools available:

| Tool Name                  | Description                                                               |
|----------------------------|---------------------------------------------------------------------------|
| shipping_rate_calculator   | Get shipping rates for a specific package between origin and destination. |
| estimated_date_of_delivery | Estimate the delivery date for a shipment based on locations.             |
| order_create               | Create a new shipment/order in the Shiprocket platform.                   |
| order_list                 | List recent orders created via the account.                               |
| order_track                | Track a specific order using AWB, Shiprocket Order ID, or source ID.      |
| order_ship                 | Assign a courier and generate shipping for a created order.               |
| order_pickup_schedule      | Schedule a pickup for an existing order.                                  |
| generate_shipment_label    | Generate or retrieve the shipping label (PDF).                            |
| order_cancel               | Cancel a created order before it is shipped.                              |
|                            |                                                                           |

## Use cases :

### Use Case 1: Get Shipping Rates for a New Order

**Goal:** You want to know how much it would cost to ship a parcel from Delhi to Bangalore.

**User Command (Natural Language):**

"How much does it cost to send a 1kg package from Delhi to Bangalore with COD?"

**Behind the scenes (Tool Used):**

- Tool: `shipping_rate_calculator`
- Inputs:
  - Pickup Pincode: 110001 (Delhi)
  - Delivery Pincode: 560001 (Bangalore)
  - Weight: 1kg
  - COD: Yes

**AI Response (Simplified Output):**

You have 3 courier options:

- Delhivery Express: ₹85, Delivery in 2 days

- **Bluedart: ₹110, Delivery in 1 day**
- **Xpressbees: ₹90, Delivery in 3 days**

COD available with all options.

This allows the user to choose the best courier based on cost and speed, all without logging into a dashboard.

## Use Case 2: Create and Ship an Order

**Goal:** You've received an order on your website and now want to ship it via Shiprocket.

**User Command:**

"Create a shipment for a 2kg item from Mumbai to Pune. COD ₹999. Customer name is Ramesh, phone is 9876543210."

**Behind the scenes (Tool Used):**

- **Tool:** `order_create`
- **Inputs:**
  - **Pickup Address:** Mumbai (400001)
  - **Delivery Address:** Pune (411001)
  - **Weight:** 2kg
  - **COD Amount:** ₹999
  - **Customer:** Ramesh, 9876543210

**AI Response:**

New Order created successfully with Shiprocket Order ID: SR123456.

**Next Command (User):**

"Ship the order using the fastest courier."

**Behind the scenes:**

- **Tool:** `order_ship`
- **Logic:** Auto-select fastest courier based on `shipping_rate_calculator`
- **Result:** Courier assigned, AWB generated.

**AI Response:**

Shipped via Delhivery. AWB Number: DLV987654321

## Use Case 3: Schedule Pickup and Download Label

**Goal:** You've created an order and want to schedule a pickup and download the label.

**User Command:**

"Schedule a pickup for Order SR123456 for tomorrow."

**Tool Used:** `order_pickup_schedule`

- **Inputs:**
  - **Order ID:** SR123456
  - **Date:** Tomorrow
  - **Pickup Slot:** Default (morning/afternoon)

#### AI Response:

Pickup scheduled for 24 July, 10 AM to 1 PM.

#### Next Command:

"Download the shipping label for Order SR123456."

**Tool Used:** `generate_shipment_label`

#### AI Response:

Here's your label (PDF): **Download Label**

You can now print the label and attach it to the package—done!

## Get Started

### Setup:

#### Prerequisites:

- **Node.js v22.14.0 or higher (but < v23)**
- **Claude Desktop or Cursor app for integrating MCP servers.**

## Installation & Setup

### Clone the Repository

```
bash
```

```
git clone https://github.com/bfirs/shiprocket-mcp.git
cd shiprocket-mcp
```

### 1. Install Dependencies

```
bash
```

```
npm install
npm run build
```

### 2. Configure AI Client Integration

Add your credentials in your client's MCP config file:

---

json

```
{
  "mcpServers": {
    "shiprocket": {
      "command": "npm",
      "args": ["--prefix", "{{PATH_TO_SRC}}", "start", "--silent"],
      "env": {
        "SELLER_EMAIL": "<Your Shiprocket Email>",
        "-----"
      }
    }
  }
}
```

Claude: save as ~/Library/Application Support/Claude/claude\_desktop\_config.json

Cursor: save as ~/.cursor/mcp.json

### 3. Run & Use

Open/restart Claude or Cursor. You'll see "Shiprocket" as an available MCP integration.

## Architecture Overview

- MCP Protocol via STDIO: Communicates with AI clients using standard I/O streams
- Core Components:
  - HTTP Client: Authenticates with Shiprocket using email/password to fetch a bearer token.
  - Tool Mapper: Receives MCP calls → runs validation → dispatches to Shiprocket's REST endpoints.
  - Error Handling: Wraps API calls with structured responses to AI clients.
- Code Layout:
  - src/transport/stdio.ts: MCP-stdio handler
  - src/mcp/tools.ts: Tool definitions and parameter schemas
  - src/mcp/connections.ts: Authentication/session management
  - src/main.ts: Entry point to initialize server

---

## Authentication API

The authentication token is an alphanumeric code, unique to your Shiprocket account, can be used from any system to validate your API calls to access Shiprocket's resources. Shiprocket API uses **JWT** tokens for validation.

Use this API to validate your API user and obtain the authentication token. Copy this token and use it further to validate your API calls. **The validity of this token is 10 days.**

Your API keys carry many privileges, so be sure to keep them secure! Do not share your secret token in publicly accessible areas such as GitHub, client-side code, and so forth.

#### Steps To Use Token:

1. Copy the token received in response.
2. Include '**Authorization: Bearer [yourtokenvalue]**' in the appropriate field of your code.
3. That's all! In case of any error, try checking your parameters.

---

## POST Generate Token

<https://apiv2.shiprocket.in/v1/external/auth/login>

### HEADERS

---

**Content-Type** application/json

**Body** raw

---

```
{
  "email": "",
  "password": ""
}
```

---

## POST Token Logout

<https://apiv2.shiprocket.in/v1/external/auth/logout>

<https://apiv2.shiprocket.in/v1/external/auth/logout>

### HEADERS

---

Content-Type

application/json

Authorization

Bearer xxx

---

## Create Or Update Order

Using these APIs, you can create new orders in your Shiprocket account or update existing orders.

You can also cancel an order, bulk import orders from a CSV file and update inventory for an ordered product.

---

### POST Create Custom Order

<https://apiv2.shiprocket.in/v1/external/orders/create/adhoc>

Use this API to create a quick custom order. Quick orders are the ones where we do not store the product details in the master catalogue.

You have to pass all the required params at the minimum to create a quick custom order. You can add additional parameters as per your preference.

#### Note:

- In case the 'shipping\_is\_billing' field is false, further shipping detail fields are required.

If no channel id is passed, the order will be assigned to the default custom channel. If the channel id is not known, use the 'Get All Channels' API to get the list of all integrated channels in your Shiprocket account.

- order\_id field cannot be equal to an already existing id. Doing so does not change or affect the existing order.
- New orders cannot be created with order id's same as that of cancelled orders. If error 422 shows up despite filling in the correct details, consider changing the order\_id.
- Be sure to input the correct calculated sub\_total amount. The total is not calculated automatically through the API.
- The 'order\_id' returned in the response is the Shiprocket order\_id. Please save this order ID as we will use this in future API calls.

#### Parameters:

| PARAMS                       | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                                             | EXAMPLE           |
|------------------------------|----------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| <code>order_id</code>        | YES      | <i>string</i>  | The order id you want to specify to the order. Max char: 50. (Avoid passing character values as this contradicts some other API calls). | 224477 or 224-477 |
| <code>order_date</code>      | YES      | <i>string</i>  | The date of order creation in yyyy-mm-dd format. Time is additional.                                                                    | 2019-07-24 11:11  |
| <code>pickup_location</code> | YES      | <i>string</i>  | The name of the pickup location added in your Shiprocket account. This cannot be a new location.                                        | Jammu             |
| <code>channel_id</code>      | NO       | <i>integer</i> | Mention this in case you need to                                                                                                        | 27022             |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "order_id": "",
  "order_date": "",
  "pickup_location": "",
  "comment": "",
  "reseller_name": "",
  "company_name": "",
  "billing_customer_name": "",
  "billing_last_name": "",
  "billing_address": "",
  "billing_address_2": "",
  "billing_isd_code": "",
  "billing_city": "",
  "billing_pincode": "",
```

```

"billing_state": "",
"billing_country": "",
"billing_email": "",

"billing_phone": "",
"billing_alternate_phone": "",
"shipping_is_billing": "",
"shipping_customer_name": "",
"shipping_last_name": "",
"shipping_address": "",
"shipping_address_2": "",
"shipping_city": "",
"shipping_pincode": "",
"shipping_country": "",
"shipping_state": "",
"shipping_email": "",
"shipping_phone": "",
"order_items": [
  {
    "name": "",
    "sku": "",
    "units": "",
    "selling_price": "",
    "discount": "",
    "tax": "",
    "hsn": ""
  }
],
"payment_method": "",
"shipping_charges": "",
"giftwrap_charges": "",
"transaction_charges": "",
"total_discount": "",
"sub_total": "",
"length": "",
"breadth": "",
"height": "",
"weight": "",
"ewaybill_no": "",
"customer_gstin": "",
"invoice_number": "",
"order_type": ""
}

```

## POST Create Channel Specific Order

<https://apiv2.shiprocket.in/v1/external/orders/create>

This API can be used to create a custom order, the same as the Custom order API, except that you have to specify and select a custom channel to create the order.

The order created will be added under the specified channel. All the other parameters are the same.

**Note:**

- Channel\_id field is required.
- Order\_id cannot be the same as the already existing order id.
- Inventory Sync must be turned on to use this API. This can be done under the 'Channels' portion on the left-hand panel of your Shiprocket account.
- Inventory details of your Shiprocket account can be accessed using the 'Get Inventory Details' API.

**Parameters:**

| PARAMS                       | REQUIRED | DATA TYPE     | DESCRIPTION                                                                                                                             | EXAMPLE           |
|------------------------------|----------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| <code>order_id</code>        | YES      | <i>string</i> | The order id you want to specify to the order. Max char: 20. (Avoid passing character values as this contradicts some other API calls). | 224477 or 224-477 |
| <code>order_date</code>      | YES      | <i>string</i> | The date of order creation in yyyy-mm-dd format. Time is an additional option.                                                          | 2019-07-24 11:11  |
| <code>pickup_location</code> | NO       | <i>string</i> | The name of the pickup location added in your Shiprocket account. This cannot be a new location. Default Pickup location is             | Jammu             |

**HEADERS****Content-Type**

application/json

**Body** raw

```
{
  "order_id": "3167",
  "order_date": "2020-01-14 13:25",
  "pickup_location": "mrj",
  "channel_id": "443555",
  "comment": "fast and furious".
}
```

```

"billing_customer_name": "rahul",
"billing_last_name": "",
"billing_address": "malviya nagar",
"billing_address_2": "",
"billing_city": "new delhi",
"billing_pincode": "273303",
"billing_state": "delhi",
"billing_country": "india",
"billing_email": "raushanra4@gmail.com",
"billing_phone": "9721562372",
"shipping_is_billing": 1,
"shipping_customer_name": "",
"shipping_last_name": "",
"shipping_address": "",
"shipping_address_2": "",
"shipping_city": "",
"shipping_pincode": "",
"shipping_country": "",
"shipping_state": "",
"shipping_email": "",
"shipping_phone": "",
"order_items": [
  {
    "name": "shoes",
    "sku": "shoes123",
    "units": "2",
    "selling_price": "1500",
    "discount": "100",
    "tax": "50",
    "hsn": ""
  }
],
"payment_method": "COD",
"shipping_charges": "",
"giftwrap_charges": "",
"transaction_charges": "",
"total_discount": "",
"sub_total": "2950",
"length": "10",
"breadth": "10",
"height": "10",
"weight": "1.5"
}

```

## PATCH Change/Update Pickup Location of Created Orders

<https://apiv2.shiprocket.in/v1/external/orders/address/pickup>

Using this API, you can modify the pickup location of an already created order. Multiple order ids can be passed to update their pickup location together.

**Note:**

- Pickup location can only be changed/updated to an already existing pickup location in your account.
- The 'order\_id' to be passed is the Shiprocket order\_id received at the time of order creation.
- Multiple order ids can be passed as an array, separated by commas. eg: ["141414,142424,143434"]

#### Parameters:

| PARAMS                       | REQUIRED | DATA TYPE      | DESCRIPTION                                                             | EXAMPLE  |
|------------------------------|----------|----------------|-------------------------------------------------------------------------|----------|
| <code>order_id</code>        | YES      | <i>integer</i> | The Shiprocket order_id specified to the order.                         | 16167171 |
| <code>pickup_location</code> | YES      | <i>string</i>  | The pickup location you want to change your current pickup location to. | Delhi    |

#### HEADERS

**Content-Type**                      application/json

#### Body raw

```
{
  "order_id": [],
  "pickup_location": ""
}
```

## POST    Update Customer Delivery Address

<https://apiv2.shiprocket.in/v1/external/orders/address/update>

You can update the customer's name and delivery address through this API by passing the Shiprocket order id and the necessary customer details.

#### Parameters:

| PARAMS                              | REQUIRED | DATA TYPE      | DESCRIPTION                                     | EXAMPLE         |
|-------------------------------------|----------|----------------|-------------------------------------------------|-----------------|
| <code>order_id</code>               | YES      | <i>integer</i> | The Shiprocket order_id specified to the order. | 16178831        |
| <code>shipping_customer_name</code> | YES      | <i>string</i>  | The name of the customer.                       | John Doe        |
| <code>shipping_phone</code>         | YES      | <i>integer</i> | Phone number of the customer.                   | 9988998899      |
| <code>shipping_address</code>       | YES      | <i>string</i>  | Primary address of the customer.                | House no 123    |
| <code>shipping_address_2</code>     | NO       | <i>string</i>  | Further address details of the customer.        | Beside CM house |
| <code>shipping_city</code>          | YES      | <i>string</i>  | Shipping city name.                             | Pune            |
| <code>shipping_state</code>         | YES      | <i>string</i>  | Shipping state name.                            | Maharashtra     |
| <code>shipping_country</code>       | YES      | <i>string</i>  | Shipping country name.                          | India           |
|                                     |          |                |                                                 |                 |

## HEADERS

**Content-Type** application/json

## Body raw

```
{
  "order_id": "",
  "shipping_customer_name": "",
  "shipping_phone": "",
  "shipping_address": "",
  "shipping_address_2": "",
  "shipping_city": "",
  "shipping_state": "",
  "shipping_country": "",
  "shipping_pincode": "",
  "shipping_email": "",
  "billing_alternate_phone": ""
}
```

## POST Update Order

<https://apiv2.shiprocket.in/v1/external/orders/update/adhoc>

Use this API to update your orders. You have to pass all the required params at the minimum to create a quick custom order. You can add additional parameters as per your preference.

You can update only the order\_items details before assigning the AWB (before Ready to Ship status). You can only update these key-value pairs i.e., increase/decrease the quantity, update tax/discount, add/remove product items. We've also enabled changing the nature of the order from a non-document to a document. You just need to pass the is\_document key with the value of 1 in the payload.

### HEADERS

**Content-Type** application/json

### Body raw

```
{
  "order_id": "4TestOrderOct28",
  "order_date": "2024-10-28",
  "pickup_location": "23659_7026",
  "channel_id": "",
  "comment": "Reseller: M/s Goku",
  "billing_customer_name": "Naruto",
  "billing_last_name": "Uzumaki",
  "billing_address": "House 221B, Leaf Village",
  "billing_address_2": "Near Hokage House",
  "billing_city": "New Delhi",
  "billing_pincode": "110002",
  "billing_state": "Delhi",
  "billing_country": "India",
  "billing_email": "naruto@uzumaki.com",
  "billing_phone": "9876543210",
  "shipping_is_billing": true,
  "shipping_customer_name": "",
  "shipping_last_name": "",
  "shipping_address": "",
  "shipping_address_2": "",
  "shipping_city": "",
  "shipping_pincode": "",
  "shipping_country": "",
  "shipping_state": "",
  "shipping_email": "",
  "shipping_phone": "",
```

```
"is_document": "0",
"order_items": [
  {
    "name": "Agreement",
    "sku": "chakra123",
    "units": 1,
    "selling_price": "900",
    "discount": "",
    "tax": "",
    "hsn": 441122
  }
],
"payment_method": "Prepaid",
"shipping_charges": 0,
"giftwrap_charges": 0,
"transaction_charges": 0,
"total_discount": 0,
"sub_total": 9000,
"length": 10,
"breadth": 15,
"height": 20,
"weight": 2.5
}
```

## POST Cancel an Order

<https://apiv2.shiprocket.in/v1/external/orders/cancel>

Use this API to cancel a created order. Multiple order\_ids can be passed together as an array to cancel them simultaneously.

### Parameters:

| PARAMS           | REQUIRED | DATA TYPE      | DESCRIPTION                                                         | EXAMPLE  |
|------------------|----------|----------------|---------------------------------------------------------------------|----------|
| <code>ids</code> | YES      | <i>integer</i> | The Shiprocket order id/ids of the orders that need to be canceled. | 16178831 |

### HEADERS

**Content-Type**                      application/json

**Body** raw

```
{
  "ids": []
}
```

## PATCH Add Inventory for Ordered Product

<https://apiv2.shiprocket.in/v1/external/orders/fulfill>

Use this API to add inventory for ordered products that are out of stock or low on quantity. You have to pass the order id and order product id. You can also specify the number of items.

### Notes:

- Inventory sync of your account must be turned on to use this API.
- The order\_id to be passed is the shiprocket order id. If you don't know the product id, Use the 'Get Product Details' API to get details about all the existing products.

### Parameters:

| PARAMS                        | REQUIRED | DATA TYPE      | DESCRIPTION                                     | EXAMPLE  |
|-------------------------------|----------|----------------|-------------------------------------------------|----------|
| <code>order_id</code>         | YES      | <i>integer</i> | The Shiprocket order_id specified to the order. | 16167171 |
| <code>order_product_id</code> | YES      | <i>integer</i> | The product id of the product to be added.      | 17171717 |
| <code>quantity</code>         | YES      | <i>string</i>  | The number of items you want to add.            | 10       |
| <code>action</code>           | YES      | <i>string</i>  | The action you want to carry out. Is 'add'.     | add      |

### HEADERS

**Content-Type** application/json

**Body** raw

```
{
```

```
"data": [
  {
    "order_id": "",
    "order_product_id": "",
    "quantity": "",
    "action": ""
  }
]
```

## PATCH Map Unmapped Products

<https://apiv2.shiprocket.in/v1/external/orders/mapping>

This API maps your unmapped inventory products.

### Note:

- Products must be unmapped to run this API successfully.
- Inventory sync must be turned on to use this API.

### Parameters:

| PARAMS                        | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                                                                                | EXAMPLE   |
|-------------------------------|----------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| <code>order_id</code>         | YES      | <i>integer</i> | The Shiprocket order_id specified to the order.                                                                                                                            | 16167171  |
| <code>order_product_id</code> | YES      | <i>integer</i> | The product id of the product to be mapped.                                                                                                                                | 17171717  |
| <code>master_sku</code>       | YES      | <i>string</i>  | The sku id of the product. In the case of a single integrated channel, master sku is the same as channel_sku; Otherwise, it can be found using the 'Get All Products' API. | chakra123 |

## HEADERS

**Content-Type**

application/json

## Body raw

---

```
{
  "data": [
    {
      "order_id": "",
      "order_product_id": "",
      "master_sku": ""
    }
  ]
}
```

---

## POST Import Orders in Bulk

<https://apiv2.shiprocket.in/v1/external/orders/import>

Use this API to import orders in bulk to your Shiprocket account from an existing '.csv' file. The imported orders are automatically added to your panel.

## HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

## Body formdata

---

file

---

# Couriers

Use these APIs to assign AWB to your order, check for courier serviceability, and request for the pickup of your order.

All available couriers, along with their codes, are mentioned below:

| COURIER ID | COURIER NAME             |
|------------|--------------------------|
| 1          | Blue Dart                |
| 4          | Amazon Shipping 5Kg      |
| 6          | DTDC Surface             |
| 10         | Delhivery                |
| 14         | Ecom Express Surface     |
| 18         | DTDC 5kg                 |
| 19         | Ecom Express Surface 2kg |
| 23         | Xpressbees 1kg           |
| 24         | Xpressbees 2kg           |
| 25         | Xpressbees 5kg           |
| 29         | Amazon Shipping 1Kg      |
| 32         | Amazon Shipping 2Kg      |
| 33         | Xpressbees               |
| 35         | Aramex International     |

## POST Generate AWB for Shipment

<https://apiv2.shiprocket.in/v1/external/courier/assign/awb>

This API can be used to assign the AWB (Air Waybill Number) to your shipment. The AWB is a unique number that helps you track the shipment and get details about it.

### Parameters:

| PARAMS                   | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                           | EXAMPLE  |
|--------------------------|----------|----------------|-----------------------------------------------------------------------------------------------------------------------|----------|
| <code>shipment_id</code> | YES      | <i>integer</i> | The shipment id of the order you want to create the AWB for.                                                          | 16016920 |
| <code>courier_id</code>  | NO       | <i>integer</i> | The courier id of the courier service you want to select. The default courier is selected in case no id is specified. | 10       |
| <code>status</code>      | NO       | <i>string</i>  | Use this to change the courier of a shipment. Value: reassign. Note that this can be done only once in 24 hours.      | reassign |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "shipment_id": "",
  "courier_id": "",
  "status": ""
}
```

## GET List of Couriers

<https://apiv2.shiprocket.in/v1/external/courier/courierListWithCounts>

Use this API to check the list of couriers and the related information with Shiprocket based on the search criteria.

**Note:**

- ### Parameters:

## HEADERS

## Content-Type

```
application/json
```

## GET Check Courier Serviceability

<https://apiv2.shiprocket.in/v1/external/courier/serviceability/>

**Note:**

- ### Parameters:

| PARAMS                         | REQUIRED        | DATA TYPE      | DESCRIPTION                                                                                                   | EXAMPLE |
|--------------------------------|-----------------|----------------|---------------------------------------------------------------------------------------------------------------|---------|
| <code>pickup_postcode</code>   | YES             | <i>integer</i> | Postcode from where the order will be picked.                                                                 | 110030  |
| <code>delivery_postcode</code> | YES             | <i>integer</i> | Postcode where the order will be delivered                                                                    | 122002  |
| <code>order_id</code>          | NO              | <i>integer</i> | If order id is already created in Shiprocket panel then you can use this shiprocket order id in servicibility | 123456  |
| <code>cod</code>               | CONDITIONAL YES | <i>boolean</i> | 1 for Cash on Delivery and 0 for Prepaid orders.                                                              | 1       |
| <code>weight</code>            | CONDITIONAL YES | <i>string</i>  | The weight of shipment in kgs.                                                                                | 2       |
| <code>length</code>            | NO              | <i>integer</i> | The length of the shipment in cms                                                                             | 15      |

## HEADERS

**Content-Type** application/json

## POST Request for Shipment Pickup

<https://apiv2.shiprocket.in/v1/external/courier/generate/pickup>

Use this API to create a pickup request for your order shipment. The API returns the pickup status along with the estimated pickup time.

You will have to call the 'Generate Manifest' API after the successful response of this API.

### Note:

- The AWB must be already generated for the shipment id to generate the pickup request.
- Only one shipment\_id can be passed at a time.
- In case the pickup\_date falls on a holiday or Sunday, the shipment will be booked for the next available date.

### Parameters:

| PARAMS                   | REQUIRED | DATA TYPE             | DESCRIPTION                                                                                                                                           | EXAMPLE        |
|--------------------------|----------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <code>shipment_id</code> | YES      | integer               | The shipment id of the shipment which is requested for pickup.                                                                                        | [16090109]     |
| <code>status</code>      | NO       | <i>string</i>         | Use this field to retry if the pickup request fails.<br>Value: retry                                                                                  | retry          |
| <code>pickup_date</code> | NO       | <i>Array of Dates</i> | Use this field to schedule a pickup for a future date. The date format would be YYYY-MM-DD. You can reschedule the date till that date has not passed | ["2022-06-04"] |

## HEADERS

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

**Body** raw

```
{
  "shipment_id": [16090109]
}
```

## POST Upload Blocked Pincodes

<https://serviceability.shiprocket.in/v1/external/blocked-pincodes/upload>

Adds pincodes to the seller's delivery-block list, or removes them.

The `block` action runs **per-pincode classification** — valid entries are saved, invalid or duplicate entries are recorded in **Activity Logs** as a downloadable CSV instead of failing the whole request. The `unlock` action is **all-or-nothing**: the first invalid pincode aborts the call

first invalid pincode aborts the call.

## Authentication

Pass the bearer token via header or query parameter:

| Method            | Where         | Example                               |
|-------------------|---------------|---------------------------------------|
| Header (standard) | Authorization | Authorization: {{vault:bearer-token}} |
| Query parameter   | ?token=       |                                       |

## Request Body Parameters

| Field                     | Type     | Required | Description                                               |
|---------------------------|----------|----------|-----------------------------------------------------------|
| postcode                  | object   | Yes      | Container for the delivery_blocked array.                 |
| postcode.delivery_blocked | string[] | Yes      | Pincodes to add to / remove from the delivery block list. |
| action                    | string   | Yes      | "block" or "unblock". Trimmed and lowercased server-side. |

## Notes

- **Idempotency** — block is naturally idempotent. unblock is similarly idempotent for already-removed pincodes.
- **Request size cap** — 1 MiB.
- **Unblock does not write to Activity Logs** — only block produces a per-pincode result CSV; unblock surfaces the first malformed entry inline in the response.
- **Timestamps** — stored in IST ( Asia/Kolkata ).

## HEADERS

Authorization Bearer {{token}}

Content-Type application/json

Body raw (json)

```
json

{"postcode": {"delivery_blocked": ["110001", "560034"]}, "action": "block"}
```

## GET Get Blocked Pincodes

`https://serviceability.shiprocket.in/v1/external/block-pincodes/get`

Reads the seller's delivery-block list. **Multi-mode** — the mode is selected by query parameters:

| Query parameter                              | Mode                            |
|----------------------------------------------|---------------------------------|
| <code>?is_download=1</code>                  | CSV download (highest priority) |
| <code>?search=</code> (non-empty after trim) | Prefix search                   |
| (default — neither of the above)             | Paginated list                  |

Only `delivery_blocked` data is exposed.

### Authentication

Pass the bearer token via header or query parameter:

| Method            | Where                      | Example                            |
|-------------------|----------------------------|------------------------------------|
| Header (standard) | <code>Authorization</code> | <code>Authorization: Bearer</code> |
| Query parameter   | <code>?token=</code>       | <code>?token=</code>               |

### Query Parameters

| Param                     | Type   | Required | Default         | Description                                                                              |
|---------------------------|--------|----------|-----------------|------------------------------------------------------------------------------------------|
| <code>is_download</code>  | int    | No       | —               | Set to <code>1</code> for a presigned S3 link to a CSV of all pincodes.                  |
| <code>search</code>       | string | No       | —               | Prefix-match filter. Frontend should enforce a 4-char minimum; server does not validate. |
| <code>per_page</code>     | int    | No       | <code>15</code> | Page size (paginated mode only). Range <code>1–15</code> (silently capped at 15).        |
| <code>current_page</code> | int    | No       | <code>1</code>  | Page number (paginated mode only). Must be <code>&gt;=</code>                            |

## Mode Precedence

1. `is_download=1` — wins over everything
2. `search` (non-empty after trim) — wins over pagination
3. Default — paginated list

## Notes

- **Search isn't validated server-side** — pass any string; the server does prefix matching as-is.
- **CSV download URL is presigned for 24 hours** — generate a fresh link by calling the endpoint again after expiry.
- `per_page` is silently capped at 15; values above 15 are treated as 15.

## HEADERS

---

Authorization

Bearer {{token}}

---

# Orders

These APIs can be used to get details about your created orders, as well as manage them, which include fetching orders from your channel, syncing their status, and exporting them to a CSV file.

### Filters:

The 'filter' values are mentioned below. Use these to filter your data:

| filter_by        | filter  | description             |
|------------------|---------|-------------------------|
| payment_method   |         |                         |
| →                | cod     | cash on delivery orders |
| →                | Prepaid | for prepaid orders      |
| channel_order_id |         |                         |
| →                | 123     | Your order id           |
| status           |         |                         |
| →                | 1       | New                     |
| →                | 2       | Invoiced                |
| →                | 3       | Ready To Ship           |
| →                | 4       | Pickup Scheduled        |
| →                | 5       | Canceled                |
| →                | 6       | Shipped                 |
| →                | 7       | Delivered               |
| →                | 8       | ePavment Failed         |

## GET Get all Orders

<https://apiv2.shiprocket.in/v1/external/orders>

This API call will display a list of all created and available orders in your Shiprocket account. The product and shipment details are displayed as sub-arrays within each order detail.

You can also sort and filter the data according to your needs by passing the optional parameters. Not passing anything will display the data in the default format.

You can also fetch the data based on the order update date. PFB the validations:

### Plain Text

1. **if** updated\_to => passed and updated\_from not passed =>, error will come => Please send update
2. **if** updated\_from => passed and updated\_to => paased => and from-to > 30 then error => Differenc
3. **if** updated\_From < 30 then error => Updated\_from date should not be less than 30 days from c

### Parameters:

| PARAMS    | REQUIRED | DATA TYPE | DESCRIPTION                                     | EXAMPLE                                                             |
|-----------|----------|-----------|-------------------------------------------------|---------------------------------------------------------------------|
| page      | NO       | integer   | The page number to display.                     | 5                                                                   |
| per_page  | NO       | integer   | The number of entries per page.                 | 5                                                                   |
| sort      | NO       | string    | Sort conditions: ASC or DESC                    | ASC                                                                 |
| sort_by   | NO       | string    | The Field to sort by: id or status              | id                                                                  |
| to        | NO       | string    | The end date.                                   | 2018-07-24                                                          |
| from      | NO       | string    | The start date.                                 | 2019-07-24                                                          |
| filter_by | NO       | string    | Field to filter by.                             | status,<br>payment_method,<br>delivery_country,<br>channel_order_id |
| filter    | NO       | string    | Value of the field                              |                                                                     |
| search    | NO       | string    | Search for AWB or by Channel order_id (order id | 224477                                                              |

## HEADERS

**Content-Type** application/json

**Authorization**

## GET Get Specific Order Details

<https://apiv2.shiprocket.in/v1/external/orders/show>

Get the order and shipment details of a particular order through this API by passing the Shiprocket order\_id in the endpoint URL itself — type in your order\_id in place of {id}.

No other body parameters are required.

### Note:

For SRF orders, you'll receive an extra parameter viz., fulfillment\_status. This key will have four values:

- Ready to Pack

- Ready to Pack,
- Packed
- Added to Picklist
- Picked up

#### Path:

##### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/orders/show/16167171>

#### HEADERS

---

|               |                  |
|---------------|------------------|
| Content-Type  | application/json |
| Authorization | Bearer {token}   |

### POST Export your orders

<https://apiv2.shiprocket.in/v1/external/orders/export>

This API downloads and creates a CSV file of all the orders in your Shiprocket account and sends the download URL to the linked email account of the API user.

The CSV file containing is accessible via this URL. No parameters are required to access this API.

#### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

#### Body raw

---

```
{  
  
}
```

## Return & Exchange Orders

---

## POST Create a Return Order

<https://apiv2.shiprocket.in/v1/external/orders/create/return>

Use this API to create a new return order in your Shiprocket panel. Return orders are created in case the buyer refuses/rejects/returns a specific order.

The parameter specifications are the same as the custom order API, with a few exceptions.

### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                                            | EXAMPLE    |
|-------------------------|----------|----------------|----------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>order_id</code>   | YES      | <i>string</i>  | The order id you want to specify to the order. Max char: 50. (Avoid passing character values as this contradicts some other API calls) | 99711997   |
| <code>order_date</code> | YES      | <i>string</i>  | The date of order creation in yyyy-mm-dd format. Time is an additional option.                                                         | 2019-08-05 |
| <code>channel_id</code> | NO       | <i>integer</i> | Id of the desired channel where the order is to be placed. 'Custom' channel id is selected in case parameter is not filled.            | 768903     |

### Possible return\_reason values:

#### Plain Text

1. Bought by Mistake
2. Better price available
3. Performance or quality not adequate
4. Incompatible or not useful
5. Product damaged, but shipping box OK
6. Item arrived too late
7. Missing parts or accessories
8. Both product and shipping box damaged
9. Wrong item was sent
10. Item defective or doesn't work
11. No longer needed

## HEADERS

---

Content-Type

application/json

Body raw

---

```
{
  "order_id": "r121579B09ap3o",
  "order_date": "2021-12-30",
  "channel_id": "27202",
  "pickup_customer_name": "iron man",
  "pickup_last_name": "",
  "company_name": "iorn pvt ltd",
  "pickup_address": "b 123",
  "pickup_address_2": "",
  "pickup_city": "Delhi",
  "pickup_state": "New Delhi",
  "pickup_country": "India",
  "pickup_pincode": 110030,
  "pickup_email": "deadpool@red.com",
  "pickup_phone": "9810363552",
  "pickup_isd_code": "91",
  "shipping_customer_name": "Jax",
  "shipping_last_name": "Doe",
  "shipping_address": "Castle",
  "shipping_address_2": "Bridge",
  "shipping_city": "ghaziabad",
  "shipping_country": "India",
  "shipping_pincode": 201005,
  "shipping_state": "Uttarpardesh",
  "shipping_email": "kumar.abhishek@shiprocket.com",
  "shipping_isd_code": "91",
  "shipping_phone": 8888888888,
  "order_items": [
    {
      "sku": "WSH234",
      "name": "shoes",
      "units": 2,
      "selling_price": 100,
      "discount": 0,
      "qc_enable": true,
      "hsn": "123",
      "brand": "",
      "qc_size": "43"
    }
  ],
  "payment_method": "PREPAID",
  "total_discount": "0",
  "sub_total": 400,
  "length": 11,
  "breadth": 11,
}
```

```
    "height": 11,  
  
    "weight": 0.5  
  }  
}
```

POST

Create Exchange Order

https://apiv2.shiprocket.in/v1/external/orders/create/exchange

Use this API to create a new exchange order in your Shiprocket panel. Exchange orders are created in case the buyer needs to replace an item due to reasons such as size mismatch, wrong product received, or defective product. This API helps sellers seamlessly process exchange requests while ensuring the correct quality checks and logistics handling

Parameters:

| PARAMS                      | REQUIRED | DATA TYPE | DESCRIPTION                          | EXAMPLE    |
|-----------------------------|----------|-----------|--------------------------------------|------------|
| exchange_order_id           | YES      | String    | Unique ID for the exchange order     | EX_TEST002 |
| seller_pickup_location_id   | YES      | String    | Pickup location ID of the seller     | 5723898    |
| seller_shipping_location_id | YES      | String    | Shipping location ID of the seller   | 5723898    |
| return_order_id             | YES      | String    | Unique ID for the return order       | R_TEST002  |
| order_date                  | YES      | Date      | Date of order placement (YYYY-MM-DD) | 2024-12-10 |
| payment_method              | YES      | String    | Payment method used for the order    | prepaid    |
| buyer_shipping_first_name   | YES      | String    | First name of the shipping buyer     | Test       |
| buyer_shipping_last_name    | NO       | String    | Last name of the shipping buyer      | Test       |

AUTHORIZATION Bearer Token

HEADERS

Content-Type

application/json

Authorization

Bearer {{token}}

Body raw (json)

json

```
{
  "order_items": [
    {
      "name": "Black tshirt XL",
      "selling_price": "500.00",
      "units": "1",
      "hsn": "1733808730720",
      "sku": "mackbook",
      "tax": "",
      "discount": "",
      "brand": "",
      "color": "",
      "exchange_item_id": "193658024",
      "exchange_item_name": "Black tshirt XL",
      "exchange_item_sku": "mackbook",
      "qc_enable": true,
      "qc_product_name": "Black tshirt XL",
      "qc_product_image": "https://sr-multichannel-stage.s3.ap-south-1.amazonaws.com/1310/qc_p",
      "qc_brand": "changedname1",
      "qc_color": "changeclr",
      "qc_size": "changesize112",
      "accessories": "",
      "qc_used_check": "1",
      "qc_sealtag_check": "1",
      "qc_brand_box": "1",
      "qc_check_damaged_product": "yes"
    }
  ],
  "buyer_pickup_first_name": "Test",
  "buyer_pickup_last_name": "Test",
  "buyer_pickup_email": "test@gmail.com",
  "buyer_pickup_address": "Test",
  "buyer_pickup_address_2": "",
  "buyer_pickup_city": "South West Delhi",
  "buyer_pickup_state": "Delhi",
  "buyer_pickup_country": "India",
  "buyer_pickup_phone": "9716414139",
  "buyer_pickup_pincode": "110045",
  "buyer_shipping_first_name": "Test",
  "buyer_shipping_last_name": "Test",
  "buyer_shipping_email": "test@gmail.com",
  "buyer_shipping_address": "dkalsd",
  "buyer_shipping_address_2": "",
  "buyer_shipping_city": "South West Delhi",
  "buyer_shipping_state": "Delhi",
  "buyer_shipping_country": "India",
  "buyer_shipping_phone": "9716414139"
```

```
    "buyer_shipping_phone": "7710414137",  
    "buyer_shipping_pincode": "110045",  
    "seller_pickup_location_id": "5723898",  
    "seller_shipping_location_id": "5723898",  
    "exchange_order_id": "EX_TEST002",  
    "return_order_id": "R_TEST002",  
    "payment_method": "prepaid",  
    "order_date": "2024-12-10",  
    "channel_id": "1960878",  
    "existing_order_id": "",  
    "return_reason": "29",  
    "sub_total": "500.00",  
    "shipping_charges": "",  
    "giftwrap_charges": "",  
    "total_discount": "0",  
    "transaction_charges": "",  
    "exchange_length": "11",  
    "exchange_breadth": "11",  
    "exchange_height": "11",  
    "exchange_weight": "11",  
    "return_length": "10.00",  
    "return_breadth": "10.00",  
    "return_height": "10.00",  
    "return_weight": "0.500",  
    "qc_check": "true"  
}
```

## POST Update Return Order



<https://apiv2.shiprocket.in/v1/external/orders/edit>

Use this API to update your return orders. Please specify the parameters based on the "action" key.

### Parameters:

| PARAMS                | REQUIRED        | DATA TYPE     | DESCRIPTION                                                                                                                                                                                             | EXAMPLE                          |
|-----------------------|-----------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <code>order_id</code> | YES             | <i>string</i> | Your return order ID                                                                                                                                                                                    | R_1231234                        |
| <code>action</code>   | YES             | <i>string</i> | Pass array of action. Allowed actions:<br><code>1. product_details</code> : Allows you to edit the weight and dimensions<br><code>2. warehouse_address</code> : Allows you to change the return address | "action":<br>["product_details"] |
| <code>length</code>   | CONDITIONAL YES | <i>float</i>  | The length of the item in cms. Must be more than 0.5                                                                                                                                                    | 12                               |
| <code>breadth</code>  | CONDITIONAL     | <i>float</i>  | The breadth of                                                                                                                                                                                          | 23                               |

**AUTHORIZATION** Bearer Token

**HEADERS**

**Content-Type** application/json

**Body** raw

```
{
  "order_id": "79596",
  "action": ["product_details"],
  "length": "11",
  "breadth": "10",
  "height": "10",
  "return_warehouse_id": 1072,
  "weight": 1.5
}
```

## GET Get All Return Orders

<https://apiv2.shiprocket.in/v1/external/orders/processing/return>

Using this API, you can get a list of all created return orders in your Shiprocket account, along with their details.

No parameters are required to use the API. However, further parameters can be defined to sort and filter the data.

### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                    | EXAMPLE    |
|----------|----------|-----------|--------------------------------|------------|
| page     | NO       | integer   | The page number to display.    | 1          |
| per_page | NO       | integer   | The number of orders per page. | 2          |
| to       | NO       | string    | Ending date of search.         | 2019-08-04 |
| from     | NO       | string    | Starting date of search.       | 2019-08-05 |

### HEADERS

Content-Type                      application/json

## GET Check Courier Serviceability

<https://apiv2.shiprocket.in/v1/external/courier/serviceability/>

Use this API to check the availability of couriers between the pickup and delivery postal codes.

Further details like the estimated time of delivery, the rates along with the ids are also shown.

### Note:

- One of either the 'order\_id' or 'cod' and 'weight' is required. If you specify the order id, the cod and weight fields are not required and vice versa.
- You can add further fields to add the shipment details and filter the search.

### Parameters:

| PARAMS                         | REQUIRED           | DATA TYPE      | DESCRIPTION                                                                                                           | EXAMPLE  |
|--------------------------------|--------------------|----------------|-----------------------------------------------------------------------------------------------------------------------|----------|
| <code>pickup_postcode</code>   | YES                | <i>integer</i> | The shipment id of the order you want to create the AWB of.                                                           | 16016920 |
| <code>delivery_postcode</code> | YES                | <i>integer</i> | The courier id of the courier service you want to select. The default courier is selected in case no id is specified. | 10       |
| <code>order_id</code>          | CONDITIONAL<br>YES | <i>integer</i> | Use this to change the courier of a shipment. Value: reassign Note that this can be done only once in 24 hours.       | reassign |
| <code>cod</code>               | CONDITIONAL<br>YES | <i>boolean</i> | 1 for Cash on Delivery and 0 for                                                                                      | 1        |

## HEADERS

Content-Type                      application/json

## POST    Generate AWB for Return Shipment

<https://apiv2.shiprocket.in/v1/external/courier/assign/awb>

This API can be used to assign the AWB (Air Waybill Number) to your shipment. The AWB is a unique number that helps you track the shipment and get details about it.

### Parameters:

| PARAMS                   | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                           | EXAMPLE  |
|--------------------------|----------|----------------|-----------------------------------------------------------------------------------------------------------------------|----------|
| <code>shipment_id</code> | YES      | <i>integer</i> | The shipment id of the order you want to create the AWB of.                                                           | 16016920 |
| <code>courier_id</code>  | NO       | <i>integer</i> | The courier id of the courier service you want to select. The default courier is selected in case no id is specified. | 10       |
| <code>status</code>      | NO       | <i>string</i>  | Use this to change the courier of a shipment. Value: reassign Note that this can be done only once in 24 hours.       | reassign |
| <code>is_return</code>   | YES      | <i>integer</i> | Whether the order is return order or                                                                                  | 1        |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "shipment_id": "",
  "courier_id": "",
  "status": "",
  "is_return": ""
}
```

# Shipments

These APIs can be used to get shipment details. You can either get all shipment details at once or the details of a

particular shipment.

Below are some associated status codes related to the shipments:

Status Codes:

| STATUS CODE | DESCRIPTION                |
|-------------|----------------------------|
| 1           | AWB Assigned               |
| 2           | Label Generated            |
| 3           | Pickup Scheduled/Generated |
| 4           | Pickup Queued              |
| 5           | Manifest Generated         |
| 6           | Shipped                    |
| 7           | Delivered                  |
| 8           | Cancelled                  |
| 9           | RTO Initiated              |
| 10          | RTO Delivered              |
| 11          | Pending                    |
| 12          | Lost                       |
| 13          | Pickup Error               |
| 14          | RTO Acknowledged           |

GET Get All Shipment Details

https://apiv2.shiprocket.in/v1/external/shipments

Use this API to get the shipment details of all the shipments in your Shiprocket account.

The data is displayed in the default format if no filter or sort condition is passed. You can use the filter and sort conditions to streamline your data.

Parameters:

| PARAMS                 | REQUIRED | DATA TYPE     | DESCRIPTION                     | EXAMPLE |
|------------------------|----------|---------------|---------------------------------|---------|
| <code>sort</code>      | NO       | <i>string</i> | The sort format:<br>ASC or DESC | ASC     |
| <code>sort_by</code>   | NO       | <i>string</i> | The field to sort<br>by.        | id      |
| <code>filter</code>    | NO       | <i>string</i> | The filter value.               | 141121  |
| <code>filter_by</code> | NO       | <i>string</i> | The filed to filter<br>by.      | id      |

## HEADERS

**Content-Type**                      application/json

## GET    Get Details of Specific Shipment

<https://apiv2.shiprocket.in/v1/external/shipments>

Get the details of a specific Shipment by passing the value of shipment\_id in the endpoint URL. No other body parameters are required.

**Path:**

### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/shipments/16016920>

## HEADERS

**Content-Type**                      application/json

## POST    Cancel a Shipment

<https://apiv2.shiprocket.in/v1/external/orders/cancel/shipment/awbs>

Use this API to cancel a created shipment before the "Out for Pickup" state. Multiple AWBs can be passed together as an array to cancel them simultaneously.

Limit: 2000 AWBs

#### Parameters:

| PARAMS            | REQUIRED | DATA TYPE     | DESCRIPTION                                    | EXAMPLE        |
|-------------------|----------|---------------|------------------------------------------------|----------------|
| <code>awbs</code> | YES      | <i>string</i> | The AWB/List of AWBs that need to be canceled. | 19041211125783 |

#### HEADERS

**Content-Type** application/json

#### Body raw

```
{
  "awbs": ["19041211125783"]
}
```

## Labels | Manifests | Invoice

These APIs are designed for the generation of manifests, invoices and labels for your shipment. You can also get manifest details and print a manifest using the respective API's.

### POST Generate Manifest

<https://apiv2.shiprocket.in/v1/external/manifests/generate>

Using this API, you can generate the manifest for your order. This API generates the manifest and displays the download URL of the same.

#### Note:

- Multiple ids can also be passed as an array for bulk generation of manifests.
- AWB must be assigned and pickup requested on the shipment id to generate manifest.

#### Parameters:

| PARAMS                   | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                   | EXAMPLE    |
|--------------------------|----------|----------------|-----------------------------------------------------------------------------------------------|------------|
| <code>shipment_id</code> | YES      | <i>integer</i> | The shipment id of the order.<br>Multiple ids can be passed as an array, separated by commas. | [16090109] |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "shipment_id": []
}
```

## POST Print Manifest

<https://apiv2.shiprocket.in/v1/external/manifests/print>

Use this API to print the generated manifest of orders at an individual level.

### Note

- Manifest needs to be generated first for this API to print it. Use the 'Generate Manifest' API to do the same.
- Multiple order ids can be passed together.

### Parameters:

| PARAMS                 | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                | EXAMPLE    |
|------------------------|----------|----------------|------------------------------------------------------------------------------------------------------------|------------|
| <code>order_ids</code> | YES      | <i>integer</i> | The Shiprocket order id of whose manifest is to be generated.<br>Multiple ids can be passed together as an | [16090109] |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "order_ids": []
}
```

## POST Generate Label

https://apiv2.shiprocket.in/v1/external/courier/generate/label

Generate the label of order by passing the shipment id in the form of an array. This API displays the URL of the generated label.

**Note:**

- The AWB must be assigned to the shipment to generate the label.
- 'shipment\_id' must be passed as an array.

**Parameters:**

| PARAMS      | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                   | EXAMPLE             |
|-------------|----------|-----------|---------------------------------------------------------------------------------------------------------------|---------------------|
| shipment_id | YES      | integer   | The shipment id of the order whose label is to be generated. Multiple ids can be passed together as an array. | [16104408,16104409] |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "shipment_id": []
}
```

**POST**   **Generate Invoice**

https://apiv2.shiprocket.in/v1/external/orders/print/invoice

Use this API to generate the invoice for your order by passing the respective Shiprocket order ids.

The generated invoice URL is displayed as a response. Multiple ids can be passed together as an array.

**Note**

- Order ids must be passed as an array.

**Parameters:**

| PARAMS | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                              | EXAMPLE             |
|--------|----------|-----------|--------------------------------------------------------------------------------------------------------------------------|---------------------|
| ids    | YES      | integer   | The Shiprocket order id of the orders whose invoices are to be created. Multiple ids can be passed together as an array. | [16255275,16255276] |

**HEADERS**

**Content-Type**                      application/json

**Body** raw

```
{
  "ids": []
}
```

# Wrapper API

This is an all-in-one API to create an order, ship the order, add a new pickup location and generate a label along with the manifest for the same.

## POST Forward

<https://apiv2.shiprocket.in/v1/external/shipments/create/forward-shipment>

Use this API to do multiple tasks in one go, namely creating a quick order, requesting its shipment, and finally generating the label and the manifest for the same order.

This API integrates several other APIs to perform all these tasks together.

### Notes:

- Use the 'vendor\_details' array to add a new pickup location to your account and assign it to your order.
- The 'pickup\_location' field must contain a new pickup location name for adding a new pickup location to your Shiprocket account.
- In case of multiple items per order, please pass the final weight (sum total weight of items) of the shipment.

### Parameters:

| PARAMS                         | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                | EXAMPLE |
|--------------------------------|----------|----------------|--------------------------------------------------------------------------------------------|---------|
| <code>mode</code>              | NO       | <i>string</i>  | The mode of shipment, either surface or air.<br><i>Value: <b>Surface</b> or <b>Air</b></i> | Air     |
| <code>request_pickup</code>    | NO       | <i>boolean</i> | Use false if you dont want to request pickup. Default value is true.                       | true    |
| <code>print_label</code>       | NO       | <i>boolean</i> | Use false if you dont want to print label. Default value is true.                          | true    |
| <code>generate_manifest</code> | NO       | <i>boolean</i> | Use false if you dont want to generate manifest. Default                                   | true    |

|            |    |         |                   |    |
|------------|----|---------|-------------------|----|
|            |    |         | value is true.    |    |
| courier_id | NO | integer | The courier id of | 10 |

HEADERS

Content-Type                      application/json

Body raw

```
{
  "mode": "",
  "request_pickup": "",
  "print_label": "",
  "generate_manifest": "",
  "ewaybill_no": "",
  "courier_id": "",
  "reseller_name": "",
  "order_id": "",
  "isd_code": "",
  "billing_isd_code": "",
  "order_date": "",
  "channel_id": "",
  "company_name": "",
  "billing_customer_name": "",
  "billing_last_name": "",
  "billing_address": "",
  "billing_address_2": "",
  "billing_city": "",
  "billing_state": "",
  "billing_country": "",
  "billing_pincode": "",
  "billing_email": "",
  "billing_phone": "",
  "billing_alternate_phone": "",
  "shipping_is_billing": "1",
  "shipping_customer_name": "",
  "shipping_last_name": "",
  "shipping_address": "",
  "shipping_address_2": "",
  "shipping_city": "",
  "shipping_state": "",
  "shipping_country": "",
  "shipping_pincode": "",
  "shipping_email": "",
  "shipping_phone": "",
  "order_items": [
    {
      "name": "",
      "sku": "",
      "units": "",
      "hsn": "",
```

```

        "selling_price": "",
        "tax": "",
        "discount": ""
    }
],
"payment_method": "",
"shipping_charges": "",
"giftwrap_charges": "",
"transaction_charges": "",
"total_discount": "",
"sub_total": "",
"weight": "",
"length": "",
"breadth": "",
"height": "",
"pickup_location": "",
"customer_gstin": "",
"vendor_details": {
    "email": "",
    "phone": "",
    "name": "",
    "address": "",
    "address_2": "",
    "city": "",
    "state": "",
    "country": "",
    "pin_code": "",
    "pickup_location": ""
}
}

```

## POST Return

<https://apiv2.shiprocket.in/v1/external/shipments/create/return-shipment>

Use this API to perform multiple tasks like Create, AWB generation & scheduling reverse pickups for your Returns. The specifications are the same as the custom return order API, with a few exceptions.

### Notes:

- pickup\_location field is not required.
- Label and Manifest are not required in case of returns.

### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                                            | EXAMPLE    |
|-------------------------|----------|----------------|----------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>order_id</code>   | YES      | <i>string</i>  | The order id you want to specify to the order. Max char: 50. (Avoid passing character values as this contradicts some other API calls) | 99711997   |
| <code>order_date</code> | YES      | <i>string</i>  | The date of order creation in yyyy-mm-dd format. Time is an additional option.                                                         | 2019-08-05 |
| <code>channel_id</code> | NO       | <i>integer</i> | Id of the desired channel where the order is to be placed. 'Custom' channel id is selected in case parameter is not filled.            | 768903     |

## HEADERS

**Content-Type** application/json

## Body raw

```
{
  "order_id": "",
  "order_date": "",
  "channel_id": "",
  "pickup_customer_name": "",
  "pickup_last_name": "",
  "company_name": "",
  "pickup_address": "",
  "pickup_address_2": "",
  "pickup_city": "",
  "pickup_state": "",
  "pickup_country": "",
  "pickup_pincode": ,
  "pickup_email": "",
}
```

```
"pickup_phone": "",
"pickup_isd_code": "",
"shipping_customer_name": "",

"shipping_last_name": "",
"shipping_address": "",
"shipping_address_2": "",
"shipping_city": "",
"shipping_country": "",
"shipping_pincode": ,
"shipping_state": "",
"shipping_email": "",
"shipping_isd_code": "",
"shipping_phone": ,
"order_items": [
{
"sku": "",
"name": "",
"units": "",
"selling_price": "",
"discount": ""
}
],
"payment_method": "",
"total_discount": "",
"sub_total": "",
"length": "",
"breadth": "",
"height": "",
"weight": "",
"request_pickup": ""
}
```

---

## NDR

These APIs can be used to get details about your shipments that are in NDR, as well as manage them, which includes fetching NDR shipments from your account (all or specific) and taking actions such as Reattempt and RTO based on the reason.

---

### GET Get All NDR Shipments

<https://apiv2.shiprocket.in/v1/external/ndr/all>

This API call will display a list of all the shipments that are in NDR in your Shiprocket account.

You can also sort and filter the data according to your needs by passing the optional parameters. Not passing anything will display the data in the default format.

#### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                     | EXAMPLE    |
|----------|----------|-----------|---------------------------------|------------|
| page     | NO       | integer   | The page number to display.     | 5          |
| per_page | NO       | integer   | The number of entries per page. | 5          |
| to       | NO       | string    | The end date.                   | 2021-08-02 |
| from     | NO       | string    | The start date.                 | 2021-08-02 |
| search   | NO       | string    | Search for AWB.                 | 224477     |

## HEADERS

**Content-Type** application/json

**Authorization**

## GET Get Specific NDR Shipment Details

`https://apiv2.shiprocket.in/v1/external/ndr/{AWB}`

Get the shipment details of a particular order through this API by passing the AWB number in the endpoint URL itself. You can get the details like AWB, NDR Attempt, NDR Reason, Customer Details, Product Details, Courier.

Type in your AWB code in place of {AWB}. No other body parameters are required.

**Path:**

### EXAMPLE

`https://apiv2.shiprocket.in/v1/external/ndr/94711332`

## HEADERS

**Content-Type** application/json

**Authorization** Bearer {token}

## POST Action NDR

https://apiv2.shiprocket.in/v1/external/ndr/{awb}/action

This API will let you take actions like Reattempt and RTO on the shipments that are in NDR.

### Parameters:

| PARAMS                   | REQUIRED        | DATA TYPE     | DESCRIPTION                                                                 | EXAMPLE                                                                                                                                                                                                                           |
|--------------------------|-----------------|---------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>action</code>      | YES             | <i>string</i> | The action needs to be specified                                            | 'fake-attempt' or 're-attempt' or 'return'                                                                                                                                                                                        |
| <code>comments</code>    | YES             | <i>string</i> | Any comment can be mentioned                                                | The Byer does not want the product                                                                                                                                                                                                |
| <code>phone</code>       | NO              | <i>string</i> | The phone number will be updated at the time of re-attempt and fake-attempt | 9999988888                                                                                                                                                                                                                        |
| <code>proof_audio</code> | CONDITIONAL YES | <i>string</i> | URL of the audio which will be updated at the time of the fake attempt      | <a href="https://s3-ap-southeast-1.amazonaws.com/kr-multichannel/imports/ndr/1655100133_file_example_MP3_700KB.mp3">https://s3-ap-southeast-1.amazonaws.com/kr-multichannel/imports/ndr/1655100133_file_example_MP3_700KB.mp3</a> |
| <code>proof_image</code> | CONDITIONAL YES | <i>string</i> | URL of the image which will be                                              | <a href="https://s3-ap-southeast-1.amazonaws.com/kr-multichannel/imports/ndr/1655100133_file_example_MP3_700KB.mp3">https://s3-ap-southeast-</a>                                                                                  |

### HEADERS

**Content-Type** application/json

### Body raw

```
{
  "action": "",
  "comments": ""
}
```

# Tracking

Use these APIs to get the tracking details of your shipments through the AWB code or the Shipment ID.

## Shipment Status Codes:

| STATUS CODE |  | DESCRIPTION            |
|-------------|--|------------------------|
| 6           |  | Shipped                |
| 7           |  | Delivered              |
| 8           |  | Canceled               |
| 9           |  | RTO Initiated          |
| 10          |  | RTO Delivered          |
| 12          |  | Lost                   |
| 13          |  | Pickup Error           |
| 14          |  | RTO Acknowledged       |
| 15          |  | Pickup Rescheduled     |
| 16          |  | Cancellation Requested |
| 17          |  | Out For Delivery       |
| 18          |  | In Transit             |
| 19          |  | Out For Pickup         |
| 20          |  | Pickup Exception       |

## GET Get Tracking through AWB

`https://apiv2.shiprocket.in/v1/external/courier/track/awb/{awb_code}`

Get the tracking details of your shipment by entering the AWB code of the same in the endpoint URL itself. No other body parameters are required to access this API.

The response is displayed in JSON format.

### Path:

#### EXAMPLE

`https://apiv2.shiprocket.in/v1/external/courier/track/awb/788830567028`

## HEADERS

---

Content-Type

application/json

---

## POST Get Tracking Data for Multiple AWBS

`https://apiv2.shiprocket.in/v1/external/courier/track/awbs`

Get the tracking details of multiple shipments by entering their AWB codes together as an array.

The response is displayed in JSON format.

### Notes:

- Data must be passed as a string array.
- Maximum of 50 AWB codes is supported at a time.

### Parameters:

| PARAMS            | REQUIRED | DATA TYPE     | DESCRIPTION                                                    | EXAMPLE                                       |
|-------------------|----------|---------------|----------------------------------------------------------------|-----------------------------------------------|
| <code>awbs</code> | YES      | <i>string</i> | The AWB codes of the shipments.<br>Must be passed as an array. | <code>["788830567028", "788829354408"]</code> |

## HEADERS

---

Content-Type

application/json

Body raw

---

```
{  
  "awbs": [ "", "" ]  
}
```

## GET Get Tracking through Shipment ID

`https://apiv2.shiprocket.in/v1/external/courier/track/shipment/{shipment_id}`

Get the tracking details of your shipment by entering the shipment\_id of the same in the endpoint URL. No other body parameters are required to access this API.

The response is displayed in JSON format.

### Path:

#### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/courier/track/shipment/16104408>

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

## GET Get Tracking Data through Order ID

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

Get the tracking details of your shipment by entering the Order ID of the same in the endpoint URL itself. If you have the same order ID in more than one channel, then use the param `channel_id`.

The response is displayed in JSON format.

### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                           | EXAMPLE |
|-------------------------|----------|----------------|---------------------------------------|---------|
| <code>order_id</code>   | YES      | <i>string</i>  | The order ID/number of your store.    | NO-123  |
| <code>channel_id</code> | NO       | <i>integer</i> | Channel ID corresponding to the store | 12345   |

### Path:

#### EXAMPLE

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

### HEADERS

#### Authorization

Bearer {token}

### PARAMS

|                         |       |
|-------------------------|-------|
| <code>order_id</code>   | 123   |
| <code>channel_id</code> | 12345 |

## Pickup Addresses

Use these APIs to get a list of all available pickup locations in your account or add a new pickup location.

---

## GET Get All Pickup Locations

`https://apiv2.shiprocket.in/v1/external/settings/company/pickup`

Get a list of all pickup locations that have been added to your Shiprocket account through this API.

No parameters are required to use this API.

---

## POST Add a New Pickup Location

`https://apiv2.shiprocket.in/v1/external/settings/company/addpickup`

This API can be used to add a new pickup location to your account.

Pass the minimum required parameters to add the location.

Further details to the address can be added if required.

### Parameters:

| PARAMS                       | REQUIRED | DATA TYPE      | DESCRIPTION                                                 | EXAMPLE                               |
|------------------------------|----------|----------------|-------------------------------------------------------------|---------------------------------------|
| <code>pickup_location</code> | YES      | <i>string</i>  | The nickname of the new pickup location. Max 36 characters. | Home                                  |
| <code>name</code>            | YES      | <i>string</i>  | The shipper's name.                                         | Deadpool                              |
| <code>email</code>           | YES      | <i>string</i>  | The shipper's email address.                                | <code>deadpool@chimichanga.com</code> |
| <code>phone</code>           | YES      | <i>integer</i> | Shipper's phone number.                                     | 977777779                             |
| <code>address</code>         | YES      | <i>string</i>  | Shipper's primary address. Max 80 characters.               | Mutant Facility, Sector 3             |
| <code>address_2</code>       | NO       | <i>string</i>  | Additional address details.                                 | House number 34                       |
| <code>city</code>            | YES      | <i>string</i>  | Pickup location city name.                                  | Pune                                  |
| <code>state</code>           | YES      | <i>string</i>  | Pickup location state name                                  | Maharashtra                           |

### HEADERS

---

**Content-Type**

application/json

**Body** raw

---

```
{
  "pickup_location": "",
  "name": "",
  "email": "",
  "phone": "",
  "address": "",
  "address_2": "",
  "city": "",
  "state": "",
  "country": "",
  "pin_code": ""
}
```

---

## Hyperlocal

### Orders

These APIs can be used to get details about your created orders, as well as manage them, which include fetching orders from your channel, syncing their status, and exporting them to a CSV file.

**Filters:**

The 'filter' values are mentioned below. Use these to filter your data:

| filter_by        | filter  | description             |
|------------------|---------|-------------------------|
| payment_method   |         |                         |
| →                | cod     | cash on delivery orders |
| →                | Prepaid | for prepaid orders      |
| channel_order_id |         |                         |
| →                | 123     | Your order id           |
| status           |         |                         |
| →                | 1       | New                     |
| →                | 2       | Invoiced                |
| →                | 3       | Ready To Ship           |
| →                | 4       | Pickup Scheduled        |
| →                | 5       | Canceled                |
| →                | 6       | Shipped                 |
| →                | 7       | Delivered               |
| →                | 8       | ePayment Failed         |

## POST Create Custom Order

<https://apiv2.shiprocket.in/v1/external/orders/create/adhoc>

Use this API to create a quick custom order. Quick orders are the ones where we do not store the product details in the master catalogue.

You have to pass all the required params at the minimum to create a quick custom order. You can add additional parameters as per your preference.

### Note:

- In case the 'shipping\_is\_billing' field is false, further shipping detail fields are required.

If no channel id is passed, the order will be assigned to the default custom channel. If the channel id is not known, use the 'Get All Channels' API to get the list of all integrated channels in your Shiprocket account.

- order\_id field cannot be equal to an already existing id. Doing so does not change or affect the existing order.
- New orders cannot be created with order id's same as that of cancelled orders. If error 422 shows up despite filling in the correct details, consider changing the order\_id.
- Be sure to input the correct calculated sub total amount. The total is not calculated automatically through the API.

- The 'order\_id' returned in the response is the Shiprocket order\_id. Please save this order ID as we will use this in future API calls.

### Parameters:

| PARAMS                       | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                                             | EXAMPLE           |
|------------------------------|----------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| <code>order_id</code>        | YES      | <i>string</i>  | The order id you want to specify to the order. Max char: 50. (Avoid passing character values as this contradicts some other API calls). | 224477 or 224-477 |
| <code>order_date</code>      | YES      | <i>string</i>  | The date of order creation in yyyy-mm-dd format. Time is additional.                                                                    | 2019-07-24 11:11  |
| <code>pickup_location</code> | YES      | <i>string</i>  | The name of the pickup location added in your Shiprocket account. This cannot be a new location.                                        | Jammu             |
| <code>channel_id</code>      | NO       | <i>integer</i> | Mention this in case you need to                                                                                                        | 27022             |

## HEADERS

## Content-Type

```
application/json
```

**Body** raw

```
{
  "order_id": "",
  "order_date": "",
  "pickup_location": "",
  "channel_id": "",
  "comment": "",
  "reseller_name": "",
  "company_name": "",
  "billing_customer_name": "",
  "billing_last_name": "",
  "billing_address": "",
  "billing_city": "",
  "billing_state": "",
  "billing_zip": ""
}
```

```

"billing_address_2": "",
"billing_isd_code": "",
"billing_city": "",

"billing_pincode": "",
"billing_state": "",
"billing_country": "",
"billing_email": "",
"billing_phone": "",
"billing_alternate_phone": "",
"shipping_is_billing": "",
"shipping_customer_name": "",
"shipping_last_name": "",
"shipping_address": "",
"shipping_address_2": "",
"shipping_city": "",
"shipping_pincode": "",
"shipping_country": "",
"shipping_state": "",
"shipping_email": "",
"shipping_phone": "",
"order_items": [
    {
        "name": "",
        "sku": "",
        "units": "",
        "selling_price": "",
        "discount": "",
        "tax": "",
        "hsn": ""
    }
],
"payment_method": "",
"shipping_charges": "",
"giftwrap_charges": "",
"transaction_charges": "",
"total_discount": "",
"sub_total": "",
"length": "",
"breadth": "",
"height": "",
"weight": "",
"ewaybill_no": "",
"customer_gstin": "",
"invoice_number": "",
"order_type": ""
}

```

## GET Get all Orders

<https://apiv2.shiprocket.in/v1/external/orders>

This API call will display a list of all created and available orders in your Shiprocket account. The product and shipment

details are displayed as sub-arrays within each order detail.

You can also sort and filter the data according to your needs by passing the optional parameters. Not passing anything will display the data in the default format.

You can also fetch the data based on the order update date. PFB the validations:

Plain Text

1. if updated\_to => passed and updated\_from not passed =>, error will come => Please send update

2. if updated\_from => passed and updated\_to => paased => and from-to > 30 then error => Difference

3. if updated\_From < 30 then error => Updated\_from date should not be less than 30 days from c

Parameters:

| PARAMS    | REQUIRED | DATA TYPE | DESCRIPTION                                     | EXAMPLE                                                    |
|-----------|----------|-----------|-------------------------------------------------|------------------------------------------------------------|
| page      | NO       | integer   | The page number to display.                     | 5                                                          |
| per_page  | NO       | integer   | The number of entries per page.                 | 5                                                          |
| sort      | NO       | string    | Sort conditions: ASC or DESC                    | ASC                                                        |
| sort_by   | NO       | string    | The Field to sort by: id or status              | id                                                         |
| to        | NO       | string    | The end date.                                   | 2018-07-24                                                 |
| from      | NO       | string    | The start date.                                 | 2019-07-24                                                 |
| filter_by | NO       | string    | Field to filter by.                             | status, payment_method, delivery_country, channel_order_id |
| filter    | NO       | string    | Value of the field                              |                                                            |
| search    | NO       | string    | Search for AWB or by Channel order id (order id | 224477                                                     |

HEADERS

Content-Typeapplication/json

Authorization

<https://apiv2.shiprocket.in/v1/external/orders/show>

Get the order and shipment details of a particular order through this API by passing the Shiprocket order\_id in the endpoint URL itself — type in your order\_id in place of {id}.

No other body parameters are required.

**Note:**

For SRF orders, you'll receive an extra parameter viz., fulfillment\_status. This key will have four values:

- Ready to Pack,
- Packed
- Added to Picklist
- Picked up

**Path:**

**EXAMPLE**

<https://apiv2.shiprocket.in/v1/external/orders/show/16167171>

## HEADERS

---

|                     |                  |
|---------------------|------------------|
| <b>Content-Type</b> | application/json |
|---------------------|------------------|

|                      |                |
|----------------------|----------------|
| <b>Authorization</b> | Bearer {token} |
|----------------------|----------------|

## POST Export your orders

<https://apiv2.shiprocket.in/v1/external/orders/export>

This API downloads and creates a CSV file of all the orders in your Shiprocket account and sends the download URL to the linked email account of the API user.

The CSV file containing is accessible via this URL. No parameters are required to access this API.

## HEADERS

---

|                     |                  |
|---------------------|------------------|
| <b>Content-Type</b> | application/json |
|---------------------|------------------|

```
{  
  
}
```

## Couriers

Use these APIs to assign AWB to your order, check for courier serviceability, and request for the pickup of your order.

### POST Generate AWB for Shipment

https://apiv2.shiprocket.in/v1/external/courier/assign/awb

This API can be used to assign the AWB (Air Waybill Number) to your shipment. The AWB is a unique number that helps you track the shipment and get details about it.

Parameters:

| PARAMS      | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                           | EXAMPLE  |
|-------------|----------|-----------|-----------------------------------------------------------------------------------------------------------------------|----------|
| shipment_id | YES      | integer   | The shipment id of the order you want to create the AWB for.                                                          | 16016920 |
| courier_id  | NO       | integer   | The courier id of the courier service you want to select. The default courier is selected in case no id is specified. | 10       |
| status      | NO       | string    | Use this to change the courier of a shipment. Value: reassign. Note that this can be done only once in 24 hours.      | reassign |

HEADERS

## HEADERS

---

**Content-Type** application/json

**Body** raw

---

```
{
  "shipment_id": "",
  "courier_id": "",
  "status": ""
}
```

---

## GET Check Courier Serviceability

<https://apiv2.shiprocket.in/v1/external/courier/serviceability/>

Use this API to check the availability of couriers between the pickup and delivery postal codes. Further details like the estimated time of delivery, the rates along with the ids are also shown.

### Note:

- One of either the 'order\_id' or 'cod' and 'weight' is required. If you specify the order id, the cod and weight fields are not required and vice versa.
- You can add further fields to add the shipment details and filter the search.

### Parameters:

| PARAMS                         | REQUIRED           | DATA TYPE      | DESCRIPTION                                                                                                   | EXAMPLE         |
|--------------------------------|--------------------|----------------|---------------------------------------------------------------------------------------------------------------|-----------------|
| <code>pickup_postcode</code>   | YES                | <i>integer</i> | Postcode from where the order will be picked.                                                                 | 110030          |
| <code>delivery_postcode</code> | YES                | <i>integer</i> | Postcode where the order will be delivered                                                                    | 122002          |
| <code>order_id</code>          | NO                 | <i>integer</i> | If order id is already created in Shiprocket panel then you can use this shiprocket order id in servicibility | 123456          |
| <code>cod</code>               | CONDITIONAL<br>YES | <i>boolean</i> | 1 for Cash on Delivery and 0 for Prepaid orders.                                                              | 1               |
| <code>is_new_hyperlocal</code> | YES                | <i>boolean</i> | 1 in case of hyper-local shipments                                                                            | 1               |
| <code>lat_from</code>          | YES                | <i>float</i>   | Pickup Latitude. Mandatory in case                                                                            | 28.509223937988 |

## HEADERS

**Content-Type**                      application/json

# Tracking

Use these APIs to get the tracking details of your shipments through the AWB code or the Shipment ID.

**Shipment Status Codes:**

| STATUS CODE | DESCRIPTION            |
|-------------|------------------------|
| 6           | Shipped                |
| 7           | Delivered              |
| 8           | Canceled               |
| 9           | RTO Initiated          |
| 10          | RTO Delivered          |
| 12          | Lost                   |
| 13          | Pickup Error           |
| 14          | RTO Acknowledged       |
| 15          | Pickup Rescheduled     |
| 16          | Cancellation Requested |
| 17          | Out For Delivery       |
| 18          | In Transit             |
| 19          | Out For Pickup         |
| 20          | Pickup Exception       |

## GET Get Tracking through AWB

`https://apiv2.shiprocket.in/v1/external/courier/track/awb/{awb_code}`

Get the tracking details of your shipment by entering the AWB code of the same in the endpoint URL itself. No other body parameters are required to access this API.

The response is displayed in JSON format.

### Path:

#### EXAMPLE

`https://apiv2.shiprocket.in/v1/external/courier/track/awb/788830567028`

### HEADERS

Content-Type

application/json

## POST Get Tracking Data for Multiple AWBS

https://apiv2.shiprocket.in/v1/external/courier/track/awbs

Get the tracking details of multiple shipments by entering their AWB codes together as an array.

The response is displayed in JSON format.

**Notes:**

- Data must be passed as a string array.
- Maximum of 50 AWB codes is supported at a time.

**Parameters:**

| PARAMS          | REQUIRED | DATA TYPE | DESCRIPTION                                                    | EXAMPLE                             |
|-----------------|----------|-----------|----------------------------------------------------------------|-------------------------------------|
| <div>awbs</div> | YES      | string    | The AWB codes of the shipments.<br>Must be passed as an array. | ["788830567028",<br>"788829354408"] |

### HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "awbs": ["", ""]
}
```

## GET Get Tracking through Shipment ID

https://apiv2.shiprocket.in/v1/external/courier/track/shipment/{shipment\_id}

Get the tracking details of your shipment by entering the shipment\_id of the same in the endpoint URL. No other body parameters are required to access this API.

The response is displayed in JSON format.

#### Path:

##### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/courier/track/shipment/16104408>

#### HEADERS

Content-Type

application/json

## GET Get Tracking Data through Order ID

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

Get the tracking details of your shipment by entering the Order ID of the same in the endpoint URL itself. If you have the same order ID in more than one channel, then use the param channel\_id.

The response is displayed in JSON format.

#### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                           | EXAMPLE |
|-------------------------|----------|----------------|---------------------------------------|---------|
| <code>order_id</code>   | YES      | <i>string</i>  | The order ID/number of your store.    | NO-123  |
| <code>channel_id</code> | NO       | <i>integer</i> | Channel ID corresponding to the store | 12345   |

#### Path:

##### EXAMPLE

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

#### HEADERS

Authorization

Bearer {token}

#### PARAMS

order\_id

123

channel\_id

12345

---

## Pickup Addresses

Use these APIs to get a list of all available pickup locations in your account or add a new pickup location.

---

### **GET** Get All Pickup Locations

`https://apiv2.shiprocket.in/v1/external/settings/company/pickup`

Get a list of all pickup locations that have been added to your Shiprocket account through this API.

No parameters are required to use this API.

---

### **POST** Add a New Pickup Location

`https://apiv2.shiprocket.in/v1/external/settings/company/addpickup`

This API can be used to add a new pickup location to your account.

Pass the minimum required parameters to add the location.

Further details to the address can be added if required.

**Parameters:**

| PARAMS                       | REQUIRED | DATA TYPE      | DESCRIPTION                                                 | EXAMPLE                   |
|------------------------------|----------|----------------|-------------------------------------------------------------|---------------------------|
| <code>pickup_location</code> | YES      | <i>string</i>  | The nickname of the new pickup location. Max 36 characters. | Home                      |
| <code>name</code>            | YES      | <i>string</i>  | The shipper's name.                                         | Deadpool                  |
| <code>email</code>           | YES      | <i>string</i>  | The shipper's email address.                                | deadpool@chimichanga.com  |
| <code>phone</code>           | YES      | <i>integer</i> | Shipper's phone number.                                     | 9777777779                |
| <code>address</code>         | YES      | <i>string</i>  | Shipper's primary address. Max 80 characters.               | Mutant Facility, Sector 3 |
| <code>address_2</code>       | NO       | <i>string</i>  | Additional address details.                                 | House number 34           |
| <code>city</code>            | YES      | <i>string</i>  | Pickup location city name.                                  | Pune                      |
| <code>state</code>           | YES      | <i>string</i>  | Pickup location state name                                  | Maharashtra               |

## HEADERS

**Content-Type** application/json

**Body** raw

```
{
  "pickup_location": "",
  "name": "",
  "email": "",
  "phone": "",
  "address": "",
  "address_2": "",
  "city": "",
  "state": "",
  "country": "",
  "pin_code": ""
}
```

---

# International

These endpoints are used for operations related to international orders and shipments.

---

## Tracking

Use these APIs to get the tracking details of your shipments through the AWB code or the Shipment ID.

---

### GET Get Tracking through AWB

`https://apiv2.shiprocket.in/v1/external/courier/track/awb/{awb_code}`

Get the tracking details of your shipment by entering the AWB code of the same in the endpoint URL itself. No other body parameters are required to access this API.

The response is displayed in JSON format.

**Path:**

| EXAMPLE                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="https://apiv2.shiprocket.in/v1/external/courier/track/awb/788830567028">https://apiv2.shiprocket.in/v1/external/courier/track/awb/788830567028</a> |

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

### GET Get Tracking through Shipment ID

`https://apiv2.shiprocket.in/v1/external/courier/track/shipment/{shipment_id}`

Get the tracking details of your shipment by entering the shipment\_id of the same in the endpoint URL. No other body parameters are required to access this API.

The response is displayed in JSON format.

**Path:**

#### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/courier/track/shipment/16104408>

## HEADERS

**Content-Type** application/json

## GET Get Tracking Data through Order id

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

Get the tracking details of your shipment by entering the Order ID of the same in the endpoint URL itself. If you have the same order ID in more than one channel, then use the param channel\_id.

The response is displayed in JSON format.

### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                           | EXAMPLE |
|-------------------------|----------|----------------|---------------------------------------|---------|
| <code>order_id</code>   | YES      | <i>string</i>  | The order ID/number of your store.    | NO-123  |
| <code>channel_id</code> | NO       | <i>integer</i> | Channel ID corresponding to the store | 12345   |

### Path:

#### EXAMPLE

[https://apiv2.shiprocket.in/v1/external/courier/track?order\\_id=123&channel\\_id=12345](https://apiv2.shiprocket.in/v1/external/courier/track?order_id=123&channel_id=12345)

## HEADERS

**Authorization** Bearer {token}

## PARAMS

order\_id123

channel\_id12345

GETTracking

🔒

https://apiv2.shiprocket.in/v1/external/international/orders/track

Get the tracking details of your shipments. No other body parameters are required to access this API.

AUTHORIZATIONBearer Token

Token

<token>

POSTInternational KYC

🔒

https://apiv2.shiprocket.in/v1/external/international/settings/international\_kyc

Use this API for your international KYC. This API return your KYC status.  
Please check the documentation for the documents for KYC.

| PARAMS            | REQUIRED DATA | DATA TYPE    | DESCRIPTION                                                                 | EXAMPLE              |
|-------------------|---------------|--------------|-----------------------------------------------------------------------------|----------------------|
| organization_type | Yes           | string       | Seller organization                                                         | company              |
| ip_address        | Yes           | int unsigned | Seller's ip_address                                                         | 192.168.1.1.0        |
| documents         | Yes           | array        | Documentaion for organization type (document size is not greater than 3 MB) | Please check request |

AUTHORIZATIONBearer Token

Token

<token>

Bodyraw (json)

json

```
{
  "organization_type": "Sole Proprietor",
  "ip_address": "35.207.230.249",
  "documents": [
    {
      "attachment": [
        {
          "file": "/9j/4AAQSkZJRgABAQAAQABAAD//gA8Q1JFQVRPUjogZ2QtanBlZyB2MS4wICCh1c3
          "extension": "pdf"
        }
      ],
      "document_name": "iec_code",
      "document_value": "0514039752"
    },
    {
      "attachment": [
        {
          "file": "/9j/4AAQSkZJRgABAQAAQABAAD//gA8Q1JFQVRPUjogZ2QtanBlZyB2MS4wICCh1c3
          "extension": "pdf"
        }
      ],
      "document_name": "ad_code",
      "document_value": "63919662900009"
    },
    {
      "attachment": [
        {
          "file": "/9j/4AAQSkZJRgABAQAAQABAAD//gA8Q1JFQVRPUjogZ2QtanBlZyB2MS4wICCh1c3
          "extension": "pdf"
        }
      ],
      "document_name": "gst_certificate",
      "document_value": "07AESP5142H1ZE"
    },
    {
      "attachment": [
        {
          "file": "/9j/4AAQSkZJRgABAQAAQABAAD//gA8Q1JFQVRPUjogZ2QtanBlZyB2MS4wICCh1c3
          "extension": "pdf"
        }
      ],
      "document_name": "pan_card",
      "document_value": "AESP5142H"
    },
    {
      "attachment": [
        {
          "file": "/9j/4AAQSkZJRgABAQAAQABAAD//gA8Q1JFQVRPUjogZ2QtanBlZyB2MS4wICCh1c3
          "extension": "pdf"
        }
      ],
      "document_name": "aadhar_card",
      "document_value": "613168861273"
    }
  ]
}
```

]

}

## POST Add Bank Details



https://apiv2.shiprocket.in/v1/external/international/settings/add-bank-details

This documentation provides information about the Bank Details API, which allows you to add bank details for international settings. The API endpoint, parameters, request sample data, success response, and failed response are outlined below.

| PARAMS              | REQUIRED | DATA TYPE | DESCRIPTION                                              | EXAMPLE       |
|---------------------|----------|-----------|----------------------------------------------------------|---------------|
| bank_account_type   | YES      | string    | Bank account type. Must be either "saving" or "current". | "saving"      |
| beneficiary_name    | YES      | string    | Beneficiary name. Alphabets and spaces only.             | "JohnDoe"     |
| bank_ifsc_code      | YES      | string    | Bank IFSC code. Must follow a specific pattern.          | "ABCD0123456" |
| bank_account_number | YES      | integer   | Bank account number. Should be between 9 and 18 digits.  | 1234567890    |

### AUTHORIZATION Bearer Token

Token <token>

### HEADERS

Content-Type application/json

Body raw

```
{  
  "bank_account_type": "saving",  
  "beneficiary_name": "JohnDoe",  
  "bank_ifsc_code": "ABCD0123456",  
  "bank_account_number": "1234567890"  
}
```

## POST Create order



<https://apiv2.shiprocket.in/v1/external/international/orders/create/adhoc>

Use this API to create a quick custom order. Quick orders are the ones where we do not store the product details in the master catalogue.

You have to pass all the required params at the minimum to create a quick custom order. You can add additional parameters as per your preference.

### Note:

- In case the 'shipping\_is\_billing' field is false, further shipping detail fields are required.

If no channel id is passed, the order will be assigned to the default custom channel. If the channel id is not known, use the 'Get All Channels' API to get the list of all integrated channels in your Shiprocket account.

- order\_id field cannot be equal to an already existing id. Doing so does not change or affect the existing order.
- New orders cannot be created with order id's same as that of cancelled orders. If error 422 shows up despite filling in the correct details, consider changing the order\_id.
- Be sure to input the correct calculated sub\_total amount. The total is not calculated automatically through the API.
- The 'order\_id' returned in the response is the Shiprocket order\_id. Please save this order ID as we will use this in future API calls.

### Parameters:



```
"billing_pincode":"134113",
"landmark":"",
"shipping_is_billing":1,

"shipping_customer_name":"Elena ",
"shipping_last_name":"",
"shipping_address":"Plot No. 348, Panchkula, 134113, India",
"shipping_address_2":"",
"shipping_city":"Dallas",
"order_type":1,
"shipping_country":"United States",
"shipping_pincode":"134090",
"shipping_state":"Texas",
"shipping_email":"test.test@shiprocket.com",
"product_category":"",
"shipping_phone":9762343722,
"billing_alternate_phone":"",
"order_items":[
  {
    "name":"Combo of 4 Way Spanner and Hydraulic trolly Jack",
    "sku":"5-47606",
    "category_name":"Default Category",
    "tax":"",
    "hsn":"",
    "units":"1",
    "selling_price":"100",
    "discount":"",
    "category_id":"",
    "caetgroy_code":""
  }
],
"payment_method":"Prepaid",
"shipping_charges":0,
"giftwrap_charges":0,
"transaction_charges":0,
"total_discount":0,
"sub_total":100,
"weight":0.41,
"length":10,
"breadth":10,
"height":10,
"pickup_location_id":255,
"reseller_name":"",
"company_name":"",
"ewaybill_no":"",
"customer_gstin":"",
"is_order_revamp":1,
"is_document":0,
"delivery_challan":false,
"order_tag":"",
"purpose_of_shipment":0,
"currency":"USD",
"reasonOfExport":2,
"commodity":"true",
"bies":"true",
"igstPaymentStatus":"C",
"Terms_Of_Invoice":"FOB",
"is insurance opt":false
```

```
}
```

## POST Update order



<https://apiv2.shiprocket.in/v1/external/international/orders/update/adhoc>

Use this API to update your orders. You have to pass all the required params at the minimum to create a quick custom order. You can add additional parameters as per your preference.

You can update only the order\_items details before assigning the AWB (before Ready to Ship status). You can only update these key-value pairs i.e increase/decrease the quantity, update tax/discount, add/remove product items. Some params specific to international order are.

| PARAMS              | REQUIRED | DATA TYPE | DESCRIPTION                                                                                              | EXAMPLE |
|---------------------|----------|-----------|----------------------------------------------------------------------------------------------------------|---------|
| purpose_of_shipment | NO       | integer   | The purpose of the shipment. values are 0 - gift, 1- sample, commercial - 2.                             | 1       |
| currency            | YES      | string    | The currency of the order. Possible values are INR,USD,GBP, EUR, AUD, CAD, SAR, AED,SGD                  | USD     |
| reasonOfExport      | No       | integer   | The reason for the export. Possible values are 0 - BONAFIDE_SAMPLE, 1 - SAMPLE, 2 - GIFT, 3 - COMMERCIAL | 2       |
| commodity           | NO       | boolean   | Indicates if the order is a commodity or not                                                             | true    |

### AUTHORIZATION Bearer Token

**Token** <token>

**Body** raw (json)

icon

```
json
{
  "order_id":1726470481,
  "isd_code":"+1",
  "billing_isd_code":"",
  "order_date":"2022-03-30T00:34:12.311Z",
  "channel_id":2252386,
  "billing_customer_name":"Elena ",
  "billing_last_name":"",
  "billing_address":"Plot No. 348, 134113, India",
  "billing_address_2":"",
  "billing_city":"Panchkula",
  "billing_state":"Haryana",
  "billing_country":"India",
  "billing_pincode":"134113",
  "billing_email":"test.test@shiprocket.com",
  "billing_phone":9760858933,
  "landmark":"",
  "shipping_is_billing":1,
  "shipping_customer_name":"Elena ",
  "shipping_last_name":"",
  "shipping_address":"Plot 1, Panchkula, Haryana 134113, India",
  "shipping_address_2":"",
  "shipping_city":"Dallas",
  "order_type":1,
  "shipping_country":"United States",
  "shipping_pincode":"134090",
  "shipping_state":"Texas",
  "shipping_email":"test.test@shiprocket.com",
  "product_category":"",
  "shipping_phone":9760853722,
  "billing_alternate_phone":"",
  "order_items":[
    {
      "name":"Combo of 4 Way Spanner and Hydraulic trolly Jack",
      "sku":"5-47606",
      "category_name":"Default Category",
      "tax":"",
      "hsn":"",
      "units":"1",
      "selling_price":"100",
      "discount":"",
      "category_id":"",
      "caetgroy_code":""
    }
  ],
  "payment_method":"Prepaid",
  "shipping_charges":0,
  "giftwrap_charges":0,
  "transaction_charges":0,
  "total_discount":0,
  "sub_total":100,
  "weight":0.51,
  "length":20,
  "breadth":20
```

```
        "height":20,  
        "pickup_location_id":255,  
        "reseller_name":"","  
        "company_name":"","  
        "ewaybill_no":"","  
        "customer_gstin":"","  
        "is_order_revamp":1,  
        "is_document":0,  
        "delivery_challan":false,  
        "order_tag":"","  
        "purpose_of_shipment":0,  
        "currency":"EUR",  
        "reasonOfExport":2,  
        "commodity":"true",  
        "mies":"true",  
        "igstPaymentStatus":"C",  
        "Terms_Of_Invoice":"FOB",  
        "is_insurance_opt":false  
    }  
}
```

## POST International Wrapper API



<https://apiv2.shiprocket.in/v1/external/international/shipments/create/forward-shipment>

Use this API to do multiple tasks in one go, namely creating a quick order, requesting its shipment, pickup generation generating the label and the manifest for the same order.

This API integrates several other APIs to perform all these tasks together.

### AUTHORIZATION Bearer Token

Token <token>

### HEADERS

Content-Type application/json

### Body raw

```
{  
    "order_id": "320988727",  
    "order_date": "2022-05-08 12:23",  
    "channel_id": "",  
    "billing_customer_name": "Jax",  
    "billing_last_name": "Tank",  
}
```

```
"billing_address": "Dust2",
"billing_city": "New Delhi",
"billing_pincode": "442001",

"billing_state": "Delhi",
"billing_country": "India",
"billing_email": "jax@counterstike.com",
"billing_phone": "9988998899",
"shipping_is_billing": false,
"shipping_customer_name": "Elena ",
"shipping_last_name": "",
"shipping_address": "Plot 1, Panchkula, Haryana 134113, India",
"shipping_address_2": "",
"shipping_city": "UPTON",
"order_type": 1,
"shipping_country": "United States",
"shipping_pincode": "11973",
"shipping_state": "New York",
"shipping_email": "test.test@shiprocket.com",
"product_category": "",
"shipping_phone": 9760853722,
"order_items": [
  {
    "name": "Delta",
    "sku": "delta123",
    "units": 10,
    "selling_price": "1000",
    "hsn": "24567870"
  }
],
"payment_method": "PREPAID",
"sub_total": 40,
"length": 10,
"breadth": 10,
"height": 10,
"weight": 0.7,
"pickup_location": "rtryttest",
"vendor_details": {
  "email": "mayur.p@iksula.com",
  "phone": 9879879879,
  "name": "Coco Cookie",
  "address": "F2004 Street Street 1 Street ",
  "address_2": "",
  "city": "delhi",
  "state": "new delhi",
  "country": "india",
  "pin_code": "442001",
  "pickup_location": "rtryttest"
},
"purpose_of_shipment": 0,
"currency": "INR",
"igstPaymentStatus": "A",
"Terms_Of_Invoice": "FOB",
"igst_amount": 10,
"ioss": "IM1234567890",
"pickup_location_id": 647
```

```
}
```

## GET Serviceability



[https://apiv2.shiprocket.in/v1/external/international/courier/serviceability?order\\_id=247825513](https://apiv2.shiprocket.in/v1/external/international/courier/serviceability?order_id=247825513)

This API checks courier serviceability for international orders and displays them as a list.

### Notes:

- 'cod' field must be 0 as COD is not available for international orders.

### Parameters:

| PARAMS           | REQUIRED | DATA TYPE | DESCRIPTION                                                                                 | EXAMPLE |
|------------------|----------|-----------|---------------------------------------------------------------------------------------------|---------|
| weight           | YES      | integer   | The weight of the shipment.                                                                 | 10      |
| cod              | YES      | integer   | Cash on delivery status. Must be 0.                                                         | 0       |
| delivery_country | YES      | string    | The destination country ISO Alpha 2 code.                                                   | US      |
| order_id         | NO       | integer   | The Shiprocket order_id of the shipment if available.                                       | 1       |
| pickup_postcode  | NO       | integer   | Use this field to select a different pickup postcode other than the primary pickup address. | 2       |

## AUTHORIZATION Bearer Token

Token <token>

### PARAMS

order\_id 247825513

## POST AWB Assignment

<https://apiv2.shiprocket.in/v1/external/international/courier/assign/awb>

This API can be used to assign the AWB (Air Waybill Number) to your shipment. The AWB is a unique number that helps you track the shipment and get details about it.

| PARAMS      | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                           | EXAMPLE  |
|-------------|----------|-----------|-----------------------------------------------------------------------------------------------------------------------|----------|
| shipment_id | yes      | integer   | The shipment id of the order you want to create the AWB for.                                                          | 1603434  |
| courier_id  | no       | integer   | The courier id of the courier service you want to select. The default courier is selected in case no id is specified. | 35       |
| status      | no       | string    | Use this to change the courier of a shipment. Value: reassign. Note that this can be done only once in 24 hours.      | reassign |
|             |          |           |                                                                                                                       |          |

## HEADERS

**accept** application/json

**Body** raw (json)

json

```
{
  "shipment_id": 160169474,
  "courier_id": 332,
  "status": "reassign"
}
```

## POST Manifest Generation

<https://apiv2.shiprocket.in/v1/external/international/manifests/generate>

Use this API to create a pickup request for your order shipment. The API returns the pickup status along with the estimated pickup time.

You will have to call the 'Generate Manifest' API after the successful response of this API.

### Note:

- The AWB must be already generated for the shipment id to generate the pickup request.
- Only one shipment\_id can be passed at a time.

| PARAMS      | REQUIRED | DATA TYPE | DESCRIPTION                                                          | EXAMPLE |
|-------------|----------|-----------|----------------------------------------------------------------------|---------|
| shipment_id | yes      | integer   | The shipment id of the shipment which is requested for pickup.       | 1603434 |
| status      | no       | string    | Use this field to retry if the pickup request fails.<br>Value: retry | retry   |

### Body raw (json)

json

```
{
  "shipment_id": [12345]
}
```

## POST Generate Pickup



<https://apiv2.shiprocket.in/v1/external/courier/generate/pickup>

Use this API to create a pickup request for your order shipment. The API returns the pickup status along with the estimated pickup time.

You will have to call the 'Generate Manifest' API after the successful response of this API.

**Note:**

- The AWB must be already generated for the shipment id to generate the pickup request.
- Only one shipment\_id can be passed at a time.

| PARAMS      | REQUIRED | DATA TYPE | DESCRIPTION                                                          | EXAMPLE |
|-------------|----------|-----------|----------------------------------------------------------------------|---------|
| shipment_id | yes      | integer   | The shipment id of the shipment which is requested for pickup.       | 1603434 |
| status      | no       | string    | Use this field to retry if the pickup request fails.<br>Value: retry | retry   |

**AUTHORIZATION** Bearer Token

Token <token>

**HEADERS**

accept application/json

**Body** raw (json)

```
json

{
  "shipment_id": [12847483]
}
```

## Account

**GET** Get Wallet Balance

<https://apiv2.shiprocket.in/v1/external/account/details/wallet-balance>

Use this API to get the Wallet balance details of your Shiprocket account. No parameters are required to access this API.

## HEADERS

|                     |                  |
|---------------------|------------------|
| <b>Content-Type</b> | application/json |
|---------------------|------------------|

## Products

Use these APIs to get information on your added products or update their details. You can also add a new product or import them in bulk.

**GET** Get All Products

<https://apiv2.shiprocket.in/v1/external/products>

This API can be used to display a detailed list of all the products that you have in your Shiprocket account.

There are no required parameters to access this API. However, the displayed result can be filtered or sorted using additional parameters.

### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                              | EXAMPLE  |
|----------|----------|-----------|--------------------------------------------------------------------------------------------------------------------------|----------|
| page     | NO       | integer   | The page number you want to display.                                                                                     | 5        |
| per_page | NO       | integer   | The number of products to get per page.                                                                                  | 2        |
| sort     | NO       | string    | The order to sort by. Value: ASC or DESC                                                                                 | ASC      |
| sort_by  | NO       | string    | Allows you to choose the value field by which the items will be sorted. Could be sorted by id, by sku, time created etc. | sku      |
| filter   | NO       | string    | The data to be                                                                                                           | 11223344 |

|       |    |        |                                              |         |
|-------|----|--------|----------------------------------------------|---------|
| 11101 | NO | string | The data to be matched for the filter value. | 1122047 |
|-------|----|--------|----------------------------------------------|---------|

## HEADERS

**Content-Type** application/json

## GET Get Specific Product Details

`https://apiv2.shiprocket.in/v1/external/products/show/{product_id}`

Use this API to get the details of a specific product. The product details will be displayed in JSON format.

You need to pass the product id in the endpoint URL for the successful call of the API. No other body parameters are required.

### Path:

#### EXAMPLE

`https://apiv2.shiprocket.in/v1/external/products/show/17484610`

## HEADERS

**Content-Type** application/json

## POST Add New Products

`https://apiv2.shiprocket.in/v1/external/products`

Use this API to add a new product to your Shiprocket account.

Provide the required product details and any additional info to successfully add a new product to your product list.

### Notes:

- 'sku' Id has to be unique. It cannot be the same as an existing sku.
- In case no category code is added, the code should be default.
- 'type' field should be either 'single' or 'multiple.'

### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                                                                       | EXAMPLE    |
|----------|----------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| sku      | YES      | string    | Stock Keeping Unit or the identification unit of an individual product (generally alphanumeric).                                                                  | bat123     |
| HSN      | NO       | string    | Harmonised System Nomenclature. A code number is used to classify goods for taxation purposes. Done to determine which category of taxes do the goods come under. | 4412       |
| name     | YES      | string    | Name of the product.                                                                                                                                              | Batman Toy |
| tax_code | NO       | string    | The percentage of tax that is to be                                                                                                                               | 10         |

HEADERS

Content-Typeapplication/json

Body raw

```
{
  "name": "Batman451",
  "category_code": "default",
  "type": "Single",
  "qty": "10",
  "sku": "b118771212",
  "qc_details": {
    "product_image": "https://kr-multichannel-stage.s3.ap-south-1.amazonaws.com/1310/qc_pro",
    "brand": "redlabel",
    "color": "white",
    "size": "L",
    "product_imei": "",
    "serial_no": "790878",
    "ean_barcode": "",
  }
}
```

```
    "check_damaged_product": true
  }
```

## POST Convert to QC Product

<https://apiv2.shiprocket.in/v1/external/products/qc-product-update/{productID}>

Use this API to convert an existing product to a QC product. The {productID} will be the "id" from the "Get all products" or "Get specific product details" API.

### Parameters:

| PARAMS                     | REQUIRED | DATA TYPE     | DESCRIPTION                                                                                                                       | EXAMPLE                                               |
|----------------------------|----------|---------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| <code>sku</code>           | YES      | <i>string</i> | Stock Keeping Unit or the identification unit of an individual product (generally alphanumeric).                                  | bat123                                                |
| <code>product_image</code> | YES      | <i>string</i> | Pickup agent will cross check shared product color with the actual product received from the buyer. Mandatory for all QC Products | <a href="https://abc/xyz.jpg">https://abc/xyz.jpg</a> |
| <code>serial_no</code>     | NO       | <i>string</i> | A serial number (SN) is a unique alphanumeric value assigned to each individual product.                                          | 12345                                                 |

### HEADERS

**Content-Type** `application/json`

**Body** raw (json)

json

```
{
  "sku": "PROD12345",
  "product_image": "https://kr-multichannel.s3.ap-southeast-1.amazonaws.com/2/products/images/",
  "brand_box": "12323chacha",
  "brand": "blue",
  "color": "Red",
  "size": "M",
  "serial_no": "",
  "check_damaged_product": 0
}
```

---

## POST Bulk Import Products

<https://apiv2.shiprocket.in/v1/external/products/import>

Use this API to import your products in bulk from a .csv file.

No parameters are required. Choose the target file as required. You will receive an import id upon successful import operation.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

Body formdata

---

file

---

## GET Get Sample .csv Format

<https://apiv2.shiprocket.in/v1/external/products/sample>

This API will provide a sample format for a CSV file that can be used for importing orders. You can use this format to create your CSV file, which you want to use to import products into your Shiprocket account.

No additional parameters are required.

## HEADERS

## Content-Type

```
application/json
```

# Listings

**GET** Get All Listings

<https://apiv2.shiprocket.in/v1/external/listings>

This API can be used to get a JSON representation of all the product listings in your Shiprocket account, i.e., all the products associated with a specific channel.

No parameters are required to access this API. However, the displayed data can be filtered and sorted using further parameters. If no sort parameter is used, the data is displayed in the default format.

### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                                 | EXAMPLE  |
|----------|----------|-----------|-----------------------------------------------------------------------------------------------------------------------------|----------|
| page     | NO       | integer   | The page number you want to display.                                                                                        | 5        |
| per_page | NO       | integer   | The number of listings to get per page.                                                                                     | 2        |
| sort     | NO       | string    | The order to sort by. Value: <b>ASC</b> or <b>DESC</b>                                                                      | ASC      |
| sort_by  | NO       | string    | Allows you to choose the value field by which the listings will be sorted. Could be sorted by id, by sku, time created etc. | sku      |
| filter   | NO       | string    | The data to be matched for the filter value.                                                                                | 11223344 |

## HEADERS

Content-Type

application/json

## POST Map Channel Product

<https://apiv2.shiprocket.in/v1/external/listings/link>

Use this API to map a product present in the channel catalogue to a product present in the master catalogue.

Pass the product and listing id for the successful call of the API

### Parameters:

| PARAMS                  | REQUIRED | DATA TYPE      | DESCRIPTION                                   | EXAMPLE  |
|-------------------------|----------|----------------|-----------------------------------------------|----------|
| <code>product_id</code> | YES      | <i>integer</i> | The id of item in the master catalog.         | 17908342 |
| <code>listing_id</code> | YES      | <i>integer</i> | The id of the product in the channel catalog. | 15897064 |
| <code>ID</code>         | NO       | <i>integer</i> | The id placed in the respective 'GET' codes.  | 15897064 |

### HEADERS

Content-Type

application/json

### Body raw

```
{
  "product_id": "",
  "listing_id": "",
  "ID": ""
}
```

## POST Import Catalog Mappings

<https://apiv2.shiprocket.in/v1/external/listings/import>

Use this API to import a CSV file containing channel catalogue to the master catalogue mappings.

No other body parameters are required.

**Body** formdata

---

file

---

## GET Export Mapped Products

<https://apiv2.shiprocket.in/v1/external/listings/export/mapped>

This API downloads the list of mapped items in your channel catalogue sheet. After mapping the items, you can see the number of products in one channel present in the Master Catalogue.

The downloaded CSV file URL is shared as the response. No other body parameters are required.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## GET Export Unmapped Products

<https://apiv2.shiprocket.in/v1/external/listings/export/unmapped>

Get a list of all the unmapped products in your channel catalogue using this API.

The list is downloaded into a CSV file, and the download URL is displayed as the response. No other body parameters are required.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## GET Export Catalog Sample

<https://apiv2.shiprocket.in/v1/external/listings/sample>

This API displays the download link of a sample catalogue sheet for reference purposes.

No additional parameters are required.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## Channels

Use this API to get details about all the integrated channels in your Shiprocket account, including channel id. This channel id can be used to select or specify a custom channel at the time of order creation.

---

## GET Get Integrated Channel Details

<https://apiv2.shiprocket.in/v1/external/channels>

This API shows a list of all the channels that have already been integrated with your Shiprocket account.

No parameters are required to access this API.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## POST Create Custom Channel

<https://apiv2.shiprocket.in/v1/external/channels>

Creates a new manual (custom) channel in the seller's Shiprocket account.

**Pre-condition:** This endpoint is gated. Your account must be allow-listed for "Channel Creation by API" by the Shiprocket Tech Support / KAM team before it will work.

## Request body

| Field      | Type   | Required | Description                                                                |
|------------|--------|----------|----------------------------------------------------------------------------|
| name       | string | Yes      | Channel display name.<br>Max 12 characters.<br>Unique within your account. |
| brand_name | string | No       | Brand label on invoices and shipping labels.<br>Max 50 characters.         |

## Error responses

- **401 Unauthorized** — Missing or invalid bearer token.
- **403 Forbidden** — "Channel Creation by API" flag is not enabled for your account, or channel limit reached.
- **422 Unprocessable Entity** — Validation failure (name missing, name > 12 chars, name already exists, or brand\_name > 50 chars).

## Notes

- Default order-status mapping is applied automatically (matches the canonical mapping used when you create a manual channel from the Shiprocket dashboard).

## HEADERS

---

**Authorization** Bearer {{jwt\_token}}

**Content-Type** application/json

**Body** raw (json)

---

json

```
{  
  "name": "MANUAL-25149",  
  "brand_name": "SIORA-12"  
}
```

---

## Inventory

Use this API to update and get Inventory details.

---

## GET Get Inventory Details

<https://apiv2.shiprocket.in/v1/external/inventory>

This API can be used to check the inventory details of a product sku. There are no required parameters for this API, but additional parameters can be used to sort and filter the data.

In case no filter conditions are passed, the details are displayed in the default JSON format.

### Parameters:

| PARAMS                | REQUIRED | DATA TYPE      | DESCRIPTION                                                                                                       | EXAMPLE |
|-----------------------|----------|----------------|-------------------------------------------------------------------------------------------------------------------|---------|
| <code>page</code>     | NO       | <i>integer</i> | The page number to be displayed.                                                                                  | 4       |
| <code>per_page</code> | NO       | <i>integer</i> | The total products you want to display in each page.                                                              | 2       |
| <code>sort</code>     | NO       | <i>string</i>  | Sort conditions if any. Value: ASC or DESC                                                                        | ASC     |
| <code>sort_by</code>  | NO       | <i>integer</i> | Allows you to choose the field by which the data will be sorted. Could be sorted by id, by sku, time created etc. | sku     |

### HEADERS

---

**Content-Type**                      application/json

---

## PUT Update Your Inventory

[https://apiv2.shiprocket.in/v1/external/inventory/{product\\_id}/update](https://apiv2.shiprocket.in/v1/external/inventory/{product_id}/update)

This API is used to update your product inventory details.

First, you need to pass the `product_id` of the product in the endpoint URL. You can then set the quantity and action you want to perform on the existing inventory of the specified product.

#### Note:

- The product\_id can be found using the 'Get Inventory Details' API.
- The id is to be passed in the endpoint URL itself.

#### Path:

##### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/inventory/17454637/update>

#### Parameters:

| PARAMS   | REQUIRED | DATA TYPE | DESCRIPTION                                                                                                                                                                                                                                                                          | EXAMPLE |
|----------|----------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| quantity | YES      | integer   | The quantity of the product you want.                                                                                                                                                                                                                                                | 2       |
| action   | YES      | integer   | The action you want to perform.<br><i>Value:</i> - <b>add</b> :<br>Adds the specific quantity to the product inventory.<br>- <b>replace</b> :<br>Replaces the existing quantity with the specified number. - <b>remove</b> : Removes the specific number from the product inventory. | add     |

#### HEADERS

##### Content-Type

application/json

##### Body raw

```
{  
  "quantity": "",  
  "action": ""  
}
```

---

# Countries

The following APIs provide details about the various country codes and their respective zone details along with the locality details.

---

## GET Get Country Codes

<https://apiv2.shiprocket.in/v1/external/countries>

This API lists all the countries present in the Shiprocket database and the respective country ids, ISO 2 and ISO 3 codes.

There are a total of 44 available countries in the database. You can use these codes to check the serviceability and use them in your dropdown menu.

No parameters are required to access this API.

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## GET Get All Zones

[https://apiv2.shiprocket.in/v1/external/countries/show/{country\\_id}](https://apiv2.shiprocket.in/v1/external/countries/show/{country_id})

Use this API to get a further list of all the available zones within a country, along with their ids and details.

The country ID must be passed as a path parameter to access this API. No other body parameters are required.

**Path:**

#### EXAMPLE

<https://apiv2.shiprocket.in/v1/external/countries/show/4>

### HEADERS

---

|              |                  |
|--------------|------------------|
| Content-Type | application/json |
|--------------|------------------|

---

## GET Get Locality Details

<https://apiv2.shiprocket.in/v1/external/open/postcode/details>

Use this API to get further locality details of any given postcode. Just pass the valid locality Pincode, and the details will be displayed in JSON format.

### Parameters:

| PARAMS                | REQUIRED | DATA TYPE      | DESCRIPTION                                       | EXAMPLE |
|-----------------------|----------|----------------|---------------------------------------------------|---------|
| <code>postcode</code> | YES      | <i>integer</i> | The Pincode you want to get the locality details. | 110077  |

### HEADERS

---

Content-Type `application/json`

---

## Statement Details

Get your Shiprocket account's statement details using this API.

---

## GET Get Statement Details

<https://apiv2.shiprocket.in/v1/external/account/details/statement>

Use this API to get the account statement details of your Shiprocket account. No parameters are required to access this API. However, you sort and filter the data displayed using the optional parameters.

### Parameters:

| PARAMS                | REQUIRED | DATA TYPE      | DESCRIPTION                              | EXAMPLE    |
|-----------------------|----------|----------------|------------------------------------------|------------|
| <code>page</code>     | NO       | <i>integer</i> | The page number you want to display.     | 5          |
| <code>per_page</code> | NO       | <i>integer</i> | The number of orders to get per request. | 2          |
| <code>from</code>     | NO       | <i>string</i>  | From a specific date.                    | 2017-08-12 |
| <code>to</code>       | NO       | <i>string</i>  | To a specific date.                      | 2017-09-12 |

## HEADERS

---

**Content-Type** `application/json`

---

# Discrepancy Details

Use this API to get the discrepancy details of your account.

---

## GET Get Discrepancy Data

`https://apiv2.shiprocket.in/v1/external/billing/discrepancy`

Get the discrepancy data associated with your account, if any. No parameters are required to use this API.

The data is displayed in JSON format.

## HEADERS

---

**Content-Type** `application/json`

---

# File Imports

Check the status response of files that have been imported using the API.

---

## GET Get File import Results

`https://apiv2.shiprocket.in/v1/external/errors/{import_id}/check`

Check the import response of various file imports for any error, including bulk order imports, products and product listings.

You will have to pass the file import id as a path parameter in the endpoint URL. This id is provided at the time of importing the file. No other body parameters are required.

### Path:

#### EXAMPLE

`https://apiv2.shiprocket.in/v1/external/errors/20212061/check`

### HEADERS

---

Content-Type

application/json