COURSE CURRICULUM

# Storefront Masterclass

Build a web and mobile storefront where sellers open a store, list items and get paid. Guests can buy without an account.

Next.js 15 · Supabase · Paystack · Resend · Capacitor · Vercel · GitHub Actions

**10 MODULES** one video each · Noah 1, 3, 5, 6, 9 · Co-founder 2, 4, 7, 8, 10

| | MODULE | WHAT GETS BUILT | OWNER | END STATE |
|---|---|---|---|---|
| 01 | **Setup Everything** | Repo, Next.js app (static export), Supabase project, tables (stores, products, orders, order_items), Row Level Security, buy the domain, deploy to Vercel on the domain, verify the domain with Resend, .env.local and Vercel env vars, set up Claude safely with SQL migrations on a dev project | Noah | Blank app live on the domain, database secured, email ready; no more setup |
| 02 | **Capacitor & Build Pipeline** | Wrap the app in Capacitor for Android, GitHub Actions builds a signed APK on every push to main using one release keystore stored in GitHub secrets, version number goes up with each build, web deploys to Vercel | Co-founder | Each push gives an APK that updates the old one |
| 03 | **Seller Accounts & Store Creation** | Supabase Auth, store profile, add and edit products with image upload | Noah | A seller can sign up and list an item |
| 04 | **Storefront, Cart & Guest Checkout** | Public store page, product listing, cart state, checkout with no login, account prompt only at the pay step | Co-founder | A guest can fill a cart and reach checkout |
| 05 | **Payments & Orders** | Paystack checkout, Edge Function webhook to verify payment, order saved as paid | Noah | A test-mode payment creates a paid order |
| 06 | **Email Verification & Notifications** | Email verification code at checkout, order confirmation and receipt emails to the buyer, new-order emails to the seller (Resend) | Noah | A sale triggers emails to buyer and seller |
| 07 | **Seller Dashboard** | Orders list and order detail, mark as fulfilled, simple sales summary | Co-founder | A seller can see and manage their orders |
| 08 | **Native Features & iOS** | Push notifications (FCM), splash screen and icons, deep links, iOS build and TestFlight | Co-founder | A sale sends a push to the seller's phone |
| 09 | **Go Live** | Switch Paystack to live, Supabase production settings, production env vars, Play Store release | Noah | Real payments on the real domain and in the store |
| 10 | **Onboarding Assessment** | Students sign up on the live app and complete the assessment; Terms and Privacy published | Co-founder | Students onboarded on the MVP |

## KEY HANDLING RULES Module 1

**Assume the app bundle is public.** Anything prefixed NEXT_PUBLIC_ is bundled into the website and the APK. Only three values ship in the app: the Supabase URL, the Supabase anon key and the API URL.

**The anon key is safe because of Row Level Security.** Plain reads and writes (products, cart, store profile) go straight to Supabase.

**Sensitive actions go through Edge Functions.** Create order, verify payment and send email run in Supabase Edge Functions that check the user's login token. Allow the Capacitor origins (https://localhost, capacitor://localhost) in CORS.

**Secrets live only in Edge Function secrets.** The service-role key, Paystack secret key and Resend key are set with supabase secrets set. They never go in the app, the repo or Vercel.

**Local and Vercel setup.** Public values go in .env.local (gitignored) with a blank .env.example committed, and the same public values go in Vercel environment variables.

**Claude and the database.** Claude writes SQL migrations applied with the Supabase CLI against a separate dev project. It never gets the service-role key, and a deny rule stops it reading .env files.

**Safety nets.** GitHub push protection and secret scanning. If a key leaks, rotate it in the dashboard immediately.

## DECISIONS AND RISKS TO SETTLE BEFORE RECORDING

**Updates that install over the old app**
Android only accepts an update if it is signed with the same key and has a higher version number. Use one release keystore in GitHub secrets and set the version from the build number. CI debug builds use a random key each run and will not upgrade. Firebase App Distribution can notify testers of each new build.

**Resend free tier**
Notes say about 300 emails a month. I believe the free plan is higher (about 3,000 a month, 100 a day). Confirm on their pricing page.

**Android build tools**
An APK still needs the Android SDK. GitHub Actions builds it for students, but Module 2 needs Android Studio or the SDK locally to test.

**iOS**
Needs a Mac and a paid Apple Developer account (about $99 a year). Say so up front.

**Paystack**
Test mode until Module 9. Going live needs business verification, so start early. Decide how sellers get paid (split payments or subaccounts) before Module 5.

**Static export**
No server-rendered pages. Use client-side routing for stores and products, and put webhooks in Edge Functions.