

## DYNAMIC MIXER WITH **DISPOSABLE MIXING CHAMBER** AND TWO COMPONENT SWIVEL JOINT FOR INTEGRATION INTO MANUAL SEALING PLANTS



### ECONOMIC BENEFITS

**SAVINGS OF OPERATING  
EXPENSES UP TO € 15.000,-  
PER YEAR THROUGH:**

- Freezer or solvent flushing pump  
no longer required
- No more loss of material through  
purging processes
- Saving of costs for disposal of waste material
- No more necessity for cleaning of Z-swivel joint
- No complementary purchase of trumpet mixer  
required
- Less wear of the plant by lowering the pressure  
level to approximately 120 bar

Dimensions	Length	Width	Height
	700 mm	80 mm	100 mm
Admissible operating pressure	200 bar		
Output	450 - 1000 ccm/min		
Air pressure	6 bar		
Weight approx.	4150 g		

**Optionally available as integrated in Ecostar evo series or as  
retro-fit kit for existing installations.**

## YOUR GLOBAL PARTNER FOR METERING AND MIXING TECHNOLOGY

- Processing and application of single and multi component adhesive and sealants as well as casting/encapsulation liquids.
- Ambient and temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification



**We look forward to discuss further details with you.**

**Reinhardt-Technik GmbH**

Waldheimstraße 3

58566 Kierspe/Germany

T +49 (0) 23 59 - 6 66.0

F +49 (0) 23 59 - 6 66.1 29

[info@reinhardt-technik.de](mailto:info@reinhardt-technik.de)

[www.reinhardt-technik.de](http://www.reinhardt-technik.de)