

# LSR 20 LC

Two component metering and mixing plant for material unloading out of 20l-hobbocks.

## STANDARD FEATURES

- attractive industrial design
- clear and ergonomic arrangement of control elements
- easy drum exchange
- space saving compact footprint
- doors open to 180°
- material unloading out of 20 l hobbocks
- electric pressure and level control
- pneumatic control station
- PLC-control
- processing unit 1/2" with static mixer
- pressure regulator

## OPTIONS

- dosing of one colour/additive
- cooling for static mixer
- processing unit 1" or 8 mm with static mixer

## THE ECONOMICAL SOLUTION FOR HIGH TECHNICAL DEMANDS



Dimensions	Length	Width	Height
basic machine / ram	800 mm	750 mm	1.895 mm

Mixing ratio according to volume	1:1
Maximum dyn. operating pressure	300 bar
Connected loads electrical	230 V-AC
Output	max.1500 g/min
Weight	approx. 600 kg



Drum change  
and rear view

## YOUR GLOBAL PARTNER FOR METERING AND MIXING TECHNOLOGY

- Processing and application of single and multi component adhesive and sealants as well as casting/encapsulation liquids.
- Ambient and temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification



**We look forward to discuss further details with you.**

**Reinhardt-Technik GmbH**

Waldheimstraße 3

58566 Kierspe/Germany

T +49 (0) 23 59 - 6 66.0

F +49 (0) 23 59 - 6 66.1 29

[info@reinhardt-technik.de](mailto:info@reinhardt-technik.de)

[www.reinhardt-technik.de](http://www.reinhardt-technik.de)