

# Dynamic Mix 6.0

## COMPONENT A

- pressure monitoring

## SERVO DRIVE

- controlled mixer speed  
provide constant quality

## COMPONENT B

- pressure monitoring

disposable mixer  
chamber

integrated  
valves

## AUTOMATIC DYNAMIC MIXER WITH **DISPOSABLE MIXING CHAMBER**

The Dynamic Mix 6.0 combines the technical advantages of a dynamic mixer with the economical benefits of a static mixer.

## ECONOMIC BENEFITS

### **SAVINGS OF OPERATING EXPENSES UP TO € 15.000,- PER YEAR THROUGH:**

- elimination of purging losses
- minimizing cost of waste material
- low wear of the system through reduction of pressure down to 120bar
- no complementary purchase of trumpet mixer required

The Dynamic Mix 6.0 requires a controller. Depending on version the mixer will be integrated in parent control or it comes with a retrofit integration kit.

Dimensions	Length	Width	Height
	150 mm	125 mm	140 mm

Max. pressure	200 bar
Output	450 - 1000 ccm/min
Mixer speed	700 1/min
Air pressure	6 bar
Weight approx.	7.200 g

## YOUR GLOBAL PARTNER FOR METERING AND MIXING TECHNOLOGY

- Processing and application of single and multi component adhesive and sealants as well as casting/encapsulation liquids.
- Ambient and temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification



**We look forward to discuss further details with you.**

**Reinhardt-Technik GmbH**

Waldheimstraße 3

58566 Kierspe/Germany

T +49 (0) 23 59 - 6 66.0

F +49 (0) 23 59 - 6 66.1 29

[info@reinhardt-technik.de](mailto:info@reinhardt-technik.de)

[www.reinhardt-technik.de](http://www.reinhardt-technik.de)