



Information Management and Data Engineering

CSU 34041

7. Mapping to Logical Design





Today's Lecture

- Introduction to Relational Schema Mapping
- Mapping Entity Types
- Mapping Multivalued Attributes
- Mapping Relationships
- Cinema Example





Relational Schema Mapping





Relational Schema Mapping

- How to move from a conceptual database design
 - Entity Relationship Model
- ...to a logical database design
 - Relational Database Schema
- We follow a series of steps to map entity types, relationships and attributes into relations





Relational Schema Mapping

- We will use the examples from the previous lectures to illustrate these mapping steps
- The mapping will create:
 - Relations
 - with simple, single-valued attributes
 - Constraints
 - primary keys
 - unique keys
 - referential integrity constraints





Mapping Entity Types





Mapping of Entity Types

- For each entity type E in the ER diagram, create a relation R that includes all the simple attributes of E
- Composite attributes
 - when mapping composite attributes include only the simple component attributes in the new relation R






Mapping of Entity Types

- Key attributes
 - choose one of the key attributes of E as the primary key of R
 - composite key attributes are included as a *composite primary key*
- Additional key attributes should be included as secondary unique keys of the relation



Mapping of Entity Types



BRANCH

| <u>branch_id</u> | name | street | town | county | phone_no | website |
|------------------|------|--------|------|--------|----------|---------|
|------------------|------|--------|------|--------|----------|---------|




Mapping Multivalued Attributes





Mapping Multivalued Attributes




- For each multivalued attribute A , create a new relation R
- The new relation R will include:
 - An attribute corresponding to A
 - The primary key K from the relation that represents the entity type that A came from
 - This becomes a *foreign key* in R
 - The *primary key* of R is the combination of A and K





Mapping Multivalued Attributes



BOOK

| | | | | | | | | |
|----------------|-------|----------|--------|------|-----------|-------------|---------------|--------------|
| <u>book_id</u> | title | synopsis | author | cert | publisher | release_day | release_month | release_year |
|----------------|-------|----------|--------|------|-----------|-------------|---------------|--------------|

GENRE

| | |
|----------------|--------------|
| <u>book_id</u> | <u>genre</u> |
|----------------|--------------|





Mapping Relationships





Mapping Relationships

- In addition to mapping the entity types from the ER model into the Relational Schema, we also need to map the relationship types
- Each relationship type is modeled differently
 - 1:1 One to One
 - 1:N One to Many
 - M:N Many to Many





Mapping 1:1 Relationships





Mapping 1:1 Relationships

- There are two main approaches to mapping binary 1:1 relationships
 - Foreign Key Approach
 - Most useful and most commonly used
 - Merged-Relation Approach
 - Used in cases of *total participation*
- For each binary 1:1 relationship type R
 - identify the relations S and T that correspond to the entity types participating in R






Mapping 1:1 Relationships

- Foreign Key Approach
 - choose one of the participating relations, say S
 - include as a foreign key in S the primary key of T
 - if possible, choose an entity type with *total participation* in R for the role of S
 - include all the simple attributes of the relationship type R as attributes of S



Mapping 1:1 Relationships






Mapping 1:1 Relationships

- Merged Relation Approach
 - This can only be used when both S and T have *total participation* in the relationship type R
 - Merge the two entity types S and T and the relationship type R into one single relation V
 - V should include all the simple component attributes of S, T and R
 - This is possible as the joint total participation indicates that the two tables will have an identical number of tuples at all time





Mapping 1:1 Relationships



EMPLOYEE_RECORD

| | | | | | | | |
|--------------------|-----|------------|--------------------|-------|-------|---------|-----|
| <u>contract_id</u> | ... | start_date | <u>employee_id</u> | fname | lname | address | ... |
|--------------------|-----|------------|--------------------|-------|-------|---------|-----|





Mapping 1:N Relationships






Mapping 1:N Relationships

- For each binary 1:N relationship type R
 - identify the relation S that corresponds to the entity types on the N-side of R
- Include as a foreign key in S , the primary key of T , which is the relation representing the entity type at the other side of R
- Include any simple attributes of the relationship type R as attributes of S
 - or simple component attributes of a composite attribute





Mapping 1:N Relationships



PLAY

| <u>play_id</u> | title | time | date |
|----------------|-------|------|------|
|----------------|-------|------|------|

STAGE

| <u>number</u> | stage_type | capacity | location |
|---------------|------------|----------|----------|
|---------------|------------|----------|----------|

PLAY

| <u>play_id</u> | time | date | stage_number |
|----------------|------|------|--------------|
|----------------|------|------|--------------|

STAGE

| <u>number</u> | stage_type | capacity | location |
|---------------|------------|----------|----------|
|---------------|------------|----------|----------|





Mapping Recursive Relationships






Mapping Recursive Relationships

- Recursive relationships
 - where an entity instance can refer to another instance of the same entity type
- For each recursive relationship type R
 - Include the primary key of T, which is the relation representing the entity type involved, as a foreign key in the same relation, T
 - Include any simple attributes of the relationship type R as attributes of T
 - or simple component attributes of a composite attribute





Mapping Recursive Relationships





Mapping M:N Relationships





Mapping M:N Relationships

- Many to Many relationship types are more complex to map than 1:1 or 1:N
- As each entity instance may reference many entity instances in the other participating entity type
 - You cannot use a foreign key attribute in either participating entity
 - You must create a new relation to represent the relationship type






Mapping M:N Relationships

- For each binary M:N relationship type R
 - create a new relation S to represent R
- Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types
 - The combination of these foreign keys is the composite primary key of S
- Include any simple attributes of the relationship type R as attributes of S
 - or simple component attributes of a composite attribute






Mapping M:N Relationships






Mapping M:N Relationships



Cinema Example

Cinema Example





Cinema Example

