
Notes for teaching and learning



Item Response Theory

with mirt and mirtverse

A hands-on course in measurement with R

mirtverse

Okan Bulut

Item Response Theory

with mirt and mirtverse

Notes for teaching and learning

Okan Bulut

Measurement, Evaluation, and Data Science
University of Alberta

bulut@ualberta.ca · www.okanbulut.com

Item Response Theory with mirt and mirtverse: Notes for Teaching and Learning
by Okan Bulut

© 2026 Okan Bulut. The text and figures of this book are licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International licence (CC BY-NC-SA 4.0). The R code is licensed under GPL-3.

DOI: 10.5281/zenodo.23885605
Online edition: https://www.okanbulut.com/mirtverse/book/
Source: https://github.com/okanbulut/mirtverse/tree/main/book

Typeset with bookdown and XeLaTeX on November 2, 2026. The cover illustration is an original engraving-style drawing made for this book.

Contents

Preface **8**
How the book is organised . . . 8
Before you start . . . 9
Other teaching materials . . . 9
Using and adapting the book . . . 10
Other formats . . . 10
How to cite this book . . . 10
Licence . . . 10
Acknowledgements . . . 11

About the author **12**

1 Measurement, scoring and classical item analysis **14**
1.1 The ideas . . . 14
1.2 Example 1: a multiple-choice science test . . . 15
1.3 Example 2: a wellbeing questionnaire . . . 17
1.4 A first look with mirtverse . . . 19
1.5 Your turn . . . 19
In the lab . . . 20
Further reading . . . 20

2 The Rasch, 2PL and 3PL models **21**
2.1 The ideas . . . 21
2.2 Example 1: the LSAT section 7 items . . . 22
2.3 Example 2: a driving theory test with guessing . . . 26
2.4 Your turn . . . 27
In the lab . . . 28
Further reading . . . 28

3 Estimation and comparing models **29**
3.1 The ideas . . . 29
3.2 Example 1: a test the Rasch model fits . . . 30
3.3 Example 2: when the criteria disagree . . . 31
3.4 Your turn . . . 33
In the lab . . . 34
Further reading . . . 34

4 Dimensionality and local independence **35**
4.1 The ideas . . . 35
4.2 Example 1: a mathematics test with a reading dimension . . . 36
4.3 Example 2: a reading passage that ties four items together . . . 38
4.4 Your turn . . . 40
In the lab . . . 42
Further reading . . . 42

5 Item fit, person fit and item quality **43**
5.1 The ideas . . . 43
5.2 Example 1: the same items under two models . . . 44
5.3 Example 2: finding aberrant response patterns . . . 47
5.4 Your turn . . . 49
In the lab . . . 50
Further reading . . . 50

6 Information, precision and reliability **51**
6.1 The ideas . . . 51
6.2 Example 1: where does the science test measure well? . . . 52
6.3 Example 2: designing a test for a decision . . . 54
6.4 Your turn . . . 56
In the lab . . . 57
Further reading . . . 57

7 Scoring people **58**
7.1 The ideas . . . 58
7.2 Example 1: four estimators, one short test . . . 59
7.3 Example 2: a proficiency cut on a mathematics test . . . 60
7.4 Your turn . . . 62
In the lab . . . 63
Further reading . . . 64

8 Polytomous items and open-ended responses **65**
8.1 The ideas . . . 65
8.2 Example 1: attitudes to science . . . 66
8.3 Example 2: a rating category nobody uses . . . 69
8.4 Open-ended responses and raters . . . 70
8.5 Your turn . . . 71
In the lab . . . 72
Further reading . . . 72

9 Differential item functioning and fairness **73**
9.1 The ideas . . . 73
9.2 Example 1: paper versus tablet . . . 74
9.3 Example 2: Mantel-Haenszel on a chemistry quiz . . . 78
9.4 Your turn . . . 79
In the lab . . . 80
Further reading . . . 80

10 Linking and equating **81**
10.1 The ideas . . . 81
10.2 Example 1: separate calibration and linking . . . 82
10.3 Example 2: concurrent calibration and equating a pass mark . . . 84
10.4 Your turn . . . 86
In the lab . . . 87
Further reading . . . 87

11 Item banks, test assembly and adaptive testing **88**
11.1 The ideas . . . 88
11.2 Example 1: a vocabulary bank and a fixed form . . . 89
11.3 Example 2: a CAT from scratch . . . 91
11.4 Your turn . . . 93
In the lab . . . 94
Further reading . . . 94

12 Cut scores, reporting and communicating results **95**
12.1 The ideas . . . 95
12.2 Example 1: setting a proficiency standard . . . 96
12.3 Example 2: telling the story . . . 98
12.4 Your turn . . . 100
In the lab . . . 101
Further reading . . . 101

A Datasets used in the book **102**
Other datasets for practice . . . 104

B Adapting the book for your course **105**
The files . . . 105
Every chapter has the same shape . . . 106
Swapping in your own data . . . 106
Building the book . . . 106
Suggesting changes . . . 107

List of Figures

2.1 Item characteristic curves of the 2PL model for the five LSAT7 items. 23
2.2 Rasch curves (left) are parallel by construction; 2PL curves (right) can differ in slope. 24
2.3 Empirical item curve of the hardest driving-test item, D20, under the 2PL (left) and the 3PL (right). 27

3.1 Model comparison for LSAT6: each model's information criterion relative to the best model (0 = best). 31

4.1 Q3 residual correlations from a unidimensional 2PL fitted to the reading test with a four-item passage. 39

5.1 S-X^2 RMSEA of each SAT12 item under the Rasch model; flagged items are marked. 44
5.2 Empirical item curve of the worst-fitting item under the Rasch model (left) and the 2PL (right). 46
5.3 Item health card of the SAT12 item with the lowest discrimination under the 2PL. 47
5.4 Distribution of the Zh person-fit statistic for regular students, random responders and students with pre-knowledge. 48
5.5 Empirical item curve of the best-fitting item under the Rasch model. 50

6.1 Test information (left) and standard error of measurement (right) for the SAT12 science test under the 2PL. 52
6.2 Item information curves of six SAT12 items. 53
6.3 Test information of three 20-item forms drawn from the nursing pool; the dashed line marks the pass mark. 55

7.1 Distribution of the estimated scores (left) and the Wright map of people and items (right) for LSAT7. 60
7.2 True and estimated ability on the mathematics test; misclassified students lie near the cut. 62

8.1 Category response curves of the graded response model for the four Science items. 67
8.2 Expected item score curves of the graded response model for the Science items. 68
8.3 Wright map of the Science items: category thresholds next to the distribution of people. 68

8.4 Category response curves of J2 and J3; category 2 of J3 is never the most likely response. 70

9.1 DIF effect sizes for the 25 reading items, paper versus tablet. 76
9.2 Item curves for the paper and tablet groups: uniform DIF in R07, non-uniform DIF in R22. 76

10.1 Anchor difficulties in the old and new calibrations; items off the line may have drifted. 83
10.2 Test characteristic curves of the old and new forms on the common scale, with the cut score. 86

11.1 Information of the 200-item vocabulary bank, stacked by content area. 90
11.2 Number of items administered by the CAT against true ability. 92

12.1 Item map of the ordered item booklet with the proficient cut score. 98

List of Tables

1 The twelve chapters and their matching labs. 8

A.1 Data chunks in the book and the objects each defines. 102

B.1 Source files of the book. 105

Preface

This book is a set of extended course notes on item response theory (IRT). It is written for instructors who teach measurement with R and for the students in their courses. Every chapter mixes a short explanation of the ideas with worked examples that you can run line by line, using the mirt package (Chalmers 2012) for estimation and mirtverse for model choice, tidy tables, graphics and plain-language interpretation.

How the book is organised

The twelve chapters follow the twelve weeks of the mirtverse course map, so an instructor can assign one chapter a week and pair it with the matching lab.

Table 1: The twelve chapters and their matching labs.

Chapter	Topic	Matching lab
1	Measurement, scoring and classical item analysis	Lab 1 (first two sections)
2	The Rasch, 2PL and 3PL models	
3	Estimation and comparing models	
4	Dimensionality and local independence	Lab 1
5	Item fit, person fit and item quality	
6	Information, precision and reliability	
7	Scoring people	Lab 2
8	Polytomous items and open-ended responses	Lab 6
9	Differential item functioning and fairness	Lab 3
10	Linking and equating	Lab 4

Chapter	Topic	Matching lab
11	Item banks, test assembly and adaptive testing	Lab 5
12	Cut scores, reporting and communicating results	Final project

Every chapter has the same parts:

- **Learning goals:** what you should be able to do after the chapter.
- **Key terms:** links to the mirtverse glossary.
- **The ideas:** a short explanation, with formulas only where they help.
- **Example 1 and Example 2:** two worked analyses on different data, so you see the same method in two settings.
- **Your turn:** exercises with solutions. In the online edition the solutions are folded away; click to open them.
- **In the lab:** the interactive mirtverse lab that goes with the chapter.
- **Further reading.**

The examples deliberately use different data from the labs. The labs hide problems in their data for students to find, and the book does not give those away.

Before you start

You need R (version 4.1 or later), mirt (version 1.48 or later) and mirtverse:

```
install.packages(c("mirt", "learnr"))
install.packages("mirtverse", repos = c("https://okanbulut.r-universe.dev",
                                        "https://cloud.r-project.org"))
library(mirtverse)
```

Loading mirtverse also loads mirt, so `mirt()`, `fscores()`, `itemfit()` and the mirt datasets are available straight away. Every example runs in a few seconds on a laptop, and no internet connection is needed once the packages are installed.

Students who are new to R can follow much of the book without writing code. The workbench (`launch_workbench()`) runs the same analyses by pointing and clicking and shows the R code for every step, and `mv_ask()` writes a script from a plain-language request.

Other teaching materials

- Teaching labs: six interactive learnr labs with an instructor guide and answer key.
- Course map: a 12-week syllabus with readings, functions, labs and assessment ideas.
- Glossary of IRT terms.
- Cheat sheet of the main functions, on two printable pages.

- Assessment pipeline: a test's full life cycle from blueprint to bank monitoring.

Using and adapting the book

The source of every chapter is an R Markdown file in the `book/` folder of the mirtverse repository. Each example loads its data in one clearly labelled chunk, so you can swap in your own data and rebuild the chapter. Appendix B explains how.

Other formats

The book is free to read online at https://www.okanbulut.com/mirtverse/book/. It is also available as a PDF for printing and an EPUB for e-readers; in the online edition, use the download button in the toolbar. All three are built from the same source each time the book changes.

How to cite this book

If you use the book in a course or in your work, please cite it as:

> Bulut, O. (2026). *Item response theory with mirt and mirtverse: Notes for teaching and learning*. Zenodo. https://doi.org/10.5281/zenodo.23885605

The DOI above always points to the latest edition of the book. Each archived edition also has its own DOI, listed on the Zenodo record; cite that one if you need to refer to the exact text you read (version 1.0 is 10.5281/zenodo.23885606).

```
@book{bulut2026irt,
  author    = {Okan Bulut},
  title     = {Item Response Theory with mirt and mirtverse: Notes for Teaching and Learning},
  year      = {2026},
  publisher = {Zenodo},
  doi       = {10.5281/zenodo.23885605},
  url       = {https://www.okanbulut.com/mirtverse/book/}
}
```

Please also cite the software you use: mirt (Chalmers 2012) and mirtverse (`citation("mirtverse")` gives the reference with its DOI).

Licence

© 2026 Okan Bulut. The text and figures of this book are licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International licence (CC BY-NC-SA 4.0): you may share and adapt them for non-commercial purposes, such as teaching, as long as

you give credit and share your adaptations under the same licence. The R code in the book is licensed under GPL-3, like mirtverse, so you can reuse it freely in your own analyses.

Acknowledgements

This book stands on the work of many people. Phil Chalmers wrote and maintains mirt, which does all of the estimation in these pages. The book was written with R Markdown and bookdown, by Yihui Xie and colleagues, and the figures were drawn with ggplot2. My thanks to all of them, and to the R community that makes open teaching materials like this possible.

About the author



Okan Bulut is a Professor of Measurement, Evaluation, and Data Science at the University of Alberta. His work sits where artificial intelligence meets educational measurement, data mining and learning analytics, and it asks a practical question: how can assessments learn about the learner while the learner is learning?

His research uses AI-driven algorithms and natural language processing to build digital assessment systems that adapt to learners' preferences, cognitive styles and performance over time. A large part of that work is about scale: generating test items automatically, scoring open-ended responses automatically, and giving every student timely, useful feedback, not just the few whose work a teacher has time to mark by hand.

He works closely with international research teams, school districts and professional organizations to advance the responsible and ethical use of AI in education, and partners with industry and regulatory bodies to turn advances in psychometrics and learning analytics into practical assessment and feedback systems that support better educational decisions.

At the University of Alberta he teaches courses in educational measurement, assessment, computational psychometrics and machine learning, and he gives workshops on computational techniques, programming and data visualization. This book grew out of that teaching. mirtverse, the R package used throughout, is his attempt to make modern item response theory as approachable in the classroom as it is powerful in research.

- E-mail: bulut@ualberta.ca
- Website: http://www.okanbulut.com

- GitHub: https://github.com/okanbulut

Chapter 1

Measurement, scoring and classical item analysis

> **Learning goals.** After this chapter you can
> - turn raw responses into item scores with a key, and reverse-score negatively worded items;
> - compute and read proportion correct, item-total correlations and coefficient alpha;
> - use a distractor analysis to spot an item that is miskeyed or badly written;
> - say what a sum score can and cannot tell you, and why we need IRT.

Key terms: classical test theory, sum score, p-value, item-total correlation, dichotomous item, polytomous item.

1.1 The ideas

A test is a sample of tasks that we use to make an inference about something we cannot see directly: a student's reading ability, a nurse's clinical knowledge, a patient's level of anxiety. Before any model is fitted, raw responses have to be turned into **item scores**. For a multiple-choice item that means comparing the option chosen with the key (1 = right, 0 = wrong). For a rating scale it means coding the categories as 0, 1, 2, ... and making sure that a higher score always means "more" of the trait, which is why negatively worded items are reverse-scored.

The simplest summary of a person's performance is the **sum score**, the total of the item scores. **Classical test theory** (CTT) models the sum score as a true score plus error, $X = T + E$, and gives us a small toolkit for judging items (Crocker and Algina 1986):

- **Item difficulty** (p): the proportion of people who answer correctly (for rating items, the item mean). Confusingly, a *high* p means an *easy* item.
- **Item discrimination**: the correlation between the item score and the total score. Items that good performers get right and weak performers get wrong have high item-total

correlations. The *corrected* correlation removes the item from the total first, which matters for short tests.

- **Coefficient alpha**: an estimate of reliability, the proportion of sum-score variance that is true-score variance.
- **Distractor analysis**: for multiple-choice items, how often each wrong option is chosen, and by whom. A good distractor attracts low scorers. An option that attracts high scorers is a warning sign: it may be a second correct answer, or the key may be wrong.

CTT statistics are easy to compute and to explain, and you should always start with them. But they have two limits that motivate the rest of this book. First, p and the item-total correlation depend on the group that took the test: the same item looks easy in a strong group and hard in a weak one. Second, the sum score treats every item as equally informative and gives one standard error for everybody, even though a test measures some people more precisely than others. Item response theory addresses both.

1.2 Example 1: a multiple-choice science test

The `SAT12` data in mirt hold the answers of 600 high-school students to 32 multiple-choice science items with five options (8 marks an omitted item). The key is published on the help page, `?SAT12`.

```
# Raw multiple-choice responses (options 1-5, 8 = omitted) and the key.
raw <- SAT12
key <- c(1,4,5,2,3,1,2,1,3,1,2,4,2,1,5,3,4,4,1,4,3,3,4,1,3,5,1,3,1,5,4,5)
```

`key2binary()` scores every response against the key. Omits count as wrong.

```
resp <- key2binary(raw, key)
resp[1:5, 1:8]
#>      Item.1 Item.2 Item.3 Item.4 Item.5 Item.6 Item.7 Item.8
#> [1,]      1      1      1      1      1      1      1      1
#> [2,]      0      1      0      0      1      0      1      0
#> [3,]      1      1      1      0      1      0      1      0
#> [4,]      0      1      0      1      1      0      1      0
#> [5,]      0      1      1      1      1      0      1      1
total <- rowSums(resp)
summary(total)
#>    Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
#>     4.0    14.8    18.0    18.2    22.0    32.0
```

`itemstats()` gives the classical statistics for every item in one table.

```
st <- itemstats(resp)
st$overall
#>    N mean.total sd.total std.alpha alpha SEM.alpha mean.r  sd.r
#>  600       18.2     5.05     0.795 0.798      2.27  0.108 0.075
```

```
head(st$itemstats, 8)
#>          N K  mean    sd cor_if_rm   smc alpha_if_rm
#> Item.1 600 2 0.283 0.451     0.300 0.158       0.793
#> Item.2 600 2 0.568 0.496     0.464 0.270       0.785
#> Item.3 600 2 0.280 0.449     0.371 0.184       0.789
#> Item.4 600 2 0.378 0.485     0.235 0.145       0.796
#> Item.5 600 2 0.620 0.486     0.340 0.197       0.791
#> Item.6 600 2 0.160 0.367     0.351 0.185       0.791
#> Item.7 600 2 0.760 0.427     0.289 0.200       0.793
#> Item.8 600 2 0.202 0.402     0.233 0.116       0.795
```

The `mean` column is the proportion correct, `cor_if_rm` is the corrected item-total correlation, and `alpha_if_rm` is alpha with the item removed. Let us sort the items by their corrected correlation and look at the weakest.

```
items <- st$itemstats
items[order(items$cor_if_rm), c("mean", "cor_if_rm", "alpha_if_rm")][1:5, ]
#>          mean cor_if_rm alpha_if_rm
#> Item.32 0.162     0.037       0.802
#> Item.12 0.415     0.076       0.803
#> Item.9  0.885     0.127       0.798
#> Item.21 0.915     0.136       0.798
#> Item.11 0.983     0.156       0.797
```

A corrected correlation near zero, or an alpha that goes *up* when the item is removed, means the item is not measuring what the rest of the test measures. Before blaming the item writer, check the key. A distractor analysis splits students into groups by total score and shows which option each group chose.

```
distractors <- function(raw, total, item, groups = 5) {
  band <- cut(rank(total, ties.method = "first"), groups,
              labels = c("lowest", paste0("band ", 2:(groups - 1)), "highest"))
  round(prop.table(table(band, option = raw[[item]]), 1), 2)
}
distractors(raw, total, "Item.32")
#>          option
#> band         1    2    3    4    5    8
#>   lowest  0.12 0.26 0.35 0.09 0.14 0.04
#>   band 2  0.10 0.31 0.36 0.07 0.14 0.02
#>   band 3  0.19 0.16 0.42 0.08 0.15 0.00
#>   band 4  0.16 0.12 0.48 0.08 0.16 0.00
#>   highest 0.06 0.07 0.62 0.04 0.22 0.00
```

The keyed answer to item 32 is option 5, yet option 3 is the most popular choice in every band, and its share climbs steeply from the lowest band to the highest. Option 5 gains far less. When

an "unkeyed" option behaves the way a correct answer should, suspect the key. The help page for `SAT12` agrees: the key for item 32 is probably wrong and should be 3. Re-scoring fixes the item:

```
key_fixed <- replace(key, 32, 3)
resp_fixed <- key2binary(raw, key_fixed)
st_fixed <- itemstats(resp_fixed)
c(old_r = items["Item.32", "cor_if_rm"],
  new_r = st_fixed$itemstats["Item.32", "cor_if_rm"],
  old_alpha = st$overall$alpha, new_alpha = st_fixed$overall$alpha)
#>     old_r     new_r old_alpha new_alpha
#>    0.0371    0.2026    0.7979    0.8023
```

What to take away. A low item-total correlation is a symptom, not a diagnosis. The distractor table tells you *why*: a wrong key, two defensible answers, an option that confuses strong students, or simply an item that is too hard for everyone.

1.3 Example 2: a wellbeing questionnaire

Rating scales need the same care. Here we simulate a short questionnaire: 800 adults rate eight statements about their wellbeing from 0 (*strongly disagree*) to 3 (*strongly agree*). Items 3 and 7 are negatively worded ("I often feel tense"), so agreeing with them means *lower* wellbeing.

```
# Simulated 8-item wellbeing scale, 0-3, items W3 and W7 negatively worded.
set.seed(101)
a <- matrix(c(1.6, 1.4, 1.2, 1.8, 1.3, 1.5, 1.1, 0.5))
d <- matrix(c( 2.0, 0.5, -1.5,
               1.8, 0.2, -1.8,
               2.2, 0.8, -1.0,
               1.5, 0.0, -2.0,
               2.5, 1.0, -0.8,
               1.7, 0.3, -1.6,
               2.0, 0.6, -1.2,
               1.0, 0.0, -1.0), ncol = 3, byrow = TRUE)
resp <- simdata(a, d, N = 800, itemtype = "graded")
colnames(resp) <- paste0("W", 1:8)
resp[, c("W3", "W7")] <- 3 - resp[, c("W3", "W7")]   # as answered on the form
resp <- as.data.frame(resp)
```

If we forget to reverse-score, the two negative items correlate *negatively* with the total, and alpha is badly understated.

```
itemstats(resp)$itemstats[, c("mean", "cor_if_rm")]
#>    mean cor_if_rm
#> W1 1.64     0.348
#> W2 1.49     0.341
```

```
#> W3 1.24    -0.412
#> W4 1.44     0.326
#> W5 1.88     0.296
#> W6 1.60     0.356
#> W7 1.29    -0.433
#> W8 1.48     0.122
itemstats(resp)$overall$alpha
#> [1] 0.224
```

Reverse-scoring maps 0 to 3, 1 to 2 and so on:

```
scored <- resp
scored[, c("W3", "W7")] <- 3 - scored[, c("W3", "W7")]
st <- itemstats(scored)
st$itemstats[, c("mean", "cor_if_rm", "alpha_if_rm")]
#>    mean cor_if_rm alpha_if_rm
#> W1 1.64     0.543       0.710
#> W2 1.49     0.459       0.725
#> W3 1.76     0.451       0.727
#> W4 1.44     0.538       0.710
#> W5 1.88     0.443       0.728
#> W6 1.60     0.507       0.716
#> W7 1.71     0.473       0.723
#> W8 1.48     0.210       0.773
st$overall$alpha
#> [1] 0.753
```

All items now point the same way. Item W8 still has a low corrected correlation, and alpha rises from 0.75 to 0.77 without it: it is a weak item, and an IRT model will give it a low discrimination too (Chapter 2). For rating scales the category frequencies are worth a look as well. A category almost nobody uses carries little information and may need to be merged with its neighbour (Chapter 8).

```
round(st$proportions, 2)
#>       0    1    2    3
#> W1 0.19 0.23 0.34 0.24
#> W2 0.24 0.24 0.32 0.20
#> W3 0.16 0.22 0.33 0.30
#> W4 0.26 0.26 0.27 0.21
#> W5 0.12 0.21 0.35 0.32
#> W6 0.20 0.23 0.33 0.23
#> W7 0.17 0.22 0.34 0.27
#> W8 0.27 0.25 0.20 0.28
```

1.4 A first look with mirtverse

`profile_data()` gives a quick overview of any response file, and is what `mv_ask()` uses before it writes an analysis. For each column it reports the type, the number of distinct values, the range and the share of missing values, and it guesses which columns are items and which are IDs or grouping variables.

```
profile_data(scored)
#> Data profile: 800 rows, 8 columns (8 look like items)
#>  column    type n_distinct min max prop_missing role levels
#>      W1 integer          4   0   3            0 item
#>      W2 integer          4   0   3            0 item
#>      W3 integer          4   0   3            0 item
#>      W4 integer          4   0   3            0 item
#>      W5 integer          4   0   3            0 item
#>      W6 integer          4   0   3            0 item
#>      W7 integer          4   0   3            0 item
#>      W8 integer          4   0   3            0 item
```

1.5 Your turn

1. Score `SAT12` with the corrected key. Which three items are now the hardest, and which three have the lowest corrected item-total correlation?
2. Run `distractors()` on the item with the lowest corrected correlation. Is the problem the key, a distractor, or the difficulty of the item?
3. In Example 2, what happens to alpha if you drop W8? Would you drop it? Give one reason for and one against.
4. Suppose 30% of students omitted the last five items of `SAT12` because they ran out of time. Why would scoring omits as wrong distort the item statistics of those items?

Solutions

```
resp_fixed <- key2binary(SAT12, replace(key, 32, 3))
it <- itemstats(resp_fixed)$itemstats
rownames(it)[order(it$mean)][1:3]                # hardest
#> [1] "Item.6" "Item.8" "Item.3"
rownames(it)[order(it$cor_if_rm)][1:3]        # weakest
#> [1] "Item.12" "Item.9"  "Item.21"
```

2. Use `distractors(SAT12, rowSums(resp_fixed), "<item>")`. If no option is preferred by the top band and the correct option rises only slowly, the item is simply hard or vague rather than miskeyed.
3. Alpha rises only a little. Dropping W8 shortens the scale and may remove content the scale is meant to cover; keeping it costs little precision. A content review should decide,

not alpha alone.

4. Not-reached items would look harder and would correlate with speed rather than knowledge. Treat not-reached items as missing (`NA`) rather than wrong; IRT estimation handles missing responses naturally.

In the lab

> The first two sections of Lab 1, `run_lab("model-choice")`, put you in charge of scoring a certification exam with 1,200 candidates. You score the responses, screen the items and decide what to do about anything suspicious. See Teaching labs.

Further reading

Crocker and Algina (1986) remain the classic introduction to classical test theory and item analysis. The *Standards for Educational and Psychological Testing* (American Educational Research Association et al. 2014) set out what evidence a test score needs before it is used.

Chapter 2

The Rasch, 2PL and 3PL models

Learning goals. After this chapter you can

- explain what a latent trait is and why IRT puts people and items on the same scale;
- write down the Rasch, 2PL and 3PL models and say what each parameter does to the item characteristic curve;
- fit the three models with `mirt()` and read their parameters in the traditional IRT metric;
- describe an item in words from its curve.

Key terms: item response theory, latent trait, logit, Rasch model, 2PL, 3PL, item characteristic curve, difficulty, discrimination, guessing, slope-intercept form.

2.1 The ideas

IRT assumes that a person's responses depend on an unobserved **latent trait** θ (theta): ability, knowledge, an attitude. By convention θ has mean 0 and standard deviation 1 in the calibration group, so a person at $\theta = 1$ is one standard deviation above average.

Each item gets an **item characteristic curve** (ICC): the probability of a correct answer as a function of θ. The three classic models differ in how many parameters shape that curve (Hambleton et al. 1991; Embretson and Reise 2000).

The Rasch (1PL) model has one parameter per item, the difficulty b_j:

$$P(X_{ij} = 1 \mid \theta_i) = \frac{\exp(\theta_i - b_j)}{1 + \exp(\theta_i - b_j)}.$$

The difficulty is the point on the θ scale where the probability is 0.5. All curves have the same slope, so they never cross, and the sum score contains all the information about θ.

The two-parameter logistic (2PL) model adds a discrimination a_j:

$$P(X_{ij} = 1 \mid \theta_i) = \frac{\exp[a_j(\theta_i - b_j)]}{1 + \exp[a_j(\theta_i - b_j)]}.$$

A larger a_j gives a steeper curve: the item separates people just below b_j from people just above it more sharply. Values between about 0.8 and 2.5 are typical for good achievement items; values below about 0.5 mean the item hardly tells people apart.

The three-parameter logistic (3PL) model adds a lower asymptote c_j, often called the guessing parameter:

$$P(X_{ij} = 1 \mid \theta_i) = c_j + (1 - c_j)\frac{\exp[a_j(\theta_i - b_j)]}{1 + \exp[a_j(\theta_i - b_j)]}.$$

Even very low-ability people get a multiple-choice item right with probability c_j, roughly one over the number of options if they guess at random. With a lower asymptote, b_j is where the probability is $(1 + c_j)/2$ rather than 0.5.

mirt estimates the models in **slope-intercept form**, $a_j\theta_i + d_j$, which behaves better numerically. The two forms are related by $b_j = -d_j/a_j$. Use `coef(mod, IRTpars = TRUE)`, or mirtverse's `tidy()` (which uses `IRTpars = TRUE` by default), to see a and b.

2.2 Example 1: the LSAT section 7 items

`LSAT7` holds the response patterns of 1,000 people to five items from a section of the Law School Admission Test, stored as a frequency table. `expand.table()` turns it into one row per person.

```
# Five dichotomous LSAT items, one row per test taker.
resp <- expand.table(LSAT7)
```

We fit the three models. `itemtype` chooses the model and `verbose = FALSE` hides the iteration history.

```
rasch <- mirt(resp, 1, itemtype = "Rasch", verbose = FALSE)
twopl <- mirt(resp, 1, itemtype = "2PL",   verbose = FALSE)
threepl <- mirt(resp, 1, itemtype = "3PL", verbose = FALSE)
```

The item parameters in the IRT metric:

```
coef(twopl, IRTpars = TRUE, simplify = TRUE)$items
#>            a      b g u
#> Item.1 0.988 -1.879 0 1
#> Item.2 1.081 -0.748 0 1
#> Item.3 1.706 -1.058 0 1
#> Item.4 0.765 -0.635 0 1
#> Item.5 0.736 -2.520 0 1
```

The columns `g` and `u` are the lower and upper asymptotes, fixed at 0 and 1 for the 2PL. The same information as a tidy table, ready for a report:

```
tidy(twopl)
#> # A tibble: 10 x 5
#>    item   itemtype term  estimate std.error
#>    <chr>  <chr>    <chr>    <dbl>     <dbl>
#>  1 Item.1 2PL      a        0.988        NA
#>  2 Item.1 2PL      b       -1.88         NA
#>  3 Item.2 2PL      a        1.08         NA
#>  4 Item.2 2PL      b       -0.748        NA
#>  5 Item.3 2PL      a        1.71         NA
#>  6 Item.3 2PL      b       -1.06         NA
#>  7 Item.4 2PL      a        0.765        NA
#>  8 Item.4 2PL      b       -0.635        NA
#>  9 Item.5 2PL      a        0.736        NA
#> 10 Item.5 2PL      b       -2.52         NA
```

All five items have negative difficulties: this is an easy section for this group. Item 3 has the steepest slope, items 4 and 5 the flattest. The curves show it at a glance.

```
gg_trace(twopl, facet = FALSE)
```




Figure 2.1: Item characteristic curves of the 2PL model for the five LSAT7 items.

Compare the Rasch curves, which are parallel by construction, with the 2PL curves, which are not:

```
library(patchwork)
(gg_trace(rasch, facet = FALSE) + ggplot2::ggtitle("Rasch")) +
  (gg_trace(twopl, facet = FALSE) + ggplot2::ggtitle("2PL")) +
```

```
  plot_layout(guides = "collect")
```




Figure 2.2: Rasch curves (left) are parallel by construction; 2PL curves (right) can differ in slope.

The 3PL adds a lower asymptote for each item. With only five easy items there is very little information about what low-ability people do. Look at the c estimates (`g`) and their confidence intervals:

```
threepl_se <- mirt(resp, 1, itemtype = "3PL", SE = TRUE, verbose = FALSE)
tidy(threepl_se, conf.int = TRUE) |> subset(term == "g")
#> # A tibble: 5 x 7
#>   item   itemtype term   estimate std.error conf.low conf.high
#>   <chr>  <chr>    <chr>     <dbl>     <dbl>    <dbl>     <dbl>
#> 1 Item.1 3PL      g     0.0000703   0.00930 -0.0182    0.0183
#> 2 Item.2 3PL      g     0.295       0.140    0.0209    0.569
#> 3 Item.3 3PL      g     0.000258    0.0278  -0.0543    0.0548
#> 4 Item.4 3PL      g     0.0000506   0.00435 -0.00847   0.00857
#> 5 Item.5 3PL      g     0.000155    0.0209  -0.0408    0.0411
```

Four of the five lower asymptotes sit at essentially zero, on the boundary of the parameter space, and the one that does not (Item 2) has a confidence interval that runs from almost 0 to well over 0.5. The data say very little about guessing. Which model should we report? That is a question for Chapter 3. For now, notice that a model with more parameters is not automatically better: it has to be supported by the data.

`interpret()` describes the fitted model in plain language. Its *Items* section is a useful check on your own reading of the curves.

```
interpret(twopl)
#> Overview
#> --------
#> * A 2PL model with 1 dimension was fitted to 1000 respondents and 5 items (EM
#>   estimation).
#> * The estimation converged normally.
#>
#> Model fit
#> ---------
#> * Overall model fit is close: M2 = 11.94, df = 5, RMSEA = 0.037, CFI = 0.968,
#>   SRMSR = 0.032.
#> * The chi-square test is significant, but with large samples this is common;
#>   the RMSEA indicates the misfit is small in practical terms.
#>
#> Reliability
#> -----------
#> * Marginal reliability is 0.44 (low).
#> * Scores are too imprecise for decisions about individuals; consider adding
#>   items or using the scores only for group-level summaries.
#>
#> Targeting
#> ---------
#> * The average item location is -1.37 and the average person score is 0.00, so
#>   the test is relatively easy for this group.
#> * Measurement is most precise around theta = -1.08 (information = 1.47, SE =
#>   0.83).
#>
#> Items
#> -----
#> * Low item-total correlation: Item.5 (r = 0.17). These items relate weakly to
#>   the rest of the test.
#> * Misfit: Item.2 (S-X2 p < .001). The model does not describe responses to
#>   these items well (alpha = 0.01); inspect them with gg_empirical() or
#>   item_card().
#>
#> Local dependence
#> ----------------
#> * No item pairs show signs of local dependence (Q3).
#>
#> Person fit
#> ----------
#> * 2.1% of respondents have unusual response patterns (Zh < -1.96), which is
#>   within what chance alone would produce.
```

2.3 Example 2: a driving theory test with guessing

To see when the 3PL matters, we simulate a 20-item driving theory test with four options per question, taken by 3,000 learner drivers. Because we simulate, we know the true parameters and can check how well each model recovers them.

```
# Simulated 20-item, four-option test with real guessing (c around 0.2).
set.seed(202)
n_items <- 20
true <- data.frame(a = rlnorm(n_items, 0.2, 0.25),
                   b = seq(-1.5, 2, length.out = n_items),
                   c = rbeta(n_items, 5, 17))
resp <- simdata(a = matrix(true$a), d = matrix(-true$a * true$b),
                N = 3000, itemtype = "3PL", guess = true$c)
colnames(resp) <- sprintf("D%02d", 1:n_items)
```

The data chunk converts the true b into an intercept with $d = -ab$, because `simdata()` uses the slope-intercept form.

```
fit2 <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
fit3 <- mirt(resp, 1, itemtype = "3PL", verbose = FALSE)
est2 <- coef(fit2, IRTpars = TRUE, simplify = TRUE)$items
est3 <- coef(fit3, IRTpars = TRUE, simplify = TRUE)$items
recovery <- data.frame(
  model = rep(c("2PL", "3PL"), each = 2),
  parameter = rep(c("a", "b"), 2),
  bias = c(mean(est2[, "a"] - true$a), mean(est2[, "b"] - true$b),
           mean(est3[, "a"] - true$a), mean(est3[, "b"] - true$b)),
  rmse = c(sqrt(mean((est2[, "a"] - true$a)^2)), sqrt(mean((est2[, "b"] - true$b)^2)),
           sqrt(mean((est3[, "a"] - true$a)^2)), sqrt(mean((est3[, "b"] - true$b)^2))))
recovery
#>   model parameter    bias  rmse
#> 1   2PL         a -0.4681 0.583
#> 2   2PL         b -0.5731 0.698
#> 3   3PL         a  0.0622 0.338
#> 4   3PL         b -0.0188 0.379
```

When people really do guess, the 2PL absorbs the guessing into the other parameters: it **underestimates discrimination** and makes hard items look **easier** than they are. The 3PL recovers the parameters much better, and its lower asymptotes are close to the truth on average:

```
c(mean_true_c = mean(true$c), mean_estimated_c = mean(est3[, "g"]))
#>      mean_true_c mean_estimated_c
#>            0.239           0.226
```

The empirical item curve makes the problem visible. For the hardest item, the observed proportions correct for low-ability groups sit well above the 2PL curve, which heads towards zero:

```
gg_empirical(fit2, "D20") + gg_empirical(fit3, "D20")
```




Figure 2.3: Empirical item curve of the hardest driving-test item, D20, under the 2PL (left) and the 3PL (right).

What to take away. The 3PL is worth its extra parameters when items can be answered by guessing *and* there are enough low-ability test takers to estimate the lower asymptote: here 3,000 people and a range of difficulties. With small samples or easy tests, c is poorly determined, and a 2PL (or a 3PL with a prior on c) is often the safer choice.

2.4 Your turn

1. Using the 2PL for `LSAT7`, compute by hand the probability that a person at $\theta = -1$ answers Item 3 correctly. Check your answer with `probtrace(extract.item(twopl, 3), -1)`.
2. Fit the Rasch model to `LSAT7` and compare its difficulties with the 2PL difficulties. Which item moves most, and why?
3. In Example 2, refit the 3PL using only the first 300 test takers. What happens to the recovery of c?
4. Sketch (on paper) the curve of an item with $a = 0.3$ and $b = 0$. Would you keep this item on a test used to award licences?

Solutions

```
p <- coef(twopl, IRTpars = TRUE, simplify = TRUE)$items
plogis(p["Item.3", "a"] * (-1 - p["Item.3", "b"]))
#> [1] 0.525
probtrace(extract.item(twopl, 3), matrix(-1))
#>        P.0   P.1
```

```
#> [1,] 0.475 0.525

pr <- coef(rasch, IRTpars = TRUE, simplify = TRUE)$items
round(cbind(rasch = pr[, "b"], twopl = p[, "b"]), 2)
#>        rasch twopl
#> Item.1 -1.87 -1.88
#> Item.2 -0.79 -0.75
#> Item.3 -1.46 -1.06
#> Item.4 -0.52 -0.64
#> Item.5 -1.99 -2.52

small <- mirt(resp[1:300, ], 1, itemtype = "3PL", verbose = FALSE)
summary(coef(small, IRTpars = TRUE, simplify = TRUE)$items[, "g"] - true$c)
#>    Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
#> -0.3425 -0.0895  0.0558  0.0270  0.1615  0.3461
```

2. Items whose 2PL slope is far from the common Rasch slope move most, here Item 3 (the steepest) and Item 5 (one of the flattest). A flat item (small a) has a 2PL difficulty further from zero, because its curve only reaches 0.5 far out on the scale.
3. You may first see a warning that the EM algorithm stopped after 500 cycles: the 3PL is hard to estimate in small samples (Chapter 3). With 300 people the c estimates scatter much more widely around the truth, and some may be close to 0 or implausibly large. The estimates of a and b get worse too, because the three parameters trade off.
4. The curve is almost flat: the chance of a correct answer barely depends on ability. Such an item adds little information and some noise; it should go back to the item writers.

In the lab

> Lab 1, `run_lab("model-choice")`, asks you to compare the Rasch, 2PL and 3PL models for a real-sized certification exam and to defend your choice to the board. Chapter 3 gives you the tools for that comparison.

Further reading

Embretson and Reise (2000) give an accessible introduction for psychologists; Hambleton, Swaminathan and Rogers (1991) a short classic; de Ayala (2022) a thorough modern treatment. Chalmers (2012) describes the mirt package.

Chapter 3

Estimation and comparing models

Learning goals. After this chapter you can

- describe marginal maximum likelihood estimation in words;
- check whether a model has converged, and know what to do when it has not;
- compare nested models with a likelihood-ratio test and any models with information criteria;
- judge overall model fit with M2, RMSEA, SRMSR and CFI;
- explain why AIC and BIC can disagree, and what sample size has to do with it.

Key terms: calibration, marginal maximum likelihood, convergence, standard error, likelihood-ratio test, information criteria, M2, RMSEA, SRMSR, CFI and TLI.

3.1 The ideas

Calibration means estimating the item parameters. We never observe θ, so we cannot simply regress responses on it. **Marginal maximum likelihood** (MML) instead assumes a distribution for θ in the population, usually standard normal, and integrates it out: the likelihood of a response pattern is its probability averaged over all possible values of θ. The item parameters are chosen to make the observed patterns as likely as possible (Bock and Aitkin 1981).

mirt maximizes this likelihood with the **EM algorithm** by default. It replaces the integral with a sum over a grid of *quadrature points* and alternates two steps: the E-step works out, for every person, how likely each grid point is given their responses and the current item parameters; the M-step updates each item's parameters as if those expected counts were data. The cycles stop when the parameters stop changing, which is called **convergence**. If the algorithm hits its limit of 500 cycles first, mirt warns you, and the estimates should not be trusted.

Once a model has converged, we compare it with alternatives.

- **Likelihood-ratio test (LRT).** For *nested* models (the Rasch model is a 2PL with equal slopes; the 2PL is a 3PL with $c = 0$), twice the difference in log-likelihoods is approx-

imately chi-square distributed with degrees of freedom equal to the difference in the number of parameters. With large samples even trivial improvements become significant.

- **Information criteria.** AIC $= -2\log L + 2k$ and BIC $= -2\log L + k\log N$, where k is the number of parameters and N the sample size. Smaller is better. BIC punishes extra parameters more heavily once $N > 7$, so it favours simpler models. A difference of 10 or more BIC points is usually read as strong evidence.
- **Absolute fit.** The **M2** statistic (Maydeu-Olivares and Joe 2006) compares observed and expected proportions for single items and pairs of items. RMSEA (below about 0.05 is close fit), SRMSR (below about 0.05) and CFI (above about 0.95) are effect sizes built from it. Treat the cut-offs as rough guides, not rules.

3.2 Example 1: a test the Rasch model fits

`LSAT6` is another five-item section of the Law School Admission Test, with 1,000 test takers. It is a textbook example of data the Rasch model fits well.

```
# Five dichotomous LSAT items, one row per test taker.
resp <- expand.table(LSAT6)
```

Fit the models one at a time, check convergence, and compare them:

```
rasch <- mirt(resp, 1, itemtype = "Rasch", verbose = FALSE)
twopl <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
extract.mirt(rasch, "converged")
#> [1] TRUE
extract.mirt(twopl, "iterations")
#> [1] 22
anova(rasch, twopl)
#>        AIC SABIC   HQ  BIC logLik    X2 df     p
#> rasch 4946  4956 4957 4975  -2467
#> twopl 4953  4971 4972 5002  -2467 0.569  4 0.966
```

The 2PL improves the log-likelihood by a fraction of a point for four extra parameters, so the LRT is far from significant and both AIC and BIC prefer the Rasch model. `glance()` adds the absolute fit statistics:

```
glance(rasch)[, c("logLik", "AIC", "BIC", "M2", "df", "p.value", "RMSEA", "SRMSR", "CFI")]
#> # A tibble: 1 x 9
#>   logLik   AIC   BIC    M2    df p.value RMSEA  SRMSR   CFI
#>    <dbl> <dbl> <dbl> <dbl> <int>   <dbl> <dbl>  <dbl> <dbl>
#> 1 -2467. 4946. 4975.  5.29     9   0.808     0 0.0224     1
```

`select_model()` runs all of this in one call. It fits the Rasch, 2PL and 3PL models (or the polytomous equivalents), checks convergence, ranks them by BIC, runs the LRTs between nested pairs and explains its recommendation.

```
sel <- select_model(resp, verbose = FALSE)
sel
#> mirtverse model selection (ranked by BIC)
#>
#>  model npar logLik  AIC  BIC SABIC RMSEA CFI delta weight
#>  Rasch    6  -2467 4946 4975  4956     0   1   0.0      1
#>    2PL   10  -2467 4953 5002  4971     0   1  27.1      0
#>    3PL   15  -2467 4963 5037  4989    NA  NA  61.6      0
#>
#> The Rasch model is recommended because it has the lowest BIC (4975.3). The
#> runner-up, 2PL, is 27.1 BIC points worse, which is very strong evidence for the
#> Rasch model. Likelihood-ratio test Rasch vs. 2PL: chi-square(4) = 0.57, p =
#> .966; the extra parameters of 2PL are not needed. Likelihood-ratio test Rasch
#> vs. 3PL: chi-square(9) = 0.54, p = 1.000; the extra parameters of 3PL are not
#> needed. Absolute fit of the Rasch model: RMSEA = 0.000 (close fit), CFI =
#> 1.000, SRMSR = 0.022.
```

```
autoplot(sel)
```




Figure 3.1: Model comparison for LSAT6: each model's information criterion relative to the best model (0 = best).

The `weight` column converts BIC differences into the relative support for each model; here nearly all of it goes to the Rasch model.

3.3 Example 2: when the criteria disagree

Now take the 32 science items of `SAT12`, scored with the corrected key from Chapter 1.

```
# SAT12 science items, scored with the corrected key (item 32 keyed 3).
key <- c(1,4,5,2,3,1,2,1,3,1,2,4,2,1,5,3,4,4,1,4,3,3,4,1,3,5,1,3,1,5,4,3)
resp <- key2binary(SAT12, key)
```

```
sel <- select_model(resp, verbose = FALSE)
sel
#> mirtverse model selection (ranked by BIC)
#>
#>  model npar logLik   AIC   BIC SABIC RMSEA   CFI delta weight
#>    2PL   64  -9622 19373 19654 19451 0.029 0.953   0.0      1
#>  Rasch   33  -9768 19602 19747 19642 0.039 0.905  92.5      0
#>    3PL   96  -9572 19337 19759 19454 0.022 0.975 104.5      0
#>
#> The 2PL model is recommended because it has the lowest BIC (19654.2). The
#> runner-up, Rasch, is 92.5 BIC points worse, which is very strong evidence for
#> the 2PL model. Likelihood-ratio test Rasch vs. 2PL: chi-square(31) = 290.83, p
#> < .001; the 2PL model fits significantly better. Likelihood-ratio test 2PL vs.
#> 3PL: chi-square(32) = 100.16, p < .001; the 3PL model fits significantly
#> better. Note the tension: the likelihood-ratio test prefers 3PL, while BIC
#> penalizes extra parameters and prefers 2PL. Choose 2PL if parsimony matters
#> most, or 3PL if fit to these data matters most. AIC would instead select the
#> 3PL model. Absolute fit of the 2PL model: RMSEA = 0.029 (close fit), CFI =
#> 0.953, SRMSR = 0.045.
sel$lrt
#> # A tibble: 3 x 5
#>   simpler complex    X2    df  p.value
#>   <chr>   <chr>   <dbl> <int>    <dbl>
#> 1 Rasch   2PL      291.    31 5.30e-44
#> 2 Rasch   3PL      391.    63 7.62e-49
#> 3 2PL     3PL      100.    32 6.00e- 9
```

This time the evidence is mixed. The LRT and AIC prefer the 3PL, while BIC prefers the 2PL. Neither is "wrong": they answer different questions. The LRT asks whether the extra 32 guessing parameters improve fit beyond chance, and with 600 people the answer is yes. BIC asks which model is more likely to be the better description once we account for the cost of 32 more parameters, and it says the 2PL. A sensible report states the tension and the reason for the final choice: if scores will be used for decisions about low-scoring students, where guessing matters most, the 3PL may be worth its cost; for a short research scale, the 2PL is easier to defend.

3.3.1 Small samples and convergence

The 3PL is the hardest of the three to estimate, because the lower asymptote is determined only by what low-ability people do. With 200 students the EM algorithm may not converge at all:

```
set.seed(303)
small <- resp[sample(nrow(resp), 200), ]
```

```
fit_small <- mirt(small, 1, itemtype = "3PL", verbose = FALSE)
extract.mirt(fit_small, "converged")
#> [1] FALSE
summary(coef(fit_small, IRTpars = TRUE, simplify = TRUE)$items[, "g"])
#>     Min.  1st Qu.   Median     Mean  3rd Qu.     Max.
#> 0.000276 0.002136 0.079776 0.125231 0.207500 0.500034
```

Some lower asymptotes drift to zero and others to implausibly large values. Three common remedies are to use a 2PL, to fix c at a sensible value (for five-option items, 0.2), or to put a **prior** on c so that the data only move it away from a plausible value when they have something to say. In mirt a prior is part of the model syntax. Here a beta(5, 17) prior centres c near 0.2 (`expbeta` applies it on the scale mirt uses internally):

```
spec <- mirt.model("F = 1-32
                    PRIOR = (1-32, g, expbeta, 5, 17)")
fit_prior <- mirt(small, spec, itemtype = "3PL", verbose = FALSE)
#> Warning: Observed log-likelihood may still be increasing.
#>   Final log-likelihood values were:
#>   -3154.689, -3151.159, -3149.755
extract.mirt(fit_prior, "converged")
#> [1] TRUE
summary(coef(fit_prior, IRTpars = TRUE, simplify = TRUE)$items[, "g"])
#>    Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
#>   0.109   0.181   0.192   0.187   0.195   0.235
```

With the prior the model converges and the lower asymptotes stay in a believable range. Report priors when you use them: they are part of the model.

3.4 Your turn

1. For `LSAT6`, compute the LRT statistic for Rasch versus 2PL by hand from the two log-likelihoods, and check it against `anova()`.
2. Fit the 2PL to `SAT12` with `quadpts = 15` and with the default of 61 points. Do the item parameters change? What does that tell you?
3. Draw 300 students from `SAT12` and rerun `select_model()`. Does the recommendation change? Repeat with another random sample.
4. A colleague reports "the 3PL fitted significantly better ($p < .001$), so we used it". What would you ask them?

Solutions

```
ll <- c(extract.mirt(rasch, "logLik"), extract.mirt(twopl, "logLik"))
lrt <- 2 * (ll[2] - ll[1])
c(X2 = lrt, df = 4, p = pchisq(lrt, 4, lower.tail = FALSE))
```

```
#>    X2    df     p
#> 0.569 4.000 0.966

m15 <- mirt(resp, 1, "2PL", quadpts = 15, verbose = FALSE)
m61 <- mirt(resp, 1, "2PL", quadpts = 61, verbose = FALSE)
max(abs(coef(m15, simplify = TRUE)$items - coef(m61, simplify = TRUE)$items))
#> [1] 0.142
```

2. With only 15 points some estimates move by about 0.1 on the slope-intercept scale; between 61 (the default for one dimension) and more points they hardly move at all. Fewer points trade accuracy for speed, which matters mainly for models with several dimensions.
3. With fewer people, BIC's penalty matters relatively more and the likelihood gains of the 3PL are smaller, so the 2PL (or even the Rasch model) is chosen more often. Model choice depends on the sample, not only on the items.
4. Did the model converge? What did BIC say? How large is the sample? Are the guessing estimates plausible, and what were their standard errors? Would the scores or decisions differ between the 2PL and the 3PL?

In the lab

> Lab 1, `run_lab("model-choice")`, ends with a model choice you have to justify to a certification board, using the same evidence as this chapter: convergence, likelihood-ratio tests, information criteria and absolute fit.

Further reading

Bock and Aitkin (1981) introduced the EM approach to marginal maximum likelihood. Maydeu-Olivares and Joe (2006) describe M2. de Ayala (2022) discusses model comparison and fit in detail.

Chapter 4

Dimensionality and local independence

Learning goals. After this chapter you can

- explain the assumptions of unidimensionality and local independence;
- compare one- and two-factor models and read rotated factor loadings;
- fit a confirmatory model in which each item measures a named dimension;
- read standardized residuals and Yen's Q3, and tell local dependence from a second trait;
- choose a remedy for locally dependent items.

Key terms: dimensionality, local independence, local dependence, Q3, multidimensional IRT.

4.1 The ideas

The models in Chapter 2 make two related assumptions. **Unidimensionality** says that one latent trait accounts for the relationships among the items. **Local independence** says that once we know a person's θ, their responses to different items are independent: the only reason two items correlate is that both depend on θ.

Both can fail, in different ways.

- A test may measure **two or more traits**, for example reading and arithmetic in a set of mathematics word problems. Then a one-factor model forces two traits into one score, and the items of the smaller dimension look poorly discriminating.
- A **small cluster of items** may share something beyond the trait: a common reading passage, a shared stimulus, near-identical wording, or an item whose answer gives away the next. These pairs or clusters are *locally dependent*. They look like extra-good items, they inflate reliability, and they distort the item parameters.

The tools differ too. For the first problem we compare models with one and two factors and look at the factor loadings. For the second we look at what is left over after fitting a one-factor model: if local independence holds, the residual correlations between item pairs should be

close to zero. Yen's **Q3** statistic (Yen 1984) is the correlation between two items' residuals. Values well above the average Q3 (often by 0.2 or more) flag dependent pairs.

4.2 Example 1: a mathematics test with a reading dimension

We simulate a 24-item mathematics test taken by 1,500 Grade 8 students. Items M01 to M12 are calculation items. Items W01 to W12 are word problems that also depend on reading, which correlates 0.5 with calculation skill.

```
# Simulated 24-item test, two correlated traits (r = 0.5), 12 items each.
set.seed(404)
a <- cbind(c(runif(12, 1.0, 2.0), runif(12, 0.3, 0.6)),
           c(rep(0, 12),          runif(12, 1.0, 1.8)))
d <- matrix(rnorm(24, 0, 0.8))
sigma <- matrix(c(1, 0.5, 0.5, 1), 2)
resp <- simdata(a, d, N = 1500, itemtype = "2PL", sigma = sigma)
colnames(resp) <- c(sprintf("M%02d", 1:12), sprintf("W%02d", 1:12))
```

First, an exploratory comparison of one and two factors. We keep a copy of the data as `math` for the exercises.

```
math <- resp
f1 <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
f2 <- mirt(resp, 2, itemtype = "2PL", verbose = FALSE)
anova(f1, f2)
#>      AIC SABIC    HQ   BIC logLik      X2 df p
#> f1 41008 41111 41103 41263 -20456
#> f2 40185 40337 40326 40563 -20022 868.777 23 0
```

The two-factor model is far better on every criterion. `summary()` shows the standardized loadings after an oblique rotation, which lets the factors correlate:

```
summary(f2, rotate = "oblimin", suppress = 0.25)
#>
#> Rotation:  oblimin
#>
#> Rotated factor loadings:
#>
#>        F1    F2    h2
#> M01       0.708 0.509
#> M02       0.717 0.504
#> M03       0.663 0.453
#> M04       0.628 0.453
#> M05       0.581 0.360
#> M06       0.598 0.394
#> M07       0.665 0.398
```

```
#> M08       0.559 0.281
#> M09       0.473 0.233
#> M10       0.617 0.390
#> M11       0.715 0.539
#> M12       0.724 0.492
#> W01 0.634       0.428
#> W02 0.520       0.430
#> W03 0.751       0.572
#> W04 0.646       0.444
#> W05 0.588       0.373
#> W06 0.737       0.512
#> W07 0.560       0.451
#> W08 0.785       0.600
#> W09 0.697       0.484
#> W10 0.766       0.570
#> W11 0.775       0.555
#> W12 0.716       0.486
#>
#> Rotated SS loadings:  5.67 5
#>
#> Factor correlations:
#>
#>       F1 F2
#> F1 1.000
#> F2 0.654  1
```

The calculation items load on one factor and the word problems on the other. The factor correlation is higher than the 0.5 we simulated between the two traits, because the word problems also need calculation skill: the rotation cannot separate that shared part cleanly, so some of it shows up as correlation between the factors. The one-factor fit statistics give the same message from the other side:

```
rbind(one_factor = glance(f1)[, c("RMSEA", "SRMSR", "CFI")],
      two_factor = glance(f2)[, c("RMSEA", "SRMSR", "CFI")])
#> # A tibble: 2 x 3
#>    RMSEA  SRMSR   CFI
#> *  <dbl>  <dbl> <dbl>
#> 1 0.0644 0.0518 0.936
#> 2 0      0.0173 1
```

Exploratory models are useful for finding structure. When the structure is known from the test blueprint, a **confirmatory** model states it directly. Each item loads only on its own factor, and the factor correlation is estimated (`COV = F1*F2`):

```
spec <- mirt.model("Calc    = 1-12
                    Reading = 13-24
                    COV     = Calc*Reading")
cfa <- mirt(resp, spec, itemtype = "2PL", verbose = FALSE)
coef(cfa, simplify = TRUE)$cov
#>          Calc Reading
#> Calc    1.000   0.676
#> Reading 0.676   1.000
anova(cfa, f2)
#>       AIC SABIC    HQ   BIC logLik     X2 df     p
#> cfa 40174 40279 40271 40434 -20038
#> f2  40185 40337 40326 40563 -20022 32.658 22 0.067
```

The confirmatory model is nearly as good as the exploratory one with far fewer parameters, so BIC prefers it. What should we report to the school? That depends on use. Two subscores are defensible if each is reliable enough (Chapter 6); a single total score mixes two skills, and students with weak reading will look weaker at mathematics than they are.

4.3 Example 2: a reading passage that ties four items together

In this test of 20 items, items R05 to R08 all refer to the same passage. Students who happen to understand the passage well do better on all four than their general reading ability predicts. We simulate this with a small extra factor that only those four items share.

```
# Simulated 20-item reading test; R05-R08 share a passage (testlet effect).
set.seed(405)
a_gen <- runif(20, 1.0, 1.8)
a_pas <- c(rep(0, 4), rep(2.0, 4), rep(0, 12))
resp <- simdata(cbind(a_gen, a_pas), matrix(rnorm(20, 0, 0.7)),
                N = 1200, itemtype = "2PL")
colnames(resp) <- sprintf("R%02d", 1:20)
```

We fit an ordinary unidimensional 2PL, as an analyst who did not know about the passage would, and look at the Q3 matrix.

```
uni <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
gg_q3(uni)
```




Figure 4.1: Q3 residual correlations from a unidimensional 2PL fitted to the reading test with a four-item passage.

The six pairs among R05 to R08 stand out. Most other Q3 values are slightly negative, which is normal: residuals are a little negatively correlated on average, so we judge a pair against the average Q3 rather than against zero. The numbers behind the plot:

```
q3 <- residuals(uni, type = "Q3", verbose = FALSE)
round(q3[5:8, 5:8], 2)
#>      R05  R06  R07  R08
#> R05 1.00 0.31 0.25 0.28
#> R06 0.31 1.00 0.28 0.26
#> R07 0.25 0.28 1.00 0.24
#> R08 0.28 0.26 0.24 1.00
```

Local dependence has a cost. The unidimensional model has nowhere to put the passage effect, so it bends the item parameters to accommodate it and treats part of the passage effect as reading ability. Remedy 1 below shows how different the passage items look once the dependence is modelled.

There are three common remedies.

1. **Model the dependence.** A *testlet* or *bifactor* model gives the passage items a specific factor of their own, uncorrelated with the general factor. `bfactor()` fits it; its second argument says which specific factor each item belongs to (`NA` for none).

```
specific <- c(rep(NA, 4), rep(1, 4), rep(NA, 12))
bf <- bfactor(resp, specific, verbose = FALSE)
anova(uni, bf)
#>       AIC SABIC    HQ   BIC logLik      X2 df p
#> uni 28458 28534 28534 28661 -14189
#> bf  27901 27985 27985 28125 -13906 564.869  4 0
round(coef(bf, simplify = TRUE)$items[3:10, c("a1", "a2")], 2)
#>       a1   a2
#> R03 1.51 0.00
#> R04 0.93 0.00
#> R05 1.44 2.11
#> R06 1.45 2.20
#> R07 1.27 1.76
#> R08 1.88 1.99
#> R09 1.38 0.00
#> R10 1.31 0.00
```

The passage effect now has its own slope (`a2`), and the general slopes (`a1`) of R05 to R08 are higher than in the unidimensional model, which had diluted them. Compare them with `coef(uni, simplify = TRUE)$items[5:8, "a1"]`. Likelihood-ratio test and BIC both favour the bifactor model.

2. **Combine the items.** Sum R05 to R08 into one polytomous "super-item" scored 0 to 4 and fit a polytomous model (Chapter 8). This is simple and robust, at the cost of some information.
3. **Drop or rewrite items** in a future form, so that no two items depend on each other beyond the trait.

4.4 Your turn

1. In Example 1, compute the sum score of the word problems and of the calculation items separately. How strongly do they correlate? Why is this lower than the factor correlation?
2. Use `select_model(resp, dims = 1:2)` on the data of Example 1. Which model does it choose?
3. In Example 2, compare the empirical reliability of the scores (`empirical_rxx()` on `fscores(..., full.scores.SE = TRUE)`) from the unidimensional model with that of the general factor of the bifactor model. Which one would you report, and why?
4. Make the super-item from R05 to R08, fit a graded model to the 17 items, and check the Q3 matrix again.

Solutions

```
cor(rowSums(math[, 1:12]), rowSums(math[, 13:24]))
#> [1] 0.554
```

1. Sum scores contain measurement error, which attenuates (weakens) the correlation; the factor correlation is corrected for it.

```
select_model(math, dims = 1:2, verbose = FALSE)
#> mirtverse model selection (ranked by BIC)
#>
#>     model npar logLik   AIC   BIC SABIC RMSEA   CFI delta weight
#>  2PL (2F)   71 -20022 40185 40563 40337 0.000 1.000     0      1
#>     Rasch   25 -20526 41102 41235 41156 0.064 0.931   673      0
#>       2PL   48 -20456 41008 41263 41111 0.064 0.936   701      0
#>       3PL   72 -20450 41044 41426 41198 0.064 0.942   864      0
#>
#> The 2PL (2F) model is recommended because it has the lowest BIC (40562.7). The
#> runner-up, Rasch, is 672.6 BIC points worse, which is very strong evidence for
#> the 2PL (2F) model. Likelihood-ratio test Rasch vs. 2PL (2F): chi-square(46) =
#> 1008.97, p < .001; the 2PL (2F) model fits significantly better.
#> Likelihood-ratio test 2PL vs. 2PL (2F): chi-square(23) = 868.78, p < .001; the
#> 2PL (2F) model fits significantly better. Absolute fit of the 2PL (2F) model:
#> RMSEA = 0.000 (close fit), CFI = 1.000, SRMSR = 0.017.
```

2. It fits one- and two-factor versions of each candidate and should prefer a two-factor model, because the second dimension is strong.

```
empirical_rxx(fscores(uni, full.scores.SE = TRUE))
#>   F1
#> 0.85
empirical_rxx(fscores(bf, full.scores.SE = TRUE))
#>     G    S1
#> 0.838 0.587
```

3. The unidimensional model reports a somewhat higher reliability, because it counts the shared passage effect as signal about reading. The general factor of the bifactor model gives the more honest figure. With one small passage the difference is modest; with several passages it grows.

```
super <- data.frame(resp[, -(5:8)], R05_08 = rowSums(resp[, 5:8]))
sup <- mirt(super, 1, itemtype = c(rep("2PL", 16), "graded"), verbose = FALSE)
q3s <- residuals(sup, type = "Q3", verbose = FALSE)
max(abs(q3s[upper.tri(q3s)]))
#> [1] 0.131
```

4. The super-item removes the dependent pairs, and the largest remaining Q3 is small.

In the lab

> Lab 1, `run_lab("model-choice")`, includes a dimensionality check and a local dependence screen on a certification exam. Decide for yourself whether anything needs fixing before you choose a model.

Further reading

Yen (1984) introduced Q3 and showed how local dependence affects parameter estimates and equating. Embretson and Reise (2000) cover multidimensional and bifactor models.

Chapter 5

Item fit, person fit and item quality

Learning goals. After this chapter you can

- explain what item fit means and why it is always fit *to a model*;
- compute and read the S-X^2 item-fit statistic and its RMSEA;
- compare an empirical item curve with the model curve;
- flag aberrant response patterns with the Zh person-fit statistic, and say what can cause them;
- summarize an item's health for a review meeting.

Key terms: item fit, S-X^2, empirical item curve, person fit, Zh, model fit.

5.1 The ideas

Chapter 3 asked whether a model fits the test *as a whole*. Item fit asks the same question one item at a time: does the item's curve describe how people at different ability levels actually responded?

The most widely used statistic is Orlando and Thissen's **S-X^2** (Orlando and Thissen 2000). It groups people by their sum score, compares the observed proportion correct in each group with the proportion the model predicts, and adds up the squared differences. A small p-value means the item does not follow the model. Because a test has many items, some will be flagged by chance, so it is good practice to adjust the p-values (for example with the Benjamini-Hochberg method) and to look at an effect size too: mirt reports an RMSEA for each item, where values below about 0.05 mean the misfit is small in practice.

Item fit is always fit *to a particular model*. An item with an unusually steep curve fits the 2PL perfectly well but misfits the Rasch model, which forces all slopes to be equal. A misfitting item is a question, not a verdict: look at the empirical curve, the content and the key before you decide.

Person fit turns the question around: does a person's response pattern look like what the

model expects of someone at their θ? The **Zh** statistic (Drasgow et al. 1985) is a standardized log-likelihood of the pattern. Values near zero are typical; large negative values (below about -2) mean the pattern is unlikely: a strong student who misses easy items, or a weak one who gets the hardest items right. Causes include careless responding, guessing, cheating, misaligned answer sheets, fatigue and atypical instruction. Zh flags a pattern for a closer look; it never proves misconduct.

5.2 Example 1: the same items under two models

We return to the `SAT12` science items, scored with the corrected key.

```
# SAT12 science items, scored with the corrected key (item 32 keyed 3).
key <- c(1,4,5,2,3,1,2,1,3,1,2,4,2,1,5,3,4,4,1,4,3,3,4,1,3,5,1,3,1,5,4,3)
resp <- key2binary(SAT12, key)
```

First, the Rasch model. `gg_itemfit()` plots each item's S-X² RMSEA and marks the items whose p-value is below `alpha`.

```
rasch <- mirt(resp, 1, itemtype = "Rasch", verbose = FALSE)
gg_itemfit(rasch, p_adjust = "BH")
```




Figure 5.1: S-X^2 RMSEA of each SAT12 item under the Rasch model; flagged items are marked.

`item_table()` puts the classical statistics, IRT parameters, fit and flags in one table. Here are

the items that misfit the Rasch model most:

```
tab_r <- item_table(rasch, p_adjust = "BH")
tab_r[order(tab_r$p.value), c("item", "item_total_r", "location", "S_X2", "df",
                              "RMSEA", "p.value")][1:5, ]
#> # A tibble: 5 x 7
#>   item    item_total_r location  S_X2    df  RMSEA  p.value
#>   <chr>          <dbl>    <dbl> <dbl> <dbl>  <dbl>    <dbl>
#> 1 Item.12       0.0685    0.394  91.7    18 0.0827 2.26e-10
#> 2 Item.30       0.157     0.274  60.7    18 0.0629 2.52e- 5
#> 3 Item.4        0.236     0.574  53.1    18 0.0571 2.69e- 4
#> 4 Item.31       0.425    -1.85   41.3    17 0.0488 6.80e- 3
#> 5 Item.32       0.203     0.258  41.4    18 0.0466 8.45e- 3
```

The worst-fitting items include items whose item-total correlation is far from the typical value: either much flatter or much steeper than the common slope the Rasch model imposes. Now fit the 2PL, which lets the slopes vary:

```
twopl <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
tab_2 <- item_table(twopl, p_adjust = "BH")
c(misfit_rasch = sum(tab_r$p.value < 0.01), misfit_2pl = sum(tab_2$p.value < 0.01))
#> misfit_rasch   misfit_2pl
#>            5            0
```

The 2PL removes the misfit. Whether that is the right response depends on the purpose. A Rasch programme would rather revise or drop the items that do not fit, because equal slopes give the sum score its simple meaning; a 2PL programme would keep them.

An **empirical item curve** shows the misfit directly. People are grouped by their estimated θ, and the observed proportion correct in each group is plotted against the model curve:

```
worst <- tab_r$item[which.min(tab_r$p.value)]
gg_empirical(rasch, worst) + gg_empirical(twopl, worst)
```




Figure 5.2: Empirical item curve of the worst-fitting item under the Rasch model (left) and the 2PL (right).

Under the Rasch model the observed points do not follow the curve; under the 2PL they do. Fit is not the only thing that matters about an item, though. `item_table()` also flags items that are very easy or very hard, or that discriminate poorly:

```
tab_2[tab_2$flag != "", c("item", "mean", "item_total_r", "discrimination",
                          "location", "flag")]
#> # A tibble: 7 x 6
#>   item     mean item_total_r discrimination location flag
#>   <chr>   <dbl>        <dbl>          <dbl>    <dbl> <chr>
#> 1 Item.9  0.885       0.123           0.518   -4.13  extreme location; low item~
#> 2 Item.11 0.983       0.150           1.69    -3.07  extreme location; low item~
#> 3 Item.12 0.415       0.0685          0.156    2.21  low discrimination; low it~
#> 4 Item.17 0.963       0.199           1.53    -2.71  low item-total correlation
#> 5 Item.21 0.915       0.131           0.600   -4.19  extreme location; low item~
#> 6 Item.30 0.44        0.157           0.383    0.647 low discrimination; low it~
#> 7 Item.32 0.443       0.203           0.490    0.484 low discrimination
```

An **item health card** collects everything about one item on a page, with a traffic-light status, for item review meetings:

```
weak <- tab_2$item[which.min(tab_2$discrimination)]
item_card(twopl, weak)
```




Figure 5.3: Item health card of the SAT12 item with the lowest discrimination under the 2PL.

`item_cards(twopl, file = "cards.html")` writes a card for every item into one HTML page that reviewers can open in a browser.

5.3 Example 2: finding aberrant response patterns

We simulate a 30-item quiz taken by 1,000 students. Most students respond according to a 2PL model, but 40 answered at random (careless responding) and 30 weak students somehow got the ten hardest items right (perhaps they saw them in advance). We record who is who so we can check the person-fit statistic.

```
# Simulated 30-item quiz: 930 regular students, 40 random responders and
# 30 weak students who know the 10 hardest items. `type` records which.
set.seed(505)
a <- matrix(rlnorm(30, 0.2, 0.2)); b <- seq(-2, 2, length.out = 30)
resp <- simdata(a, matrix(-a * b), N = 1000, itemtype = "2PL")
colnames(resp) <- sprintf("Q%02d", 1:30)
type <- rep(c("regular", "random", "preknowledge"), c(930, 40, 30))
resp[type == "random", ] <- rbinom(40 * 30, 1, 0.5)
weak <- simdata(a, matrix(-a * b), N = 30, itemtype = "2PL",
                Theta = matrix(rnorm(30, -1.2, 0.3)))
weak[, 21:30] <- 1
resp[type == "preknowledge", ] <- weak
```

`augment()` adds each person's score, its standard error and, with `person_fit = TRUE`, the Zh statistic to the data:

```
mod <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
scores <- augment(mod, person_fit = TRUE)
scores$type <- type
head(scores[, c(".F1", ".se_F1", ".Zh", "type")])
#> # A tibble: 6 x 4
#>       .F1 .se_F1    .Zh type
#>     <dbl>  <dbl>  <dbl> <chr>
#> 1 -1.74    0.472  0.166 regular
#> 2  1.48    0.406  0.970 regular
#> 3 -0.422   0.388  0.809 regular
#> 4 -0.0768  0.376 -0.238 regular
#> 5  1.01    0.380  1.03  regular
#> 6 -0.822   0.407 -0.218 regular
```

How well does Zh separate the groups?

```
library(ggplot2)
ggplot(scores, aes(.Zh, fill = type)) +
  geom_histogram(bins = 40, position = "identity", alpha = 0.6) +
  geom_vline(xintercept = -2, linetype = 2) +
  labs(x = "Zh person-fit statistic", y = "Students", fill = NULL) +
  theme_mirtverse()
```




Figure 5.4: Distribution of the Zh person-fit statistic for regular students, random responders and students with pre-knowledge.

```
aggregate(.Zh < -2 ~ type, data = scores, FUN = mean)
#>           type .Zh < -2
#> 1 preknowledge  1.00000
#> 2       random  0.85000
```

```
#> 3      regular  0.00323
```

All of the students with pre-knowledge are flagged: getting the hardest items right while missing easier ones is very unlikely under the model. Most random responders are flagged too, because on a 30-item test with a wide range of difficulties a coin-flip pattern contradicts the model again and again. Only a handful of regular students fall below -2. Real data are rarely this clean: aberrance is usually milder, and only part of a test may be affected (the last items, say, for a student who ran out of time). That is why Zh is a screening tool: flagged patterns need a human look, and often other evidence such as response times (see the response-time article).

Do the aberrant patterns distort the item parameters? We can check by refitting without the flagged students and comparing both sets of difficulties for the ten hardest items with the values used to simulate the data:

```
clean <- mirt(resp[scores$.Zh >= -2, ], 1, itemtype = "2PL", verbose = FALSE)
b_all <- coef(mod, IRTpars = TRUE, simplify = TRUE)$items[21:30, "b"]
b_clean <- coef(clean, IRTpars = TRUE, simplify = TRUE)$items[21:30, "b"]
round(c(error_all = mean(abs(b_all - b[21:30])),
        error_clean = mean(abs(b_clean - b[21:30]))), 3)
#>   error_all error_clean
#>       0.145       0.140
```

Here the difference is small, because only 7% of the students are aberrant and the model is estimated from everyone else. With more contamination, or with pre-knowledge concentrated on a few items, the damage grows, and removing flagged cases before calibration is common practice.

5.4 Your turn

1. Plot the empirical curve of the best-fitting item under the Rasch model in Example 1. How does it compare with the worst-fitting one?
2. Rerun `gg_itemfit()` for the Rasch model without the p-value adjustment. How many more items are flagged? Which result would you report?
3. In Example 2, which value of the Zh cut-off flags at most 5% of the regular students? How many students with pre-knowledge does it catch?
4. Write two sentences to a school principal explaining what a flagged person-fit statistic means and what it does not mean.

Solutions

```
best <- tab_r$item[which.max(tab_r$p.value)]
gg_empirical(rasch, best)
```




Figure 5.5: Empirical item curve of the best-fitting item under the Rasch model.

```
sum(item_table(rasch)$p.value < 0.01)
#> [1] 8
cut5 <- quantile(scores$.Zh[type == "regular"], 0.05)
c(cutoff = unname(cut5),
  caught = mean(scores$.Zh[type == "preknowledge"] < cut5))
#> cutoff caught
#> -0.945  1.000
```

2. Without adjustment more items are flagged, some only by chance. With 32 tests, report the adjusted results, and look at the RMSEA to judge size.
3. For example: "This student's pattern of right and wrong answers is unusual for someone with their overall score, so we checked it more closely. It is not evidence of cheating on its own; it can also come from guessing, fatigue or a mismatch between what was taught and what was tested."

In the lab

> Lab 1, `run_lab("model-choice")`, includes an item fit step in which you decide which items, if any, a certification board should drop or send back to the item writers.

Further reading

Orlando and Thissen (2000) introduced S-X^2. Drasgow, Levine and Williams (1985) introduced the standardized person-fit index Zh. de Ayala (2022) discusses item and person fit at length.

Chapter 6

Information, precision and reliability

Learning goals. After this chapter you can

- read item and test information curves;
- convert information into a conditional standard error of measurement;
- compute marginal and empirical reliability, and explain why a single reliability coefficient hides how precision changes along the scale;
- use information to judge whether a test is well targeted for a decision.

Key terms: item information, test information, standard error of measurement, marginal reliability, targeting, precision.

6.1 The ideas

In classical test theory a test has one standard error of measurement for everyone. In IRT, precision depends on where you are on the scale. An item tells us most about people whose ability is close to its difficulty: for them the outcome is most uncertain, so observing it is most informative. The **item information function** of a 2PL item is

$$I_j(\theta) = a_j^2 \, P_j(\theta) \, [1 - P_j(\theta)],$$

which peaks at $\theta = b_j$, where $P_j = 0.5$, with height $a_j^2/4$. A steep item gives a lot of information in a narrow range; a flat item a little information over a wide range. For the 3PL the peak is lower and a little above b_j, because guessing makes correct answers less informative.

Information adds up over items. The **test information function** is the sum of the item information functions, and the **conditional standard error** of a θ estimate is approximately

$$SE(\theta) = \frac{1}{\sqrt{I(\theta)}}.$$

So doubling the information shrinks the standard error by a factor of $\sqrt{2}$, not 2. A test information of 10 gives $SE \approx 0.32$, and on a scale with standard deviation 1 that corresponds to a reliability of about $1 - 0.32^2 = 0.90$ for people at that point.

Two summary reliability coefficients are common:

- **Marginal reliability** averages the error variance over the assumed population distribution of θ: $\rho = 1 - \overline{SE^2}/\sigma^2_\theta$.
- **Empirical reliability** does the same with the estimated scores and their standard errors in the sample.

Both are useful single numbers, but a test can have a respectable overall reliability and still be imprecise exactly where an important decision is made. That is why we look at the curves.

6.2 Example 1: where does the science test measure well?

```
# SAT12 science items, scored with the corrected key (item 32 keyed 3).
key <- c(1,4,5,2,3,1,2,1,3,1,2,4,2,1,5,3,4,4,1,4,3,3,4,1,3,5,1,3,1,5,4,3)
resp <- key2binary(SAT12, key)
```

```
mod <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
gg_info(mod) + gg_info(mod, type = "se")
```




Figure 6.1: Test information (left) and standard error of measurement (right) for the SAT12 science test under the 2PL.

The test is most informative a little below average ability and loses precision quickly above $\theta = 1$. The values behind the curves:

```
theta <- matrix(-3:3)
data.frame(theta = theta[, 1],
           information = testinfo(mod, theta),
           se = 1 / sqrt(testinfo(mod, theta)))
#>   theta information    se
#> 1    -3       3.53 0.533
#> 2    -2       5.82 0.415
#> 3    -1       7.12 0.375
#> 4     0       5.74 0.417
#> 5     1       4.12 0.492
#> 6     2       2.41 0.644
#> 7     3       1.31 0.875
```

Each item's contribution:

```
gg_info(mod, type = "items", which.items = c(1, 6, 9, 12, 19, 28))
```




Figure 6.2: Item information curves of six SAT12 items.

Items differ a lot. Steep items in the middle of the scale do most of the work; very easy items (such as Item.9) add information only far below average, and flat items (such as Item.12) add almost nothing anywhere.

Reliability:

```
marginal_rxx(mod)
#> [1] 0.837
empirical_rxx(fscores(mod, full.scores.SE = TRUE))
#>    F1
#> 0.838
```

`areainfo()` tells us how much of the test's total information lies in a range of the scale, here between $\theta = -1$ and $\theta = 1$:

```
areainfo(mod, c(-1, 1))
#>  LowerBound UpperBound Info TotalInfo Proportion nitems
#>          -1          1 11.4      34.2      0.334     32
```

Suppose the school awards a science prize to students above $\theta = 1.5$. At that point the standard error is

```
1 / sqrt(testinfo(mod, matrix(1.5)))
#> [1] 0.559
```

about half a standard deviation. A student estimated at 1.5 could easily have a true ability of 1.0 or 2.0. The overall reliability of about 0.84 gives a much rosier picture than the precision at the decision point.

6.3 Example 2: designing a test for a decision

Information curves are also a design tool. Imagine a calibrated pool of 90 2PL items for a nursing entrance test, with a pass mark at $\theta = 0.5$. We compare three 20-item forms built from the pool, without collecting any new data: the information function only needs the item parameters.

```
# A pool of 90 calibrated 2PL items (a, b), as stored in an item bank.
# No responses are needed: this example works from item parameters only.
set.seed(606)
pool <- data.frame(item = sprintf("N%02d", 1:90),
                   a = rlnorm(90, 0.15, 0.3),
                   b = rnorm(90, -0.3, 1.1))
```

A small function computes 2PL information from the formula above:

```
info_2pl <- function(items, theta) {
  sapply(theta, function(t) {
    p <- plogis(items$a * (t - items$b))
    sum(items$a^2 * p * (1 - p))
  })
}
```

Three ways to choose 20 items:

```r
forms <- list(
  random   = pool[sample(nrow(pool), 20), ],
  spread   = pool[order(pool$b)[round(seq(1, 90, length.out = 20))], ],
  targeted = pool[order(abs(pool$b - 0.5) / pool$a)[1:20], ]
)
grid <- seq(-3, 3, by = 0.05)
curves <- do.call(rbind, lapply(names(forms), function(f)
  data.frame(form = f, theta = grid, info = info_2pl(forms[[f]], grid))))
library(ggplot2)
ggplot(curves, aes(theta, info, colour = form)) +
  geom_line(linewidth = 1) +
  geom_vline(xintercept = 0.5, linetype = 2) +
  labs(x = expression(theta), y = "Test information", colour = "Form") +
  theme_mirtverse()
```




Figure 6.3: Test information of three 20-item forms drawn from the nursing pool; the dashed line marks the pass mark.

The *targeted* form picks items whose difficulty is close to the pass mark, favouring steep ones (dividing by a ranks steep items first). The *spread* form covers the whole range evenly, and the *random* form is what we get by chance. At the pass mark:

```r
sapply(forms, function(f) c(info = info_2pl(f, 0.5), se = 1 / sqrt(info_2pl(f, 0.5))))
#>      random spread targeted
#> info   4.17  5.879    10.44
#> se     0.49  0.412     0.31
```

The targeted form has more than twice as much information at the pass mark as the random one, with the same number of items. The price is precision far from the cut: the spread form is better for reporting scores across the whole range. Which is better depends on what the scores are for. A licensing test cares about the pass mark; a progress test cares about everyone. Chapter 11 builds on this idea with automated test assembly and adaptive testing.

6.4 Your turn

1. Show, using `info_2pl()` and a single item with $a = 2$, $b = 0$, that the information peaks at $\theta = 0$ with height $a^2/4 = 1$.
2. In Example 1, how many items like the average SAT12 item would you need to add to bring the standard error at $\theta = 1.5$ down to 0.35?
3. In Example 2, build a 30-item targeted form. How much does the standard error at the pass mark improve over the 20-item targeted form?
4. Explain to a colleague why "the test has a reliability of 0.84" is not enough to decide whether it can be used to award the prize.

Solutions

```
one <- data.frame(a = 2, b = 0)
grid[which.max(info_2pl(one, grid))]; max(info_2pl(one, grid))
#> [1] 0
#> [1] 1

# 2. information needed for SE = 0.35, and the average item information at 1.5
need <- 1 / 0.35^2
have <- testinfo(mod, matrix(1.5))
per_item <- have / 32
ceiling((need - have) / per_item)
#> [1] 50

t30 <- pool[order(abs(pool$b - 0.5) / pool$a)[1:30], ]
1 / sqrt(c(twenty = info_2pl(forms$targeted, 0.5), thirty = info_2pl(t30, 0.5)))
#> twenty thirty
#>  0.310  0.272
```

2. Many more items, because the average item adds little information at 1.5. Adding a few *hard, discriminating* items would be far more efficient than adding average ones.
3. Reliability is an average over everybody. The prize decision happens at $\theta = 1.5$, where the test has much less information than in the middle; what matters is the standard error there.

In the lab

> The "Precision at the pass mark" section of Lab 2, `run_lab("decisions")`, asks how precisely a certification exam measures candidates close to the pass mark, and what that means for misclassification.

Further reading

Lord (1980) introduced information functions as a tool for test construction; Hambleton, Swaminathan and Rogers (1991) give an accessible account. van der Linden (2005) shows how to build tests to target information curves.

Chapter 7

Scoring people

Learning goals. After this chapter you can

- compare EAP, MAP, ML and WLE scores and say when each is a sensible choice;
- explain why maximum likelihood fails for perfect and zero scores;
- convert sum scores to IRT scores with a conversion table;
- read a Wright map;
- estimate how often people are classified on the wrong side of a cut score.

Key terms: person score, EAP, MAP, ML, WLE, Wright map, classification accuracy.

7.1 The ideas

Once the item parameters are known, we can estimate each person's θ from their responses. The **likelihood** of a response pattern, viewed as a function of θ, is the product of the item probabilities: $P_j(\theta)$ for each item answered correctly and $1 - P_j(\theta)$ for each item answered wrongly. The four common estimators use it differently.

- **ML** (maximum likelihood) takes the θ that maximizes the likelihood. It uses only the responses, which makes it attractive for fairness arguments, but it does not exist for all-correct or all-wrong patterns (the likelihood keeps rising towards $\pm\infty$), and it is biased outwards for short tests.
- **WLE** (weighted likelihood, Warm (1989)) adds a small correction that removes most of ML's bias and gives finite estimates for perfect patterns.
- **MAP** (maximum a posteriori) multiplies the likelihood by a prior distribution for θ, usually the population distribution, and takes the mode of the result.
- **EAP** (expected a posteriori) takes the *mean* of that posterior. It is easy to compute, always finite and has the smallest average error, which is why it is mirt's default. Like MAP, it **shrinks** estimates towards the population mean, more so when the test is short.

The standard error of an EAP estimate is the standard deviation of the posterior, and it comes for free.

For the Rasch model the sum score carries all the information about θ, so everyone with the same sum score gets the same estimate. For the 2PL and 3PL, two people with the same sum score can get different estimates, because correct answers to steep items count for more. Some programmes still want one score per sum score. **EAP for sum scores** (`method = "EAPsum"`) gives exactly that, and produces a conversion table that can be printed in a manual.

7.2 Example 1: four estimators, one short test

With only five items, the differences between estimators are easy to see.

```
# Five dichotomous LSAT items, one row per test taker.
resp <- expand.table(LSAT7)
```

```
mod <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
patterns <- unique(resp)
est <- sapply(c("EAP", "MAP", "ML", "WLE"), function(m)
  fscores(mod, method = m, response.pattern = patterns)[, "F1"])
scored <- data.frame(pattern = apply(patterns, 1, paste, collapse = ""),
                     sum = rowSums(patterns), round(est, 2))
scored[order(scored$sum, scored$EAP), ][c(1:4, 15:18, 29:32), ]
#>     pattern sum   EAP   MAP    ML   WLE
#> 1     00000   0 -1.87 -1.82  -Inf -4.14
#> 13    00001   1 -1.53 -1.49 -3.12 -2.60
#> 32    00010   1 -1.51 -1.48 -3.07 -2.56
#> 173   10000   1 -1.41 -1.39 -2.71 -2.31
#> 264   10100   2 -0.65 -0.69 -1.17 -1.15
#> 107   01100   2 -0.61 -0.65 -1.11 -1.10
#> 230   10011   3 -0.75 -0.78 -1.31 -1.26
#> 100   01011   3 -0.70 -0.74 -1.25 -1.21
#> 145   01111   4  0.14  0.06  0.13 -0.22
#> 525   11101   4  0.27  0.18  0.43 -0.03
#> 661   11110   4  0.28  0.20  0.47 -0.01
#> 693   11111   5  0.73  0.64   Inf  1.09
```

Read the table from top to bottom. For the all-wrong pattern ML gives `-Inf`, and for the all-correct pattern `Inf`; WLE, MAP and EAP give finite values. EAP and MAP are pulled towards zero compared with ML and WLE. And patterns with the same sum score get different scores under the 2PL, because Item.3 (the steepest) counts for more than Item.5.

The sum-score conversion table:

```
fscores(mod, method = "EAPsum", full.scores = FALSE)
#>   Sum.Scores     F1 SE_F1 observed expected std.res
#> 0          0 -1.870 0.693       12     10.1   0.601
#> 1          1 -1.432 0.684       40     44.7   0.697
#> 2          2 -0.949 0.694      114    109.8   0.403
```

```
#> 3          3 -0.413 0.721      205    207.7   0.191
#> 4          4  0.152 0.759      321    319.2   0.102
#> 5          5  0.727 0.801      308    308.6   0.031
```

`gg_scores()` shows the distribution of the estimated scores, and `gg_wright()` puts people and items on the same scale. With five easy items the Wright map shows the problem at once: the items sit low on the scale, where few people need to be measured.

```
gg_scores(mod) + gg_wright(mod)
```




Figure 7.1: Distribution of the estimated scores (left) and the Wright map of people and items (right) for LSAT7.

7.3 Example 2: a proficiency cut on a mathematics test

We simulate a 40-item end-of-year mathematics test for 2,000 students. The province calls students at or above $\theta = 0.8$ *proficient*. Because the data are simulated we know each student's true θ, so we can see how often the estimates put students on the wrong side of the cut.

```
# Simulated 40-item mathematics test; true_theta is known for checking.
set.seed(707)
true_theta <- rnorm(2000)
a <- matrix(rlnorm(40, 0.1, 0.25)); b <- rnorm(40, 0, 1)
resp <- simdata(a, matrix(-a * b), N = 2000, itemtype = "2PL",
                Theta = matrix(true_theta))
colnames(resp) <- sprintf("M%02d", 1:40)
```

```
mod <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
eap <- fscores(mod, method = "EAP", full.scores.SE = TRUE)
wle <- fscores(mod, method = "WLE", full.scores.SE = TRUE)
```

```
c(cor_eap = cor(eap[, 1], true_theta), cor_wle = cor(wle[, 1], true_theta),
  sd_eap = sd(eap[, 1]), sd_wle = sd(wle[, 1]))
#> cor_eap cor_wle  sd_eap  sd_wle
#>   0.945   0.945   0.947   1.049
```

With 40 items both estimators correlate about 0.95 with the true values, and they rank students almost identically. The EAP scores have a smaller spread than the true values (whose standard deviation is 1) and the WLE scores a slightly larger one: shrinkage on one side, measurement error on the other.

Now the classification. A student is classified correctly if the estimate and the true value fall on the same side of the cut.

```
cut <- 0.8
truth <- true_theta >= cut
observed <- eap[, 1] >= cut
table(true = truth, estimated = observed)
#>        estimated
#> true    FALSE TRUE
#>   FALSE  1503   58
#>   TRUE     81  358
mean(truth == observed)
#> [1] 0.93
```

In practice we never know the truth, but we can estimate the accuracy from the scores and their standard errors (Rudner 2001). If a student's posterior is roughly normal with mean $\hat{\theta}$ and standard deviation $SE(\hat{\theta})$, the probability that their true θ is above the cut is $1 - \Phi\left((c - \hat{\theta})/SE\right)$. Averaging the probability of the side they were classified on gives the expected accuracy:

```
p_above <- pnorm((eap[, 1] - cut) / eap[, 2])
expected_accuracy <- mean(ifelse(observed, p_above, 1 - p_above))
expected_accuracy
#> [1] 0.935
```

The estimate is close to the accuracy we observed against the truth. The misclassified students are, of course, the ones near the cut:

```
library(ggplot2)
ggplot(data.frame(true = true_theta, est = eap[, 1], wrong = truth != observed),
       aes(true, est, colour = wrong)) +
  geom_point(alpha = 0.5, size = 1) +
  geom_vline(xintercept = cut, linetype = 2) +
  geom_hline(yintercept = cut, linetype = 2) +
  scale_colour_manual(values = c(`FALSE` = "grey60", `TRUE` = "#C0392B"),
                      labels = c("correct", "misclassified")) +
```

```
  labs(x = "True theta", y = "EAP estimate", colour = NULL) +
  theme_mirtverse()
```



Figure 7.2: True and estimated ability on the mathematics test; misclassified students lie near the cut.

`augment()` returns the scores, their standard errors and the response data as one table, ready to export:

```
head(augment(mod)[, c("M01", "M02", ".F1", ".se_F1")])
#> # A tibble: 6 x 4
#>     M01   M02    .F1 .se_F1
#>   <int> <int>  <dbl>  <dbl>
#> 1     0     0 -1.70   0.384
#> 2     1     0 -0.246  0.304
#> 3     1     0  0.368  0.300
#> 4     1     0  1.18   0.319
#> 5     0     0 -0.746  0.319
#> 6     0     0 -1.09   0.336
```

7.4 Your turn

1. In Example 1, find two response patterns with a sum score of 3 that get different EAP scores. Which items explain the difference?
2. Fit the Rasch model to `LSAT7` and repeat the EAP table. Do patterns with the same sum score still get different scores?
3. In Example 2, compute the expected classification accuracy using only the first 15 items. How much does it drop?

4. A parent asks why their child, who got 30 of 40 right, has a lower score than a classmate who also got 30 right. Write a short answer.

Solutions

```
subset(scored, sum == 3)
#>     pattern sum   EAP   MAP    ML   WLE
#> 65    00111   3 -0.41 -0.47 -0.82 -0.88
#> 100   01011   3 -0.70 -0.74 -1.25 -1.21
#> 114   01101   3 -0.26 -0.32 -0.59 -0.71
#> 137   01110   3 -0.24 -0.31 -0.56 -0.69
#> 230   10011   3 -0.75 -0.78 -1.31 -1.26
#> 278   10101   3 -0.30 -0.37 -0.66 -0.76
#> 329   10110   3 -0.29 -0.35 -0.63 -0.75
#> 440   11001   3 -0.60 -0.64 -1.09 -1.09
#> 465   11010   3 -0.59 -0.63 -1.07 -1.08
#> 507   11100   3 -0.13 -0.20 -0.38 -0.56

rasch <- mirt(expand.table(LSAT7), 1, itemtype = "Rasch", verbose = FALSE)
r_eap <- fscores(rasch, response.pattern = patterns)[, "F1"]
tapply(round(r_eap, 4), rowSums(patterns), function(x) length(unique(x)))
#> 0 1 2 3 4 5
#> 1 1 1 1 1 1

short <- mirt(resp[, 1:15], 1, itemtype = "2PL", verbose = FALSE)
e15 <- fscores(short, full.scores.SE = TRUE)
p15 <- pnorm((e15[, 1] - cut) / e15[, 2])
mean(ifelse(e15[, 1] >= cut, p15, 1 - p15))
#> [1] 0.898
```

2. No: under the Rasch model every pattern with the same sum score gets the same estimate.
3. For example: "The test gives more weight to questions that are better at telling apart students who have mastered the material from those who have not. Your child and their classmate answered different questions correctly, so their scores differ slightly even though their number correct is the same."

In the lab

Lab 2, `run_lab("decisions")`, asks you to choose a scoring method for a certification board, estimate how many candidates are misclassified at the pass mark, and write a memo about it.

Further reading

Embretson and Reise (2000) compare the scoring methods; Warm (1989) introduced the weighted likelihood estimator; Rudner (2001) the approach to expected classification accuracy used here.

Chapter 8

Polytomous items and open-ended responses

> **Learning goals.** After this chapter you can
> - fit the partial credit, generalized partial credit and graded response models, and say how they differ;
> - read category response curves and thresholds;
> - recognise disordered thresholds and decide whether to collapse categories;
> - describe how rater-scored open-ended responses fit into an IRT analysis.

Key terms: polytomous item, graded response model, GPCM, category response curve, threshold, expected score, QWK.

8.1 The ideas

Many items have more than two score categories: rating scales (*strongly disagree* to *strongly agree*), partial-credit mathematics problems, essays scored 0 to 4 against a rubric. Three families of models are used most.

- The **graded response model** (GRM, Samejima (1969)) models the cumulative probability of scoring in category k *or higher* with a 2PL curve, $P(X \geq k \mid \theta) = \text{logistic}[a(\theta - b_k)]$. The thresholds $b_1 < b_2 < \ldots$ are ordered by construction: b_k is where a person has a 50% chance of scoring k or more.
- The **partial credit model** (PCM, Masters (1982)) is the polytomous Rasch model. It models each *step* from category $k-1$ to k as a Rasch item, with a step difficulty b_k. All items share the same slope.
- The **generalized partial credit model** (GPCM, Muraki (1992)) adds an item slope to the PCM.

In the PCM and GPCM the step difficulties are the points where adjacent category curves cross. They do *not* have to be in order. **Disordered steps** (for example $b_2 < b_1$) mean that a middle

category is never the most likely response at any ability: respondents skip over it. That is often a sign of a category label that is unclear or a rubric level that raters cannot distinguish, and a common remedy is to merge the category with a neighbour.

Each item's **expected score** curve, the average score as a function of θ, summarizes the categories in one line and is often the easiest plot to explain.

8.2 Example 1: attitudes to science

`Science` holds the responses of 392 people to four statements about science and technology, each rated on a four-point scale (1 = *strongly disagree* to 4 = *strongly agree*).

```
# Four 4-category attitude items (scored 1-4), 392 respondents.
resp <- Science
```

`select_model()` compares the three models:

```
sel <- select_model(resp, verbose = FALSE)
sel
#> mirtverse model selection (ranked by BIC)
#>
#>        model npar logLik  AIC  BIC SABIC RMSEA   CFI delta weight
#>          GRM   16  -1609 3250 3313  3263 0.148 0.910  0.00  0.795
#>  PCM (Rasch)   13  -1619 3265 3316  3275 0.117 0.860  2.90  0.187
#>         GPCM   16  -1613 3257 3321  3270 0.136 0.924  7.63  0.018
#>
#> The GRM model is recommended because it has the lowest BIC (3313.3). The
#> runner-up, PCM (Rasch), is 2.9 BIC points worse, which is positive evidence for
#> the GRM model. Absolute fit of the GRM model: RMSEA = 0.148 (poor fit), CFI =
#> 0.910, SRMSR = 0.073.
```

The GRM has the lowest BIC, but the absolute fit (RMSEA) is not good for any of the three. With only four items, M2 has few degrees of freedom and RMSEA is unstable, so read it with care, and look at the items.

```
grm <- sel$models[["GRM"]]
tidy(grm)
#> # A tibble: 16 x 5
#>    item    itemtype term  estimate std.error
#>    <chr>   <chr>    <chr>    <dbl>     <dbl>
#>  1 Comfort graded   a         1.04         NA
#>  2 Comfort graded   b1       -4.67         NA
#>  3 Comfort graded   b2       -2.53         NA
#>  4 Comfort graded   b3        1.41         NA
#>  5 Work    graded   a         1.23         NA
#>  6 Work    graded   b1       -2.39         NA
```

```
#>  7 Work    graded   b2      -0.735        NA
#>  8 Work    graded   b3       1.85         NA
#>  9 Future  graded   a        2.29         NA
#> 10 Future  graded   b1      -2.28         NA
#> 11 Future  graded   b2      -0.965        NA
#> 12 Future  graded   b3       0.856        NA
#> 13 Benefit graded   a        1.09         NA
#> 14 Benefit graded   b1      -3.06         NA
#> 15 Benefit graded   b2      -0.906        NA
#> 16 Benefit graded   b3       1.54         NA
```

Each item has one slope and three thresholds. *Future* has by far the steepest slope. The category curves show how the thresholds divide the scale:

```
gg_trace(grm)
```




Figure 8.1: Category response curves of the graded response model for the four Science items.

and the expected score curves summarize them:

```
gg_trace(grm, type = "expected", facet = FALSE)
```




Figure 8.2: Expected item score curves of the graded response model for the Science items.

The lowest category is rare for every item: its first threshold is far below average, so the curve for "strongly disagree" only rises for people far out in the left tail. The Wright map shows every threshold next to the distribution of people:

```
gg_wright(grm)
```




Figure 8.3: Wright map of the Science items: category thresholds next to the distribution of people.

8.3 Example 2: a rating category nobody uses

We simulate a six-item job satisfaction scale with five categories (0 to 4), answered by 1,500 employees. On item J3 the middle label was badly worded, so respondents tend to skip category 2.

```
# Simulated 6-item, 5-category scale; item J3 has disordered steps.
set.seed(808)
steps <- rbind(c(-2.0, -0.8, 0.4, 1.6),
               c(-1.8, -0.6, 0.6, 1.8),
               c(-1.6,  0.9, -0.3, 1.4),   # J3: step 2 harder than step 3
               c(-2.2, -1.0, 0.2, 1.4),
               c(-1.9, -0.7, 0.5, 1.7),
               c(-1.7, -0.5, 0.7, 1.9))
a <- c(1.3, 1.5, 1.4, 1.2, 1.6, 1.3)
d <- cbind(0, -a * t(apply(steps, 1, cumsum)))   # GPCM intercepts
resp <- simdata(matrix(a), d, N = 1500, itemtype = "gpcm")
colnames(resp) <- paste0("J", 1:6)
```

The category frequencies already hint at the problem:

```
round(t(apply(resp, 2, function(x) table(factor(x, levels = 0:4)) / length(x))), 2)
#>       0    1    2    3    4
#> J1 0.05 0.21 0.34 0.28 0.12
#> J2 0.07 0.23 0.37 0.24 0.08
#> J3 0.12 0.41 0.10 0.25 0.13
#> J4 0.05 0.18 0.32 0.30 0.14
#> J5 0.07 0.22 0.36 0.27 0.08
#> J6 0.09 0.24 0.37 0.22 0.08
```

Fit the GPCM and look at the step parameters:

```
gpcm <- mirt(resp, 1, itemtype = "gpcm", verbose = FALSE)
coef(gpcm, IRTpars = TRUE, simplify = TRUE)$items
#>       a    b1     b2     b3   b4
#> J1 1.33 -2.14 -0.831  0.345 1.53
#> J2 1.51 -1.87 -0.665  0.603 1.72
#> J3 1.24 -1.81  1.008 -0.380 1.44
#> J4 1.18 -2.20 -0.963  0.163 1.39
#> J5 1.46 -1.92 -0.723  0.501 1.76
#> J6 1.21 -1.75 -0.625  0.768 1.87
```

For J3 the second step (b_2) is larger than the third (b_3), unlike every other item. The category curves make it plain: category 2 of J3 is never the most likely response.

```
gg_trace(gpcm, which.items = c("J2", "J3"))
```




Figure 8.4: Category response curves of J2 and J3; category 2 of J3 is never the most likely response.

Disordered steps are not always a problem; they mean a category is rarely the *most likely* response, not that nobody uses it. Look at the wording or the rubric, and at how many people chose the category. Here we decide that the middle label is unclear and merge categories 1 and 2 of J3, so it is scored 0 to 3:

```
collapsed <- resp
collapsed[, "J3"] <- c(0, 1, 1, 2, 3)[resp[, "J3"] + 1]
gpcm_c <- mirt(collapsed, 1, itemtype = "gpcm", verbose = FALSE)
coef(gpcm_c, IRTpars = TRUE, simplify = TRUE)$items["J3", ]
#>      a     b1     b2     b3     b4
#>  1.613 -1.663  0.575  1.302     NA
```

The steps of the collapsed item are now in order. The GRM would never have shown the problem, because its thresholds are ordered by definition: this is one reason to fit a PCM or GPCM when you are developing a rating scale.

8.4 Open-ended responses and raters

Open-ended tasks, such as essays and constructed responses, are usually scored by trained raters against a rubric, and then analysed with a polytomous model like the ones above. Two extra questions come first. **Do the raters agree?** Agreement on ordinal scores is usually summarized by exact agreement and by **quadratic weighted kappa** (QWK), which gives partial credit for near misses (Cohen 1968). **Are some raters harsher or less consistent than others?** Rater effects can be studied by comparing each rater's scores with those of the other raters on the same responses, or with models that include rater parameters.

mirtverse's assessment pipeline has a scoring stage for this, `score_open()`, which resolves two

reads into a final score and checks agreement (see section 9 of the assessment pipeline article). Lab 6 works through the whole process with eight raters and an automated scoring engine.

8.5 Your turn

1. Fit the PCM (`itemtype = "Rasch"`) to `Science`. Are any of its step difficulties disordered?
2. In Example 2, fit the GRM to the original data. What do the thresholds of J3 look like, and why do they not reveal the problem?
3. Compare the test information of the original and the collapsed GPCM. How much information is lost by collapsing one category of one item?
4. Two raters score 200 essays from 0 to 4 and agree exactly on 60% of them. Why is QWK a better summary than exact agreement for deciding whether the raters can be trusted?

Solutions

```
pcm <- mirt(Science, 1, itemtype = "Rasch", verbose = FALSE)
coef(pcm, IRTpars = TRUE, simplify = TRUE)$items
#>         a    b1     b2   b3
#> Comfort 1 -3.09 -2.595 1.39
#> Work    1 -1.90 -0.911 1.86
#> Future  1 -2.65 -1.421 1.14
#> Benefit 1 -2.45 -0.900 1.36

grm2 <- mirt(resp, 1, itemtype = "graded", verbose = FALSE)
coef(grm2, IRTpars = TRUE, simplify = TRUE)$items["J3", ]
#>       a      b1      b2      b3      b4
#>  1.9899 -1.6164  0.0767  0.4230  1.5352

theta <- matrix(seq(-3, 3, by = 1))
round(rbind(original = testinfo(gpcm, theta), collapsed = testinfo(gpcm_c, theta)), 2)
#>           [,1] [,2] [,3] [,4] [,5] [,6] [,7]
#> original  1.95 4.19 5.80 6.99 6.16 3.64 1.43
#> collapsed 1.95 4.41 5.89 6.31 6.34 3.85 1.42
```

2. The GRM thresholds of J3 are in order, because the model forces them to be; the second and third are just close together.
3. Hardly any. At some points the collapsed model even has a little more information, because the slope of J3 is estimated higher once the model no longer has to accommodate the skipped category. Collapsing a category that people skip costs almost nothing.
4. Exact agreement treats a 3 versus 4 disagreement the same as a 0 versus 4 disagreement. QWK weights disagreements by their size and corrects for agreement by chance, so it reflects whether the raters rank the essays in the same way.

In the lab

> Lab 6, `run_lab("open-ended")`, follows six rater-scored science tasks from rater agreement to the final IRT model: QWK, rater severity and consistency, resolving two reads, PCM versus GPCM versus GRM, collapsing categories, and checking an automated scoring engine.

Further reading

Samejima (1969), Masters (1982) and Muraki (1992) introduced the three models; Embretson and Reise (2000) compare them. Cohen (1968) introduced weighted kappa.

Chapter 9

Differential item functioning and fairness

Learning goals. After this chapter you can

- tell **impact** (a real difference between groups) from **DIF** (an item that works differently for people of the same ability);
- run an IRT likelihood-ratio DIF analysis and read its effect sizes;
- distinguish uniform from non-uniform DIF;
- run a Mantel-Haenszel DIF test and classify items with the ETS A/B/C rules;
- explain why anchor items matter.

Key terms: DIF, reference and focal groups, uniform and non-uniform DIF, DIF effect size, anchor items.

9.1 The ideas

Groups often differ in their average scores. That alone says nothing about whether a test is fair: the groups may simply differ in what the test measures, which is called **impact**. An item shows **differential item functioning** (DIF) when people from different groups *with the same ability* have different chances of answering it correctly (Holland and Wainer 1993). DIF is a statistical finding, not a verdict of bias; a content review decides whether the reason is irrelevant to what the test should measure (bias) or a real difference in what was taught.

We compare a **reference group** (often the majority group) with a **focal group**. In IRT terms, DIF means the item has different parameters in the two groups.

- **Uniform DIF:** the item is harder for one group at every ability level (the difficulty differs, the curves are parallel).
- **Non-uniform DIF:** the size or direction of the difference changes with ability (the slopes differ and the curves cross).

To compare groups we must first put them on a common scale, and that needs items we trust to work the same way in both: the **anchors**. mirtverse's `dif()` uses a *constrained-baseline* approach:

it fits a multiple-group model in which all item parameters are equal across groups while the group means and variances are free, then frees each item's parameters in turn and tests the change with a likelihood-ratio test. Items you do not test serve as anchors. Because each test involves only one free item, the approach works well when DIF is confined to a few items; when many items have DIF, a *purification* step (testing, removing flagged items from the anchor set, and testing again) is safer.

A significant test is not enough: with large samples tiny differences are significant. `dif()` therefore reports effect sizes on the item score scale. The signed version (`esd`) is the average difference in the probability of a correct answer between the focal and the reference group at the same ability; the unsigned version (`uesd`) also captures crossing curves.

The **Mantel-Haenszel** (MH) procedure (Holland and Thayer 1988) is the classical alternative. It matches people on their sum score, builds a 2×2 table (group $\times$ right/wrong) at every score level and tests whether the odds of a correct answer differ between groups across the tables. ETS classifies the size of MH DIF as A (negligible), B (moderate) or C (large).

9.2 Example 1: paper versus tablet

A district moved its Grade 5 reading test from paper to tablets. We simulate 25 items answered by 1,200 students on paper (reference) and 800 on tablets (focal). The tablet group is slightly weaker on average (impact). Two items that ask students to drag text into a table are harder on tablets (uniform DIF), and one long-passage item is easier for strong tablet readers and harder for weak ones (non-uniform DIF).

```
# Simulated 25-item reading test; `group` is the test mode for each student.
set.seed(909)
a <- matrix(rlnorm(25, 0.2, 0.25)); d <- matrix(rnorm(25, 0.2, 0.9))
a_tab <- a; d_tab <- d
d_tab[c(7, 18)] <- d[c(7, 18)] - 0.8          # R07, R18: uniform DIF
a_tab[22] <- a[22] * 1.8; d_tab[22] <- d[22]   # R22: non-uniform DIF
paper  <- simdata(a, d, N = 1200, itemtype = "2PL")
tablet <- simdata(a_tab, d_tab, N = 800, itemtype = "2PL",
                  Theta = matrix(rnorm(800, -0.2, 1)))
resp <- rbind(paper, tablet)
colnames(resp) <- sprintf("R%02d", 1:25)
group <- factor(rep(c("Paper", "Tablet"), c(1200, 800)),
                levels = c("Paper", "Tablet"))
```

The raw scores differ between the groups, but that alone does not tell us which items, if any, are unfair:

```
mode_resp <- resp; mode_group <- group   # kept for the exercises
tapply(rowSums(resp), group, mean)
#>  Paper Tablet
#>   12.6   11.1
```

`dif()` tests every item. Paper is the reference group because it is the first level of the factor.

```
res <- dif(resp, group = group)
res
#> DIF analysis: Paper (reference) vs Tablet; 25 items tested
#> Likelihood-ratio tests freeing a1, d; BH-adjusted p < 0.05 flags DIF
#>
#>  item     X2 df p.value p.adjusted flag    esd  uesd converged
#>   R01  1.273  2    .529       .758      -0.007 0.018      TRUE
#>   R02  2.153  2    .341       .758       0.016 0.022      TRUE
#>   R03  0.264  2    .876       .876       0.005 0.009      TRUE
#>   R04  1.480  2    .477       .758      -0.022 0.022      TRUE
#>   R05  1.158  2    .560       .758       0.011 0.019      TRUE
#>   R06  0.953  2    .621       .758      -0.017 0.018      TRUE
#>   R07 29.459  2  < .001     < .001  DIF -0.100 0.100      TRUE
#>   R08  1.447  2    .485       .758       0.021 0.024      TRUE
#>   R09  1.793  2    .408       .758      -0.019 0.021      TRUE
#>   R10  5.327  2    .070       .290       0.013 0.044      TRUE
#>   R11  4.878  2    .087       .312       0.041 0.041      TRUE
#>   R12  7.665  2    .022       .108       0.041 0.047      TRUE
#>   R13  0.720  2    .698       .758       0.001 0.014      TRUE
#>   R14  1.044  2    .593       .758       0.018 0.018      TRUE
#>   R15  0.578  2    .749       .780      -0.007 0.012      TRUE
#>   R16  0.783  2    .676       .758      -0.011 0.013      TRUE
#>   R17  9.572  2    .008       .052       0.061 0.061      TRUE
#>   R18 45.538  2  < .001     < .001  DIF -0.135 0.135      TRUE
#>   R19  2.351  2    .309       .758       0.017 0.024      TRUE
#>   R20  1.087  2    .581       .758      -0.006 0.018      TRUE
#>   R21  1.270  2    .530       .758       0.002 0.019      TRUE
#>   R22 32.166  2  < .001     < .001  DIF  0.043 0.075      TRUE
#>   R23  4.298  2    .117       .364       0.028 0.032      TRUE
#>   R24  0.878  2    .645       .758       0.012 0.015      TRUE
#>   R25  1.456  2    .483       .758       0.024 0.024      TRUE
```

The flagged items are the three we planted. The signed effect sizes of R07 and R18 are negative, meaning the items are harder for tablet users of the same ability. R22's signed effect is small but its unsigned effect is larger: the curves cross, so the advantages and disadvantages partly cancel out on average.

```
gg_dif(res)
```




Figure 9.1: DIF effect sizes for the 25 reading items, paper versus tablet.

```
gg_dif(res, type = "curves", which.items = c("R07", "R22"))
```




Figure 9.2: Item curves for the paper and tablet groups: uniform DIF in R07, non-uniform DIF in R22.

`interpret()` writes the findings up:

```
interpret(res)
#> DIF overview
#> ------------
#> * Items were tested for DIF between Paper and Tablet, with Paper as the
#>   reference group (n = 1200 Paper, n = 800 Tablet).
#> * Each item's parameters (a1, d) were freed in turn and compared with a model
#>   holding them equal across groups (likelihood-ratio test, BH-adjusted p <
#>   0.05).
#> * On the common scale, the Tablet group's mean ability is 0.28 SD below the
#>   Paper group's, and its SD is 1.09.
#>
#> DIF items
#> ---------
#> * 3 of 25 items show DIF: R18 (expected score difference -0.135, favours
#>   Paper; p < .001); R07 (expected score difference -0.100, favours Paper; p <
#>   .001); R22 (expected score difference 0.043, favours Tablet; p < .001).
#> * Statistical DIF is not proof of bias: ask content experts whether these
#>   items measure something other than the intended ability for one group
#>   before removing or revising them.
```

The baseline model also estimates the impact: the latent mean of the tablet group relative to the paper group (fixed at 0).

```
coef(res$baseline, simplify = TRUE)$Tablet$means
#>     F1
#> -0.283
```

9.2.1 Choosing anchors

If we already know some items are clean, we can test only the others: the untested items become anchors. Here, as a check, we test only the three flagged items against the other 22:

```
dif(resp, group = group, items = c("R07", "R18", "R22"))$table
#> # A tibble: 3 x 9
#>   item     X2    df  p.value p.adjusted flag      esd   uesd converged
#>   <chr> <dbl> <int>    <dbl>      <dbl> <lgl>   <dbl>  <dbl> <lgl>
#> 1 R07    29.5     2 4.01e- 7   4.01e- 7 TRUE  -0.0997 0.0997 TRUE
#> 2 R18    45.5     2 1.29e-10   3.88e-10 TRUE  -0.135  0.135  TRUE
#> 3 R22    32.2     2 1.04e- 7   1.55e- 7 TRUE   0.0430 0.0755 TRUE
```

Does the DIF matter for scores? One way to judge is to compare the expected total score of the test in the two groups at the same ability, which is called differential test functioning. With two items that are harder for tablet users and one that crosses, the total effect is a fraction of a score point; a content review would still look at the drag-and-drop items, because the problem

can be fixed by changing the interface.

9.3 Example 2: Mantel-Haenszel on a chemistry quiz

The MH test needs no IRT model, which makes it a good first screen and a useful check. We simulate a 20-item chemistry quiz taken by 600 girls and 600 boys of equal average ability; item C11 involves a sports context and is easier for boys of the same ability.

```
# Simulated 20-item quiz; `group` is gender. C11 has uniform DIF.
set.seed(910)
a <- matrix(rlnorm(20, 0.2, 0.2)); d <- matrix(rnorm(20, 0, 0.8))
d_boys <- d; d_boys[11] <- d[11] + 0.7
resp <- rbind(simdata(a, d, N = 600, itemtype = "2PL"),
              simdata(a, d_boys, N = 600, itemtype = "2PL"))
colnames(resp) <- sprintf("C%02d", 1:20)
group <- factor(rep(c("Girl", "Boy"), each = 600), levels = c("Girl", "Boy"))
```

For each item we match on the total score of the *other* items, build the stratified 2×2 tables and run the MH test. The common odds ratio α_{MH} converts to the ETS delta scale as MH D-DIF $= -2.35 \ln \alpha_{MH}$. The ETS rules call DIF negligible (A) when $|\text{MH D-DIF}| < 1$ or the test is not significant, large (C) when $|\text{MH D-DIF}| \geq 1.5$ and significant, and moderate (B) otherwise (the full rules also test the size against 1).

```
mh_item <- function(resp, group, item) {
  rest <- rowSums(resp[, colnames(resp) != item])
  strata <- cut(rest, unique(quantile(rest, 0:5 / 5)), include.lowest = TRUE)
  tab <- table(group, factor(resp[, item], levels = 1:0), strata)
  mh <- mantelhaen.test(tab, exact = FALSE)
  delta <- -2.35 * log(unname(mh$estimate))
  data.frame(item = item, alpha_MH = unname(mh$estimate),
             MH_D_DIF = delta, p.value = mh$p.value,
             ETS = ifelse(mh$p.value >= 0.05 | abs(delta) < 1, "A",
                          ifelse(abs(delta) >= 1.5, "C", "B")))
}
mh <- do.call(rbind, lapply(colnames(resp), mh_item, resp = resp, group = group))
mh[order(mh$p.value), ][1:5, ]
#>    item alpha_MH MH_D_DIF  p.value ETS
#> 11  C11    0.576    1.297 3.55e-05   B
#> 4   C04    1.288   -0.596 4.54e-02   A
#> 13  C13    0.789    0.556 1.22e-01   A
#> 1   C01    1.222   -0.471 1.36e-01   A
#> 9   C09    1.224   -0.476 1.42e-01   A
```

The table is arranged so that α_{MH} is the odds of a correct answer in the reference group (girls) divided by the odds in the focal group (boys), at the same score. Values above 1, and negative

MH D-DIF, mean the item favours the reference group; values below 1, and positive MH D-DIF, favour the focal group. C11 stands out, with a moderate (B) DIF in favour of boys. Matching on five score bands keeps the tables reasonably full in a sample of this size; with more people you can match on every score.

The IRT analysis agrees:

```
subset(dif(resp, group = group)$table, flag)
#> # A tibble: 1 x 9
#>   item     X2    df  p.value p.adjusted flag    esd  uesd converged
#>   <chr> <dbl> <int>    <dbl>      <dbl> <lgl> <dbl> <dbl> <lgl>
#> 1 C11    18.1     2 0.000117    0.00233 TRUE  0.104 0.104 TRUE
```

9.4 Your turn

1. In Example 1, refit `dif()` with `p_adjust = "none"`. How many items are flagged now? Which result would you report, and why?
2. Run the MH procedure on the data of Example 1. Does it detect R22? Why is MH weaker for non-uniform DIF?
3. In Example 2, what happens to the MH results if you match on the total score *including* the studied item? On five versus ten score bands?
4. A newspaper writes that "the tablet test is biased because tablet users scored lower". Using the results of Example 1, write three sentences in reply.

Solutions

```
sum(dif(mode_resp, group = mode_group, p_adjust = "none")$table$flag)
#> [1] 5
mh_mode <- do.call(rbind, lapply(colnames(mode_resp), mh_item,
                                 resp = mode_resp, group = mode_group))
subset(mh_mode, item %in% c("R07", "R18", "R22"))
#>    item alpha_MH MH_D_DIF  p.value ETS
#> 7   R07    1.980   -1.605 1.16e-09   C
#> 18  R18    2.079   -1.720 1.57e-12   C
#> 22  R22    0.689    0.876 4.67e-03   A
```

1. Without adjustment a few more items may be flagged at the 5% level by chance alone, since 25 tests are run. Report the adjusted results, and use the effect sizes to decide which items matter.
2. MH compares the *average* odds across score levels. When the curves cross, the advantage at one end and the disadvantage at the other cancel out, so MH (like the signed effect size) often misses non-uniform DIF. The IRT likelihood-ratio test, which frees the slope, catches it.
3. Including the studied item in the matching score is the textbook MH procedure; excluding it, as above, is a common variant. With 20 items the results are similar. More bands

make the matching finer, but leave fewer people per table.

4. For example: "Tablet users did score a little lower on average, but most of that difference reflects a real difference in reading between the groups, not the test. When we compared students of the same reading ability, only three of 25 questions worked differently, and two of them involve dragging text on a screen, which we are redesigning."

In the lab

> Lab 3, `run_lab("fairness")`, investigates a complaint that a numeracy test is biased against English language learners, with Mantel-Haenszel and IRT DIF tests, anchor purification and differential test functioning. Lab 2 has a shorter DIF section on a certification exam.

Further reading

Holland and Wainer (1993) remain the standard reference; Holland and Thayer (1988) introduced the MH procedure for DIF.

Chapter 10

Linking and equating

Learning goals. After this chapter you can

- explain why two separately calibrated forms are not on the same scale;
- describe common-item (anchor) and common-person designs;
- link two calibrations with the mean-sigma and Stocking-Lord methods;
- check anchor items for parameter drift;
- run a concurrent calibration with a multiple-group model;
- carry a cut score from one form to another with IRT true-score equating.

Key terms: linking, anchor items, moment linking, characteristic curve linking, parameter drift, test characteristic curve.

10.1 The ideas

Every calibration fixes the scale by assuming that the people in it have θ with mean 0 and standard deviation 1. If this year's candidates are stronger than last year's, a separate calibration of this year's form will still put *them* at mean 0, and every item will look harder than it is. To compare forms, or groups, the two calibrations must be put on a common scale. That is **linking**; when the goal is to make scores on two forms interchangeable, it is called **equating** (Kolen and Brennan 2014).

Because the IRT scale is only determined up to a linear transformation, linking amounts to finding two constants A and B such that, for the new form's parameters,

$$\theta^* = A\theta + B, \qquad b^* = Ab + B, \qquad a^* = a/A.$$

The constants come from information the two calibrations share. In the common design, the **non-equivalent groups with anchor test** (NEAT) design, the two forms share a set of **anchor items**. Two families of methods estimate A and B from the anchors.

- **Moment methods.** *Mean-sigma* matches the mean and standard deviation of the anchor difficulties: $A = s_{b,\text{old}}/s_{b,\text{new}}$ and $B = \bar{b}_{\text{old}} - A\,\bar{b}_{\text{new}}$. They are simple, but sensitive to a single unusual anchor.
- **Characteristic curve methods.** *Stocking-Lord* (Stocking and Lord 1983) chooses A and B to make the anchors' test characteristic curve (the expected anchor score as a function of θ) as similar as possible on the two scales. They use all the parameters at once and are more robust.

An alternative to linking two separate calibrations is **concurrent calibration**: fit one multiple-group model to both forms, constraining the anchor items to be equal across groups and estimating the new group's mean and standard deviation.

Everything rests on the anchors behaving the same way in both administrations. An anchor whose parameters have changed, because it was exposed, taught to, or its position or wording changed, shows **parameter drift**, and it must be removed from the anchor set before linking.

10.2 Example 1: separate calibration and linking

A language school has an old and a new 30-item placement test that share 10 anchor items. We simulate 1,000 students on each. The new cohort is stronger (mean 0.4, standard deviation 1.1), and anchor A06 was leaked and became easier on the new form.

```
# Simulated NEAT design: old form (O01-O20 + anchors A01-A10) and new form
# (N01-N20 + the same anchors); anchor A06 drifts on the new form.
set.seed(1010)
anchors <- sprintf("A%02d", 1:10)
pars <- data.frame(item = c(sprintf("O%02d", 1:20), sprintf("N%02d", 1:20), anchors),
                   a = rlnorm(50, 0.15, 0.25), b = rnorm(50, 0, 1))
gen <- function(items, n, mean, sd, shift = NULL) {
  p <- pars[match(items, pars$item), ]
  if (!is.null(shift)) p$b[p$item %in% names(shift)] <- p$b[p$item %in% names(shift)] + shift
  out <- simdata(matrix(p$a), matrix(-p$a * p$b), N = n, itemtype = "2PL",
                 Theta = matrix(rnorm(n, mean, sd)))
  colnames(out) <- items
  as.data.frame(out)
}
old <- gen(c(sprintf("O%02d", 1:20), anchors), 1000, 0, 1)
new <- gen(c(sprintf("N%02d", 1:20), anchors), 1000, 0.4, 1.1, shift = c(A06 = -1.2))
```

Calibrate each form on its own:

```
fit_old <- mirt(old, 1, itemtype = "2PL", verbose = FALSE)
fit_new <- mirt(new, 1, itemtype = "2PL", verbose = FALSE)
p_old <- coef(fit_old, IRTpars = TRUE, simplify = TRUE)$items[anchors, c("a", "b")]
p_new <- coef(fit_new, IRTpars = TRUE, simplify = TRUE)$items[anchors, c("a", "b")]
round(cbind(b_old = p_old[, "b"], b_new = p_new[, "b"]), 2)
```

```
#>     b_old b_new
#> A01 -0.49 -0.90
#> A02  0.69  0.18
#> A03 -1.44 -1.74
#> A04 -0.13 -0.38
#> A05 -1.05 -1.53
#> A06 -0.43 -2.10
#> A07 -1.10 -1.51
#> A08 -0.62 -1.02
#> A09  1.14  0.65
#> A10 -1.82 -2.15
```

The anchors look easier on the new calibration, because the new students are stronger and their calibration puts them at mean 0. Before linking, check for drift. On a common scale the anchor difficulties should lie on a straight line:

```
library(ggplot2)
ggplot(data.frame(old = p_old[, "b"], new = p_new[, "b"], item = anchors),
       aes(new, old)) +
  geom_smooth(method = "lm", se = FALSE, colour = "grey70", formula = y ~ x) +
  geom_point() + geom_text(aes(label = item), nudge_y = 0.15, size = 3) +
  labs(x = "Difficulty, new calibration", y = "Difficulty, old calibration") +
  theme_mirtverse()
```




Figure 10.1: Anchor difficulties in the old and new calibrations; items off the line may have drifted.

A06 sits well off the line formed by the others. A simple rule is to flag anchors whose difference in difficulty is far from the typical difference:

```
diff_b <- p_old[, "b"] - p_new[, "b"]
round(sort((diff_b - median(diff_b)) / mad(diff_b)), 1)
#>  A04  A03  A10  A08  A01  A07  A09  A05  A02  A06
#> -1.3 -0.9 -0.7 -0.1  0.0  0.0  0.7  0.7  0.9 10.8
```

We drop A06 from the anchor set and compute the mean-sigma constants from the remaining nine:

```
keep <- setdiff(anchors, "A06")
A <- sd(p_old[keep, "b"]) / sd(p_new[keep, "b"])
B <- mean(p_old[keep, "b"]) - A * mean(p_new[keep, "b"])
c(A = A, B = B)
#>    A    B
#> 1.04 0.44
```

B estimates how much stronger the new cohort is on the old scale (we simulated 0.4), and A how much more spread out (1.1). Stocking-Lord finds the constants that make the two anchor characteristic curves agree:

```
tcc <- function(a, b, theta) sapply(theta, function(t) sum(plogis(a * (t - b))))
grid <- seq(-3, 3, length.out = 41)
sl_loss <- function(k) {
  A <- k[1]; B <- k[2]
  sum((tcc(p_old[keep, "a"], p_old[keep, "b"], grid) -
       tcc(p_new[keep, "a"] / A, A * p_new[keep, "b"] + B, grid))^2 * dnorm(grid))
}
sl <- optim(c(1, 0), sl_loss)$par
c(A = sl[1], B = sl[2])
#>    A    B
#> 1.05 0.41
```

Both methods recover the cohort difference well. What would have happened if we had kept the drifted anchor?

```
A_all <- sd(p_old[, "b"]) / sd(p_new[, "b"])
c(A = A_all, B = mean(p_old[, "b"]) - A_all * mean(p_new[, "b"]))
#>     A     B
#> 0.963 0.487
```

One leaked item is enough to distort the link, and with it every score on the new form.

10.3 Example 2: concurrent calibration and equating a pass mark

Concurrent calibration fits both forms at once. We stack the two datasets; each student has `NA` for the items they did not take.

```
# The same NEAT data stacked: NA for items not on a student's form.
# A06 is renamed on the new form, so it is not treated as an anchor.
new_a <- new; names(new_a)[names(new_a) == "A06"] <- "A06_new"
resp <- merge(transform(old, form = "old", id = seq_len(nrow(old))),
              transform(new_a, form = "new", id = nrow(old) + seq_len(nrow(new_a))),
              all = TRUE)
form <- factor(resp$form, levels = c("old", "new"))
resp <- resp[, setdiff(names(resp), c("form", "id"))]
```

Renaming A06 on the new form turns it into two separate items, one per form, which is the usual way to drop a drifted anchor from the link without discarding its responses. `multipleGroup()` constrains every item to have the same parameters in both groups (each unique item is only seen by one group anyway) and frees the new group's mean and variance:

```
mg <- suppressWarnings(
  multipleGroup(resp, 1, group = form, itemtype = "2PL", verbose = FALSE,
                invariance = c(colnames(resp), "free_means", "free_var")))
coef(mg, simplify = TRUE)$new[c("means", "cov")]
#> $means
#>    F1
#> 0.411
#>
#> $cov
#>      F1
#> F1 1.12
```

The new group's mean and variance are estimated on the old group's scale, and are close to the values we simulated (0.4 and $1.1^2 = 1.21$).

Now the pass mark. The old form's pass mark was 18 correct out of 30. What score on the new form corresponds to the same ability? **IRT true-score equating** finds the θ at which the old form's expected score (its test characteristic curve) equals 18, then reads off the new form's expected score at that θ.

```
items <- coef(mg, IRTpars = TRUE, simplify = TRUE)$old$items
old_items <- c(sprintf("O%02d", 1:20), anchors)
new_items <- c(sprintf("N%02d", 1:20), setdiff(anchors, "A06"), "A06_new")
tcc_form <- function(ids, theta) tcc(items[ids, "a"], items[ids, "b"], theta)
theta_cut <- uniroot(function(t) tcc_form(old_items, t) - 18, c(-4, 4))$root
c(theta_cut = theta_cut, new_form_cut = tcc_form(new_items, theta_cut))
#>    theta_cut new_form_cut
#>        0.419       19.763
```

```
curves <- data.frame(theta = rep(grid, 2),
                     score = c(tcc_form(old_items, grid), tcc_form(new_items, grid)),
                     form = rep(c("Old form", "New form"), each = length(grid)))
```

```
ggplot(curves, aes(theta, score, colour = form)) +
  geom_line(linewidth = 1) +
  geom_vline(xintercept = theta_cut, linetype = 2) +
  geom_hline(yintercept = 18, linetype = 3) +
  labs(x = expression(theta), y = "Expected number correct", colour = NULL) +
  theme_mirtverse()
```




Figure 10.2: Test characteristic curves of the old and new forms on the common scale, with the cut score.

If the new form is easier, its curve lies above the old form's and the pass mark on the new form is higher; if it is harder, the pass mark is lower. Here the new form is a little easier, so the old pass mark of 18 corresponds to about 19.8 on the new form. Rounding the equated score to a whole number is a policy decision: rounding down passes slightly more candidates than the old standard, rounding up slightly fewer.

10.4 Your turn

1. Repeat the mean-sigma link in Example 1 with the *mean-mean* method: $A = \bar{a}_{\text{new}}/\bar{a}_{\text{old}}$, $B = \bar{b}_{\text{old}} - A\,\bar{b}_{\text{new}}$. How close are the constants to the Stocking-Lord ones?
2. Rerun the concurrent calibration of Example 2 *with* A06 as an anchor. How much does the estimated mean of the new group change?
3. Compute the pass mark on the new form if the old pass mark were 22.
4. A board member asks why the pass mark changed from one year to the next "when the standard was supposed to stay the same". Answer in two sentences.

Solutions

```
A_mm <- mean(p_new[keep, "a"]) / mean(p_old[keep, "a"])
c(A = A_mm, B = mean(p_old[keep, "b"]) - A_mm * mean(p_new[keep, "b"]))
#>     A     B
#> 1.025 0.422

resp_all <- merge(transform(old, form = "old", id = seq_len(nrow(old))),
                  transform(new, form = "new", id = nrow(old) + seq_len(nrow(new))),
                  all = TRUE)
form_all <- factor(resp_all$form, levels = c("old", "new"))
resp_all <- resp_all[, setdiff(names(resp_all), c("form", "id"))]
mg_all <- suppressWarnings(
  multipleGroup(resp_all, 1, group = form_all, itemtype = "2PL", verbose = FALSE,
                invariance = c(colnames(resp_all), "free_means", "free_var")))
coef(mg_all, simplify = TRUE)$new$means
#>   F1
#> 0.54

theta22 <- uniroot(function(t) tcc_form(old_items, t) - 22, c(-4, 4))$root
tcc_form(new_items, theta22)
#> [1] 23.1
```

2. With A06 treated as an anchor, the new group's mean rises well above the simulated 0.4. The model has to explain why the new students do so much better on A06; since A06 is constrained to be the same item, part of the leak is credited to the students' ability. Every new-form score would be too high.
3. For example: "The standard is the same level of ability, not the same number of questions. This year's form was a little easier, so reaching that level of ability takes a slightly higher number of correct answers."

In the lab

> Lab 4, `run_lab("linking")`, asks why a licensure exam's pass rate jumped on a new form. You calibrate both forms, link them, check the anchors, compare separate and concurrent calibration, and carry the pass mark over.

Further reading

Kolen and Brennan (2014) is the standard reference on equating and linking. Stocking and Lord (1983) introduced the characteristic curve method used here.

Chapter 11

Item banks, test assembly and adaptive testing

Learning goals. After this chapter you can

- describe what an item bank stores and what it is for;
- read a bank's information curve and spot where the bank is thin;
- assemble a fixed form from a bank under content constraints;
- explain, step by step, how a computerized adaptive test (CAT) selects items, scores people and decides when to stop;
- judge a CAT design by its precision, test length and item exposure.

Key terms: item bank, automated test assembly, parallel forms, computerized adaptive test, multistage test, exposure.

11.1 The ideas

Once items have been calibrated on a common scale (Chapter 10), their parameters can be stored in an **item bank** together with their content codes, usage history and review status. Because the parameters are on one scale, any selection of items from the bank yields scores on that scale. That makes two things possible.

Automated test assembly (ATA) picks items for a fixed form so that the form meets a blueprint (for example, ten items from each content area) and its information curve matches a target: high at a cut score for a licensing test, flat across the range for a progress test (Linden 2005). Exact solutions use mixed-integer programming; simple greedy rules, which add the best remaining item that still fits the blueprint, often get close.

A **computerized adaptive test** (CAT) goes further and builds a different test for every person while they take it (Wainer et al. 2000). The loop is:

1. Start with a provisional θ (often 0).

2. Choose the unused item with the most information at the current θ, subject to content and exposure rules.
3. Score the response and update θ (usually by EAP, which works even after one item).
4. Stop when the standard error is small enough or a maximum length is reached; otherwise go back to step 2.

A CAT typically reaches the precision of a fixed test with half as many items or fewer. The price is a bank large enough to cover the whole range, and **exposure**: without control, the most informative items are given to almost everybody and soon become known. A **multistage test** (MST) is a compromise: people take pre-assembled modules, and the next module depends on their performance on the last one.

11.2 Example 1: a vocabulary bank and a fixed form

A language-assessment centre has a calibrated bank of 200 vocabulary items in four areas.

```
# A calibrated 2PL item bank: 200 items, four content areas.
set.seed(1111)
bank <- data.frame(item = sprintf("V%03d", 1:200),
                   area = factor(rep(c("Everyday", "Academic", "Workplace", "Idioms"),
                                     each = 50)),
                   a = rlnorm(200, 0.2, 0.3),
                   b = c(rnorm(50, -0.8, 0.9), rnorm(50, 0.4, 0.9),
                         rnorm(50, 0, 0.9),    rnorm(50, 0.9, 0.7)))
```

The bank's information curve, overall and by area, shows where it can measure well:

```
item_info <- function(a, b, theta) {
  p <- plogis(a * (theta - b)); a^2 * p * (1 - p)
}
grid <- seq(-3, 3, by = 0.1)
bank_info <- do.call(rbind, lapply(levels(bank$area), function(ar) {
  s <- bank[bank$area == ar, ]
  data.frame(area = ar, theta = grid,
             info = sapply(grid, function(t) sum(item_info(s$a, s$b, t))))
}))
library(ggplot2)
ggplot(bank_info, aes(theta, info, fill = area)) +
  geom_area() +
  labs(x = expression(theta), y = "Bank information", fill = NULL) +
  theme_mirtverse()
```




Figure 11.1: Information of the 200-item vocabulary bank, stacked by content area.

The bank is rich in the middle and thin at the extremes, especially below $\theta = -2$ and above $\theta = 2$. Everyday vocabulary covers the low end, idioms the high end. Item writers should be asked for very easy and very hard items.

Now a 24-item fixed form with six items from each area, to measure well between $\theta = -1$ and $\theta = 1$. A greedy assembly adds, one at a time, the item that adds the most information at the target points, as long as its area is not yet full:

```
assemble_greedy <- function(bank, length, per_area, targets) {
  chosen <- integer(0)
  while (length(chosen) < length) {
    full <- names(which(table(bank$area[chosen]) >= per_area))
    cand <- setdiff(which(!bank$area %in% full), chosen)
    gain <- sapply(cand, function(i) sum(item_info(bank$a[i], bank$b[i], targets)))
    chosen <- c(chosen, cand[which.max(gain)])
  }
  bank[chosen, ]
}
form <- assemble_greedy(bank, length = 24, per_area = 6, targets = c(-1, 0, 1))
table(form$area)
#>
#>  Academic  Everyday    Idioms Workplace
#>         6         6         6         6
```

Compared with a random 24-item form that meets the same blueprint:

```
random_form <- do.call(rbind, lapply(split(bank, bank$area), function(s) s[sample(50, 6), ]))
se_at <- function(f, theta) 1 / sqrt(sapply(theta, function(t) sum(item_info(f$a, f$b, t))))
round(rbind(assembled = se_at(form, c(-1, 0, 1)),
            random = se_at(random_form, c(-1, 0, 1))), 3)
#>            [,1]  [,2]  [,3]
#> assembled 0.265 0.236 0.276
#> random    0.318 0.304 0.332
```

The assembled form measures more precisely at all three target points with the same length and blueprint. For real programmes, `assemble_forms()` in the mirtverse assessment pipeline solves the same problem exactly, builds several parallel forms at once and handles enemy items (items that must not appear together).

11.3 Example 2: a CAT from scratch

We now write a complete CAT in about 30 lines, using the same bank. The scoring step computes the EAP estimate on a grid of quadrature points, with a standard normal prior.

```
quad <- seq(-4, 4, length.out = 81)
prior <- dnorm(quad)
eap <- function(a, b, x) {
  like <- sapply(quad, function(t) prod(ifelse(x == 1, plogis(a * (t - b)),
                                               1 - plogis(a * (t - b)))))
  post <- like * prior / sum(like * prior)
  est <- sum(quad * post)
  c(theta = est, se = sqrt(sum((quad - est)^2 * post)))
}
cat_one <- function(true_theta, bank, se_stop = 0.3, max_items = 30, top = 1) {
  used <- integer(0); x <- integer(0); est <- c(theta = 0, se = 1)
  while (length(used) < max_items && est["se"] > se_stop) {
    info <- item_info(bank$a, bank$b, est["theta"]); info[used] <- -Inf
    best <- order(info, decreasing = TRUE)[seq_len(top)]
    item <- if (top == 1) best else sample(best, 1)   # randomesque exposure control
    used <- c(used, item)
    x <- c(x, rbinom(1, 1, plogis(bank$a[item] * (true_theta - bank$b[item]))))
    est <- eap(bank$a[used], bank$b[used], x)
  }
  list(theta = est[["theta"]], se = est[["se"]], n = length(used), items = used)
}
```

Simulate 300 test takers across the ability range. (To run the CAT on your own bank, replace `bank` in the data chunk of Example 1; it needs columns `item`, `area`, `a` and `b`.)

```
# Simulated test takers for the CAT: one true theta per person.
set.seed(1112)
true_theta <- rnorm(300)
```

```
runs <- lapply(true_theta, cat_one, bank = bank)
res <- data.frame(true = true_theta,
                  est = sapply(runs, `[[`, "theta"),
                  se = sapply(runs, `[[`, "se"),
                  n = sapply(runs, `[[`, "n"))
c(mean_length = mean(res$n), rmse = sqrt(mean((res$est - res$true)^2)),
  cor = cor(res$est, res$true))
#> mean_length        rmse         cor
#>      12.337       0.292       0.959
```

On average the CAT reaches a standard error of 0.3 with far fewer than 30 items. Test length depends on where a person is: in the middle, where the bank is rich, the CAT stops quickly; at the extremes it runs out of informative items and goes to the maximum.

```
ggplot(res, aes(true, n)) + geom_point(alpha = 0.5) +
  labs(x = "True theta", y = "Items administered") + theme_mirtverse()
```




Figure 11.2: Number of items administered by the CAT against true ability.

Exposure is the other side of the coin. With pure maximum-information selection, a few items are given to a large share of test takers:

```
exposure <- function(runs) {
  table(factor(unlist(lapply(runs, `[[`, "items")), levels = 1:200)) / length(runs)
}
exp_max <- exposure(runs)
sort(round(exp_max, 2), decreasing = TRUE)[1:6]
#>
```

```
#>   31  100   97   67  135  140
#> 1.00 0.68 0.64 0.60 0.48 0.48
```

The first item is the same for everybody (the most informative item at $\theta = 0$), so its exposure is 100%. The **randomesque** method picks at random among the five most informative items, which spreads exposure at a small cost in test length:

```
set.seed(1113)
runs_r <- lapply(true_theta, cat_one, bank = bank, top = 5)
exp_r <- exposure(runs_r)
rbind(max_info = c(max_exposure = max(exp_max), mean_length = mean(sapply(runs, `[[`, "n"))),
      randomesque = c(max_exposure = max(exp_r), mean_length = mean(sapply(runs_r, `[[`, "n"))))
#>             max_exposure mean_length
#> max_info           1.000        12.3
#> randomesque        0.677        12.9
```

Content balancing (for example, cycling through the four areas) works the same way: restrict the candidate items before choosing the most informative one. `simulate_cat()` in the assessment pipeline runs this kind of simulation on a real bank, and the mirtCAT package can deliver an operational CAT.

11.4 Your turn

1. Add 20 hard items ($b \sim N(2.2, 0.4)$) to the bank in Example 1 and redraw the information curve. What happens to CAT length for the most able test takers?
2. Change the stopping rule to $SE < 0.25$. How do mean length and RMSE change?
3. Add content balancing to `cat_one()` so that each test has at least four items from every area. (Hint: while an area has fewer than four items, restrict the candidates to that area.)
4. An admissions officer asks why two applicants got different questions and different numbers of questions. Write a short explanation.

Solutions

```
set.seed(1114)
hard <- data.frame(item = sprintf("H%02d", 1:20), area = factor("Idioms", levels(bank$area)),
                   a = rlnorm(20, 0.2, 0.3), b = rnorm(20, 2.2, 0.4))
bank2 <- rbind(bank, hard)
top <- true_theta > 1.5
mean(sapply(lapply(true_theta[top], cat_one, bank = bank2), `[[`, "n"))
#> [1] 14.8
mean(res$n[top])
#> [1] 17.8
```

```
runs25 <- lapply(true_theta, cat_one, bank = bank, se_stop = 0.25)
c(mean_length = mean(sapply(runs25, `[[`, "n")),
  rmse = sqrt(mean((sapply(runs25, `[[`, "theta") - true_theta)^2)))
#> mean_length        rmse
#>      18.963       0.246
```

1. The CAT reaches the target precision sooner for the most able test takers, because it now has informative items for them.
2. Tests get longer and estimates more precise: precision costs items.
3. For example: "The test adapts to each applicant: after every answer it picks the next question that tells us most about that applicant. Everyone is measured on the same scale, and the test stops when it has measured each person precisely enough, which takes fewer questions for some people than for others."

In the lab

> Lab 5, `run_lab("cat-design")`, asks whether a college should replace its fixed math placement test with a CAT. You examine the bank, run a CAT by hand, simulate it, and set exposure, content and stopping rules.

Further reading

Wainer and colleagues (2000) give an accessible introduction to CAT; van der Linden (2005) covers optimal test assembly.

Chapter 12

Cut scores, reporting and communicating results

Learning goals. After this chapter you can

- describe the Bookmark standard-setting method and build an item map at a response probability of 0.67;
- turn a cut on the θ scale into a raw-score cut;
- estimate classification accuracy and consistency at a cut score;
- report IRT results to people who do not use R, with a written summary, a report and a dashboard.

Key terms: cut score, standard setting, response probability, classification accuracy, classification consistency, test characteristic curve.

12.1 The ideas

A **cut score** divides a scale into categories such as *pass* and *fail*, or *below basic*, *proficient* and *advanced*. Where the cut goes is a judgement about what performance is good enough, made by people who know the content and the consequences. **Standard setting** is the family of structured procedures for making that judgement defensibly (Cizek and Bunch 2007).

The **Bookmark method** is closely tied to IRT. Items are ordered from easiest to hardest in an *ordered item booklet*, where each item's location is the θ at which a test taker has a fixed probability (usually 0.67, the **response probability** RP67) of answering it correctly. Each panelist places a bookmark after the last item that a *just-qualified* candidate should master. The location of the bookmarked item is that panelist's cut, and the panel's cut is usually the median over panelists after several rounds of discussion. For a 2PL item, the RP67 location is

$$\theta_{0.67} = b + \frac{\ln(0.67/0.33)}{a}.$$

Once a cut is fixed on the θ scale, two numbers describe how well the test sorts people. **Classification accuracy** is the proportion of people whose estimated category matches their true category. **Classification consistency** is the proportion who would be placed in the same category on two independent administrations of the test. Both can be estimated from a single administration using the scores and their standard errors (Rudner 2001).

Finally, results have to be communicated. People who make decisions with test scores rarely read item parameters. They need a short, honest summary of what the test measures, how precisely, for whom it works, and what the scores mean.

12.2 Example 1: setting a proficiency standard

A provincial Grade 6 science test has 36 items. We simulate a calibration on 2,500 students.

```
# Simulated 36-item science test, 2,500 students.
set.seed(1212)
a <- matrix(rlnorm(36, 0.15, 0.25)); b <- sort(rnorm(36, 0, 1))
resp <- simdata(a, matrix(-a * b), N = 2500, itemtype = "2PL")
colnames(resp) <- sprintf("S%02d", 1:36)
```

```
mod <- mirt(resp, 1, itemtype = "2PL", verbose = FALSE)
pars <- coef(mod, IRTpars = TRUE, simplify = TRUE)$items
booklet <- data.frame(item = rownames(pars), a = pars[, "a"], b = pars[, "b"])
booklet$rp67 <- booklet$b + log(0.67 / 0.33) / booklet$a
booklet <- booklet[order(booklet$rp67), ]
booklet$page <- seq_len(nrow(booklet))
head(booklet, 8)
#>     item     a      b   rp67 page
#> S02  S02 1.924 -1.473 -1.105    1
#> S01  S01 0.928 -1.827 -1.064    2
#> S03  S03 1.243 -1.387 -0.818    3
#> S05  S05 1.335 -0.955 -0.425    4
#> S06  S06 1.118 -1.011 -0.377    5
#> S04  S04 0.833 -1.090 -0.239    6
#> S08  S08 1.245 -0.741 -0.173    7
#> S10  S10 1.931 -0.488 -0.121    8
```

The ordered item booklet is `booklet`, one page per item. Suppose eight panelists, after two rounds of discussion, place their bookmarks for *proficient* on these pages:

```
bookmarks <- c(20, 22, 21, 23, 22, 24, 21, 22)
panel_cuts <- booklet$rp67[bookmarks]
theta_cut <- median(panel_cuts)
c(theta_cut = theta_cut, spread = sd(panel_cuts))
#> theta_cut    spread
#>    0.7943    0.0586
```

The standard deviation of the panelists' cuts, divided by the square root of the number of panelists, is a rough standard error of the panel's cut. It should be reported alongside the cut.

Teachers and parents see raw scores, so we convert the cut with the **test characteristic curve**: the expected number correct at θ.

```
raw_cut <- expected.test(mod, matrix(theta_cut))
c(theta_cut = theta_cut, expected_raw = raw_cut, raw_cut = ceiling(raw_cut))
#>    theta_cut expected_raw      raw_cut
#>        0.794       24.583       25.000
```

How many students are classified as proficient, and how accurately?

```
sc <- fscores(mod, full.scores.SE = TRUE)
above <- sc[, 1] >= theta_cut
p_above <- pnorm((sc[, 1] - theta_cut) / sc[, 2])
c(percent_proficient = mean(above),
  accuracy = mean(ifelse(above, p_above, 1 - p_above)),
  consistency = mean(p_above^2 + (1 - p_above)^2))
#> percent_proficient           accuracy        consistency
#>              0.204              0.925              0.893
```

Accuracy compares each student's category with where their true score probably lies; consistency asks how often two independent testings would agree (here approximated from each student's posterior probability of being above the cut). Consistency is always the lower of the two, because both testings carry error.

An item map makes the cut concrete for teachers: it shows which items a just-proficient student is likely to answer correctly (the items below the line). Printing the text of a few items on each side of the line is a good way to describe what *proficient* means.

```
library(ggplot2)
ggplot(booklet, aes(page, rp67, colour = rp67 <= theta_cut)) +
  geom_hline(yintercept = theta_cut, colour = "#C0392B", linewidth = 0.8) +
  geom_point(size = 2) +
  annotate("text", x = 1, y = theta_cut + 0.15, label = "Proficient cut",
           colour = "#C0392B", hjust = 0, size = 3.5) +
  scale_colour_manual(values = c(`TRUE` = "#2C5F8A", `FALSE` = "grey60"),
                      labels = c(`TRUE` = "mastered at the cut", `FALSE` = "not yet")) +
  labs(x = "Page in the ordered item booklet", y = "RP67 location (theta)",
       colour = NULL) +
  theme_mirtverse()
```




Figure 12.1: Item map of the ordered item booklet with the proficient cut score.

In a real programme, `item_map()` and `set_cuts()` in the assessment pipeline produce the booklet, record the panel's judgements, and report impact and classification statistics for several cuts at once.

12.3 Example 2: telling the story

We return to the attitude scale from Chapter 8 to show the reporting tools on a different kind of instrument.

```
# Four 4-category attitude items (scored 1-4), 392 respondents.
resp <- Science
```

`select_model()` and `interpret()` give a plain-language summary that is a good first draft for the methods and results sections of a report:

```
sel <- select_model(resp, verbose = FALSE)
interpret(sel$best)
#> Overview
#> --------
#> * A graded model with 1 dimension was fitted to 392 respondents and 4 items
#>   (EM estimation).
#> * The estimation converged normally.
#>
#> Model fit
#> ---------
#> * Overall model fit is poor: C2 = 19.18, df = 2, RMSEA = 0.148, CFI = 0.910,
#>   SRMSR = 0.073.
```

```
#>
#> Reliability
#> -----------
#> * Marginal reliability is 0.67 (low).
#> * Scores are too imprecise for decisions about individuals; consider adding
#>   items or using the scores only for group-level summaries.
#>
#> Targeting
#> ---------
#> * The average item location is -0.99 and the average person score is 0.00, so
#>   the test is relatively easy for this group.
#> * Measurement is most precise around theta = -2.20 (information = 2.42, SE =
#>   0.64).
#>
#> Items
#> -----
#> * No items were flagged for low discrimination, extreme location, or misfit.
#>
#> Local dependence
#> ----------------
#> * 1 item pair shows possible local dependence (Q3 exceeds the average of
#>   -0.19 by more than 0.2).
#> * Strongest: Comfort & Benefit (Q3 = 0.08).
#> * Check whether these items share a stimulus, wording, or content; consider a
#>   testlet or bifactor model.
#>
#> Person fit
#> ----------
#> * 4.8% of respondents have unusual response patterns (Zh < -1.96), which is
#>   within what chance alone would produce.
```

Read it critically before you use it: it flags the poor absolute fit and the low precision, and a careful report says what that means for the intended use of the scores.

`interpret_prompt()` packages the same results into a prompt you can paste into an AI assistant to draft a longer narrative. Nothing is sent anywhere.

For people who want to see everything, mirtverse writes a complete HTML report in one call, with the model comparison, the interpretation, tables, figures, a sum-score conversion table, item health cards and the code to reproduce it:

```
mv_report(sel, file = "science-attitudes-report.html")
```

For people who want to explore, a dashboard lets them move an ability slider, click through items and download tables, without R:

```
mv_dashboard(sel$best, title = "Attitudes to science")
export_dashboard(sel$best, "science-dashboard.html", format = "html")
```

See Sharing results with a dashboard for the options.

12.3.1 A one-page memo

Decision makers usually want one page. A structure that works:

1. **The question.** What decision will the scores support?
2. **The answer.** One or two sentences: can the test support it?
3. **The evidence.** Three to five bullets: precision where the decision is made, classification accuracy, fairness checks, any items removed.
4. **What it means.** The consequences of the cut for the people tested, for example the percentage classified in each category and how many are close to the cut.
5. **Recommendations and limits.**

12.4 Your turn

1. In Example 1, how many raw-score points does the cut move if every panelist moves their bookmark one page later?
2. Repeat the item map with RP50 instead of RP67. Does the cut move up or down? Why does the choice of response probability matter to panelists?
3. Add a second cut for *advanced* at page 30. Estimate the accuracy of the three-category classification.
4. Write the "answer" and "evidence" parts of a memo about the proficiency cut in Example 1.

Solutions

```
cut_later <- median(booklet$rp67[bookmarks + 1])
c(expected.test(mod, matrix(theta_cut)), expected.test(mod, matrix(cut_later)))
#> [1] 24.6 24.7

rp50 <- sort(booklet$b)
c(rp67_cut = theta_cut, rp50_cut = median(rp50[bookmarks]))
#> rp67_cut rp50_cut
#>    0.794    0.100

adv <- median(booklet$rp67[rep(30, 8)])
cats <- cut(sc[, 1], c(-Inf, theta_cut, adv, Inf), labels = c("below", "proficient", "advanced"))
p_cat <- cbind(pnorm((theta_cut - sc[, 1]) / sc[, 2]),
               pnorm((adv - sc[, 1]) / sc[, 2]) - pnorm((theta_cut - sc[, 1]) / sc[, 2]),
               1 - pnorm((adv - sc[, 1]) / sc[, 2]))
```

```
mean(p_cat[cbind(seq_len(nrow(p_cat)), as.integer(cats))])
#> [1] 0.88
```

1. Hardly at all here, because the items in that part of the booklet have very similar RP67 locations. Where the booklet has gaps between items, a single page can move the cut a lot, which is worth showing panelists.
2. With RP50 every item's location is lower, so the same bookmark gives a lower cut. Panelists must understand what "mastered" means (a 50% or a 67% chance), or their bookmarks will not mean what they intend.
3. For example: "The test can support a proficient/not proficient decision. About 93% of students are expected to be classified correctly, and 89% would be classified the same way if tested again. The panel's eight judgements were close together, and about one student in five is classified as proficient." Use the numbers from your own output, and add the standard error at the cut (`1 / sqrt(testinfo(mod, matrix(theta_cut)))`).

In the lab

> The course map ends with a final project: a full analysis of a dataset of the student's choice, handed in as an `mv_report()` or a dashboard plus a two-page memo. The assessment pipeline is a useful checklist for it.

Further reading

Cizek and Bunch (2007) describe the Bookmark method and other standard-setting procedures. Rudner (2001) shows how to estimate classification accuracy from IRT results. The *Standards* (American Educational Research Association et al. 2014) set out what to report about cut scores.

Appendix A

Datasets used in the book

Every example loads its data in one chunk, labelled `data-<chapter>-<n>`, at the start of the example. The table lists what each chunk defines. *Real* data come with mirt; *simulated* data are generated in the chunk itself, so the true parameters are known and the examples can check estimates against them.

Table A.1: Data chunks in the book and the objects each defines.

Chunk	Data	Kind	Defines
`data-measurement-1`	`SAT12`: 600 students, 32 five-option science items	Real	`raw`, `key`
`data-measurement-2`	8-item wellbeing scale, 0 to 3, two negatively worded items	Simulated	`resp`
`data-irt-models-1`	`LSAT7`: 1,000 test takers, 5 items	Real	`resp`
`data-irt-models-2`	20-item, four-option driving theory test with guessing	Simulated	`resp`, `true`
`data-estimation-1`	`LSAT6`: 1,000 test takers, 5 items	Real	`resp`
`data-estimation-2`	`SAT12`, scored with the corrected key	Real	`resp`, `key`
`data-dimensionality-1`	24-item mathematics test with calculation and reading dimensions	Simulated	`resp`, `a`, `d`, `sigma`

Chunk	Data	Kind	Defines
`data-dimensionality-2`	20-item reading test with a four-item passage	Simulated	`resp`
`data-fit-1`	`SAT12`, scored with the corrected key	Real	`resp`, `key`
`data-fit-2`	30-item quiz with random responders and pre-knowledge	Simulated	`resp`, `type`, `a`, `b`
`data-information-1`	`SAT12`, scored with the corrected key	Real	`resp`, `key`
`data-information-2`	Item parameters of a 90-item nursing pool	Simulated	`pool`
`data-scoring-1`	`LSAT7`	Real	`resp`
`data-scoring-2`	40-item mathematics test, true abilities known	Simulated	`resp`, `true_theta`
`data-polytomous-1`	`Science`: 392 respondents, 4 attitude items scored 1 to 4	Real	`resp`
`data-polytomous-2`	6-item job satisfaction scale, 0 to 4, one item with disordered steps	Simulated	`resp`
`data-dif-1`	25-item reading test taken on paper or tablet	Simulated	`resp`, `group`
`data-dif-2`	20-item chemistry quiz by gender	Simulated	`resp`, `group`
`data-linking-1`	Two 30-item placement forms with 10 anchors (NEAT design)	Simulated	`old`, `new`, `anchors`, `pars`
`data-linking-2`	The same two forms stacked for concurrent calibration	Simulated	`resp`, `form`
`data-banks-cat-1`	Parameters of a 200-item vocabulary bank in four areas	Simulated	`bank`
`data-banks-cat-2`	300 simulated test takers for the CAT	Simulated	`true_theta`

Chunk	Data	Kind	Defines
`data-reporting-1`	36-item Grade 6 science test	Simulated	`resp`
`data-reporting-2`	`Science`	Real	`resp`

The book deliberately does not analyse the mirtverse lab datasets (`certexam`, `numeracy`, `linking`, `catbank` and `openended`), because the labs ask students to discover problems hidden in them. They are described in the teaching labs article and on their help pages, for example `?certexam`.

Other datasets for practice

mirt ships more datasets that work well for exercises:

- `LSAT6` and `LSAT7`: short dichotomous tests (expand them with `expand.table()`).
- `deAyala`: five dichotomous mathematics items from de Ayala's textbook, as a frequency table.
- `SLF`: five dichotomous statements about social life feelings, answered by 1,490 respondents.
- `Bock1997`: a three-item polytomous test, as a frequency table.
- `ASVAB`: four arithmetic reasoning items with response counts for four groups defined by sex and race, a ready-made exercise for multiple-group models and DIF.

Use `?<name>` for the details of each.

Appendix B

Adapting the book for your course

The book is meant to be changed. Each chapter is a separate R Markdown file, each example starts from one data chunk, and the book builds with one command, so you can reorder chapters, replace examples with your own data, or add a chapter for a topic you teach.

The files

All sources are in the `book/` folder of the mirtverse repository:

Table B.1: Source files of the book.

File	Contents
`index.Rmd`	Title page and preface
`00-author.Rmd`	About the author
`01-measurement.Rmd` to `12-reporting.Rmd`	The twelve chapters, one per course week
`90-datasets.Rmd`, `91-adapting.Rmd`	The appendices
`_bookdown.yml`	Chapter order (`rmd_files`) and output folder
`_output.yml`	Look of the HTML, PDF and EPUB editions
`latex/`	Title page, preamble and box styles of the PDF edition
`cover/`	Cover artwork and how to regenerate it
`_common.R`	Code run before every chapter: loads mirtverse and sets chunk options
`references.bib`	References cited in the book

The chapter files and their ids (`{#measurement}`, `{#irt-models}` and so on) are kept stable, so links to a chapter keep working across versions.

Every chapter has the same shape

1. A **Learning goals** box.
2. **Key terms**, linked to the glossary.
3. **The ideas.**
4. **Example 1** and **Example 2**, each starting with a data chunk labelled `data-<chapter id>-1` or `-2`.
5. **Your turn**, with solutions in a folded `<details>` block.
6. **In the lab** and **Further reading**.

Keep this shape when you add a chapter, and students will always know where to look.

Swapping in your own data

To use your own data in an example, replace the body of its data chunk and keep the label and the object names listed in Appendix A. For example, to run Example 1 of Chapter 2 on your own dichotomous test:

````
```{r data-irt-models-1}
# Our midterm: 40 multiple-choice items, scored 0/1.
resp <- read.csv("midterm-scored.csv")[, -1]   # drop the ID column
```
````

The rest of the example then runs on your data. Two caveats:

- Examples built on **simulated** data compare estimates with the true values used to simulate them (objects such as `true`, `true_theta` or the planted DIF items). With real data there is no truth, so delete those comparisons or turn them into questions for students.
- The prose describes the original results. Re-read the text around each output after you swap the data, and edit the interpretation to match.

The mirtverse instructor toolkit automates these steps, for example copying a chapter into a course folder and replacing a data chunk; see the instructor toolkit guide.

Building the book

Install bookdown once, then build from the `book/` folder:

```
install.packages("bookdown")
bookdown::render_book("index.Rmd")           # the whole book, into _book/
bookdown::preview_chapter("05-fit.Rmd")      # one chapter, faster
```

Open `_book/index.html` in a browser to read the result. The whole book builds in a few minutes on a laptop. To publish your own version, put the `_book/` folder on any web server, or use GitHub Pages as the mirtverse repository does (its `book` workflow builds the book and publishes it next to the package website).

Suggesting changes

Every page has a *Suggest an edit* link at the top, which opens the chapter's source on GitHub. Corrections and new examples are welcome as issues or pull requests in the mirtverse repository.

American Educational Research Association, American Psychological Association, and National Council on Measurement in Education. 2014. *Standards for Educational and Psychological Testing*. American Educational Research Association.

Ayala, R. J. de. 2022. *The Theory and Practice of Item Response Theory*. 2nd ed. Guilford Press.

Bock, R. Darrell, and Murray Aitkin. 1981. "Marginal Maximum Likelihood Estimation of Item Parameters: Application of an EM Algorithm." *Psychometrika* 46 (4): 443–59.

Chalmers, R. Philip. 2012. "mirt: A Multidimensional Item Response Theory Package for the R Environment." *Journal of Statistical Software* 48 (6): 1–29. https://doi.org/10.18637/jss.v048.i06.

Cizek, Gregory J., and Michael B. Bunch. 2007. *Standard Setting: A Guide to Establishing and Evaluating Performance Standards on Tests*. Sage.

Cohen, Jacob. 1968. "Weighted Kappa: Nominal Scale Agreement with Provision for Scaled Disagreement or Partial Credit." *Psychological Bulletin* 70 (4): 213–20.

Crocker, Linda, and James Algina. 1986. *Introduction to Classical and Modern Test Theory*. Holt, Rinehart; Winston.

Drasgow, Fritz, Michael V. Levine, and Esther A. Williams. 1985. "Appropriateness Measurement with Polychotomous Item Response Models and Standardized Indices." *British Journal of Mathematical and Statistical Psychology* 38 (1): 67–86.

Embretson, Susan E., and Steven P. Reise. 2000. *Item Response Theory for Psychologists*. Lawrence Erlbaum Associates.

Hambleton, Ronald K., H. Swaminathan, and H. Jane Rogers. 1991. *Fundamentals of Item Response Theory*. Sage.

Holland, Paul W., and Dorothy T. Thayer. 1988. "Differential Item Performance and the Mantel-Haenszel Procedure." In *Test Validity*, edited by Howard Wainer and Henry I. Braun. Lawrence Erlbaum Associates.

Holland, Paul W., and Howard Wainer, eds. 1993. *Differential Item Functioning*. Lawrence Erlbaum Associates.

Kolen, Michael J., and Robert L. Brennan. 2014. *Test Equating, Scaling, and Linking: Methods and Practices*. 3rd ed. Springer.

Linden, Wim J. van der. 2005. *Linear Models for Optimal Test Design*. Springer.

Lord, Frederic M. 1980. *Applications of Item Response Theory to Practical Testing Problems*. Lawrence Erlbaum Associates.

Masters, Geoff N. 1982. "A Rasch Model for Partial Credit Scoring." *Psychometrika* 47 (2): 149–74.

Maydeu-Olivares, Alberto, and Harry Joe. 2006. "Limited Information Goodness-of-Fit Testing in Multidimensional Contingency Tables." *Psychometrika* 71 (4): 713–32.

Muraki, Eiji. 1992. "A Generalized Partial Credit Model: Application of an EM Algorithm." *Applied Psychological Measurement* 16 (2): 159–76.

Orlando, Maria, and David Thissen. 2000. "Likelihood-Based Item-Fit Indices for Dichotomous Item Response Theory Models." *Applied Psychological Measurement* 24 (1): 50–64.

Rudner, Lawrence M. 2001. "Computing the Expected Proportions of Misclassified Examinees." *Practical Assessment, Research, and Evaluation* 7 (14).

Samejima, Fumiko. 1969. "Estimation of Latent Ability Using a Response Pattern of Graded Scores." *Psychometrika Monograph Supplement* 34 (4, Pt. 2).

Stocking, Martha L., and Frederic M. Lord. 1983. "Developing a Common Metric in Item Response Theory." *Applied Psychological Measurement* 7 (2): 201–10.

Wainer, Howard et al. 2000. *Computerized Adaptive Testing: A Primer*. 2nd ed. Lawrence Erlbaum Associates.

Warm, Thomas A. 1989. "Weighted Likelihood Estimation of Ability in Item Response Theory." *Psychometrika* 54 (3): 427–50.

Yen, Wendy M. 1984. "Effects of Local Item Dependence on the Fit and Equating Performance of the Three-Parameter Logistic Model." *Applied Psychological Measurement* 8 (2): 125–45.