

m1

Three.js Terrain Grid System | Vertex-Based Procedural Terrain Architecture, BufferGeometry Data Model & Real-Time Grid Simulation

This lesson introduces the fundamental architecture of procedural terrain systems in Three.js, focusing on how a simple PlaneGeometry is transformed into a fully programmable vertex grid.

The key idea is a conceptual shift:

Terrain is not a mesh — it is a structured data system.

Each vertex becomes an independent computational unit inside a dynamic grid.

<https://www.udemy.com/course/web-based-3d-terrain-industrial-printing-engine-mastery/>

2. PlaneGeometry as Terrain Foundation

PlaneGeometry is used as the base structure because it provides:

- A flat surface in 3D space
- Adjustable segmentation (resolution control)
- A structured grid of vertices

• more segments → more vertices → higher detail

- Fewer segments → fewer vertices → better performance

This introduces the first major trade-off in procedural terrain design: **quality vs performance**.

3. Vertex Grid Architecture

Terrain is constructed as a **2D grid mapped into a 1D memory array**.

Structure:

- Rows → vertical division
- Columns → horizontal division
- Intersection points → vertices

Each vertex represents a unique spatial coordinate in 3D space.

This grid structure enables deterministic terrain manipulation and procedural control.

4. BufferGeometry Position System

All vertex data is stored in:

- `BufferGeometry.position`
- A `Float32Array`

Each vertex contains:

- X → horizontal position
- Y → height (elevation)
- Z → depth position

Key Transformation:

The terrain is no longer a visual object — it is a **linear numerical dataset in memory**.

5. Index-Based Vertex Mapping

Each vertex has a fixed index inside the array.

- 2D grid coordinates

Formulas:

- $\text{Row} = \text{index} / \text{width}$
- $\text{Column} = \text{index} \% \text{width}$

This mapping enables:

- Direct vertex access
- Predictable terrain structure
- Efficient procedural iteration

6. Grid Traversal System

Terrain generation uses nested loops:

- Outer loop → rows
- Inner loop → columns

For each vertex:

- Index is calculated
- Position is retrieved
- Height is modified
- Buffer is updated

This is the core mechanism behind all procedural terrain generation systems.

7. Procedural Height Generation

Terrain elevation is computed using procedural methods such as:

- Noise functions
- Heightmaps
- Mathematical formulas

The result is stored in:

- `vertex.y`

This generates natural terrain formations including:

- Mountains

- Flat regions

All generated dynamically at runtime.

8. Neighbor Relationship System

Each vertex has implicit neighbors:

- Left
- Right
- Up
- Down
- (Optional diagonals)

Although no explicit links exist, adjacency is derived from index math.

This enables:

- Smoothing algorithms
- Erosion systems
- Brush-based deformation
- Local averaging operations

9. Performance Scaling Model

Terrain resolution directly impacts performance:

- High segment count → more vertices → higher GPU cost
- Low segment count → fewer vertices → faster rendering

This introduces a critical design decision in terrain engines:

Balance between visual fidelity and computational efficiency

10. Terrain as a Data Field

The fundamental paradigm shift:

Terrain is not geometry — it is a **computational data field**.

Each vertex is:

- Addressable
- Modifiable
- Recomputable

11. Real-Time GPU Update System

When vertex data changes:

- Buffer attributes are updated
- GPU is notified via update flags
- Scene is re-rendered instantly

This enables:

- Live terrain sculpting
- Real-time procedural generation
- Continuous visual feedback loops

12. System Summary

By the end of this lesson, learners understand:

- PlaneGeometry represents a structured vertex grid
- Terrain is a programmable dataset, not a static model
- Vertices exist in a linear memory buffer
- Index mapping connects 1D memory to 2D grid logic
- Procedural generation is driven by nested loops and noise functions
- Neighbor relationships enable simulation systems
- Performance scales with vertex density
- Terrain operates as a live, real-time data field

13. Learning Outcome

Students gain the ability to:

- Understand terrain as a data-driven system
- Manipulate BufferGeometry vertex data
- Map grid-based structures in 3D space
- Build procedural terrain generation logic
- Design scalable WebGL terrain architectures
- Implement real-time simulation foundations

© 2026 Okan Kaplan – MIT License [Read full license](#)

