

# Package ‘DescriptiveStats.OBeu’

December 13, 2016

**Type** Package

**Title** Descriptive Statistics OpenBudgets.eu

**Version** 1.1.5

**Date** 2016-09-18

**Description** Descriptive Statistics and other related analysis for OBeu datasets.

**Author** Kleanthis Koupidis

**Contributor** Aikaterini Chatzopoulou <katerinachat@yahoo.com>

**Maintainer** Kleanthis Koupidis <koupidis.okfgr@gmail.com>

**URL** <https://github.com/okgreece/DescriptiveStats.OBeu>

**BugReports** <https://github.com/okgreece/DescriptiveStats.OBeu/issues>

**License** GPL-2 | file LICENSE

**LazyData** true

**Imports** grDevices,jsonlite,reshape,stats

**RoxygenNote** 5.0.1

## R topics documented:

ds.analysis . . . . .	2
ds.box . . . . .	3
ds.boxplot . . . . .	4
ds.correlation . . . . .	4
ds.frequency . . . . .	5
ds.hist . . . . .	6
ds.kurtosis . . . . .	7
ds.skewness . . . . .	7
ds.statistics . . . . .	8
nums . . . . .	9
open_spending.ds . . . . .	9
sample_json_link_openspending . . . . .	10
sample_json_link_rudolf . . . . .	11
sample_json_openspending . . . . .	11
<b>Index</b>	<b>12</b>

---

`ds.analysis`*Calculation of some Descriptive Tasks*

---

**Description**

The input of this function can be a matrix or data frame. The function calculates the basic descriptive measures, the correlation and the boxplot parameters of all the numerical variables, the frequencies of all the nominal variables and the necessary components of the selected generalized linear model.

**Usage**

```
ds.analysis(data, c.out=1.5, box.width=0.15, outliers=T, hist.class="Sturges",  
corr.method= "pearson", fr.select=NULL)
```

**Arguments**

<code>data</code>	The input data
<code>c.out</code>	Determines the length of the "whiskers" plot. If it is equal to zero no outliers will be returned.
<code>box.width</code>	The width level is determined 0.15 times the square root of the size of the input data.
<code>outliers</code>	If TRUE the outliers will be computed at the selected "c.out" level (default is 1.5 times the Interquartile Range).
<code>hist.class</code>	The method or the number of classes for the histogram.
<code>corr.method</code>	The correlation coefficient method to compute: "pearson" (default), "kendall" or "spearman".
<code>fr.select</code>	One or more nominal variables to calculate their corresponding frequencies.

**Details**

...

**Value**

A list with...

**Author(s)**

Kleanthis Koupidis

**See Also**

[open\\_spending.ds](#)

---

`ds.box`*Calculation of Statistics for the Boxplot*

---

**Description**

This function calculates the statistics for the boxplot of the numeric vector for visualization purposes.

**Usage**

```
ds.box(x, c=1.5, c.width = 0.15 , out = T)
```

**Arguments**

x	The input matrix or data frame
c	Determines the length of the "whiskers" plot. If it is equal to zero no outliers will be returned.
c.width	The width level is determined 0.15 times the square root of the size of the input vector
out	If TRUE the outliers will be computed at the selected "c" level (default is 1.5 times the Interquartile Range).

**Details**

This function returns the statistics needed to visualize boxplot.

**Value**

Returns a list with the following components:

- lo.whisker The extreme of the lower whisker
- lo.hinge The lower "hinge"
- median The median
- up.hinge The upper "hinge"
- up.whisker The extreme of the upper whisker
- box.width The width of the box (default is 0.15 times the square root of the size of the vector)
- lo.out The values of any data points which lie below the extreme of the lower whisker
- up.out The values of any data points which lie above the extreme of the upper whisker
- n The non-NA observations of the vector

**Author(s)**

Kleanthis Koupidis

**See Also**

[ds.analysis](#), [open\\_spending.ds](#)

---

ds.boxplot	<i>Calculation of Statistics for the Boxplot</i>
------------	--

---

### Description

This function calculates the statistics for the boxplot of the input numeric vector, matrix or data frame.

### Usage

```
ds.boxplot(data, out.level=1.5, width = 0.15 , outl = T)
```

### Arguments

data	The input numeric vector, matrix or data frame.
out.level	Determines the length of the "whiskers" plot. If it is equal to zero no outliers will be returned.
width	The width level is determined 0.15 times the square root of the size of the input data.
outl	If TRUE the outliers will be computed at the selected "c" level (default is 1.5 times the Interquartile Range).

### Details

This function returns the statistics needed to visualize boxplots.

### Value

Returns a list with the extracted components of [ds.box](#) for each variable of the input data.

### Author(s)

Aikaterini Chatzopoulou, Kleanthis Koupidis

### See Also

[ds.box](#), [ds.analysis](#), [open\\_spending.ds](#)

---

ds.correlation	<i>Correlation Coefficient</i>
----------------	--------------------------------

---

### Description

This functions calculates the correlation coefficient of the input vectors, matrix or data frame. By default, the correlation coefficient of pearson is computed.

### Usage

```
ds.correlation(x, y=NULL, cor.method="pearson")
```

**Arguments**

x	A vector, matrix or data frame
y	A vector, matrix or data frame
cor.method	The correlation coefficient method to compute: "pearson" (default), "kendall" or "spearman".

**Details**

This function returns an upper triangle matrix with the correlation coefficients of the input data. The correlation coefficient of pearson is computed, by default. Other options are "kendall" or "spearman".

**Author(s)**

Aikaterini Chatzopoulou, Kleanthis Koupidis

**See Also**

[ds.analysis](#), [open\\_spending.ds](#)

---

ds.frequency

*Frequencies of nominal variables*

---

**Description**

This function calculates frequencies and relative frequencies of factors/characters of the input dataset.

**Usage**

```
ds.frequency(data, select=NULL)
```

**Arguments**

data	A vector, matrix or data frame which includes at least one factor/character.
select	One or more nominal variables to calculate their corresponding frequencies.

**Details**

This function returns a data frame with the frequencies and relative frequencies of factors/characters of the input dataset.

**Author(s)**

Kleanthis Koupidis

**See Also**

[ds.analysis](#), [open\\_spending.ds](#)

---

`ds.hist`*Histogram breaks and frequencies*

---

### Description

This function computes the histogram parameters of the numeric input vector. The default for breaks is the value resulted from "Sturges" algorithm.

### Usage

```
ds.hist(x, breaks="Sturges")
```

### Arguments

x	The input numeric vector.
breaks	The method or the number of classes for the histogram.

### Details

The possible values for breaks are "Sturges"(see `nclass.Sturges`), "Scott"(see `nclass.scott`), "FD" / "Freedman-Diaconis" (see `nclass.FD`) and other integer value.

### Value

A list with the following components:

- cuts The boundaries of the histogram classes
- counts The frequency of each histogram class
- normal.curve The normal curve
- mean The average value of the input vector
- median The median value of the input data

### Author(s)

Kleanthis Koupidis

### See Also

[ds.analysis,open\\_spending.ds](#)

---

ds.kurtosis	<i>Calculation of Kurtosis</i>
-------------	--------------------------------

---

**Description**

This function calculates kurtosis of the input vector, matrix or data frame.

**Usage**

```
ds.kurtosis(x)
```

**Arguments**

x	A vector, matrix or data frame.
---	---------------------------------

**Details**

This function returns the kurtosis of numbers of the input data.

**Author(s)**

Aikaterini Chatzopoulou

**See Also**

[ds.skewness](#), [ds.statistics](#), [ds.analysis](#), [open\\_spending.ds](#)

---

ds.skewness	<i>Calculation of Skewness</i>
-------------	--------------------------------

---

**Description**

This function calculates skewness of the input vector, matrix or data frame.

**Usage**

```
ds.skewness(x)
```

**Arguments**

x	A vector, matrix or data frame.
---	---------------------------------

**Details**

This function returns the skewness of numbers of the input data.

**Author(s)**

Aikaterini Chatzopoulou

**See Also**

[ds.kurtosis](#), [ds.statistics](#), [ds.analysis](#), [open\\_spending.ds](#)

---

`ds.statistics`*Calculation of the Statistic Measures*

---

### Description

This function calculates the basic descriptive measures of the input dataset.

### Usage

```
ds.statistics(data)
```

### Arguments

`data`                      A numeric vector, matrix or data frame

### Details

This function returns the min, max, range, mean, median, 0%,25%,50%,75%,100% quantiles variance, standartdeviation, skewness and kurtosis of the input data.

### Value

A json file with the following components:

- Min The minimum observed value of the input data
- Max The maximum observed value of the input data
- Range The range, defined as the difference of the maximum and the minimum value.
- Mean The average value of the input data
- Median The median value of the input data
- Quantiles The 0%,25%,50%,75%,100% percentiles
- Variance The variance of the input data
- StandardDeviation The standard deviation of the input data
- Skewness The Skewness of the input data
- Kurtosis The Kurtosis of the input data

### Author(s)

Katerina Chatzopoulou, Kleanthis Koupidis

### See Also

[open\\_spending.ds](#)



---

nums	<i>Select the numeric columns of a given dataset</i>
------	--

---

**Description**

Extract and return a data frame with the columns that include only numeric values

**Usage**

```
nums(data)
```

**Arguments**

data                      The input data frame

**Value**

This function returns a data frame with the numeric columns of the input dataset.

**Author(s)**

Kleanthis Koupidis

---

open_spending.ds	<i>Read and Calculate the Basic Information for Basic Descriptive Tasks from Open Spending API</i>
------------------	--

---

**Description**

Extract and analyze the input data provided from Open Spending API, using the ds.analysis function.

**Usage**

```
open_spending.ds(json_data,
dimensions=NULL, amounts=NULL, measured.dimensions=NULL,
coef.outl=1.5, box.outliers=T, box.width=0.15,
cor.method= "pearson", freq.select=NULL)
```

**Arguments**

json\_data                The json string, URL or file from Open Spending API

dimensions               The dimensions of the input data

amounts                  The measures of the input data

measured.dimensions     The dimensions to which correspond amount/numeric variables

coef.outl                Determines the length of the "whiskers" plot. If it is equal to zero no outliers will be returned.

box.outliers	If TRUE the outliers will be computed at the selected "coef.outl" level (default is 1.5 times the Interquartile Range).
box.width	The width level is determined 0.15 times the square root of the size of the input data.
cor.method	The correlation coefficient method to compute: "pearson" (default), "kendall" or "spearman".
freq.select	One or more nominal variables to calculate their corresponding frequencies.

### Details

This function is used to read data in json format from Open Spending API, in order to implement some basic descriptive tasks through [ds.analysis](#) function.

### Value

A json string with the resulted parameters of the [ds.analysis](#) function.

### Author(s)

Kleanthis Koupidis

### See Also

[ds.analysis](#)

---

sample\_json\_link\_openspending

*Sample data from Open Spending*

---

### Description

Sample data of Revised Budget phase amounts

- The year (2016) of the recorded approved budget phase amounts
- The revised budget phase amounts of 2016
- The original amounts of this year
- The functional classification description
- The functional classification code

### Format

A link with the json format data

### Source

OpenSpending

---

sample\_json\_link\_rudolf

*Sample data from Rudolf API*

---

**Description**

Sample data from Rudolf API

- The year (2016) of the recorded approved budget phase amounts
- The revised budget phase amounts of 2016
- The original amounts of this year
- The functional classification description
- The functional classification code

**Format**

A link with the json format data

**Source**

Rudolf

---

sample\_json\_openspending

*Sample data from Open Spending*

---

**Description**

Sample data of Revised Budget phase amounts

- The year (2016) of the recorded approved budget phase amounts
- The revised budget phase amounts of 2016
- The original amounts of this year
- The functional classification description
- The functional classification code

**Format**

A json format file

**Source**

OpenSpending

# Index

`ds.analysis`, [2](#), [3–7](#), [10](#)  
`ds.box`, [3](#), [4](#)  
`ds.boxplot`, [4](#)  
`ds.correlation`, [4](#)  
`ds.frequency`, [5](#)  
`ds.hist`, [6](#)  
`ds.kurtosis`, [7](#), [7](#)  
`ds.skewness`, [7](#), [7](#)  
`ds.statistics`, [7](#), [8](#)  
  
`nums`, [9](#)  
  
`open_spending.ds`, [2–8](#), [9](#)  
  
`sample_json_link_openspending`, [10](#)  
`sample_json_link_rudolf`, [11](#)  
`sample_json_openspending`, [11](#)