

Program Design Phase

- ❖ Write Program Specifications
 - ◆ Analysis of requirements
 - ◆ Program specifications description
 - ◆ Describe what the goals of the program
 - ◆ Describe appearance of input and output
- ❖ Algorithm Design
 - ◆ Mathematical Analysis and Algorithm
 - ◆ Flow Chart to describe event sequencing
- ❖ Verify algorithm
 - ◆ Test with known data
 - ◆ Solve manually

Copyright © 2019 R.M. Laurie

1

1

Algorithm Design - Mathematical

- ❖ Mathematical Description
 - ◆ Boiling point
F = 212
C = 100
 - ◆ Freezing point
F = 32
C = 0

$Y = MX + B$

$F = (180 / 100) C + 32$
 $= (9/5) C + 32$
 $= 1.8 C + 32$

Copyright © 2019 R.M. Laurie

2

2

Algorithm Design - Sequence

- ❖ Flowcharts are an excellent way to plan the sequence of operations for the program to run

Copyright © 2019 R.M. Laurie

3

3

Verify Algorithm

- ❖ Testing with known data
 - ◆ Boiling point
F = 212 C = 100
 - ◆ Freezing point
F = 32 C = 0
 - ◆ Collect Data
 - ◆ Bank thermometer
 - ◆ Radio weather report
- ❖ Solve manually by hand using calculator

Copyright © 2019 R.M. Laurie

4

4


Implementation Phase

- ❖ Translate Algorithm into Code
 - ◆ Create HTML source code file embedding JavaScript code
 - ◆ Run to detect *syntax errors*
- ❖ Test Program
 - ◆ Test with known data
 - ◆ Detects program *logic errors*
 - ◆ Often requires several iterations
 - ◆ May require re-evaluation of specifications and algorithms

Copyright © 2019 R.M. Laurie 5

5

Coding First Is No Shortcut?



Copyright © 2019 R.M. Laurie 6

6

JavaScript Programming Language

- ❖ All Web browsers support the **JavaScript** client-side scripting language and contain the **JavaScript Interpreter**, which processes JavaScript commands.
- ❖ JavaScript code usually appears in the **<head>** section of the HTML document. The browser interprets the contents of the **<head>** section first, before the **<body>** of the HTML document is rendered.
- ❖ JavaScript is **Case Sensitive** and all **Keywords** must be lower case
- ❖ JavaScript is an **object based** language
- ❖ **Whitespace** is ignored = space, tabs, new lines

Copyright © 2019 R.M. Laurie 7

7

HTML <script> Element

- ❖ **<script>** element indicates to browser that text that follows is part of a script.
 - ◆ Most browser use JavaScript as the default scripting language
 - ◆ **type** attribute specifies type of scripting language and is optional for HTML5

```
<script type="text/javascript">  
    script code statements;  
</script>
```

Copyright © 2019 R.M. Laurie 8

8

JavaScript Comments and Statements


- ❖ Text contained within a JavaScript comment is not executed by the JavaScript interpreter
 - ◆ Single-line comments `// This is a comment`
 - ◆ Multi-line comments `/* This is a comment */`
- ❖ Browser that does not support scripts, ignores the `<script>` element and the script code
- ❖ All JavaScript statements end with a semicolon `;`
- ❖ JavaScript can output HTML code to the browser which then displays the contents.
`document.write ("<h3>Hello World!</h3>");`

Copyright © 2019 R.M. Laurie 9

9

JavaScript Output

- ❖ `document.write()`
 - ❖ Object is `document`
 - ❖ Method is `write` = sends string to body
- ```
<!DOCTYPE html>
<html lang="en">
 <head>
 <meta charset="utf-8">
 <title>A First Program in JavaScript</title>
 </head>
 <body>
 <script>
 document.write("<h3>Hello World!</h3>");
 </script>
 </body>
</html>
```



Copyright © 2019 R.M. Laurie 10

10

## Strings and Escape Characters

- ❖ Character Strings are denoted by enclosing text in either `'single'` or `"double quotes"`
- ❖ **Escape Characters** must use a backslash preceding the specification

Text string escape character specifications:

|                                |                                   |
|--------------------------------|-----------------------------------|
| <code>\n</code> = new line     | <code>\\</code> = backslash       |
| <code>\"</code> = double quote | <code>\'</code> = single quote    |
| <code>\t</code> = tab          | <code>\r</code> = carriage return |

Copyright © 2019 R.M. Laurie 11

11

## String Concatenation and Escape Characters

- ❖ String Concatenation Operator `+`
    - ◆ Connects two strings together
    - ◆ Special Character `\`
- ```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title>Using String Concatenation</title>
  </head>
  <body>
    <script>
      document.write("<h2>");
      document.write("Welcome to string" +
        " \"concatenation\"!</h2>");
    </script>
  </body>
</html>
```



Copyright © 2019 R.M. Laurie 12

12



JavaScript Output: Alert Window

❖ **window.alert()**

Object

Method

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="utf-8">
<title>Alert Window</title>
</head>
<body>
<h2>Click Refresh (or Reload)
to run this script again.</h2>
<script>
window.alert("Welcome to\nJavaScript\nProgramming!");
</script>
</body>
</html>
```



Copyright © 2019 R.M. Laurie 13

13

JavaScript Variables

❖ A **Variable** is a container of data

❖ Variables **declared** with **var** statement

- ◆ **var nl;** // Single variable declaration
- ◆ **var sEntry1, sEntry2, nJ, nM;** // Multiple variables
- ◆ **var nl=0, nJ=0;** // Variables can be initialized to value

❖ Declaration statements end with semicolon (;)

❖ Multiple variable declaration comma separated

❖ Variable name can be any valid **identifier**.

- ◆ An identifier is a name for a variable of function
- ◆ Consisting of letters, digits, "_" and "\$"
- ◆ Can NOT begin with a digit
- ◆ Can NOT have spaces or symbols other then _ and \$
- ◆ Can NOT be a JavaScript keyword

Copyright © 2019 R.M. Laurie 14

14

JavaScript Keywords

❖ JavaScript has only 22 keywords that can NOT be used for an identifier name.

| | | | | |
|-------|-------|----------|----------|--------|
| break | case | continue | delete | do |
| else | false | for | function | if |
| in | new | null | return | switch |
| this | true | typeof | var | void |
| while | with | | | |

❖ Twelve other keywords also can not be used for identifiers

| | | | | |
|-------|--------|---------|----------|---------|
| catch | class | const | debugger | default |
| enum | export | extends | finally | import |
| super | | | | |

Copyright © 2019 R.M. Laurie 15




15

JavaScript Prompt for Input Data

❖ **window.prompt(prompt, default)**

- ◆ Return the string entered to assigned variable

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="utf-8">
<title>What is your name</title>
</head>
<body>
<script>
var sFirstName; // String of characters input variable
sFirstName = window.prompt( "What is your name?", "" );
window.alert(sFirstName + "'s mother\nwears army boots!");
document.write("<h2>" + sFirstName
+ " she really does...</h2>");
</script>
<p>Click Refresh (or Reload) to run the script again</p>
</body>
</html>
```



Copyright © 2019 R.M. Laurie 16

16

JavaScript Data Types and Values

- ❖ JavaScript is "loosely" typed language
- ❖ Simple Data Types
 - ◆ String of text `var sFirstName, sEntry;`
 - ◆ Symbolized using `"abc123"` or `'abc123'`
 - ◆ Special Characters may be used `\n \t \b \' \" \'`
 - ◆ Numbers `var n1 = 0, fArea, fTotal = 0;`
 - ◆ 8 byte (64 bit) floating point format $\pm 1.8 \times 10^{\pm 308}$
 - ◆ `int parseInt(string)`
 - ▶ Converts string to integer (whole number)
 - ▶ Drops all fractional part to right of decimal point
 - ◆ `float parseFloat(string)`
 - ▶ Converts string to floating point (real number)
 - ▶ Keeps fractional part to right of decimal point

Copyright © 2019 R.M. Laurie

17

17

JavaScript Arithmetic Operators

- ❖ Used to perform arithmetic operations on numbers and data contained in variables, with the result usually assigned to variable
- ❖ Order of precedence determines which order the operations will be performed
- ❖ Note that the assignment operator `=` is defined last and precedence is last
- ❖ For readability insert parenthesis if order of operation not apparent in code

Copyright © 2019 R.M. Laurie

18

18

Arithmetic Operators Precedence

(Highest to Lowest)

| | |
|-------|---------------------------------------|
| () | Defines order of operation |
| - | Negative (unary) |
| * / % | Multiply, Division, Remainder |
| + - | Addition (concatenation), Subtraction |
| = | Assignment |

Copyright © 2019 R.M. Laurie

19


19

3 Exams Average Example

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Average Test Score</title>
</head>
<body>
  <script src="script.js"></script>
</body>
</html>
```

// script.js file source code

```
var fAvgScore, fScore, fTotalScore = 0;
var sEntry = window.prompt( "Enter Exam 1 Score", "0" );
fScore = parseFloat(sEntry);
fTotalScore = fTotalScore + fScore;
sEntry = window.prompt( "Enter Exam 2 Score", "0" );
fScore = parseFloat(sEntry);
fTotalScore = fTotalScore + fScore;
sEntry = window.prompt( "Enter Exam 3 Score", "0" );
fScore = parseFloat(sEntry);
fTotalScore = fTotalScore + fScore;
document.write( "Average Score = " + fTotalScore/3.0 );
```



Copyright © 2019 R.M. Laurie

20

20

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title>Double Sum Program</title>
  </head>
  <body>
    <p>Click Refresh (or Reload) to run the script again</p>
    <script>
      var sEntry1, sEntry2; // Strings entered by user
      var nNum1, nNum2, nSum; //Prompt and Receive numbers
      sEntry1 = window.prompt("Enter first number", "0");
      sEntry2 = window.prompt("Enter second number", "0");
      // Convert numbers from strings to integers
      nNum1 = parseInt(sEntry1);
      nNum2 = parseInt(sEntry2);
      // Add the numbers
      nSum = nNum1 + nNum2;
      var nDouble = nSum * 2;
      // Display the results
      document.write("<h2>The double sum is " + nDouble + "</h2>");
    </script>
  </body> </html>
```

Copyright © 2019 R.M. Laurie 21

21

A Shorter Double Sum Program

❖ Previous program with less code

- ◆ How many variables?
- ◆ Combine input prompt and parseInt in one statement
- ◆ Do calculations in output

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title>Shorter Double Sum Program</title>
    <link href="style.css" rel="stylesheet" type="text/css">
  </head>
  <body>
    <p>Click Refresh (or Reload) to run the script again</p>
    <script src="script.js"> </script>
  </body>
</html>
```

script.js file

```
var nNum1, nNum2; // Converted number entries
nNum1 = parseInt(window.prompt("Enter first number", "0"));
nNum2 = parseInt(window.prompt("Enter second number", "0"));
document.write("<h2>The double sum is " + (nNum1 + nNum2) * 2
  + "</h2>");
```

Copyright © 2019 R.M. Laurie 22

22