



Forest PPL



Table of Contents

Introduction.....	7
Scope Management (Scope Manager)	8
Trees	13
Comments.....	18
Configuration	19
Identifiers and Scope Manager	19
Public and private variables and functions	21
Compound statements (blocks)	23
Libraries	24
Keywords	25
HTML Reference	30
Service Commands	31
help	31
version	31
cls	31
shell.....	31
init	32
code	32
showcode.....	32
readcode(rc)	32
createpplcode (cpc)	33
display (d)	34
displaynodes (dn)	34
dstree.....	36
printscope.....	37
suspend and resume.....	38
debugppl (dbg)	38
traceppl.....	38
recreate	38
log	39
checksyntax	39
exit	39

sumdata	40
withset	41
start, stop.....	41
using.....	42
Special Commands	43
import	43
importlist (il)	43
eval.....	43
length	44
isexist	45
isdigits	45
Isinteger	46
Isalldigits	46
isallinteger	46
iseven, isodd	46
del	47
calc	49
sleep.....	49
getbykey (getk)	50
getbyvalue (getv)	50
set	50
setkvp.....	53
getvalue (get).....	54
getname.....	54
gettoken.....	55
type	56
Nodes and Leaves.....	57
createnode.....	57
copynode	57
getnodes	59
getleaves.....	60
definestruct	62
insertstruct	63

createstruct	63
instancename	66
functionstruct	68
dstruct.....	71
dd	71
Arithmetic operators.....	73
Logical operators.....	73
Conditional ?: operator	73
Variables and Arrays.....	74
var	74
const	75
setconst	76
array.....	77
resize.....	80
array.push.....	82
array.pop	83
array.reverse.....	84
array.shift.....	84
array.remove	84
array.clear	85
array.unshift	85
array.insert	85
array.slice.....	86
array.sum	87
array.copy	88
array.filtercopy	88
array.min.....	89
array.max.....	89
array.average.....	90
array.first	90
array.last	90
array.concat.....	90
array.sort	91

Storage	92
storage	92
sinit	93
sget	94
sset.....	94
swrite	95
sinfo	96
sresize	97
sdimsize	98
Backup & Recovery.....	100
savedata (sd).....	100
readdata (rd).....	101
Control Flow	102
if, else.....	102
switch, case, default	104
loop,do.....	106
setloopend.....	107
for	108
break.....	109
continue.....	110
Input and Output.....	111
write.....	111
write#, writeline	111
writearray	113
readline	114
Functions	115
function.....	119
call.....	128
return.....	130
getresult.....	131
funclist	131
funcname	132
argc	132

getargname.....	133
finally and failure blocks	134
Delegates and callbacks	135
delegate	135
dltinstance	136
dltset	137
dltcall.....	137
callback	138
VS Code support.....	139
Additional functionalities	141
Math	142
String.....	144
Directory	149
Queue	151
Stack.....	153
Dictionary.....	155
Convert	158
File.....	160
Random.....	162
Console	164
Vector	166
Matrix	167
DataFrame	169
StorageLib	188
Structure of User's DLL.....	193
Error detection	197
Examples of code	198
References.....	203

Introduction

ForestPPL Overview

ForestPPL is a console application developed in C++ using Microsoft Developer Studio, without relying on third-party packages. It operates on **PPL.DLL**, an implementation of the **Parenthesis Programming Language (PPL)**. Originally written in C#, the PPL code was translated into C++. PPL is an interpreted programming language in which all elements (statements, parameters, blocks) are enclosed in parentheses, resembling LISP syntax.

It includes a preprocessor to simplify code writing and reduce parentheses usage. PPL source code (**format: .scr**) is converted into an intermediate representation (**format: .ppl**) for immediate execution.

In this document, program text examples are shown as follows

```
>var x = 0
>d x
```

the results of running the examples are as follows

```
-----Variables and arrays-----
-L0      x                               [0]
```

Sign > used as prompt in interactive mode.

Key features of PPL

1. Extensibility:

- Combines C++ functionalities with custom user libraries by creating DLLs via the CodeGen.exe utility.
- Enables adding full PPL functionality to any user application.

2. Modes:

- **ppl (base) mode:** Syntax similar to LISP, using prefix notation for mathematical and logical expressions.

Examples:

```
var (x [0]);
set(x) (+ (1) (2));
set (x) ( - (0) (+ (3) (2))); // infix notation: x = -(3 + 2);
if(==(x) (1)) ...
```

- **scr (preprocessor) mode:** Syntax similar to C, using infix notation for mathematical and logical expressions.

Examples:

```
var x = 0;
set x = 1 + 2; // or x = 1 + 2;
if (x == 1)...
```

Commands in format scr may be used on the left side of the expression [\(example\)](#).

3. Parsing:

- Code written in scr mode is translated into ppl mode before execution. Each parser level creates a syntax tree.
- ForestPPL calls PPL API functions, which can also be used in other applications.

4. Execution Modes:

- The operating mode (scr or ppl) is determined by the file extension or a command in the code itself.
- scr mode simplifies coding by eliminating the need for enclosing statements in parentheses.
- Default mode is set in **Configuration.Data: (Code [ppl])**

Built-In Statements and Compound Blocks

Preprocessor includes the **following statements** –

var, const, resize,
storage statements,
array statements,
set, setkvp,cpc, sumdata,
savedata,readdata,array,
write#, writearray,call,
createstruct, insertstruct,
delegate, dlgtinstance,dlgtset,dlgtcall,callback,
setloopend,savedata,readdata

and following **compound statements (blocks)** –

definestruct,function, for, if, else, switch, case, default, finally,failure.

All ppl mode statements may be also added to scr code in format ppl if these statements do not have scr mode.

Data Handling

Unicode Storage: All data is saved as Unicode symbols, while digital data is converted into strings.

Examples:

```
set x = 5.2; saved as string "5.2"
```

Boolean values are saved as strings - "True" and "False":

```
set x = True;
```

Scope Management (Scope Manager)

ForestPPL utilizes a dedicated Scope Manager to handle memory allocation and variable lifecycles efficiently throughout the execution of a script.

- **Hierarchical Tracking:** Maintains strict tracking of execution scopes, including Global, Local, Function, and Loop boundaries.

- **Variable Lifecycle:** Handles the dynamic registration, lookup, modification, and safe removal of variables, constants, arrays, and complex structures.
- **Context Isolation:** Ensures local function variables remain isolated while safely passing arguments and resolving pointers from caller to callee scopes.
- **Dynamic Parameter Binding:** Supports advanced argument mapping across boundaries, including handling optional omitted parameters (using the # marker) and resolving loop counters.

Script Execution Stages

Script execution involves:

- Creating an array of statements (simple or compound).
- Generating a syntax tree for each statement.
- Traversing all nodes in the syntax tree and executing the associated procedures.
- Repeating the process recursively for each statement in compound blocks.
- Continuing the process for each statement in the array until completion.
- The dstree command allows users to visualize syntax trees for each script statement.

Debugging Features

ForestPPL includes commands for debugging:

- **dbg:** Enables debugging mode.
- **traceppl:** Traces code execution.
- **suspend and resume:** Temporarily pauses script execution and resumes it.
- **start and stop:** Measures the execution duration and outputs results in milliseconds.
- **On-the-fly code generation:** The script can analyze data, collect new PPL commands from them (in the form of strings) and immediately execute them.
-
- **Dynamic patches:** The ability to redefine variables, change constants or even operating logic right during program execution without restarting the kernel.
-
- **Interactive Debugging:** If you want to make a REPL console (like Python or JavaScript) for your engine, a global eval like this would be the ideal heart of it, allowing the user to tamper with memory on the fly. ForestPPL doesn't treat programmers like children from whom sharp tools must be hidden. It grants absolute control over memory and code at runtime, trusting their expertise (see command "eval").

Fundamentals

The code is executed in the order it is written without main function.

As is customary in many programming language guides the first program is:

write("Hello World!");

Another example with using Console and String libraries:

See file examples\console\colors.scr:

```
import Console;
import String;

var text = "##Hello World!##";
array colors[] = {"Black",
                  "DarkBlue", "DarkGreen", "DarkCyan",
                  "DarkRed", "DarkMagenta", "DarkYellow",
                  "Gray", "DarkGray", "Blue", "Green",
                  "Cyan", "Red", "Magenta", "Yellow", "White"};

array ArrayChars;
call String.ToCharArray(text, ArrayChars);


for(i,0,length(text))
{
    Console.ForegroundColor(colors[i]);
    Console.Write(ArrayChars[i]);
}
Console.DefaultColors();
var pos = Console.GetCursorPosition();
array separator[] = {comma,space};
array pos_array;
call String.Split(pos,separator,pos_array);
pos_array[0] = 0;           // column
pos_array[1] = pos_array[1] + 1; // row
call Console.SetCursorPosition(pos_array[0], pos_array[1]);
write(); // to new line
```



The following 4 samples illustrate the possibilities of PPL:

```
1.
>rc examples\cowsay\cowsay1.scr
array cow[] =
{
  "  _____  ",
  "< P P L >",
  "  -----  ",
  "          \  ^  ^",
  "          (oo)\_____ ",
  "          ( _)\_____ )\ /\ ",
  "          ||-----w ||",
  "          ||         ||"
};

Console.Clear();
for(i,0,length(cow))
{
  call Console.SetCursorPosition(0,i);
  call Console.Write(cow[i]);
}
call Console.SetCursorPosition(0,length(cow));
```




```
2. Added loading of second file, function call, creation node and
array under this node
>rc examples\cowsay\cowsay2.scr
```

3. Added second operator 'for' to move cow
>rc examples\cowsay\cowsay3.scr

4. Added passing data as arguments when calling command readcode
>rc examples\cowsay\cowsay4.scr 1 1 10

Trees

Functions and data are stored in PPL as several kinds of Trees – **root**, **NS**, **Functions**, **Configuration** and may be displayed on Screen, saved and restored.



Blue nodes are created automatically when ForestPPL.exe) loads or re-created when command **init** is called.

By default Tree **Functions** is filling from file **Functions\ CommonFunctions.ppl**, defined as "**default_loaded_functions**" in file **Configuration.data**. This may be changed by the user to another file. To display its contents, perform:

```
>display Functions;
```

User may perform command **readcode (rc)** to read files with user's functions and add these functions to Tree **Functions** or to node, created under Tree **Functions**.

Tree **Functions** (or nodes under Tree **Functions**) saves only functions, not data (see examples 6-8 in [function](#)).

Examples:

```
>d Functions
-----Functions-----
-N2      Sum      [function]
---L0    result1
---L1    n1
---L2    n2
---N1    #        [internal_block]
```

```
-----N2 set
-----L0      result1
-----N3      +
-----L0      n1
-----L1      n2
```

Adding functions to node under Tree Functions:

```
>createnode Functions.Calc;
function
(
  Functions.Calc.Sum(result1) (n1) (n2)
  (
    (set(result1) (+ (n1) (n2)))
  )
);
>d Functions
-----Functions-----
-N2      Calc      [Node]
---N3     Sum      [function]
-----L0 result1
-----L1 n1
-----L2 n2
-----N1 #        [internal_block]
-----N2      set
-----L0      result1
-----N3      +
-----L0      n1
-----L1      n2
```

Tree **Configuration** is filling from file **Configuration.data**, to display its contents perform:

```
>display Configuration;
(default_loaded_functions [Functions\CommonFunctions.ppl])
  //(UserFunctions1      [])
  //(UserFunctions2      [])
  //(UserFunctions3      [])
  //
  (Code                  [ppl])
  (debugppl              [no])
  (delete_all_in_readcode [yes])
  (log                   [no])
  (stay_interactive      [no])      // for ForestPPL.exe

  (ThreadPriorityHighest [yes])

  //(UserFunctions1      [Functions\printchar.ppl])
  (UserImport1           [Directory])
  (UserImport2           [Math])
  (UserImport3           [String])
  (UserImport4           [File])
  (UserImport5           [Console])

  //(UserImport6         [Convert])
  //(UserImport8         [Stack])
```

```
// (UserImport9           [Queue])
// (UserImport10          [DataFrame])
// (UserImport11          [Dictionary])
```

If **ThreadPriorityHighest = yes** (Win32 API) processing thread runs ahead of normal and above-normal threads in the process:

```
if(ThreadPriorityHighest == "yes")
    SetThreadPriority(hProcessingThread, THREAD_PRIORITY_HIGHEST);
else
    SetThreadPriority(hProcessingThread, THREAD_PRIORITY_NORMAL);
```

Any public variables (var, const, array, storage and node) are saved in Tree **Global** as common data for all functions and for code without functions(in "main function").

Public functions are available to functions from any node in Tree **Global**.

Private variables and functions are available to functions in the node, that they belong to only. Full name variables and functions include name of node.

Example:

```
createnode N1;
function
(
    N1.f()
    (
        (write("public function N1.f"))
        (N1._f())
    )
);

function
(
    N1._f()    // private
    (
        (write("private function N1._f"))
        (write(N2.x))
        //(write(N2._x))    // Error: [GetValue] [N2._x] private
                           // object, no access
        //(N2._f())        // Error: [Traversal] [N2._f] private
                           // function, no access
    )
);

createnode N2;
var(N2.x["public var N2.x"]);
var(N2._x["private var N2._x"]);
function
(
    N2._f()    // private
    (
        (write("private function N2._f"))
    )
);
```

```
);  
  
N1.f();  
write(N2.x);  
//write(N2._x);    // Error: [GetValue] [N2._x] private object, no  
                    access
```


Variables for functions are created in Tree **Local**, to display its contents perform in function:

>display Local

When exiting a function, its variables are deleted.

For illustration difference between modes scr and ppl consider the following examples:

```
>rc Examples\scr\for.scr
=== scr code for preprocessor ===
var begin = 0;
var end = 3;
for(i,begin + 1,end + 1,1)
{
    write(i);
}
=== generated by preprocessor ppl code ===
>var (begin[0]);
>var (end[3]);
>loop (i) ( + ( begin ) ( 1 ) ) ( + ( end ) ( 1 ) ) ( 1 )
(
    do
    (
        (write(i))
    )
);
1
2
3
```

Statement terminator ';' always follows after each type of statements in scr mode.

In ppl mode statement terminator ';' does not follow after statements within compound statements(blocks) – loop, switch,if,function.

Examples in ppl mode:

```
loop (i) (0) (3) (1)
(
    do
    (
        (write(hello))
        (write(world))
    )
);
```

Comments

Two kinds of commentaries are possible:

`/*...*/` - for several lines of code

and

`//` - for one line of code or part of line.

Configuration

Configuration is defined in the file **Configuration.data**, meaning of its members is explained in this tutorial.

Identifiers and Scope Manager

Names of nodes, variables, arrays, storage and functions contain any symbols, first symbol is any upper or lower case letter or any of the following symbols: `_$#`, but not a digit. Variables with first symbol `"_"` in name are hidden or private variables (see hidden variables).

A reserved name **"result"** is used for internal purposes in functions and cannot be used to create any variables.

Name **"all"** can not be used ([see cmd del](#)).

Length of identifiers is not limited. Do not set keywords and names of Libraries as identifiers.

When data is created, its full name and saved address are added to **Scope Manager**.

The **Scope Manager** intelligently manages variable lifecycles, memory cleanup, and visibility boundaries, ensuring the safety and predictability of your code.

- **Block-level scopes:** Variables and arrays created within a block (such as a loop or conditional statement) exist only within that block. Upon exiting the block, all local variables are immediately and safely deleted from memory.
- **Function isolation:** Each function call creates a strict, isolated environment. Local variables defined within a function cannot conflict with variables in the parent code. This ensures function independence and the absence of side effects, while maintaining access to global variables.
- **Intelligent variable overriding:** Variable names may be safely reused. If a local variable has the same name as a global variable, the local variable temporarily "overrides" (replaces) the global variable within its specific block, without changing the original global data.
- **Automatic conflict prevention:** The engine performs instant, real-time checks when declaring new variables. This prevents accidental name conflicts within a single scope and ensures automatic memory resizing if a variable is intentionally re-created.
- **No memory leaks:** The user never has to manually delete variables. The **Scope Manager** tracks the exact lifecycle of each data structure and immediately frees memory upon scope exit.

Symbolic values are enclosed in quotation marks, to include a quotation mark in a symbolic expression, precede it with backslash.

Example:

```
"123\"qwe" => "123"qwe"
```

Backslash before the last quote mark it is backslash, not quote mark.

```
"123\qwe\\" => "123\qwe\"
```

Public and private variables and functions

Variables, constants, arrays, storage and functions, whose names start with **underscore** are private, all other are public.

Examples:

1.

```
>code ppl;
>createnode N1;
>var(N1.x["public var N1.x"]);
>var(N1._x["private var N1._x"]);
function
(
  N1._f()    // private
  (
    (write("private function N1._f"))
    (write(N1.x))
    (write(N1._x))
  )
);
function
(
  N1.f()
  (
    (N1._f())
  )
);
N1.f();
code: ppl
private function N1._f
public var N1.x
private var N1._x
```

2.

```
>code scr;
>createnode N1;
>var N1.x = "public var N1.x";
>var N1._x = "private var N1._x";
function N1._f()    // private
{
  write("private function N1._f");
  write(N1.x);
  write(N1._x);
}
function N1.f()    // public
{
  N1._f();
}
N1.f();
```

Error occurs when re-creating a variable, it is possible to delete this variable and to create again:

```
>code scr;  
>var x;  
>var x;  
Error: [FuncCreateVariables] name [x] already exists  
>del x;  
>var x;
```

To allow re-creating use command **recreate yes**

```
>code scr;  
>var x;  
>recreate yes;  
>var x;    // re-creation
```

Compound statements (blocks)

Compound statements include one or several statements enclosed in curly brackets:

```
if (x == 1)
{
    write("COMPOUND");
    write("STATEMENTS");
}
else
{
    write("compound");
    write("statements");
}
```

If compound statements **"for"**, **"if"** contain only one **not compound statement** in curly brackets it is possible to omit brackets:

```
if (x == 1)
    write("COMPOUND");
else
    write("statements");
```

```
if (x == 1)                                // right
{
    if (y == 2)
        write("right sample");
}
```

```
if (x == 1)                                // wrong
    if (y == 2)
    {
        write("wrong sample");
    }
```

Libraries

Default name of library is **Main**, it loads always when ForestPPL.exe starts. It is possible to set in file **Configuration.data** as "UserImportN" names of additional libraries initialization loaded . To display list of loaded libraries perform:

```
>importlist;  
Main  
Directory  
Math
```

To display contents of any library perform:

<name of library>.help

or **help** for Main library

Example:

```
>Directory.help;  
help  
GetFiles  
GetDirectories  
SetCurrentDirectory  
GetCurrentDirectory
```

To get short information about any library function perform:

<name of library>.help(function name)

```
>Math.help(Sinh)  
Returns the hyperbolic sine of the specified angle:  
Math.Sinh(double value)
```

For Main Library help or ?:

```
>? d  
display | d [root|NS| Functions|Local|node name]  
display NS.namespace.name]
```


Keywords

Keyword formats are defined in this tutorial, all format are defined for **ppl mode** by default. Additionally defined format for **scr mode** for some keywords. All keywords are divided into 11 groups and presented below:

Service Commands

help, version, cls, shell, init, code, showcode, readcode, fdreadcode, createpplcode, display, displaynodes, dn, dstree, suspend, resume, debugppl, traceppl, recreate, log, exit, createcodeppl, sumdata, printscope, start, stop, checksyntax

Special Commands

import, importlist, eval, length, calc, sleep, isexist, isdigits, isinteger, isalldigits, isallinteger, iseven, isodd, del, getbykey, getbyvalue, set, setkvp, getvalue, getname, gettoken, type

Nodes and Leaves

createnode, copynode, getnodes, getleaves

Structures

definestruct, insertstruct, createstruct, dstruct, dd

Variables and Arrays

var, const, array, resize, array.push, array.pop, array.reverse, array.shift, array.remove, array.clear, array.unshift, array.insert, array.slice, array.sum, array.copy, array.min, array.max, array.average, array.first, array.last, array.concat

Storage

storage, sinit, sget, sset, swrite, sinfo, sresize, sdimsz

Backup and Recovery

savedata, readdata

Control Flow

if, else, switch, case, default, loop, do, for, break, continue, setloopend.

Input Output

write, writeline (write#), writearray, readline

Functions

function, funclist, funcname, argc, getargname, call, return, getresult

Delegates and callbacks

delegate, dlginstance, dlgset, dlgcall, callback

ForestPPL utility

Command-line REPL utility **ForestPPL.exe** is a PPL interpreter which syntax and keywords are given in this tutorial. This utility is written in C++ without any third party packages.

```

ForestPPL v.2.0.0.3

-----Init-----
-N0    root
---N1   NS
-----N2 Global
-----N2 Local
---N1   Functions
---N1   Configuration
code: scr
debugppl = no
showcode = no
log = no
stay_interactive = no
withset = no
recreate = no
ThreadPriorityHighest = yes
default_loaded_functions [Functions\CommonFunctions.ppl] have been loaded
Imported [Directory]
Imported [Math]
Imported [String]
Imported [File]
Imported [Console]

>>

-----Main-----
-----Service Commands-----
help      version    cls         shell       init        code
showcode  dstree   display    displaynodes exit        log
printscope suspend  resume     debugppl    dbg         traceppl
recreate  sumdata  withset    createpplcode readcode    fdreadcode
start     stop

-----Special Commands-----
import    importlist  eval        length      type        del
isexist   isdigits   isinteger   calc        sleep
isalldigits isallinteger iseven      isodd       getname
getbykey  getbyvalue set         setkvp      getvalue
gettoken

-----Nodes and Leaves-----
createnode  copynode  getnodes   getleaves

-----Structures-----
definestruct createstruct insertstruct dstruct    functionstruct
instancename

-----Variables and Arrays-----

```

These are following subdirectories and files used to work with ForestPPL.exe

Subdirectories:

\Data

\Examples

\Functions

\CodeGen

Files:

Configuration.data

ForestPPL.exe, DLL's.

Set Screen Buffer Size and Window Size in Properties\Layout.

There are 2 operating modes in accordance with ForestPPL.exe arguments:

1. NonInteractive mode

Execute program in file with extension scr or ppl.

```
ForestPPL.exe file [arg1 arg2 ...]  
file := file.ppl|file.scr
```

If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file. Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Value of argument is literal, not command.

When value of **stay_interactive** in file **Configuration.data** = "no" ForestPPL.exe finishes after program execution, when value of **stay_interactive** = "yes" ForestPPL.exe does not finish and continues in interactive mode.

Example:

File example.scr

```
var $1$ = $2$;  
>ForestPPL.exe example.scr x 2;
```

2. Interactive mode

ForestPPL.exe

Command input from standard input stream.

To get list of commands and their short explanation perform **help** (or ?).

Examples:

```
>? display;  
display | d [root|NS|Functions|Local|node name]  
>? d;  
display | d [root|NS|Functions|Local|node name]
```

Prompt > appears on Screen before each command.

Examples:

```
>d;  
-N1      NS  
---N2    Global  
>var x; x=1;  
>var x; set x=1;  
>var x;  
>x=1;
```

In addition to commands required to work with scr/ppl programs, ForestPPL.exe allows you to execute all Windows commands and save the results. Command **shell** uses for that.

Examples:

```
>code scr;  
>var x;  
>x = shell(cd);           // output is saved in var x  
>write(x);
```

The following often used commands and operators with one parameter may be used with or without parentheses around arguments:


help (?), import, readcode (rc), showcode, createnode, isexist, display (d), displaynodes(dn), del, code, debugppl (dbg).

HTML Reference

The interactive HTML reference guide is the primary tool for quickly finding information on ForestPPL syntax and built-in functions. The file works locally and opens in any modern web browser, providing instant access to documentation without an internet connection.

Structure of the Reference Guide

- **Syntax and Arguments:** Exact call specifications for every engine command, ranging from basic variables to multidimensional Storage structures.
- **Brief Description:** A concise explanation of what a specific function does and the results it returns.
- **Practical Examples:** Ready-to-use code snippets demonstrating the correct application of a command in real scripts, allowing you to instantly copy and paste them into your project.
- **Categorization:** Commands are logically grouped into categories (e.g., mathematics, arrays, input/output, flow control) to streamline navigation.



Service Commands

help

Displays keywords list for Library by <name> or format of command from Main library.
Library must be loaded before (see <import>)
by default name = Main, this library is loaded automatically
Format: **help** | **? keyword**

Examples:

```
>? Code;  
    Sets mode for Console input or displays on Screen  
code ppl | scr  
>? "display"    // only display in quotes  
    display | d [root|NS| Functions|Local|node name]  
    display [NS.namespace.name]
```

Any other library has function help for display its contents.

<name of library>.help [(keyword)]

```
>Matrix.help (Rotate)
```

version

Display current version

Format: **version**

cls

Clears the Screen

Format: **cls**

shell

Executes Windows Console Commands, several commands are hash symbol separated.

Results of shell may be saved or displayed by commands **write**, **write#** or by

debugppl yes

Format: **shell (command with parameters[#command with parameters])**

Examples:

```
>write(shell (cd:\));  
>dbg yes;  
>shell (dir /b tests#cd);
```

init

Deletes all data and functions and creates new root, use this command for **console input only**.

Format: **init**

code

Sets mode for Console input or displays it on Screen.

Mode scr is more convenient for writing code with blocks and for using infix expressions. But in other cases there is no difference.

Format: **code [ppl|scr]**

default - ppl

It is possible to set **code** in file **Configuration.data**.

showcode

Shows or hides on Screen ppl_code when command readcode is executed or displays showcode value on Screen

Format: **showcode [yes|no]**

Default: no

Examples:

```
>showcode no;
```

readcode(rc)

Reads file with code in format scr or ppl.

At the end of the execution readcode the previous code (scr or ppl) will be set.

Format: **readcode | rc <file.scr|ppl> [arg1 arg2 ...]**

If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file.

Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Arguments are literals, not commands.

If **delete_all_in_readcode = yes** in **Configuration.data** command

delete all is added automatically as first command when first command **readcode** is called.

The file being called may also include readcode commands. Files called by command readcode may be of different formats - .scr or .ppl.

If caller script and internal scripts are in the same path you may omit path for internals.

You may specify relatively path from ForestPPL.exe or full path, including drive:

```
>rc path\file.scr|ppl
```



```
or
>rc drive:\path\ file.scr|ppl
```

Examples

1.

```
>Directory.SetCurrentDirectory(examples\ppl);
>rc loop.ppl; // or rc examples\ppl\loop.ppl
loop (i) (0) (3) (1)
(
    do
    (
        (write("PPL"))
        (write("ppl"))
    )
);
```

2. File example.scr

```
var $1$ = $2$;
//pass arguments via rc
>rc example.scr x 2;
```

3. reading script with command readcode inside:

File main.scr:

```
write("main script");
rc examples\rc\first.scr;
rc examples\rc\second.scr;
write("return from main script");
```

File first.scr:

```
write("first script");
rc examples\rc\third.scr;
write("return from first script");
```

File second.scr:

```
write("second script");
```

File third.scr

```
write("third script");
```

```
>rc examples\rc\main.scr;
```

```
main script
first script
third script
return from first script
second script
return from main script
```

createpplcode (cpc)

Creates file in format ppl from file (or files) in format scr.

Format **ppl**: **createpplcode|cpc (file.scr) [(file.ppl) [(all)]]**

Format **scr**: **createpplcode|cpc [file.scr file.ppl [all]]**

arg **all** – include all files, loaded by command **readcode**.

Examples

```
> code ppl;
> createpplcode (ttt.scr) (ttt.ppl);
> cpc (ttt.scr) (ttt.ppl);

> code scr;
> cpc ttt.scr;
```

display (d)

Displays nodes(N) and leaves(L) in Tree.

Format:

display | d [root | Global | Functions | Configuration | Local | path_node.name]

default: **Global**

Increase Screen Buffer Size.Height in ForestPPL.exe Properies\Layout in case large number of lines.

Examples:

```
> array(y[2]) (0);
> d;
-N NS
---N Global
-----N y
-----L0 [0]
-----L1 [0]
> d Global.y;
> d y;
> d Functions.Sum;
```

displaynodes (dn)

Displays nodes(N) only.

Format:

displaynodes | dn [root | Global | Functions | Configuration | Local | path_node.name]

Increase Screen Buffer Size.Height in ForestPPL.exe Properies\Layout in case large number of lines.

Example:

```
>dn Functions
```

```
-----Functions-----
```

```
-N3      Sum      [function]
```

```
---N1    #        [internal_block]
```

```
-----N2 set
```

```
-----N3      +
```

```
-N3      Sub      [function]
```

```
---N1    #        [internal_block]
```

```
-----N2 set
```

```
-----N3      -
```

```
.....
```

dstree

Displays syntax tree per each statement in script and corresponding statement in format ppl.

dstree may be entered from script only, not from console in interactive mode.

dstree is for one-time running before presentation.

Format: **dstree()** | **dstree**

Examples:

File `examples\if.scr`

`dstree;`

`for(i,0,2)`

`{`

`if(i == 0)`

`{`

`write#("i == 0");`

`continue;`

`}`

`else`

`write#("i != 0 = {0}",i);`

`}`

`>rc examples\if.scr;`

`--N0    root`

`----N1  loop`

`-----L0        i`

`-----L1        0`

`-----L2        2`

`-----L3        1`

`-----N2        do`

`-----N3        #                    [internal_block]`

`-----N4        if`

`-----N5        ==`

`-----L0          i`

`-----L1          0`

`-----N5        #                    [internal_block]`

`-----N6          write`

`-----L0          "i == 0"`

`-----N0          continue`

`-----N4        else`

`-----N5        #                    [internal_block]`

`-----N6          write`

`-----L0          "i != 0 = {0}"`

`-----L1          i`

`code: scr`

`i == 0`

`i != 0 = 1`

printscope

The printscope command is an advanced debugging tool designed to inspect how the interpreter manages memory and execution contexts at a system level.

What it does: When executed, this command queries the scopeManager directly and outputs detailed, low-level information about the active scopes. It reveals the engine's internal tracking of contexts and variable lifetimes.

How is it different from the d (display) command? It is important to understand the distinction between these two debugging tools:

d (display): This is a user-facing command. It visually renders the hierarchical syntax tree (NS -> Global / Local) and shows the declared variables alongside their current values.

printscope: This is an engine-facing command. It focuses on the mechanics of the scopeManager, revealing the underlying stack architecture, particularly how execution contexts are pushed and popped during function calls.

When to use it: The printscope command is highly valuable when debugging complex UserFunctions. It allows you to verify that local contexts are properly isolated, arguments are correctly passed, and that the scopeManager is accurately cleaning up memory upon returning from nested blocks of code.

Format: **printscope**

Examples:

```
>var x
>createnode N1
>var N1.x
>array N1.arr[5]
>printscope
```

```
===== State of SCOPE MANAGER =====
Depth [0]
(Global)
<-- TOP (Current of Context)

* empty
* x
* N1 = 'node Node'
* N1.x
* N1.arr = 'array N1.Array 5'
```

suspend and resume

Stops script to perform manually one or several commands,
Enter **resume** - exit from command suspend and continue script execution
Enter **exit** - stop script, not exit from interpreter. If you want to exit from interpreter – run command **exit out of suspend**.

Format: **suspend**

Examples:

```
>suspend
Enter:
>d
-N1      NS
---N1    Global
>resume // continue script execution
```

debugppl (dbg)

Displays information about creation and deletion variables, results operations and duration or displays debugppl value on Screen.

Format: **debugppl | dbg [yes|no]**

It is possible to set **debugppl** in file **Configuration.data**.

Example:

```
>var (x)
>debugppl yes
>del x
leaf [x] is deleted
>duration = 0.0054401
```

traceppl

Displays all commands and function names on screen during the execution of commands. By default – traceppl no.

Format: **traceppl [yes|no]**

Example:

```
>traceppl yes;
```

recreate

Permits recreation vars, arrays, storage and nodes. By default – recreate no.

Format: **recreate [yes|no]**

Example:

```
>recreate yes;  
>code scr;  
code: scr  
>var x;  
>var x;  
>recreate no;  
>var x;  
Error: [FuncCreateVariables] name [x] already exists
```

log

Writes commands and results to logfile in directory **Log** or displays log value on Screen.

Format: **log [yes|no]**

It is possible to set **log** in file **Configuration.data**.

Opened logfile will be closed by command init or exit.

checksyntax

Checks the syntax of the code before execution, use this command for **console input only**.

Format: **checksyntax [yes|no]**

It is possible to set **checksyntax** in file **Configuration.data**.

exit

Exit from ForestPPL.exe **exit** or exit from script **exit()**.

sumdata

Defines argument type for summation. By default – **sumdata digit**.

Format:

sumdata [digit | string]

Example:

```
>code scr;
>sumdata digit;
>write#(1+2);
3
>sumdata string;
>write#(1+2);    // scr-format
12
>write(1+2);
Error: [funcWrite] name [1+2] write supports only prefix
expression
>write(+(1)(2);  // right: ppl-format
12
```

```
>sumdata string;
>var x = 1;
>call Sum(x,2);
>write#("x={0}",x);
x=12
```

It is possible to sum more than 2 items:

```
>sumdata string;
>var x;
>x = "a"+"\" + "c" + 1;
a"c1
>sumdata digit;
>var y;
>y = 1+2+3+4;
10
```

```
sumdata digit;
function f(a,b,c,q)
{
    q = a + b + c;
}
var res;
call f(1,2,3,res);
write#("res={0}",res);

sumdata string;
call f(1,2,3,res);
write#("res={0}",res);
sumdata digit;
res=6
res=123
```


withset

Adds or no operator 'set' in code

Format:

withset [yes | no]

by default **no**.

It is possible to set in file **Configuration.data**.

start, stop

For measuring duration of a script or its part.

Format:

start | start()

stop | stop (text)

Example:

```
start;
array x[10];
for(i,0,length(x))
{
    x[i] = i;
}
writearray x row;
stop("test duration:");
-----Array x-----
0, 1, 2, 3, 4, 5, 6, 7, 8, 9
test duration: 0.7918 msec
```

using

Creates nickname for long name. Variable (var,const, array,node,storage) must be created before. It is possible to use long name or nickname for access to this variable.

Format **ppl**:

using (short_name) (long_name)

Format **scr**:

using short_name = long_name

Example:

```
>code scr
>var xxxxx
>using x = xxxxx
>x = 0
>d
-N2      NS
---N3    Global
-----L0 empty    (const)
-----L1 xxxxx    [0]
---N3    Local
>write#("x = {0}",x)
x = 0
>write#("xxxxx = {0}", xxxxx)
xxxxx = 0
```

Special Commands

import

Loads Library from current directory or from user directory.

Format:

import Library name | Directory\Library name

Examples:

```
>import Math;
>import DLL\Erato;    // (see examples\scr\erato.scr)
```

importlist (il)

Displays list of loaded Libraries

Format: **importlist | il**

Examples:

```
>importlist;
Main
Math
```

eval

EVAL IS NOT EVIL

Performs the operations described by the parameter, which is a quoted string in ppl format or a variable whose value is a quoted string in ppl format.

Format: **eval ("ppl expression") | eval (variable_name)**

Examples:

```
>var x = "var(r) ; set(r) (/ (180) (Math.PI())); write(r) ;";
>eval(x) ;
>d
-N1      NS
---N2    Global
-----L0      empty                      (const)
-----L1      x      [var(r) ; set(r) (/ (180) (Math.PI())); write(r) ;]
-----L2      r      [57.29577951308232]

>write(eval("+ (1) (2)"))
3
```

```
>var x = "array (y) (1) (2) (3) ;d;"
>eval(x)
-N2      NS
---N3    Global
-----L0      empty                      (const)
-----L1      x      [array (y) (1) (2) (3) ;d;]
```

```

-----N4 y                                     [Array 3]
-----L0      #      [1]
-----L1      #      [2]
-----L2      #      [3]

```

```

>code scr
>array y[3]
>y[0] = "write(\"Hello World\")"
>eval(y[0])
Hello World

```

```

>code ppl
code: ppl
>storage(stor) (2) (2)
>sset(stor) (0) (0) ("var (x) (0);d")
>eval(sget(stor) (0) (0))

```

```

-N2      NS
---N3     Global
-----L0      empty      (const)
-----N4 stor                                     [Storage 2 2x2]
-----N5      0                                     [Array element]
-----N6      Row                                     [Array 2]
-----L0      #      [var (x[0];d)]
-----L1      #
-----N5      1                                     [Array element]
-----N6      Row                                     [Array 2]
-----L0      #
-----L1      #
-----L1      x [0]
---N3     Local

```

```

function f(x)
{
    write#("x = {0}",x);
}
var y = "f(\"Hello\");write(\" f is ended\")";
eval (y);
x = Hello
f is ended

```

```

>var x = "write(\"Hello\")"
>eval (x)
Hello

```

length

Returns length of value for var | const or length array | storage

Format: **length (var | const name | array name|storage name)**

Examples:

```
>array y[3];
>write(length(y));
3
>var (x["Hello!"]);
>write(length(x));
6
>var c = "Hello";
>write(length(c));
5
```

isexist

Determines whether var, array or storage with specified name exists or not in Global or Local, returns "True" or "False".

Format: **isexist(name)**

name:= [NS.][namespace.][node.]name

Example:

```
1.
>code scr;
>dbg yes
>var x;
>isexist (x);
True
2.
>createnode Functions.New;
>isexist (Functions.New);
True
```

isdigits

Checks is value of var or member of array or storage digital, returns "True" or "False".

Format: **isdigits(var name | member of array or storage | literal)**

Example:

```
>code scr;
>dbg yes;
>var x = 1.1;
>isdigits (x);
True
```

Isinteger

Checks is value of var or member of array or storage integer, returns, returns **"True"** or **"False"**.

Format: **isinteger(var name | member of array or storage | literal)**

```
Example:  
>code scr;  
>dbg yes;  
>var x = 1;  
>isinteger (x);  
True
```

Isalldigits

Checks is all members of array or storage digital, returns, returns **"True"** or **"False"**.

Format: **isalldigits(member of array or storage)**

```
Example:  
>code scr;  
>dbg yes;  
>array x[] = {1,2,3};  
>isalldigits (x);  
True
```

isallinteger

Checks is all members of array or storage integer, returns, returns **"True"** or **"False"**.

Format: **isallinteger(member of array or storage)**

```
Example:  
>array(x) (1) (2) (3) ;  
>isallinteger (x);  
True
```

iseven, isodd

Checks is integer value even or odd, returns **"True"** or **"False"**.

Format:

iseven(var name | member of array or storage | literal)

isodd(var name | member of array or storage | literal)

del

Deletes any kinds of data from Global or Local Tree and from ScopeManager, also deletes nodes from Functions.

Format: **del (fullname) | del fullname**

To delete all Global contents: **del all**, so name “all” can not be used as any kind of variable names.

If **"delete_all_in_readcode" = yes** in **Configuration.data** command

delete all adds automatically as first command when command **readcode** is called (**not for readdata**). Otherwise all data will be saved in memory, if necessary add this command manually.

fullname:= node path.name

node path:= node path | node

Example:

```
>createnode Node1;  
>var(Node1.x);  
//the following line removes Node1 and Node1.x  
>del Node1;  
>createnode Functions.Geo  
>del Functions.Geo
```

To re-run script, that creates array or use command **recreate yes**:

```
if(isexist(y) == True)  
    del y;  
array y[5];
```

If **"delete_all_in_readcode" = yes**

command "del all" added for external readcode only, not for internal, to save for using all variables, defined in external readcode.

Example:

```
File examples\x51.scr
var x = 0;
rc examples\x51.scr;
d;
```

```
File examples\x51.scr
array y;
```

```
>rc examples\x50.scr
```

```
code: scr
```

```
code: scr
```

```
-N2      NS
```

```
---N3    Global
```

```
-----L0      empty                (const)
```

```
-----L1      x                    [0]
```

```
-----N4 y                [Array 0]
```

```
---N3    Local
```


calc

Calculates **infix notation math. expression** and writes result on screen, may be used for ppl and scr modes, **but in interactive mode only**, not in .ppl or .scr files.

Format: **calc math.expression**

Examples:

```
>code ppl;  
>var (x) (1);  
>calc x + 2*Math.PI();  
7.283185307179586  
>code scr;  
>array arr[] = {1,2,3};  
>var x = 1;  
>calc 1 + arr[0];  
2  
>calc 1 + arr[1+1];  
4  
>calc Math.Sqrt(1+3) + 1;  
3
```

sleep

Suspends the interpreter for the specified number of milliseconds. If the script simply sleeps, the time and execution will complete. If a stopRequested signal is received, the sleep will be immediately interrupted and the program will exit without delay.

Format: **sleep(msec)**

Example:

```
>sleep(100);
```

getbykey (getk)

Gets value from array by name.

Format: **getbykey | getk (name array)(name element)**

Example:

```
See example in readdata  
>getbykey(Colors) (Black) ;  
0
```

if key is absent return **nan**.

getbyvalue (getv)

Gets name from array by value.

Format: **getbyvalue | getv (name array)(value element)**

Example:

```
See example in readdata  
>getbyvalue(Colors) (0) ;  
Black
```

if value is absent return **nan**.

set

Sets value for variable , array or storage element

Format **ppl**:

set (var_name | array_name [index]) (value | array_name [index]) |

set (storage_name[index1,index2,...])

(value | (storage_name[index1,index2,...] | array_name [index])

index:=value| ppl expression

Format **scr**:

set var_name | array_name [index] = value | scr expression

set storage_name [index1,index2,...] =

value | array_name[index] | storage_name [index1,index2,...] | scr expression

index:=value| scr expression

Command **set** checks whether array index is out of bounds.

In **scr-mode** name of command **set** may be omitted.

Examples:

```
>code ppl:  
>var (x) ;  
>set(x) (+ (1) (2)) ;  
>array(y[3]) ;  
>set(y[+(1) (2)]) (0) ;
```

```
>code scr:
>var x;
>x = 1;
>array y[3];
>y[x + 1] = 2 + 3;
>y[0] = y[1];
>y[3]=0;
Error: [SetElementArray] wrong index 3 array y out of of bounds
```

```
>code scr:
>var x;
>x = d;          // error, command "d" is running
>set x = "d";    // or x = "d";
>eval(x);        // this statement runs command "d"
```

```
>code scr;
>storage s[2,2];
>s[0,0] = s[0,1];
```

To calculate indexes for access to array elements command set in scr-mode creates temporary variables and deletes them at the end:

file test.scr

```
>showcode yes;
>array y[] = {1,2,3,4,5,6,7};
>y[1+2] = y[2+2] + 1;

array (y) (1) (2) (3) (4) (5) (6) (7) ;
var (#0[ + (1) (2) ]);
var (#1[ + (2) (2) ]);
set (y[#0])(+ (y[#1]) (1) );
del #0;
del #1;
```

I It is possible to use logical and comparison operands:

```
>code scr;
>var x;
>x = ((1==1) && (2==2)) && (3==3);
>write(x);
True
```

```
>code scr
array x[3] = 0;
x[1+1] = ((1==1) && (2==2)) && (3==3);
writearray x row;
```

The following ppl-code will be generated:

```
>array(x[3]) (0) ;
>var (#0[ + (1) (1) ]);
>set (x[#0])( && ( && ( == (1) (1) ) ( == (2) (2) ) ( ==
(3) (3) ) ) );
```

```
>del #0;  
>writearray (x ) ( row );
```

```
>var x;  
>x = 1==1? t:f;  
>write(x);
```

The following ppl-code will be generated:

```
var (x);  
if (== (1) (1) )  
(  
  (set (x) (t))  
);  
(  
  else  
  (  
    (set (x) (f))  
  )  
);  
write(x);
```

To set data in structure see ([sample](#)).

setkvp

Sets key and value array element

Format **ppl**:

setkvp(array_name [index])(key)(value | ppl expression)

index:=value | ppl expression

Format **scr**:

setkvp(array_name [index]) = key, value | scr expression)

index:=value | scr expression

Command **setkvp** checks whether index is out of bounds. For setting key and value command **setkvp** checks whether key already exists in array.

To calculate indexes for access to array elements command setkvp in scr-mode creates temporary variables and deletes them at the end (**for non-interactive mode only**):

To get key and value it is possible by commands **getbykey** and **getbyvalue**.

>code ppl:

```
>array(y[3]);  
>setkvp(y[0])(+(1)(2));  
>setkvp(y[1])("one")(1);  
>setkvp(y[2])("two")(2);
```

>code scr:

```
>var x = 1;  
>array y[3];  
>setkvp y[x + 1] = "five", 2 + 3;  
>setkvp y[0] = "null", 0;
```

In scr-mode name of command **setkvp** may be omitted:

```
>y[0] = "five", 2 + 3;  
>y[1] = "Two", 2;
```

getvalue (get)

Returns value of single var|const or array element.

Error: when argument is literal or not existed variable.

Format: **getvalue** | **get (var_name)** |
getvalue | **get(array_name[index]**

index:= value|ppl expression

Examples:

```
>array y[3] = 999;
>write#("getvalue(y[0]) = {0}",get(y[0]));
getvalue (y[0]) = 999
>write#("getvalue(y[0]) = {0}",get(yy[0]))
Error: [FuncGetValue] wrong name [yy]
```

To get data from structure see ([sample](#)).

getname

Returns name of single var|const | array | array element as string.

Error: when argument is literal or not existed variable.

Format: **getname (name)**

Examples:

1.

```
>code ppl;
>var (x) ("ppl");
>write("{0} = {1}") (getname(x)) (getvalue(x));
x = ppl
```

2.

```
function f(array: arr)
{
    write#("argname={0}   name={1}",getargname(arr), getname(arr));
}
array y;
f(y);
argname=y   name=arr
```

```
function f2(storage: stor)
{
    write#("arg_name={0} param_name={1}",
           getargname(stor),getname(stor));
}
storage s[2];
f2(s);
arg_name=s   param_name=stor
```

gettoken

Returns token in accordance with its number in string, string contains tokens, separated by "**separator**". Parts of string surrounded by quotes are passed.

As well gettoken may return number of tokens.

If number $\geq$ max number of tokens cmd returns "**Exception**".

Format: **gettoken (string)(separator)(number)**

return: **item_value**

or

gettoken (string)(separator)

return: **number of tokens**

Example:

```
1.
>dbg yes;
>gettoken("Hello,World") ("","") (0) ;
result = Hello
>gettoken("Hello,World") ("","") (1) ;
result = World
>gettoken("Hello,World") ("","") (2) ;
result = Exception
```

```
2.
>code scr;
>var x = "\"Hello,World\"", PPL";
>dbg yes
>gettoken(x) ("","") (0) ;
result = Hello,World
>gettoken(x) ("","") (1) ;
result = PPL
3.
>code ppl;
>gettoken("\"Hello,World\",PPL") ("","") (1) ;
result = PPL
4.
>gettoken("Hello,World") ("","") ;
result = 2
```

If it is needed to use math.expression or result of operation call function **GetToken** from **CommonFunctions**:

```
4.
function GetToken(text,separator,index,res)
{
    res = gettoken(text)(separator)(index);
}

var name = "Nissan.Juke";
var count;
count = gettoken(name)(".");
write#("count={0}",count);
var token;

GetToken(name)(".") ( -(count) (2) ) (token); // ppl-format
write#("token={0}",token);
call GetToken(name,".", count - 2 , token); // scr-format
write#("token={0}",token);
call GetToken(name,".",
    gettoken(name)(".") - 20 , token); // scr-format
write#("token={0}",token);
```

```
count=2;
token=Nissan
token=Nissan
token=Exception
```

type

Returns type of object (var, const, array, storage or struct).

Format: **type (name) | type name**

Example:

```
>var x;
>write(type(x));
var
```


Nodes and Leaves

createnode

Creates node in path, default path is "**Global**", it is possible to create nodes in Global, Local and Functions Trees. It will be error if name already exists (see [recreate](#)).

Format: **createnode(path.name) | createnode path.name**

Examples:

```
> createnode (Node)
> createnode Node.SubNode
>d
-N1      NS
---N1    Global
-----N2 Node
-----N3      SubNode

>createnode Functions.Geo
```

copynode

Copies one or more times node from path with new name, by default path is "Global"

Format:

copynode (src node)(dst node)[number of copies]

default number of copies: 1

Examples:

```
>code scr;
>createnode Person;
>var Person.Name;
>var Person.Family;
>var Person.Gender;
>array Person.cars[3];
>createnode Team;
>copynode (Person) (Team) ;
>Team.Name = Oscar;
>Team.Family = Ko;
>Team.Gender = m;
>setkvp Team.cars[0] = Juke,Nissan;
>setkvp Team.cars[1] = Qashqai,Nissan;
>d
-N1      NS
---N2    Global
-----N3 Person  [Node]
```

```

-----L0      Name
-----L1      Family
-----L3      Gender
-----N4      cars      [Array 3]
-----L0      #
-----L1      #
-----L2      #
-----N3 Team   [Person]
-----L0      Name      [Oscar]
-----L1      Family    [Ko]
-----L3      Gender    [m]
-----N1      cars      [Array 3]
-----L0      Juke       [Nissan]
-----L1      Qashqai    [Nissan]
-----L2      #
---N2      Local

```

```

>createnode N
>var N.x
>var N.y
>createnode N2
>copynode (N) (N2) (2)
>d

```

```

-N2      NS
---N3     Global
-----L0      empty                (const)
-----N4 N      [Node]
-----L0      x
-----L1      y
-----N4 N2     [N]
-----N5      0
-----L0      x
-----L1      y
-----N5      1
-----L0      x
-----L1      y
---N3     Local

```

getnodes

Creates (or recreates if exists) ppl_array with fullnames of nodes till defined nesting. Processing results of commands getnodes and getleaves allows you to find required information in hierarchical data structure.

Format:

getnodes (top node)((nesting))(ppl_array)

Number of required nesting it is possible to get by command displaynode.

If (nesting) do not set node names under top_node will be saved in ppl_array.

For example there is file Data\Mng2.data

```
(Staff
  (Marketing
    (Managers
      (Personal Data1 [base]
        (Name [Benjamin])
        (Salary [6000])
        (Hobby
          (sport [tennis])
          (music [jazz])
        )
      )
    )
  )
  (Clerks
    (Personal Data2 [base]
      (Name [Oliver])
      (Salary [4000])
    )
  )
  .....
)
```

Read it:

```
>readdata (data\Mng2.data) ;
>d
-N2      NS
---N3    Global
-----N4 Staff
-----N5      Marketing
-----N6      Managers
-----N7      Personal Data1  [base]
-----L0 Name      [Benjamin]
-----L1 Salary    [6000]
-----N8 Hobby
-----L0          sport      [tennis]
-----L1          music      [jazz]
-----N6      Clerks
-----N7      Personal Data2  [base]
-----L0 Name      [Oliver]
-----L1 Salary    [4000]
```

or

```
>dn Staff
-----Variables and arrays-----
-N4      Staff
---N5     Marketing
-----N6 Managers
-----N7      Personal Data1  [base]
-----N8      Hobby
-----N6 Clerks
-----N7      Personal Data2  [base]
-----N7      Personal Data3  [base]
-----N8      Hobby
-----N7      Personal Data4  [base]
-----N7      Personal Data5  [base]
-----N8      Hobby
```

Get fullnames of nodes till nesting 7 and save in ppl_array "persons":

```
>getnodes(Staff) (7) ("persons") ;
```

```
>d persons
```

```
-----Variables and arrays-----
-N4      persons [Array 21]
---L0    #      [Staff.Marketing.Managers.Personal Data1]
---L1    #      [Staff.Marketing.Clerks.Personal Data2]
---L2    #      [Staff.Marketing.Clerks.Personal Data3]
---L3    #      [Staff.Marketing.Clerks.Personal Data4]
---L4    #      [Staff.Marketing.Clerks.Personal Data5]
---L5    #      [Staff.Finance.Managers.Personal Data6]
---L6    #      [Staff.Finance.Managers.Personal Data7]
---L7    #      [Staff.Finance.Managers.Personal Data8]
---L8    #      [Staff.Finance.Clerks.Personal Data9]
---L9    #      [Staff.Finance.Clerks.Personal Data10]
---L10   #      [Staff.Finance.Clerks.Personal Data11]
---L11   #      [Staff.Operations management.Managers.Personal
                  Data12]
---L12   #      [Staff.Operations management.Managers.Personal
                  Data13]
---L13   #      [Staff.Operations management.Clerks.Personal Data14]
---L14   #      [Staff.Operations management.Clerks.Personal Data15]
---L15   #      [Staff.Operations management.Clerks.Personal Data16]
---L16   #      [Staff.Operations management.Clerks.Personal Data17]
---L17   #      [Staff.Operations management.Clerks.Personal Data18]
---L18   #      [Staff.Operations management.Clerks.Personal Data19]
---L19   #      [Staff.Human Resource.Managers.Personal Data20]
---L20   #      [Staff.Human Resource.Clerks.Personal Data21]
```

getleaves

Creates ppl_array whose elements have names and values of node.

Format:

```
getleaves(node_name | value)(ppl_array)
```

```
value = var_value | array_item_value
```

Example:

See previous example with command `getnodes`

```
>array property;  
>getleaves(Staff.Marketing.Managers.Personal Data1) (property)  
>d property
```

```
-----Variables and arrays-----
```

```
-N4      property      [Array 2]  
---L0    "Name"      [Benjamin]  
---L1    "Salary"     [6000]
```

Full code of file `Data\mng2.scr` to find persons with salary = 2000:

```
>var tmp;  
>var salary;  
>var name;  
>readdata data\Mng2.data;  
  
getnodes(Staff) (7) ("persons"); // create ppl_array persons  
for(i,0,length(persons))  
{  
  getleaves(persons[i]) ( property);  
  name = getbykey(property) ("Name");  
  salary = getbykey(property) ("Salary");  
  //write#("name={0},salary={1}",name,salary);  
  if (salary == 2000)  
  {  
    write#("[{0}] {1} {2}",persons[i], name, salary);  
  }  
}
```

```
>rc data\mng2.scr
```

```
[Staff.Marketing.Clerks.Personal Data4] Charlotte 2000  
[Staff.Marketing.Clerks.Personal Data5] Olivia 2000  
[Staff.Marketing.Clerks.Personal Data5] Olivia 2000  
[Staff.Operations management.Clerks.Personal Data18] Felix  
2000  
[Staff.Operations management.Clerks.Personal Data19] James  
2000  
[Staff.Human Resource.Clerks.Personal Data21] Sophia 2000
```

Structures

Preprocessor generates additional ppl-code for commands **definestruct**, **insertstruct** and **createststruct** so they used for non-interactive mode only (in scripts).

definestruct

Creates named block statement, that contains one or several objects - vars, arrays, storages and insertstructs. Struct named block cannot be empty, functions may be located inside **definestruct** or behind.

Variables and functions with first character "_" are private. (see example Examples\struct\TestStruct14.scr).

Format **scr**:

definestruct name

```
{  
  array ...;  
  var ...;  
  storage...;  
  insertstruct ...;  
  ...  
}
```

Example:

```
definestruct Room  
{  
  array computers[3];  
  array tables[3];  
}
```

Generated code in ppl-mode

```
definestruct  
(Room  
  (  
    (array (computers[3]) )  
    (array (tables[3]) )  
  )  
);
```

insertstruct

Inserts defined structure, previously defined by `definestruct`. It is possible to insert several instances.

Format **scr**:

insertstruct object_name [[size]] as struct_name

Example:

```
insertstruct rooms[2] as Room;
```

Generated ppl_code:


```
(createnode (rooms) )  
(copynode (rooms) (Room) (2))
```

createstruct

Creates one or several instances in accordance with structure type, previously defined by `definestruct`.

Command `createstruct` creates per each instance of struct node with name of instance, that contains all objects except of functions.

Additionally for all instances it is created one time node with name of struct, that contains struct functions only, not struct objects.



Format **scr: createstruct name[[size]] as struct_name**

Example: create struct array

```
createstruct Group[2] as Person;
```

Generated ppl_code:

```
createstruct (Group) (Person) (2) ;
```

See examples\struct\teststr4.scr

Tree of above-created object:

```
>displaynodes;
```

```
-N4      Group          [Person]
---N5    0              [Node]
-----N6 rooms         [Rooms]
-----N7      0
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
-----N7      1
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
---N5    1              [Node]
-----N6 rooms         [Rooms]
-----N7      0
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
-----N7      1
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
```

To set data for structure members it is possible by this manner (see examples above):
(see file Examples\Struct\TestStruct4.scr)

```
definestruct Room
{
    array computers[3];
    array tables[3];
}
definestruct Person
{
    var Name;
    var Family;
    insertstruct rooms[2] as Room;
}
createstruct person[2] as Person;
//person.0.Name = "John";
// index as var
var y = 0;
person.y.Name = "John";
```



```
person.y.Family = "Deere";
var x = person.y.Name;           // right;
var x1 = person.0.Name;          // right
var x2 = get(person.y.Name);     // right
write#("x = {0}",x);
write#("x1 = {0}",x1);
write#("x2 = {0}",x2);
person.y.rooms.y.computers[0] = "HPE Cray EX";
person.y.rooms.y.computers[0] = "Asus";
person.y.rooms.y.computers[1] = "Sony";
person.y.rooms.y.computers[2] = "HP";
person.y.rooms.y.tables[0] = "IKEA 70x140";
person.y.rooms.y.tables[1] = "IKEA 70x160";
person.y.rooms.y.tables[2] = "IKEA 70x200";
d Person;
d Room;
dd person;
```

instancename

Returns the current structure instance name for using in structure functions.

Format:

instancename() | instancename

Example:

```
>write(instancename);
```

File examples\struct\teststruct10.scr

```
function Print()
{
    write("Print: Global Function");
}

definestruct Script
{
    var x;
    var y;
}
functionstruct Print(Script)
{
    write#("==={0}==={1}===",funcname,instancename);
    write#("\tthis.x = {0} this.y = {1}",this.x,this.y);
}

functionstruct Foo(Script)
{
    write#("==={0}==={1}===",funcname,instancename);
    this.Print();
}
createstruct script as Script;
script.x = 100;
script.y = "PPL";
script.Foo();
script.Print();

function Script.Print()
{
    write#("==={0}==={1}===",funcname,instancename);
    write#("Updated function Print    this.x = {0} this.y = {1}",
        this.x,this.y);
}

script.Print();
Print();
```

```
>rc examples\struct\teststruct10.scr
===Script.Foo===script===
===Script.Print===script===
    this.x = 100 this.y = PPL
===Script.Print===script===
    this.x = 100 this.y = PPL
Warning: [FuncCreateFunction] function [Script.Print] is updated
===Script.Print===script===
Updated function Print    this.x = 100 this.y = PPL
Print: Global Function
```

functionstruct

Adds function to structure.

Format is the same as format of function plus structure name.

Format **ppl**:

functionstruct are located behind **definestruct** in this format:

```
functionstruct
(
    function_name
    (struct name)
    parameter_list
    ( function body )
);
function_name | struct_name::= identifier
parameter_list::= parameter [parameter_list]
parameter::= (identifier) | (identifier[default value]) | empty
function body::= (statement1) [(statement2) (statementN)]
identifier::= [var] | [array] | [storage] |
    [struct <struct_name>] | [struct array <struct_name>]:<param_name>
```

Format **scr**:

functionstruct may be located inside **definestruct** or behind in this format:

For using inside the **definestruct**:

```
functionstruct function_name
    (parameter_list)
{
    function body
}
```

For using behind the **definestruct** add struct_name:

```
functionstruct function_name
    (struct name,parameter_list)
{
    function body
}
```

```
function_name | struct_name::= identifier
parameter_list::= parameter, [parameter_list]
parameter::=
    identifier | identifier[default value] | identifier = default value | empty
function body::= statement1; [ statement2; statement; ]
identifier::= [var] | [array] | [storage]:<name>
By default parameter type is var.
```

See examples:

Examples\struct\TestStruct11.scr (functions of struct are located behind struct)

Examples\struct\TestStruct12.scr (functions of struct are located inside struct)

Any function, belonging to structure by command **funcstruct**, may be replaced behind by command **function**.

Access to struct functions and any struct objects is provided via **"this"**.

See example in Examples\Struct\TestStruct10.scr:

```
function Print()
{
    write("Global Function");
}

definestruct Script
{
    var x;
    var y;
}
functionstruct Print(Script)
{
    write#("==={0}==={1}===",funcname,instancename);
    write#("this.x = {0} this.y = {1}",this.x,this.y);
}

functionstruct Foo(Script)
{
    write#("==={0}==={1}===",funcname,instancename);
    this.Print();
}

createstruct script as Script;
script.x = 100;
script.y = "PPL";
script.Foo();
script.Print();
Print();

function script.Print()
{
    write#("==={0}==={1}===",funcname,instancename);
    write#("Updated function Print    this.x = {0} this.y =
        {1}",this.x,this.y);
}
script.Print();
```

```
===Script.Foo===script===
===Script.Print===script===
    this.x = 100 this.y = PPL
===Script.Print===script===
    this.x = 100 this.y = PPL
Warning: [FuncCreateFunction] function [Script.Print] is updated
===Script.Print===script===
Updated function Print    this.x = 100 this.y = PPL
Print: Global Function
```

Example of using delegates for functions of structures:

```
definestruct Person
{
    var name;
    var family;
    var age;
    functionstruct Init(n,f,a)
    {
        this.name = n;
        this.family = f;
        this.age = a;
    }
}
function Print2()
{
    write("global function: Print2");
}
definestruct Employee
{
    var position;
    insertstruct person as Person;
    functionstruct Print()
    {
        write( "struct function: Employee.Print");
        write#("    person: name={0} family={1} age={2}",
            this.person.name,this.person.family,this.person.age) ;
        write#("    position={0}",this.position) ;
    }
}
createstruct employee as Employee;
employee.position = "Manager";
call employee.person.Init("Johnny","Walker",40) ;

delegate myDlgt ();
dlgtinstance instance myDlgt;
dlgtset instance Print2;
dlgtcall instance();

dlgtset instance employee.Print;
dlgtcall instance();
```

dstruct

Displays contents of structure types.

Format **ppl**:

```
dstruct [ (struct_name) [(data)] ];
```

Format **scr**:

```
dstruct [ struct_name [data] ];
```

dd

Displays contents of structure instance (as well as "display") without functions.

Format: **dd instance_name**

Example:

see examples\struct\testCar.scr.

```
definestruct Car
{
    var model;
    var color;
    var year;
}
functionstruct Print(Car)
{
    write#("==={0}===", InstanceName);
    write#("model = {0},  color = {1},  year =
           {2}", this.model, this.color, this.year);
}
functionstruct Init(Car, m, c, y)
{
    this.model = m;
    this.color = c;
    this.year  = y;
}
createstruct Ford as Car;
Ford.Init("Mustang") ("Red") ("1969");
createstruct Nissan as Car;
Nissan.Init("Qashqai") ("White") ("2023");
Ford.Print();
Nissan.Print();
===Ford===
model = Mustang,  color = Red,  year = 1969
===Nissan===
model = Qashqai,  color = White,  year = 2023
```

>dd

```
-N2      NS
---N3     Global
-----L0 empty   (const)
```

```
-----N4 Ford      [Car]
-----L0      model  ["Mustang"]
-----L1      color  ["Red"]
-----L2      year   ["1969"]
-----N4 Nissan    [Car]
-----L0      model  ["Qashqai"]
-----L1      color  ["White"]
-----L2      year   ["2023"]
```


Arithmetic operators

+, -, *, /, ^, %, ++, --

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

Sum, Sub, Mul, Div, Pow

Examples in ppl prefix notation:

```
+ (x) (y)
write (+ (1) (2) (3))      // Result: 6
* (+ (x) (y)) (- (z) (3))
```

Examples in scr infix notation:

```
>code scr;
> var z = x + y + 1;
> var z = (x + y) * (z - 3);
```

Logical operators

<, <=, >, >=, ==, !=, &&, ||, xor

xor only for ppl mode

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

LT, LE, GT, GE, EQ, NE, AND, OR, XOR

Examples in ppl prefix notation:

```
== (x) (y)
&& (== (x) (y)) (== (z) (3))
```

Examples in scr infix notation:

```
x == y
(x == y) && (z == 3)
```

Conditional ?: operator

Condition ? if_true: if_false;

```
set x = 3 < 4 ? 1 : 2;
or
x = 3 < 4 ? 1 : 2;
```

Variables and Arrays

var

Creates a single variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

var (name) | (name)(initial value)

name:= [node path]name

node path:= node. | node

initial value:= value | ppl expression

ppl expression:=value | prefix notation expression

Format **scr**:

var name

var name1,name2,name3...

var name | name = initial value

var name1,name2,name3... = init_value

name:= node path.name

node path:= node. | node

initial value:= value | scr expression

scr expression:= value | infix notation expression

Examples:

```
➤ file var.scr
code scr;
recreate yes;
showcode yes;
array y[] = {1,2,3};
var X;
var x = 0;
var t = "Hello!";
var n = 2;
var p = y[0];
var q = n;
var w = y[n];
var a,s,z=0;
var pi = Math.PI();
var OneRadian = 180/Math.PI();
d;

>rc var.scr;
>code scr;
code: scr
>recreate yes;
>showcode yes;
```

```

>array (y) (1) (2) (3);
>var (X);
>var (x) (0);
>var (t) ("Hello!");
>var (n) (2);
>var (p) (y[0]);
>var (q) (n);
>var (w) (y[n]);
>var (a) (0);
>var (s) (0);
>var (z) (0);
>var (pi) (Math.PI());
>var (OneRadian) (/ (180) (Math.PI(0)) );
>d;
-N1      NS
---N2    Global
-----L0      empty                (const)
-----N3 y                [Array 3]
-----L0      #                    [1]
-----L1      #                    [2]
-----L2      #                    [3]
-----L1      x
-----L2      x                    [0]
-----L3      t                    [Hello!]
-----L4      n                    [2]
-----L5      p                    [1]
-----L6      q                    [2]
-----L7      w                    [3]
-----L8      a                    [0]
-----L9      s                    [0]
-----L10     z                    [0]
-----L11     pi                   [3.14159265358979323846]
-----L12     OneRadian            [57.29577951308232]
---N2      Local

```

Do not use Math.Function in Math.Function:

```

>var x = Math.Sin(30/(180/Math.PI())) // error

var OneRadian = 180/Math.PI();          // correct
var x = Math.Sin(30/OneRadian);

```

const

Creates a single constant variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

const (name)(initial value)

name:= [node.]name

initial value:= value | ppl expression

ppl expression:=value | prefix notation expression

Example:

```
>code ppl;  
>const (x) (0);  
>const (y[+(2) (3)]);
```

Format **scr**:

const name = initial value

const name1,name2,name3... = initial value

name:= node path.name

node path:= node. | node

initial value:= value | scr expression

scr expression:= value | infix notation expression

Examples:

```
>createnode N1;  
>code scr;  
>const N1.Greetings = "Hello"  
>write(N1.Greetings)  
Hello  
>const radian = 180 / Math.PI();  
>write(radian);  
57.2958
```

setconst

Converts var with assigned value to const.

Format **ppl**:

setconst (var_name)

Format **scr**:

setconst var_name

Example:

```
>code scr;  
>var x = 0;  
>setconst x;
```

array

Creates single-dimensional array in Global or in Local function scope as a composite parent node and registers it to Scope Manager. It will be error if array with same name already exists (see [recreate](#)).

Format **ppl**:

```

array(name [length]) [ (initial value)]
array(name)(1st item)(2nd item)...
name:= node path.name
node path:= node. | node
length:= value | ppl expression
initial value:= value | ppl expression
item:= value | ppl expression
ppl expression:=value | prefix notation expression

```

Examples:

```

>code ppl;
>var (x[10]);
>array (y[3]);
>array (y[/ (x) (2)]) (0);           // init by 0 all 5 elements
>array (y[x]) (* (x) (3));           // init by 30 all 10 elements
>array (y) (1) (x) (+ (1) (2));      // init 3 elements array = 1,10,3

```

Format **scr**:

```

array name[length];
array name [length] = initial value;
array name [] = {1st item, 2nd item,...};
name:= node path.name
node path:= node. | node
length:= value | scr expression
initial value:= value | scr expression
item:= value | scr expression
scr expression:=value | infix notation expression

```

Examples:

```

>code scr;
>array y[3];
>d
-N1      NS
---N2    Global
-----L0      empty                (const)
-----N3 y                [Array 3]
-----L0      #
-----L1      #
-----L2      #
---N2    Local

```

```
>array y[1+2] = 0;           // init by 0 all 3 elements
>array y[] = {1,2,1+2};     // init 3 elements array = 1,2,3
>var x = 1;
>array y[x+2];
```

To access an array element you need to calculate index as a separate variable:

```
>code scr;
>var x = 1;
>array y[] = {1,2,3,4,5};
var index = x + 1;
>write(y[index]);           // or write(y[2])
```

Index may be used as expression in command set. Name of command set may be omitted.

```
>set y[x + 1] = 100; // or y[x + 1] = 100;
```

Creation array with **length = 0**:

```
array arr; or
array arr[]; or
array arr[0];
```

In the following sample array with **length = 0** is created preliminary and resized in function **Directory.GetDirectories** in accordance with real length:

```
>createnode Dir;
>array Dir.dir;
>call Directory.GetDirectories(Dir.dir, "c:\\users\\");
```

The following commands in format **scr** are used without parentheses in simple statement without equal sign.

They are used with parentheses in statements as arguments of other commands or in statements with equal sign on the right side:

```
array.push,
array.shift,
array.unshift,
array.remove,
array.insert,
array.slice,
array.concat,
array.clear.
```

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>array.push y 10;           // simple statement
>write#( array.push (y) (20)); // argument of command write#
7
>writearray y row
1,2,3,4,5,10,20
```

Writing arguments in parentheses implies ppl-mode and prefix notation.

Example:

```
>code scr;  
>array y[] = {1,2,3,4,5};  
>array.remove (y) (1+1);           // wrong  
>array.remove (y) (+ (1) (1));     // right
```

See array commands examples in **examples\ArrayFunc\Samples.scr**.

Additional array service see in file **CommonFunctions.ppl**:

CsvToArray, ArrayToCsv, ArrayIsExist, ArrayIndexOf, ArrayLastIndexOf, ArrayForEach.

resize

Changes length of array, all elements are saved in changed array.

Format **ppl**:

```
resize(array_name)(new length)
resize(array_name)(new length) (init_value)
```

Format **scr**:

```
resize array_name[new length]
resize array_name[new length] = init_value
resize(array_name)(new length) [(init_value)] (supported format ppl)
```

Example 1

```
>code scr;
>array y[5] = 0;
>resize y[10];
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 10]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
-----L3      #      [0]
-----L4      #      [0]
-----L5      #
-----L6      #
-----L7      #
-----L8      #
-----L9      #
---N2    Local
>resize y[3];
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 3]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
---N2    Local
```


If `init_value` is specified this value will be set in all elements of the new array. If `init_value` is not specified old values are saved in the new array. Size of the new array may be equal zero, may be smaller or larger than the old one.

To resize storage use **`sresize`**.

array.push

Adds a new item to an array as last, returns a new size of array.

Format **ppl**: `array.push (array_name)(item_value) |`

or for key and value array (kvp)

`array.push (array_name)(item_name)(item_value)`

Format **scr**:

`array.push array_name item_value |`

`array.push (array_name, item_value) |`

`array.push (array_name, item_name, item_value) |`

`array.push array_name, item_name, item_value |`

`array.push array_name index item_value |`

`array.push (array_name)( item_name) |`

`array.push (array_name)( item_name)( item_value)`

It is possible to use variables or array items as item name or item value.

Example:

```
>code scr;
>array y;
>array.push (y,1);
>array.push (y,1 + 2);
>array.push (y,1 + array.min());
>writearray y row;
-----Array y-----
1, 3, 2
>var len = array.push(y) (1 + 2);    // error, it is PPL-forlamt
>var len = array.push(y) (+1) (2));  // right
or
>array.push(y,1+2);
>var len = length(y);
```

array.pop

Returns the latest item value and removes item.

For kvp-array returns item name and item value, separated by comma and removes item.

If array is empty: returns string **"Empty"**.

Format: **array.pop (array_name)**

Examples:

1.

```
>code scr
>array y[] = {1,2,3};
>var Result = "";
>Result = array.pop(y);    // Result = 3
>writearray y row;
-----Array y-----
1, 2
```

2.

```
>code scr
>array y[3];
>setkvp y[0] = one,1;
>setkvp y[1] = two,2;
>setkvp y[2] = three,3;
>var Result = "";
>Result = array.pop(y);    // return three,3
>write#("name={0}value={1}",
    getToken(Result)(",") (0),getToken(Result)(",") (1));
name=three value=3
>writearray y row;
-----Array y-----
1, 2
```

array.reverse

Reverses items order in array, returns a size of array;

Format **ppl**: `array.reverse (array_name)`

Format **scr**: `array.reverse array_name | array.reverse (array_name)`

array.shift

Removes the first item of the array, returns a new size of array.

Format **ppl**: `array.shift (array_name)`

Format **scr**: `array.shift array_name | array.shift (array_name)`

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>array.shift y;
>writearray y row
-----Array y-----
2,3,4,5
> write#(array.shift(y))
2
>writearray y row
-----Array y-----
3, 4
```

array.remove

Removes item by index, returns a new size of array.

Format **ppl**:

`array.remove (array_name)(index)`

Format **scr**:

`array.remove array_name index |`
`array.remove array_name, index |`
`array.remove (array_name, index) |`
`array.remove (array_name) (index)`

Example 1:

```
>array y[] = {1,2,3,4,5};
>write#("y.length = {0}",length(y))
y.length = 5
>write#("y.length = {0}",array.remove(y,1));
y.length = 4
>writearray y row
-----Array y-----
1, 3, 4, 5
```

It is possible to use variables or array items as array_name or index.

Example 2:

```
>array y[] = {1,2,3,4,5};  
>var i = 0;  
>var x = "y";  
>array.remove(get(x),i);  
>writearray y row;  
-----Array y-----  
2, 3, 4, 5
```

array.clear

Removes all items from array, returns 0.

Format **ppl**: **array.clear (array_name)**

Format **scr**: **array.clear array_name | array.clear (array_name)**

array.unshift

Adds a new item as first to an array, returns a new size of array.

Format **ppl**:

```
array.unshift (array_name)(item_value) |  
array.unshift (array_name)(item_name)(item_value)
```

Format **scr**:

```
array.push array_name item_value |  
array.push (array_name, item_value) |  
  
array.push (array_name, item_name, item_value) |  
array.push array_name, item_name, item_value |  
array.push array_name index item_value |  
array.push (array_name)( item_name) |  
array.push (array_name)( item_name)( item_value)
```

It is possible to use variables or array items as index, item name or item value.

array.insert

Inserts item before item with index, returns a new size of array.

Format **ppl**:

```
array.insert (array_name)(index)(item_value) |  
array.insert (array_name)(index)(item_name)(item_value)
```

Format **scr**:

```
array.insert (array_name,index, item_value) |  
array.insert (array_name,index, item_name, item_value)
```

It is possible to use variables or array items as index, item name or item value:

```
>array y[] = {1,2,3,4,5}
>array r[] = {1,3}
>array.insert(y, r[1], r[0])
>writearray y row
-----Array y-----
1, 2, 3, 1, 4, 5
```

array.slice

Forms a slice [of specified length] out of the current array segment starting at the specified index and return new array length or "**Error**".

Format **ppl**:

```
array.slice (array_name)(index)|
array.slice(array_name)(index)(length)
```

Format **scr**:

```
array.slice array_name index|
array.slice (array_name, index)|
array.slice (array_name, index, length) |
array.slice array_name, index, length |
array.slice array_name index length |
array.slice (array_name)(index)|
array.slice(array_name)(index)(length)
```

It is possible to use variables or array items as index or length.

index starts from 0

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>writearray y row;
-----Array y-----
1, 2, 3, 4, 5
>array.slice(y, 2);
>writearray y row;
-----Array y-----
3, 4, 5
>array.slice(y, 1, 2);
>writearray y row;
-----Array y-----
4, 5
```

array.sum

Returns the sum of all items in array. In case of error returns string "**Error**".
Format: **array.sum (array_name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {1,2,s,4,5,a};  
Info: [CreateArrayFormat1] Global array [y] is created  
>array.sum(y);  
Error: [FuncArraySum] not digital data array y[2] = s  
Error: [FuncArraySum] not digital data array y[5] = a  
Error;  
>recreate yes;  
>array y[] = {1,2,3,4,5};  
Info: [CreateArrayFormat1] Global array [y] is created  
>array.sum(y);    // 15
```

array.copy

Clean contents of destination array (dst) and resize it in accordance with size of source array (src). Copies src array to dst array. In case of error returns string "Error".

Format ppl : **array.copy (src array)(dst array)**

Format scr : **array.copy src_array dst_array |**
array.copy (src_array, dst_array) |
array.copy (src_array, dst_array) |
array.copy (src_array) (dst_array)

Example:

```
>code scr;
>array src[] = {1,2,3,4,5};
>array dst; // dst array must be created before array.copy
>array.copy src dst;
// or
// array.copy (src, dst);
// array.copy (src) (dst);
>writearray dst row;
-----Array dst-----
1, 2, 3, 4, 5
>writearray src row;
-----Array src-----
1, 2, 3, 4, 5
```

array.filtercopy

Copies src array to dst array except objects with value = 0. In case of error returns string "Error".

Format ppl : **array.filtercopy (src array)(dst array)**

Format scr : **array.filtercopy src_array dst_array |**
array.filtercopy (src_array, dst_array) |
array.filtercopy src_array, dst_array |
array.filtercopy (src_array) (dst_array)

Example:

```
>code scr;
>array src[] = {1,0,3,0,5};
>array dst; // dst array must be created before
array.filtercopy
>array.filtercopy src dst;
// or
// array.filtercopy (src, dst);
// array.filtercopy (src) (dst);
>writearray dst row;
-----Array dst-----
1, 3, 5
```



```
>writearray src row;  
-----Array src-----  
1, 2, 3, 4, 5
```

array.min

Returns the minimum value in array. In case of error returns string "**Error**".

Format: **array.min (array name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {10, 20, 5, 30};  
>array.min(y); // 5
```

array.max

Returns the maximum value in array. In case of error returns string "**Error**".

Format: **array.max (array name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {10, 20, 5, 30};  
>array.max(y); // 30
```

array.average

Returns the mean value in array. In case of error returns string "**Error**".

Format: **array.average (array name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {10, 20, 30, 40, 50};  
>array.average(y); // 30
```

array.first

Returns value of the first item in array. In case of error returns string "**Error**".

Format: **array.first (array name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {100, 200, 300};  
>array.first(y); // 100
```

array.last

Returns value of the last item in array. In case of error returns string "**Error**".

Format: **array.last (array name)**

Example:

```
>code scr;  
>dbg yes;  
>array y[] = {100, 200, 300};  
>array.last(y); // 300
```

array.concat

Concatenates several arrays to destination array, returns length of destination array or "**Error**" if one of arrays is absent.

Format **ppl**: **array.concat (array1)(array2)(...arrayN) (dst array)**

Format **scr**: **array.concat array1 array2 ...arrayN dst_array |**
array.concat (array1, array2, ...arrayN, dst_array) |
array.concat (array1)(array2)(...arrayN) (dst array)

Example:

1.

```
>code scr;  
>array y[] = {1,2,3,4,5};  
>array a[] = {10,20,30};  
>array b[] = {100,200};  
>array dst;
```

```
>array.concat y a b dst;    // simple statement
// or
//>array.concat (y, a, b, dst);
//>array.concat (y) (a) (b) (dst);

>writearray y row;
-----Array y-----
1, 2, 3, 4, 5
>writearray dst row;
-----Array dst-----
1, 2, 3, 4, 5, 10, 20, 30, 100, 200
```

2.

```
>code scr;
>array y[] = {1,2,3};
>array b[] = {4,5,6};
>array dst;
>var len = array.concat(y) (b) (dst);    // right side of statement
                                         // with equal sign

>writearray dst row;
-----Array dst-----
1, 2, 3, 4, 5, 6
>write#("length={0}",len);
length = 6
```

array.sort

Sort ppl_array in accordance with ascend or descend order.

Format **ppl**:

array.sort (array_name)(direction)

Format **scr**:

```
array.sort array_name, direction |
array.sort array_name direction |
array.sort ( array_name, direction) |
array.sort (array_name)( direction)
```

direction = ascend | descend | "ascend" | "descend"

Example:

```
>code scr;
>array y[] = {1,30,2};
>array.sort (y,ascend);
>writearray y row;
-----Array y-----
1, 2, 30
```

See array samples in examples\arrayfunc.

Storage

Service of multi-dimensional arrays is realized by storage operators in mode ppl (parameters with prefix expressions in parentheses, but may be used also in mode scr (see Examples 3).

storage

Creates one-dimensional or multi-dimensional array with dimension from 1 to N in Global or in Local function scope and registers it to ScopeManager. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

storage (name) (size dim1) |
storage (name) (size dim1) (size dim2)...
name:= node path.name
node path:= node. | node
length:= value | ppl expression
ppl expression:=value | prefix notation expression

Format **scr**:

storage storage_name [size dim1]
storage storage_name [size dim1, size dim2 ...]
storage (storage_name) (size dim1) (size dim2) ...

Examples:

```
1.
>code scr;
>recreate yes;
>storage x;
>storage x[2]; // 1-dimensional array
>storage (x) (2);
>storage x[2,3]; // 2-dimensional array

>>var x = 3
>storage s[x + 1]
>swrite s
```

0 0 0 0

```
storage s; // storage will be resized in storage.ReadFile
storage.ReadFile (s) ("examples\StorageLib\saved_10.csv") (" , ");
swrite s;
```

sinit

Init storage

Format **ppl**:

sinit (name)(initial value)

Format **scr**:

sinit name = initial value

sinit (name)(initial value)

initial value:= value | ppl expression

Examples:

```
>code scr;  
>storage x[2,3];  
>sinit x = 0;
```

sget

Gets value of element in storage

Format:

sget (name)(index1)(index2)...

Examples:

```
>storage s[3];
>var x = sget(s) (0); // get value of single-dimensional
                      // array,index=0

// get value of two-dimensional array,stor[0][0]
>storage s2[3,3];
>var x = sget(s2) (0) (0);
```

sset

Sets value for element in storage

Format **ppl: sset (name)(index1)(index2)...(value)**

Format **scr: sset name [index1,index2,...] = value**

In scr mode sset may be omitted.

Examples:

```
>code scr;
// set value of single-dimensional array,stor[0]= 1
>storage stor[3];
>sset stor[0] = 1; // or stor[0] = 1;

// set value of two-dimensional array,stor[0][0] = 1
>storage stor[2,3];
>sset stor[0,0] = 1;
> var y = 1;
>sset stor[y,y] = 2; // it is possible to use var as index
>swrite stor 30;
```

```

          0          1          2
-----NS.Global.stor-----
[0]      1
[1]              2
```

swrite

Displays elements values of storage

Format **ppl**:

swrite(name)

swrite(name) (max_window_width)

Format **scr**:

swrite name | swrite (name)

swrite name max_window_width | swrite (name) (max_window_width)

default max_window_width = 100

Examples:

```
>code scr;
```

```
>storage s1[3]
```

```
>swrite s1
```

```
0 0 0
```

```
>storage s2[3,4]
```

```
>swrite s2
```

```
0 0 0 0
0 0 0 0
0 0 0 0
```

```
>storage s3[2,3,4]
```

```
>swrite s3
```

```
--- Slice [0] ---
```

```
0 0 0 0
0 0 0 0
0 0 0 0
```

```
--- Slice [1] ---
```

```
0 0 0 0
0 0 0 0
0 0 0 0
```

sinfo

Displays size of each dimension in storage and number of items

Format **ppl**:

sinfo(name)

Format **scr**:

sinfo name | sinfo (name)

Examples:

```
>storage ss[3,4,5];
```

```
>var x;
```

```
>x = sinfo (ss);
```

```
>d x;
```

```
x = [Storage s3 [3, 4, 5] [Total leaves: 60]]
```


sresize

Allows you to dynamically resize a `storage` component at runtime. It may be used to expand or shrink a 1D array, or to modify the length of specific rows in a multi-dimensional array, enabling the creation of jagged arrays.

Format **ppl**:

sresize(name)(ind1)(ind2)(indN)... (new size)

Format **scr**:

sresize name[index1, index2, ..., new_size]

- **name**: The name of the existing storage array.
- **index** (optional): The path to the specific row or dimension you want to resize. Omitted for 1D arrays.
- **new_size**: The last parameter in the brackets always specifies the new length of the target array/row.

Key Behaviors:

- **Safe Resizing**: Existing values within the new bounds are preserved.
- **Zero Initialization**: Any newly allocated elements are automatically initialized to "0".
- **Bounds Protection**: The command includes strict boundary checks and will safely abort with an error message if an invalid path is provided.

Examples:

```
// 1D Array Resizing
storage s[2];
sresize s[5]; // Expands the array 's' to hold 5 elements.

// Jagged Array Resizing
storage jagged[3, 2];
sresize jagged[0, 5]; // Resizes only the 0th row to a length of
                      // 5 elements.
sresize jagged[1, 1]; // Shrinks the 1st row to a length of 1
                      // element.

//How to properly resize a one-dimensional array:
>storage s[2];
>sresize s[0,5];
Error: [FuncStorageResize] failed to resize. Invalid path or out
of bounds.
>sresize s[5];
>swrite(s);
```

0 0 0 0 0

sdimsz

Returns the number of children (size) of the storage node reached by following a path of branch indices from the root.

Format **ppl**:

sdimsz(name)[(idx1)(idx2)...(idxN)][(out_var)]

Semantics:

- No indices -> size of the top-level dimension (axis 0), i.e. how many slices/branches the storage has at its root.
- Each additional (idxK) descends one level further, into the child at that index, and returns THAT node's size.
- Because storages can be jagged (see sresize), a path of the same length can return different sizes depending on which branch you follow -- there is no single global "size of axis N" once branches have been resized independently.
- If the last argument is not a number, it is taken as out_var and the result is also written into that variable (same effect as a separate assignment).

Limitation: dimension_index arguments must be literal integers or already-evaluated expressions; a math expression that can't be resolved to an int is not accepted here.

Error: if the path is invalid (out of bounds, or descends into a leaf), sdimsz reports an error instead of returning -1 silently.

Example (rectangular storage, s3[3,4,5]):

```
>storage s3[3,4,5];
>var x;
>x = sdimsz(s3);           // top level -- axis 0
>d x;
-L3      x                  [3]

>x = sdimsz(s3) (0);       // descend into branch 0 -- axis 1
>d x;
-L3      x                  [4]

>x = sdimsz(s3) (0) (0);   // descend into branch 0, then its
                           // branch 0 -- axis 2
>d x;
-L3      x                  [5]
```

Example (jagged storage, after independent sresize of branches):

```
>storage s[3,2,4];
>sresize s[0,4];    // slice 0 now has 4 rows
>sresize s[1,3];    // slice 1 now has 3 rows
>sresize s[2,5];    // slice 2 now has 5 rows

>var x;
>x = sdimsize(s);    // -> 3    (still 3 slices)
>x = sdimsize(s)(0); // -> 4    (rows in slice 0)
>x = sdimsize(s)(1); // -> 3    (rows in slice 1)
>x = sdimsize(s)(2); // -> 5    (rows in slice 2)
>x = sdimsize(s)(1)(2); // -> 4    (columns in row 2 of slice 1)

>sdimsize(s3)(0)(0,x); // out_var form: writes the result
                        // into x as well
```

Backup & Recovery

savedata | (sd)

Saves data from node to file with extension **.data**.

If node is root, all root contents will be saved.

Format **ppl: savedata | sd (filename.data) [(node)]**

Format **scr: savedata | sd filename.data [node]**

Default node: **NS.Global**

Example:

```
>storage s[3,3]
>array y[3]
>createnode Node1
>var Node1.x = 0
>sd "Examples\SaveGlobal.data"
(Global
  (empty)
    (s [Storage]
      (_shape_
        (# "3,3"))
      )
      (row_0
        (# "0")
        (# "0")
        (# "0")
      )
      (row_1
        (# "0")
        (# "0")
        (# "0")
      )
      (row_2
        (# "0")
        (# "0")
        (# "0")
      )
    )
  )
  (y [Array 3]
    (#)
    (#)
    (#)
  )
  (Node1 [Node]
    (x [0])
  )
)
```

readdata (rd)

Reads data from file file with extension **.data** to Nodes Configuration and NS.Global, **not to Local**.

Format **ppl: readdata | rd (filename.data)[(node)]**
readdata | rd filename.data

Format **scr: readdata | rd filename.data [node]**

Default node: **NS.Global**

Examples:

```
>code scr
>rd "Data\Colors.data";
>d;
-N NS
---N Global
-----N Colors
-----L0      Black      [0]
-----L1      Blue       [9]
-----L2      Cyan       [11]
-----L3      DarkBlue   [1]
-----L4      DarkCyan   [3]
-----L5      DarkGray   [8]
-----L6      DarkGreen   [2]
-----L7      DarkMagenta [5]
-----L8      DarkRed     [4]
-----L9      DarkYellow  [6]
-----L10     Gray       [7]
-----L11     Green      [10]
-----L12     Magenta    [13]
-----L13     Red        [12]
-----L14     White      [15]
-----L15     Yellow     [14]
```

Each item in this array has key (Black, Blue,...) and value(0,9,...), use [getbykey](#) and [getbyvalue](#).

```
>createnode NODE
var filename = "data\Colors.data";
>rd filename NODE;
>d;
-N1 NS
---N2 Global
-----L0      empty      (const)
-----N3 NODE           [Node]
-----N4      Colors     [Array 15]
-----L0      Black      [0]
-----L1      Blue       [9]
-----L2      Cyan       [11]
-----L3      DarkBlue   [1]
.....
```

Control Flow

if, else

The meaning of the block "if-else" does not differ from the generally accepted. See [Base Concepts](#) about using statements terminator ";" in if.

Format **ppl**:

```
if (condition)
(
    (statement)
    (statement)
    [ (else
        (
            (statement)
            (statement)
        )
    ) ]
);
```

Here expression in prefix notation.

Statement in ppl mode.

Format **scr**:

```
if (condition)
{
    statement;
    statement;
    [else
    {
        statement;
        statement;
    } ]
}
```

Here expression in infix notation.

Statement in ppl or scr mode.

Example ppl mode:

```
var (x[1]) ;
var (y[1]) ;
if (==(x) (y))
(
    (write(TRUE))
    (else
        (
            (write(FALSE))
        )
    )
);
TRUE
```

Examples in scr mode:

```
var x = 1;
var y = 1;
if ( x == y )
{
    write(TRUE);
}
else
{
    write(FALSE);
}
```

```
var x;
if(x == empty)
    write("x = empty");
```

If block in "if" or in "else" contains only one statement it is possible to omit { }:

```
code scr;
var x = 0;
if(x == 1)
    write(TRUE);
else
    write(FALSE);
FALSE
```

switch, case, default

switch statement – for select one from several case blocks to be executed.

About using statements terminator ";" in switch see [Base Concepts](#).

Format **ppl**:

```
switch(expression)
(
    (case1) [(case2) ...]
    (
        (statement)
        (statement)
        ...
    )
    (caseN) ...
    (
        (statement)
        (statement)
        ...
    )
    ...
    [ (default)
    (
        (statement)
        (statement)
        ...
    )
]
);
```

Here expression in prefix notation.

Statements in ppl mode.

Format **scr**:

```
switch(expression)
{
    case <value>:
    case <value>:
        statement;
        statement;
        ...
    break;
    case <value>:
        statement;
        statement;
        ...
    break;
    [
    default:
        statement;
        statement;
```



```
    ...  
    break;  
  ]  
} Here expression in infix notation.  
Statement in r scr mode.
```

Examples:

Format **ppl**:

1.

```
switch(x)  
(  
  (1) (3)  
  (  
    (write("Cases 1 & 3"))  
  )  
);
```

2.

```
var (x[1]);  
switch (x)  
(  
  (1) (3)  
  (  
    (write("Case 1 & 3"))  
  )  
  (2)  
  (  
    (write("Case 2"))  
  )  
  (default)  
  (  
    (write("Default"))  
  )  
);  
Case 1 & 3
```

3.Format scr

```
var x = 2;  
switch(x)  
{  
  case 1: case 3:  
    write("Case 1 & 3");  
  break;  
  case 2:  
    write("Case 2");  
  break;  
  default:  
    write("Default");  
  break;  
}
```

loop,do

Iteration block for ppl mode only.

About using statements terminator ";" in loop see [Base Concepts](#).

Format **ppl**:

```
loop (iteration var) (begin) (end) [(step)] or
```

```
loop () //infinity loop
```

```
(do
```

```
(
```

```
    (statement)
```

```
    (statement)
```

```
    ...
```

```
)
```

```
)
```

```
begin:= value|ppl expression
```

```
end:= value|ppl expression
```

```
step:= value|ppl expression
```

By default step = 1. Step may positive or negative.

Parameter end is set before entry to iteration block and may be changed by

setlopend inside iteration block.

Statement in ppl mode.

Examples:

```
loop (i) (0) (10) (1)      // or loop (i) (10) (0) (-1)
(do
  (
    (write("i = {0}") (i))
  )
);
```

See infinity example – greatest common factor (gcf) calculation in [for](#)

setloopend

Changes "end" in loop (iteration var)(begin)(end)[(step)] inside iteration block

Format **ppl**:

setloopend(end_value)

Format **scr**:

setloopend end_value

Example:

1.

```
array arr[10] = 0;
for(j,0,length(arr))
{
    write#("j = {0}    length = {1}",j,length(arr));
    array.remove(arr)(0);
    setloopend length(arr);
}
writearray arr row;
j = 0    length = 10
j = 1    length = 9
j = 2    length = 8
j = 3    length = 7
j = 4    length = 6
-----Array arr-----
0, 0, 0, 0, 0
```

2. (see examples\lib\IsItemExist.scr)

```
// delete all repeated items from array
array arr[] = {a,1,2,a,2,3,4,4};
writearray arr row;
for(i,0,length(arr))
{
    for(j,i + 1,length(arr) )
    {
        if(arr[i] == arr[j])
        {
            array.remove (arr,j);
            setloopend length(arr);
        }
        setloopend length(arr);
    }
}
writearray arr row;
-----Array arr-----
a, 1, 2, a, 2, 3, 4, 4
-----Array arr-----
a, 1, 2, 3, 4
```

for

Iteration block for **scr mode** only.

About using statements terminator ";" in "for" see [Base Concepts](#).

Format **scr**:

for(iteration var, begin, end [, step]) or

for() // infinity for

```
{  
    statement;  
    statement;  
    ...
```

```
}
```

By default **step = 1**. Step may positive or negative.

Example:

```
var x;  
for(i, 0, 10)  
{  
    x = i * 2;  
    write#("x = {0}",x);  
}
```

If block in "for" contains only one statement it is possible to omit { }:

```
for(i, 0, 10, 1)  
    write#("i={0}",i);
```

Example with **infinity for**:

```
function gcd(x,y,z)
{
    if(isinteger (x) == "False")
    {
        write#("not integer value x={0}",x);
        return;
    }
    if(isinteger (y) == "False")
    {
        write#("not integer value y={0}",y);
        return;
    }
    for()    // infinity for
    {
        if (x > y)
        {
            x = x - y;        // or Sub(x) (x) (y) ;
        }
        if (x < y)
        {
            y = y - x;        // or Sub(y) (y) (x) ;
        }
        if (x == y)
        {
            z = x;
            return;
        }
    }
}
var z = 0;
var x = 14144;
var y = 26163;
call gcd(x,y,z);
write#(gcd = {0},z);
gcd = 17;
```

break

Exit from loop (ppl mode) or from for (scr mode) or end of case in switch block.

Example:

```
code scr;
for(i, 0, 4, 1)
{
    if (i == 2)
    {
        write#("i = {0} break",i);
        break;
    }
}
```

continue

Continue executing in loop (ppl mode) or in for (scr mode).

```
Example 1:
code ppl;
loop(x) (0) (5) (1)
(do
  (
    (if (==(x) (3))
      (
        (write("x = {0} continue") (x) )
        (continue)
      )
    )
    (write("x={0}") (x) )
  )
);
```

```
Example 2:
code scr;
for(x,0,5,1)
{
  if(x == 3)
  {
    write("x = {0} continue;",x);
    continue;
  }
  write#("x = {0}",x);
}
```

Input and Output

write

Writes the string value to the standard output stream.

String interpolation ($\$ "x"$) is not supported. If string value begins with "Error:" it will be written in red.

Format:

write(value) | write(c# format)(value)(value)...

value:=value | ppl expression with prefix notation

Example:

```
>var x = 0;
>write(x);
>write("{0}{1}") ("x=") (x); // like c# write("{0}{1}") ("x=",x);
//quote in string
>write("ppl\"language"); // ppl"language
//tab in string
>write("ppl\tlanguage"); // ppl language
//newline in string
>write("ppl\r\nlanguage"); // ppl
                             //language

>write(12col);
```

Error: [GetValue] non valid name [12col]

Error: [Traversal] [write] PrepareParameters return false

This operator is used in ppl and scr mode.

```
>code scr
>var x = 2*5;           // scr expression is calculated in var
>write("{0} {1}") ( "x = " ) (x)
>code ppl
>write("{0}") (* (2) (5)) // ppl prefix expression
>write(1+3)
Error: [funcWrite] name [1+3] write supports only prefix
expression
>write#(1+3)           // use write# for infix expression
4
```

write#, writeline

Like as write, for mode scr only, each argument is not enclosed in parentheses.

Format scr:

write#(arg) | write#("c# format", arg1 , arg2,...)

writeline(arg) | writeline("c# format", arg1 , arg2,...)

arg:= <literal> | <scr expression with infix notation>

Examples:

```
>code scr;
>write#("{0} {1}", aaaa,1+3)
aaaa 4
>write#(1+2);
3
>write(1+2);    // not same result as with write#
Error: [funcWrite] name [1+2] does not exists or wrong math.
expression
>write(+(1)(2));
3
>write#("1+2");
1+2
>write#("{0,-10}{1}\t{2}", "PPL", "Hello", "World")
PPL      Hello World
```


writearray

Writes array contents to the standard output stream. By default writearray writes array elements into the column. Writearray writes array elements into the row by second argument "row".

Format **ppl**:

writearray [(node.)array_name] [(row)] [mode]

Format **scr**:

writearray [node.]array_name [row] [mode]

or

writearray ([node.]array_name [,row] [mode])

mode = **true** | false

mode sets to write (**true**) or no array objects with value = 0; By default mode = **true**.

Examples:

1.

```
>code scr;
>array y[] = {1,2,3};
>writearray y;
-----Array y-----
[0]      1
[1]      2
[2]      3
>writearray y row
-----Array y-----
1, 2, 3
```

2.

```
>code scr;
>storage(x) (2) (3);
>sinit(x) (0);
// write the bottommost arrays in storage
>writearray (x.0.Row);
[0]      #      0
[1]      #      0
[2]      #      0
>writearray (x.1.Row, row);
0, 0, 0
```

3.

```
>code scr;
>array y[3];
>setkvp y[0] = one,1;
>setkvp y[1] = two,2;
>setkvp y[2] = three,3;
>writearray y row;
-----Array y-----
{one,1}, {two,2}, {three,3}
```

readline

Reads the next line of characters from the standard input stream. Result will be passed to calling operator.

Format: **readline()** | **readline**

Examples:

```
>var x;  
>x = readline;  
>Enter:  
>>Hello  
>d;  
-N1      NS  
---N1    Global  
-----L0 x      [Hello]
```

Functions

Function library **CommonFunctions.ppl**, defined in file **Configuration.data** as **default_loaded_functions**, loads automatically and reloads when command **init** executes. It includes 2 types of functions:

- Mathematical and Logical functions,
- Array services and other functions.

Mathematical and Logical functions:

```
Sum (_result)(n1)[( n2)]
Sub (_result)(n1)[( n2)]
Mult (_result)(n1)[( n2)]
Div (_result)(n1)[( n2)]
Pow (_result, n1, n2)
PlusPlus (_result) | Plus1 (_result)      // like c#: ++(var)
MinusMinus (_result) | Minus1 (_result)    // like c#: --(var)
LT (_result, n1, n2)
LTEQ (_result, n1, n2)
GT (_result, n1, n2)
GTEQ (_result, n1, n2)
EQ (_result, n1, n2)
NOTEQ (_result, n1, n2)
AND (_result, n1, n2)
OR (_result, n1, n2)
XOR (_result, n1, n2)
```

These functions replace using prefix notations. Result are returned in 1st parameter and does not passed to the next command:

```
>var (z) (0) ;
>var (x) (1) ;
>set (z) (Sum(x) (1)) ;      // error
>Sum(z) (x) (1)) ;          // right
```

Examples:

```
1.
>code ppl;
>var (x) (1) ;
>var (z) ;
>Sum(z) (x) (1) ;    // z = x + 1
>Sum(x) (2) ;        // x = x + 2
>d
-N2      NS
---N3    Global
-----L4 x      [3]
-----L5 z      [2]
```

2. This sample returns **wrong result**:

```
>var(x) (5);
```

```
>Sum(x) (x) (2);
```

**Info: using same args can lead to unpredictable results [Sum]
[x]**

```
>d x
```

```
-----Variables and arrays-----
```

```
-L4      x      [5]
```

```
>Sum(x) (2);    // right, x = x + 2
```

3.

```
>code scr;
```

```
>call Sum(x,2,3);
```

```
>call Sum(x,2+3);
```

```
>Sum(x) (+ (2) (3));
```

User may create own functions file, like **CommonFunctions.ppl**, and set it in file **Configuration.data** as **UserFunctionsN** or load it:

```
>rc user_functions.ppl|scr;
```

Files, defined in **Configuration**, load their function only and do not execute any command, commands in files, loaded by command rc (readcode) are executed one after another.

Array services and other functions:

CsvToArray (var:str, array:arr) – to fill array from string data separated by comma
ArrayToCsv (array:arr, var:str) – copy to string separated by comma data from array
ArrayIsExist (_result, array:arr, value) – return True/False if defined value exists in array
ArrayIndexOf (_result, array:arr, value) – return the index of the first occurrence within array or -1.
ArrayLastIndexOf (_result, array:arr, value) – return the index of the last occurrence within array or -1.

Example:

```
>array my_array;  
>call CsvToArray("1,2,3,,1,5",my_array);  
>writearray my_array row;  
  
>var Result;  
>call ArrayToCsv(my_array,Result);  
>write#("Result = {0}",Result);  
  
>call ArrayIndexOf (Result, my_array, 3);  
>write#("index = {0}",Result);  
  
>call ArrayLastIndexOf (Result, my_array, 1);  
>write#("index = {0}",Result);
```

```
1, 2, 3, , 1, 5  
Result = 1,2,3,,1,5  
index = 2  
index = 4
```

See examples\ArrayFunc\SamplesFunc.scr.

ArrayForEach(array:arr, array:callback_name) – calls a callback function once for each array element

Example: (examples\arrayfunc\foreach.scr)

```
function sumfunc(array:arr,var:i)
{
    result = result + arr[i];    // used reserved name result
}

delegate d2 (array:arr,var i);
dltinstance instance d2;
dltset instance sumfunc;
call ArrayForEach({1,2,3,4,5},instance);
write#("getresult = {0}",getresult);
result = 15
```

WindowSize() // is executed in Administrator mode only
width=120 height=30

function

Functions must be declared before being called.

Functions are saved in Tree **Functions** or in Tree **Global** for later call.

Functions return result via parameters, like a classic procedure, and via operator "return" (see Examples\ArrayFunc\mean.scr).

When function is called internal **var result** is created automatically, it may be used as any var, when function is ended value of var result received to caller and var result will be deleted.

When function is called **by name** (in mode **ppl** or **scr**) each argument must be enclosed in parentheses.

When function is called by command '**call**' (in mode **scr** only) each argument not must be enclosed in parentheses, but separated by comma.

Function uses data created inside, passed from calling function and data from NS.Global.

Data created in function are deleted when function will be finished.

The function receives parameters **by reference**. If the argument is a literal, then attempting to change it will result in an error message.

Limitations:

1. If argument value will be changed in function this argument may be used only one time when function is called(see example [Sum_wrong_result](#)).
2. Do not create function in function:

```
function f()    //error
{
    function s() {...};
}
```

Format **ppl**:

Statement terminator ';' does not follow after statements within function, but each statement is surrounded by parentheses.

```
function
(
    name
    parameter_list
    ( function body )
);
name ::= identifier
parameter_list ::= parameter [parameter_list]
parameter ::= (identifier) | (identifier[default value]) | empty
function body ::= (statement1) [(statement2) (statementN)]
identifier ::= [var] | [array] | [storage] |
               [struct <struct_name>] | [struct array <struct_name>]:<param_name>
```

Format **scr**:

Statement terminator ';' always follows after each type of statements within function.

```
function    name
            (parameter_list)
            {
                function body
            }
name ::= identifier
parameter_list ::= parameter, [parameter_list]
parameter ::=
            identifier | identifier[default value] | identifier = default value | empty
function body ::= statement1; [ statement2; statement; ]
identifier ::= [var] | [array] | [storage]:<name>
By default parameter type is var.
```


Examples:

1.function without parameters

```
>code scr
Function func ()
{
    write#("func");
}
```

2. function with default parameter

```
function func (n,m[10])    //= func (var:n,var:m[10])  or
                             //function func (n,m = 10)
{
    write#(funcname());
}
```

3. array parameter

```
function func (array: n)
{
    write#( funcname());
}
```

4. different argument types

```
function f(var: param)
{
    write#("{0} {1}",getargname(param), param);
}

array y[] = {1,2,3,4,5};
f(y[0]);
var x = 0;
f(x);
storage s[2,2];
s[0,0] = 10;
f(s[0,0]);
y 1
x 0
s 10
```

5. call function from function

```
code ppl;
function
(
    test2(n)
    (
        (write(n))
    )
);
function
(
    test()
    (
        (loop (i) (0) (5) (1)
            (do
                (
                    (test2(i))
                )
            )
        )
    )
);
test();      // function call
```

6.

```
code scr;    // (see examples\scr\func.scr)
function sum_arr(array:n,array:m)
{
    for(i,0,length(n))
        write#("[{0}] [{1}]" ,i, n[i] + m[i]);
}
d Functions.sum_arr;
array x[] = {1,2,3,4,5};
array y[] = {6,7,8,9,10};
```

```
sum_arr(x)(y); // function call
// command "call" allows use arguments by this manner:
// call sum_arr({1,2,3,4,5},{6,7,8,9,10});
[0] [7]
[1] [9]
[2] [11]
[3] [13]
[4] [15]
```

In the following example (see examples\scr\func4.scr) parameter index default value = 0 and this parameter may be omitted when the function is called.

When function is calling item array may be passed as 2 arguments (array, index)

7.

```
code scr;
function func (array:arr, var:index[0])
{
    write#("{0}[{1}] = {2}",getargname(arr),index, arr[index]);
}
array y[] = {1,2,3,4};
func(y);
call func(y,0);
call func(y,1);
call func(y,2);
y[0] = 1
y[0] = 1
y[0] = 1
y[1] = 2
y[2] = 3
```

8. Call function from node saved in Tree Global

```
code ppl;
createnode New;
function
(
    New.func(name) // public
    (
        (write(name))
    )
);
function
(
    New._hfunc(name) // private
    (
        (write(name))
    )
)
```

9. Call function from node created in Global

```
code scr;
createnode N;
function N.f()
{
    write("Global.N.f - function");
};
N.f();
dn;
Global.N.f - function
-N2      NS
---N3    Global
-----N4 N                [Node]
-----N5      f            [function]
-----N6      #            [internal_block]
-----N7      write

// Call function from node created in Functions
createnode Functions.N;
function Functions.N.f()
{
    write("Functions.N.f - function");
};
Functions.N.f();
Functions.N.f - function
```

10. Recursion

```
var tmp = 0;
function rec(x)
{
    PlusPlus(tmp);
    write#("tmp={0}",tmp);
    if (tmp == x)
    {
        return;
    }
    rec(x);
}
rec(5);
```

11. warning when function updated

```
function f()  
{  
    write("function f");  
}  
f();  
function f()  
{  
    write("updated function f");  
}  
f();
```

```
function f  
Warning: [FuncCreateFunction] function [f] is updated  
updated function f
```

12. Passing structure as function parameter

```
definestruct Room  
{  
    var x;  
    array y[3];  
}  
// function f(struct Toom:r) - wrong struct_name causes error  
function f(struct Room:r)  
{  
    r.x = 1;  
    r.y[0] = "A";  
}  
createstruct R as Room;  
f(R);
```

13. Passing structure array as function parameter

```
define struct Room
{
    var x;
    array y[3];
}
function f(struct array Room:r)
{
    r.0.x = 1;
    r.0.y[0] = "A";
}
create struct R[2] as Room;
f(R);
```

Examples with using public and private functions in Trees Functions and Global it is possible to find in directory Examples\Access.

14. Array as parameter (see Examples\ArrayFunc\mean.scr)

```
function mean2(array:arr)
{
    result = 0;    // result is internal var, created in function
    for(i,0,length(arr))
        result = result + arr[i];
    result = result/ length(arr);
    //return result/ length(arr);
}
call mean2({1,2,3,4,5,6,7,8,9,10});
write#("mean2 = {0}",getresult);

array arr[] = {1,2,3,4,5,6,7,8,9,10};
write#("mean2 = {0}",mean2(arr));
mean2 = 5.5
mean2 = 5.5
```

15. function names - funcnames

```
function fora()  
{  
    write(funcname);  
}  
fora();
```

```
function defaulta()  
{  
    write(funcname);  
}  
defaulta();
```

16.

```
function f(x)  
{  
    write(x);  
}  
var c = "qqq";  
f("v");    // literal  
f(c);      // variable  
f(v);      // error wrong argument name
```

```
>rc examples\CallFunc\func21.scr
```

```
v
```

```
qqq
```

```
Error: [FuncExecFunction] function [f] argument [v] not found
```

17. attempt to change literal argument

```
function f(var:c)  
{  
    write#(" c={0}",c);  
    c = 20;  
    write#("c={0}",c);  
}
```

```
f(10);
```

```
c=10
```

```
Error: [FuncExecFunction] attempt to change literal parameter  
[c] arg [10]
```

call

Command '**call**' invokes a function in mode **scr**, it is possible to use expression in infix notation as arguments, do not need to enclose in parentheses each argument when function is called.

Do not use '**call**' as function argument or on the right side of mathematical expression or as argument of any command.

Format **scr**:

call function_name(arg1,arg2,...)

Examples:

1.

```
>code scr
>var x = 0;
>call Sum(x,4 + 1);    // right: 2nd arg in infix notation
>d x
-----Variables and arrays-----
-L1      x      [5]

>call Sum(x,-(5)(2)); // wrong: 2nd arg in prefix notation
                        // right: Sum(x) (-(5)(2))
```

2.Call function without arguments or with one not-expression argument by command '**call**' and without '**call**':

```
call func(123);    same as    func(123);
```

3. To get return of function, called by '**call**', run '**dbg yes**' before:

```
>dbg yes;
>call Math.PI();
result = 3.141592653589793
// or
>debugppl no;
>call Math.PI();
>write(getresult);
3.141592653589793
```

4.To get return from function, when function is used as argument do not use '**call**', use **ppl** notation:

```
>write#( Math.PI() );
result = 3.141592653589793
```

5.

```
>write#(call Math.PI()); // error: call on the right side
>var x = call Math.PI(); // error
>var x = Math.PI();      // right
3.141592653589793
```


6. command "call" allows you to pass array by this manner:

call function_name({item1,item2,...},arg2,...)

Example: (see examples\CallFunc\funcarr2.scr and examples\CallFunc\funcarr2.ppl)

```
function SumArray(array:arr,var:r)
{
    for(i,0,length(arr))
        call Sum(r,arr[i]);
}
```

```
var R = 0;
call SumArray({1,2,3,4,5},R);
write#("R = {0}",R);
```

or:

```
array arr[] = {1,2,3,4,5};
call SumArray(arr,R);
```

Preprocessor generates the following ppl-code:

```
function
(
    SumArray (array:arr) (var:r)
    (
        (set (r) (0))
        (
            loop (i) (0) (length(arr)) (1)
            (
                do
                (
                    (Sum(r) (r) (arr[i]))
                )
            )
        )
    )
);
var (R);
array (arg_array0) (1) (2) (3) (4) (5 );
SumArray (arg_array0 ) ( R);
del arg_array0;
write ("R = {0}") (R);
```

```
array split_array;
call String.Split("1 2 3 4 5",{" "},split_array);
>writearray split_array row
-----Array [split_array]-----
1, 2, 3, 4, 5
```

return

Returns from function or exit from script, passes result from called function.

Format **ppl: return || return (statement in prefix notation)**

Format **scr: return | return (statement in infix notation)**

Examples:

1.

```
function f()  
{  
  for(i, 0, 5)    // step by default = 1  
  {  
    if (i == 2)  
      return;  
    write(i);  
  }  
}  
f();  
write("end of script");  
0  
1
```

2.

```
code scr;  
function f()  
{  
  return 2 + 3;  
}  
f();  
write(getresult);  
5
```

getresult

Gets result of return passed from called function.

Format:

getresult () | getresult

Examples:

1. Return from function:

```
function sum(x,y)
{
    return x + y;
}
call sum(1,2);
write#("result = {0}",getresult);
result = 3
or
write#("result = {0}",getresult(sum(1)(2)));
```

funclist

Displays loaded function names and their parameters from node Functions.

Format:

funclist | finclist()

Example:

```
>funclist;
-----Function List-----
Sum  (_result, n1, n2)
Sub  (_result, n1, n2)
Mult (_result, n1, n2)
Div  (_result, n1, n2)
Pow  (_result, n1, n2)
PlusPlus (_result)
MinusMinus (_result)
LT   (_result, n1, n2)
LTEQ (_result, n1, n2)
GT   (_result, n1, n2)
GTEQ (_result, n1, n2)
EQ   (_result, n1, n2)
NOTEQ (_result, n1, n2)
AND  (_result, n1, n2)
OR   (_result, n1, n2)
XOR  (_result, n1, n2)
```

funcname

Returns the current function name.

Format:

funcname() | funcname

Examples:

```
>write(funcname);  
main
```

```
function MyFunction()  
{  
  write(funcname);  
}  
MyFunction();  
MyFunction
```

argc

Returns number of arguments

Format:

argc() | argc

Example:

```
function Sum (_result,n1,n2 = "")  
{  
  write#("argc = {0}",argc());  
  if (argc() == 2)  
    _result = _result + n1;  
  else  
    _result = n1 + n2;  
}  
>code scr;  
>var x = 0;  
>call Sum(x,1);  
>write#("x = {0}",x);  
argc = 2  
x = 1
```

getargname

Returns argument name (or argument value if it is literal) by parameter name

Format:

getargname (parameter_name)

Example:

```
function a(n)
{
  write#("param name=[{0}] arg name=[{1}]",
        getname(n),getargname(n));
}
var i = 0;
a(i);
param name=[n] arg name=[i]
```

finally and failure blocks

finally block are called at the end of the successful completion of the script or functions.

failure block are called in case of emergency termination of the script or functions.

These blocks are added to the body of script or functions as additional nodes and have access to all variables in their scope.

Example:

```
finally { write("script finally block"); }
failure { write("script failure block"); }

function foo(var: x)
{
  finally
  {
    var str1 = "function finally block";
    //writ(str1);
    //Error: [Traversal] [foo] [finally] wrong cmd or function
    //  name [writ]
    write(str1);
  }

  failure
  {
    var str2 = "function failure block";
    write(str2);
  }

  if(isdigits (x) == True)
  {
    write("digits");
    return;
  }
  else
  {
    write("not digits");
    return;
  }
}
foo("a");

not digits
function finally block
script finally block
```

Delegates and callbacks

There are 4 operators for using delegates:

delegate – creation delegate

dltinstance – creation delegate instance

dltset - setting the function to delegate instance

dltcall – call function by delegate instance

delegate

delegate is created as an array whose elements define the method parameters.

Prefix “**delegate_**” is added to delegate name for internal using.

Format **ppl**:

delegate (<delegate name>) (param1) (param2)...

param:= <var_name> | var:<var_name> | array:<array_name> |

storage:<array_name> | struct [array] <struct_name>: < var_name >

Format **scr**:

delegate <delegate name> (param1, param2,...)

Example (**scr-mode**):

```
>delegate MyDelegate (var:x,array:arr);
```

Generated ppl code:

```
>d
```

```
-N2      NS
---N3    Global
-----L0      empty                (const)
-----N4 delegate_MyDelegate      [Array 2]
-----L0      #                    [var:x]
-----L1      #                    [array:arr]
```

dlgtinstance

dlgtinstance is created as an array with 2 elements, first is delegate name, second is empty and will be set by dlgtset. Delegate parameters types must be matched types of function parameters . Prefix “**dlgtinstance_**” is added to delegate instance name for internal using.

Format **ppl**:

dlgtinstance (<delegate instance name>)(<delegate name>)

Format **scr**:

dlgtinstance <delegate instance name> <delegate name>

Example(**scr-mode**):

```
>delegate d2 (var:x,array:arr) ;
>dlgtinstance instance d2;
>d;
-N2      NS
---N3    Global
-----L0 empty    (const)
-----N4 delegate_d2    [Array 2]
-----L0      #        [var:x]
-----L1      #        [array:arr]
-----N4 dlgtinstance_instance    [Array 2]
-----L0      #        ["delegate_d2"]
-----L1      #
```


dlgtset

dlgtset sets function name as second element in **dlgtinstance** array.

Format **ppl**:

dlgtset (delegate instance name)(function name)

Format **scr**:

dlgtset delegate instance name function name

Example (**scr-mode**):

```
// see previous example with delegate and dlgtinstance
function f1(var:x,array:arr)
{
    write#("x = [{0}]",x);
    writearray arr;
}
>dlgtset instance f1;
```

dlgtcall

dlgtcall calls function defined in dlgtset.

Format **ppl**:

dlgtcall(delegate instance name)(arg1)(arg2)(arg3)...

Format **scr**:

dlgtcall delegate instance name(arg1,arg2,arg3,...)

Example:

```
// see previous examples with delegate, dlgtinstance and dlgtset
>var z = "qqq";
>array y[] = {1,2,3};
>dlgtcall instance (z,y);
x = [qqq]
-----Array arr-----
[0]      1
[1]      2
[2]      3
```

See samples with delegates - Examples\delegates*.scr

callback

callback invokes synchronous callback method.

Format **ppl**:

callback (callback name)(arg1)(arg2)(arg3)...

Format **scr**:

callback callback name (arg1,arg2,arg3,...)

Example: (see Examples\delegates\callback.scr)

```
function cb1(var:n)
{
    write#("====={0}====",funcname);
    write#("n = {0}",n);}

function cb2(var:n)
{
    write#("====={0}====",funcname);
    write#("n = {0}",n);}

function f(array:x,var:str)
{
    callback x(str);
}

delegate d2 (var:n);
dlgtinstance instance d2;
dlgtset instance cb1;
call f(instance,"PPL");
dlgtset instance cb2;
call f(instance,"PPL");
function cb1 PPL
function cb2 PPL
```

VS Code support

Enhance your ForestPPL development experience by enabling custom syntax highlighting in Visual Studio Code. You can easily add the official syntax rules to your editor using the provided extension package.


Installing the ForestPPL Extension via UI

- Open Visual Studio Code.
- Navigate to the Extensions view by clicking the square icon in the Activity Bar on the left side of the window (or press Ctrl+Shift+X).
- Click the Views and More Actions menu (the three dots ... located at the top right corner of the Extensions panel).
- Select Install from VSIX... from the dropdown menu.
- Locate and select the **VS.Code\forestppl-vscode-0.3.0.vsix** file on your local machine, then click Install.
- Restart VS Code if prompted.

Alternative Installation via Command Line If you prefer using the terminal, you can install the extension directly by running the following command in the folder where your file is located:

code --install-extension VS.Code\forestppl-vscode-0.3.0.vsix

Once the installation is complete, Visual Studio Code will automatically recognize your ForestPPL script files. The editor will apply the dedicated color scheme and syntax highlighting to your commands, keywords, and variables, making it significantly easier to read, navigate, and debug your code.



```
1 //Sieve of Eratosthenes
2 // rc Examples\scr\sieve3.scr
3 var m = 1000;
4 showcode no;
5 var len;
6 len = m + 1;
7 array primes[len];
8
9 for (
10 {
11   pri
12 }
13   array.push
14 prime array.reverse
15   array.slice
16 start array.sort
17   for array.sum
18 {
19   if(n * n >= len)
20     break;
21
22   if (primes[n] != 0)
23   {
24     var start_j = n * n;
25
26     for(j, start_j, len, n)
27     {
28       primes[j] = 0;
29     }
30   }
31 }
32 stop("1. duration = ");
33
34 start;
35 // not write items with zero-value
36 writearray primes row false;
37 stop("2. duration = ");
38
39 start;
40 array dst;
41 //copy to array dst items with non zero value only
42 //array.filtercopy(primes, dst);
```

array declaration

- array.average
- array.max
- array.min
- array.pop
- array.push
- array.reverse
- array.slice
- array.sort
- array.sum

Ln 7, Col 6 Spaces: 2 UTF-8 CRLF {} ForestPPL

Additional functionalities

The following below-mentioned additional DLLs with C++ functionalities are added and this list will be expanded. Custom DLLs use functions from the C++ STL and internal PPL functions.

To get list of methods of additional loaded DLLs:

<DLLname>.help

For using user's library it is needed to set it in Configuration.data or to add by command [import](#) in program.

Use Utility **CodeGen.exe** to create code for additional DLLs. Arguments of additional DLLs use **prefix math.notation, only Math library uses infix math. notation in scr-mode, this feature is added to preprocessor:**

```
x = Math.Sqrt(1+3) + Math.Max(2)(3*5);
```

Math

Methods:

Max	E	PI
Min	Exp	
BigMul	Floor	
Sqrt	Log	
Round	Log10	
Abs	Pow	
Acos	Sign	
Asin	Sin	
Atan	Tan	
Atan2	Truncate	
Ceiling	Tanh	
Cos	Cosh	
DivRem	Sinh	

Limitation: Do not use Math.Function in Math.Function:

```
var x = Math.Sin(30/(180/Math.PI())) // error
```

To get short help for every method in Math.DLL:

```
>Math.help[(method name)];
```

Returns the larger of two double-precision floating-point numbers:

Math.Max(double d1)(double d2)

Returns the smaller of two double-precision floating-point numbers:

Math.Min(double d1)(double d2)

Produces the full product of two 32-bit numbers:

Math.BigMul(Int32 n1)(Int32 n2)

Returns the square root of a specified number: **Math.Sqrt(double d1)**

Rounds a double-precision floating-point value to a specified number:

Math.Round (double value)[(Int32 digits)]

Returns the absolute value of a double-precision floating-point number:

Math.Abs(double value)

Returns the angle whose cosine is the specified number: **Math.Acos(double d)**

Returns the angle whose sine is the specified number: **Math.Asin(double d)**

Returns the angle whose tangent is the specified number: **Math..Atan(double d)**

Returns the angle whose tangent is the quotient of two specified numbers:

Math.Atan2(double d1)(double d2)

Returns the smallest integral value greater than or equal to the specified number:

Math.Ceiling(double d)

Returns the cosine of the specified angle: **Math.Cos(double d)**

Returns the quotient and remainder, separated by ';' as result:

Math.DivRem(Int64 n1)(Int64 n2)

Example:

```
write#("result: {0}",Math.DivRem(9)(2));  
result: 4;1
```

Represents the ratio of the circumference of a circle to its diameter: **Math.PI()**

Represents the natural logarithmic base: **Math.E()**

Returns e raised to the specified power: **Math.Exp(double value)**

Returns the largest integral value less than or equal to the specified number:

Math.Floor(double value)

Returns the logarithm of a specified number: **Math.Log(double value)**

Returns the base 10 logarithm of a specified number: **Math.Log10(double value)**

Returns a specified number raised to the specified power:

Math.Pow(double value)(double power)

Returns an integer that indicates the sign of a double-precision floating-point number:

Math.Sign(double value)

Returns the sine of the specified angle: **Math.Sin(double value)**

Returns the tangent of the specified angle: **Math.Tan(double value)**

Calculates the integral part of a number: **Math.Truncate(double value)**

Returns the hyperbolic tangent of the specified angle: **Math.Tanh(double value)**

Returns the hyperbolic cosine of the specified angle: **Math.Cosh(double value)**

Returns the hyperbolic sine of the specified angle: **Math.Sinh(double value)**

String

Methods:

Compare	Replace
Concat	DeleteEndOfLine
Contains	StartsWith
Format	Substring
IndexOf	ToCharArray
LastIndexOf	ToLower
Insert	ToUpper
Remove	Trim
Split	Char
SplitCsv	

To get short help for every method in String.DLL:

>String.help[(method name)];

Returns signed int as string: **String.Compare(stringA)(stringB)**

Returns concatenation of several strings: **String.Concat(string1)(string2)...**

Returns true|false: **String.Contains(string)(specified substring)**

Converts the value of objects to string based on the formats specified and returns result:

String.Format(format)(string1)(string2)...

Example:

```
String.Format("{0} {1}") ("qwe") ("zxc")  
qwe zxc
```

Returns a new string in which a specified number of characters from the current string are deleted:

String.Remove(string)(startIndex)(number of deleted symbols)

Example:

>rc examples\lib\StringRemove.scr

```
import String;  
array primes = {1,2,3,5,7};  
var output = "";  
for(i,0,length(primes),1)  
{  
    set output = String.Concat(output) (primes[i]) (",");  
}  
var index = length(output) - 1;  
set output = String.Remove(output) (index) (1); //remove the  
latest ','  
write(output);  
1,2,3,5,7
```


or Returns a new string in which one or all occurrences of a specified Unicode character string in the current string are replaced with another specified Unicode character or string:

String.Replace(string)(old value)(new value)[mode]

mode:=one|last|all

by default: **all**

```
>dbg yes
>String.Replace("Hello Helo") ("l") ("f")
Heffo Hefo
>String.Replace("Hello Helo") ("l") ("f") (one)
Heflo Helo
>String.Replace("Hello Helo") ("l") ("f") (last)
Hello Hefo
>String.Replace("Hello Helo") ("l") ("f") (all)
Heffo Hefo
>String.Replace("Hello Helo") ("l") ("f") (www)
Error: [String.FuncReplace] invalid mode [www]. Expected 'one', 'last', or 'all'
```

Determines whether this string instance starts with the specified character:

Returns **True|False**:

String.StartsWith(string)(value)

Retrieves a substring from this instance. The substring starts at a specified character position and has a specified length:

String.Substring(string)(startIndex)[(length)]

Examples:

```
>var r = String.Substring("123asd") (0) (3) ;
r = 123
>var r = String.Substring("123asd") (3) ;
r = asd
```

Writes the characters in this instance to a Unicode character array:

String.ToCharArray(string)("ppl_chars_array")

node_of PPL_chars_array is string in quotes or value of variable.

```
Example:
>array chars;
>String.ToCharArray("qwerty") ("chars") ;
>writearray chars row;
importlist-----Array chars-----
q,w,e,r,t,y
```

Returns a copy of this string converted to lowercase: **String.ToLower(string)**

Returns a copy of this string converted to uppercase: **String.ToUpper(string)**

Returns a new string in which all leading and trailing occurrences of a set of specified characters from the current string are removed:

String.Trim(string)[(trim chars string)]

```
>String.Trim(" abcde") (" ae");  
bcd
```

Returns one character from string: **String.Char(string)(index)**

Returns the resized string array that contains the substrings in this instance that are delimited by elements of a specified string array or in special string var, string array must be created before with size = 0:

String.Split(string)("ppl_array_separators")(ppl_array_result) or

String.Split(string)("var_separator")(ppl_array_result)

It is possible to use **comma** instead of ','

space instead of ' '

tab instead of '\t'

String.Split does not skip separators between quotes.

Example:

```
>var text;  
>text = File.ReadAllText("Data\test.csv");  
>d text;  
-----L1      text      [<1 2 3 4 5 6 7 8 9 10>]  
>array separator[] = {comma,tab,space};  
>array split_text_array;  
>var len = length(text) - 2;  
>text = String.Substring(text) (1) (len);  
>d text;  
-----L1      text      [1 2 3 4 5 6 7 8 9 10]  
>String.Split(text)(separator)(split_text_array);  
>writearray split_text_array row  
-----Array [split_text_array]-----  
1, 2, 3, 4, 5, 6, 7, 8, 9, 10
```

Returns the resized string array that contains the substrings in this instance that are delimited by separator of a specified string var, string array must be created before with size = 0 (array <name>;).

If value with separator is surrounded by quotes it doesn't split.

(see example\lib\splitcsv.scr):

array array_result;

String.SplitCsv(string)("var_separator")(array_result)

It is possible to use **comma** instead of ','

space instead of ' '

tab instead of '\t'

String.SplitCsv skips separators between quotes.

Example:

Returns string from File.ReadAllText without EndOfLine: **DeleteEndOfLine(string)**

>rc Examples\Lib\FilesplitCsv.scr

```
var text = File.ReadAllText("examples\lib\splitcsv.txt");  
array splitcsv_text; // array with results  
call String.SplitCsv(text, ",", splitcsv_text);  
writearray splitcsv_text row;  
call File.WriteAllText(text, "examples\lib\splitcsv_copy.txt");
```

Reports the zero-based index of the first occurrence of the specified string in this instance:

String.IndexOf (string)(value)[(start_index)][(count)]

Reports the zero-based index of the last occurrence of the specified string in this instance:

String.LastIndexOf (string)(value)[(start_index)][(count)]

Example (see examples\lib\IsUniqueSymbol.scr)

```
function IsUnique(str,res)
{
    var char;
    for(i,0,length(str))
    {
        char = String.Char(str)(i);
        if( String.LastIndexOf (str)(char) != i)
        {
            res = False;
            return;
        }
    }
    res = True;
}

var Result;
call IsUnique("abcdef",Result);
write(Result);
call IsUnique("1234567",Result);
write(Result);
call IsUnique("abcABC",Result);
write(Result);
call IsUnique("abcadef",Result);
write(Result);
True
True
True
False
```

Returns a new string in which a specified string is inserted at a specified index position in this instance:

String.Insert (string)(start index)(string to insert)

Directory

Methods:

- GetFiles**
- GetDirectories**
- SetCurrentDirectory**
- GetCurrentDirectory**
- GetParent**
- CreateDirectory**
- Exists**
- Delete**

To get short help for every method in Directory.DLL:

> Directory.help[(method name)];

Writes the names of files (including their paths) in the specified directory to node_of_PPL_array, created before,its previous content will be cleared:

array PPL_array;

Directory.GetFiles(PPL_array)(path)

path = var | string_literal

Example:

```
function WriteFilesInDirectory (array:arr,var:dir)
{
    write#("[{0}] [{1}]", getargname(arr),getargname(dir));
    call Directory.GetFiles(getargname(arr),dir);
    writearray arr;
}
var c = "c:\\";
array files;
call WriteFilesInDirectory (files,c);
[files] [c]
-----Array [arr]-----
[0]      c:\appverifUI.dll
[1]      c:\devlist.txt
[2]      c:\DumpStack.log
[3]      c:\DumpStack.log.tmp
[4]      c:\Finish.log
[5]      c:\hiberfil.sys
[6]      c:\logUploaderSettings.ini
[7]      c:\logUploaderSettings_temp.ini
[8]      c:\pagefile.sys
[9]      c:\swapfile.sys
[10]     c:\vfcompat.dll
```

Writes the names of directories (including their paths) in the specified directory to **PPL_array**, created before,its previous content will be cleared:

array PPL_array;
Directory.GetDirectories(PPL_array)(path)

Example:

```
>import Directory;  
>array dir;  
>Directory.GetDirectories(dir) ("c:\Users") ;
```

Sets the current working directory to the specified directory:

Directory.SetCurrentDirectory(path)

Gets the current working directory: **Directory.GetCurrentDirectory()**

Returns parent fullname: **Directory.GetParent(path)**

Returns CreationTime: **Directory.CreateDirectory(path)**

Returns **True** or **False** : **Directory.Exists(path)**

Deletes the specified directory and any subdirectories and files in the directory

Returns **True** or **False**: **Directory.Delete(path)**

Queue

Methods:

Create	Peek	
Count	Clear	
Write	Contains	
Enqueue	AddArray	
Dequeue	ToArray	Delete

To get short help for every method in Queue.DLL:

Queue. help[(method name)]

Creates Queue object: **Queue.Create(queue name)**

Examples:

```
>import Queue;  
>Queue.Create("q") ;  
>var name = "Q";  
>Queue.Create(name) ;
```

Returns the number of elements actually contained in Queue: **Queue.Count(queue name)**

Writes queue names or all elements from the specified queue to the standard output stream:

Queue.Write() or **Queue.Write(name)**

Adds an object to the end of the Queue: **Queue.Enqueue(queue name)(string)**

To add empty string use keyword empty.

Removes and returns the object at the beginning of the Queue:

Queue.Dequeue(queue name)

return **nan** if queue is empty

Returns the object at the beginning of the Queue without removing it:

Queue.Peek(queue name)

return **nan** if queue is empty

Removes all objects from the Queue: **Queue.Clear(queue name)**

Determines whether an element is in the Queue, returns "True" or "False":

Queue.Contains(queue name)(string)

Adds PPL array to the Queue: **Queue.AddArray(ppl_array) (queue name)**

Writes all elements from Queue to the PPL array created before with size = 0:

array ppl_array;

Queue.ToArray(queue name) (ppl_array)

Delete all Queue objects: **Queue.Delete();**

Examples:

Note the difference between value as variable and value as string literal (also for **Stack** and **Dictionary**)

```
>import Queue
Imported [Queue]
>var x = 0;
>array r[] = {1,2,3};
>Queue.Create("Q")
>call Queue.Enqueue("Q",x)
>call Queue.Enqueue("Q","x")
>call Queue.Enqueue("Q",r)
>call Queue.Enqueue("Q","r")
>Queue.Write(Q)
===Q===
    0
    x
    Array 3
    r
```

It is possible to save in **Queue** (also in **Stack** and **Dictionary**) lines of code in ppl-format to be performed using **eval**:

```
>import Queue
Imported [Queue]
>Queue.Create("Q")
>var y = 1
>Queue.Enqueue("Q") ("var (x[0]);Sum(x)(y)(2);d x;")
>Queue.Write("Q")
===Q===
    var (x[0]);Sum(x)(y)(2);d x;
>eval(Queue.Dequeue("Q"))
-----Variables and arrays-----
-L0      x                                     [3]
```

See samples of code with Queue methods in **examples\lib\Queue.scr**

Stack

Methods:

Create	Peek	
Count	Clear	
Write	Contains	
Push	AddArray	
Pop	ToArray	Delete

To get short help for every method in Stack.DLL:

>Stack.help[(method name)]

Creates Stack object: **Stack.Create(stack name)**

Examples:

```
>import Stack;  
>stack.Create("st");  
>var name = "NewStack";  
>Stack.Create(name);
```

Returns the number of elements actually contained in Stack: **Stack.Count(stack name)**

Writes stack names or all elements from the specified stack to the standard output stream:

Stack.Write() or **Stack.Write(stack name)**

Inserts an object at the top of the stack: **Stack.Push(stack name)(string)**

To insert empty string use keyword **empty**.

Removes and returns the object at the top of the Stack:

Stack.Pop(stack name)

return **nan** if stack is empty

Returns the object at the top of the Stack without removing it:

Stack.Peek(stack name)

return **nan** if stack is empty

Removes all objects from the Stack: **Stack.Clear(stack name)**

Determines whether an element is in the Stack, returns **True** or **False**:

Stack.Contains(stack name)(string)

Adds PPL array to the Stack: **Stack.AddArray) (PPL array)(stack name)**

Writes all elements from Stack to the PPL array created before with size = 0:

array ppl_array;

Stack.ToArray(stack name) (ppl_array)

Delete all Stack objects: **Stack.Delete();**

Examples:

```
>dbg yes;  
>import Stack  
Imported [Stack]  
>Stack.Create("s")  
>Stack.Push("s") ("one")  
>Stack.Push("s") ("two")  
>Stack.Push("s") ("three")  
>Stack.Pop("s")  
result = three  
>Stack.Pop("s")  
result = two  
>Stack.Pop("s")  
result = one  
>Stack.Pop("s")  
result = nan
```

See samples of code with Stack methods in **examples\lib\Stacks.scr**

Dictionary

This library uses functions from **std::unordered_map**.

Methods:

Create	Clear
Delete	Write
Count	ContainsKey
Add	Remove
GetValue	AddArray
SetValue	ToArray

To get short help for every method in Dictionary.DLL:

>Dictionary.help[(method name)]

Creates Dictionary object: **Dictionary.Create(dictionary name)**

Deletes all Dictionary objects: **Dictionary.Delete()**

or deletes one object from Dictionary: **Dictionary.Delete(dictionary_name)**

Example:

```
>import Dictionary;
>Dictionary.Create("dict1");
>var name = "dict2";
>Dictionary.Create(name);
array y[] = {"dict3",0,1};
>Dictionary.Create(y[0]);
>Dictionary.Delete("dict1");    // delete dict1
>Dictionary.Delete();          // delete dict2 and dict3
```

Returns number of dictionaries or number of elements in specified dictionary:

Dictionary.Count() | Dictionary.Count(dictionary name)

Adds the specified key and value to the Dictionary:

Dictionary.Add(dictionary name)(key)(value)

Example:

```
>import Dictionary;
>Dictionary.Create("dict");
>call Dictionary.Add("dict","one",1+1);
>call Dictionary.Add("dict","two",3);
>call Dictionary.Add("dict","three",4);
>call Dictionary.Count("dict");    // => 3
>call Dictionary.Count();          // => 1
>Dictionary.Write("dict");
```

Dictionary.GetValue

Get value from Dictionary by key

return **True** or **False**:

Dictionary.GetValue(dictionary name)(key)(var name for result)

Example:

```
>import Dictionary
>Dictionary.Create("dict")
>call Dictionary.Add("dict","one",1) ;
>call Dictionary.Add("dict","two",2) ;
>call Dictionary.Add("dict","three",3) ;
>array y[3]
>var x
>call Dictionary.GetValue("dict","one",x)
>write#("x = {0}",x)
x = 1
```

Dictionary.SetValue

set value in specified dictionary for specified key, if key exists

return **True** or **False**:

Dictionary.SetValue(dictionary name)(key)(value)

Dictionary.Write

Writes dictionary names only: **Dictionary.Write()**

or

all elements from the specified Dictionary to the standard output stream:

Dictionary.Write(dictionary name)

Removes all objects from the Dictionary: **Dictionary.Clear(dictionary name)**

Determines whether the Dictionary contains the specified key, returns **True** or **False**:

Dictionary.ContainsKey(dictionary name)(key)

Removes the value with the specified key from the Dictionary:

Dictionary.Remove(dictionary name)(value)

Adds PPL array to the Dictionary:

Dictionary.AddArray(PPL array) ("dictionary name")

```
>import Dictionary
Imported [Dictionary]
>Dictionary.Create("D")
>array y[3]
>y[0] = "one",1
>y[1] = "two",2
```

```
>y[2] = "three",3  
call >Dictionary.AddArray (y,"D")  
>Dictionary.Write("D")  
Dictionary.Write [D]  
    one      1  
    two      2  
    three    3
```

Write all elements from Dictionary to new PPL array created before with size = 0:
`array ppl_array;`

Dictionary.ToArray(dictionary name) (ppl_array)

Examples of code with Dictionary methods in **examples\lib\Dictionary.scr**

Convert

Methods:

StringToInt32Array
StringToHexArray
HexToBin
BinToHex
IntToHex
HexToInt
IntToBin
BinToInt

To get short help for every method in Convert.DLL:

>Convert.help[(method name)];

String characters converts to int32 array created before with size = 0 and resized in

Convert.StringToInt32Array with size of string_characters:

Convert.StringToInt32Array(string_characters)(Int32 _ppl_array)

String characters converts to hex array created before with size = 0 and resized in

Convert.StringToHexArray with size of string_characters:

Convert.StringToHexArray(string_characters)(Hex_ppl_array)

All below mentioned methods convert data in accordance with method name and return:

Returns string bin: **Convert.HexToBin(string with hex value)**

Returns string hex: **Convert.BinToHex(string with bin value)**

Returns string hex: **Convert.IntToHex(string with Int32 value)**

Returns string Int32: **Convert.HexToInt(string with hex value)**

Returns string bin: **Convert.IntToBin(string with Int32 value)**

Returns string Int32: **Convert.BinToInt(string with bin value)**

Examples:

See Examples\lib\Convert.scr

```
>array Int32;  
>Convert.StringToInt32Array("12345") ("Int32");  
Info [CreateArrayFormat2] Global array [Int32] is created  
>writearray Int32;
```

Result:

```
-----Array Int32-----  
[0]      49  
[1]      50  
[2]      51  
[3]      52  
[4]      53
```

```
>array Hex;  
>Convert.StringToHexArray("12345") ("Hex");
```

```
>writearray Hex;
```

```
Result:
```

```
-----Array Hex-----
```

```
[0]      31  
[1]      32  
[2]      33  
[3]      34  
[4]      35
```

Examples:

```
>dbg yes
```

```
>Convert.HexToBin(16) ;
```

```
result = 10110
```

```
>Convert.BinToHex(1111111)
```

```
result = 7F
```

```
>Convert.IntToHex(256)
```

```
result = 100
```

File

Methods:

ReadAllText

WriteAllText

Exists

ReadAllLines

WriteAllLines

Delete

To get short help for every method in **File.DLL**:

>File.help[(method name)];

Returns all contents of text file: **File.ReadAllText(filename)**

Creates a new file, write the contents to the file, and then closes the file:

File.WriteAllText(var_ppl)(filename)

Determines whether the specified file exists, returns True or False: **File.Exists(filename)**

Returns string array with lines of text file: **File.ReadAllLines(filename)(ppl_array)**

Creates a new file, writes one or more strings to the file, and then closes the file:

File.WriteAllLines(ppl_array)(filename)

Deletes the specified file: **File.Delete(filename)**

Example:

```
>rc examples\lib\File.scr
```

```
var text;

//examples\lib\split.txt
//1,2,3,4,5,6,7,8,9,10,
//11,12,13,14,15,16,17,18,19,20

text = File.ReadAllText("examples\lib\split.txt");
write(text);
call File.WriteAllText(text,"examples\lib\Copy.txt");
var b = File.Exists("examples\lib\Copy.txt");
write(b);
if (b == True)
    File.Delete("examples\lib\Copy.txt");
b = File.Exists("examples\lib\Copy.txt");
write(b);

array arr[] = {"One","Two","Three"};
call File.WriteAllLines(arr,"examples\lib\Copy2.txt");
array arr2;
call File.ReadAllLines("examples\lib\copy2.txt",arr2);
writearray arr2;
```



```
File.Delete("examples\\lib\\copy2.txt");
```

Result:

```
1,2,3,4,5,6,7,8,9,10,  
11,12,13,14,15,16,17,18,19,20
```

True

False

-----Array arr2-----

```
[0]    One  
[1]    Two  
[2]    Three
```

Random

The Random library use the Mersenne Twister pseudorandom number generator (PRNG).

Methods:

Create	Delete
Next	Write
NextToArray	

To get short help for every method in **Random.DLL**:

>Random.help[(method name)];

Creates Random object: **Random.Create(random_name)(type)(from)(to)**
type:= "int" | "real"

Returns a random integer: **Random.Next(random_name)**

Creates random numbers and writes them to the of a specified **ppl_array** created before with size = 0:

Random.NextToArray(random name)(ppl_array)(quantity of random elements)

Deletes created random_name or all random_names:

Random.Delete(random_name) | Random.Delete()

Writes random_names: **Random.Write()**

Example:

File examples\lib\random.scr

```
import Random;
call Random.Create("intR","int",1,10);
write(Random.Next("intR"));
write(Random.Next("intR"));
write(Random.Next("intR"));

array int_arr;
call Random.NextToArray("intR",int_arr,10);
writearray int_arr row;

call Random.Create("dblR","real",1,10);
write(Random.Next("dblR"));
write(Random.Next("dblR"));
write(Random.Next("dblR"));

array double_arr;
call Random.NextToArray("dblR",double_arr,10);
```

```
writearray double_arr row;

write("===Random.Delete===[dblR]");
Random.Delete("dblR");
Random.Write();

write("===Random.Delete===[all]");
Random.Delete();
Random.Write();
Result:
Imported [Random]
9
2
10
-----Array int_arr-----
9, 2, 10, 10, 3, 7, 4, 1, 6, 3
2.219293
8.515077
9.719810
-----Array double_arr-----
2.98931, 3.7735, 5.92499, 2.69544, 9.93593, 9.96815, 9.70925,
7.53255, 9.82999, 1.98876
===Random.Delete===[dblR]
0      intR      int
===Random.Delete===[all]
```

Console

For using in scr or ppl files, not for console input.

Methods:

ForegroundColor	Beep
BackgroundColor	Clear
ForegroundPromptColor	SetCursorPosition
DefaultColors	GetCursorPosition
Write	
WindowWidth	WindowHeight

To get short help for every method in **Console.DLL**:

>Console.help[(method name)];

Sets the foreground color of the console:

Console.ForegroundColor(color)

Sets the background color of the console:

Console.BackgroundColor(color)

Sets the prompt foreground color of the console:

Console.ForegroundPromptColor(color)

Sets the default foreground, background and ForegroundPromptColor color of the console:

Console.DefaultColors()

Writes the text representation of the specified value or values to the standard output stream: **Console.Write [(format)](string)(string)**

Plays the sound of a beep through the console speaker:

Console.Beep (frequency)(duration)

frequency - 37 to 32767 hertz

duration - msec

Clears the console buffer and corresponding console window of display information:

Console.Clear()

Sets the position of the cursor:

Console.SetCursorPosition(left column cursor position)(top row cursor position)

Gets the position of the cursor:

Console.GetCursorPosition ()

Returns 'left column cursor position, top row cursor position'

Only for Administrator mode:

Run function **WindowSize()** (see file Functions\CommonFunctions.ppl)

>WindowSize()

width=120 height=30

Get/Set **WindowWidth(value)** and **WindowHeight(value)**

```
>Console.WindowHeight(20)    // set  
>write(Console.WindowHeight()) // get  
20
```

See examples in `examples\Console`.

Vector

Using Vector and Matrix libraries significantly increases program performance.

Methods:

Vector.Create ("vector_name")(length)(type)

type:= double|float|decimal|bool|int|uint|long|ulong|string

types in accordance with value types in

<https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-types/built-in-types>

Vector.Get(vector_name)(index)

Vector.Set(vector_name)(index)(value)

Vector.Add("vector_name")(ppl_array)

Vector.Write("vector_name")(["row" | "col" | "col0"])

Write to line - "row"

Write not nullable data to column - "col"

Write all data to column - "col0"

by default = "row"

Vector.WriteNames()

Vector.Delete("vector_name")

Vector.DeleteAll()

Vector.Sort ("vector_name")(order)

order:= "ascend" | "descend"

To get short help for every method in **Vector.DLL**:

>Vector.help[(method name)];

Examples:

```
>import Vector;
>array v[] = {1,2,3,4,5};
>call Vector.Create ("V",5, "int");
>call Vector.Add("V",v);
> call Vector.Write("V");
=====vector V=====
1      2      3      4      5
>call Vector.Set("V",0,0);
>call Vector.Write("V","col");    // write in column
=====vector V=====
[1]      2
[2]      3
[3]      4
[4]      5
>call Vector.Delete("V");
```

See examples in **examples\MatrixVector**.

Matrix

Methods:

```
Matrix.Create ("matrix_name")(rows)(columns)(type)
type:= double|float|decimal|bool|int|uint|long|ulong|string
types in accordance with value types in
https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-types/built-in-types
Matrix.Get("matrix_name")(index row)(index_column)
Matrix.Set("matrix_name")(index row)(index_column)(value)
Matrix.AddArrayToRow ("matrix_name")(row)("")ppl_array""
Matrix.AddArrayToColumn ("matrix_name")(column)("")ppl_array""
Matrix.Write to line - "row"
Matrix.Write not nullable data to column - "col"
Write all data to column - "col0"
Write("matrix_name")[("row"|"col"|"col0")]
Matrix.WriteNames()
Matrix.Delete("matrix_name")
Matrix.DeleteAll()
Matrix.Rotate("matrix_name")("cw"|"ccw") - for square matrix only

Set column_index for sorting:
Matrix.Sort("matrix_name")(column index| order)
order:= ascend | descend
```

To get short help for every method in Matrix.DLL:

>**Matrix.help[(method name)]**

Example:

```
import Matrix;
call Matrix.Create("D",3,3,"double");
array r11[] = {1,2,3};
array r12[] = {4,5,6};
array r13[] = {7,8,9};

call Matrix.AddArrayToRow("D",0,"r11");
call Matrix.AddArrayToRow("D",1,"r12");
call Matrix.AddArrayToRow("D",2,"r13");

// Rotation CCW
call Matrix.Write("D");
call Matrix.Rotate("D","ccw");
write("===ccw===");
Matrix.Write("D");
```

```
// Rotation CW
call Matrix.Rotate("D","cw");
write("===cw===");
Matrix.Write("D");
Matrix.Delete("D");
```

Result:

```
=====matrix D=====
[0]      1      2      3
[1]      4      5      6
[2]      7      8      9
===ccw===
=====matrix D=====
[0]      3      6      9
[1]      2      5      8
[2]      1      4      7
===cw===
=====matrix D=====
[0]      1      2      3
[1]      4      5      6
[2]      7      8      9
```

```
>import Matrix;
>call Matrix.Create("D",3,3,"double");
>array r11[] = {1,2,3};
>array r12[] = {4,5,6};
>array r13[] = {7,8,9};
>call Matrix.AddArrayToColumn("D",0,r11);
>call Matrix.AddArrayToColumn("D",1,r12);
>call Matrix.AddArrayToColumn("D",2,r13);
>Matrix.Write("D");
>call Matrix.Sort("D",0,"descend");
>Matrix.Write("D");
>Matrix.DeleteAll();
```

```
code: scr
Imported [Matrix]
=====matrix D=====
[0]      1      4      7
[1]      2      5      8
[2]      3      6      9
=====matrix D=====
[0]      3      6      9
[1]      2      5      8
[2]      1      4      7
```

See examples in **examples\MatrixVector**.

DataFrame

DataFrame is a table with named columns, columns may be defined with different types, number of rows and columns is not limited.

DataFrame Architecture in ForestPPL (Under the Hood)

When you create or load a **DataFrame** in ForestPPL, the engine builds a highly optimized Abstract Syntax Tree (AST) structure designed for both execution speed and memory efficiency. The engine uses a hybrid approach, separating global script variables from internal metadata.

Here is how a DataFrame is structurally organized inside the engine:

- **Root Node (DataFrame):** The parent object representing the table (e.g., `DF1`). This node is explicitly registered in the engine's global cache (`ScopeManager`), allowing the script to find the table instantly via an **O(1)** or highly optimized lookup.
- **Settings Node (Settings):** A private, internal branch directly attached to the root. It acts as a container for all table metadata, such as `RowsLength`, `PrintEmptyRows`, and specific column formats (`Type` and `Width`). To maximize performance and prevent polluting the global memory space, `Settings` and its children are **not** registered in the global cache. The core engine accesses them directly via rapid tree traversal.
- **Data Columns (Arrays):** The actual data vectors (e.g., `DF1.Name`, `DF1.Quantity`). These are stored as dedicated array nodes under the root. Because scripts often need direct and fast access to these columns, they are registered in the global cache alongside the root node.

Why this matters for performance:

By keeping internal settings encapsulated within the AST and only exposing the Root and Column arrays to the global **ScopeManager**, ForestPPL maintains a minimal memory footprint. This architecture guarantees that even with hundreds of loaded dataframes, variable lookups remain lightning-fast.

Methods:

SetRow	AddRowData
SetColumn	GetRowArray
Write	GetSliceRowArray
Save	GetColumnArray
ReadFile	GetSliceColumnArray
Init	SetCell
List	GetCell
Create	CellName
InsertRows	SetWidth
AddRows	SetType

InsertColumns	GetWidth
AddColumns	GetType
RemoveRows	SetPrintEmptyRows
RemoveColumns	GetPrintEmptyRows
ClearColumns	SetRowSelectedFrom
SetWidthForAll	GetRowSelectedFrom
SetTypeForAll	SetRowSelectedTo
Sort	GetRowSelectedTo
Reverse	SetResizeStep
SelectRows	GetResizeStep
UnselectRows	GetColumnNames
GetRowsLength	Delete
GetColumnLength	SetArrayToRow
	SetArrayToColumn

To get short help for every method in **DataFrame.DLL**:
>**DataFrame.help**[(method name)]

DataFrame.Init – to add this call in first .scr file only, if project contains several .scr-files.

Format: **DataFrame.Init()**

DataFrame.Create - creates node df_name, node Settings and arrays per each column

Formats:

DataFrame.Create() - creates DataFrame "DF" with 26x26 columns with following names: A,B,C,... BA,BB,BC,...ZA,...ZZ and 1000 rows

DataFrame.Create(Name) - creates DataFrame "Name" with 26x26 columns with following names: A,B,C,... BA,BB,BC,...ZA,...ZZ and 10 rows.

Name := <character literal> | <value of var | array_item>

Format:

DataFrame.Create(Name)(rows length) - creates DataFrame "Name" with 26 columns with following names: A,B,C,...Z and "rows length" rows

DataFrame.Create(Name)(rows length)(column1)(column2)...(columnN) - creates DataFrame "Name" with N columns and "rows length" rows

Examples:

```
>import DataFrame
> var name = "OK"
>DataFrame.Init()
>DataFrame.Create(name) (2) ( "A") ( "B")
```

```
>import DataFrame
>DataFrame.Init()
>DataFrame.Create("D") (2) ( "A") ( "B")
>d
-N2      NS
---N3    Global
-----L0 empty    (const)
-----N4 DF          [DataFrame]
-----N5      Settings
-----L0      RowSelectedFrom
-----L1      RowSelectedTo
-----L2      PrintEmptyRows [yes]
-----L3      RowsLength     [2]
-----L4      ResizeStep     [10]
-----L5      AType    [Text]
-----L6      AWidth   [12]
-----L7      BType    [Text]
-----L8      BWidth   [12]
-----N5      A          [Array 2]
-----L0      #
-----L1      #
-----N5      B          [Array 2]
-----L0      #
-----L1      #
```

DataFrame.Settings.RowSelectedFrom and **DataFrame. Settings.RowSelectedTo** sets selected rows and used in **DataFrame.Read**, **DataFrame.Save**, **DataFrame.Write**.

DataFrame.Settings.PrintEmptyRows sets to present or not empty rows and used in **DataFrame.Write**.

DataFrame. Settings.RowsLength is set automatically as number of rows.

DataFrame. Settings.ResizeStep sets number of allocated rows and used in **DataFrame Create** and **DataFrame AddRows**.

DataFrame. Settings.<column name>Type sets column type and used in **DataFrame.Read** and **DataFrame.Sort**.

DataFrame. Settings.<column name>Width sets column width and used in **Write**.

1. Example:

```

ForestPPL
>import DataFrame
Imported [DataFrame]
>call DataFrame.Create("AB",10)
>DataFrame.Write("AB")

===== AB =====
  A  B  C  D  E  F  G  H  I  J  K  L  M  N  O  P  Q  R  S  T  U  V  W  X  Y  Z  BA  BB  BC  BD  BE  BF  BG  BH  BI  BJ  BK  BL  BM
BN BO BP BQ BR BS BT BU BV BW BX BY BZ CA CB CC CD CE CF CH CI CJ CK CL CM CN CO CP CQ CR CS CT CU CV CW CX CY CZ DA
DB DC DD DE DF DG DH DI DJ DK DL DM DN DO DP DQ DR DS DT DU DV DW DX DY DZ EA EB EC ED EE EF EG EH EI EJ EK EL EN EO EP EQ ER ES ET
EU EV EW EX EY EZ FA FB FC FD FE FF FG FH FI FJ FK FL FM FN FO FP FQ FR FG FH FI FJ FK FL FM FN FO FP FQ FR FG FH FI FJ FK FL FM FN FO
GP GQ GR GS GT GU GV GW GX GY GZ HA HB HC HD HE HF HG HH HI HJ HK HL HM HN HO HP HQ HR HS HT HU HV HW HX HY HZ IA IB IC ID IE IF
IG IH II IL IM IN IO IP IQ IR IS IT IU IV IW IX IY IZ JA JB JC JD JE KF KG KH KI KJ KK KL KM KN KO KP KR KS KT KU KV KW KY KZ LA
LB LC LD LE LF LG LH LI LJ LK LL LM LN LO LP LQ LR LS LT LU LV LW LX LY LZ MA MB MC MD ME MF MG MH MI MJ MK ML MN MO MP MQ MR MS
MT MU MV MW MX MY MZ NA NB NC ND NE NF NG NH NI NJ NK NL NM NN NO NP NQ NR NS NT NU NV NW NX NY NZ OA OB OC OD OE OF OG OH OI
OJ OK OL OM ON OP OQ OR OS OT OU OV OW OX OY OZ PA PB PC PD PE PF PG PH PI PJ PK PL PM PN PO PP PQ PR PS PT PU PV PW PX PY PZ
QA QB QC QD QE QF QG QH QI QJ QK QL QM QN QO QQ QR QS QT QU QV QW QX QY QZ RA RB RC RD RE RF RG RH RI RJ RK RL RM RN RO RP RQ RR RS
RT RU RV RW RX RY RZ SA SB SC SD SE SF SG SH SI SJ SK SL SM SN SO SP SQ SR SS ST SU SV SW SX SY SZ TA TB TC TD TE TF TG TH TI TJ
TK TL TM TN TO TP TQ TR TS TT TU TV TW TX TY UA UB UC UD UE UF UG UH UI UJ UK UL UM UN UO UP UQ UR US UT UV UW UX UY UZ VA VB
VC VD VE VF VG VH VI VJ VK VL VM VN VO VP VQ VR VS VT VU VV VW VX VY VZ WA WB WC WD WE WF WG WH WI WJ WK WL WM WN WO WP WQ WR
WS WT WU WV WW WX WY WZ XA XB XC XD XE XF XG XH XI XJ XK XL XM XN XO XP XQ XR XS XT XU XV XW XZ YA YB YC YD YE YF YG YH YI YJ
YK YL YM YN YO YP YQ YR YS YT YU YV YW YX YY YZ ZA ZB ZC ZD ZE ZF ZG ZH ZI ZJ ZK ZL ZM ZN ZO ZP ZQ ZR ZS ZT ZU ZV ZW ZX ZY ZZ
0
1
2
3
4
5
6
7
8
9

```

2. Example

```

>import DataFrame
>call DataFrame.Create("MyDataFrame",2,"One","Two","Three")
-----Variables and arrays-----
-N4      MyDataFrame      [Node]
---N5      Settings      [Node]
---N5      One            [Array 2]
---N5      Two            [Array 2]
---N5      Three          [Array 2]
>DataFrame.Write(MyDataFrame)
Result:
      One      Two      Three
0
1

```

DataFrame.SetRow and **DataFrame.SetColumn** return **false** if **columnType = Number** and value is not digital

DataFrame.SetRow - sets values for each column for defined row from array,variables or literal.

Format:

DataFrame.SetRow(df_name)(row index)(ppl_array)

DataFrame.SetRow(df_name)(row index)(literal1) | (var1) (literal2) | (var2) ...

DataFrame.SetColumn - sets values for each element for defined column from array, variables or literal.

Format ppl:

DataFrame.SetColumn(df_name)(column) (ppl_array)

DataFrame.SetColumn(df_name)(column)(literal1) | (var1) (literal2) | (var2) ...

Examples:

```
import DataFrame;
DataFrame.Init();
call DataFrame.Create
    ("DF",5,"City","Population","Area","Elevation");

write#("====SetRow====");
// Setting by data
call DataFrame.SetRow("DF",0,"Ljubljana",279631,163.8,295,0,0);
    // Warning: out of bounds 0,0
call DataFrame.Write("DF");

// Setting by array
array Kranj[] = {"Kranj",37941,148,386};
call DataFrame.SetRow("DF",1,Kranj);
//call DataFrame.Write("DF");
// Setting by vars
var x = "Kranj";
var y = 37941;
call DataFrame.SetRow("DF",1,x,y);
call DataFrame.Write("DF");
```

DataFrame.Write - displays DataFrame full contents or only contents of defined columns

Format:

DataFrame.Write[(df_name)] [("column")("column")...]

To display contents of specific rows call before **DataFrame.Write**:

DataFrame. RowSelectedFrom (df_name)(row index)

DataFrame. RowSelectedTo (df_name)(row index)

or by method **SelectRows**.

DataFrame.SelectRows(df_name)(row index from)(row index to)

DataFrame.Save -saves full contents of DataFrame in file format **".csv"** or **".data"** or defined columns only in format **".csv"**

Format:

```
DataFrame.Save(df_name)("filename.csv|.data")[(column)( column)]...  
DataFrame.Save(df_name)(" filename.data")
```

DataFrame.ReadFile - reads full contents of DataFrame from file in format **".csv"** or **".data"** or contents of defined columns from file in format **".csv" only**

Format:

(1) **DataFrame.ReadFile(df_name) (filename.csv)[(column)(column)]...**

or

(2) **DataFrame.ReadFile(filename.data)**

Format (2) deletes existing data and creates new Dataframe or several DataFrames with names from file.data

Example:

```
File df.data  
(DF [DataFrame]  
  (Settings  
    (RowSelectedFrom)  
    (RowSelectedTo)  
    (PrintEmptyRows [yes])  
    (RowsLength [3])  
    (ResizeIncrement [10])  
    (NameType [Text])  
    (NameWidth [12])  
    (QuantityType [Text])  
    (QuantityWidth [12])  
  )  
  (Name [Array 3]  
    (# ["CARS"])  
    (# ["TREES"])  
    (# ["ROADS"])  
  )  
  (Quantity [Array 3]  
    (# [20])  
    (# [30])  
    (# [40])  
  )  
)  
>import DataFrame;  
>call DataFrame.ReadFile("examples\DataFrame\df.data");  
>call DataFrame.Write("DF");
```

Result:

	Name	Quantity
0	"CARS"	20
1	"TREES"	30
2	"ROADS"	40

DataFrame.InsertRows - inserts number of rows before index

Format:

DataFrame.InsertRows(df_name)(index)[(number of rows)]

By default number of added rows= 1

DataFrame.AddRows - adds number of empty rows at the end

Format:

DataFrame.AddRows([df_name)][(number of rows)]

By default df_name = DF

By default number of added rows: **DataFrame.Settingd.ResizeatedIncrement = 10**

DataFrame.InsertColumns - insert one or several named columns before defined column

Format:

DataFrame.InsertColumns(df_name))(defined column1)(column2)(column3)...

DataFrame AddColumns - adds number of named columns at the end

Format:

DataFrame.AddColumns(df_name)(column1)(column2)...

DataFrame RemoveRows – removes rows

Format:

DataFrame.RemoveRows(df_name) – removes all rows

DataFrame.RemoveRows(df_name)[(number_of_row)] – removes 1 row

DataFrame.RemoveRows(df_name)(number_from)(*) - removes rows
between number_from to the end of rows

DataFrame.RemoveRows(df_name)(number_from)(number_to) - removes rows
between number_from – number_to

DataFrame.RemoveColumns - removes named columns and their Type and Width in
Settings

Format: **DataFrame.RemoveColumns(df_name)[(column1)(column2)...**

DataFrame.RemoveColumns(df_name) - removes all columns and their Type and
Width in **Settings**:

DataFrame.ClearColumns - clears contents of all DataFrame or defined columns:

Format: **DataFrame.ClearColumns(df_name)[(column1)(column2)...]**

DataFrame.SetWidthForAll - sets same width for all columns to display DataFrame by
DataFrame.Write

Format: **DataFrame.SetWidthForAll [(df_name)] (width)**

default name – DF

default with = 12

Example:

```
>DataFrame.SetWidthForAll (14)
```

DataFrame.SetTypeForAll - sets same type for all columns

Format: **DataFrame.SetTypeForAll [(df_name)] [("Text" | "Number")]**

default name – DF

default type = Text

Example:

```
>DataFrame.SetTypeForAll ("Number")
```

DataFrame.Sort - sorts all contents by specified column in ascending or descending order

Format: **DataFrame.Sort(df_name)("ascend" | "descend")(column)**

Example:

```
File: examples\DataFrame\products.csv
```

```
Bagel,140,310,Medium
```

```
Biscuit ,86,480,High
```

```
Jaffa cake,48,370,Med-High
```

```
Bread white,96,240,Medium
```

```
Bread wholemeal,88,220,LowMed
```

```
Chapatis,250,240,Medium
```

```
Cornflakes,130,300,Med-High
```

```
Program: examples\DataFrame\df8.scr
```

```
import DataFrame;
```

```
DataFrame.Create(Products) (0) (Bread&Cereals) (Size) (per100grams)  
                        (energy) ;
```

```
set Products.Settings.Bread&CerealsWidth = 20;
```

```
DataFrame.ReadFile(Products) (examples\DataFrame\products.csv) ;
```

```
DataFrame.Write(Products) ;
```

```
DataFrame.Sort(Products) ("ascend") (per100grams) ;
```

```
DataFrame.Write(Products) ;
```

```
Forest
>rc examples\dataframe\df8.scr
code: scr
Imported [DataFrame]
DataFrame [Products] added [7] rows

=====Products=====
      Bread&Cereals      Size      per100grams  energy
0      Bagel           140          310      Medium
1      Biscuit          86          480      High
2      Jaffa cake       48          370      Med-High
3      Bread white      96          240      Medium
4      Bread wholemeal  88          220      LowMed
5      Chapatis         250         240      Medium
6      Cornflakes       130         300      Med-High
=====DF Reverse=====

=====Products=====
      Bread&Cereals      Size      per100grams  energy
0      Cornflakes       130         300      Med-High
1      Chapatis         250         240      Medium
2      Bread wholemeal  88          220      LowMed
3      Bread white      96          240      Medium
4      Jaffa cake       48          370      Med-High
5      Biscuit          86          480      High
6      Bagel           140         310      Medium
=====DF Sorted order Ascending=====
```

See examples df8.scr and df9.scr(wrong results for digital data when Type = Text).

DataFrame.Reverse - reverses all DataFrame contents by columns

Format: **DataFrame.Reverse(df_name)**

DataFrame.SelectRows

Format:

Select one row only: **DataFrame.SelectRows(df_name)(select_from)**

Select rows select_from – to end: **DataFrame.SelectRows(df_name)(select_from)(*)**

Select rows between select_from – select_to:

DataFrame.SelectRows(df_name)(select_from)(select_to)

DataFrame.UnSelectRows

Format: **DataFrame.UnSelectRows(df_name)**

DataFrame.GetRowsLength – returns number of rows

Format: **DataFrame.GetRowLength(df_name)**

DataFrame.GetColumnsLength – returns number of columns

Format: **DataFrame. GetColumnsLength (df_name)**

DataFrame.AddRowData – adds row with data per columns at the end

Format: **DataFrame.AddRowData(df_name)(ppl_array)**

DataFrame.GetRowArray – copies data from defined row to ppl array

Format:

DataFrame.GetRowArray(df_name)(index row) (ppl array)

DataFrame.GetSliceRowArray - copies dataframe data, defined by row,column_from
[and column_to] to ppl array

Format:

To the end of rows:

DataFrame. GetSliceRowArray (df_name)(row)(column_from)(ppl array)

or

DataFrame. GetSliceRowArray (df_name)(row)(column_from)(column_to)(ppl array)

DataFrame.GetColumnArray - copies data from defined column to array

Format:

DataFrame.GetColumnArray(df_name)(column) (ppl array)

DataFrame.GetSliceColumnArray – copies dataframe data, defined by column, row_from [and row_to] to array

Format:

To the end of columns:

DataFrame. GetSliceColumnArray (df_name)(column)(row_from)(ppl array)

or

**DataFrame. GetSliceColumnArray (df_name)(column)(row_from)(row_to)
(ppl array)**

Example:

```
File: Examples\DataFrame\df12.scr
recreate yes;
import DataFrame;
DataFrame.Init();
call DataFrame.Create("Table",0,"A","B","C","D","E");
call DataFrame.SetType("Table","A", "Number");
call DataFrame.ReadFile("Table","examples\dataframe\Table.csv");
DataFrame.Write("Table");

write("====DataFrame.GetColumnArray====");
array arr_column_A;
call DataFrame.GetColumnArray("Table","A",arr_column_A);
writearray arr_column_A row;

write("====DataFrame.GetRowArray====");
array arr_row_0;
call DataFrame.GetRowArray("Table",0,arr_row_0);
writearray arr_row_0 row;

write("====DataFrame.GetSliceRowArray====");
array arr_A2;
call DataFrame.GetSliceRowArray("Table",0,"A",arr_A2);

writearray arr_A2 row;

array arr_A3;
call DataFrame.GetSliceRowArray("Table",1,"B","D",arr_A3);
writearray arr_A3 row;

write("====DataFrame.GetSliceColumnArray====");
array arr_A4;
call DataFrame.GetSliceColumnArray("Table","B",1,4,arr_A4);
writearray arr_A4 row;
```

```

array arr_A5;
call DataFrame.GetSliceColumnArray("Table","B",0,arr_A5);
writearray arr_A5 row;

del all;
printscope;
>rc examples\dataframe\df12.scr
Result:
code: scr
Imported [DataFrame]

===== Table =====

      A      B      C      D      E
0      1      2      3      4      5
1     10     20     30     40     50
2    100    200    300    400    500
3   1000   2000   3000   4000   5000
4  10000  20000  30000  40000  50000

=====DataFrame.GetColumnArray=====
-----Array [arr_column_A]-----
1, 10, 100, 1000, 10000
=====DataFrame.GetRowArray=====
-----Array [arr_row_0]-----
1, 2, 3, 4, 5
=====DataFrame.GetSliceRowArray=====
-----Array [arr_A2]-----
1, 2, 3, 4, 5
-----Array [arr_A3]-----
20, 30, 40
=====DataFrame.GetSliceColumnArray=====
-----Array [arr_A4]-----
20, 200, 2000, 20000
-----Array [arr_A5]-----
2, 20, 200, 2000, 20000

===== State of SCOPE MANAGER =====
Depth [0]
(Global)
<-- TOP (Current of Context)
<no variables>

```

DataFrame.SetCell - sets value for cell ,defined by name or by column name and row index

Format:

DataFrame.SetCell(df_name)(column name)(index row)(value)

or

DataFrame.SetCell(df_name.cell_name)(value)

DataFrame.GetCell - returns value of cell, defined by name or by column name and row index

Format:

DataFrame.GetCell(df_name)(column name)(index row)

or

DataFrame.GetCell(df_name.cell_name)

DataFrame.CellName - sets name for defined cell

Format: **DataFrame.CellName(df_name)(column name)(index row)(cell name)**

DataFrame.SetWidth - sets Width value for defined column name in **Settings**

Format: **DataFrame. SetWidth (df_name)(column name)(value)**

DataFrame.SetType - sets Type value for defined column name in **Settings**

Format: **DataFrame. SetType (df_name)(column name)("Text " | "Number")**

DataFrame.GetWidth - returns Width for defined column name in **Settings**

Format: **DataFrame. GetWidth (df_name)(column name)**

Example:

```
>import DataFrame
>DataFrame.Create("DF") (2) ( "A") ("B")
>DataFrame.SetWidth("DF") ("A") (15)
>write(DataFrame.GetWidth("DF") ("A"))
15
```

DataFrame.GetType - returns Type for defined column name in **Settings**

Format: **DataFrame.GetType(df_name)(column name)**

Example:

```
>import DataFrame
>DataFrame.SetType("DF")("A")("Number")
>write(DataFrame.GetType("DF")("A"))
Number
```

DataFrame.SetPrintEmptyRows - sets PrintEmptyRows value in **Settings**

Format: **DataFrame.SetPrintEmptyRows(df_name)(value)**

value:= "yes" | "no"

DataFrame.GetPrintEmptyRows - returns PrintEmptyRows value in **Setting**

Format: **DataFrame.GetPrintEmptyRows(df_name)**

Example:

```
>import DataFrame;
>DataFrame.Create(DF)(2)(A)(B);
>DataFrame.SetPrintEmptyRows(DF)("yes");
>write(DataFrame.GetPrintEmptyRows(DF));
yes
```

DataFrame.SetRowSelectedFrom - sets RowSelectedFrom value in **Settings**

Format: **DataFrame.SetRowSelectedFrom(df_name)(index_row_from)**

DataFrame.GetRowSelectedFrom - returns RowSelectedFrom value in **Setting**

Format: **DataFrame.GetRowSelectedFrom(df_name)**

DataFrame.SetRowSelectedTo - sets RowSelectedTo value in **Settings**

Format: **DataFrame.SetRowSelectedTo(df_name)(index_row_to)**

DataFrame.GetRowSelectedTo – returns RowSelectedTo value in **Settings**

Format: **DataFrame.GetRowSelectedTo(df_name)**

Example:

```
>code scr;
>import DataFrame;
>call DataFrame.Create("DF",2, "A","B");
```

```
>call DataFrame.SetRowSelectedFrom("DF",0);  
>call DataFrame.SetRowSelectedTo("DF",1);  
>write(DataFrame.GetRowSelectedFrom("DF"));  
result: 0  
>write(DataFrame.GetRowSelectedTo("DF"));  
1
```

DataFrame.SetResizeStep - sets ResizeStep value in **Settings**

Format: **DataFrame.SetResizeStep(df_name)(value)**

DataFrame.GetResizeStep - returns ResizeStep value in **Settings**

Format: **DataFrame.GetResizeStep(df_name)**

Example:

```
>import DataFrame;  
>DataFrame.Create("DF") (2) ("A") ("B");  
>DataFrame.SetResizeStep("DF") (100);  
>write(DataFrame.GetResizeStep("DF"));  
100
```

DataFrame.GetColumnNames – returns string with column names, separated by comma

Format:

DataFrame.GetColumnNames(df_name)

Example:

```
>import DataFrame;  
>DataFrame.Init();  
>call DataFrame.Create("Table",5,"A","B","C","D","E");  
>write(DataFrame.GetColumnNames("Table"));  
A,B,C,D,E
```

DataFrame.List – displays all created DataFrame names, their settings and cell names

Format: **DataFrame.List()**

Example:

```
>import DataFrame;  
>DataFrame.Init();  
>call DataFrame.Create("Table1",10, "A","B","C","D","E");  
>call DataFrame.CellName("Table1.A",0, "A0");
```



```
>call DataFrame.CellName("Table1","B",0,"B0");
>call DataFrame.SetWidthForAll("Table1",10);
>call DataFrame.List();
=====Table1=====
  Settings
    RowSelectedFrom =
    RowSelectedTo =
    PrintEmptyRows = yes
    RowsLength = 10
    ResizeIncrement = 10
    AType = Text
    AWidth = 10
    BType = Text
    BWidth = 10
    CType = Text
    CWidth = 10
    DType = Text
    DWidth = 10
    EType = Text
    EWidth = 10
  defined cell names in DataFrame [Table1]
    name          column    row
    A0             A         0
    B0             B         0
```

DataFrame.Delete – delete all from DataFrame

Format **ppl**:

DataFrame.Delete()

DataFrame.Delete(name)

DataFrame.Delete(name1)(name2)...

Format **scr**:

DataFrame.Delete() or call **DataFrame.Delete()**

DataFrame.Delete(name) or call **DataFrame.Delete(name)**

DataFrame.Delete(name1)(name2)... or

call **DataFrame.Delete(name1,name2,...**

Important Note:

```
del all;           // delete data from DataFrame, all arrays
                   // and variables out of DataFrame
DataFrame.Delete(); // delete data from DataFrame only
```

SetArrayToRow – write data to row of df_name from array only
unlike SetRow, that works with vars, array and raw data.

Format **ppl**:

DataFrame.SetArrayToRow (df_name)(row)(array_name)

Format **scr**:

Call DataFrame.SetArrayToRow (df_name,row,array_name)

SetArrayToColumn - write data to column of df_name from array only
Unlike SetColumn, that works with vars, array and raw data.

Format **ppl**:

DataFrame.SetArrayToColumn (df_name)(column)(array_name)

Format **scr**:

Call DataFrame.SetArrayToColumn (df_name,column,array_name)

Both functions trim excess elements and display a Warning.

Examples:

```
>rc examples\dataframe\df27.scr
recreate yes;
import DataFrame;
DataFrame.Init();

write("====DataFrame.SetArrayToRow====");
call DataFrame.Create("DF",2, "Language","Complexity");
array arr[] = {"Assembler","High"};
call DataFrame.SetArrayToRow("DF",0,arr);
array arr[] = {"C","Medium","Professional"};
call DataFrame.SetArrayToRow("DF",1,arr);          // warning
DataFrame.Write("DF");
//array arr[] = {"C++","Medium","Professional"};
//call DataFrame.SetArrayToRow("DF",2,arr);          // error

call DataFrame.ClearColumns("DF");
call DataFrame.Write("DF");

write("====DataFrame.SetArrayToColumn====");
array arr[] = {"C","C++"};
call DataFrame.SetArrayToColumn("DF","Language",arr);

array arr[] = {"C","C++","ForestPPL"};
call DataFrame.SetArrayToColumn("DF","Language",arr);    // warning

array arr[] = {"High","Medium"};
call DataFrame.SetArrayToColumn("DF","Complexity",arr);
//array arr[] = {"Assembler","C","C++"};
//call DataFrame.SetArrayToColumn("DF","Creator",arr);    // error
```

```
call DataFrame.Write("DF");
=====DataFrame.SetArrayToRow=====
Warning: [DataFrame.FuncSetArrayToRow] DataFrame [DF] array size (3)
does not match columns count (2).
Data will be truncated or partially filled.

===== DF =====
      Language      Complexity
0   Assembler    High
1      C         Medium

===== DF =====
      Language      Complexity
0
1

=====DataFrame.SetArrayToColumn=====
Warning: [DataFrame.FuncSetArrayToColumn] DataFrame [DF] array size
(3) does not match rows count (2).
Data will be truncated or partially filled.

===== DF =====
      Language      Complexity
0      C         High
1    C++         Medium
```

Examples of using DataFrame methods in directory: examples\DataFrame
df1.scr – df27.scr, AddressBook2.scr, AddressBook.scr

StorageLib

The StorageLib library provides methods for creating and manipulating dynamic storage collections (arrays/lists). This library uses the names created by the storage command, so storagename is not enclosed in quotes.

Methods:

help	Push	Pop
Reverse	Shift	Remove
Clear	Unshift	Insert
Slice	Sum	Copy
Filtercopy	Min	Max
Average	First	Last
Concat	Sort	Save
ReadFile	IndexOf	Contains
CountOf	Join	Split
Unique	Shuffle	Product
Median		

To get short help for every method in **Storage.DLL**:

```
>storage.help[(method name)];
```

Example:

```
>import StorageLib
Imported [StorageLib]
>storage.help(Clear)
>storage.Clear(storage_name) - removes all elements.
```

Push

Adds an element to the end of the storage.

Format: **storage.Push(storage_name)(value)**

Example:

```
>import StorageLib
Imported [StorageLib]
>storage s1
>call storage.Push(s1,10);
>call storage.Push(s1,20);
>call storage.Push(s1,30);
>swrite (s1);
```

10	20	30
----	----	----

Pop

Removes and returns the last element.

Format: **storage.Pop(storage_name)(target_var)**

Reverse

Reverses the order of elements.

Format: **storage.Reverse(storage_name)**

Shift

Removes and returns the first element.

Format: **storage.Shift(storage_name)(target_var)**

Remove

Removes the element at index.

Format: **storage.Remove(storage_name)(index)**

Clear

Removes all elements.

Format: **storage.Clear(storage_name)**

Unshift

Adds an element to the beginning.

Format: **storage.Unshift(storage_name)(value)**

Insert

Inserts an element at index.

Format: **storage.Insert(storage_name)(index)(value)**

Slice

Extracts a section into target_storage.

Format: **storage.Slice(storage_name)(start)(end)(target_storage)**

Sum

Calculates the sum of elements.

Format: **storage.Sum(storage_name)(target_var)**

Copy

Copies all elements from source to destination.

Format: **storage.Copy(source)(destination)**

Filtercopy

Copies non-zero elements from source to dest.

Format: **storage.Filtercopy(source)(dest)**

Min

Finds the minimum element.

Format: **storage.Min(storage_name)(target_var)**

Max

Finds the maximum element.

Format: **storage.Max(storage_name)(target_var)**

Average

Calculates the average of elements.

Format: **storage.Average(storage_name)(target_var)**

First

Gets the first element.

Format: **storage.First(storage_name)(target_var)**

Last

Gets the last element.

Format: **storage.Last(storage_name)(target_var)**

Concat

Concatenates two arrays into target.

Format: **storage.Concat(storage1)(storage2)(target)**

Sort

Sorts elements in ascending order.

Format: **storage.Sort(storage_name)**

Save

Saves the array to a .csv or .data file.

Format: **storage.Save(storage_name)(filename.csv|data)[(delimiter)]**

Example:

```
>dbg yes;
>storage s[3,10];
storage.Save (s) ("examples\StorageLib\saved_3x10.csv") ("," );
storage s;
storage.ReadFile (s) ("examples\StorageLib\saved_3x10.csv") ("," );
swrite s;
```

```
File examples\StorageLib\saved_3x10.csv
_shape_,3,10
0,0,0,0,0,0,0,0,0,0,0
0,0,0,0,0,0,0,0,0,0,0
0,0,0,0,0,0,0,0,0,0,0

=====s=====
 0      0      0      0      0      0      0      0      0      0
 0      0      0      0      0      0      0      0      0      0
 0      0      0      0      0      0      0      0      0      0
```

ReadFile

Loads the array from a .csv or .data file.

Format: **storage.ReadFile(storage_name)(filename.csv|data)[(delimiter)]**

IndexOf

Finds the index of value.

Format: **storage.IndexOf(storage_name)(value)(target_var)**

Contains

Returns True/False whether value is present.

Format: **storage.Contains(storage_name)(value)(target_var)**

CountOf

Counts occurrences of value.

Format: **storage.CountOf(storage_name)(value)(target_var)**

Join

Joins elements into a string using delimiter.

Format: **storage.Join(storage_name)(delimiter)(target_var)**

Split

Format: Splits a string into target_storage.

storage.Split(source_string)(delimiter)(target_storage)

Unique

Removes duplicate elements.

Format: **storage.Unique(storage_name)**

Shuffle

Randomizes the order of elements.

Format: **storage.Shuffle(storage_name)**

Product

Multiplies all elements together.

Format: **storage.Product(storage_name)(target_var)**

Median

Calculates the median of elements.

Format: **storage.Median(storage_name)(target_var)**

See file examples\StorageLib\TestAll.scr

Structure of User's DLL

Utility **CodeGen.exe** generates files .h and .cpp in accordance with structure of User's DLL, described in configuration file.

Example:

Configuration file **Stack.cfg**

```
ProjectName = Stack
Methods = Create,Delete,Count,Write,Push,Pop,Peek,Clear,Contains,
          AddArray,ToArray
```

Run **CodeGen.exe Stack.cfg**

CodeGen.exe generates 2 files: Stack.cpp and Stack.h

Stack.cpp

```
#include "pch.h"
#include "..\PPL\PPL.h"
#include "..\PPL\Component\Component.h"
#include "..\PPL\Processing\processing.h"
#include "Stack.h"

using namespace std;
namespace PPLNS
{
    static Stack* STACKInstance = nullptr;

    void Stack_CreateInstance(PPL* ppl)
    {
        STACKInstance = new Stack(ppl);
        STACKInstance->AddToKeywordDictionary();
    }

    Stack::Stack(PPL* ppl)
    {
        this->ppl = ppl;
        keyword_dict = new unordered_map<string, function<bool(const
vector<string>&, string&, Composite*)>>>;
    }
    //=====
    void Stack::AddToKeywordDictionary()
    {
        //help_dict is created in BaseClass
        AddKeyword("help", BaseClass::FuncHelp);
        AddKeyword("Create", FuncCreate);
        AddKeyword("Delete", FuncDelete);
        AddKeyword("Count", FuncCount);
        AddKeyword("Write", FuncWrite);
        AddKeyword("Push", FuncPush);
        AddKeyword("Pop", FuncPop);
        AddKeyword("Peek", FuncPeek);
        AddKeyword("Clear", FuncClear);
        AddKeyword("Contains", FuncContains);
    }
}
```

```
AddKeyword("AddArray", FuncAddArray);
AddKeyword("ToArray", FuncToArray);

help_dict->insert({ "help", "\tStack.help([name])" });
help_dict->insert({ "Create", "\t..." });
help_dict->insert({ "Delete", "\t..." });
help_dict->insert({ "Count", "\t..." });
help_dict->insert({ "Write", "\t..." });
help_dict->insert({ "Push", "\t..." });
help_dict->insert({ "Pop", "\t..." });
help_dict->insert({ "Peek", "\t..." });
help_dict->insert({ "Clear", "\t..." });
help_dict->insert({ "Contains", "\t..." });
help_dict->insert({ "AddArray", "\t..." });
help_dict->insert({ "ToArray", "\t..." });
for (const auto pair : *keyword_dict)
{
    string key = "Stack." + pair.first;
    ppl->processing->keyword_dict->insert({ key, pair.second });
}
ppl->ImportList.insert({ "Stack", this });
}
//=====
bool Stack::FuncCreate(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncDelete(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncCount(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncWrite(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncPush(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncPop(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncPeek(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncClear(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncContains(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncAddArray(const vector<string>& parameters, string&
result, Composite* node) { return true; }
bool Stack::FuncToArray(const vector<string>& parameters, string&
result, Composite* node) { return true; }
}
```

Stack.h

```

/*****
*This code generated by Application CodeGen.exe
*for creation User DLL
*Add Project Reference PPL.Lib
*Add pch.h from Project PPL
*Author: Oscar Kogosov, email: ok21@hotmail.com
*You must not remove this notice from this software.
*****/
#ifndef STACK_H
#define STACK_H

#ifdef STACK_EXPORTS
#define STACK_API __declspec(dllexport)
#else
#define STACK_API __declspec(dllimport)
#endif

namespace PPLNS
{
    class STACK_API Stack : public BaseClass
    {
    public:
        Stack(PPL* ppl);
        void AddToKeywordDictionary();
        bool FuncCreate(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncDelete(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncCount(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncWrite(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncPush(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncPop(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncPeek(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncClear(const vector<string>& parameters, string& result,
Composite* node);
        bool FuncContains(const vector<string>& parameters, string&
result, Composite* node);
        bool FuncAddArray(const vector<string>& parameters, string&
result, Composite* node);
        bool FuncToArray(const vector<string>& parameters, string&
result, Composite* node);
    };
    extern "C" void STACK_API Stack_CreateInstance(PPL* ppl);
}
#endif

```

Add commentary in lines:

```
help_dict->insert({ "...", "\t..." });
```

Add code to each of methods in Stack.cpp –

```
FuncCreate,  
FuncDelete,  
.....
```

Add to project file from CodeGen\x64\Debug\pch.h

Add to Project References the project **PPL**.

Add created DLL-file to directory ForestPPL.

Error detection

Error detection in script files is carried out in three stages -

1. at the stage of reading files - checking the pairing of parentheses and square brackets, as well as the pairing of quotes;
2. at the pre-translation stage - checking the syntax of operators and commands, indicating name of PPL-module, the file name and line number;
3. at runtime stage.

Right code:

```
var x = 1;  
write (x);
```

```
var x = 1;  
write x);  
Error: [TCheckNumberOfParentheses] not paired number of parentheses  
[write x)]
```

```
var x = 1;  
awrite (x);  
Error: [TCreateCodeTree] file: [examples\err5.scr] line: [2] wrong  
cmd [awrite]
```

```
var x 1;  
write (x);  
Error: [TFuncVar] file: [examples\err5.scr] line: [1] wrong format  
cmd 'var' [var x 1;]
```

defence from 'glued commands'

```
>var x = 0 display  
Error: [TFuncVar] syntax error: unexpected tokens in expression  
(missing semicolon?) [var x = 0 display;]
```

Error detection in interactive mode:

```
>var x 1;  
Error: [TFuncVar] wrong format cmd 'var' [var x 1;]
```

Before executing the script, a syntax check is performed if **checksyntax yes**.

Examples of code

```
//Sieve of Eratosthenes
//>rc Examples\scr\sieve3.scr
var m = 1000;
showcode no;
var len;
len = m + 1;
array primes[len];

for (k, 0, len)
{
    primes[k] = k;
}

primes[1] = 0;

start;
for (n, 2, len)
{
    if(n * n >= len)
        break;

    if (primes[n] != 0)
    {
        var start_j = n * n;

        for(j, start_j, len, n)
        {
            primes[j] = 0;
        }
    }
}
stop("1. duration = ");

start;
// not write items with zero-value
writearray primes row false;
stop("2. duration = ");

start;
array dst;
//copy to array dst items with non zero value only
//array.filtercopy(primes, dst);
array.filtercopy primes, dst;

writearray dst row;
stop("3. duration = ");
```

```
>rc examples\scr\sieve3.scr
1. duration = 1.2613 msec
-----Array [primes]-----
2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61,
67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127, 131, 137,
139, 149, 151, 157, 163, 167, 173, 179, 181, 191, 193, 197, 199, 211,
223, 227, 229, 233, 239, 241, 251, 257, 263, 269, 271, 277, 281, 283,
293, 307, 311, 313, 317, 331, 337, 347, 349, 353, 359, 367, 373, 379,
383, 389, 397, 401, 409, 419, 421, 431, 433, 439, 443, 449, 457, 461,
463, 467, 479, 487, 491, 499, 503, 509, 521, 523, 541, 547, 557, 563,
569, 571, 577, 587, 593, 599, 601, 607, 613, 617, 619, 631, 641, 643,
647, 653, 659, 661, 673, 677, 683, 691, 701, 709, 719, 727, 733, 739,
743, 751, 757, 761, 769, 773, 787, 797, 809, 811, 821, 823, 827, 829,
839, 853, 857, 859, 863, 877, 881, 883, 887, 907, 911, 919, 929, 937,
941, 947, 953, 967, 971, 977, 983, 991, 997
2. duration = 0.579 msec
-----Array [dst]-----
2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61,
67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127, 131, 137,
139, 149, 151, 157, 163, 167, 173, 179, 181, 191, 193, 197, 199, 211,
223, 227, 229, 233, 239, 241, 251, 257, 263, 269, 271, 277, 281, 283,
293, 307, 311, 313, 317, 331, 337, 347, 349, 353, 359, 367, 373, 379,
383, 389, 397, 401, 409, 419, 421, 431, 433, 439, 443, 449, 457, 461,
463, 467, 479, 487, 491, 499, 503, 509, 521, 523, 541, 547, 557, 563,
569, 571, 577, 587, 593, 599, 601, 607, 613, 617, 619, 631, 641, 643,
647, 653, 659, 661, 673, 677, 683, 691, 701, 709, 719, 727, 733, 739,
743, 751, 757, 761, 769, 773, 787, 797, 809, 811, 821, 823, 827, 829,
839, 853, 857, 859, 863, 877, 881, 883, 887, 907, 911, 919, 929, 937,
941, 947, 953, 967, 971, 977, 983, 991, 997
3. duration = 0.7624 msec
```

Another faster solution when processing is in progress by C++ code:

```
>rc examples\scr\Erato.scr
```

```
import Erato;  
start;  
call Erato.Solve3(1000);  
stop("duration = ");
```

Result:

```
>rc examples\scr\erato.scr  
code: scr  
Imported [Erato]  
2,3,5,7,11,13,17,19,23,29,31,37,41,43,47,53,59,61,67,71,73,79,83,89,  
97,101,103,107,109,113,127,131,137,139,149,151,157,163,167,173,179,  
181,191,193,197,199,211,223,227,229,233,239,241,251,257,263,269,271,  
277,281,283,293,307,311,313,317,331,337,347,349,353,359,367,373,379,  
383,389,397,401,409,419,421,431,433,439,443,449,457,461,463,467,479,  
487,491,499,503,509,521,523,541,547,557,563,569,571,577,587,593,599,  
601,607,613,617,619,631,641,643,647,653,659,661,673,677,683,691,701,  
709,719,727,733,739,743,751,757,761,769,773,787,797,809,811,821,823,  
827,829,839,853,857,859,863,877,881,883,887,907,911,919,929,937,941,  
947,953,967,971,977,983,991,997  
duration = 0.1103 msec
```

Here C++ code:

```
void Erato::Print(vector<int> v)  
{  
    std::stringstream ss;  
    for (size_t i = 0; i < v.size(); ++i)  
    {  
        ss << v[i];  
        if (i < v.size() - 1)  
            ss << ",";  
    }  
    std::cout << ss.str() << std::endl;  
}  
// the fastest algorithm  
// Processing data without Vector & print results with erasing 0-  
// elements after processing  
bool Erato::FuncSolve3(vector<string> parameters, string& result,  
Composite* node)  
{  
    const std::string function_name = "Erato.Solve3";  
    if (parameters.size() != 1)  
    {  
        cerr << "Error: [" << function_name << "] wrong format" << endl;  
        return false;  
    }  
}
```



```
try
{
    int vector_length = stoi(parameters[0]);
    vector<int> v(vector_length);
    for (int i = 0; i < vector_length; i++) v[i] = i;
    v[1] = 0;
    for (int n = 2; n * n < vector_length; n++)
    {
        if (v[n] != 0)
        {
            // the fastest algorithm
            for (int j = n * n; j < vector_length; j += n)
            {
                v[j] = 0;
            }
        }
    }
    v.erase(remove(v.begin(), v.end(), 0), v.end());
    Print(v);
}
catch (const exception& ex)
{
    cerr << "Error: [" << function_name << "]" ... " << ex.what()
<<endl;
    return false;
}

return true;
}
```

Open console window:

cmd

and run:

Examples.bat

Callfunc.bat

Delegates.bat

Struct.bat

Dataframe.bat

ArrayFunc.bat

MatrixVector.bat

with numerous examples of code.

References

1. Crafting Interpreters by Robert Nystrom
2. Compilers: Principles, Techniques, and Tools (The Dragon Book) by Aho, Lam, Sethi, and Ullman
3. Structure and Interpretation of Computer Programs (SICP) by Harold Abelson and Gerald Jay Sussman
4. Programming Language Pragmatics by Michael L. Scott