

PPL language

Table of Contents

| | |
|------------------------------------|----|
| Introduction..... | 7 |
| Base Concepts | 9 |
| Trees | 11 |
| Comments..... | 15 |
| Configuration | 16 |
| Identifiers and DNS..... | 16 |
| Public and private variables..... | 16 |
| Compound statements (blocks) | 17 |
| Libraries | 17 |
| Keywords | 19 |
| CPPL utility..... | 21 |
| WPPL utility | 23 |
| PPL Assistant | 26 |
| Service Commands | 27 |
| help | 27 |
| version | 27 |
| cls | 28 |
| shell..... | 28 |
| init..... | 28 |
| code | 28 |
| showcode..... | 28 |
| readcode | 28 |
| fdreadcode..... | 30 |
| createpplcode (cpc) | 30 |
| display (d) | 30 |
| displaynodes (dn) | 31 |
| dstree..... | 32 |
| datanames | 33 |
| suspend and resume..... | 33 |
| debugppl..... | 33 |
| traceppl..... | 34 |

| | |
|------------------------|----|
| recreate | 34 |
| log | 34 |
| exit | 34 |
| sumdata | 34 |
| Special Commands | 35 |
| import | 35 |
| importlist | 35 |
| eval..... | 36 |
| length | 36 |
| isexist | 37 |
| isdigits | 37 |
| isinteger | 37 |
| isalldigits | 38 |
| isallinteger | 38 |
| iseven, isodd | 38 |
| del | 39 |
| calc | 39 |
| sleep..... | 40 |
| getbykey | 41 |
| getbyvalue | 41 |
| set | 41 |
| setkvp..... | 44 |
| getvalue | 45 |
| getname..... | 45 |
| gettoken..... | 46 |
| Nodes and Leaves..... | 47 |
| createnode..... | 47 |
| copynode | 47 |
| getnodes | 48 |
| getleaves..... | 50 |
| Structures | 52 |
| definestruct | 52 |
| insertstruct | 53 |

| | |
|---------------------------|----|
| createstruct | 53 |
| Arithmetic operators..... | 55 |
| Logical operators..... | 55 |
| Variables and Arrays..... | 56 |
| var | 56 |
| const | 57 |
| array..... | 58 |
| realloc | 60 |
| array.push..... | 63 |
| array.pop | 64 |
| array.reverse..... | 65 |
| array.shift..... | 65 |
| array.remove | 65 |
| array.clear | 65 |
| array.unshift | 66 |
| array.insert | 66 |
| array.slice..... | 67 |
| array.sum | 67 |
| array.copy | 68 |
| array.min..... | 68 |
| array.max | 68 |
| array.average..... | 68 |
| array.first | 68 |
| array.last | 69 |
| array.concat..... | 69 |
| Storage | 70 |
| storage | 70 |
| sinit | 72 |
| sget | 73 |
| sset..... | 73 |
| swrite | 74 |
| sinfo | 75 |
| ssetrow | 76 |

| | |
|----------------------------------|-----|
| Backup & Recovery..... | 77 |
| savedata..... | 77 |
| readdata..... | 78 |
| Control Flow | 79 |
| if, else..... | 79 |
| switch, case, default | 81 |
| loop,do..... | 83 |
| setlopend..... | 84 |
| for | 85 |
| break..... | 86 |
| continue..... | 87 |
| Input and Output..... | 88 |
| write..... | 88 |
| write#, writeline | 88 |
| writearray | 90 |
| readline..... | 91 |
| Functions | 92 |
| function..... | 96 |
| call..... | 103 |
| return..... | 105 |
| funclist | 105 |
| funcname..... | 106 |
| argc | 106 |
| getargname..... | 106 |
| Delegates and callbacks | 107 |
| delegate | 107 |
| dlgtinstance | 108 |
| dlgtset | 109 |
| dlgtcall..... | 109 |
| callback | 110 |
| Additional functionalities | 111 |
| Math | 112 |
| String..... | 114 |

| | |
|------------------------------|-----|
| Directory | 118 |
| Array | 120 |
| ArrayList..... | 122 |
| Queue | 126 |
| Stack..... | 127 |
| Dictionary..... | 129 |
| Convert | 130 |
| Excel | 132 |
| File..... | 134 |
| Random..... | 135 |
| Console | 137 |
| Vector | 138 |
| Matrix | 139 |
| MN_Numerics..... | 140 |
| DataFrame | 142 |
| Statistics..... | 155 |
| Distributions | 158 |
| Structure of User's DLL..... | 159 |
| Examples of code | 161 |
| References..... | 165 |

Introduction

PPL is the **Parenthesis Programming Language**, in which all elements (statements, parameters, blocks) are enclosed in parentheses. PPL includes a preprocessor to simplify the writing programs and reduce the number of parentheses.

There are some PPL languages (see [References](#)), and this language is not the latest with such abbreviation. The only thing that unites all these languages is the abbreviation.

PPL was developed with Microsoft Developer Studio ,C#, without using any third party packages.

PPL is interpreted language, source code (format scr) is translated into intermediate representation (format ppl) for immediately execution.

The main PPL feature – extensibility, using functionalities of C# and adding user's libraries by means of creating DLLs in accordance with [template](#), described in this tutorial.

PPL supports 2 modes:

ppl (base) mode, which syntax is similar to language LISP, math and logical expressions in prefix notation (**ppl expression**).

Examples:

```
var (x [0]);  
set(x) (+ (1) (2));  
if(==(x) (1)) ...
```

scr (preprocessor) mode, which syntax is similar to language C, math and logical expressions in infix notation (**scr expression**).

Examples:

```
var x = 0;  
set x = 1 + 2;  
if (x == 1)...
```

Commands in format scr may be used on the left side of the expression [\(example\)](#).

PPL includes 2 levels of parsing - code written in scr mode is translated to ppl mode before executing, parser on each level creates syntax tree.

CPPL and WPPL utilities call PPL API functions, PPL API may be used in other user applications.

Mode scr or ppl is set depending on file extension is being executed or by means of the command code, mode scr makes coding easier as it does not require statements to be enclosed in parentheses. Default mode is set in **Configutation.Data**:

| | |
|-------|--------|
| (Code | [ppl]) |
|-------|--------|

Preprocessor includes the following statements –

var, const, array, realloc, storage, set, setkvp,
write#, writearray,call,
createstruct, insertstruct,
delegate, dlgtistant,dlgset,dlgtcall,callback,
setloopend,savedata,readdata

and following compound statements (blocks) –

definestruct, function, for, if, else, switch, case, default.

All ppl mode statements may be also added to scr code in format ppl if these statements do not have scr mode.

Data are saved as Unicode symbols, digital data will be converted into a string.

Examples:

```
set x = 5.2; saved as "5.2"
```

Boolean values are saved as strings - "**True**" and "**False**":

```
set x = True;
```

Execution of the program in the language PPL is carried out by means of the utilities cppl.exe or wppl.exe, which control commands are listed in section [Keywords](#).

There are different statement formats for ppl mode and scr mode if a statement belongs to two modes.

Base Concepts

As is customary in many programming language guides the first ppl program is:


```
write("Hello World!");  
without main function.
```

Another example with using Console and String libraries:

File examples\console\colors.scr:

```
var text = "Hello World!";  
array colors[] = {Green,Red,Yellow,Cyan,Blue,Black,  
                  Magenta,Gray,DarkRed,DarkGray,White,Red};  
  
array ArrayChars;  
call String.ToCharArray(text, getname(ArrayChars));  
  
for(i,0,length(text))  
{  
    // function with 1 argument not need operator call  
    Console.ForegroundColor(colors[i]);  
    Console.Write(ArrayChars[i]);  
};  
Console.DefaultColors();  
write(); // to new line
```

Result:



The screenshot shows a terminal window titled "CPPL". The command prompt shows the execution of the script: `>rc examples\console\colors.scr`. The output is "Hello World!" where each word is printed in a different color (H in green, e in red, l in yellow, o in cyan, W in blue, o in black, r in magenta, l in gray, d in dark red, ! in dark gray). The prompt then returns to `>`.

The following 4 samples illustrate the possibilities of PPL:

```
1.
>rc examples\cowsay\cowsay1.scr
array cow[] =
{
  "  _____",
  "< P P L >",
  "  -----",
  "      \  ^ ^",
  "      \  (oo)\ _____",
  "      \  ( _)\ _____)\ /\",
  "      | |----w |",
  "      | |      | |",
};

Console.Clear();
for(i,0,length(cow))
{
  Console.SetCursorPosition(0)(i);
  Console.Write(cow[i]);
}
Console.SetCursorPosition(0)(length(cow));
```



2. Added loading of second file, function call, creation node and array under this node

```
>rc examples\cowsay\cowsay2.scr
```

3. Added second operator 'for' to move cow

```
>rc examples\cowsay\cowsay3.scr
```


4. Added passing data as arguments when calling command readcode

```
>rc examples\cowsay\cowsay4.scr 1 1 10
```

Trees

All information is stored in PPL as several kinds of Trees –

root, NS, Functions, Configuration and may be displayed on Screen, saved and restored.



Blue nodes are created automatically when Cppl.exe loads or re-created by command **init**.

By default Tree **Functions** is filling from file Functions\ **CommonFunctions.ppl**, defined as "**default_loaded_functions**" in file **Configuration.data**, it may be changed by user on other one, to display its contents perform:

```
>display Functions;
```

User may perform command **readcode (rc)** to read files with user's functions and add these functions to Tree **Functions** or to node, created under Tree **Functions**.

Tree **Functions (or nodes under Tree Functions)** saves only functions, not data (see examples 6-8 in [function](#)).

Examples:

```
>d Functions
-----Functions-----
-N2      Sum      [function]
---L0    result
---L1    n1
---L2    n2
---N1    #        [internal_block]
```

```
-----N2 set
-----L0      result
-----N3      +
-----L0      n1
-----L1      n2
```

Adding functions to node under Tree Functions:

```
>createnode Functions.Calc;
function
(
  Functions.Calc.Sum(result) (n1) (n2)
  (
    (set(result) (+ (n1) (n2)))
  )
);
>d Functions
-----Functions-----
-N2      Calc      [Node]
---N3     Sum      [function]
-----L0 result
-----L1 n1
-----L2 n2
-----N1 #        [internal_block]
-----N2      set
-----L0      result
-----N3      +
-----L0      n1
-----L1      n2
```

Tree **Configuration** is filling from file **Configuration.data**, to display its contents perform:

```
>display Configuration;
(default_loaded_functions [Functions\CommonFunctions.ppl])
  //(UserFunctions1      [])
  //(UserFunctions2      [])
  //(UserFunctions3      [])
  //
  (Code                  [ppl])
  (debugppl              [no])
  (delete_all_in_readcode [yes])
  (log                   [no])
  (stay_interactive      [no])      // for cppl.exe
  (OFD_port              [11000])  // for cppl.exe
  //(UserFunctions1      [Functions\printchar.ppl])
  (UserImport1           [Directory])
  (UserImport2           [Math])
  (UserImport3           [String])
  (UserImport4           [File])
  (UserImport5           [Console])

  //(UserImport6         [Convert])
  //(UserImport7         [ArrayList])
  //(UserImport8         [Excel])
  //(UserImport9         [Queue])
```

```
// (UserImport10      [Stack])  
// (UserImport11      [Dictionary])
```

Any public variables (var, const, array, storage and node) are saved in Tree **Global** as common data for all functions and for code without functions(in "main function").

Public functions are available to functions from any node in Tree **Global**.

Private variables and functions are available to functions in the node, that they belong to only. Full name variables and functions include name of node.

Example:

```
createnode N1;  
function  
(  
    N1.f()  
    (  
        (write("public function N1.f"))  
        (N1._f())  
    )  
);  
  
function  
(  
    N1._f()    // private  
    (  
        (write("private function N1._f"))  
        (write(N2.x))  
        //(write(N2._x))    // Error: [GetValue] [N2._x] private  
                           object, no access  
        //(N2._f())        // Error: [Traversal] [N2._f] private  
                           function, no access  
    )  
);  
  
createnode N2;  
var(N2.x["public var N2.x"]);  
var(N2._x["private var N2._x"]);  
function  
(  
    N2._f()    // private  
    (  
        (write("private function N2._f"))  
    )  
);  
  
N1.f();  
write(N2.x);  
//write(N2._x);    // Error: [GetValue] [N2._x] private object, no  
                   access
```

Variables for functions are created in Tree **Local**, to display its contents perform in function:

>display Local

When exiting a function, its variables are deleted.

For illustration difference between modes scr and ppl consider the following examples:

```
>rc Examples\scr\for.scr
=== scr code for preprocessor ===
var begin = 0;
var end = 3;
for(i,begin + 1,end + 1,1)
{
    write(i);
}
=== generated by preprocessor ppl code ===
>var (begin[0]);
>var (end[3]);
>loop (i) ( + ( begin ) ( 1 ) ) ( + ( end ) ( 1 ) ) ( 1 )
(
    do
    (
        (write(i))
    )
);
Result:
1
2
3
```

Statement terminator ';' always follows after each type of statements in scr mode.

In ppl mode statement terminator ';' does not follow after statements within compound statements(blocks) – loop, switch,if,function.

Examples in ppl mode:

```
loop (i) (0) (3) (1)
(
    do
    (
        (write(hello))
        (write(world))
    )
);
```

Comments

Two kinds of commentaries are possible:

`/*...*/` - for several lines of code

and

`//` - for one line of code or part of line.

Configuration

Configuration is defined in the file **Configuration.data**, meaning of its members is explained in this tutorial.

Identifiers and DNS

Names of nodes, variables, arrays, storage and functions contain any symbols, first symbol is any upper or lower case letter or any of the following symbols: `_` `$` `#`, but not a digit. Variables with first symbol `_` in name are hidden or private variables ([see hidden variables](#)).

Name **"all"** can not be used ([see cmd del](#)).

Length of identifiers is not limited. Do not set keywords and names of Libraries as identifiers.

When data is created, its full name and saved address are added to **Data Names Structure (DNS)**. DNS creates separately for non-functions identifiers in Global and for each function in Local, DNS of function will be destroyed when exiting the function.

Symbolic values are enclosed in quotation marks, to include a quotation mark in a symbolic expression, precede it with backslash.

Example:

```
"123\"qwe" => "123"qwe"
```

Backslash before the last quote mark it is backslash, not quote mark.

```
"123\"qwe\" => "123\"qwe\""
```

Public and private variables

Variables, constants, arrays, storage and functions, whose names start with **underscore** are private, all other are public.

Examples:

```
>createnode N1;
>var(N1.x["public var N1.x"]);
>var(N1._x["private var N1._x"]);
function
(
  N1._f()    // private
  (
    (write("private function N1._f"))
    (write(N1.x))
    (write(N1._x))
  )
);
```

Error occurs when re-creating a variable, it is possible to delete this variable and to create again:

```
>var(x);
>var(x);    // re-creation
Error: [FuncCreateVariables] name [x] already exists
>del x;
>var(x);
```


Compound statements (blocks)

The following blocks **for**, **if**, **else** include one or several statements enclosed in curly brackets:

```
if (x == 1)
{
    write("COMPOUND");
    write("STATEMENTS");
}
else
{
    write("compound");
    write("statements");
}
```

When only one statement (**not compound statement**) is in curly brackets it is possible to omit brackets:

```
if (x == 1)
    write("COMPOUND");
else
    write("statements");
```

```
if (x == 1)                                // right
{
    if (y == 2)
        write("right sample");
}
```

```
if (x == 1)                                // wrong
    if (y == 2)
    {
        write("wrong sample");
    }
```

Libraries

Default name of library is **Main**, it loads always when Cpl.exe or Wppl.exe starts. It is possible to set in file **Configuration.data** as "**UserImportN**" names of additional libraries initialization loaded . To display list of loaded libraries perform:

```
>importlist;
Main
Directory
Math
```

To display contents of any library perform:

<name of library>.help
or **help** for Main library

Example:

```
>Directory.help;
```

```
help
GetFiles
GetDirectories
SetCurrentDirectory
GetCurrentDirectory
```

To get short information about any library function perform:

<name of library>.help(function name)

```
>Math.help(Sinh)
    Returns the hyperbolic sine of the specified angle:
    Math.Sinh(double value)
```

For Main Library help or ?:

```
>? d
    display | d [root|NS| Functions|Local|node name]
    display NS.namespace.name]
```

Keywords

Keyword formats are defined in this tutorial, all format are defined for **ppl mode** by default. Additionally defined format for **scr mode** for some keywords. All keywords are divided into 9 groups and presented below:

Service Commands

help, version, cls, shell, init, code, showcode, readcode, fdreadcode, createpplcode, display, displaynodes, dn, dstree, datanames, suspend, resume, debugppl, traceppl, recreate, log, exit, createcodeppl, sumdata

Special Commands

import, importlist, eval, length, calc, sleep, isexist, isdigits, isinteger, isalldigits, isallinteger, iseven, isodd, del, getbykey, getbyvalue, set, setkvp, getvalue, getname , gettoken

Nodes and Leaves

createnode, copynode, getnodes, getleaves

Structures

defunestruct, insertstruct, createstruct

Variables and Arrays

var, const, array, realloc, array.push, array.pop, array.reverse, array.shift, array.remove, array.clear, array.unshift, array.insert

Storage

storage, sinit, sget, sset, swrite, sinfo, ssetrow

Backup and Recovery

savedata, readdata

Control Flow

if, else, switch, case, default, loop, do, for, break, continue, setloopend.

Input Output

write, writeline (write#), writearray, readline

Functions

function, funclist, funcname, argc, getargname, call, return

Delegates and callbacks

delegate, dlgtinstance, dlgtset, dlgtcall, callback

Special variables, constants and words

empty – see methods `ArrayList.Add`, `Queue.Enqueue`, `Stack.Push`

tab,comma,space – see `String.Split`, `String.Splitcsv`.

If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file. Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Value of argument is literal, not command.

When value of **stay_interactive** in file **Configuration.data** = "no" cppl.exe finishes after program execution, when value of **stay_interactive** = "yes" cppl.exe does not finish and continues in interactive mode.

Example:

File example.scr

```
var $1$ = $2$;  
>cppl.exe example.scr x 2;
```

2.Interactive mode

cppl.exe

Command input from standard input stream.

To get list of commands and their short explanation perform **help** (or ?).

Examples:

```
>? Display;  
      display | d [root|NS|Functions|Local|node name]  
>? d;  
      display | d [root|NS|Functions|Local|node name]
```

Prompt ">" appears on Screen before each command.

Examples:

```
>display;  
-N1      NS  
---N2    Global
```

When code scr is defined only one command is executed interactively:

```
>var x; set x=1;    // wrong  
>var x;            // right  
>set x=1;
```

In addition to commands required to work with scr/ppl programs, cppl.exe allows you to execute all Windows commands and save the results. Command **shell** uses for that.

Examples:

```
>var (x);  
>set(x)(shell(cd));    // output is saved in var x  
>write(x);
```

The following often used commands and operators with one parameter may be used with or without parentheses around arguments:

help (?), **import**, **readcode** (rc), **showcode**, **createnode**, **isexist**, **display** (d), **displaynodes**(dn), **del**, **code**, **debugppl**.

WPPL utility

WPPL.exe is also a PPL interpreter, its functionalities are liked cpp.exe. WPPL.exe is WPF Application, runs in interactive mode only.

The screenshot shows the WPPL application window. The top part is a command prompt where the user has entered the following commands:

```
>showcode;
>version
version 1.0.6
>help
>
```

The bottom part of the window displays a detailed help menu with the following sections:

```
-----Init-----
-N0 root
--N1 NS
----N2Global
----N2Local
code: ppl
debugppl = no
log = no
stay_interactive = no
Imported [Directory]
Imported [Math]
ShowCode=yes

-----Main-----
-----Service Commands-----
help      version  cls      shell      init       code
showcode  readcode  fdreadcode  dstree     display    createppl
datanames suspend  resume      debugppl   log        exit
-----Special Commands-----
import    importlist eval      length     exist       del
getbyname getbyvalue set       getvalue   getname
-----Nodes-----
createnode copynode
-----Variables and Arrays-----
var      const    array    realloc
```


Top part is used as input any PPL commands, down part is for results presentation. Also service commands may be performed by menu and wpf controls over top part. The following dialogs are used to perform service commands:

Clicking on **CreatePPL in Menu** opens the following dialog:

The screenshot shows the CreatePPLDlg dialog box. It contains two text input fields and two buttons:


- SCR filename:** PL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Examples\rc.scr (with a **Browse** button next to it)
- PPL filename:** C:\Users\ok21\MyProjects.Work\C#2\PPL\PPL\PPL\WPPL\bin\ (with a **CreatePPL** button next to it)

Clicking on **ReadCode in Menu** opens the following dialog:



The ReadCodeDlg dialog box has a title bar with a close button (X). It contains two text input fields. The first field is labeled 'Filename:' and contains the text '2\PPL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Examples\rc.scr'. To its right is a 'Browse' button. The second field is labeled 'args:' and is empty. To its right is a 'ReadCode' button.

Clicking on **ReadData in Menu** opens the following dialog:




The ReadDataDlg dialog box has a title bar with minimize, maximize, and close buttons. It contains two text input fields. The first field is labeled 'Filename:' and contains the text '\PPL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Data\Colors.data'. To its right is a 'Browse' button. The second field is labeled 'Node:' and is empty. To its right is a 'ReadData' button.

Clicking on **SaveData in Menu** opens the following dialog:



The SaveDataDlg dialog box has a title bar with a close button (X). It contains two text input fields. The first field is labeled 'Filename:' and contains the text 'Data\'. To its right is a dropdown menu showing '.data'. The second field is labeled 'Node:' and contains the text 'Global'. To its right is a 'SaveData' button.

Clicking on button **display** opens the following dialog:




History of commands is supported by buttons **PgUp** and **Pgdn**.

WPPL.exe is an example of using the PPL API, which can be easily used in the user's application.

PPL Assistant

PPL Assistant displays format commands in ppl and scr modes. As well this application displays format methods in [additional libraries](#).

Files JsonHelp*.json are generated by utility CreateUserLibCode.exe (version 1.0.15).



Service Commands

help

Displays keywords list for Library by <name> or format of command from Main library.

Library must be loaded before (see <import>)

by default name = Main, this library is loaded automatically

Format: **help** | ? [<library name>] | keyword

```

>?
-----Main-----
Service Commands-----
help      version  cls      shell    init     code
showcode  readcode  fdreadcode dstree   display  displaynodes
datanames suspend  resume   debugppl traceppl  recreate
log       exit     createppcode

Special Commands-----
import    importlist eval      length   del
isexist   isdigits  isinteger calc      sleep
isalldigits isallinteger iseven   isodd
getbykey  getbyvalue set       getvalue  getname

Nodes and Leaves-----
createnode copynode  getnodes  getleaves

Variables and Arrays-----
var      const    array    realloc

Storage-----
storage  sinit    sget     sset
swrite   sinfo    ssetrow

Backup and Recovery-----
savedata readdata

Control Flow-----
if      else     switch   case     default
loop    do       for      break    continue

Input Output-----
write   write#   writeline writearray readline

Functions-----
function call    funclist funcname argc     return

to get short explanation of each command: help command
>

```

Examples:

```

>? Code;
    Sets mode for Console input or displays on Screen
    code ppl | scr
>? "display" // only display in quotes
    display | d [root|NS| Functions|Local|node name]
    display [NS.namespace.name]

```

Any other library has function help for display its contents.

<name of library>.help [(keyword)]

>Matrix.help (Rotate)

version

Display current version

Format: **version**

cls

Clears the Screen

Format: **cls**

shell

Executes Windows Console Commands, several commands are hash symbol separated.

Results of shell are saved and can be displayed by commands **write** or by **debugppl yes**

Format: **shell (command with parameters[#command with parameters])**

Examples:

```
>write(shell (cd:\));  
>debugppl yes;  
>shell (dir /b tests#cd);
```

init

Deletes all data and functions and creates new root, use this command for console input only.

Format: **init**

code

Sets mode for Console input or displays it on Screen.

Mode scr is more convenient for writing code with blocks and for using infix expressions. But in other cases there is no difference.

Format: **code [ppl|scr]**

default - ppl

It is possible to set **code** in file **Configuration.data**.

showcode

Shows or hides on Screen ppl_code when command readcode is executed or displays

showcode value on Screen

Format: **showcode [yes|no]**

Default: no

Examples:

```
>showcode no;
```

readcode

Reads file with code in format scr or ppl.

At the end of the execution readcode the previous code will be set.

Format: **readcode | rc <file.scr|ppl> [arg1 arg2 ...]**

If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file.

Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Arguments are literals, not commands.

If **delete_all_in_readcode = yes** in **Configuration.data** command

delete all is added automatically as first command when first command **readcode** is called.

The file being called can also include readcode commands. Files called by command **readcode** can be of different formats - .scr or .ppl.

If caller script and internal scripts are in the same path you can omit path for internals.

You can specify relative path from cppl.exe or full path, including drive:

```
>rc path\caller.scr
call internal script:
    rc internal.scr
or    rc path\internal.scr or rc drive:\path\internal.scr
```

Example

```
1.
>Directory.SetCurrentDirectory(examples\ppl);
>rc loop.ppl; // or rc examples\ppl\loop.ppl
loop (i) (0) (3) (1)
(
    do
    (
        (write("PPL"))
        (write("ppl"))
    )
);
```

```
2. File example.scr
var $1$ = $2$;
>rc example.scr x 2;
```

3. reading script with command **readcode** inside:

```
File main.scr:
    write("main script");
    rc examples\rc\first.scr;
    rc examples\rc\second.scr;
    write("return from main script");
```

```
File first.scr:
    write("first script");
    rc examples\rc\third.scr;
    write("return from first script");
```

```
File second.scr:
    write("second script");
```

```
File third.scr
    write("third script");
```

```
>rc examples\rc\main.scr;
```

Result:

```
main script
first script
third script
return from first script
second script
return from main script
```

fdreadcode

Like readcode with using OpenFileDialog to select file. This command loads ofd.exe and sets connection with **cppl.exe** via UDP protocol, port defined in file **Configuration.data** as **OFD_port**.

Format: **fdreadcode|fdrc**

createpplcode (cpc)

Creates file in format ppl from file (or files) in format scr.

Format **ppl**: **createpplcode|cpc (file.scr)(file.ppl) [(all)]**

Format **scr**: **createpplcode|cpc file.scr file.ppl [all]**

arg **all** – include all files, loaded by command **readcode**.

Examples

```
> code ppl;
>createpplcode (ttt.scr) (ttt.ppl);
>cpc (ttt.scr) (ttt.ppl);

>code scr;
>cpc ttt.scr ttt.ppl;
```

display (d)

Displays nodes(N) and leaves(L) in Tree, alias – d.

Format:

display | d [root | Global | Functions | Configuration| Local | path_node.name]

Increase Screen Buffer Size.Height in CPPL.exe Properties\Layout in case large number of lines.

default: Global

Examples:

```
>array(y[2])(0);
>d;
-N NS
---N Global
-----N y
-----L0 [0]
-----L1 [0]
>d Global.y;
>d y;
>d Functions.Sum;
```

displaynodes (dn)

Displays nodes(N) only, alias – dn.

Format:

**displaynodes | dn [root | Global | Functions | Configuration | Local |
path_node.name]**

**Increase Screen Buffer Size.Height in CPPL.exe Properties\Layout in case large
number of lines.**

Example:

```
>dn Functions
-----Functions-----
-N3      Sum      [function]
---N1    #        [internal_block]
-----N2 set
-----N3      +
-N3      Sub      [function]
---N1    #        [internal_block]
-----N2 set
-----N3      -
.....
```

dstree

Displays function syntax tree with nodes(N) and leaves(L) of code.

dstree displays all function tree within function.

Format: **dstree()** | **dstree**

Examples:

```
>rc examples\scr\func7.scr
```

```
function func(n,m)
{
    write#("{0} {1}", n , m);
    dstree;
}
func(aaa) (111) ;
```

Result:

```
aaa 111
-----Syntax Tree-----
-N3      func      [function]
---L0     n
---L1     m
---N4     #         [internal_block]
-----N5 write
-----L0         "{0} {1}"
-----L1         n
-----L2         m
-----N5 dstree
-----L0
```


datanames

Displays contents of [DNS](#).

Format: **datanames [Local]**

Examples:

```
>var(x);
>createnode Node1;
>array(Node1.arr[5]);
>var(Node1.y);
>datanames;
-----Global_dns-----
node          name          type
-----
              empty        const
              x
Node1          arr          array
Node1          y           var

>datanames Local;    // for using in functions
```

suspend and resume

Stops script to perform manually one or several commands,

continue script execution – **resume**

stop script – **exit** and double click

Format: **suspend**

Examples:

```
>Enter:
>d
-N1      NS
---N1    Global
>resume // continue script execution
```

debugppl

Displays information about creation and deletion variables, results operations and duration or displays debugppl value on Screen.

Format: **debugppl [yes|no]**

It is possible to set **debugppl** in file **Configuration.data**.

Example:

```
>var(x)
>debugppl yes
>duration = 0.0015026
>del x
leaf [x] is deleted
>duration = 0.0054401
```

traceppl

Displays all commands and function names on screen during the execution of commands. By default – traceppl no.

Format: **traceppl [yes|no]**

Example:

```
>traceppl yes;
```

recreate

Permits recreation vars, arrays, storage and nodes. By default – recreate no.

Format: **recreate [yes|no]**

Example:

```
>recreate yes;  
>code scr;  
code: scr  
>var x;  
>var x;  
>recreate no;  
>var x;  
Error: [FuncCreateVariables] name [x] already exists
```

log

Writes commands and results to logfile in directory **Log** or displays log value on Screen.

Format: **log [yes|no]**

It is possible to set **log** in file **Configuration.data**.

Opened logfile will be closed by command init or exit.

exit

Exit from Cpp.exe (**exit**) or exit from script (**exit()**).

sumdata

Defines argument type for summation. By default – **sumdata digit**.

Format:

sumdata [digit | string]

Example:

```
>code scr;  
>sumdata digit;  
>write#(1+2);  
3  
>sumdata string;  
>write#(1+2);  
12
```

```
>sumdata string;  
>var x = 1;  
>call Sum(x,2);  
>write#("x={0}",x);  
x=12
```

Special Commands

import

Loads Library from current directory or from user directory.

Format:

import <Library name>

import <Directory\><Library name>

Examples:

```
>import Math;  
>import DLL\Erato;    // (see examples\scr\erato.scr)
```

importlist

Displays list of loaded Libraries

Format: **importlist**

Examples:

```
>importlist;  
Main  
Math
```

eval

Performs string in format ppl.

Format: **eval** <ppl expression>[<result>]

result:=var_name to save result

Examples

```
Ex. 1
> var (sum) ;
>var(x["+ (2) (3) "]) ;
>d;
-N1      NS
---N2    Global
-----L0 sum
-----L1 x      ["+ (2) (3) "]
---N2    Local
>eval(x) (sum)
>d
-N1      NS
---N2    Global
-----L0 sum      [5]
-----L1 x      ["+ (2) (3) "]
---N2    Local

Ex. 2
array y[] = {"+ (3) (5) ", "+ (4) (6) "};
for(j,0,length(y))
{
    eval(y[j]);
};

Ex. 3
var(x) ;
eval("+ (1) (2) ") (x) ;
write("{0} = {1}") (getname(x)) (getvalue()) ;
x = 3
```

length

Returns length of value for var | const or length array | storage

Format: **length** (var | const name | array name|storage name)

Examples:

```
>array (y[3]);  
>length(y);  
Result: 3  
>var (x["Hello!"]);  
>length(x);  
Result: 6
```

isexist

Determines whether var, array or storage with specified name exists or not in Global or Local, returns **"True"** or **"False"**.

Format: **isexist(name)**

name:= [NS.][namespace.][node.]name

Example:

```
1.  
>debugpp1 yes  
>var (x);  
>isexist (x);  
Result: True  
2.  
>createnode Functions.New;  
>isexist (Functions.New);  
Result: True
```

isdigits

Checks is value of var or member of array or storage digital, returns **"True"** or **"False"**.

Format: **isdigits(var name | member of array or storage | literal)**

Example:

```
>var(x[1.1]);  
>isdigits (x);  
Result: True
```

isinteger

Checks is value of var or member of array or storage integer, returns, returns **"True"** or **"False"**.

Format: **isinteger(var name | member of array or storage | literal)**

Example:

```
>var(x[1]);  
>isinteger (x);  
Result: True
```

isalldigits

Checks if all members of array or storage are digital, returns **"True"** or **"False"**.

Format: **isalldigits(member of array or storage)**

Example:

```
>code scr;  
>array x[] = {1,2,3};  
>isalldigits (x);  
Result: True
```

isallinteger

Checks if all members of array or storage are integer, returns **"True"** or **"False"**.

Format: **isallinteger(member of array or storage)**

Example:

```
> array(x) (1) (2) (3) ;  
>isallinteger (x);  
Result: True
```

iseven, isodd

Checks if integer value is even or odd, returns **"True"** or **"False"**.

Format:

iseven(var name | member of array or storage | literal)

isodd(var name | member of array or storage | literal)

del

Deletes any kinds of data from Global or Local Tree, also deletes nodes from Functions.

Format: **del (fullname) | del fullname**

To delete all Global contents: **del all**, so name “all” can not be used as any kind of variable names.

If “**delete_all_in_readcode**” = **yes** in **Configuration.data** command

delete all adds automatically as first command when command **readcode** is called. Otherwise all data will be saved in memory, if necessary add this command manually.

fullname:= node path.name

node path:= node path | node

Example:

```
>createnode Node1;
>var (Node1.x);
>del Node1.x;

>createnode Functions.Geo
>del Functions.Geo
```

For re-run script, that creates array or use command **recreate yes**:

```
>if(==(isexist(y)) (True))
(
    (del y)
);
>array(y[5]);
```

calc

Calculates infix notation math. expression and writes result on screen, may be used for ppl and scr modes, **but in interactive mode only**, not in .ppl or .scr files.

Limitation: do not use expression for calculation indexes to array elements.

Format: **calc math.expression**

Example:

```
>code ppl;
>var (x[1]);
>calc x + 2*Math.PI();
7.283185307179586
```

```
>code scr;
>array arr[] = {1,2,3};
>var x = 1;
>calc 1+ arr[0];
>calc 1+ arr[1+1];    // error: calculation indexes
> var y = 1+1;
>calc 1 + arr[y];    // right
```

```
>calc Math.Sqrt(1+3) + 1;
```

sleep

Suspends the interpreter for the specified number of milliseconds

Format: **sleep(msec)**

Example:

```
>sleep(100) ;
```


getbykey

Gets value from array by name.

Format: **getbykey(name array)(name element)**

Example:

```
See example in readdata  
>getbykey(Colors) (Black) ;  
Result: 0
```

if key is absent return **nan**.

getbyvalue

Gets name from array by value.

Format: **getbyvalue(name array)(value element)**

Example:

```
See example in readdata  
>getbyvalue(Colors) (0) ;  
Result: Black
```

if value is absent return **nan**.

set

Sets value for variable and array element

Format **ppl**:

set (var_name | array_name [index]) (value | array_name [index])

index:=value | ppl expression

Format **scr**:

set var_name | array_name [index] = value | scr expression

index:=value | scr expression

Command **set** checks whether index is out of bounds.

Examples:

>code ppl:

```
>var (x) ;  
>set(x) (+ (1) (2)) ;  
>array(y[3]) ;  
>set(y[+ (1) (2)]) (0) ;
```

>code scr:

```
>var x;  
>set x = 1;  
>array y[3];  
>set y[x + 1] = 2 + 3;  
>set y[0] = y[1];
```

```
>code scr:
>var x;
>set x = d;      // error, command "d" is running
>set x = "d";
>eval(x);        // this statement runs command "d"
```

To calculate indexes for access to array elements command set in scr-mode creates temporary variables and deletes them at the end (**for non-interactive mode only**):
file test.scr

```
array a[] = {1,2,3,4,5,6,7};
set a[1+2] = a[2+2]+ 1;
```

>rc test.scr

The following ppl-code will be generated:

```
array (a) (1) (2) (3) (4) (5) (6) (7) ;
var (#0[ + (1) (2) ]);
var (#1[ + (2) (2) ]);
set (a[#0]) (+ (a[#1]) (1));
del #0;
del #1;
```

It is possible to use logical and comparison operands:

```
>code scr;
>var x;
>set x = ((1==1) && (2==2)) && (3==3);
>write(x);
Result: True
```

```
>code scr
array x[3] = 0;
set x[1+1] = ((1==1) && (2==2)) && (3==3);
writearray x row;
```

The following ppl-code will be generated:

```
>array(x[3]) (0) ;
>var (#0[ + (1) (1) ]);
>set (x[#0]) ( && ( && ( == (1) (1) ) ( == (2) (2) ) ( ==
(3) (3) ) ) );
>del #0;
>writearray (x ) ( row );
```

See examples\if\QuestionMark.scr: **(for non-interactive mode only)**

```
var x;  
set x = 1==1? t:f;  
write(x);
```

The following ppl-code will be generated:

```
var (x);  
if (== (1) (1) )  
(  
  (set (x) (t))  
);  
(  
  else  
  (  
    (set (x) (f))  
  )  
);  
write(x);
```

To set data in structure see ([sample](#)).

setkvp

Sets key and value array element

Format **ppl**:

setkvp(array_name [index])(key)(value | ppl expression)

index:=value | ppl expression

Format **scr**:

setkvp(array_name [index]) = key, value | scr expression)

index:=value | scr expression

Command **setkvp** checks whether index is out of bounds. For setting key and value command **setkvp** checks whether key already exists in array.

To calculate indexes for access to array elements command setkvp in scr-mode creates temporary variables and deletes them at the end (**for non-interactive mode only**):

To get key and value it is possible by commands **getbykey** and **getbyvalue**.

>code ppl:

```
>array(y[3]);  
>setkvp(y[0])(+(1)(2));  
>setkvp(y[1])(one)(1);  
>setkvp(y[2])(two)(2);
```

code scr:

```
var x = 1;  
array y[3];  
setkvp y[x + 1] = five, 2 + 3;    //(for non-interactive mode only)  
setkvp y[0] = null, 0;
```

getvalue

Returns value of single var|const or array element.

Error: when argument is literal or not existed variable.

Format: **getvalue (var_name) | getvalue(array_name[index]**

index:= value|ppl expression

Alias: get

Examples:

```
>array (y[3]) (999);  
>write("getvalue(y[0]) = {0}") (getvalue (y[0]));  
Result: getvalue (y[0]) = 999
```

To get data from structure see ([sample](#)).

getname

Returns name of single var|const | array | array element as string.

Error: when argument is literal or not existed variable.

Format: **getname (name)**

Examples:

1.

```
>var (x[ppl]);  
>write("{0} = {1}") (getname(x)) (getvalue(x));  
x = ppl
```

2.

```
function f(array: arr)  
{  
  write#("argname={0}  name={1}", getargname(arr), getname(arr));  
}  
array y;  
f(y);  
Result: argname=y  name=arr
```

```
function f2(storage: stor)  
{  
  write#("argname={0}  name={1}", getargname(stor), getname(stor));  
}  
storage s[2];  
f2(s);  
Result: argname=s  name=stor
```

gettoken

Returns token in accordance with its number in string, string contains tokens, separated by "separator". Parts of string arounded by quotes are passed.

As well gettoken may return number of tokens.

If number \geq max number of tokens cmd returns "Exception".

Format: **gettoken (string)(separator)(number)**

return: **item_value**

gettoken (string)(separator)

return: **number of tokens**

Example:

```
1.
>code ppl;
>debugppl yes;
>gettoken("Hello,World") (",") (0) ;
result = Hello
>gettoken("Hello,World") (",") (1) ;
result = World
>gettoken("Hello,World") (",") (2) ;
Result = Exception
```

```
2.
>code scr;
>var x = "\"Hello,World\"", PPL";
>debugppl yes
>gettoken(x) (",") (0) ;
result = Hello,World
>gettoken(x) (",") (1) ;
result = PPL
3.
>code ppl;
>gettoken("\"Hello,World\",PPL") (",") (1) ;
result = PPL
4.
>gettoken("Hello,World") (",") ;
result = 2
```

Nodes and Leaves

createnode

Creates node in path, default path is "**Global**", it is possible to create nodes in Global, Local and Functions Trees. It will be error if name already exists (see [recreate](#)).

Format: **createnode(path.name) | createnode path.name**

Examples:

```
> createnode (Node)
> createnode Node.SubNode
>d
-N1      NS
---N1    Global
-----N2 Node
-----N3      SubNode

>createnode Functions.Geo
```

copynode

Copies one or more times node from path with new name, by default path is "Global"

Format:

copynode (src node)(dst node)[number of copies]

default number of copies: 1

Examples:

```
>cope ppl;
>createnode Person;
>var(Person.Name);
>var(Person.Family);
>var(Person.DOB);
>var(Person.Gender);
>array(Person.cars[3]);
>createnode Team;
>copynode(Person)(Team);
>set(Team.Name)(Oscar);
>set(Team.Family)(Ko);
>set(Team.DOB)(2050);
>set(Team.Gender)(m);
>set(Team.cars[0])(Juke)(Nissan);
>set(Team.cars[1])(Qashqai)(Nissan);
>d
-N1      NS
---N2    Global
-----N3 Person  [Node]
-----L0      Name
```

```

-----L1      Family
-----L2      DOB
-----L3      Gender
-----N4      cars      [Array 3]
-----L0      #
-----L1      #
-----L2      #
-----N3 Team  [Person]
-----L0      Name      [Oscar]
-----L1      Family    [Ko]
-----L2      DOB       [2050]
-----L3      Gender    [m]
-----N1      cars      [Array 3]
-----L0      Juke       [Nissan]
-----L1      Qashqai    [Nissan]
-----L2      #
---N2      Local

```

getnodes

Creates ppl_array with fullnames of nodes till defined nesting. Processing results of commands getnodes and getleaves allows to find required information in hierarchical data dstructure.

Format:

getnodes (top node)[(nesting)]("ppl_array")

Number of required nesting it is possible to get by command displaynode.

If (nesting) do not set node names under top_node will be saved in ppl_array.

For example there is file Data\Mng2.data

```

(Staff
  (Marketing
    (Managers
      (Personal Data1 [base]
        (Name [Benjamin])
        (Salary [6000])
        (Hobby
          (sport [tennis])
          (music [jazz])
        )
      )
    )
  )
  (Clerks
    (Personal Data2 [base]
      (Name [Oliver])
      (Salary [4000])
    )
  )
  .....
)

```

Read it:

```

>readdata (data\Mng2.data) ;
>d

```



```

-N2      NS
---N3    Global
-----N4 Staff
-----N5      Marketing
-----N6      Managers
-----N7      Personal Data1  [base]
-----L0      Name      [Benjamin]
-----L1      Salary    [6000]
-----N8      Hobby
-----L0      sport      [tennis]
-----L1      music      [jazz]
-----N6      Clerks
-----N7      Personal Data2  [base]
-----L0      Name      [Oliver]
-----L1      Salary    [4000]

```

or

```

>dn Staff
-----Variables and arrays-----
-N4      Staff
---N5    Marketing
-----N6 Managers
-----N7      Personal Data1  [base]
-----N8      Hobby
-----N6 Clerks
-----N7      Personal Data2  [base]
-----N7      Personal Data3  [base]
-----N8      Hobby
-----N7      Personal Data4  [base]
-----N7      Personal Data5  [base]
-----N8      Hobby

```

Get fullnames of nodes till nesting 7 and save in ppl_array "persons":

```

>getnodes(Staff) (7) ("persons") ;
>d persons
-----Variables and arrays-----
-N4      persons [Array 21]
---L0    #      [Staff.Marketing.Managers.Personal Data1]
---L1    #      [Staff.Marketing.Clerks.Personal Data2]
---L2    #      [Staff.Marketing.Clerks.Personal Data3]
---L3    #      [Staff.Marketing.Clerks.Personal Data4]
---L4    #      [Staff.Marketing.Clerks.Personal Data5]
---L5    #      [Staff.Finance.Managers.Personal Data6]
---L6    #      [Staff.Finance.Managers.Personal Data7]
---L7    #      [Staff.Finance.Managers.Personal Data8]
---L8    #      [Staff.Finance.Clerks.Personal Data9]
---L9    #      [Staff.Finance.Clerks.Personal Data10]
---L10   #      [Staff.Finance.Clerks.Personal Data11]
---L11   #      [Staff.Operations management.Managers.Personal
                  Data12]
---L12   #      [Staff.Operations management.Managers.Personal
                  Data13]
---L13   #      [Staff.Operations management.Clerks.Personal Data14]

```

```
---L14 # [Staff.Operations management.Clerks.Personal Data15]
---L15 # [Staff.Operations management.Clerks.Personal Data16]
---L16 # [Staff.Operations management.Clerks.Personal Data17]
---L17 # [Staff.Operations management.Clerks.Personal Data18]
---L18 # [Staff.Operations management.Clerks.Personal Data19]
---L19 # [Staff.Human Resource.Managers.Personal Data20]
---L20 # [Staff.Human Resource.Clerks.Personal Data21]
```

getleaves

Creates ppl_array whose elements have names and values of node:

Format:

`getleaves(node)("ppl_array")`

Example:

See previous example with command `getnodes`

```
>getleaves(Staff.Marketing.Managers.Personal Data1) ("property")
>d property
-----Variables and arrays-----
-N4      property      [Array 2]
---L0    "Name"        [Benjamin]
---L1    "Salary"      [6000]
```

Full code of file Data\mng2.scr to find persons with salary = 2000:

```
var tmp;
var salary;
var name;
readdata (data\Mng2.data);
getnodes(Staff) (7) ("persons");
for(i,0,length(persons))
{
  if (isexist(property) == True)
  {
    del property;
  }
  getleaves(persons[i]) ("property");
  for(j,0,length(property))
  {
    set tmp = getname(property[j].name);
    if (tmp == "Name")
    {
      set name = property[j].value;
    }
    if (tmp == "Salary")
    {
      set salary = property[j].value;
      if (salary == 2000)
      {
        write("Name = {0,-15}\tSalary = {1}") (name) (salary);
      }
    }
  }
}
```

```
}
```

```
>rc data\mng2.scr
```

```
Result:
```

```
Name = Charlotte      Salary = 2000
```

```
Name = Olivia         Salary = 2000
```

```
Name = Felix          Salary = 2000
```

```
Name = James           Salary = 2000
```

```
Name = Sophia          Salary = 2000
```

Structures

Preprocessor generates additional ppl-code for commands **definestruct**, **insertstruct** and **createststruct** so they used for non-interactive mode only (in scripts).

definestruct

Creates named block statement, that contains one or several objects - vars, arrays, storages and insertstructs.

Format **scr**:

definestruct name

```
{  
  array ...;  
  var ...;  
  storage...;  
  insertstruct ...;  
  ...  
}
```

Example:

```
definestruct Room  
{  
  array computers[3];  
  array tables[3];  
}
```

Generated code in ppl-mode

```
definestruct  
(Room  
  (  
    (array (computers[3]) )  
    (array (tables[3]) )  
  )  
);
```

insertstruct

Inserts defined structure, previously defined by `definestruct`. It is possible to insert several instances.

Format **scr**:

insertstruct object_name [[size]] as struct_name

Example:

```
insertstruct rooms[2] as Room;
```

Generated ppl_code:

```
(createnode (rooms) )
(copynode (rooms) (Room) (2) )
```

createstruct

Creates one or several instances in accordance with structure, previously defined by `definestruct`.

Format **scr**:

createstruct name[[size]] as struct_name;

Example: create struct array

```
createstruct Group[2] as Person;
```

Generated ppl_code:

```
createstruct (Group) (Person) (2) ;
```

See examples\struct\teststr4.scr

Tree of above-created object:

```
>displaynodes;
```

Result:

```
-N4      Group          [Person]
---N5    0              [Node]
-----N6 rooms        [Rooms]
-----N7              0
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
-----N7              1
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
---N5     1              [Node]
-----N6 rooms        [Rooms]
-----N7              0
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
-----N7              1
-----N8      computers [Array 3]
-----N8      tables   [Array 3]
```

To set data for structure members it is possible by this manner (see examples above):

```
set Group.0.Name = Oscar;
set Group.0.Family = Kogosov;
set Group.0.rooms.0.computers[0] = "HPE Cray EX";
set Group.0.rooms.1.computers[0] = "Asus";
set Group.0.rooms.1.computers[1] = "Sony";
set Group.0.rooms.1.computers[2] = "HP";
set Group.0.rooms.1.tables[0] = "IKEA 70x140";
set Group.0.rooms.1.tables[1] = "IKEA 70x160";
set Group.0.rooms.1.tables[2] = "IKEA 70x200";

set Group.1.Name = John;
set Group.1.Family = Deere;
```

or:

```
var y,x = 0;
set Group.y.Name = Oscar;
set Group.y.Family = Kogosov;
set Group.y.rooms.x.computers[0] = "HPE Cray EX";
```

To get data from structure, using variable:

```
definestruct Person
{
    var Name;
}
createstruct Group[2] as Person;
// index as var
var y = 0;
set Group.y.Name = "John";
//var x = Group.y.Name;      // error
var x = get(Group.y.Name);   // right

write#("x = {0}",x);
//Result: x = John
```

Arithmetic operators

+, -, *, /, ^, %, ++, --

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

Sum, Sub, Mul, Div, Pow

Examples in ppl prefix notation:

```
+ (x) (y)
* (+ (x) (y)) (- (z) (3))
```

Examples in scr infix notation:

```
>code scr;
> var z = x + y;
> var z = (x + y) * (z - 3);
```

Logical operators

<, <=, >, >=, ==, !=, &&, ||, xor

xor only for ppl mode

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

LT, LE, GT, GE, EQ, NE, AND, OR, XOR

Examples in ppl prefix notation:

```
== (x) (y)
&& (== (x) (y)) (== (z) (3))
```

Examples in scr infix notation:

```
x == y
(x == y) && (z == 3)
```

Variables and Arrays

var

Creates a single variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

var (name) | (name[init value])

name:= [node path]name

node path:= node. | node

init value:= value | ppl expression

ppl expression:=value | prefix notation expression

Examples:

```
>var (greeting["Hello"]);
>var (x);
>code ppl;
>array(z) (1) (2) (3);
>var (x[z[0]]);           or
>var (x[get(z[0])]);
>var (x[get(y[get([y0])])]); // error: var (x[y[y0]]);
```

Format **scr**:

To calculate indexes for access to array elements command **var** in scr-mode creates temporary variables and deletes them at the end:

var name

var name1,name2,name3...

var name | name = init value

var name1,name2,name3... = init_value

name:= node path.name

node path:= node. | node

init value:= value | scr expression

scr expression:= value | infix notation expression

Examples:

```
>code scr;
>createnode N1;
>createnode N1.N2;
>var greeting = "Hello";
>var x;
>var N1.N2.z = 2 + 3;
>var x = z[0];
>var x = get(y[get(y[0])]);
>array arr[] = {1,2,3};
>var y = arr[0] + arr[1];
>var a,b,c = 0;
```



```
>var OneRadian = 180/Math.PI();  
>var x = Math.Sin(30/OneRadian);  
Do not use Math.Function in Math.Function:  
>var x = Math.Sin(30/(180/Math.PI())) // error
```

const

Creates a single constant variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

const (name[init value])

name:= [node.]name

init value:= value | ppl expression

ppl expression:=value | prefix notation expression

Example:

```
>const (x[0])  
>const (y[+(2) (3)]);
```

Format **scr**:

To calculate indexes for access to array elements command **const** in scr-mode creates temporary variables and deletes them at the end (**for non-interactive mode only**):

const name = init value

const name1,name2,name3... = init value

name:= node path.name

node path:= node. | node

init value:= value | scr expression

scr expression:= value | infix notation expression

Examples:

```
>createnode N1;  
>code scr;  
>const greeting = "Hello";  
>const radian = 180 / Math.PI();  
Result: 57.29577951308232
```

array

Creates single-dimensional array in Global or in Local function scope. It will be error if array with same name already exists (see [recreate](#)).

Format **ppl**:

array(name [length]) [(init value)]

array(name)(1st item)(2nd item)...

name:= node path.name

node path:= node. | node

length:= value | ppl expression

init value:= value | ppl expression

item:= value | ppl expression

ppl expression:=value | prefix notation expression

Examples:

```
>var (x[10]);
>array (y[3]);
>array (y[/(x) (2)]) (0);           // init by 0 all 5 elements
>array (y[x]) (* (x) (3));          // init by 30 all 10 elements
>array (y) (1) (x) (+ (1) (2));     // init 3 elements array = 1,10,3
```

Format **scr**:

array name[length];

array name [length] = init value;

array name [] = {1st item, 2nd item,...};

name:= node path.name

node path:= node. | node

length:= value | scr expression

init value:= value | scr expression

item:= value | scr expression

scr expression:=value | infix notation expression

Examples:

```
>code scr;
>array y[3];
>array y[1+2] = 0;           // init by 0 all 3 elements
>array y[] = {1,2,1+2};     // init 3 elements array = 1,2,3
>var x = 1;
>array y[x+2];
```

To access an array element you need to calculate index as a separate variable:

```
>code scr;
>var x = 1;
>array y[] = {1,2,3,4,5};
var index = x + 1;
>write(y[index]);           // or write(y[2])
Only operator set can use index as expression
>set y[x + 1] = 100;
```

Creation array with **length = 0**:

```
array arr; or  
array arr[]; or  
array arr[0];
```

In the following sample array with **length = 0** is created preliminary and reallocated in function **Directory.GetDirectories** in accordance with real length:

```
> array Dir.dir; // or array Dir.dir [0];  
> call Directory.GetDirectories(getname(Dir.dir), "c:\\users\\");
```

realloc

Changes length of array, all elements are saved in changed array.

Format **ppl**:

```
realloc(array name)(new length)
realloc(array name)(new length) (init_value)
```

Format **scr**:

```
realloc array name[new length]
realloc array name[new length] = init_value
realloc(array name)(new length) [(init_value)] (old format, format ppl)
```

Examples:

```
>code scr;
>array y[5] = 0;
>realloc y[10];
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 10]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
-----L3      #      [0]
-----L4      #      [0]
-----L5      #
-----L6      #
-----L7      #
-----L8      #
-----L9      #
---N2     Local
>realloc y[3];
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 3]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
---N2     Local
```

If `init_value` is specified this value will be set in all elements of the new array. If `init_value` is not specified old values are saved in the new array. Size of the new array can be smaller or larger than the old one.

It is possible to use realloc for storage on Row level.

Example 1

```
storage s[3,4,5];
realloc s.0.0.Row[3]; // or realloc(s.0.0.Row)(3);
ssetrow s[0,0] = {1,2,3};
sinit s = 0;

realloc s.0.1.Row[10];
ssetrow s[0,1] = {1,2,3,4,5,6,7,8,9,10};

realloc s.0.2.Row[15];
ssetrow s[0,2] = {1,2,3,4,5,6,7,8,9,10,11,12,13,14,15};
realloc s.1.1.Row[10];

ssetrow s[1,1] = {1,2,3,4,5,6,7,8,9,10};

realloc s.2.1.Row[10];
ssetrow s[2,1] = {1,2,3,4,5,6,7,8,9,10};
swrite s;
```

Result:

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14

-----NS.Global.s.0-----

| | | | | | | | | | | | | | | | |
|-----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| [0] | 0 | 0 | 0 | | | | | | | | | | | | |
| [1] | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | | | | | |
| [2] | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| [3] | 0 | 0 | 0 | 0 | 0 | | | | | | | | | | |

-----NS.Global.s.1-----

| | | | | | | | | | | |
|-----|---|---|---|---|---|---|---|---|---|----|
| [0] | 0 | 0 | 0 | 0 | 0 | | | | | |
| [1] | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| [2] | 0 | 0 | 0 | 0 | 0 | | | | | |
| [3] | 0 | 0 | 0 | 0 | 0 | | | | | |

-----NS.Global.s.2-----

| | | | | | | | | | | |
|-----|---|---|---|---|---|---|---|---|---|----|
| [0] | 0 | 0 | 0 | 0 | 0 | | | | | |
| [1] | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| [2] | 0 | 0 | 0 | 0 | 0 | | | | | |
| [3] | 0 | 0 | 0 | 0 | 0 | | | | | |

Example 2

```
>storage s[2,1];
>realloc s.0.Row[3];
>d s;
-----Variables and arrays-----
-N4      s                      [Storage 2 *]
---N5    0                      [Array element]
-----N6 Row                    [Array 3]
-----L1      #
-----L2      #
-----L0      #
---N5     1                      [Array element]
-----N6 Row                    [Array 1]
-----L0      #

>code scr;
>storage s[2,3];
>realloc s.0.Row[0] = 0;

>storage s[2];
>realloc s.Row[3];
>d s;
-----Variables and arrays-----
-N4      s                      [Storage 1 *]
---N5    Row                    [Array 3]
-----L0 #
-----L1 #
-----L2 #
```

The following commands in format **scr** are used without parentheses in simple statement without equal sign.

They are used with parentheses in statements as arguments of other commands or in statements with equal sign on the right side:

push, shift, unshift, remove, insert, slice, concat, clear.

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>array.push y 10;           // simple statement
>write#( array.push (y) (20)); // argument of command write#
7
>writearray y row
1,2,3,4,5,10,20
```

Writing arguments in parentheses implies ppl-mode and prefix notation.

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>array.remove (y) (1+1);           // wrong
>array.remove (y) (+ (1) (1));     // right
```

array.push

Adds a new item to an array as last, returns a new size of array.

Format **ppl**: **array.push (array_name)(item_value) |**

or for key and value array

array.push (array_name)(item_name)(item_value)

Format **scr**: **array.push (array_name, item_value) |**

array.push (array_name, item_name, item_value)

Example:

```
>code scr;
>array y;
>array.push (y,1);
>array.push (y,1 + 2);
>array.push (y,1 + array.min());
>writearray y row;
-----Array y-----
1, 3, 2
>var length = array.push(y) (1 + 2); // error
>var length = array.push(y) (+ (1) (2)); // right
```

array.pop

Returns the latest item value and removes item.

For kvp-array returns item name and item value, separated by comma and removes item.

If array is empty: returns string **"Empty"**.

Format: **array.pop (array_name)**

Examples:

1.

```
>code scr
>array y[] = {1,2,3};
>var result = "";
>set result = array.pop(y);    // result = 3
>writearray y row;
```

Result:

```
-----Array y-----
1, 2
```

2.

```
>code scr
>array y[3];
>setkvp y[0] = one,1;
>setkvp y[1] = two,2;
>setkvp y[2] = three,3;
>var result = "";
>set result = array.pop(y);    // return three,3
>write#("name={0}value={1}",
    gettoken(result)(",") (0),gettoken(result)(",") (1));
name=three value=3
>writearray y row;
```

Result:

```
-----Array y-----
1, 2
```


array.reverse

Reverses items order in array, returns a size of array;

Format **ppl: array.reverse (array_name)**

Format **scr: array.reverse array_name | array.reverse (array_name)**

array.shift

Removes the first item of the array, returns a new size of array.

Format **ppl: array.shift (array_name)**

Format **scr: array.shift array_name | array.shift (array_name)**

Example:

```
>code scr;  
>array y[] = {1,2,3,4,5};  
>array.shift y;  
>writearray y row  
-----Array y-----  
2,3,4,5  
> write#(array.shift(y))  
2  
>writearray y row  
-----Array y-----  
3, 4
```

array.remove

Removes item by index, returns a new size of array.

Format **ppl: array.remove (array_name)(index)**

Format **scr: array.remove array_name index |**

array.remove (array_name, index) |

array.remove (array_name) (index)

array.clear

Removes all items from array, returns 0.

Format **ppl: array.clear (array_name)**

Format **scr: array.clear array_name | array.clear (array_name)**

array.unshift

Adds a new item as first to an array, returns a new size of array.

Format **ppl**: **array.unshift (array_name)(item_value) |**
array.unshift (array_name)(item_name)(item_value)

Format **scr**: **array.unshift (array_name, item_value) |**
array.unshift (array_name, item_name, item_value)

array.insert

Inserts item before item with index, returns a new size of array.

Format **ppl**:
array.insert (array_name)(index)(item_value) |
array.insert (array_name)(index)(item_name)(item_value)

Format **scr**:
array.insert (array_name,index, item_value) |
array.insert (array_name,index, item_name, item_value)

See array commands examples in **examples\ArrayFunc\Samples.scr**.

Additional array service see in file **CommonFunctions.Data**.

array.slice

Forms a slice [of specified length] out of the current array segment starting at the specified index and return new array length or "Error".

Format **ppl**:

array.slice (array_name)(index)| array.slice(array_name)(index)(length)

Format **scr**:

array.slice (array_name, index)|

array.slice (array_name, index, length)

index starts from 0

Example:

```
>code scr;
>array y[] = {1,2,3,4,5};
>writearray y row;
-----Array y-----
1, 2, 3, 4, 5
>array.slice(y, 2);
>writearray y row;
-----Array y-----
3, 4, 5
>array.slice(y, 1, 2);
>writearray y row;
-----Array y-----
4, 5
```

array.sum

Returns the sum of all items in array. In case of error returns string "Error".

Format: **array.sum (array_name)**

Example:

```
>code scr;
>debugppl yes;
>array y[] = {1,2,s,4,5,a};
Info: [CreateArrayFormat1] Global array [y] is created
>array.sum(y);
Error: [FuncArraySum] not digital data array y[2] = s
Error: [FuncArraySum] not digital data array y[5] = a
result = Error;
>recreate yes;
>array y[] = {1,2,3,4,5};
Info: [CreateArrayFormat1] Global array [y] is created
>array.sum(y);
result = 15
```

array.copy

Copies src array to dst array. In case of error returns string "**Error**".

Format ppl : **array.copy (src array)(dst array)**

Format scr : **array.copy src_array dst_array |**
array.copy (src_array, dst_array) |
array.copy (src_array) (dst_array)

Example:

```
>code scr;  
>array src[] = {1,2,3,4,5};  
>array dst;  
>array.copy src dst;  
      // or  
      // array.copy (src, dst);  
      // array.copy (src) (dst);  
>set dst[0] = 10;  
>writearray dst row;  
-----Array dst-----  
10, 2, 3, 4, 5  
>writearray src row;  
-----Array src-----  
1, 2, 3, 4, 5
```

array.min

Returns the minimum value in array. In case of error returns string "**Error**".

Format: **array.min (array name)**

array.max

Returns the maximum value in array. In case of error returns string "**Error**".

Format: **array.max (array name)**

array.average

Returns the mean value in array. In case of error returns string "**Error**".

Format: **array. average (array name)**

array.first

Returns value of the first item in array. In case of error returns string "**Error**".

Format: **array.first (array name)**

array.last

Returns value of the last item in array. In case of error returns string "**Error**".

Format: **array.last (array name)**

array.concat

Concatenates several arrays to destination array, returns length of destination array or "**Error**" if one of arrays is absent.

Format **ppl**: **array.concat (array1)(array2)(...arrayN) (dst array)**

Format **scr**: **array.concat array1 array2 ...arrayN dst_array |**
array.concat (array1, array2, ...arrayN, dst_array) |
array.concat (array1)(array2)(...arrayN) (dst array)

Example:

1.

```
>code scr
>array y[] = {1,2,3,4,5};
>array a[] = {10,20,30};
>array b[] = {100,200};
>array dst;
>array.concat y a b dst;    // simple statement
    // or
    //>array.concat (y, a, b, dst);
    //>array.concat (y) (a) (b) (dst);
```

```
>writearray y row;
-----Array y-----
1, 2, 3, 4, 5
>writearray dst row;
-----Array dst-----
1, 2, 3, 4, 5, 10, 20, 30, 100, 200
```

2.

```
>code scr;
>array y[] = {1,2,3};
>array b[] = {4,5,6};
>array dst;
>var len = array.concat(y) (b) (dst);    // right side of statement
                                         // with equal sign

>writearray dst row;
-----Array dst-----
1, 2, 3, 4, 5, 6
>write#("length={0}",len);
length = 6
```

See array samples in examples\arrayfunc.

Storage

Service of multi-dimensional arrays is realized by storage operators in mode ppl (parameters with prefix expressions in parentheses, but may be used also in mode scr (see Examples 3).

storage

Creates single variable, single-dimensional or multi-dimensional array with dimension from 1 to N in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Storage contains several levels of arrays, name of the topmost level is name of storage, name of the bottommost arrays in each level is **Row**. Names of intermediate levels are array index in level. To set different length arrays on Row level use realloc. (see examples\scr\testswrite.scr).

Size of the lowest level may be 0.

Format **ppl**:

storage (name)[(length dim1)][(length dim2)]...

name:= node path.name

node path:= node. | node

length:= value | ppl expression

ppl expression:=value | prefix notation expression

Format **scr**:

storage name || storage name [length dim1, length dim2 ...]

Examples:

```
1.
>code scr;
>storage x;      // or in format ppl: storage (x)
>d;
-N1      NS
---N1    Global
-----L0 x
```

```
2.
>code scr;
>storage x[2]; // or in format ppl:
               // storage (x)(2); - single-dimensional array
>d;
-N1      NS
---N1    Global
-----N3 x      [Storage 1 2]
-----N4      Row      [Array 2]
-----L0      #
-----L1      #
[Storage 1 2] - dimension length
```

```
3.
>code ppl
// size calculation for ppl only
>storage (x) (+ (2) (3)) - single -dimensional array [Storage 1 5]
or same result:
```

```
>code scr;
>var y = 2 + 3;
>storage x[y]; // single-dimensional array, length = 5
```

```
4.
>storage x[2,3] - two-dimensional array
>d
```

Result:

```
-N1      NS
---N2    Global
-----N3 x      [Storage 2 2x3]
-----N4        0      [Array element]
-----N5        Row    [Array 3]
-----L0        #
-----L1        #
-----L2        #
-----N4        1      [Array element]
-----N5        Row    [Array 3]
-----L0        #
-----L1        #
-----L2        #
[Storage 2 2x3] - dimension length x length
```

```
5.
>storage x[3,4,5,100] - four-dimensional array
```

```
6.
>storage x[0,2]; //error length=0 may by for the lowest
                  Level only
```

```
>storage x [2,0]; // right
```

sinit

Init storage

Format **ppl**:

sinit (name)(init value)

Format **scr**:

sinit name = init value

init value:= value | ppl expression

Examples:

```
>code scr;  
>storage x[2,3];  
>sinit x = 0;  
>d;
```

Result:

```
-N1      NS  
---N2    Global  
-----N3 x      [Storage 2 2x3]  
-----N4        0      [Array element]  
-----N5        Row    [Array 3]  
-----L0        #      [0]  
-----L1        #      [0]  
-----L2        #      [0]  
-----N4        1      [Array element]  
-----N5        Row    [Array 3]  
-----L0        #      [0]  
-----L1        #      [0]  
-----L2        #      [0]
```


sget

Gets value of element in storage

Format:

sget (name)(index1)(index2)...

Format scr not used, because this command may be used on the left side of the expression.

Examples:

```
>sget(stor);           // get value of single-variable
>sget(stor)(0);        // get value of single-dimensional array,index=0

// get value of two-dimensional array,stor[0][0]
>storage stor[2,2];
>sget(stor)(0)(0);     // or stor.0.Row[0] for using on the right
                        // side of the expression
>var x = sget(stor)(0)(0); // error
>var x = stor.0.Row[0];  // right
```

sset

Sets value for element in storage

Format **ppl: sset (name)(index1)(index2)(value)**

Format **scr: sset name [index1,index2] = value**

Examples:

```
>code scr;
>storage stor;
>sset stor = 0; // set value of single-variable = 0
                // or: set stor = 0;

// set value of single-dimensional array,stor[0]= 1
>storage stor[3];
>sset stor[0] = 1; // or: set stor.Row[0] = 1;

// set value of two-dimensional array,stor[0][0] = 1
>storage stor[2,3];
>sset stor[0,0] = 1; // or: set stor.0.Row[0] = 1;
> var y = 1;
>sset stor[y,y] = 2; // it is possible to use var as index
>swrite stor 30
```

result:

```

          0          1          2

-----NS.Global.stor-----
[0]      1
[1]              2
```

swrite

Displays elements values of storage

Format **ppl**:

swrite(name)

swrite(name) (max_window_width)

Format **scr**:

swrite name

swrite name max_window_width

default max_window_width = 100

Limit for CPPL.exe max_window_width = Console.WindowWidth = 120

NoLimit for WPPL.exe

Examples:

```
>code scr;
>storage x[3];
>sinit x = 0;
>swrite x 50;
```

| | 0 | 1 | 2 |
|-----|---------------------|---|---|
| | -----NS.Global----- | | |
| [x] | 0 | 0 | 0 |

```
>code scr;
storage s[5,3];
>sinit s = 0;
>swrite s;
```

| | 0 | 1 | 2 |
|-----|-----------------------|---|---|
| | -----NS.Global.s----- | | |
| [0] | 0 | 0 | 0 |
| [1] | 0 | 0 | 0 |
| [2] | 0 | 0 | 0 |
| [3] | 0 | 0 | 0 |
| [4] | 0 | 0 | 0 |

```
>swrite s 30;
```

| | 0 | 1 | 2 |
|-----|-----------------------|---|---|
| | -----NS.Global.s----- | | |
| [0] | 0 | 0 | 0 |
| [1] | 0 | 0 | 0 |
| [2] | 0 | 0 | 0 |
| [3] | 0 | 0 | 0 |
| [4] | 0 | 0 | 0 |

```
>code scr;
>storage xxx[3,3,5];
>sinit xxx = 0;
>swrite xxx 40;
    0    1    2    3    4

-----NS.Global.xxx.0-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
-----NS.Global.xxx.1-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
-----NS.Global.xxx.2-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
```

sinfo

Displays length of each dimension in storage

Format: **sinfo(name)**

Format scr not used, because this command may be used on the left side of the expression.

Examples:

```
>storage y[5];
```

```
>sinfo(y);
```

Result: Storage 1 5 // single-dimensional array length 5

After using realloc for storage Row it will be written:

```
>code scr;
```

```
>storage s[3,5];
```

```
>realloc s.0.Row[10];
```

```
>sinfo(s);
```

Result: Storage 2 *

ssetrow

Sets value for elements of the lowest level.

Format **ppl**:

ssetrow(name)(ind1)(ind2)(indN)... (elem1)(elem2)(elemM)...

Format **scr**:

ssetrow name [ind1,ind2,indN...] = {elem1,elem2,elemM...}

Examples:

```
// N = 2, M=3
>code scr;
>storage y[2,3];
>ssetrow y[0]={1,2,3};
>ssetrow y[1]={4,5,6};
>swrite y 50;
```

| | 0 | 1 | 2 |
|-----------------------|---|---|---|
| -----NS.Global.y----- | | | |
| [0] | 1 | 2 | 3 |
| [1] | 4 | 5 | 6 |

Backup & Recovery

savedata

Saves data from node to file with extension **.data**.

If node is root, all root contents will be saved.

Format **ppl**: **savedata(filename.data) [(node)]**

Format **scr**: **savedata filename.data [node]**

Default node: **NS.Global**

Example:

```
>code ppl;  
>savedata(Data\Colors1.data) (Colors) ;
```

readdata

Reads data from file with extension **.data** to Nodes Configuration and NS.Global, **not to Local**.

Format **ppl**: `readdata(filename.data)[(node)]`

Format **scr**: `readdata filename.data [node]`

Default node: **NS.Global**

Examples:

```
>code scr
>readdata Data\Colors.data;
>d
-N NS
---N Global
-----N Colors
-----L0      Black      [0]
-----L1      Blue       [9]
-----L2      Cyan       [11]
-----L3      DarkBlue   [1]
-----L4      DarkCyan   [3]
-----L5      DarkGray   [8]
-----L6      DarkGreen  [2]
-----L7      DarkMagenta [5]
-----L8      DarkRed    [4]
-----L9      DarkYellow [6]
-----L10     Gray       [7]
-----L11     Green      [10]
-----L12     Magenta    [13]
-----L13     Red        [12]
-----L14     White      [15]
-----L15     Yellow     [14]
```

Each item in such array has key (Black, Blue,...) and value(0,9,...) , use [getbykey](#) and [getbyvalue](#).

Control Flow

if, else

The meaning of the block "if-else" does not differ from the generally accepted.
About using statements terminator ";" in if see [Base Concepts](#).

Format **ppl**:

```
if (condition)
(
    (statement)
    (statement)
    [ (else
        (
            (statement)
            (statement)
        )
    ) ]
);
```

Here expression in prefix notation.

Statement in ppl mode.

Format **scr**:

```
if (condition)
{
    statement;
    statement;
    [else
    {
        statement;
        statement;
    } ]
}
```

Here expression in infix notation.

Statement in ppl or scr mode.

Example ppl mode:

```
var(x[1]);
var(y[1]);
if (==(x)(y))
(
    (write(true))
    (write(TRUE))
    else
    (
        (write(false))
        (write(FALSE))
    )
)
);
true
TRUE
>write(end);
end
```

Example scr mode:

```
var x = 1;
var y = 1;
if ( x == y )
{
    write(true);
    write(TRUE);
    else
    {
        write(false);
        write(FALSE);
    }
}
write(end);
```


switch, case, default

switch statement – for select one from several case blocks to be executed.

About using statements terminator ";" in switch see [Base Concepts](#).

Format **ppl**:

```
switch(expression)
(
    (case1) [ (case2) ...]
    (
        (statement)
        (statement)
        ...
    )
    (caseN) ...
    (
        (statement)
        (statement)
        ...
    )
    ...
    [ (default)
    (
        (statement)
        (statement)
        ...
    ) ]
);
```

Here expression in prefix notation.

Statement in ppl mode.

Format **scr**:

```
switch(expression)
{
    case <value>:
    case <value>:
        statement;
    break;
    case <value>:
        [ statement;
    break;
    default:
        statement;
    break; ]
}
```

Here expression in infix notation.

Statement in ppl or scr mode.

Examples:

Format **ppl**:

1.

```
switch(x)
(
  (1) (3)
  (
    (write("Cases 1 & 3"))
  )
);
```

2.

```
var (x[1]);
switch (x)
(
  (1) (3)
  (
    (write("Case 1 & 3"))
  )
  (2)
  (
    (write("Case 2"))
  )
  (default)
  (
    (write("Default"))
  )
);
```

Result:

Case 1 & 3

3.Format scr

```
var x = 2;
switch(x)
{
  case 1: case 3:
    write("Case 1 & 3");
    break;
  case 2:
    write("Case 2");
    break;
  default:
    write("Default");
    break;
}
```

loop,do

Iteration block for ppl mode only.

About using statements terminator ";" in loop see [Base Concepts](#).

Format **ppl**:

```
loop (iteration var) (begin) (end) [(increment)] or  
loop () //infinity loop
```

```
(do  
  (  
    (statement)  
    (statement)  
    ...  
  )  
)
```

begin:= value|ppl expression

end:= value|ppl expression

increment:= value|ppl expression

By default increment = 1. Increment may positive or negative.

Parameter end is set before entry to iteration block and may be changed by

setloopend inside iteration block.

Statement in ppl mode.

Examples:

```
loop (i) (0) (10) (1)      // or loop (i) (10) (0) (-1)  
(do  
  (  
    (write("i = {0}") (i))  
  )  
) ;
```

See infinity example – greatest common factor (gcf) calculation in [for](#)

setloopend

Changes "end" in loop (iteration var)(begin)(end)[(increment)] inside iteration block

Format **ppl**:

setloopend (end)

Format **scr**:

setloopend end

Example:

```
array arr[10] = 0;  
for(j,0,length(arr))  
{  
    write#("j = {0}    length = {1}",j,length(arr));  
    array.remove(arr)(0);  
    setloopend length(arr);  
}  
writearray arr row;
```

Result:

```
j = 0    length = 10  
j = 1    length = 9  
j = 2    length = 8  
j = 3    length = 7  
j = 4    length = 6
```

for

Iteration block for **scr mode** only.

About using statements terminator ";" in for see [Base Concepts](#).

Format **scr**:

```
for(iteration var, begin, end [, increment]) or
```

```
for() // infinity for
```

```
{
```

```
    statement;
```

```
    statement;
```

```
    ...
```

```
}
```

By default increment = 1. Increment may positive or negative.

Statement in ppl or scr mode.

Examples:

```
var x;
for(i, 0, 10, 1)
{
    set x = i * 2;           // scr statement
    write("x = {0}") (x);    // ppl statement
}
```

Example with Infinity for:

```
function gcd(x,y,z)
{
    if(isinteger (x) == "False")
    {
        write#("not integer value x={0}",x);
        return;
    }
    if(isinteger (y) == "False")
    {
        write#("not integer value y={0}",y);
        return;
    }
    for()    // infinity for
    {
        if (x > y)
        {
            set x = x - y;        // or Sub(x) (x) (y) ;
        }
        if (x < y)
        {
            set y = y - x;        // or Sub(y) (y) (x) ;
        }
        if (x == y)
        {
            set z = x;
            return;
        }
    }
}
var z = 0;
var x = 14144;
var y = 26163;
gcd(x) (y) (z) ;
write#(gcd = {0},z) ;
Result: gcd = 17;
```

break

Exit from loop (ppl mode) or from for (scr mode) or end of case in switch block.

Example:

```
for(i, 0, 4, 1)
{
    if (i == 2)
    {
        write("true i = {0}") (i);
        break;
    }
};
```

continue

Continue executing in loop (ppl mode) or in for (scr mode).

Example:

```
loop(x) (0) (5) (1)
(do
  (
    (write("x={0}") (x) )
    (if (==(x) (3))
      (
        (write("x = {0} continue") (x) )
        (continue)
      )
    )
  )
);
```

Input and Output

write

Writes the string value to the standard output stream.

String interpolation ($\$ "x"$) is not supported. If string value contains "Error:" it will be wrote in red color in cppl.exe or in wppl.exe.

Format:

write(value) | write(c# format)(value)(value)...

value:=value | ppl expression with prefix notation

Example:

```
>var (x[0]);
>write(x);
>write("{0}{1}") ("x=") (x); // like c# write("{0}{1}") ("x=",x);
//quote in string
>write("ppl\language"); // ppl\language
//tab in string
>write("ppl\tlanguage"); // ppl language
//newline in string
>write("ppl\r\nlanguage"); // ppl
//language

>write(12col);
Result: 12col
>write("Error: wrong name {0}") (12col);
Result: Error: wrong name 12col
```

This operator is used in ppl and scr mode.

```
>code scr;
>var x = 2*5; // scr expression is calculated in var
>write("{0} {1}") ( "x = " ) (x);
>code ppl
>write("{0}") (* (2) (5)); // ppl expression
```

write#, writeline

Like as write, for mode scr only, each argument is not enclosed in parentheses.

Format scr:

write#(arg) | write#("c# format", arg1 , arg2,...)

writeline(arg) | writeline("c# format", arg1 , arg2,...)

arg:= <literal> | <scr expression with infix notation>

Example:

```
1.
>write#("{0} {1}", aaaa,1+3)
Result: aaaa 4
```


2.

```
>code scr;  
>write#(1+2);  
3  
>write(1+2);    // not same result as with write#  
1+2  
>write#("1+2");  
1+2
```

writearray

Writes array contents to the standard output stream. By default writearray writes array elements into the column. Writearray writes array elements into the row by second argument "row".

Format **ppl**:

writearray ([node.]array_name) [(row)]

Format **scr**:

writearray [node.]array_name [row]

or

writearray ([node.]array_name [,row])

Examples:

1.

```
>code scr
>array y[] = {1,2,3}
>writearray y
-----Array y-----
[0]      1
[1]      2
[2]      3
>writearray y row
```

Result:

```
-----Array y-----
1, 2, 3
```

2.

```
>code scr;
>storage(x) (2) (3);
>sinit(x) (0);
// write the bottommost arrays in storage
>writearray (x.0.Row);
```

Result:

```
[0]      #      0
[1]      #      0
[2]      #      0
```

```
>writearray (x.1.Row, row);
```

Result:

```
0, 0, 0
```

3.

```
>array y[3];
>setkvp y[0] = one,1;
>setkvp y[1] = two,2;
>setkvp y[2] = three,3;
>writearray y row
```

Result:

```
-----Array y-----
{one,1}, {two,2}, {three,3}
```

readline

Reads the next line of characters from the standard input stream. Result will be passed to calling operator.

Format: **readline()**

Examples:

```
var (x) ;
>set(x) (readline()) ;
>Enter:
>>Hello
>d;
Result:
-N1      NS
---N1    Global
-----L0 x      [Hello]
```

Functions

Function library **CommonFunctions.ppl**, defined in file **Configuration.data** as **default_loaded_functions**, loads automatically and reloads when command **init** executes. It includes 2 types of functions:

- Mathematical and Logical functions,
- Array services and other functions.

Mathematical and Logical functions:

```

Sum (result)(n1)[( n2)]
Sub (result)(n1)[( n2)]
Mult (result)(n1)[( n2)]
Div (result)(n1)[( n2)]
Pow (result, n1, n2)
PlusPlus (result) | Plus1 (result)           // like c#: ++(var)
MinusMinus (result) | Minus1 (result)        // like c#: --(var)
LT (result, n1, n2)
LTEQ (result, n1, n2)
GT (result, n1, n2)
GTEQ (result, n1, n2)
EQ (result, n1, n2)
NOTEQ (result, n1, n2)
AND (result, n1, n2)
OR (result, n1, n2)
XOR (result, n1, n2)

```

These functions replace using prefix notations. Result are returned in 1st parameter and does not passed to the next command:

```

>var (z[0]);
>var (x[1]);
>set (z) (Sum(x) (1));           // error
>Sum(z) (x) (1);                 // right

```

Examples:

```

1.
>var (x[1]);
>var (z);
>Sum(z) (x) (1);    // set z = x + 1
>Sum(x) (2);        // set x = x + 2
>d
-N2      NS
---N3    Global
-----L4 x      [3]
-----L5 z      [2]

```

2. This sample returns **wrong result**:

```
>var(x[5]);  
>Sum(x)(x)(2);  
>d x  
-----Variables and arrays-----  
-L4      x      [5]  
>Sum(x)(2);    // right, x = x + 2
```

3.

```
>code scr;  
>call Sum(x,2,3);  
>call Sum(x,2+3);  
>Sum(x)(+(2)(3));
```

User may create own functions file, like CommonFunctions.ppl, and set it in file

Configuration.data as **UserFunctionsN** or load it:

```
>rc user_functions.ppl|scr;
```

Files, defined in **Configuration**, load their function only and do not execute any command, commands in files, loaded by command rc (readcode) are executed one after another.

Array services and other functions:

CsvToArray (var:str, array:arr) – to fill array from string data separated by comma

ArrayToCsv (array:arr, var:str) – copy to string separated by comma data from array

ArrayIsExist (result, array:arr, value) – return True/False if devined value exists in
array

ArrayIndexOf (result, array:arr, value) – return the index of the first
occurrence within array or -1.

ArrayLastIndexOf (result, array:arr, value) – return the index of the last
occurrence within array or -1.

Example:

```
array my_array;  
call CsvToArray("1,2,3,,1,5",my_array);  
writearray my_array row;  
  
var result;  
call ArrayToCsv(my_array,result);  
write#("result = {0}",result);  
  
call ArrayIndexOf (result, my_array, 3);  
write#("index = {0}",result);  
  
call ArrayLastIndexOf (result, my_array, 1);  
write#("index = {0}",result);
```

```
Result:  
1, 2, 3, , 1, 5  
result = 1,2,3,,1,5  
index = 2  
index = 4
```

See **examples\ArrayFunc\SamplesFunc.scr**.

ArrayForEach(array:arr, array:callback_name) – calls a callback function once for each array element

Example: (examples\arrayfunc\foreach.scr)

```
function sumfunc(array:arr,var:i)
{
    set result = result + arr[i];
}

var result = 0;
delegate dd (array:arr,var i);
dltinstance instance dd;
dltset instance sumfunc;
call ArrayForEach({1,2,3,4,5},instance);
write#("result = {0}",result);
//result = 15
```

function

Functions must be declared before being called.

Functions are saved in Tree **Functions** or in Tree **Global** for later call.

Functions return data via parameters, like a classic procedure.

When function is called **by name** (in mode **ppl** or **scr**) each argument must be enclosed in parentheses.

When function is called by command '**call**' (in mode **scr** only) each argument not must be enclosed in parentheses, but separated by comma.

Function uses data created inside and data from NS.Global.

Data created in function are deleted when function will be finished.

Limitations:

1. For passing array member use 2 arguments **(sample)**:

array name, index array member
or temporary variable:

```
>array y[] = {1,2,3};  
>var x = 10;  
>set tmp = y[0];  
>call Sum(x,tmp);  
>write#("x={0}",x)  
x=11
```

2. If argument value will be changed in function this argument can be used only one time when function is called(see example **Sum_wrong_result**).

Format **ppl**:

Statement terminator ';' does not follow after statements within function, but each statement is surrounded by parentheses.

function

```
(  
  name  
  parameter_list  
  ( function body )  
);  
name ::= identifier  
parameter_list ::= parameter [parameter_list]  
parameter ::= (identifier) | (identifier[default value]) | empty  
function body ::= (statement1) [(statement2) (statementN)]  
identifier ::= [var] | [array] | [storage] |  
               [struct <struct_name>] | [struct array <struct_name>]:<param_name>
```


Format **scr**:

Statement terminator ';' always follows after each type of statements.

```
function    name
            (parameter_list)
            {
                function body
            }
name::= identifier
parameter_list::= parameter, [parameter_list]
parameter::=
    identifier | identifier[default value] | identifier = default value | empty
function body::= statement1 [ statement2 statementN ]
identifier::= [var] | [array] | [storage]:<name>
By default parameter type is var.
```

Examples:

```
>code scr
1.Function func ()
{
    write#("func");
}
2. function func (n,m[10])    // = func (var:n,var:m[10])    or
                               //function func (n,m = 10)
{
    write#(funcname());
}
3.function func (array: n)
{
    write#( funcname());
}
```

```
4.code ppl;
function
(
  test2(n)
  (
    (write(n))
  )
);
function
(
  test()
  (
    (loop (i) (0) (5) (1)
      (do
        (
          (test2(i))
        )
      )
    )
  )
);
test();      // function call
```

```
5.
code scr;    // (see  examples\scr\func.scr)
function sum_arr(array:n,array:m)
{
  // dstree;
  for(i,0,length(n),1)
  {
    write#("[{0}]  [{1}]" ,i, n[i] + m[i]);
  }
}
array x[] = {1,2,3,4,5};
array y[] = {6,7,8,9,10};
sum_arr(x)(y);  // function call

result:
[0]  [7]
[1]  [9]
[2]  [11]
[3]  [13]
[4]  [15]
```

In the following example (see examples\scr\func4.scr) parameter index default value = 0 and this parameter may be omitted when the function is called. Array and member array index are passed as 2 arguments.

```
6. code scr;
function func (array:arr, var:index[0])
{
    write#("{0} [{1}] = {2}",getargname(arr),index, arr[index]);
}
array y[] = {1,2,3,4};
func(y);
call func(y); // same as previous line
call func(y,0);
call func(y,1);
call func(y,2);
=====result=====
y[0] = 1
y[0] = 1
y[0] = 1
y[1] = 2
y[2] = 3
```

```
7. Call function from node saved in Tree Global
code ppl;
createnode New;
function
(
    New.func(name) // public
    (
        (write(name))
    )
);
function
(
    New._hfunc(name) // private
    (
        (write(name))
    )
)
```

```
New.func("Greetings!");  
8. Call function from node saved in Tree Functions  
code ppl;  
createnode Functions.New;  
    function  
    (  
        Functions.New.func(name)    // public  
        (  
            (write(name))  
            (Functions.New._hfunc(name))  
        )  
    );  
function  
(  
    Functions.New._hfunc(name)    // private  
    (  
        (write(name))  
    )  
)  
Functions.New.func("Greetings!");
```

9. Recursion example

```
var tmp = 0;
function rec(x)
{
    set tmp = tmp + 1;
    write#("tmp={0}",tmp);
    if (tmp == x)
    {
        return;
    }
    rec(x);
}
rec(5);
```

10. Function may be updated

```
function f()
{
    write("f");
}
f();
function f()
{
    write("f2");
}
f();

result:
f
Warning: [FuncCreateFunction] function [f] is updated
f2
```

11. Passing structure as function parameter

```
definestruct Room
{
    var x;
    array y[3];
}
// function f(struct Toom:r) - wrong struct_name causes error
function f(struct Room:r)
{
    set r.x = 1;
    set r.y[0] = "A";
}
createstruct R as Room;
f(R);
```

```
12. Passing structure array as function parameter
define struct Room
{
    var x;
    array y[3];
}
function f(struct array Room:r)
{
    set r.0.x = 1;
    set r.0.y[0] = "A";
}
create struct R[2] as Room;
f(R);
```

Examples with using public and private functions in Trees Functions and Global it is possible to find in directory Examples\Access.

```
13. Passing array as parameter (see examples\scr\arr.scr)
function mean(array:arr,result)
{
    set result = 0;
    for(i,0,length(arr))
        set result = result + arr[i];
    set result = result/ length(arr);
}
var result;
call mean({1,2,3,4,5,6,7,8,9,10},result);
write#("mean = {0}",result);
```

call

Command '**call**' invokes a function in mode **scr**, it is possible to use expression in infix notation as arguments, do not need to enclose in parentheses each argument when function is called.

Format:

call function_name(arg1,arg2,...)

Examples:

```
1.
>code scr
>var x = 0;
>call Sum(x,4 + 1);
>d x
-----Variables and arrays-----
-L1      x      [5]

1.Call function without arguments or with one not-expression
argument by command 'call' and directly(without 'call') is same:
call func(123);    same as    func(123);

2. To get return of function, called by 'call',
   run 'debugppl yes' before:

>debugppl yes;
>call (Math.PI());
result = 3.141592653589793

3. For transfer return of function to the next command
   do not use 'call'
>write#( Math.PI() );
result = 3.141592653589793

4.
>write#(call Math.PI());    // error
>set x = call Math.PI();    // error
>set x = Math.PI();
3.141592653589793
```

It is possible to pass array by this manner:

call function_name({item1,item2,...},arg2,...)

Example: (see examples\CallFunc\funcarr2.scr and examples\CallFunc\funcarr2.ppl)

```
function SumArray(array:arr,var:result)
{
    for(i,0,length(arr))
        call Sum(result,arr[i]);
}
```

```
var result=0;
call SumArray({1,2,3,4,5},result);
write#("result = {0}",result);
```

instead of:

```
array arr[] = {1,2,3,4,5};
call SumArray(arr,result);
```

Preprocessor generates the following ppl-code:

```
function
(
    SumArray (array:arr) (var:result)
    (
        (set (result) (0))
        (
            loop (i) (0) (length(arr)) (1)
            (
                do
                (
                    (Sum(result) (result) (arr[i]))
                )
            )
        )
    )
);
var (result);
array (arg_array0) (1) (2) (3) (4) (5 );
SumArray (arg_array0 ) ( result );
del arg_array0;
write ("result = {0}") (result);
```


return

Exit from function or from script.

Example:

```
function f()
{
    for(i, 0, 5, 1)
    {
        write(i);
        if (i == 3)
        {
            return;
        }
    };
};
f();
write("end of script");
```

funclist

Displays function names and their parameters from node Functions.

Format:

funclist| finclist()

Example:

```
>funclist;
Result:
-----Function List-----
Sum  (result, n1, n2)
Sub  (result, n1, n2)
Mult (result, n1, n2)
Div  (result, n1, n2)
Pow  (result, n1, n2)
PlusPlus (result)
MinusMinus (result)
LT    (result, n1, n2)
LTEQ  (result, n1, n2)
GT    (result, n1, n2)
GTEQ  (result, n1, n2)
EQ    (result, n1, n2)
NOTEQ (result, n1, n2)
AND   (result, n1, n2)
OR    (result, n1, n2)
XOR   (result, n1, n2)
```

funcname

Returns the current function name.

Format:

funcname()

Example:

```
>write(funcname());  
main
```

argc

Returns number of arguments

Format:

argc()

Example:

```
function Sum (result,n1,n2 = "")  
{  
    write#("argc = {0}",argc());  
    if (argc() == 2)  
        set result = result + n1;  
    else  
        set result = n1 + n2;  
}  
>code scr;  
> var x = 0;  
>call Sum(x,1);  
>write#("x = {0}",x);  
Result:  
argc = 2  
x = 1
```

getargname

Returns argument name (or argument value if it is literal) by parameter name

Format:

getargname (parameter_name)

Example:

```
function a(n)  
{  
    write#("param name=[{0}] arg name=[{1}]",  
        getname(n),getargname(n));  
}  
var i = 0;  
a(i);  
Result:  
param name=[n] arg name=[i]
```

Delegates and callbacks

There are 4 operators for using delegates:

delegate – creation delegate

dlgtinstance – creation delegate instance

dlgtset - setting the function to delegate instance

dlgtcall – call function by delegate instance

delegate

delegate is created as an array whose elements define the method parameters.

Prefix “**delegate_**” is added to delegate name for internal using.

Format **ppl**:

delegate | **dlgt** (<delegate name>) (param1) (param2)...

param:= <var_name> | var:<var_name> | array:<array_name> |

storage:<array_name> | struct [array] <struct_name>: < var_name >

Format **scr**:

delegate | **dlgt** <delegate name> (param1, param2,...)

Example (**scr-mode**):

```
>delegate MyDelegate (var:x,array:arr);  
>dlgt MyDelegate (struct array Letter:ltr);
```

dlgtinstance

dlgtinstance is created as an array with 2 elements, first is delegate name, second is empty and will be set by dlgtset. Delegate parameters types must be matched types of function parameters . Prefix “**dlgtinstance_**” is added to delegate instance name for internal using.

Format **ppl**:

dlgtinstance (<delegate instance name>)(<delegate name>)

Format **scr**:

dlgtinstance <delegate instance name><delegate name>

Example(**scr-mode**):

```
>dlgt dd (var:x,array:arr);
>dlgtinstance instance dd;
>d;
-N2      NS
---N3    Global
-----L0 empty    (const)
-----N4 delegate_dd [Array 2]
-----L0      #      [var:x]
-----L1      #      [array:arr]
-----N4 dlgtinstance_instance [Array 2]
-----L0      #      ["delegate_dd"]
-----L1      #
```

dlgtset

dlgtset sets function name as second element in **dlgtinstance** array.

Format **ppl**:

dlgtset (delegate instance name)(function name)

Format **scr**:

dlgtset delegate instance name function name

Example (**scr-mode**):

```
// see previous example with dlgt and dlgtinstance
function f1(var:x,array:arr)
{
    write#("x = [{0}]",x);
    writearray arr;
}
>dlgtset instance f1;
```

dlgtcall

dlgtcall calls function defined in dlgtset.

Format **ppl**:

dlgtcall(delegate instance name)(arg1)(arg2)(arg3)...

Format **scr**:

dlgtcall delegate instance name(arg1,arg2,arg3,...)

Example:

```
// see previous examples with dlgt, dlgtinstance and dlgtset
var z = "qqq";
array y[] = {1,2,3};
dlgtcall instance (z,y);
```

Result:

```
x = [qqq]
-----Array arr-----
[0]      1
[1]      2
[2]      3
```

See the samples with delegates - Examples\delegates*.scr

callback

callback invokes synchronous callback method.

Format **ppl**:

callback (callback name)(arg1)(arg2)(arg3)...

Format **scr**:

callback callback name (arg1,arg2,arg3,...)

Example: (see Examples\delegates\callback.scr)

```
function cb1(var:n)
{
    write#("====={0}====",funcname);
    write#("n = {0}",n);}

function cb2(var:n)
{
    write#("====={0}====",funcname);
    write#("n = {0}",n);}

function f(array:x,var:str)
{
    callback x(str);
}

delegate dd (var:n);
dlgtinstance instance dd;
dlgtset instance cb1;
call f(instance,"PPL");
dlgtset instance cb2;
call f(instance,"PPL");
```

Result:

```
function cb1 PPL
function cb2 PPL
```

Additional functionalities

The following below-mentioned additional DLLs with C# functionalities are added and this list will be expanded.

There are two types of methods called from additional DLLs:

- methods that return result, this result may be used in the next operation, for example:

```
var result = Math.Max(10) (20) ;
```

- methods that not return result, for example:

```
ArrayList.Remove(arrlist, item1) ;
```

Methods of second type of may be called by command 'call' in scr-format:

```
call ArrayList.Remove(arrlist, item1) ;
```

```
write#("ArrayList.Contains item1 = {0}", ArrayList.Contains(arrlist)( item1)); // right  
write#("ArrayList.Contains item1 = {0}", call ArrayList.Contains(arrlist)( item1)); // wrong
```

In the following sample it is created wrapper for calling method that returns result (examples\lib\char.scr):

```
code scr;  
function GetChar(result,text,index)  
{  
    set result = String.Char(text) (index) ;  
}  
var char;  
var text = "Hello";  
for(i,0,length(text))  
{  
    call GetChar(char,text,i) ;  
    write(char) ;  
}
```

To get list of methods of additional loaded DLLs:

<DLLname>.help

Use Application ULC.exe([Structure of User's DLL](#)) to create code for additional DLL. Arguments of additional DLLs use **prefix math.notation, only Math library uses infix math. notation in scr-mode, this feature is added to preprocessor:**

```
set x = Math.Sqrt(1+3) + Math.Max(2)(3*5);
```

Math

Methods:

| | | |
|---------|----------|----|
| Max | E | PI |
| Min | Exp | |
| BigMul | Floor | |
| Sqrt | Log | |
| Round | Log10 | |
| Abs | Pow | |
| Acos | Sign | |
| Asin | Sin | |
| Atan | Tan | |
| Atan2 | Truncate | |
| Ceiling | Tanh | |
| Cos | Cosh | |
| DivRem | Sinh | |

Limitation: Do not use Math.Function in Math.Function:

```
var x = Math.Sin(30/(180/Math.PI())) // error
```

To get short help of every method in Math.DLL:

>Math.help[(method name)];

Returns the larger of two double-precision floating-point numbers:

Math.Max(double d1)(double d2)

Returns the smaller of two double-precision floating-point numbers:

Math.Min(double d1)(double d2)

Produces the full product of two 32-bit numbers:

Math.BigMul(Int32 n1)(Int32 n2)

Returns the square root of a specified number: **Math.Sqrt(double d1)**

Rounds a double-precision floating-point value to a specified number:

Math.Round (double value)[(Int32 digits)]

Returns the absolute value of a double-precision floating-point number:

Math.Abs(double value)

Returns the angle whose cosine is the specified number: **Math.Acos(double d)**

Returns the angle whose sine is the specified number: **Math.Asin(double d)**

Returns the angle whose tangent is the specified number: **Math..Atan(double d)**

Returns the angle whose tangent is the quotient of two specified numbers:

Math.Atan2(double d1)(double d2)

Returns the smallest integral value greater than or equal to the specified number:

Math.Ceiling(double d)

Returns the cosine of the specified angle: **Math.Cos(double d)**

Returns the remainder in an output parameter: **Math.DivRem(Int64 n1)(Int64 n2)**

Represents the ratio of the circumference of a circle to its diameter: **Math.PI()**

Represents the natural logarithmic base: **Math.E()**

Returns e raised to the specified power: **Math.Exp(double value)**

Returns the largest integral value less than or equal to the specified number:

Math.Floor(double value)

Returns the logarithm of a specified number: **Math.Log(double value)**

Returns the base 10 logarithm of a specified number: **Math.Log10(double value)**

Returns a specified number raised to the specified power:

Math.Pow(double value)(double power)

Returns an integer that indicates the sign of a double-precision floating-point number:

Math.Sign(double value)

Returns the sine of the specified angle: **Math.Sin(double value)**

Returns the tangent of the specified angle: **Math.Tan(double value)**

Calculates the integral part of a number: **Math.Truncate(double value)**

Returns the hyperbolic tangent of the specified angle: **Math.Tanh(double value)**

Returns the hyperbolic cosine of the specified angle: **Math.Cosh(double value)**

Returns the hyperbolic sine of the specified angle: **Math.Sinh(double value)**

String

Methods:

| | |
|--------------------|------------------------|
| Compare | Replace |
| Concat | DeleteEndOfLine |
| Contains | StartsWith |
| Format | Substring |
| IndexOf | ToArray |
| LastIndexOf | ToLower |
| Insert | ToUpper |
| Remove | Trim |
| Split | Char |
| SplitCsv | |

To get short help of every method in String.DLL:

>String.help[(method name)];

Returns signed int as string: **String.Compare(stringA)(stringB)**

Returns concatenation of several strings: **String.Concat(string1)(string2)...**

Returns true|false: **String.Contains(string)(specified substring)**

Converts the value of objects to string based on the formats specified and returns result:

String.Format(format)(string1)(string2)...

Example:

```
String.Format("{0} {1}") ("qwe") ("zxc")
```

```
Result: qwe zxc
```

Returns a new string in which a specified number of characters from the current string are deleted:

String.Remove(string)(startIndex)(number of deleted symbols)

Example:

```
>rc examples\lib\StringRemove.scr
```

```
import String;
array primes = {1,2,3,5,7};
var output = "";
for(i,0,length(primes),1)
{
    set output = String.Concat(output) (primes[i]) (",");
}
var index = length(output) - 1;
set output = String.Remove(output) (index) (1); //remove the
latest ','
write(output);
Result:1,2,3,5,7
```

Returns a new string in which all occurrences of a specified Unicode character or string in the current string are replaced with another specified Unicode character or string:

String.Replace(string)(old value)(new value)

Determines whether this string instance starts with the specified character:

Returns **True** | **False**: **String.StartsWith(string)(value)**

Retrieves a substring from this instance. The substring starts at a specified character position and has a specified length:

String.Substring(string)(startIndex)(length)

Writes the characters in this instance to a Unicode character array:

String.ToCharArray(string)(node_of PPL_chars_array)

node_of PPL_chars_array is string in quotes or value of variable.

Example:

```
>array chars;  
>String.ToCharArray("qwerty") (getname(chars)) ;  
>writearray chars;
```

Result:

-----Array chars-----

```
[0]    q  
[1]    w  
[2]    e  
[3]    r  
[4]    t  
[5]    y
```

Returns a copy of this string converted to lowercase: **String.ToLower(string)**

Returns a copy of this string converted to uppercase: **String.ToUpper(string)**

Returns a new string in which all leading and trailing occurrences of a set of specified characters from the current string are removed:

String.Trim(string)[(trim chars string)]

```
>String.Trim(" abcde") (" ae");
```

Result: bcd

Returns one character from string: **String.Char(string)(index)**

Returns the reallocated string array that contains the substrings in this instance that are delimited by elements of a specified string array or in special string var, string array must be created before with size = 0:

String.Split(string)("ppl_array_separators")(getname(ppl_array_result)) or
String.Split(string)("var_separator")(getname(ppl_array_result))

Use comma instead of ','
 space instead of ' '
 tab instead of '\t'

Example:

> var text;

```
>set text = File.ReadAllText("Data\test.csv");  
>array separator[] = {comma,tab,space};  
>array split_text_array;  
>String.Split(text) ("separator") (getname(split_text_array));
```

Returns the reallocated string array that contains the substrings in this instance that are delimited by separator of a specified string var, string array must be created before with size = 0.

If substring surrounded by quotes it may contain separator
(see example\lib\splitcsv.scr):

array ppl_array_result;

String.SplitCsv(string)("var_separator")("ppl_array_result")

Use comma instead of ','
 space instead of ' '
 tab instead of '\t'

Do not use whitespace as separator:

Example:

Returns string from File.ReadAllText without EndOfLine: **DeleteEndOfLine(string)**

>rc Examples\Lib\FilesplitCsv.scr

```
var text = File.ReadAllText("examples\lib\splitcsv.txt");  
array splitcsv_text;    // array with results  
String.SplitCsv(text) (comma) (getname(splitcsv_text));  
File.WriteAllText("text") ("examples\lib\splitcsv_copy.txt");
```

Reports the zero-based index of the first occurrence of the specified string in this instance:

String.IndexOf (string)(value)(index)

Reports the zero-based index of the last occurrence of the specified string in this instance:

String.LastIndexOf (string)(value)(index)

Returns a new string in which a specified string is inserted at a specified index position in this instance:

String.Insert (string)(start index)(string to insert)

Directory

Methods:

```
GetFiles
GetDirectories
SetCurrentDirectory
GetCurrentDirectory
GetParent
CreateDirectory
Exists
Delete
```

To get short help of every method in Directory.DLL:

```
> Directory.help[(method name)];
```

Writes the names of files (including their paths) in the specified directory to **node_of_PPL_array**, created before with size = 0:

```
array node_of_PPL_array;
```

```
Directory.GetFiles("node_of_PPL_array")("path")
```

node of PPL array is string in quotes or value of variable or `getname(node_of_PPL_array)`.

Example:

1.

```
>array files;
>Directory.GetFiles("files") ( "c:\" );
or
var (x["files"]);
>Directory.GetFiles (x) (path) ;
```

2.

```
>rc examples\lib\WriteFilesInDir.scr
```

```
function WriteFilesInDirectory (array:arr,dir)
{
    array arr;
    Directory.GetFiles(arr) (dir) ;
    Writearray arr;
}
WriteFilesInDirectory ("files") ("c:\");
```

Result:

-----Arr files-----

```
[0]      c:\DumpStack.log.tmp
[1]      c:\hiberfil.sys
[2]      c:\pagefile.sys
[3]      c:\swapfile.sys
```

Writes the names of files (including their paths) in the specified directory to **node_of_PPL_array**, created before with size = 0:

```
array node_of_PPL_array;  
Directory.GetDirectories("node_of_PPL_array")( "path")
```

node of PPL array is string in quotes or value of variable or
getname(**node_of_PPL_array**).

Example:

```
array dir;  
Directory.GetDirectories("dir") ("c:\Users") ;  
or  
var (x["dir"]);
```

Sets the current working directory to the specified directory:

```
Directory.SetCurrentDirectory("path")
```

Gets the current working directory: **Directory.GetCurrentDirectory()**

Returns parent fullname: **Directory.GetParent("path")**

Returns CreationTime: **Directory.CreateDirectory("path")**

Returns **True** or **False** : **Directory.Exists("path")**

Deletes the specified directory and any subdirectories and files in the directory

Returns **True** or **False**: **Directory.Delete("path")**

Array

Methods:

| | | |
|----------------|----------------|--------------------|
| Max | Min | Sum |
| Average | Sum2 | Sub2 |
| Mult2 | Div2 | Sort |
| Reverse | IndexOf | LastIndexOf |

To get short help of every method in ArrayDLL: **Array.help[(method name)];**

Returns result: **Array.Max("ppl_array")**

Returns result: **Array.Min("ppl_array")**

Returns result: **Array.Sum("ppl_array")**

Returns result : **Array.Average("ppl_array")**

Math operations with 2 array, result is saved in **result_ppl_array**:

Array.Sum2("ppl_array1")("ppl_array2")("result_ppl_array")

Array.Sub2("ppl_array1")("ppl_array2")("result_ppl_array")

Array.Mult2("ppl_array1")("ppl_array2")("result_ppl_array")

Array.Div2("ppl_array1")("ppl_array2")("result_ppl_array")

Replaces source array: **Array.Sort("ppl_array") ("double" | "string")**

Replaces source array: **Array.Reverse("ppl_array")**

Returns result: **Array.IndexOf("ppl_array")(value)**

Returns result: **Array.LastIndexOf("ppl_array")(value)**

Example:

```
>code scr;
>import Array;
>array arr[] = {-4,4, -3,3,-2,2};
>Array.Sort("arr") ("double");
>writearray arr;
>Array.Reverse("arr");
>writearray arr;
Result:
-----Array arr----- double-----
[0]      -4
[1]      -3
[2]      -2
[3]       2
[4]       3
[5]       4
-----Array arr----- double-----
[0]       4
[1]       3
[2]       2
[3]      -2
[4]      -3
[5]      -4
```



```
>import Array;  
>code scr;  
>array a[] = {1,3,,5};  
>debugppl yes;  
>Array.Average(a);  
result = 3  
>recreate yes;  
>array a[] = {1,3,0,5};  
Info: [CreateArrayFormat1] Global array [a] is created  
>Array.Average(a);  
Result: 2.25
```

See samples in Examples\lib\Array.scr.

The following collections are supported: **ArrayList, Queue, Stack, Dictionary.**

ArrayList

Methods:

| | | |
|-----------------|----------------|---------------|
| Create | ToArray | Count |
| Write | Reverse | Get |
| Add | Remove | Set |
| Clear | Insert | Delete |
| Contains | IndexOf | |
| AddArray | Sort | |

To get short help of every method in ArrayList.DLL: **ArrayList.help[(method name)];**

Creates ArrayList object: **ArrayList.Create(name)**

It is possible to create ArrayList repeatedly, in this case previous data removed.

Writes all array_list_names or all elements from the specified array_list to the standard output stream: **ArrayList.Write()** or **ArrayList.Write(arrlist name)**

Adds a string to the end of the ArrayList: **ArrayList.Add(arrlist name)(string)**

To add empty string use keyword **empty**:

Example:

```
>ArrayList.Create(ar)
>ArrayList.Add(ar) (empty)
```

Adds node of PPL array to the end of the ArrayList:

ArrayList.AddArray("PPL array")(arrlist name)

Name of PPL array is **string in quotes** or value of variable with value = name of PPL array .

Removes all elements from the ArrayList: **ArrayList.Clear(arrlist name)**

Determines whether an element is in the ArrayList, returns **"True"** or **"False"**:

ArrayList.Contains(arrlist name)(string)

Writes all elements from arrlist to PPL array created before with size = 0 and reallocated in **ArrayList.ToArray** with size of arrlist name:

array "ppl_array";

ArrayList.ToArray(arrlist name)(getname("ppl_array"))

Name of PPL array is **string in quotes** or value of variable with value = name of PPL array .

Error: If PPL array exists.

Reverses the order of the elements in the ArrayList: **ArrayList.Reverse(arrlist name)**

Removes the first occurrence of a specific object from the ArrayList:

ArrayList.Remove(arrlist name)(string)

Inserts an element into the ArrayList at the specified index:

ArrayList.Insert(arrlist name)(index)(element)

To insert empty string use keyword **empty**.

Returns the zero-based index of the first occurrence of a value in the ArrayList:

ArrayList.IndexOf(arrlist name)(value)

Sorts the elements in the ArrayList: **ArrayList.Sort(arrlist name)**

Returns the number of elements actually contained in ArrayList: **ArrayList.Count(arrlist name)**

The following example includes all ArrayList methods:

```
>rc Examples\lib\ArrayList.scr
>import ArrayList;
>ArrayList.Create("all");
>createnode Private;
>array (Private.src) (ONE) (TWO) (THREE);
>var (x["Private.src"]);
>ArrayList.AddArray(x) (all);
>ArrayList.Write(all);
>ArrayList.Add(all) (empty);
>ArrayList.Add(all) (2two);
>ArrayList.Add(all) (3three);
>ArrayList.Add(all) (lone);
>write("====Added objects====");
>ArrayList.Write(all);
>ArrayList.Remove(all) (lone);
>ArrayList.Remove(all) (lone); // // error: lone does not exist
>write("====Removed objects====");
>ArrayList.Write(all);
>ArrayList.Reverse(all);
>write("====Reverse====");
>ArrayList.Write(all);
>write("ArrayList.Contains lone" = {0}) (ArrayList.Contains(all)
                                         (lone));
>ArrayList.Insert(all) (2) (4four);
>write("ArrayList.Contains 4four" = {0}) (ArrayList.Contains(all)
                                         (4four));
>ArrayList.IndexOf(all) (3three);
>ArrayList.Sort(all);
>write("====Sort====");
>ArrayList.Write(all);
>array (N1.dst_arr);
>ArrayList.ToArray(all) (getname(N1.dst_arr));
```

```
>ArrayList.Clear(all) ;
>d;
Result:
Imported [ArrayList]
all
    ONE
    TWO
    THREE
=====Added objects=====
all
    ONE
    TWO
    THREE

    2two
    3three
    lone
Warning: [ArrayList.FuncRemove] element [lone] does not exist
=====Removed objects=====
all
    ONE
    TWO
    THREE

    2two
    3three
=====Reverse=====
all
    3three
    2two

    THREE
    TWO
    ONE
ArrayList.Contains lone" = False
ArrayList.Contains 4four" = True
=====Sort=====
all
    2two
    3three
    4four
    ONE
    THREE
    TWO
-N1  NS
---N2 Global
-----N3  Private  [Node]
-----N4  src     [Array 3]
-----L0  #       [ONE]
-----L1  #       [TWO]
-----L2  #       [THREE]
```

```
-----N4  dst_arr      [Array 7]
-----L0      #
-----L1      #      [2two]
-----L2      #      [3three]
-----L3      #      [4four]
-----L4      #      [ONE]
-----L5      #      [THREE]
-----L6      #      [TWO]
-----L11     x      ["Private.src"]
---N2 Local
```

Returns value of ArrayList member by index:

ArrayList.Get(arrlist_name)(index)

Set value of ArrayList member by index:

ArrayList.Set(arrlist_name)(index)(value)

Example:

```
>import ArrayList
Imported [ArrayList]
>ArrayList.Create(x)
>ArrayList.Add(x) (qqq)
>ArrayList.Add(x) (zzz)
>ArrayList.Get(x) (0)
result = qqq
>ArrayList.Set(x) (0) (aaa)
>ArrayList.Get(x) (0)
result = aaa
```

Delete all ArrayList objects:

ArrayList .Delete();

Queue

Methods:

| | | |
|----------------|-----------------|---------------|
| Create | Peek | |
| Count | Clear | |
| Write | Contains | |
| Enqueue | AddArray | |
| Dequeue | ToArray | Delete |

To get short help of every method in Queue.DLL:

Queue. help[(method name)]

Creates Queue object: **Queue.Create(queue name)**

Returns the number of elements actually contained in Queue: **Queue.Count(queue name)**

Writes queue names or all elements from the specified queue to the standard output stream:

Queue.Write() or **Queue.Write(name)**

Adds an object to the end of the Queue: **Queue.Enqueue(queue name)(string)**

To add empty string use keyword **empty**.

Removes and returns the object at the beginning of the Queue:

Queue.Dequeue(queue name)

Returns the object at the beginning of the Queue without removing it:

Queue.Peek(queue name)

Removes all objects from the Queue: **Queue.Clear(queue name)**

Determines whether an element is in the Queue, returns "True" or "False":

Queue.Contains(queue name)(string)

Adds PPL array to the Queue: **Queue.AddArray("PPL array") (queue name)**

Writes all elements from Queue to the PPL array created before with size = 0:

```
array "ppl_array";  
Queue.ToArray(queue name) ("ppl_array")
```

Delete all Queue objects: **Queue.Delete();**

Examples of code with Dictionary methods in **examples\lib\Queue.ppl**

Stack

Methods:

| | | |
|---------------|-----------------|---------------|
| Create | Peek | |
| Count | Clear | |
| Write | Contains | |
| Push | AddArray | |
| Pop | ToArray | Delete |

To get short help of every method in Stack.DLL:

>Stack.help[(method name)]

Creates Stack object: **Stack.Create(stack name)**

Returns the number of elements actually contained in Stack: **Stack.Count(stack name)**

Writes stack names or all elements from the specified stack to the standard output stream:

Stack.Write() or **Stack.Write(stack name)**

Inserts an object at the top of the stack: **Stack.Push(stack name)(string)**

To insert empty string use keyword **empty**.

Removes and returns the object at the top of the Stack:

Stack.Pop(stack name)

Returns the object at the top of the Stack without removing it:

Stack.Peek(stack name)

Removes all objects from the Stack: **Stack.Clear(stack name)**

Determines whether an element is in the Stack, returns "True" or "False":

Stack.Contains(stack name)(string)

Adds PPL array to the Stack: **Stack.AddArray ("PPL array")(stack name)**

Writes all elements from Stack to the PPL array created before with size = 0:

array "ppl_array";

Stack.ToArray(stack name) ("ppl_array")

Delete all Queue objects: **Stack.Delete();**

Examples:

```
>debugppl yes;  
>import Stack  
Imported [Stack]  
>Stack.Create(s)  
>Stack.Push(s) (one)  
>Stack.Push(s) (two)  
>Stack.Push(s) (three)  
>debugppl yes  
>Stack.Pop(s)  
result = three  
>Stack.Pop(s)  
result = two  
>Stack.Pop(s)  
result = one  
>Stack.Pop(s)  
result = empty
```

Examples of code with Stack methods in **examples\lib\Stacks.ppl**

Dictionary

Methods:

| | | |
|---------------|----------------------|---------------|
| Create | ContainsKey | |
| Count | ContainsValue | |
| Add | Remove | |
| Write | AddArray | |
| Clear | ToArray | Delete |

To get short help of every method in Dictionary.DLL:

>**Dictionary.help[(method name)]**

Creates Dictionary object: **Dictionary.Create(dictionary name)**

Returns the number of elements actually contained in Dictionary:

Dictionary.Count(dictionary name)

Adds the specified key and value to the Dictionary:

Dictionary.Add(dictionary name)(key)(value)

Writes dictionary names or all elements from the specified Dictionary to the standard output stream: **Dictionary.Write()** or **Dictionary.Write(dictionary name)**

Removes all keys and values from the Dictionary: **Dictionary.Clear(dictionary name)**

Determines whether the Dictionary contains the specified key, returns **True** or **False**:

Dictionary.ContainsKey(dictionary name)(key)

Removes the value with the specified key from the Dictionary:

Dictionary.Remove(dictionary name)(value)

Determines whether the Dictionary contains a specific value, returns **True** or **False**:

Dictionary.ContainsValue(dictionary name)(value)

Adds PPL array to the Dictionary: **Dictionary.AddArray("PPL array")(dictionary name)**

Write all elements from Dictionary to new PPL array created before with size = 0:

array "ppl_array";

Dictionary.ToArray(dictionary name) ("ppl_array")

Delete all Queue objects: **Dictionary.Delete();**

Examples of code with Dictionary methods in **examples\lib\Dictionary.ppl**

Convert

Methods:

```
StringToInt32Array
StringToHexArray
HexToBin
BinToHex
IntToHex
HexToInt
IntToBin
BinToInt
```

To get short help of every method in Convert.DLL:

>Convert.help[(method name)];

String characters converts to int32 array created before with size = 0 and reallocated in **Convert.StringToInt32Array** with size of string_characters:

Convert.StringToInt32Array(string_characters)("Int32 "ppl_array")

String characters converts to hex array created before with size = 0 and reallocated in **Convert.StringToHexArray** with size of string_characters:

Convert.StringToHexArray(string_characters)("Hex "ppl_array")

All below mentioned methods convert data in accordance with method name and return:

Returns string bin: **Convert.HexToBin(string with hex value)**

Returns string hex: **Convert.BinToHex(string with bin value)**

Returns string hex: **Convert.IntToHex(string with Int32 value)**

Returns string Int32: **Convert.HexToInt(string with hex value)**

Returns string bin: **Convert.IntToBin(string with Int32 value)**

Returns string Int32: **Convert.BinToInt(string with bin value)**

Examples:

See Examples\lib\Convert.scr

```
>array Int32;
>Convert.StringToInt32Array("12345")("Int32");
Info [CreateArrayFormat2] Global array [Int32] is created
>writearray Int32;
Result:
-----Array Int32-----
[0]      49
[1]      50
[2]      51
[3]      52
[4]      53
```

```
>array Hex;  
>Convert.StringToHexArray("12345")("Hex");  
>writearray Hex;
```

```
Result:  
-----Array Hex-----  
[0]      31  
[1]      32  
[2]      33  
[3]      34  
[4]      35
```

Examples:

```
>debugpp1 yes  
>Convert.HexToBin(16);  
result = 10110  
>Convert.BinToHex(1111111)  
result = 7F  
>Convert.IntToHex(256)  
result = 100
```

Excel

The following methods may be used for reading from XLSX files to two-dimensional storage or writing from two-dimensional storage to XLSX files.

Methods:

```
Open
Close
Read
CreateWorkbook
Write
SaveAs
```

To get short help of every method in Excel.DLL:

```
> Excel.help[(method name)];
```

Opens XLSX file for reading:

```
Excel.Open(filename.xlsx)
```

Closes XLSX file after reading or writing:

```
Excel.Close()
```

Reads opened XLSX to storage, size of storage must be enough to save Excel cells:

```
Excel.Read("sheet")("left top")("right down")("storage")
```

Example:

```
"left top": "A1"
```

```
"right down": "H10"
```

Creates workbook for writing:

```
Excel.CreateWorkbook()
```

Writes storage to Excel cells, quantity of cells must be enough to save storage:

```
Excel.Write("sheet")("left top")("right down")("storage")
```

Saves created XLSX file after writing:

```
Excel.SaveAs(filename.xlsx)
```

Examples:

see file Examples\Excel\test.scr

```
import Excel;
Excel.Open("$1$\examples\Excel\example.xlsx");
Excel.Read("Sheet1")("A1")("H10")("Example_XLSX");
Excel.Close();
swrite(Example_XLSX);
```

```
Excel.CreateWorkBook();  
Excel.Write("Sheet1")("A1")("H10")("Example_XLSX");  
Excel.SaveAs("$1$\examples\Excel\example2.xlsx");  
Excel.Close();
```

>rc examples\excel\test.scr c:\path

Parameter **c:\path** overrides the variable **\$1\$** in file test.scr.

File

Methods:

| | |
|---------------------|----------------------|
| ReadAllText | ReadAllLines |
| WriteAllText | WriteAllLines |
| Exists | Delete |

Returns all contents of text file: **File.ReadAllText(filename)**

Creates a new file, write the contents to the file, and then closes the file:

File.WriteAllText(var_ppl)(filename)

Determines whether the specified file exists, returns **True** or **False**: **File.Exists(filename)**

Returns string array with lines of text file: **File.ReadAllLines(filename)("ppl_array")**

Example:

```
>File.ReadAllLines("examples\lib\split.txt")("x")
```

```
>d
```

```
Result:
```

```
-N1  NS
```

```
---N2 Global
```

```
-----N3 x    [Array 2]
```

```
-----L0  #    [1,2,3,4,5,6,7,8,9,10,]
```

```
-----L1  #    [11,12,13,14,15,16,17,18,19,20]
```

Creates a new file, writes one or more strings to the file, and then closes the file:

File.WriteAllLines("ppl_array")(filename)

Deletes the specified file: **File.Delete(filename)**

Random

Methods:

| | |
|------------------|-------------------|
| Create | NextDouble |
| Next | NextInt64 |
| NextBytes | NextSingle |

Creates Random object: **Random.Create(name)[(Seed)]**

Returns a non-negative random integer: **Random.Next(random_name)**

Returns a non-negative random integer that is less than the specified maximum:
Random.Next(random_name) (maxValue)

Returns a random integer that is within a specified range:
Random.Next(random_name) (minValue)(maxValue)

Creates random numbers and writes them to the of a specified “**ppl_array**” created before with size = 0:
Random.NextBytes(random name) (“ppl_array”)(quantity of random elements)

Returns a random floating-point number that is greater than or equal to 0.0, and less than 1.0:
Random.NextDouble(random name)

Returns a non-negative random integer: **Random.NextInt64(random name)**

Returns a non-negative random integer that is less than the specified maximum:
Random.NextInt64(random name)(maxValue)

Returns a random integer that is within a specified range:
Random.NextInt64(random name)(minValue)(maxValue)

Returns a random floating-point number that is greater than or equal to 0.0, and less than 1.0:
Random.NextSingle(random name)

Examples:

```
>debugpppl yes;
```

```
>import Random;
```

```
Imported [Random]
```

```
>Random.Create(r);
```

```
>Random.Next(r)(0)(10);
```

```
Result : 2
```

```
>array x;
```

```
>Random.NextBytes(r)(x)(5);
```

```
>writearray x;
```

```
Result:
```

```
-----Array x-----
```

```
[0]      5
```

```
[1]     121
```

```
[2]     226
```

```
[3]     108
```

```
[4]      61
```


Console

Methods:

| | |
|------------------------------|--------------------------|
| ForegroundColor | Beep |
| BackgroundColor | Clear |
| ForegroundPromptColor | SetCursorPosition |
| DefaultColors | GetCursorPosition |
| Write | |

Sets the foreground color of the console:

Console.ForegroundColor(color)

Sets the background color of the console:

Console.BackgroundColor(color)

Sets the prompt foreground color of the console:

Console.ForegroundPromptColor(color)

Sets the default foreground, background and ForegroundPromptColor color of the console:

Console.DefaultColors()

Writes the text representation of the specified value or values to the standard output stream: **Console.Write [(format)](string)(string)**

Plays the sound of a beep through the console speaker:

Console.Beep (frequency)(duration)

frequency - 37 to 32767 hertz

duration - msec

Clears the console buffer and corresponding console window of display information:

Console.Clear()

Sets the position of the cursor:

Console.SetCursorPosition(left column cursor position)(top row cursor position)

Gets the position of the cursor:

Console.GetCursorPosition ()

Returns '**left column cursor position, top row cursor position**'

See examples in examples\Console.

Vector

For using with library MathNet.Numerics and others. Using Vector and Matrix libraries significantly increases program performance.

Methods:

```
Vector.Create ("vector_name")(length)(type)
type:= double|float|decimal|bool|int|uint|long|ulong|string
types in accordance with value types in
https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-types/built-in-types
```

```
Vector.Get(vector_name)(index);
Vector.Set(vector_name)(index)(value);
Vector.Add("vector_name")( "ppl_array")
```

Write to line - "row"

Write not nullable data to column - "col"

Write all data to column - "col0"

```
Vector.Write("vector_name")(["row"|"col"|"col0"])
```

```
Vector.WriteNames()
```

```
Vector.Delete("vector_name")
```

```
Vector.DeleteAll()
```

Examples:

```
>import Vector;
>array v[] = {1,2,3,4,5};
>call Vector.Create ("V",5,int);
>call Vector.Add("V",getname(v));
> call Vector.Write("V");
```

Result:

```
=====vector V=====
```

```
1   2   3   4   5
```

```
>call Vector.Set("V",0,0);
> call Vector.Write("V",col);
```

Result:

```
=====vector V=====
```

```
[1]   2
```

```
[2]   3
```

```
[3]   4
```

```
[4]   5
```

```
>call Vector.Delete("V");
```

See examples in **examples\MatrixVector**, **examples\scr\erato.scr**.

Matrix

For using with library MathNet.Numerics and others.

Methods:

```
Create ("matrix_name")(rows)(columns)(type)
type:= double|float|decimal|bool|int|uint|long|ulong|string
types in accordance with value types in
https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-types/built-in-types
Get("matrix_name")(index_row)(index_column)
Set("matrix_name")(index_row)(index_column)(value)
AddArrayToRow ("matrix_name")(row)("")ppl_array""
AddArrayToColumn ("matrix_name")(column)("")ppl_array""
Write to line - "row"
Write not nullable data to column - "col"
Write all data to column - "col0"

Write("matrix_name")[("row" | "col" | "col0")]
WriteNames()
Delete("matrix_name")
DeleteAll()
Rotate("matrix_name")("cw" | "ccw") - for square matrix only
```

Example:

```
>import Matrix;
>call Matrix.Create ("A",3,3,float);
>array r1[] = {1,2,3};
>array r2[] = {4,5,6};
>array r3[] = {7,8,9};
>call Matrix.AddArrayToRow ("A",0, getname(r1));
>call Matrix.AddArrayToRow ("A",1, getname(r2));
>call Matrix.AddArrayToRow ("A",2, getname(r3));
>call Matrix.Write("A");
>call Matrix.Delete("A");
```

See examples in **examples\MatrixVector**.

MN_Numerics

For using MathNet.Numerics.dll

Methods:

```
Matrix("matrix_name")(rows)(columns)           // like as Matrix.CreateDouble
Vector("vector_name")(length)                   // like as Vector.CreateDouble
AddRowToMatrix("matrix_name")("ppl_array")       // like as Matrix.AddRow
AddColumnToMatrix("matrix_name")("ppl_array")    // like as Matrix.AddColumn
AddDataToVector("vector_name")("ppl_array")      // like as Vector.Add
```

Linear Equation Systems:

See detailed information: <https://numerics.mathdotnet.com/LinearEquations.html>

```
Solve("matrix_name")("vector_name")("ppl_array_result")
```

```
DeleteAll() // delete all matrix and name
```

```
DeleteMatrix("matrix_name")
```

```
DeleteVector("vector_name")
```

For operations with vectors and matrices It is possible to use methods from
MN_Numerics.Matrix and MN_Numerics.Vector
or from

Matrix and Vector, **but not together.**

Example: (see examples\mnn\lesrow2.scr)

```
//linear equation systems
// AX = B
// Creation rows as "ppl_array"s
// Creation Matrix.matrix
// Creation Vector.vector
import Matrix;
import Vector;
import MN_Numerics;
Matrix.DeleteAll();
Vector.DeleteAll();
write("-----Creation Matrix.matrix & Vector.vector-----");
call Matrix.Create("A",3,3,double);
array row1[] = {3,2,-1};
array row2[] = {2,-2,4};
array row3[] = {-1,0.5,-1};
call Matrix.AddArrayToRow("A",0,getname(row1)); // fill matrix
call Matrix.AddArrayToRow("A",1,getname(row2));
call Matrix.AddArrayToRow("A",2,getname(row3));

call Vector.Create("B",3,double);
array vector[] = {1,-2,0}; // create vector as "ppl_array"
call Vector.Add("B",getname(vector)); // fill vector
```

```
array X[length(vector)] = 0; // create result as "ppl_array"  
call MN_Numerics.Solve("A","B",getname(X));  
writearray X;  
Vector.Delete("B");
```

Result:

-----Array X-----

```
[0]  1  
[1] -1.9999999999999996  
[2] -1.9999999999999993
```

Constants: to get list of constants from MathNet.Numerics:
>MN_Numerics.help();

Examples:

```
>debugppl yes  
>import MN_Numerics;  
>MN_Numerics.Pi()  
Result: 3.141592653589793  
>MN_Numerics.E()  
Result: 2.718281828459045
```

DataFrame

DataFrame is a table with named columns, columns may be defined with different types, number of rows and columns is not limited.

Methods:

| | |
|------------------------|----------------------------|
| SetRow | AddRowData |
| SetColumn | GetRowArray |
| Write | GetSliceRowArray |
| Save | GetColumnArray |
| ReadFile | GetSliceColumnArray |
| Create | SetCell |
| InsertRows | GetCell |
| AddRows | CellName |
| InsertColumns | SetWidth |
| AddColumns | SetType |
| RemoveRows | GetWidth |
| RemoveColumns | GetType |
| ClearColumns | SetPrintEmptyRows |
| SetWidthForAll | GetPrintEmptyRows |
| SetTypeForAll | SetRowSelectedFrom |
| Sort | GetRowSelectedFrom |
| Reverse | SetRowSelectedTo |
| SelectRows | GetRowSelectedTo |
| UnselectRows | SetReallocIncrement |
| GetRowsLength | GetReallocIncrement |
| GetColumnLength | |

Delete DataFrame – **del df_name**
df_name – DataFrame name

Create - creates node **df_name**, node **<df_name>.Settings** and arrays per each column

```
>import DataFrame
>DataFrame.Create(DF)(2)(A)(B)
>d
-N2  NS
---N3 Global
-----L0 empty (const)
-----N4 DF      [DataFrame]
-----N5  Settings
-----L0  RowSelectedFrom
-----L1  RowSelectedTo
-----L2  PrintEmptyRows [yes]
-----L3  RowsLength    [2]
-----L4  ReallocIncrement [10]
-----L5  AType [Text]
-----L6  AWidth [12]
-----L7  BType [Text]
-----L8  BWidth [12]
-----N5  A      [Array 2]
-----L0  #
-----L1  #
-----N5  B      [Array 2]
-----L0  #
-----L1  #
```

RowSelectedFrom and **RowSelectedTo** sets selected rows and used in Read,Save,Write

PrintEmptyRows sets to present or not empty rows and used in Write.

RowsLength is set automatically as number of rows.

ReallocIncrement sets number of rows and used in Create and AddRows.

<column name>Type sets column type and used in Read and Sort.

<column name>Width sets column width and used in Write.

Formats:

DataFrame.Create() - creates DataFrame "**DF**" with 26x26 columns with following names: A,B,C,... BA,BB,BC,...ZA,...ZZ and 1000 rows

DataFrame.Create(Name) - creates DataFrame "Name" with 26x26 columns with following names: A,B,C,... BA,BB,BC,...ZA,...ZZ and 10 rows

DataFrame.Create(Name)(rows length) - creates DataFrame "Name" with 26 columns with following names: A,B,C,...Z and "**rows length**" rows

DataFrame.Create(Name)(rows length)(column1)(column2)...(columnN) - creates DataFrame "Name" with N columns and "**rows length**" rows

1. Example:



```
CPPL
>import DataFrame
Imported [DataFrame]
>DataFrame.Create(AB)(10)
>DataFrame.Write(AB)

  A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0
1
2
3
4
5
6
7
8
9
=== defined names in DataFrame [AB]===
name      column  row
>
```

2. Example

```
>import DataFrame
>DataFrame.Create(MyDataFrame)(2)(One)(Two)(Three)
----Variables and arrays-----
-N4 MyDataFrame [Node]
---N5 Settings [Node]
---N5 One      [Array 2]
---N5 Two      [Array 2]
---N5 Three     [Array 2]
>DataFrame.Write(MyDataFrame)
Result:
  One  Two  Three
0
1
```

SetRow - sets value for each column for defined row:

Format:

DataFrame.SetRow(df_name)(row index)(value column1)(value column2)...

SetColumn - sets value for each column for defined column:

Format:

DataFrame.SetColumn(df_name)(column)(value row1)(value row2)...

Write - displays DataFrame full contents or only contents of defined columns:

Format:

DataFrame.Write([df_name])[(column)(column)...

To display contents of specific rows:

DataFrame. RowSelectedFrom (df_name)(row index)

DataFrame. RowSelectedTo (df_name)(row index)

or by method **SelectRows.**

DataFrame.SelectRows(df_name)(row index from)(row index to)

Save -saves full contents of DataFrame in file format ".csv" or ".[data](#)" or defined columns only in format ".csv"

Format:

DataFrame.Save(df_name)(filename.csv|.data)[(column)(column)]...

ReadFile - reads full contents of DataFrame from file in format ".csv" or ".[data](#)" or contents of defined columns from file in format ".csv" only.

Format:

DataFrame.ReadFile(df_name) (filename.csv|.data)[(column)(column)]...

InsertRows - inserts number of rows before index

Format:

DataFrame.InsertRows(df_name)(index)[(number of rows)]

By default number of added rows= 1

AddRows - adds number of empty rows at the end

Format:

DataFrame.AddRows([df_name])[(number of rows)]

By default df_name = DF

By default number of added rows = 10

InsertColumns - insert one or several named columns before defined column

Format:

DataFrame.InsertColumns(df_name))(defined column1)(column2)(column3)...

AddColumns - adds number of named columns at the end

Format:

DataFrame.AddColumns(df_name)(column1)(column2)...

RemoveRows

Format:

DataFrame.RemoveRows(df_name) – remove all rows

DataFrame.RemoveRows(df_name)((number_of_row) – remove 1 row

DataFrame.RemoveRows(df_name)(number_from)(*) - remove rows
between number_from to end

DataFrame.RemoveRows(df_name)(number_from)(number_to) - remove rows
between number_from – number_end

RemoveColumns

Format:

Removes named columns and their Type and Width from Settings:

RemoveColumns(df_name)[(column1)(column2)...

Removes all columns and their Type and Width in Settings:

RemoveColumns(df_name)

ClearColumns - clears contents of all DataFrame or defined columns:

Format:

DataFrame.ClearColumns(df_name)[(column)(column)...

SetWidthForAll - sets same width for all columns to display DataFrame by DataFrame.Write:

Format:

DataFrame.SetWidthForAll([df_name])([width])

default name – DF

default with = 12

Example:

>DataFrame.SetWidthForAll(14)

SetTypeForAll - sets same type for all columns

Format:

DataFrame.SetTypeForAll([df_name])([Text | Number])

default name – DF

default type = Text

Example:

>DataFrame.SetTypeForAll(Number)

Sort - sorts all contents by specified column in ascending or descending order

Format:

DataFrame.Sort(df_name)(ascend | descend)(column)

Example:

File: examples\DataFrame\products.csv

Bagel,140,310,Medium

Biscuit ,86,480,High

Jaffa cake,48,370,Med-High

Bread white,96,240,Medium

Bread wholemeal,88,220,LowMed

Chapatis,250,240,Medium

Cornflakes,130,300,Med-High

Program: examples\DataFrame\df8.scr

```
import DataFrame;
```

```
DataFrame.Create(Products) (0) (Bread&Cereals) (Size) (per100grams)  
                                (energy);
```

```
set Products.Settings.Bread&CerealsWidth = 20;
```

```
DataFrame.ReadFile(Products) (examples\DataFrame\products.csv);
```

```
DataFrame.Write(Products);
```

```
DataFrame.Sort(Products) (ascend) (per100grams);
```

```
DataFrame.Write(Products);
```

results:

```

Select CPPL
>rc examples\df\df8.scr
code: scr
Info: [FuncImport] the library [DataFrame] is already loaded
DataFrame [Products] added [7] rows
-----Variables and arrays-----
-N4   Products      [Node]
---N5   Settings    [Node]
---N5   Bread&Cereals [Array 7]
---N5   Size        [Array 7]
---N5   per100grams  [Array 7]
---N5   energy      [Array 7]

      Bread&Cereals      Size      per100grams energy
0   Bagel                140        310        Medium
1   Biscuit              86         480         High
2   Jaffa cake           48         370        Med-High
3   Bread white          96         240        Medium
4   Bread wholemeal      88         220        LowMed
5   Chapatis            250         240        Medium
6   Cornflakes          130         300        Med-High

      Bread&Cereals      Size      per100grams energy
0   Bread wholemeal      88         220        LowMed
1   Bread white          96         240        Medium
2   Chapatis            250         240        Medium
3   Cornflakes          130         300        Med-High
4   Bagel                140         310        Medium
5   Jaffa cake           48         370        Med-High
6   Biscuit              86         480         High
>

```

See examples df8.scr and df9.scr(wrong results for digital data when Type = Text).

Reverse - reverses all DataFrame contents by defined column

Format:

DataFrame.Reverse(df_name)(column)

SelectRows

Format:

Select one row only: **DataFrame.SelectRows(df_name)(select_from)**

Select rows select_from – to end: **DataFrame.SelectRows(df_name)(select_from)(*)**

Select rows between select_from – select_to:

DataFrame.SelectRows(df_name)(select_from)(select_to)

UnSelectRows

Format: **DataFrame.UnSelectRows(df_name)**

GetRowsLength – returns number of rows

Format: **DataFrame.GetRowLength(df_name)**

GetColumnsLength – returns number of columns

Format: **DataFrame.GetRowLength(df_name)**

AddRowData – adds row with data per columns at the end

Format:

DataFrame.AddRowData(df_name)(column1 data) (column2 data)...

GetRowArray – copies data from defined row to ppl array

Format:

DataFrame.GetRowArray(df_name)(index row) ("ppl array")...

GetSliceRowArray - copies part of array defined by index row to ppl array

Format:

DataFrame. GetSliceRowArray (df_name)(index row)[length]("ppl array")

GetColumnArray - copies data from defined column to array

Format:

DataFrame.GetColumnArray(df_name)(column) ("ppl array")...

GetSliceColumnArray – copies part of array defined by column name to ppl array

Format:

DataFrame. GetSliceColumnArray (df_name)(column name)[length]("ppl array")

SetCell - sets value for cell ,defined by name or by column name and row index

Format: **DataFrame.SetCell(df_name)(column name)(index row)(value)**
DataFrame.SetCell(df_name.cell_name)(value)

GetCell - returns value of cell, defined by name or by column name and row index

Format: **DataFrame.GetCell(df_name)(column name)(index row)**
DataFrame.GetCell(df_name.cell_name)

CellName - sets name for defined cell

Format: **DataFrame.CellName(df_name)(column name)(index row)(cell name)**

SetWidth - sets Width value for defined column name in Settings

Format: **DataFrame. SetWidth (df_name)(column name)(value)**

SetType - sets Type value for defined column name in Settings

Format: **DataFrame. SetType (df_name)(column name)(Text | Number)**

GetWidth - returns Width for defined column name in Settings

Format: **DataFrame. GetWidth (df_name)(column name)**

Example:

```
>import DataFrame
>DataFrame.Create(DF)(2)(A)(B)
>DataFrame.SetWidth(DF)(A)(15)
>write(DataFrame.GetWidth(DF)(A))
result: 15
```

GetType - returns Type for defined column name in Settings

Format: **DataFrame. GetType(df_name)(column name)**

Example:

```
>import DataFrame
>DataFrame.SetType(DF)(A)(Number)
>write(DataFrame.GetType(DF)(A))
result: Number
```

SetPrintEmptyRows - sets PrintEmptyRows value in Settings

Format: **DataFrame. SetPrintEmptyRows (df_name)(value)**

GetPrintEmptyRows - returns PrintEmptyRows value from Setting

Format:: **DataFrame. GetPrintEmptyRows (df_name)**

Example:

```
>import DataFrame;
>DataFrame.Create(DF)(2)(A)(B);
>DataFrame.SetPrintEmptyRows(DF)(yes);
>write(DataFrame.GetPrintEmptyRows(DF));
result: yes
```

SetRowSelectedFrom - sets RowSelectedFrom value in Setting

Format: **DataFrame. SetRowSelectedFrom (df_name)(value)**

GetRowSelectedFrom - returns RowSelectedFrom value from Setting

Format: **DataFrame. GetRowSelectedFrom (df_name)**

SetRowSelectedTo - sets RowSelectedTo value in Setting

Format: **DataFrame. SetRowSelectedTo (df_name)(value)**

GetRowSelectedTo – returns RowSelectedTo value from Setting

Format: **DataFrame.GetRowSelectedTo(df_name)**

Example:

```
>code scr;  
>import DataFrame;  
>call DataFrame.Create(DF,2,A,B);  
>call DataFrame.SetRowSelectedFrom(DF,0);  
>call DataFrame.SetRowSelectedTo(DF,1);  
>write(DataFrame.GetRowSelectedFrom(DF));  
result: 0  
>write(DataFrame.GetRowSelectedTo(DF));  
result: 1
```

SetReallocIncrement - sets ReallocIncrement value in Setting

Format: **DataFrame.SetReallocIncrement(df_name)(value)**

GetReallocIncrement - returns ReallocIncrement value from Setting

Format: **DataFrame.GetReallocIncrement(df_name)**

Example:

```
>import DataFrame;  
>DataFrame.Create(DF)(2)(A)(B);  
>DataFrame.SetReallocIncrement(DF)(100);  
>write(DataFrame.GetReallocIncrement(DF));  
result: 100
```

Examples of using DataFrame methods in directory: **examples\DataFrame**

df1.scr - methods ReadFile, Save

df2.scr - methods ReadFile, RemoveColumns, Save

df3.scr - methods AddColumns

df4.scr - methods DataFrame with default name DF

df5.scr - methods ClearColumns

df6.scr - methods RemoveRows, RemoveColumns

df7.scr - methods InsertRows, InsertColumns, SetRow, SetColumn, Sort, Reverse

df8.scr - methods Create,ReadFile,Write, ascending and descending Sort, Reverse

df9.scr - methods Create,ReadFile,Write, ascending Sort for Type = Text and Type Number

df10.scr - methods SetType, GetRowArray, CellName, SetCell, GetCell, GetSlicedRowArray

df11.scr - methods CellName, SetCell, GetCell

df12.scr - methods GetSlicedColumnArray

AddressBook2.scr – methods AddRowData

Statistics

Statistics.dll uses MathNet.Numerics.dll.

See details in -

<https://numerics.mathdotnet.com/api/MathNet.Numerics.Statistics/ArrayStatistics.htm>

Methods:

| | |
|------------------------------------|-----------------------------|
| Covariance | FiveNumberSummary |
| GMean | HMean |
| Maximum | Mean |
| MeanStandardDeviation | Median |
| Minimum | OrderStatistic |
| Percentile | PopulationCovariance |
| PopulationStandardDeviation | PopulationVariance |
| QuantileCustom | Quantile |
| RanksInplace | RootMeanSquare |
| StandardDeviation | Variance |

Formats:

```
Statistics.help([name])
Statistics.Covariance("\"sample1\"")( "\"sample2\"")
Statistics.FiveNumberSummary("\"sample_name\"")( "\"result_array5\"")
Statistics.GMean("\"array_ppl\"")
Statistics.HMean("\"array_ppl\"")
Statistics.Maximum("\"array_ppl\"")
Statistics.Mean("\"array_ppl\"")
Statistics.MeanStandardDeviation("\"array_ppl\"")
Statistics.Median("\"array_ppl\"")
Statistics.Minimum("\"array_ppl\"")
Statistics.OrderStatistic("\"array_ppl\"")(order)
Statistics.Percentile("\"array_ppl\"")(selector)
Statistics.FuncCovariance("\"sample1\"")( "\"sample2\"")
Statistics.PopulationStandardDeviation("\"array_ppl\"")
Statistics.PopulationVariance("\"array_ppl\"")
Statistics.QuantileCustom("\"array_ppl\"")(tau)(definition)
Statistics.Quantile("\"array_ppl\"")(tau)
Statistics.Ranks("\"array_ppl\"")( "\"rank_array_ppl\"")(definition)
Statistics.RootMeanSquare("\"array_ppl\"")
Statistics.StandardDeviation("\"array_ppl\"")
Statistics.Variance("\"array_ppl\"")
```

Example: (examples\Statistics\test.scr)

```
import Statistics;
recreate yes;
write#("Statistics Array Tests");

array sample1[] = {2.1,2.5,3.6,4};
array sample2[] = {8,10,12,14};
var covariance = Statistics.Covariance("sample1")("sample2");
write#("Covariance = {0}",covariance);

var population_covariance = Statistics.PopulationCovariance("sample1")("sample2");
write#("PopulationCovariance = {0}",population_covariance);

array arr[] = {5,9,3,1,7};
var gm = Statistics.GMean("arr");
var hm = Statistics.HMean("arr");
var msd = Statistics.MeanStandardDeviation("arr");

write#("GeometricMean = {0}",gm);
write#("HarmonicMean = {0}",hm);
write#("Mean, StandardDeviation = {0}",msd);

array arr[] = {3,2,5, 7, 6, 4, 6, 9,6, 8,7};
array FiveNumberSummary[5];
call Statistics.FiveNumberSummary("arr", "FiveNumberSummary");
writearray FiveNumberSummary;
write#("min = {0}",FiveNumberSummary[0]);
write#("low_quartile = {0}",FiveNumberSummary[1]);
write#("median = {0}",FiveNumberSummary[2]);
write#("upper_quartile = {0}",FiveNumberSummary[3]);
write#("max = {0}",FiveNumberSummary[4]);
write#("quartile_range = {0}",FiveNumberSummary[3] - FiveNumberSummary[1]);
write#();
var max = Statistics.Maximum("arr");
write#("max = {0}",max);

var min = Statistics.Minimum("arr");
write#("min = {0}",min);

var mean = Statistics.Mean("arr");
write#("mean = {0}",mean);

var order_statistic = Statistics.OrderStatistic("arr")(3);
write#("order_statistic = {0}",order_statistic);

var variance = Statistics.Variance("arr");
```

```
write#("variance = {0}",variance);

var population_variance = Statistics.PopulationVariance("arr");
write#("population_variance = {0}",population_variance);

var median = Statistics.Median("arr");
write#("median = {0}",median);

var percentile = Statistics.Percentile("arr")(50);
write#("percentile = {0}",percentile);

array arr[] = {5,9,3,1,7};
var standard_deviation = Statistics.StandardDeviation("arr");
write#("standard_deviation = {0}",standard_deviation);

var population_standard_deviation = Statistics.PopulationStandardDeviation("arr");
write#("population_standard_deviation = {0}",population_standard_deviation);

var quantile_customR1 = Statistics.QuantileCustom("arr")(0)(R1);
write#("quantile_customR1 = {0}",quantile_customR1);

var quantile_customR8 = Statistics.QuantileCustom("arr")(0)(R8);
write#("quantile_customR8 = {0}",quantile_customR8);

var quantile = Statistics.Quantile("arr")(0);
write#("quantile = {0}",quantile);

array ranks;
Statistics.Ranks("arr")(Average)("ranks");
writearray ranks;

var rms = Statistics.RootMeanSquare("arr");
write#("rms = {0}",rms);
```

Distributions

Distributions.dll uses MathNet.Numerics.dll

See details in -

<https://numerics.mathdotnet.com/api/MathNet.Numerics.Distributions.htm>

Distributions.dll includes the following classes:

Normal, StudentT , ChiSquared , FisherSnedecor.

Only static methods and constructors in these classes are supported.

Project Distributions.csproj with sources -> github/okogoso/PPL/Distributions.zip.

Structure of User's DLL

Directory Template is the example for creation user's DLL, see Template.cs.

Example:

```
>import Template
>Template.sum(1) (2)
result = 3

>Template.help
help
sum
>Template.help(sum)
Returns sum of two double-precision floating-point numbers:
Template.sum(double d1) (double d2)
```

Add in Project Dependencies the project **PPL**.

Utility **ulc.exe** creates code for User's DLL .

ulc.exe [config_file.json]

by default name of config file - ConfigULC.json

Examples:

1. creation code without classes:

```
ulc.exe ConfigULC.Array.json
```

File ConfigULC.Array.json:

```
{
  "name": "Array",
  "path": "",          // save generated code
  "functions":
  [
    "Max",
    "Min",
    "Sum",
    ...
  ]
}
```

Utility ulc.exe generates 2 files:

- **Array.cs** , this file must be added to user's dll project
- **Array.json** , this file must be added to directory **JsonHelp** (for Assistant.exe).

2. creation code with classes:

`ulc.exe ConfigULC.json`

File `ConfigULC.json`:

```
{
  "name": "Distributions",
  "path": "",
  "ulc_classes": [
    { "name": "Normal",
      "functions":
      [
        "Normal",
        "CDF",
        "Estimate",
        "InvCDF"
      ]
    },
    { "name": "StudentT",
      "functions":
      [
        "StudentT",
        "CDF",
        "InvCDF"
      ]
    },
    { "name": "ChiSquared",
      "functions":
      [
        "ChiSquared",
        "CDF",
        "InvCDF"
      ]
    }
  ]
}
```

Utility `ulc.exe` generates files:

- **Distributions.cs** - must be added to user's dll project
- **Normal.cs** - must be added to user's dll project
- **StudentT.cs** - must be added to user's dll project
- **ChiSquared.cs** - must be added to user's dll project
- **Distributions.json** - must be added to directory **JsonHelp** (for Assistant.exe).

Examples of code

See Examples\scr\Eratosthenes3.scr
mode scr

```
//Sieve of Eratosthenes
function FillArray(array:arr)
{
    for (k,0,length(arr))
        set arr[k] = k;
}
function WriteArray(array:arr)
{
    var len = length(arr);
    var output = "";

    for (i,0,len)
    {
        if (primes[i] != 0)
            set output = String.Concat(output) (primes[i]) (",");
    }
    var index = length(output) - 1;
    // remove the latest ','
    set output = String.Remove(output) (index) (1);
    write#("{0}",output );
}
var n = 100;
var len = m + 1;
array primes[len];
var tmp;
FillArray(primes);

for (n,2,len)
{
    for (j,n + 1,len)
    {
        if (primes[j] % n == 0)
        {
            array.remove(primes) (j);
        }
        set len = length(primes);
        setloopend len;
    }
    setloopend len;
}
WriteArray(primes);
```

Examples\scr\erato.scr

This samples significantly improves performance because all calculations are performed in Erato.DLL and data are saved by Vector.DLL.

```
// calculations in library Erato.dll
import Vector;
import Erato;
debugppl yes;
Vector.DeleteAll();

var m = 1000;
var len = m + 1;
array primes[len];
for (k,0,len)
    set primes[k] = k;
call Vector.Create("VPrimes",m + 1,int);
call Vector.Add("VPrimes",getname(primes));

call Erato.Solve("VPrimes");
var output = "";
var tmp;
for (i,0,len)
{
    set tmp = Vector.Get("VPrimes")(i);
    if (tmp != 0)
        set output = String.Concat(output)(tmp)(",");
}

var index = length(output) - 1;
set output = String.Remove(output)(index)(1);
writeln("{0}",output);
```

The following example performs copying elements from two dimensional storage to one dimensional array

(see examples\scr\CopyTo.scr)

```
// copy row elements from first column to last column
function CopyRowElementsToArray(storage:src,row,first_element,last_element,array:dst)
{
    write#("====={0}=====",funcname);
    write(src={0} row={1} first_element={2} last_element={3} dst={4})
        (getname(src))(row)(first_element)(last_element) (getname(dst));
    var x;
    for(i,first_element,last_element + 1)
        set dst[i] = sget(src)(row)(i);
}
//=====
```

```
function CopyColumnElementsToArray(storage:src,column,first_element,last_element,array:dst)
{
  write#("====={0}=====",funcname);
  write(src={0} column={1} first_element={2} last_element={3} dst={4})
    (getname(src))(column)(first_element)(last_element) (getname(dst));

  for(i,first_element,last_element + 1)
    set dst[i] = sget(src)(i)(column);
}
//=====

storage(src)(8)(8);

var tmp = 0;
for(i,0,8)
{
  for(j,0,8)
  {
    PlusPlus(tmp);
    sset(src)(i)(j)(tmp);
  }
}
swrite(src);

array dstRow[6];
var row = 1;
var first = 0;
var last = 5;

call CopyRowElementsToArray(src,row,first,last,dstRow);
writearray dstRow row;

array dstColumn[8];
call CopyColumnElementsToArray(src,7,0,7,dstColumn);
writearray dstColumn row; >rc examples\scr\copyto.scr;
```

```
Result:
  0      1      2      3      4      5      6      7
-----NS.Global.src-----
[0]  1      2      3      4      5      6      7      8
[1]  9     10     11     12     13     14     15     16
[2] 17     18     19     20     21     22     23     24
[3] 25     26     27     28     29     30     31     32
[4] 33     34     35     36     37     38     39     40
[5] 41     42     43     44     45     46     47     48
[6] 49     50     51     52     53     54     55     56
[7] 57     58     59     60     61     62     63     64
=====CopyRowElementsToArray=====
src=src row=1 first_element=0 last_element=5 dst=dst
9, 10, 11, 12, 13, 14
=====CopyColumnElementsToArray=====
src=src column=7 first_element=0 last_element=7 dst=dst
-----Array dstColumn-----
8, 16, 24, 32, 40, 48, 56, 64
```

Open console window:

cmd

and run:

Examples.bat

Callfunc.bat

Delegates.bat

Struct.bat

Dataframe.bat

ArrayFunc.bat

with numerous examples of code.

References

1. Polymorphic Programming Language

https://en.wikipedia.org/wiki/Polymorphic_Programming_Language

1969 Thomas A. Standish

2. Prototypical Programming Language

<https://www.mathstat.dal.ca/~selinger/ppl/>

2000, Ari Lamstein and Peter Selinger

3. Practical Programming Language

<https://www.ppl-lang.dev/index.html>

4. Introducing Gen, a new PPL language by MIT

Probabilistic Programming Language

<https://becominghuman.ai/introducing-gen-a-new-ppl-language-by-mit-f77397eeff3>

Gen it is packet for Julia

2019, Alexandre Dall Alba

5. Piped Processing Language

<https://opendistro.github.io/for-elasticsearch-docs/docs/ppl/>