

**PPL** language

## Table of Contents

Introduction.....	7
Base Concepts .....	9
Trees .....	11
Comments.....	15
Configuration .....	16
Identifiers and DNS.....	16
Public and private variables.....	16
Compound statements (blocks) .....	17
Libraries .....	18
Keywords .....	19
CPPL utility.....	21
WPPL utility .....	23
PPL Assistant .....	26
Service Commands .....	27
help .....	27
version .....	27
cls .....	28
shell.....	28
init.....	28
code .....	28
showcode.....	28
readcode .....	28
fdreadcode.....	30
createpplcode.....	30
display .....	30
displaynodes .....	30
dstree.....	32
datanames .....	33
suspend and resume.....	33
debugppl.....	33
traceppl.....	34

recreate .....	34
log .....	34
exit .....	34
sumdata .....	34
Special Commands .....	35
import .....	35
importlist .....	35
eval.....	35
length .....	36
isexist .....	36
isdigits .....	37
isinteger .....	37
isalldigits .....	38
isallinteger .....	38
iseven, isodd .....	38
del .....	39
calc .....	39
sleep.....	39
getbykey .....	40
getbyvalue .....	40
set .....	40
setkvp.....	41
getvalue .....	42
getname.....	42
gettoken.....	42
Nodes and Leaves.....	44
createnode.....	44
copynode .....	44
getnodes .....	45
getleaves.....	47
struct.....	48
CopyStruct .....	49
Arithmetic operators.....	50

Logical operators .....	50
Variables and Arrays.....	51
var .....	51
const .....	51
array.....	52
realloc .....	54
array.push .....	56
array.pop .....	56
array.reverse.....	56
array.shift.....	56
array.remove .....	56
array.clear .....	56
array.unshift .....	57
array.insert .....	57
Storage .....	58
storage .....	58
sinit .....	59
sget .....	59
sset.....	60
swrite .....	60
sinfo .....	61
ssetrow .....	61
Backup & Recovery.....	62
savedata.....	62
readdata.....	64
Control Flow .....	65
if, else.....	65
switch, case, default .....	67
loop,do.....	69
for .....	70
break .....	71
continue.....	72
Input and Output.....	73

write.....	73
write#, writeline .....	73
writearray .....	74
readline.....	75
Functions .....	76
function.....	80
call.....	85
return .....	87
funclist .....	87
funcname .....	88
argc .....	88
getargname.....	88
Delegates and callbacks .....	89
delegate .....	89
dlgtinstant.....	89
dlgtset .....	90
dlgtcall.....	90
callback .....	91
Additional functionalities .....	92
Math .....	93
String.....	95
Directory .....	99
Array .....	101
ArrayList.....	103
Queue .....	107
Stack.....	108
Dictionary.....	110
Convert .....	111
Excel .....	113
File.....	115
Random.....	116
Console .....	118
Vector .....	119

Matrix .....	120
MN_Numerics.....	121
DataFrame .....	123
Statistics.....	130
Structure of User's DLL.....	133
Examples of code .....	135
References.....	139

## Introduction

**PPL** is the **Parenthesis Programming Language**, in which all elements (statements, parameters, blocks) are enclosed in parentheses. PPL includes a preprocessor to simplify the writing programs and reduce the number of parentheses.

There are some PPL languages (see [References](#)), and this language is not the latest with such abbreviation. The only thing that unites all these languages is the abbreviation.

PPL was developed with Microsoft Developer Studio ,C#, without using any third party packages.

The main PPL feature – extensibility, using functionalities of C# and adding user's libraries by means of creating DLLs in accordance with [template](#), described in this tutorial.

PPL supports 2 modes:

**ppl (base) mode**, which syntax is similar to language LISP, math and logical expressions in prefix notation (**ppl expression**).

Examples:

```
var (x [0]);  
set(x) (+ (1) (2) );  
if (== (x) (1)) ...
```

**scr (preprocessor) mode**, which syntax is similar to language C, math and logical expressions in infix notation (**scr expression**).

Examples:

```
var x = 0;  
set x = 1 + 2;  
if (x == 1)...
```

PPL includes 2 levels of parsing - code written in scr mode translates to ppl mode before executing, parser on each level creates syntax tree.

CPPL and WPPL utilities call PPL API functions, PPL API may be used in other user applications.

Mode scr or ppl is set depending on file extension is being executed or by means of the command code, mode scr makes coding easier as it does not require statements to be enclosed in parentheses. By default mode is **ppl**.

Preprocessor includes the following statements – **var, const, array, set, write#, call** and following compound statements (blocks) – **struct,function, for, if, else, switch, case, default**.

All ppl mode statements except above mentioned may be also added to scr code in format ppl.

Data are saved as Unicode symbols, digital data will be converted into a string.

Examples:

```
set x = 5.2; saved as "5.2"
```

Boolean values are saved as strings - "True" and "False":

```
set x = True;
```

Execution of the program in the language PPL is carried out by means of the utilities cppl.exe or wppl.exe, which control commands are listed in section [Keywords](#). There are different statement formats for ppl mode and scr mode if a statement belongs to two modes.



## Base Concepts


As is customary in many programming language guides the first ppl program is:

```
write("Hello World!");  
without main function.
```

Another example with using Console and String libraries:

File examples\console\colors.scr:

```
var text = "Hello World!";  
array colors[] = {Green,Red,Yellow,Cyan,Blue,Black,  
                  Magenta,Gray,DarkRed,DarkGray,White,Red};  
  
array ArrayChars;  
call String.ToCharArray(text, getname(ArrayChars));  
  
for(i,0,length(text))  
{  
    // function with 1 argument not need operator call  
    Console.ForegroundColor(colors[i]);  
    Console.Write(ArrayChars[i]);  
};  
Console.DefaultColors();  
write();    // to new line
```



The screenshot shows a command prompt window titled "CPPL". The prompt is at the root directory, and the user has entered the command `>rc examples\console\colors.scr`. The output of the script is displayed on the next line: `Hello World!`, where each word is a different color (H: green, e: red, l: yellow, o: cyan, space: blue, W: black, o: magenta, r: gray, l: dark red, d: dark gray, !: white). The prompt is now at the next line: `>`.

More 4 samples to illustrate the possibilities of PPL:

```
1.
>rc examples\cowsay\cowsay1.scr
array cow[] =
{
  "  _____",
  "< P P L >",
  "  -----",
  "  \      ^ ^",
  "  \      (oo)\_____",
  "  \      ( _)\      )\/\ ",
  "          ||----w |",
  "          ||     ||"
};

Console.Clear();
for(i,0,length(cow))
{
  Console.SetCursorPosition(0)(i);
  Console.Write(cow[i]);
}
Console.SetCursorPosition(0)(length(cow));
```



2. Added loading of second file, function call, creation node and array under this node

```
>rc examples\cowsay\cowsay2.scr
```

3. Added second operator 'for' to move cow

```
>rc examples\cowsay\cowsay3.scr
```


4. Added passing data as arguments when calling command readcode

```
>rc examples\cowsay\cowsay4.scr 1 1 10
```

## Trees

All information is stored in PPL as several kinds of Trees –

**root, NS, Functions, Aliases, Configuration** and may be displayed on Screen, saved and restored.



Blue nodes are created automatically when Cpl.exe loads or re-created by command **init**.

By default Tree **Functions** is filling from file Functions\ **CommonFunctions.ppl**, defined as "**default\_loaded\_functions**" in file **Configuration.data**, it may be changed by user on other one, to display its contents perform:

```
>display Functions;
```

User may perform command **readcode (rc)** to read files with user's functions and add these functions to Tree **Functions** or to node, created under Tree **Functions**.

Tree **Functions (or nodes under Tree Functions)** saves only functions, not data (see examples 6-8 in [function](#)).

Examples:

```
>d Functions
-----Functions-----
-N2      Sum      [function]
---L0    result
---L1    n1
---L2    n2
```

```
---N1  #      [internal_block]
-----N2 set
-----L0      result
-----N3      +
-----L0      n1
-----L1      n2
```

Adding functions to node under Tree Functions:

```
>createnode Functions.Calc;
function
(
  Functions.Calc.Sum(result) (n1) (n2)
  (
    (set(result) (+ (n1) (n2)))
  )
);
>d Functions
-----Functions-----
-N2      Calc      [Node]
---N3     Sum      [function]
-----L0 result
-----L1 n1
-----L2 n2
-----N1 #      [internal_block]
-----N2      set
-----L0      result
-----N3      +
-----L0      n1
-----L1      n2
```

Tree **Aliases** is filling from file **Aliases.data**, to display its contents perform:

```
>display Aliases;
```

Tree **Configuration** is filling from file **Configuration.data**, to display its contents perform:

```
>display Configuration;
```

Any public variables (var, const, array, storage and node) are saved in Tree **Global** as common data for all functions and for code without functions(in "main function").

Public functions are available to functions from any node in Tree **Global**.

Private variables and functions are available to functions in the node, that they belong to only. Full name variables and functions include name of node.

Example:

```
createnode N1;
function
(
    N1.f()
    (
        (write("public function N1.f"))
        (N1._f())
    )
);

function
(
    N1._f()    // private
    (
        (write("private function N1._f"))
        (write(N2.x))
        //(write(N2._x))    // Error: [GetValue] [N2._x] private
                           // object, no access
        //(N2._f())         // Error: [Traversal] [N2._f] private
                           // function, no access
    )
);

createnode N2;
var(N2.x["public var N2.x"]);
var(N2._x["private var N2._x"]);
function
(
    N2._f()    // private
    (
        (write("private function N2._f"))
    )
);

N1.f();
write(N2.x);
//write(N2._x);    // Error: [GetValue] [N2._x] private object, no
                   // access
```

Variables for functions are created in Tree **Local**, to display its contents perform in function:

**>display Local**

When exiting a function, its variables are deleted.

For illustration difference between modes scr and ppl consider the following Examples:

```
>rc Examples\scr\for.scr
=== scr code for preprocessor ===
var begin = 0;
var end = 3;
for(i,begin + 1,end + 1,1)
{
    write(i);
}
=== generated by preprocessor ppl code ===
>var (begin[0]);
>var (end[3]);
>loop (i) ( + ( begin ) ( 1 ) ) ( + ( end ) ( 1 ) ) ( 1 )
(
    do
    (
        (write(i))
    )
);
=== results ===
1
2
3
```

Statement terminator ';' always follows after each type of statements in scr mode.

**In ppl mode statement terminator ';' does not follow after statements within compound statements(blocks) – loop, switch,if,function.**

Examples in ppl mode:

```
loop (i) (0) (3) (1)
(
    do
    (
        (write(hello))
        (write(world))
    )
);
```

## Comments

Two kinds of commentaries are possible:

`/*...*/` - for several lines of code

and

`//` - for one line of code or part of line.

## Configuration

Configuration is defined in the file **Configuration.data**, meaning of its members is explained in this tutorial.

```
(Configuration
  (default_loaded_functions [Functions\ CommonFunctions .pp1])
  (Code [pp1])
  (debugpp1 [no])
  (delete all in readcode [yes])
  (log [no])
  (stay_interactive [no])
  (ReplaceMathLogicOperators [no])
  (OFD_port [11000])
  // (UserFunctions1 [Functions\*.pp1])
  // (UserFunctions2 [Functions\*.pp1])
  (UserImport1 [Directory])
  (UserImport2 [Math])
  // (UserImport3 [String])
)
```

## Identifiers and DNS

Names of nodes, variables, arrays, storage and functions contain any symbols, first symbol is any upper or lower case letter or any of the following symbols: **\_ \$ #** , but not a digit. Variables with first symbol **\_** in name are hidden or private variables ([see hidden variables](#)).

String **"all"** can not be used as name([see cmd del](#)).

Length of identifiers is not limited. Do not set keywords, their aliases and names of Libraries as identifiers.

When data is created, its full name and saved address are added to **Data Names Structure (DNS)**. DNS creates separately for non-functions identifiers in Global and for each function in Local, function DNS will be destroyed when exiting the function.

Symbolic values are enclosed in quotation marks, to include a quotation mark in a symbolic expression, precede it with backslash.

Example:

```
"123\"qwe" => "123"qwe"
```

Backslash before the last quote mark it is backslash, not quote mark.

```
"123\qwe\" => "123\qwe\"
```

## Public and private variables

Variables, constants, arrays, storage and functions, whose names start with **underscore** are private, all other are public.

Examples:

```
>createnode N1;
```



```
>var(N1.x["public var N1.x"]);
>var(N1._x["private var N1._x"]);
function
(
  N1._f()    // private
  (
    (write("private function N1._f"))
    (write(N1.x))
    (write(N1._x))
  )
);
```

Error occurs when re-creating a variable, it is possible to delete this variable and to create again:

```
>var(x);
>var(x);    // re-creation
Error: [FuncCreateVariables] name [x] already exists
>del x;
>var(x);
```

## Compound statements (blocks)

The following blocks **for**, **if**, **else** include one or several statements enclosed in curly brackets:

```
if (x == 1)
{
  write("COMPOUND");
  write("STATEMENTS");
}
else
{
  write("compound");
  write("statements");
}
```

When only one statement (**not compound statement**) is in curly brackets it is possible to omit brackets:

```
if (x == 1)
  write("COMPOUND");
else
  write("statements");
```

```
if (x == 1)                                // right
{
  if (y == 2)
    write("right sample");
}
```

```
if (x == 1)                                // wrong
  if (y == 2)
  {
    write("wrong sample");
  }
```

## Libraries

Default name of library is **Main**, it loads always when Cppl.exe or Wppl.exe starts. It is possible to set in file **Configuration.data** as "**UserImportN**" names of additional libraries initialization loaded . To display list of loaded libraries perform:

```
>importlist;  
Main  
Directory  
Math
```

To display contents of any library perform:

**<name of library>.help**

or **help** for Main library

Example:

```
>Directory.help;  
help  
GetFiles  
GetDirectories  
SetCurrentDirectory  
GetCurrentDirectory
```

To get short information about any library function perform:

**<name of library>.help(function name)**

```
>Math.help(Sinh)  
Returns the hyperbolic sine of the specified angle:  
Math.Sinh(double value)
```

For Main Library help or ?:

```
>? d  
display | d [root|NS|Aliases|Functions|Local|node name]  
display NS.namespace.name]
```

## Keywords

Keyword formats are defined in this tutorial, all format are defined for **ppl mode** by default. Additionally defined format for **scr mode** for some keywords. All keywords are divided into 9 groups and presented below:

### Service Commands

help, version, cls, shell, init, code, showcode, readcode, fdreadcode, createpplcode, display, displaynodes, dn, dstree, datanames, suspend, resume, debugppl, traceppl, recreate, log, exit, createcodeppl, sumdata

### Special Commands

import, importlist, eval, length, calc, sleep, isexist, isdigits, isinteger, isalldigits, isallinteger, iseven, isodd, del, getbykey, getbyvalue, set, setkvp, getvalue, getname , gettoken

### Nodes and Leaves

createnode, copynode, getnodes, getleaves

### Variables and Arrays

var, const, array, realloc, array.push, array.pop, array.reverse, array.shift, array.remove, array.clear, array.unshift, array.insert

### Storage

storage, sinit, sget, sset, swrite, sinfo, ssetrow

### Backup and Recovery

savedata, readdata

### Control Flow

if, else, switch, case, default, loop, do, for, break, continue

### Input Output

write, writeline (write#), writearray, readline

### Functions

function, funclist, funcname, argc, getargname, call, return

### Delegates and callbacks

delegate, dlgtinstant, dlgtset, dlgtcall, callback

### Special variables, constants and words

**empty** – see methods ArrayList.Add, Queue.Enqueue, Stack.Push

**tab,comma,space** – see String.Split, String.Splitcsv.





If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file. Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Value of argument is literal, not command.

When value of **stay\_interactive** in file **Configuration.data** = "no" cppl.exe finishes after program execution, when value of **stay\_interactive** = "yes" cppl.exe does not finish and continues in interactive mode.

Example:

File example.scr

```
var $1$ = $2$;  
>cppl.exe example.scr x 2;
```

## 2.Interactive mode

### cppl.exe

Command input from standard input stream.

To get list of commands and their short explanation perform **help** (or ?).

Examples:

```
>? Display;  
      display [root|NS|Aliases]  
>? d;  
      display [root|NS|Aliases]
```

Prompt ">" appears on Screen before each command.

Examples:

```
>display;  
-N1      NS  
---N2    Global
```

In addition to commands required to work with scr/ppl programs, cppl.exe allows you to execute all Windows commands and save the results. Command **shell** uses for that.

Examples:

```
>var (x) ;  
>set(x) (shell(cd)) ;      // output is saved in var x  
>write(x) ;
```

The following often used commands and operators with one parameter may be used with or without parentheses around arguments:

**help** (?), **import**, **readcode** (rc), **showcode**, **createnode**, **isexist**, **display** (d), **del**, **code**, **debugppl**.

## WPPL utility

WPPL.exe is also a PPL interpreter, its functionalities are liked cpp.exe. WPPL.exe is WPF Application, runs in interactive mode only.

The screenshot shows the WPPL application window. The title bar is 'WPPL'. The menu bar has 'File' and 'Data'. The toolbar contains buttons for 'init', 'cls', 'display', 'importlist', 'ppl' (with a dropdown arrow), 'showcode' (checked), 'debugppl' (unchecked), 'log' (unchecked), and 'help'. The main area is a blue console window with the following text:

```
>showcode;
>version
version 1.0.6
>help
>
```

---

```
-----Init-----
-N0   root
--N1  NS
----N2 Global
----N2 Local
code: ppl
debugppl = no
log = no
stay_interactive = no
Imported [Directory]
Imported [Math]
ShowCode=yes

-----Main-----
-----Service Commands-----
help      version  cls      shell      init      code
showcode  readcode  fdreadcode  dstree    display  createppl
datanames suspend  resume      debugppl  log       exit
-----Special Commands-----
import    importlist eval      length    exist      del
getbyname getbyvalue set       getvalue  getname
-----Nodes-----
createnode copynode
-----Variables and Arrays-----
var        const    array    realloc
```

Top part is used as input any PPL commands, down part is for results presentation. Also service commands may be performed by menu and wpf controls over top part. The following dialogs are used to perform service commands:

Clicking on **CreatePPL in Menu** opens the following dialog:

The screenshot shows the 'CreatePPLDlg' dialog box. It has two text input fields and two buttons. The first field is labeled 'SCR filename:' and contains the path 'PL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Examples\rc.scr'. The second field is labeled 'PPL filename:' and contains the path 'C:\Users\ok21\MyProjects.Work\C#2\PPL\PPL\PPL\WPPL\bin\'. There is a 'Browse' button next to the first field and a 'CreatePPL' button next to the second field.

Clicking on **ReadCode in Menu** opens the following dialog:



The ReadCodeDlg dialog box has a title bar with a close button (X). It contains two text input fields: 'Filename:' with the text '2\PPL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Examples\rc.scr' and 'args:' which is empty. To the right of the 'Filename:' field is a 'Browse' button. To the right of the 'args:' field is a 'ReadCode' button.

Clicking on **ReadData in Menu** opens the following dialog:



The ReadDataDlg dialog box has a title bar with minimize, maximize, and close buttons. It contains two text input fields: 'Filename:' with the text '\PPL\PPL\PPL\WPPL\bin\Debug\netcoreapp3.1\Data\Colors.data' and 'Node:' which is empty. To the right of the 'Filename:' field is a 'Browse' button. To the right of the 'Node:' field is a 'ReadData' button.


Clicking on **SaveData in Menu** opens the following dialog:



The SaveDataDlg dialog box has a title bar with a close button (X). It contains two text input fields: 'Filename:' with the text 'Data\' and a dropdown menu showing '.data', and 'Node:' with the text 'Global'. To the right of the 'Node:' field is a 'SaveData' button.



Clicking on button **display** opens the following dialog:




History of commands is supported by buttons **PgUp** and **Pgdn**.

WPPL.exe is an example of using the PPL API, which can be easily used in the user's application.

## PPL Assistant

PPL Assistant displays format commands in ppl and scr modes. As well this application displays format methods in [additional libraries](#).

Files JsonHelp\\*.json are generated by utility CreateUserLibCode.exe (version 1.0.15).



## Service Commands

### help

Displays keywords list for Library by <name> or format of command from Main library.

Library must be loaded before (see <import>)

by default name = Main, this library is loaded automatically

Format: **help | ? [<library name>] | keyword**

```

>?
-----Main-----
Service Commands-----
  help      version  cls      shell     init      code
  showcode  readcode  fdreadcode  dstree    display   displaynodes
  datanames suspend  resume    debugppl  traceppl  recreate
  log       exit     createpplcode

-----Special Commands-----
  import  importlist  eval      length  del
  isexist isdigits   isinteger  calc     sleep
  isalldigits isallinteger iseven    isodd
  getbykey  getbyvalue  set       getvalue  getname

-----Nodes and Leaves-----
  createnode  copynode  getnodes  getleaves

-----Variables and Arrays-----
  var      const  array  realloc

-----Storage-----
  storage  sinit  sget  sset
  swrite   sinfo  ssetrow

-----Backup and Recovery-----
  savedata  readdata

-----Control Flow-----
  if      else  switch  case  default
  loop    do    for     break continue

-----Input Output-----
  write  write#  writeline  writearray  readline

-----Functions-----
  function  call  funclist  funcname  argc  return

to get short explanation of each command: help command
>
  
```

Examples:

```

>? Code;
    Sets mode for Console input or displays on Screen
    code ppl | scr
>? "display" // only display in quotes
    display | d [root|NS|Aliases|Functions|Local|node name]
    display [NS.namespace.name]
  
```

Any other library has function help for display its contents.

**<name of library>.help [(keyword)]**

**>Matrix.help (Rotate)**

### version

Display current version

Format: **version**

## cls

Clears the Screen

Format: **cls**

## shell

Executes Windows Console Commands, several commands are hash symbol separated. Results of shell are saved and can be displayed by commands **write** or by **debugppl yes**

Format: **shell (command with parameters[#command with parameters])**

Examples:

```
>write(shell (cd:\));  
>debugppl yes;  
>shell (dir /b tests#cd);
```

## init

Deletes all data and functions and creates new root, use this command for console input only.

Format: **init**

## code

Sets mode for Console input or displays it on Screen.

Mode scr is more convenient for writing code with blocks and for using infix expressions. But in other cases there is no difference.

Format: **code [ppl|scr]**

default - ppl

It is possible to set **code** in file **Configuration.data**.

## showcode

Shows or hides on Screen ppl\_code when command readcode is executed or displays showcode value on Screen

Format: **showcode [yes|no]**

Default: no

Examples:

```
>showcode no;
```

## readcode

Reads file with code in format scr or ppl.

At the end of the execution readcode the previous code will be set.

Format: **readcode | rc <file.scr|ppl> [arg1 arg2 ...]**

If arguments are present, they override the variables \$1\$, \$2\$ and so on in the body of the called file.

Number between two symbols \$ is the serial number of argument.

An error occurs if arguments quantity less than max variable number.

Arguments are literals, not commands.

If **delete\_all\_in\_readcode = yes** in **Configuration.data** command

**delete all** is added automatically as first command when first command **readcode** is called.

The file being called can also include readcode commands. Files called by command **readcode** can be of different formats - .scr or .ppl.

If caller script and internal scripts are in the same path you can omit path for internals.

You can specify relative path from cppl.exe or full path, including drive:

```
>rc path\caller.scr
call internal script:
    rc internal.scr
or    rc path\internal.scr or rc drive:\path\internal.scr
```

Example

```
1.
>Directory.SetCurrentDirectory(examples\ppl);
>rc loop.ppl; // or rc examples\ppl\loop.ppl
loop (i) (0) (3) (1)
(
    do
    (
        (write("PPL"))
        (write("ppl"))
    )
);
2. File example.scr
var $1$ = $2$;
>rc example.scr x 2;

3. reading script with command readcode inside:
File main.scr:
    write("main script");
    rc examples\rc\first.scr;
    rc examples\rc\second.scr;
    write("return from main script");
File first.scr:
    write("first script");
    rc examples\rc\third.scr;
    write("return from first script");
File second.scr:
    write("second script");
File third.scr
    write("third script");

    >rc examples\rc\main.scr;
Results:
main script
first script
third script
return from first script
second script
return from main script
```

## fdreadcode

Like readcode with using FileDialog to select file. This command loads ofd.exe and sets connection with **cppl.exe** via UDP protocol, port defined in file **Configuration.data** as **OFD\_port**.

Format: **fdreadcode|fdrc**

## createpplcode

Creates file in format ppl from file in format scr.

Format: **createpplcode|cpc (file.scr)(file.ppl)**

Examples

```
>createpplcode (ttt.scr) (ttt.ppl);  
>cpc (ttt.scr) (ttt.ppl);
```

## display

Displays nodes(N) and leaves(L) in Tree, alias – d.

Format:

**display | d [root | Global | Functions | Aliases | Configuration | Local |  
path\_node.name]**

default: Global

Examples:

```
>array(y[2]) (0);  
>d;  
-N  NS  
---N Global  
----N y  
-----L0          [0]  
-----L1          [0]  
>d Global.y;  
>d y;  
>d Functions.Sum;
```

## displaynodes

Displays nodes(N) only, alias – dn.

Format:

**displaynodes | dn [root | Global | Functions | Aliases | Configuration | Local |  
path\_node.name]**

Example:

```
>dn Functions
-----Functions-----
-N3      Sum      [function]
---N1    #        [internal_block]
-----N2 set
-----N3      +
-N3      Sub      [function]
---N1    #        [internal_block]
-----N2 set
-----N3      -
.....
```

## dstree

Displays function syntax tree with nodes(N) and leaves(L) of code.

dstree displays all function tree within function.

Format: **dstree()** | **dstree**

Examples:

```
>rc examples\scr\func7.scr
```

```
function func(n,m)
{
    write#("{0} {1}", n , m);
    dstree;
}
func(aaa)(111);
```

Result:

```
aaa 111
-----Syntax Tree-----
-N3      func      [function]
---L0    n
---L1    m
---N4    #          [internal_block]
-----N5 write
-----L0          "{0} {1}"
-----L1          n
-----L2          m
-----N5 dstree
-----L0
```



## datanames

Displays contents of [DNS](#).

Format: **datanames [Local]**

Examples:

```
>var(x) ;
>createnode Node1;
>array(Node1.arr[5]);
>datanames;
-----Global_dns-----
      _main0   var
      _main1   var
      _main2   var
      empty    const
      x
Node1   arr
>datanames Local;    // for using in functions
-----Local dns-----
```

## suspend and resume

Stops script to perform manually one or several commands,

continue script execution – **resume**

stop script – **exit** and double click

Format: **suspend**

Examples:

```
>Enter:
>d
-N1      NS
---N1    Global
>resume  // continue script execution
```

## debugppl

Displays information about creation and deletion variables, results operations and duration or displays debugppl value on Screen.

Format: **debugppl [yes|no]**

It is possible to set **debugppl** in file **Configuration.data**.

Example:

```
>var(x)
>debugppl yes
>duration = 0.0015026
>del x
leaf [x] is deleted
>duration = 0.0054401
```

## traceppl

Displays all commands and function names on screen during the execution of commands. By default – traceppl no.

Format: **traceppl [yes|no]**

Example:

```
>traceppl yes;
```

## recreate

Permits recreation vars, arrays, storage and nodes. By default – recreate no.

Format: **recreate [yes|no]**

Example:

```
>recreate yes;  
>code scr;  
code: scr  
>var x;  
>var x;  
>recreate no;  
>var x;  
Error: [FuncCreateVariables] name [x] already exists
```

## log

Writes commands and results to logfile in directory **Log** or displays log value on Screen.

Format: **log [yes|no]**

It is possible to set **log** in file **Configuration.data**.

Opened logfile will be closed by command init or exit.

## exit

Exit from Cppl.exe (**exit**) or exit from script (**exit()**).

## sumdata

Defines argument type for summation. By default – **sumdata digit**.

Format:

**sumdata [digit | string]**

Example:

```
>code scr;  
>sumdata digit;  
>write#(1+2);  
3  
>sumdata string;  
>write#(1+2);  
12
```

## Special Commands

### import

Loads Library, name of Library is name of DLL.

Format: **import <Library name>**

Examples:

```
>import Math;
```

### importlist

Displays list of loaded Libraries

Format: **importlist**

Examples:

```
>importlist;
```

```
Main
```

```
Math
```

### eval

Performs string in format ppl.

Format: **eval <ppl expression>[<result>]**

**result:=var\_name to save result**

Examples

```
Ex. 1
> var (sum) ;
>var (x["+(2) (3)"]);
>d;
-N1      NS
---N2    Global
-----L0 sum
-----L1 x      ["+(2) (3)"]
---N2    Local
>eval(x)(sum)
>d
-N1      NS
---N2    Global
-----L0 sum      [5]
-----L1 x      ["+(2) (3)"]
---N2    Local
```

```
Ex. 2
array y[] = {"+(3) (5) ", "+(4) (6) "};
for(j,0,length(y))
{
    eval(y[j]);
};
```

```
Ex.3
var(x);
eval("+(1) (2)")(x);
write("{0} = {1}") (getname(x)) (getvalue());
x = 3
```

## length

Returns length of value for var | const or length array | storage

Format: **length (var | const name | array name|storage name)**

Examples:

```
>array (y[3]);
>length(y);
result = 3
>var (x["Hello!"]);
>length(x);
result = 6
```

## isexist

Determines whether var, array or storage with specified name exists or not in Global or Local, returns **"True"** or **"False"**.

Format: **isexist(name) | isexist name**

name:= [NS.][namespace.][node.]name

Example:

```
1.
>debugpp1 yes
>var (x);
>isexist x;
result=True
2.
> createnode Functions.New
> isexist Functions.New
result=True
```

### isdigit

Checks is value of var or member of array or storage digital, returns **"True"** or **"False"**.

Format: **isdigit(var name | member of array or storage | literal ) |**

**isdigit var name | member of array or storage | literal**

Example:

```
>var (x[1.1]);
>isdigit x;
result=True
```

### isinteger

Checks is value of var or member of array or storage integer, returns, returns **"True"** or **"False"**.

Format: **isinteger(var name | member of array or storage | literal ) |**

**isinteger var name | member of array or storage | literal**

Example:

```
>var (x[1]);
>isinteger x;
result=True
```

### isalldigits

Checks if all members of array or storage are digital, returns, returns **"True"** or **"False"**.

Format: **isalldigits(member of array or storage) |**  
**isalldigits member of array or storage**

Example:

```
>array(x) (1) (2) (3) ;  
>isalldigits x;  
result=True
```

### isallinteger

Checks if all members of array or storage are integer, returns, returns **"True"** or **"False"**.

Format: **isallinteger(member of array or storage) |**  
**isallinteger member of array or storage**

Example:

```
> array(x) (1) (2) (3) ;  
>isallinteger x;  
result=True
```

### iseven, isodd

Checks if integer value is even or odd, returns **"True"** or **"False"**.

Format:

**iseven(var name | member of array or storage | literal ) |**  
**iseven var name | member of array or storage | literal**

**isodd(var name | member of array or storage | literal ) |**  
**isodd var name | member of array or storage | literal**

## del

Deletes any kinds of data from Global or Local Tree, also deletes nodes from Functions.

Format: **del fullname**

To delete all Global contents: **del all**, so name “all” can not be used as any kind of variable names.

If **delete\_all\_in\_readcode = yes** in **Configuration.data** command

**delete all** adds automatically as first command when command **readcode** is called. Otherwise all data will be saved in memory, if necessary add this command manually.

fullname:= node path.name

node path:= node path | node

Example:

```
>createnode Node1;  
>var(Node1.x);  
>del Node1.x;  
  
>createnode Functions.Geo  
>del Functions.Geo
```

For re-run script, that creates array:

```
>if(==(isexist(y)) (True))  
(  
    (del y)  
);  
>array(y[5]);
```

## calc

Calculates infix notation math. expression and writes result on screen, may be used for ppl and scr modes, but in interactive mode only, not in .ppl or .scr files.

Format: **calc math.expression**

Example:

```
>var (x[1]);  
>calc x + 2*Math.PI();  
7.283185307179586
```

## sleep

Suspends the interpreter for the specified number of milliseconds

Format: **sleep(msec)**

Example:

```
>sleep(100);
```

## getbykey

Gets value from array by name.

Format: **getbykey(name array)(name element)**

Example:

```
See example in readdata  
>getbykey(Colors) (Black) ;  
result = 0
```

if key is absent return **nan**.

## getbyvalue

Gets name from array by value.

Format: **getbyvalue(name array)(value element)**

Example:

```
See example in readdata  
>getbyvalue(Colors) (0) ;  
result = Black
```

if value is absent return **nan**.

## set

Sets value for variable and array element

Format for **ppl** code:

**set (var\_name | array\_name [index]) (value | array\_name [index])**  
**index:=value | ppl expression**

Format for **scr** code:

**set var\_name | array\_name [index] = value | scr expression**  
**index:=value | scr expression**

Command **set** checks whether index is out of bounds.

Examples:

```
>code ppl:  
>var (x) ;  
>set(x) (+ (1) (2)) ;  
>array(y[3]) ;  
>set(y[+ (1) (2)]) (0) ;  
  
>code scr:  
>var x;  
>set x = 1;  
>array y[3];  
>set y[x + 1] = 2 + 3;  
>set y[0] = y[1];
```



To calculate indexes command **set** in **scr**-mode creates temporary variables and deletes them at the end:

```
>code scr;  
>array (a) (1) (2) (3) (4) (5) (6) (7) ;  
>set a[1+2] = a[2+2]+ 1;
```

Generated **ppl**-code:

```
array (a) (1) (2) (3) (4) (5) (6) (7) ;  
var (#0[ + (1) (2) ]);  
var (#1[ + (2) (2) ]);  
set (a[#0]) (+ (a[#1]) (1)) ;  
del #0;  
del #1;
```

## setkvp

Sets key and value array element

Formats for **ppl** code:

**setkvp(array\_name [index])(key)(value | ppl expression)**

**index:=value | ppl expression**

Command **set** checks whether index is out of bounds. For setting key and value command **set** checks whether key already exists in array.

To get key and value it is possible by commands **getbykey** and **getbyvalue**.

**>code ppl:**

```
>array(y[3]);  
>setkvp(y[0]) (+ (1) (2)) ;  
>setkvp(y[1]) (one) (1) ;  
>setkvp(y[2]) (two) (2) ;
```

**>code scr:**

```
>var x = 1;  
>array y[3];  
>setkvp y[x + 1] = five, 2 + 3;  
>setkvp y[0] = null, 0;
```

## getvalue

Returns value of single var|const or array element.

Error: when argument is literal or not existed variable.

Format: **getvalue (var\_name) | getvalue(array\_name[index]**

**index:= value|ppl expression**

**Alias: get**

Examples:

```
>array (y[3]) (999);  
>write("getvalue(y[0]) = {0}") (getvalue (y[0]));  
result: getvalue (y[0]) = 999
```

## getname

Returns name of single var|const | array | array element as string.

Error: when argument is literal or not existed variable.

Format: **getname (name)**

Examples:

```
>var (x[ppl]);  
>write("{0} = {1}") (getname x) (getvalue x);  
x = ppl
```

Using operators getvalue and getname in function see examples\scr\func4.scr

## gettoken

Returns token in accordance with its number in string, string contains tokens, separated by "separator". Parts of string surrounded by quotes are passed.

As well gettoken may return number of tokens.

If number >= max number of tokens cmd returns **"Exception"**.

Format: **gettoken (string)(separator)(number)**

return: **item\_value**

**gettoken (string)(separator)**

return: **number of tokens**

Example:

```
1.  
>code ppl;  
>debugppl yes;  
>gettoken("Hello,World") (" ,") (0);  
result = Hello  
>gettoken("Hello,World") (" ,") (1);  
result = World  
>gettoken("Hello,World") (" ,") (2);  
result = Exception
```

```
2.
>code scr;
>var x = "\"Hello,World\"", PPL";
>debugppl yes
>gettoken(x)(",") (0);
result = Hello,World
>gettoken(x)(",") (1);
result = PPL
3.
>code ppl;
>gettoken("\"Hello,World\",PPL")(",") (1);
result = PPL
4.
>gettoken("Hello,World")(",");
result = 2
```

## Nodes and Leaves

### createnode

Creates node in path, default path is "**Global**", it is possible to create nodes in Global, Local and Functions Trees. It will be error if name already exists (see [recreate](#)).

Format: **createnode(path.name) | createnode path.name**

Examples:

```
> createnode (Node)
> createnode Node.SubNode
>d
-N1      NS
---N1    Global
-----N2 Node
-----N3      SubNode

>createnode Functions.Geo
```

### copynode

Copies one or more times node from path with new name, by default path is "Global"

Format:

**copynode (src node) (dst node) [number of copies]**

default number of copies: 1

Examples:

```
>rc tests\struct\personglob.ppl
>createnode Person;
>var(Person.Name);
>var(Person.Family);
>var(Person.DOB);
>var(Person.Gender);
>array(Person.cars[3]);
>copynode(Person)(Team);
Info [FuncCopyNode] Global node [Team] is created
>set(Team.Name)(Oscar);
>set(Team.Family)(Ko);
>set(Team.DOB)(2050);
>set(Team.Gender)(m);
>set(Team.cars[0])(Juke)(Nissan);
>set(Team.cars[1])(Qashqai)(Nissan);
>d
-N1      NS
---N2    Global
-----N3 Person  [Node]
-----L0          Name
-----L1          Family
```

```

-----L2      DOB
-----L3      Gender
-----N4      cars      [Array 3]
-----L0      #
-----L1      #
-----L2      #
-----N3 Team  [Person]
-----L0      Name      [Oscar]
-----L1      Family    [Ko]
-----L2      DOB       [2050]
-----L3      Gender    [m]
-----N1      cars      [Array 3]
-----L0      Juke       [Nissan]
-----L1      Qashqai    [Nissan]
-----L2      #
---N2      Local

```

### getnodes

Creates ppl\_array with fullnames of nodes till defined nesting. Processing results of commands getnodes and getleaves allows to find required information in hierarchical data dstructure.

Format:

**getnodes (top node)[(nesting)]("ppl\_array")**

Number of required nesting it is possible to get by command displaynode.

If (nesting) do not set node names under top\_node will be saved in ppl\_array.

For example there is file Data\Mng2.data

```

(Staff
  (Marketing
    (Managers
      (Personal Data1 [base]
        (Name [Benjamin])
        (Salary [6000])
        (Hobby
          (sport [tennis])
          (music [jazz])
        )
      )
    )
  )
  (Clerks
    (Personal Data2 [base]
      (Name [Oliver])
      (Salary [4000])
    )
  )
  .....
)

```

Read it:

```

>readdata (data\Mng2.data) ;
>d
-N2      NS
---N3     Global

```

```

-----N4 Staff
-----N5      Marketing
-----N6      Managers
-----N7      Personal Data1  [base]
-----L0      Name      [Benjamin]
-----L1      Salary    [6000]
-----N8      Hobby
-----L0              sport    [tennis]
-----L1              music    [jazz]
-----N6      Clerks
-----N7      Personal Data2  [base]
-----L0      Name      [Oliver]
-----L1      Salary    [4000]

```

or

```

>dn Staff
-----Variables and arrays-----
-N4      Staff
---N5      Marketing
-----N6 Managers
-----N7      Personal Data1  [base]
-----N8      Hobby
-----N6 Clerks
-----N7      Personal Data2  [base]
-----N7      Personal Data3  [base]
-----N8      Hobby
-----N7      Personal Data4  [base]
-----N7      Personal Data5  [base]
-----N8      Hobby

```

Get fullnames of nodes till nesting 7 and save in ppl\_array "persons":

```

>getnodes(Staff) (7) ("persons") ;
>d persons
-----Variables and arrays-----
-N4      persons [Array 21]
---L0      #      [Staff.Marketing.Managers.Personal Data1]
---L1      #      [Staff.Marketing.Clerks.Personal Data2]
---L2      #      [Staff.Marketing.Clerks.Personal Data3]
---L3      #      [Staff.Marketing.Clerks.Personal Data4]
---L4      #      [Staff.Marketing.Clerks.Personal Data5]
---L5      #      [Staff.Finance.Managers.Personal Data6]
---L6      #      [Staff.Finance.Managers.Personal Data7]
---L7      #      [Staff.Finance.Managers.Personal Data8]
---L8      #      [Staff.Finance.Clerks.Personal Data9]
---L9      #      [Staff.Finance.Clerks.Personal Data10]
---L10     #      [Staff.Finance.Clerks.Personal Data11]
---L11     #      [Staff.Operations management.Managers.Personal
                  Data12]
---L12     #      [Staff.Operations management.Managers.Personal
                  Data13]
---L13     #      [Staff.Operations management.Clerks.Personal Data14]
---L14     #      [Staff.Operations management.Clerks.Personal Data15]
---L15     #      [Staff.Operations management.Clerks.Personal Data16]

```

```
---L16 # [Staff.Operations management.Clerks.Personal Data17]
---L17 # [Staff.Operations management.Clerks.Personal Data18]
---L18 # [Staff.Operations management.Clerks.Personal Data19]
---L19 # [Staff.Human Resource.Managers.Personal Data20]
---L20 # [Staff.Human Resource.Clerks.Personal Data21]
```

## getleaves

Creates ppl\_array whose elements have names and values of node:

Format:

**getleaves(node)("ppl\_array")**

Example:

See previous example with command getnodes

```
>getleaves(Staff.Marketing.Managers.Personal Data1)("property")
>d property
-----Variables and arrays-----
-N4      property      [Array 2]
---L0    "Name"        [Benjamin]
---L1    "Salary"      [6000]
```

Full code of file Data\mng2.scr to find persons with salary = 2000:

```
var tmp;
var salary;
var name;
readdata (data\Mng2.data);
getnodes(Staff) (7) ("persons");
for(i,0,length(persons))
{
  if (isexist(property) == True)
  {
    del property;
  }
  getleaves(persons[i]) ("property");
  for(j,0,length(property))
  {
    set tmp = getname(property[j].name);
    if (tmp == "Name")
    {
      set name = property[j].value;
    }
    if (tmp == "Salary")
    {
      set salary = property[j].value;
      if (salary == 2000)
      {
        write("Name = {0,-15}\tSalary = {1}") (name) (salary);
      }
    }
  }
}
```

```
>rc data\mng2.scr
result:
Name = Charlotte      Salary = 2000
Name = Olivia         Salary = 2000
Name = Felix          Salary = 2000
Name = James           Salary = 2000
Name = Sophia          Salary = 2000
```

## struct

Struct is block statement for **scr mode** only

Format:

**struct name**

```
{
    var| array| |storage| struct name;
    var| array| |storage| struct name;
    .....
}
```

Example:

```
struct MyStruct
{
    var x = 0;
    struct N
    {
        array arr[] = {1,2,3};
        var w;
    }
}
```

The following ppl code will be generated:

```
createnode MyStruct;
var (MyStruct.x[0]);
createnode MyStruct.N;
array (MyStruct.N.arr[]) (1) (2) (3);
var (MyStruct.N.w);
```

```
>d;
-N2      NS
---N3    Global
-----L0 empty    (const)
-----N4 MyStruct    [Node]
-----L0      x      [0]
-----N5      N      [Node]
-----N6      arr     [Array 3]
-----L0      #      [1]
-----L1      #      [2]
-----L2      #      [3]
-----L0      w
```



## CopyStruct

CopyStruct is a function (see **Functions\CommonFunctions.ppl**) to create copy of struct one (by default) or several times. Node with destination name must be created before.

```
CopyStruct(src) (dst) (n[1]);
{
    if ( argc == 2 )
        copynode (src) (dst) (1);
    else
        copynode (src) (dst) (n);
}
```

Example 1:

See creation MyStruct in example for **struct**:

```
>createnode MMM;          // create destination node
>call CopyStruct("MyStruct","MMM");
>d;
-----N4 MMM                [MyStruct]
-----L0      x              [0]
-----N5      N                [Node]
-----N2      arr              [Array 3]
-----L0      #              [1]
-----L1      #              [2]
-----L2      #              [3]
-----L0      w
```

Example 2:

```
>createnode AAA;
>call CopyStruct("MyStruct","AAA") (2);
>d;
-----N4 AAA                [MyStruct]
-----N5      0
-----L0      x              [0]
-----N1      N                [Node]
-----N2      arr              [Array 3]
-----L0      #              [1]
-----L1      #              [2]
-----L2      #              [3]
-----L0      w
-----N5      1
-----L0      x              [0]
-----N1      N                [Node]
-----N2      arr              [Array 3]
-----L0      #              [1]
-----L1      #              [2]
-----L2      #              [3]
-----L0      w
>set AAA.0.x = 2;          // assignment
```

## Arithmetic operators

**+, -, \*, /, ^, %, ++, --**

and their aliases:

sum, sub, mul, div, pow, mod (see Aliases.data).

To use these aliases set **yes** for **ReplaceMathLogicOperators** in file **Configuration.data**.

By default **ReplaceMathLogicOperators** = **no** to decrease processing time.

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

**Sum, Sub, Mul, Div, Pow**

Examples in ppl prefix notation:

```
+ (x) (y)
* (+ (x) (y)) (- (z) (3))
```

Examples in scr infix notation:

```
>code scr;
> var z = x + y;
> var z = (x + y) * (z - 3);
```

Example with Aliases:

```
> var z = (2 plus 3) mul 4;
```

## Logical operators

**<, <=, >, >=, ==, !=, &&, ||, xor**

xor only for ppl mode

and their aliases:

lt, le, gt, ge, eq, ne, and, or (see Aliases.data).

To use these aliases set **yes** for **ReplaceMathLogicOperators** in file **Configuration.data**.

By default **ReplaceMathLogicOperators** = **no** to decrease processing time.

These are binary operators.

Do not confuse with functions names in file **CommonFunctions.ppl**:

**LT, LE, GT, GE, EQ, NE, AND, OR, XOR**

Examples in ppl prefix notation:

```
== (x) (y)
&& (== (x) (y)) (== (z) (3))
```

Examples in scr infix notation:

```
x == y
(x == y) && (z == 3)
```

## Variables and Arrays

### var

Creates a single variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

**var (name) | (name[init value])**

**name:= [node path]name**

**node path:= node. | node**

**init value:= value | ppl expression**

**ppl expression:=value | prefix notation expression**

Examples:

```
>var (greeting["Hello"]);  
>var (x);  
>var (y[+(2) (3)]);
```

Format **scr**:

**var name | name = init value**

**name:= node path.name**

**node path:= node. | node**

**init value:= value | scr expression**

**scr expression:= value | infix notation expression**

Examples:

```
>code scr;  
>createnode N1;  
>createnode N1.N2;  
>var greeting = "Hello";  
>var x;  
>var N1.N2.z = 2 + 3;
```

### const

Creates a single constant variable in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Format **ppl**:

**const (name[init value])**

**name:= [node.]name**

**init value:= value | ppl expression**

**ppl expression:=value | prefix notation expression**

Example:

```
>const (x[0])  
>const (y[+(2) (3)]);
```

Format **scr**:

**const** name = init value  
**name**:= node path.name  
**node path**:= node. | node  
**init value**:= value | scr expression  
**scr expression**:= value | infix notation expression

Examples:

```
>createnode N1;  
>code scr;  
>const greeting = "Hello";  
>const radian = 180 / Math.PI();  
result = 57.29577951308232
```

## array

Creates single-dimensional array in Global or in Local function scope. It will be error if array with same name already exists (see [recreate](#)).

Format **ppl**:

**array**(name [length]) [ (init value)]  
**array**(name)(1<sup>st</sup> item)(2<sup>nd</sup> item)..  
**name**:= node path.name  
**node path**:= node. | node  
**length**:= value | ppl expression  
**init value**:= value | ppl expression  
**item**:= value | ppl expression  
**ppl expression**:=value | prefix notation expression

Examples:

```
>var (x[10]);  
>array (y[3]);  
>array (y[(x)(2)])(0); // init by 0 all 5 elements  
>array (y[x])(*(x)(3)); // init by 30 all 10 elements  
>array (y)(1)(x)(+(1)(2)); // init 3 elements array = 1,10,3
```

Format **scr**:

**array** name[length];  
**array** name [length] = init value;  
**array** name [] = {1<sup>st</sup> item, 2<sup>nd</sup> item,...};  
**name**:= node path.name  
**node path**:= node. | node  
**length**:= value | scr expression  
**init value**:= value | scr expression  
**item**:= value | scr expression

**scr expression:=value | infix notation expression**

Examples:

```
>code scr;  
>array y[3];  
>array y[1+2] = 0;      // init by 0 all 3 elements  
>array y[] = {1,2,1+2}; // init 3 elements array = 1,2,3  
>var x = 1;  
>array y[x+2];
```

To access an array element you need to calculate index as a separate variable:

```
>code scr;  
>var x = 1;  
>array y[] = {1,2,3,4,5};  
var index = x + 1;  
>write(y[index]);      // or write(y[2])
```

Only operator set can use index as expression

```
>set y[x + 1] = 100;
```

Creation array with **length = 0**:

```
array arr; or  
array arr[]; or  
array arr[0];
```

In the following sample array with **length = 0** is created preliminary and reallocated in function **Directory.GetDirectories** in accordance with real length:

```
> array Dir.dir; // or array Dir.dir [0];  
>call Directory.GetDirectories(getname(Dir.dir), "c:\\users\\");
```

## realloc

Changes length of array, all elements are saved in changed array.

Format: **realloc(array name)(new length) [(init\_value)]**

Examples:

```
>array(y[5])(0);
>realloc(y)(10);
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 10]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
-----L3      #      [0]
-----L4      #      [0]
-----L5      #
-----L6      #
-----L7      #
-----L8      #
-----L9      #
---N2    Local
>realloc(y)(3);
>d;
-N1      NS
---N2    Global
-----N3 y      [Array 3]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
---N2    Local
```

If init\_value is specified this value will be set in all elements of the new array. If init\_value is not specified old values are saved in the new array. Size of the new array can be smaller or larger than the old one.

It is possible to use realloc for storage on Row level.

```
>rc examples\scr\testswrite.scr
>>storage(s)(3)(4)(5);
>realloc(s.0.0.Row)(3);
>ssetrow(s)(0)(0) (1)(2)(3);
>sinit(s)(0);
>realloc(s.0.1.Row)(10);
>ssetrow(s)(0)(1) (1)(2)(3)(4)(5)(6)(7)(8)(9)(10);
>realloc(s.0.2.Row)(15);
>ssetrow(s)(0)(2) (1)(2)(3)(4)(5)(6)(7)(8)(9)(10)(11)(12)(13)(14)(15);
>realloc(s.1.1.Row)(10);
>ssetrow(s)(1)(1) (1)(2)(3)(4)(5)(6)(7)(8)(9)(10);
>realloc(s.2.1.Row)(10);
>ssetrow(s)(2)(1) (1)(2)(3)(4)(5)(6)(7)(8)(9)(10);
>swrite(s);
```

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14

```
-----NS.Global.s.0-----
[0] 0 0 0
[1] 1 2 3 4 5 6 7 8 9 10
[2] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
[3] 0 0 0 0 0
```

```
-----NS.Global.s.1-----
[0] 0 0 0 0 0
[1] 1 2 3 4 5 6 7 8 9 10
[2] 0 0 0 0 0
[3] 0 0 0 0 0
```

```
-----NS.Global.s.2-----
[0] 0 0 0 0 0
[1] 1 2 3 4 5 6 7 8 9 10
[2] 0 0 0 0 0
[3] 0 0 0 0 0
```

The following array commands are to add, remove, clear, reverse items in array.

### **array.push**

Adds a new item to an array as last, returns a new size of array.

Format **ppl: array.push (array\_name)(item\_value) |**  
**array.push (array\_name)(item\_name)(item\_value)**

### **array.pop**

Returns the latest **item name and itemvalue, separated by comma**, and removes item from array or **Empty**(if array is empty) .

Format **ppl: array.pop (array\_name)**

Example:

```
>code scr
code: scr
>array y[] = {1,2,3};
>var result = "";
>set result = array.pop(y);    // return #,3
>write#("name={0}value={1}",
        gettoken(result) (",") (0) ,gettoken(result) (",") (1) );
name=# value=3
>writearray y row;
-----Array y-----
1, 2
```

### **array.reverse**

Reverses items order in array, returns a size of array;

Format **ppl: array.shift (array\_name)**

### **array.shift**

Removes the first item of the array, returns a new size of array.

Format **ppl: array.shift (array\_name)**

### **array.remove**

Removes item by index, returns a new size of array.

Format **ppl: array.remove (array\_name)(index)**

### **array.clear**

Removes all items from array, returns 0.

Format **ppl: array.clear (array\_name)**



### **array.unshift**

Adds a new item as first to an array, returns a new size of array.

Format **ppl: array.unshift (array\_name)(item\_value) |**  
**array.unshift (array\_name)(item\_name)(item\_value)**

### **array.insert**

Inserts item before item with index, returns a new size of array.

Format **ppl: array.insert (array\_name)(index)(item\_value) |**  
**array.insert (array\_name)(index)(item\_name)(item\_value)**

See array commands examples in **examples\ArrayCmds\Samples.scr**.

Additional array service see in file **CommonFunctions.Data**.

## Storage

Service of multi-dimensional arrays is realized by storage operators in mode ppl (parameters with prefix expressions in parentheses, but may be used also in mode scr (see Examples 3).

### storage

Creates single variable, single-dimensional or multi-dimensional array with dimension from 1 to N in Global or in Local function scope. It will be error if name already exists (see [recreate](#)).

Storage contains several levels of arrays, name of the topmost level is name of storage, name of the bottommost arrays in each level is **Row**. Names of intermediate levels are array index in level. To set different length arrays on Row level use realloc. (see examples\scr\testswrite.scr).

Format **ppl**:

Format: **storage (name)[(length dim1)][(length dim2)]...**

**name:= node path.name**

**node path:= node. | node**

**length:= value | ppl expression**

**ppl expression:=value | prefix notation expression**

Examples:

```
(1)
>storage (x); - variable
>d;
-N1      NS
---N1    Global
-----L0 x
```

```
(2)
>storage (x) (2); - single-dimensional array
>d;
-N1      NS
---N1    Global
-----N3 x      [Storage 1 2]
-----N4      Row      [Array 2]
-----L0      #
-----L1      #
[Storage 1 2] - dimension length
```

```
(3)
>code ppl
>storage (x) (+ (2) (3)) - single -dimensional array [Storage 1 5]
or same result
>code scr;
>var y = 2 + 3;
>storage (x) (y); // single-dimensional array, length = 5
(4) storage (x) (2) (3) - two-dimensional array
```

```
>d
-N1      NS
---N2    Global
-----N3 x      [Storage 2 2x3]
-----N4      0      [Array element]
-----N5      Row    [Array 3]
-----L0      #
-----L1      #
-----L2      #
-----N4      1      [Array element]
-----N5      Row    [Array 3]
-----L0      #
-----L1      #
-----L2      #
[Storage 2 2x3] - dimension length x length
```

(5) storage(x) (3) (4) (5) (100) - four-dimensional array

## sinit

Init storage

Format: **sinit (name)(init value)**

**init value:= value | ppl expression**

Examples:

```
>storage (x) (2) (3) ;
>sinit (x) (0) ;
-N1      NS
---N2    Global
-----N3 x      [Storage 2 2x3]
-----N4      0      [Array element]
-----N5      Row    [Array 3]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
-----N4      1      [Array element]
-----N5      Row    [Array 3]
-----L0      #      [0]
-----L1      #      [0]
-----L2      #      [0]
```

## sget

Gets value of element in storage

Format: **sget (name)(index1)(index2)...**

Examples:

```
>sget(stor);      // get value of single-variable
>sget(stor) (0);  // get value of single-dimensional array, index=0
```

```
// get value of two-dimensional array,stor[0][0]
>sget(stor) (0) (0) ;
```

## sset

Sets value for element in storage

Format: **sset (name)(index1)(index2)(value)**

Examples:

```
>sset(stor) (0) ; // set value of single-variable = 0
```

```
// set value of single-dimensional array,stor[0]= 1
>sset(stor) (0) (1) ;
```

```
// set value of two-dimensional array,stor[0][0] = 1
>sset(stor) (0) (0) (1) ;
```

## swrite

Displays elements values of storage

Format: **swrite(name) [(max\_window\_width = 100)]**

Limit for CPPL.exe max\_window\_width = Console.WindowWidth = 120

NoLimit for WPPL.exe

Examples:

```
>storage (x) (3) ;
>sinit(x) (0) ;
>swrite(x) (50) ;
```

	0	1	2
-----NS.Global-----			
[x]	0	0	0

```
>storage(s) (5) (3)
>sinit(s) (0)
>swrite(s)
```

	0	1	2
-----NS.Global.s-----			
[0]	0	0	0
[1]	0	0	0
[2]	0	0	0
[3]	0	0	0
[4]	0	0	0

```
>swrite(s) (30)
```

	0	1	2
-----NS.Global.s-----			
[0]	0	0	0
[1]	0	0	0
[2]	0	0	0

```
[3]    0        0        0
[4]    0        0        0
```

```
>storage(xxx)(3)(3)(5)
>sinit(xxx)(0)
>swrite(xxx)(40)
    0    1    2    3    4

-----NS.Global.xxx.0-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
-----NS.Global.xxx.1-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
-----NS.Global.xxx.2-----
[0]  0    0    0    0    0
[1]  0    0    0    0    0
[2]  0    0    0    0    0
```

## sinfo

Displays length of each dimension in storage

Format: **sinfo(name)**

Examples:

```
>sinfo(y);
result = Storage 1 5 // single-dimensional array length 5
```

After using realloc for storage Row it will be written:

```
>storage(s)(3)(5);
>realloc(s)(0)(10);
>sinfo(s);
result = Storage 2 reallocated
```

## ssetrow

Sets value for elements of the lowest level.

Format: **ssetrow(name)(ind1)(ind2)(indN)... (elem1)(elem2)(elemM)...**

Examples:

```
// N = 2, M=3
>storage(y) (2) (3) ;
>ssetrow(y) (0) (1) (2) (3) ;
>ssetrow(y) (1) (4) (5) ;
>ssetrow(y) (1) (4) (5) (6) (7) (8) ;
```

```
Error: [FuncStorageSetRow] wrong format, number of parameters
[7] > [5]
>swrite(y);
-----NS.Global.y-----
[0]      1                2                3
[1]      4                5
```

## Backup & Recovery

### savedata

Saves data from node to file with extension **.data** or **.json**

If node is root, all root contents will be saved.

Format: **savedata(filename.data | filename.json)[(node)]**

Default node: **NS.Global**

Examples:

1.

```
>createnode Node1;
>var(Node1.x[0])(Node1.y[1]);
>savedata (Examples\ppl\f3.json) (Global.Node1);
```

2.

```
>savedata (Data\Colors1.data) (Colors);
```

3.

```
>rc examples\ppl\json.ppl;
>createnode Node1;
>var(Node1.x[0])(Node1.y[1])(a[2])(b[3]);
>array(y[3])(0);
>set(y[0])(one)(1);
>set(y[1])(two)(2);
>set(y[2])(three)(3);
>var(c[true])(d[family]);
>array(cars)(Ford)(Nissan)(Renault);
>savedata (Examples\ppl\f3.json);
>shell(type f3.json)
{
  "Global":
  {
    "Node1": "Node"
    {
      "x":0,
      "y":1
    },
    "a":2,
    "b":3,
    "y":
    [
      1,
      2,
```

```
    3
    ],
    "c": "true",
    "d": "family",
    "cars":
    [
    "Ford",
    "Nissan",
    "Renault"
    ]
  }
}
```

## readdata

Reads data from file with extension **.data** to Aliases, Configuration and NS.Global node,**not to Local**.

Format: **readdata(filename.data)[(node)]**

Default node: **NS.Global**

Examples:

```
>readdata(Data\Colors.data)
>d
-N  NS
---N Global
-----N Colors
-----L0      Black      [0]
-----L1      Blue       [9]
-----L2      Cyan       [11]
-----L3      DarkBlue   [1]
-----L4      DarkCyan   [3]
-----L5      DarkGray   [8]
-----L6      DarkGreen  [2]
-----L7      DarkMagenta [5]
-----L8      DarkRed    [4]
-----L9      DarkYellow  [6]
-----L10     Gray       [7]
-----L11     Green      [10]
-----L12     Magenta    [13]
-----L13     Red        [12]
-----L14     White      [15]
-----L15     Yellow     [14]
```

Each item in such array has key (Black, Blue,...) and value(0,9,...) , use [getbykey](#) and [getbyvalue](#).



## Control Flow

### if, else

The meaning of the block "if-else" does not differ from the generally accepted.  
About using statements terminator ";" in if see [Base Concepts](#).

Format **ppl**:

```
if (condition)
(
    (statement)
    (statement)
    [ (else
        (
            (statement)
            (statement)
        )
    ) ]
);
```

Here expression in prefix notation.

Statement in ppl mode.

Format **scr**:

```
if (condition)
{
    statement;
    statement;
    [else
    {
        statement;
        statement;
    } ]
}
```

Here expression in infix notation.

Statement in ppl or scr mode.

Example ppl mode:

```
var(x[1]);
var(y[1]);
if (==(x)(y))
(
    (write(true))
    (write(TRUE))
    else
    (
        (write(false))
        (write(FALSE))
    )
)
);
true
TRUE
>write(end);
end
```

Example scr mode:

```
var x = 1;
var y = 1;
if ( x == y )
{
    write(true);
    write(TRUE);
    else
    {
        write(false);
        write(FALSE);
    }
}
write(end);
```

## switch, case, default

switch statement – for select one from several case blocks to be executed.  
About using statements terminator ";" in switch see [Base Concepts](#).

Format ppl:

```
switch(expression)
(
    (case1) [(case2)...]
    (
        (statement)
        (statement)
        ...
    )
    (caseN) ...
    (
        (statement)
        (statement)
        ...
    )
    ...
    [ (default)
    (
        (statement)
        (statement)
        ...
    ) ]
);
```

Here expression in prefix notation.  
Statement in ppl mode.

Format scr:

```
switch(expression)
{
    case <value>:
    case <value>:
        statement;
    break;
    case <value>:
        [ statement;
    break;
    default:
        statement;
    break; ]
}
```

Here expression in infix notation.  
Statement in ppl or scr mode.

Examples:

Format ppl:

1.

```
switch(x)
(
  (1) (3)
  (
    (write("Cases 1 & 3"))
  )
);
```

2.

```
var (x[1]);
switch (x)
(
  (1) (3)
  (
    (write("Case 1 & 3"))
  )
  (2)
  (
    (write("Case 2"))
  )
  (default)
  (
    (write("Default"))
  )
);
```

Result:

Case 1 & 3

1. Format scr

```
var x = 2;
switch(x)
{
  case 1: case 3:
    write("Case 1 & 3");
    break;
  case 2:
    write("Case 2");
    break;
  default:
    write("Default");
    break;
}
```

## loop,do

Iteration block for ppl mode only.

About using statements terminator ";" in loop see [Base Concepts](#).

Format:

```
loop (iteration var) (begin) (end) [(increment)]  or  
loop () //infinity loop
```

```
(do  
  (  
    (statement)  
    (statement)  
    ...  
  )  
)
```

**begin:= value|ppl expression**

**end:= value|ppl expression**

**increment:= value|ppl expression**

By default increment = 1. Increment may positive or negative.

Statement in ppl mode.

Examples:

```
loop (i) (0) (10) (1)      // or loop (i) (10) (0) (-1)  
(do  
  (  
    (write("i = {0}") (i))  
  )  
)  
);
```

See infinity example – greatest common factor (gcf) calculation in [for](#)

## for

Iteration block for **scr mode** only.

About using statements terminator ";" in for see [Base Concepts](#).

Format:

```
for(iteration var, begin, end [, increment]) or
```

```
for() // infinity for
```

```
{
```

```
    statement;
```

```
    statement;
```

```
    ...
```

```
}
```

By default increment = 1. Increment may positive or negative.

Statement in ppl or scr mode.

Examples:

```
var x;
for(i, 0, 10, 1)
{
    set x = i * 2;           // scr statement
    write("x = {0}") (x);    // ppl statement
}
```

Example with Infinity for:

```
function gcd(x,y,z)
{
    if(isinteger (x) == "False")
    {
        write#("not integer value x={0}",x);
        return;
    }
    if(isinteger (y) == "False")
    {
        write#("not integer value y={0}",y);
        return;
    }
    for()    // infinity for
    {
        if (x > y)
        {
            set x = x - y;        // or Sub(x) (x) (y) ;
        }
        if (x < y)
        {
            set y = y - x;        // or Sub(y) (y) (x) ;
        }
        if (x == y)
        {
            set z = x;
            return;
        }
    }
}
var z = 0;
var x = 14144;
var y = 26163;
gcd(x) (y) (z) ;
write#(gcd = {0},z) ;
//result
//gcd = 17;
```

## break

Exit from loop (ppl mode) or from for (scr mode) or end of case in switch block.

Example:

```
for(i, 0, 4, 1)
{
    if (i == 2)
    {
        write("true i = {0}") (i);
        break;
    }
};
```

## **continue**

Continue executing in loop (ppl mode) or in for (scr mode).

Example:

```
loop(x) (0) (5) (1)
(do
  (
    (write("x={0}") (x) )
    (if (==(x) (3))
      (
        (write("x = {0} continue") (x) )
        (continue)
      )
    )
  )
);
```



## Input and Output

### write

Writes the string value to the standard output stream.

String interpolation ( $\$ "x"$ ) is not supported. If string value contains "Error:" it will be wrote in red color in cppl.exe or in wppl.exe.

Format:

**write(value) | write(c# format)( value )(value)...**

**value:=value | ppl expression with prefix notation**

Example:

```
>var (x[0]);
>write(x);
>write("{0}{1}") ("x=") (x); // like c# write("{0}{1}") ("x=",x);
//quote in string
>write("ppl\tlanguage"); // ppl\tlanguage
//tab in string
>write("ppl\tlanguage"); // ppl language
//newline in string
>write("ppl\r\nlanguage"); // ppl
//language

>write(12col);
Result: 12col
>write("Error: wrong name {0}") (12col);
Result: Error: wrong name 12col
```

This operator is used in ppl and scr mode.

```
>code scr;
>var x = 2*5; // scr expression is calculated in var
>write("{0} {1}") ( "x = " ) (x);
>code ppl
>write("{0}") (* (2) (5)); // ppl expression
```

### write#, writeline

Like as write, for mode scr only, each argument is not enclosed in parentheses.

Format:

**write#(arg) | write#("c# format", arg1 , arg2,...)**

**writeline(arg) | writeline("c# format", arg1 , arg2,...)**

**arg:= <literal> | <scr expression with infix notation>**

Example:

```
>write#("{0} {1}", aaaa,1+3)
Result: aaaa 4
```

## writearray

Writes array contents to the standard output stream. By default writearray writes array elements into the column. Writearray writes array elements into the row by second argument "**row**".

Format **ppl**:

**writearray** ([node.]array\_name) [(row)]

Format **scr**:

**writearray** [node.]array\_name [row]

or

**writearray** ( [node.]array\_name [,row] )

Examples:

1.

```
>code scr
>array y[] = {1,2,3}
>writearray y
-----Array y-----
[0]      1
[1]      2
[2]      3
>writearray y row
-----Array y-----
1, 2, 3
```

2.

```
>code scr;
>storage(x) (2) (3);
>sinit(x) (0);
// write the bottommost arrays in storage
>writearray (x.0.Row);
[0]      #      0
[1]      #      0
[2]      #      0
>writearray (x.1.Row, row);
0, 0, 0
```

## readline

Reads the next line of characters from the standard input stream. Result will be passed to calling operator.

Format: **readline()**

Examples:

```
var(x) ;
>set(x) (readline()) ;
>Enter:
>>Hello
>d;
-N1      NS
---N1    Global
-----L0 x      [Hello]
```

## Functions

Function library **CommonFunctions.ppl**, defined in file **Configuration.data** as **default\_loaded\_functions**, loads automatically and reloads when command **init** executes. It includes 2 types of functions:

- Mathematical and Logical functions,
- Array services and other functions.

Mathematical and Logical functions:

```
Sum (result)(n1)[( n2)]
Sub (result)(n1)[( n2)]
Mult (result)(n1)[( n2)]
Div (result)(n1)[( n2)]
Pow (result, n1, n2)
PlusPlus (result)    // like c#: ++(var)
MinusMinus (result)  // like c#: --(var)
LT (result, n1, n2)
LTEQ (result, n1, n2)
GT (result, n1, n2)
GTEQ (result, n1, n2)
EQ (result, n1, n2)
NOTEQ (result, n1, n2)
AND (result, n1, n2)
OR (result, n1, n2)
XOR (result, n1, n2)
```

These functions replace using prefix notations. Result are returned in 1<sup>st</sup> parameter and does not passed to the next command:

```
>var (z[0]);
>var (x[1]);
>set (z) (Sum(x) (1));    // error
>Sum(z) (x) (1);         // right
```

Examples:

```
1.
>var (x[1]);
>var (z);
>Sum(z) (x) (1);    // set z = x + 1
>Sum(x) (2);        // set x = x + 2
>d
-N2      NS
---N3    Global
-----L4 x      [3]
-----L5 z      [2]
```

2. This sample returns **wrong result**:

```
>var(x[5]);  
>Sum(x)(x)(2);  
>d x  
-----Variables and arrays-----  
-L4      x      [5]  
>Sum(x)(2);    // right, x = x + 2
```

3.

```
>code scr;  
>call Sum(x,2,3);  
>call Sum(x,2+3);  
>Sum(x)(+(2)(3));
```

User may create own functions file, like CommonFunctions.ppl, and set it in file

**Configuration.data** as **UserFunctionsN** or load it:

```
>rc user_functions.ppl|scr;
```

Files, defined in **Configuration**, load their function only and do not execute any command, commands in files, loaded by command rc (readcode) are executed one after another.

Array services and other functions:

**CopyStruct (src, dst, n)** – create copy/copies of structure

Example:

See examples\struct\test.scr:

```
struct MyStruct
{
    var x = 0;
    struct N
    {
        array arr[] = {1,2,3};
        var w;
    }
}
createnode MMM;
call CopyStruct("MyStruct", "MMM");
createnode NNN;
call CopyStruct("MyStruct", "NNN", 2);
dn;
//results:
code: scr
-N2      NS
---N3    Global
-----N4 MyStruct      [Node]
-----N5      N          [Node]
-----N6      arr        [Array 3]
-----N4 MMM          [MyStruct]
-----N5      N          [Node]
-----N2      arr        [Array 3]
-----N4 NNN          [MyStruct]
-----N5      0
-----N1      N          [Node]
-----N2      arr        [Array 3]
-----N5      1
-----N1      N          [Node]
-----N2      arr        [Array 3]
```

**CsvToArray (var:str, array:arr)** – to fill array from string data separated by comma

**ArrayToCsv (array:arr, var:str)** – copy to string separated by comma data from array

**ArrayIsExist (result, array:arr, value)** – return True/False if devined value exists in array

**ArrayIndexOf (result, array:arr, value)** – return the index of the first occurrence within array or -1.

**ArrayLastIndexOf (result, array:arr, value)** – return the index of the last occurrence within array or -1.

Example:

```
array my_array;
call CsvToArray("1,2,3,,1,5",my_array);
writearray my_array row;

var result;
call ArrayToCsv(my_array,result);
write#("result = {0}",result);

call ArrayIndexOf (result, my_array, 3);
write#("index = {0}",result);

call ArrayLastIndexOf (result, my_array, 1);
write#("index = {0}",result);

//results:
1, 2, 3, , 1, 5
result = 1,2,3,,1,5
index = 2
index = 4
*/
```

See `examples\ArrayFunc\SamplesFunc.scr`.

## function

Functions must be declared before called.

Functions are saved in Tree **Functions** or in Tree **Global** for later call.

Functions return data via parameters, like a classic procedure.

When function is called **by name** (in mode **ppl** or **scr**) each argument must be enclosed in parentheses.

When function is called by command 'call' (in mode **scr** only) each argument not must be enclosed in parentheses.

### Limitations:

1. For passing array member use 2 arguments [\(sample\)](#):

array name, index array member  
or temporary variable:

```
>array y[] {1,2,3};  
>var x = 10;  
>set tmp = y[0];  
>call Sum(x,tmp);  
>write#("x={0}",x)  
x=11
```

2. If argument value will be changed in function this argument can be used only one time when function is called(see example [Sum\\_wrong\\_result](#)).

Format **ppl**:

Statement terminator ';' does not follow after statements within function.

### function

```
(  
  name  
  parameter_list  
  ( function body )  
);  
name::= identifier  
parameter_list::= parameter [parameter_list]  
parameter::= (identifier) | (identifier[default value]) | empty  
function body::= (statement1) [(statement2) (statementN)]  
identifier::= [var] | [array] :<name>
```



Format **scr**:

Statement terminator ';' always follows after each type of statements.

```
function   name
            (parameter_list)
            {
                function body
            }
name::= identifier
parameter_list::= parameter, [parameter_list]
parameter::=
    identifier | identifier[default value] | identifier = default value | empty
function body::= statement1 [ statement2 statementN ]
identifier::= [var] | [array] :<name>
By default parameter type is var.
```

Examples:

```
>code scr
1.Function func ()
{
    write#("func");
}
2. function func (n,m[10])    // = func (var:n,var:m[10])    or
    //function func (n,m = 10)
{
    write#(funcname());
}
3.function func (array: n)
{  write#( funcname());  }
```

```
4.code ppl;
function
(
    test2(n)
    (
        (write(n))
    )
);
function
(
    test()
    (
        (loop (i) (0) (5) (1)
            (do
                (
                    (test2(i))
                )
            )
        )
    )
);
```

```
    )
  )
)
);
test();    // function call
```

```
5.
code scr;    // (see examples\scr\func.scr)
function sum_arr(array:n,array:m)
{
  // dstree;
  for(i,0,length(n),1)
  {
    write#("[{0}]  [{1}]" ,i, n[i] + m[i]);
  }
}
array x[] = {1,2,3,4,5};
array y[] = {6,7,8,9,10};
sum_arr(x)(y);    // function call

result:
[0]  [7]
[1]  [9]
[2]  [11]
[3]  [13]
[4]  [15]
```

In the following example (see examples\scr\func4.scr) parameter index default value = 0 and this parameter may be omitted when the function is called.

Array and member array index are passed as 2 arguments.

```
6. code scr;
function func (array:arr, var:index[0])
{
  write#("{0}[{1}] = {2}",getargname(arr),index, arr[index]);
}
array y[] = {1,2,3,4};
func(y);
call func(y);    // same as previous line
call func(y,0);
call func(y,1);
call func(y,2);
=====result=====
y[0] = 1
y[0] = 1
y[0] = 1
y[1] = 2
y[2] = 3
```

7. Call function from node saved in Tree Global

```
code ppl;
createnode New;
function
(
    New.func(name)      // public
    (
        (write(name))
    )
);
function
(
    New._hfunc(name)    // private
    (
        (write(name))
    )
)
New.func("Greetings!");
8. Call function from node saved in Tree Functions
code ppl;
createnode Functions.New;
function
(
    Functions.New.func(name)      // public
    (
        (write(name))
        (Functions.New._hfunc(name))
    )
)
);
function
(
    Functions.New._hfunc(name)    // private
    (
        (write(name))
    )
)
);
Functions.New.func("Greetings!");
```

```
9. Recursion example
var tmp = 0;
function rec(x)
{
    set tmp = tmp + 1;
    write#("tmp={0}",tmp);
    if (tmp == x)
    {
        return;
    }
    rec(x);
}
rec(5);
```

Examples with using public and private functions in Trees Functions and Global it is possible to find in directory Examples\Access.

## call

Command 'call' calls function in mode **scr**, it is possible to use expression in infix notation as arguments, do not need to enclose in parentheses each argument when function is called.

Format:

**call function\_name(arg1,arg2,...)**

Examples:

```
1.
>code scr
>var x = 0;
>call Sum(x,4 + 1);
>d x
-----Variables and arrays-----
-L1      x      [5]
```

1.Call function without arguments or with one not-expression argument by command 'call' and directly(without 'call') is same:  
call func(123); same as func(123);

2. To get return of function, called by 'call',  
run 'debugppl yes' before:

```
>debugppl yes;
>call (Math.PI());
result = 3.141592653589793
```

3. For transfer return of function to the next command  
do not use 'call'

```
>write#( Math.PI() );
result = 3.141592653589793
```

```
4.
>write#(call Math.PI()); // error
>set x = call Math.PI(); // error
>set x = Math.PI();
3.141592653589793
```

It is possible to pass array by this manner:

**call function\_name({item1,item2,...},arg2,...)**

Example: (see examples\CallFunc\funcarr2.scr and examples\CallFunc\funcarr2.ppl)

```
function SumArray(array:arr,var:result)
{
    var x;      // this var to pass to function array element
    for(i,0,length(arr))
    {
        set x = arr[i];
        Sum(result)(x);
    }
}
```

```
var result=0;
call SumArray({1,2,3,4,5},result);
write#("result = {0}",result);
```

instead of:

```
array arr[] = {1,2,3,4,5};
call SumArray(arr,result);
```

Preprocessor generates the following ppl-code:

```
function
(
    SumArray (array:arr) (var:result)
    (
        (set (result) (0))
        (
            loop (i) (0) (length(arr)) (1)
            (
                do
                (
                    (Sum(result) (result) (arr[i]))
                )
            )
        )
    )
);
var (result);
array (arg_array0) (1) (2) (3) (4) (5 );
SumArray (arg_array0 ) ( result );
del arg_array0;
write ("result = {0}") (result);
```

## return

Exit from function or from script.

Example:

```
function f()
{
    for(i, 0, 5, 1)
    {
        write(i);
        if (i == 3)
        {
            return;
        }
    };
};
f();
write("end of script");
```

## funclist

Displays function names and their parameters from node Functions.

Format:

**funclist| finclist()**

Example:

>funclist;

```
-----Function List-----
Sum  (result, n1, n2)
Sub  (result, n1, n2)
Mult (result, n1, n2)
Div  (result, n1, n2)
Pow  (result, n1, n2)
PlusPlus (result)
MinusMinus (result)
LT    (result, n1, n2)
LTEQ  (result, n1, n2)
GT    (result, n1, n2)
GTEQ  (result, n1, n2)
EQ    (result, n1, n2)
NOTEQ (result, n1, n2)
AND   (result, n1, n2)
OR    (result, n1, n2)
XOR   (result, n1, n2)
```

## funcname

Returns the current function name.

Format:

**funcname()**

Example:

```
>write(funcname());  
main
```

## argc

Returns number of arguments

Format:

**argc()**

Example:

```
function Sum (result,n1,n2 = "")  
{  
    write#("argc = {0}",argc());  
    if (argc() == 2)  
        set result = result + n1;  
    else  
        set result = n1 + n2;  
}  
>code scr;  
> var x = 0;  
>call Sum(x,1);  
>write#("x = {0}",x);  
Result:  
argc = 2  
x = 1
```

## getargname

Returns argument name (or argument value if it is literal) by parameter name

Format:

**getargname (parameter\_name)**

Example:

```
function a(n)  
{  
    write#("arg_name for param {0} =  
        {1}]",getname(n),getargname("n"));  
}  
var i = 0;  
a(i);  
//result:  
//arg_name for param n = [i]
```



## Delegates and callbacks

There are 4 operators for using delegates:

delegate – creation delegate

dlgtinstant – creation delegate instant

dlgtset - setting the function to delegate instant

dlgtcall – call function by delegate instant

### delegate

delegate is created as an array whose elements define the method parameters.

Prefix “**delegate\_**” is added to delegate name for internal using.

Format **ppl**:

**delegate** | **dlgt** (<delegate name>) (param1) (param2)...

**param:=** var\_name | var:<var\_name> | array:<array\_name>

Format **scr**:

**delegate** | **dlgt** <delegate name> (param1, param2,...)

Example (**scr-mode**):

```
>delegate MyDelegate (var:x,array:arr);
```

### dlgtinstant

dlgtinsant is created as an array with 2 elements, first is delegate name, second is empty and will be set by dlgtset. Delegate parameters types must be matched types of function parameters . Prefix “**dlgtinstant\_**” is added to delegate instant name for internal using.

Format **ppl**:

**dlgtinstant** (<delegate instant name>)(<delegate name>)

Format **scr**:

**dlgtinstant** <delegate instant name><delegate name>

Example(**scr-mode**):

```
>dlgt dd (var:x,array:arr);
>dlgtinstant instant dd;
>d;
-N2      NS
---N3    Global
-----L0 empty    (const)
-----N4 delegate_dd      [Array 2]
-----L0      #          [var:x]
-----L1      #          [array:arr]
-----N4 dlgtinstant_instant [Array 2]
-----L0      #          ["delegate_dd"]
-----L1      #
```

## **dlgtset**

dlgtset sets function name as second element in **dlgtinstant** array.

Format **ppl**:

**dlgtset (delegate instant name)(function name)**

Format **scr**:

**dlgtset delegate instant name function name**

Example (**scr-mode**):

```
// see previous example with dlgt and dlgtinstant
function f1(var:x,array:arr)
{
    write#("x = [{0}]",x);
    writearray arr;
}
>dlgtset instant f1;
```

## **dlgtcall**

dlgtcall calls function defined in dlgtset.

Format **ppl**:

**dlgtcall(delegate instant name)(arg1)(arg2)(arg3)...**

Format **scr**:

**dlgtcall delegate instant name(arg1,arg2,arg3,...)**

Example:

```
// see previous examples with dlgt, dlgtinstant and dlgtset
var z = "qqq";
array y[] = {1,2,3};
dlgtcall instant (z,y);
result:
x = [qqq]
-----Array arr-----
[0]      1
[1]      2
[2]      3
```

See the following samples with delegates:

Examples\callfunc\dlgt.scr

Examples\callfunc\dlgt2.scr

## callback

callback invokes synchronous callback method.

Format **ppl**:

**callback (callback name)(arg1)(arg2)(arg3)...**

Format **scr**:

**callback callback name (arg1,arg2,arg3,...)**

Example: (see Examples\callfunc\callback.scr)

```
function cb1(var:n){write#("function cb1 {0}",n)};
function cb2(var:n) { write#("function cb2 {0}",n);}

function f(array:x,var:str)
{
    callback x(str);
}

delegate dd (var:n);
dlgtinstant instant dd;
dlgtset instant cb1;
call f(instant,"PPL");
dlgtset instant cb2;
call f(instant,"PPL");
result:
function cb1 PPL
function cb2 PPL
```

## Additional functionalities

The following below-mentioned additional DLLs with C# functionalities are added and this list will be expanded.

There are two types of methods called from additional DLLs:

- methods that return result, this result may be used in the next operation, for example:  
`var result = Math.Max(10) (20) ;`
- methods that not return result, for example:

`ArrayList.Remove(arrlist, item1) ;`

Methods of second type of may be called by command 'call' in scr-format:

`call ArrayList.Remove(arrlist, item1) ;`

`write#("ArrayList.Contains item1 = {0}", ArrayList.Contains(arrlist)( item1)); // right`  
`write#("ArrayList.Contains item1 = {0}", call ArrayList.Contains(arrlist)( item1)); // wrong`

In the following sample it is created wrapper for calling method that returns result (examples\lib\char.scr):

```
code scr;
function GetChar(result,text,index)
{
    set result = String.Char(text) (index) ;
}
var char;
var text = "Hello";
for(i,0,length(text))
{
    call GetChar(char,text,i) ;
    write(char) ;
}
```

To get list of methods of additional loaded DLLs:

**<DLLname>.help**

## Math

Methods:

<b>Max</b>	<b>E</b>	<b>PI</b>
<b>Min</b>	<b>Exp</b>	
<b>BigMul</b>	<b>Floor</b>	
<b>Sqrt</b>	<b>Log</b>	
<b>Round</b>	<b>Log10</b>	
<b>Abs</b>	<b>Pow</b>	
<b>Acos</b>	<b>Sign</b>	
<b>Asin</b>	<b>Sin</b>	
<b>Atan</b>	<b>Tan</b>	
<b>Atan2</b>	<b>Truncate</b>	
<b>Ceiling</b>	<b>Tanh</b>	
<b>Cos</b>	<b>Cosh</b>	
<b>DivRem</b>	<b>Sinh</b>	

To get short help of every method in Math.DLL:

**>Math.help[(method name)];**

Returns the larger of two double-precision floating-point numbers:

**Math.Max(double d1)(double d2)**

Returns the smaller of two double-precision floating-point numbers:

**Math.Min(double d1)(double d2)**

Produces the full product of two 32-bit numbers:

**Math.BigMul(Int32 n1)(Int32 n2)**

Returns the square root of a specified number: **Math.Sqrt(double d1)**

Rounds a double-precision floating-point value to a specified number:

**Math.Round (double value)[(Int32 digits)]**

Returns the absolute value of a double-precision floating-point number:

**Math.Abs(double value)**

Returns the angle whose cosine is the specified number: **Math.Acos(double d)**

Returns the angle whose sine is the specified number: **Math.Asin(double d)**

Returns the angle whose tangent is the specified number: **Math..Atan(double d)**

Returns the angle whose tangent is the quotient of two specified numbers:

**Math.Atan2(double d1)(double d2)**

Returns the smallest integral value greater than or equal to the specified number:

**Math.Ceiling(double d)**

Returns the cosine of the specified angle: **Math.Cos(double d)**

Returns the remainder in an output parameter: **Math.DivRem(Int64 n1)(Int64 n2)**

Represents the ratio of the circumference of a circle to its diameter: **Math.PI()**

Represents the natural logarithmic base: **Math.E()**

Returns e raised to the specified power: **Math.Exp(double value)**

Returns the largest integral value less than or equal to the specified number:

**Math.Floor(double value)**

Returns the logarithm of a specified number: **Math.Log(double value)**

Returns the base 10 logarithm of a specified number: **Math.Log10(double value)**

Returns a specified number raised to the specified power:

**Math.Pow(double value)(double power)**

Returns an integer that indicates the sign of a double-precision floating-point number:

**Math.Sign(double value)**

Returns the sine of the specified angle: **Math.Sin(double value)**

Returns the tangent of the specified angle: **Math.Tan(double value)**

Calculates the integral part of a number: **Math.Truncate(double value)**

Returns the hyperbolic tangent of the specified angle: **Math.Tanh(double value)**

Returns the hyperbolic cosine of the specified angle: **Math.Cosh(double value)**

Returns the hyperbolic sine of the specified angle: **Math.Sinh(double value)**

## String

Methods:

Compare	Replace
Concat	DeleteEndOfLine
Contains	StartsWith
Format	Substring
IndexOf	ToCharArray
LastIndexOf	ToLower
Insert	ToUpper
Remove	Trim
Split	Char
SplitCsv	

To get short help of every method in String.DLL:

**>String.help[(method name)];**

Returns signed int as string: **String.Compare(stringA)(stringB)**

Returns concatenation of several strings: **String.Concat(string1)(string2)...**

Returns true|false: **String.Contains(string)(specified substring)**

Converts the value of objects to string based on the formats specified and returns result:

**String.Format(format)(string1)(string2)...**

Example:

```
String.Format("{0} {1}") ("qwe") ("zxc")  
result = qwe zxc
```

Returns a new string in which a specified number of characters from the current string are deleted:

**String.Remove(string)(startIndex)(number of deleted symbols)**

Example:

**>rc examples\lib\StringRemove.scr**

```
import String;  
array primes = {1,2,3,5,7};  
var output = "";  
for(i,0,length(primes),1)  
{  
    set output = String.Concat(output) (primes[i]) (",");  
}  
var index = length(output) - 1;  
set output = String.Remove(output) (index) (1); //remove the  
latest ','  
write(output);  
Result:1,2,3,5,7
```

Returns a new string in which all occurrences of a specified Unicode character or string in the current string are replaced with another specified Unicode character or string:

**String.Replace(string)(old value)(new value)**

Determines whether this string instance starts with the specified character:

Returns **True** | **False**: **String.StartsWith(string)( value)**

Retrieves a substring from this instance. The substring starts at a specified character position and has a specified length:

**String.Substring(string)(startIndex)(length)**

Writes the characters in this instance to a Unicode character array:

**String.ToCharArray(string)(node\_of PPL\_chars\_array)**

node\_of PPL\_chars\_array is string in quotes or value of variable.

```
Example:
>array chars;
>String.ToCharArray("qwerty") (getname(chars)) ;
>writearray chars;
-----Array chars-----
[0]      q
[1]      w
[2]      e
[3]      r
[4]      t
[5]      y
```

Returns a copy of this string converted to lowercase: **String.ToLower(string)**

Returns a copy of this string converted to uppercase: **String.ToUpper(string)**

Returns a new string in which all leading and trailing occurrences of a set of specified characters from the current string are removed:

**String.Trim(string)[(trim chars string)]**

```
>String.Trim(" abcde") (" ae");
result = bcd
```

Returns one character from string: **String.Char(string)(index)**



Returns the reallocated string array that contains the substrings in this instance that are delimited by elements of a specified string array or in special string var, string array must be created before with size = 0:

**String.Split(string)("ppl\_array\_separators")( getname(ppl\_array\_result))** or  
**String.Split(string)("var\_separator")(getname(ppl\_array\_result))**

Use    comma instead of ','  
         space instead of ' '  
         tab instead of '\t'

Example:

> var text;

```
>set text = File.ReadAllText("Data\test.csv");  
>array separator[] = {comma,tab,space};  
>array split_text_array;  
>String.Split(text) ("separator") (getname(split_text_array));
```

Returns the reallocated string array that contains the substrings in this instance that are delimited by separator of a specified string var, string array must be created before with size = 0.

If substring surrounded by quotes it may contain separator  
(see example\lib\splitcsv.scr ):

**array ppl\_array\_result;**

**String.SplitCsv(string)("var\_separator")("ppl\_array\_result")**

Use    comma instead of ','  
         space instead of ' '  
         tab instead of '\t'

Do not use whitespace as separator:

Example:

Returns string from File.ReadAllText without EndOfLine: **DeleteEndOfLine(string)**

>rc Examples\Lib\FilesplitCsv.scr

```
var text = File.ReadAllText("examples\lib\splitcsv.txt");  
array splitcsv_text;    // array with results  
String.SplitCsv(text) (comma) (getname(splitcsv_text));  
File.WriteAllText("text") ("examples\lib\splitcsv_copy.txt");
```

Reports the zero-based index of the first occurrence of the specified string in this instance:

**String.IndexOf (string)(value)(index)**

Reports the zero-based index of the last occurrence of the specified string in this instance:

**String.LastIndexOf (string)(value)(index)**

Returns a new string in which a specified string is inserted at a specified index position in this instance:

**String.Insert (string)(start index)(string to insert)**

## Directory

Methods:

- GetFiles**
- GetDirectories**
- SetCurrentDirectory**
- GetCurrentDirectory**
- GetParent**
- CreateDirectory**
- Exists**
- Delete**

To get short help of every method in Directory.DLL:

> **Directory.help**[(method name)];

Writes the names of files (including their paths) in the specified directory to **node\_of\_PPL\_array**, created before with size = 0:

**array node\_of\_PPL\_array;**

**Directory.GetFiles**("node\_of\_PPL\_array")("path")

node of PPL array is string in quotes or value of variable or **getname(node\_of\_PPL\_array)**.

Example:

1.

```
>array files;  
>Directory.GetFiles("files") ( "c:\" );  
or  
var (x["files"]);  
>Directory.GetFiles (x) (path) ;
```

2.

```
>rc examples\lib\WriteFilesInDir.scr
```

```
function WriteFilesInDirectory (array:arr,dir)  
{  
    array arr;  
    Directory.GetFiles(arr) (dir) ;  
    Writearray arr;  
}  
WriteFilesInDirectory ("files") ("c:\");
```

**Result:**

-----Arr files-----

```
[0]      c:\DumpStack.log.tmp  
[1]      c:\hiberfil.sys  
[2]      c:\pagefile.sys  
[3]      c:\swapfile.sys
```

Writes the names of files (including their paths) in the specified directory to **node\_of\_PPL\_array**, created before with size = 0:

```
array node_of_PPL_array;  
Directory.GetDirectories("node_of_PPL_array") ( "path" )
```

node of PPL array is string in quotes or value of variable or `getname(node_of_PPL_array)`.

Example:

```
array dir;  
Directory.GetDirectories ("dir") ("c:\Users") ;  
or  
var (x["dir"]);
```

Sets the current working directory to the specified directory:

```
Directory.SetCurrentDirectory("path")
```

Gets the current working directory: **Directory.GetCurrentDirectory()**

Returns parent fullname: **Directory.GetParent("path")**

Returns CreationTime: **Directory.CreateDirectory("path")**

Returns **True** or **False** : **Directory.Exists("path")**

Deletes the specified directory and any subdirectories and files in the directory

Returns **True** or **False**: **Directory.Delete("path")**

## Array

Methods:

<b>Max</b>	<b>Min</b>	<b>Sum</b>
<b>Mean</b>	<b>Sum2</b>	<b>Sub2</b>
<b>Mult2</b>	<b>Div2</b>	<b>Sort</b>
<b>Reverse</b>	<b>IndexOf</b>	<b>LastIndexOf</b>

To get short help of every method in ArrayDLL: **Array.help[(method name)];**

Returns result: **Array.Max("ppl\_array")**

Returns result: **Array.Min("ppl\_array")**

Returns result: **Array.Sum("ppl\_array")**

Returns result : **Array.Average("ppl\_array")**

Math operations with 2 array, result is saved in **result\_ppl\_array**:

**Array.Sum2("ppl\_array1")("ppl\_array2")("result\_ppl\_array")**

**Array.Sub2("ppl\_array1")("ppl\_array2")("result\_ppl\_array")**

**Array.Mult2("ppl\_array1")("ppl\_array2")("result\_ppl\_array")**

**Array.Div2("ppl\_array1")("ppl\_array2")("result\_ppl\_array")**

Replaces source array: **Array.Sort("ppl\_array") ("double" | "string")**

Replaces source array: **Array.Reverse("ppl\_array")**

Returns result: **Array.IndexOf("ppl\_array")(value)**

Returns result: **Array.LastIndexOf("ppl\_array")(value)**

Example:

```
>code scr;
>import Array;
>array arr[] = {-4,4, -3,3,-2,2};
>Array.Sort("arr") ("double");
>writearray arr;
>Array.Reverse("arr");
>writearray arr;
=====result=====
-----Array arr----- double-----
[0]      -4
[1]      -3
[2]      -2
[3]       2
[4]       3
[5]       4
-----Array arr----- double-----
[0]       4
[1]       3
[2]       2
[3]      -2
[4]      -3
[5]      -4
```

```
>import Array;  
>code scr;  
>array a[] = {1,3,,5};  
>debugppl yes;  
>Array.Average(a);  
result = 3  
>recreate yes;  
>array a[] = {1,3,0,5};  
Info: [CreateArrayFormat1] Global array [a] is created  
>Array.Average(a);  
result = 2.25
```

See samples in Examples\lib\Array.scr.

The following collections are supported: **ArrayList, Queue, Stack, Dictionary.**

## **ArrayList**

Methods:

<b>Create</b>	<b>ToArray</b>	<b>Count</b>
<b>Write</b>	<b>Reverse</b>	<b>Get</b>
<b>Add</b>	<b>Remove</b>	<b>Set</b>
<b>Clear</b>	<b>Insert</b>	<b>Delete</b>
<b>Contains</b>	<b>IndexOf</b>	
<b>AddArray</b>	<b>Sort</b>	

To get short help of every method in ArrayList.DLL: **ArrayList.help[(method name)];**

Creates ArrayList object: **ArrayList.Create(name)**

It is possible to create ArrayList repeatedly, in this case previous data removed.

Writes all array\_list\_names or all elements from the specified array\_list to the standard output stream: **ArrayList.Write()** or **ArrayList.Write(arrlist name)**

Adds a string to the end of the ArrayList: **ArrayList.Add(arrlist name)(string)**

To add empty string use keyword **empty**:

Example:

```
>ArrayList.Create(ar)
>ArrayList.Add(ar) (empty)
```

Adds node of PPL array to the end of the ArrayList:

**ArrayList.AddArray("PPL array")(arrlist name)**

Name of PPL array is **string in quotes** or value of variable with value = name of PPL array .

Removes all elements from the ArrayList: **ArrayList.Clear(arrlist name)**

Determines whether an element is in the ArrayList, returns **"True"** or **"False"**:

**ArrayList.Contains(arrlist name)(string)**

Writes all elements from arrlist to PPL array created before with size = 0 and reallocated in **ArrayList.ToArray** with size of arrlist name:

**array "ppl\_array";**

**ArrayList.ToArray(arrlist name)(getname("ppl\_array"))**

Name of PPL array is **string in quotes** or value of variable with value = name of PPL array .

Error: If PPL array exists.

Reverses the order of the elements in the ArrayList: **ArrayList.Reverse(arrlist name)**

Removes the first occurrence of a specific object from the ArrayList:

**ArrayList.Remove(arrlist name)(string)**

Inserts an element into the ArrayList at the specified index:

**ArrayList.Insert(arrlist name)(index)(element)**

To insert empty string use keyword **empty**.

Returns the zero-based index of the first occurrence of a value in the ArrayList:

**ArrayList.IndexOf(arrlist name)(value)**

Sorts the elements in the ArrayList: **ArrayList.Sort(arrlist name)**

Returns the number of elements actually contained in ArrayList: **ArrayList.Count(arrlist name)**

The following example includes all ArrayList methods:

```
>rc Examples\lib\ArrayList.scr
>import ArrayList;
>ArrayList.Create("all");
>createnode Private;
>array(Private.src) (ONE) (TWO) (THREE);
>var(x["Private.src"]);
>ArrayList.AddArray(x) (all);
>ArrayList.Write(all);
>ArrayList.Add(all) (empty);
>ArrayList.Add(all) (2two);
>ArrayList.Add(all) (3three);
>ArrayList.Add(all) (1one);
>write("====Added objects====");
>ArrayList.Write(all);
>ArrayList.Remove(all) (1one);
>ArrayList.Remove(all) (1one); // // error: 1one does not exist
>write("====Removed objects====");
>ArrayList.Write(all);
>ArrayList.Reverse(all);
>write("====Reverse====");
>ArrayList.Write(all);
>write("ArrayList.Contains 1one" = {0}) (ArrayList.Contains(all)
                                         (1one));
>ArrayList.Insert(all) (2) (4four);
>write("ArrayList.Contains 4four" = {0}) (ArrayList.Contains(all)
                                         (4four));
>ArrayList.IndexOf(all) (3three);
>ArrayList.Sort(all);
>write("====Sort====");
>ArrayList.Write(all);
>array (N1.dst_arr);
>ArrayList.ToArray(all) (getname(N1.dst_arr));
```



```
>ArrayList.Clear(all);
>d;

      Result:
Imported [ArrayList]
all
      ONE
      TWO
      THREE
=====Added objects=====
all
      ONE
      TWO
      THREE

      2two
      3three
      lone
Warning: [ArrayList.FuncRemove] element [lone] does not exist
=====Removed objects=====
all
      ONE
      TWO
      THREE

      2two
      3three
=====Reverse=====
all
      3three
      2two

      THREE
      TWO
      ONE
ArrayList.Contains lone" = False
ArrayList.Contains 4four" = True
=====Sort=====
all

      2two
      3three
      4four
      ONE
      THREE
      TWO
-N1  NS
---N2 Global
-----N3  Private  [Node]
-----N4  src     [Array 3]
-----L0  #       [ONE]
-----L1  #       [TWO]
-----L2  #       [THREE]
```

```
-----N4  dst_arr      [Array 7]
-----L0      #
-----L1      #      [2two]
-----L2      #      [3three]
-----L3      #      [4four]
-----L4      #      [ONE]
-----L5      #      [THREE]
-----L6      #      [TWO]
-----L11     x      ["Private.src"]
---N2 Local
```

Returns value of ArrayList member by index:

**ArrayList.Get(arrlist\_name)(index)**

Set value of ArrayList member by index:

**ArrayList.Set(arrlist\_name)(index)(value)**

Example:

```
>import ArrayList
Imported [ArrayList]
>ArrayList.Create(x)
>ArrayList.Add(x) (qqq)
>ArrayList.Add(x) (zzz)
>ArrayList.Get(x) (0)
result = qqq
>ArrayList.Set(x) (0) (aaa)
>ArrayList.Get(x) (0)
result = aaa
```

Delete all ArrayList objects:

**ArrayList .Delete();**

## Queue

Methods:

<b>Create</b>	<b>Peek</b>	
<b>Count</b>	<b>Clear</b>	
<b>Write</b>	<b>Contains</b>	
<b>Enqueue</b>	<b>AddArray</b>	
<b>Dequeue</b>	<b>ToArray</b>	<b>Delete</b>

To get short help of every method in Queue.DLL:

**Queue. help[(method name)]**

Creates Queue object: **Queue.Create(queue name)**

Returns the number of elements actually contained in Queue: **Queue.Count(queue name)**

Writes queue names or all elements from the specified queue to the standard output stream:

**Queue.Write()** or **Queue.Write(name)**

Adds an object to the end of the Queue: **Queue.Enqueue(queue name)(string)**

To add empty string use keyword **empty**.

Removes and returns the object at the beginning of the Queue:

**Queue.Dequeue(queue name)**

Returns the object at the beginning of the Queue without removing it:

**Queue.Peek(queue name)**

Removes all objects from the Queue: **Queue.Clear(queue name)**

Determines whether an element is in the Queue, returns "True" or "False":

**Queue.Contains(queue name)(string)**

Adds PPL array to the Queue: **Queue.AddArray("PPL array") (queue name)**

Writes all elements from Queue to the PPL array created before with size = 0:

```
array "ppl_array";  
Queue.ToArray(queue name) ("ppl_array")
```

Delete all Queue objects: **Queue.Delete();**

Examples of code with Dictionary methods in **examples\lib\Queue.ppl**

## Stack

Methods:

<b>Create</b>	<b>Peek</b>	
<b>Count</b>	<b>Clear</b>	
<b>Write</b>	<b>Contains</b>	
<b>Push</b>	<b>AddArray</b>	
<b>Pop</b>	<b>ToArray</b>	<b>Delete</b>

To get short help of every method in Stack.DLL:

**>Stack.help[(method name)]**

Creates Stack object: **Stack.Create(stack name)**

Returns the number of elements actually contained in Stack: **Stack.Count(stack name)**

Writes stack names or all elements from the specified stack to the standard output stream:

**Stack.Write()** or **Stack.Write(stack name)**

Inserts an object at the top of the stack: **Stack.Push(stack name)(string)**

To insert empty string use keyword **empty**.

Removes and returns the object at the top of the Stack:

**Stack.Pop(stack name)**

Returns the object at the top of the Stack without removing it:

**Stack.Peek(stack name)**

Removes all objects from the Stack: **Stack.Clear(stack name)**

Determines whether an element is in the Stack, returns "True" or "False":

**Stack.Contains(stack name)(string)**

Adds PPL array to the Stack: **Stack.AddArray ("PPL array")(stack name)**

Writes all elements from Stack to the PPL array created before with size = 0:

**array "ppl\_array";**

**Stack.ToArray(stack name) ("ppl\_array")**

Delete all Queue objects: **Stack.Delete();**

Examples:

```
>import Stack
Imported [Stack]
>Stack.Create(s)
>Stack.Push(s) (one)
>Stack.Push(s) (two)
>Stack.Push(s) (three)
>debugppl yes
>Stack.Pop(s)
result = three
>Stack.Pop(s)
result = two
>Stack.Pop(s)
result = one
>Stack.Pop(s)
result = empty
```

Examples of code with Stack methods in **examples\lib\Stacks.ppl**

## Dictionary

Methods:

<b>Create</b>	<b>ContainsKey</b>	
<b>Count</b>	<b>ContainsValue</b>	
<b>Add</b>	<b>Remove</b>	
<b>Write</b>	<b>AddArray</b>	
<b>Clear</b>	<b>ToArray</b>	<b>Delete</b>

To get short help of every method in Dictionary.DLL:

>**Dictionary.help[(method name)]**

Creates Dictionary object: **Dictionary.Create(dictionary name)**

Returns the number of elements actually contained in Dictionary:

**Dictionary.Count(dictionary name)**

Adds the specified key and value to the Dictionary:

**Dictionary.Add(dictionary name)(key)(value)**

Writes dictionary names or all elements from the specified Dictionary to the standard output stream: **Dictionary.Write()** or **Dictionary.Write(dictionary name)**

Removes all keys and values from the Dictionary: **Dictionary.Clear(dictionary name)**

Determines whether the Dictionary contains the specified key, returns **True** or **False**:

**Dictionary.ContainsKey(dictionary name)(key)**

Removes the value with the specified key from the Dictionary:

**Dictionary.Remove(dictionary name)(value)**

Determines whether the Dictionary contains a specific value, returns **True** or **False**:

**Dictionary.ContainsValue(dictionary name)(value)**

Adds PPL array to the Dictionary: **Dictionary.AddArray("PPL array")(dictionary name)**

Write all elements from Dictionary to new PPL array created before with size = 0:

**array "ppl\_array";**

**Dictionary.ToArray(dictionary name) ("ppl\_array")**

Delete all Queue objects: **Dictionary.Delete();**

Examples of code with Dictionary methods in **examples\lib\Dictionary.ppl**

## Convert

Methods:

```
StringToInt32Array
StringToHexArray
HexToBin
BinToHex
IntToHex
HexToInt
IntToBin
BinToInt
```

To get short help of every method in Convert.DLL:

**>Convert.help[(method name)];**

String characters converts to int32 array created before with size = 0 and reallocated in **Convert.StringToInt32Array** with size of string\_characters:

**Convert.StringToInt32Array(string\_characters)("Int32 "ppl\_array")**

String characters converts to hex array created before with size = 0 and reallocated in **Convert.StringToHexArray** with size of string\_characters:

**Convert.StringToHexArray(string\_characters)("Hex "ppl\_array")**

All below mentioned methods convert data in accordance with method name and return:

Returns string bin: **Convert.HexToBin(string with hex value)**

Returns string hex: **Convert.BinToHex(string with bin value)**

Returns string hex: **Convert.IntToHex(string with Int32 value)**

Returns string Int32: **Convert.HexToInt(string with hex value)**

Returns string bin: **Convert.IntToBin(string with Int32 value)**

Returns string Int32: **Convert.BinToInt(string with bin value)**

Examples:

See Examples\lib\Convert.scr

```
>array Int32;
>Convert.StringToInt32Array("12345") ("Int32");
Info [CreateArrayFormat2] Global array [Int32] is created
>writearray Int32;
-----Array Int32-----
[0]      49
[1]      50
[2]      51
[3]      52
[4]      53
```

```
>array Hex;  
>Convert.StringToHexArray("12345") ("Hex");  
>writearray Hex;  
-----Array Hex-----  
[0]      31  
[1]      32  
[2]      33  
[3]      34  
[4]      35
```

Examples:

```
>debugpp1 yes  
>Convert.HexToBin(16);  
result = 10110  
>Convert.BinToHex(1111111)  
result = 7F  
>Convert.IntToHex(256)  
result = 100
```



## Excel

The following methods may be used for reading from XLSX files to two-dimensional storage or writing from two-dimensional storage to XLSX files.

Methods:

```
Open
Close
Read
CreateWorkBook
Write
SaveAs
```

To get short help of every method in Excel.DLL:

```
> Excel.help[(method name)];
```

Opens XLSX file for reading:

```
Excel.Open(filename.xlsx)
```

Closes XLSX file after reading or writing:

```
Excel.Close()
```

Reads opened XLSX to storage, size of storage must be enough to save Excel cells:

```
Excel.Read("sheet")("left top")("right down")("storage")
```

Example:

```
"left top": "A1"
```

```
"right down": "H10"
```

Creates workbook for writing:

```
Excel.CreateWorkBook()
```

Writes storage to Excel cells, quantity of cells must be enough to save storage:

```
Excel.Write("sheet")("left top")("right down")("storage")
```

Saves created XLSX file after writing:

```
Excel.SaveAs(filename.xlsx)
```

Examples:

see file Examples\Excel\test.scr

```
import Excel;
Excel.Open("$1$\examples\Excel\example.xlsx");
Excel.Read("Sheet1")("A1")("H10")("Example_XLSX");
Excel.Close();
swrite(Example_XLSX);
```

```
Excel.CreateWorkBook();  
Excel.Write("Sheet1")("A1")("H10")("Example_XLSX");  
Excel.SaveAs("$1$\examples\Excel\example2.xlsx");  
Excel.Close();
```

>rc examples\excel\test.scr c:\path

Parameter **c:\path** overrides the variable **\$1\$** in file test.scr.

## File

Methods:

<b>ReadAllText</b>	<b>ReadAllLines</b>
<b>WriteAllText</b>	<b>WriteAllLines</b>
<b>Exists</b>	<b>Delete</b>

Returns all contents of text file: **File.ReadAllText(filename)**

Creates a new file, write the contents to the file, and then closes the file:

**File.WriteAllText(var\_ppl)(filename)**

Determines whether the specified file exists, returns **True** or **False**: **File.Exists(filename)**

Returns string array with lines of text file: **File.ReadAllLines(filename)("")ppl\_array""**

Example:

```
>File.ReadAllLines("examples\lib\split.txt")("x")
>d
-N1  NS
---N2 Global
-----N3 x   [Array 2]
-----L0  #   [1,2,3,4,5,6,7,8,9,10,]
-----L1  #   [11,12,13,14,15,16,17,18,19,20]
```

Creates a new file, writes one or more strings to the file, and then closes the file:

**File.WriteAllLines("")ppl\_array""(filename)**

Deletes the specified file: **File.Delete(filename)**

## Random

Methods:

<b>Create</b>	<b>NextDouble</b>
<b>Next</b>	<b>NextInt64</b>
<b>NextBytes</b>	<b>NextSingle</b>

Creates Random object: **Random.Create(name)[(Seed)]**

Returns a non-negative random integer: **Random.Next(random\_name)**

Returns a non-negative random integer that is less than the specified maximum:  
**Random.Next(random\_name) (maxValue)**

Returns a random integer that is within a specified range:  
**Random.Next(random\_name) (minValue)(maxValue)**

Creates random numbers and writes them to the of a specified “**ppl\_array**” created before with size = 0:  
**Random.NextBytes(random name)(“ppl\_array”)(quantity of random elements)**

Returns a random floating-point number that is greater than or equal to 0.0, and less than 1.0:  
**Random.NextDouble(random name)**

Returns a non-negative random integer: **Random.NextInt64(random name)**

Returns a non-negative random integer that is less than the specified maximum:  
**Random.NextInt64(random name)(maxValue)**

Returns a random integer that is within a specified range:  
**Random.NextInt64(random name)(minValue)(maxValue)**

Returns a random floating-point number that is greater than or equal to 0.0, and less than 1.0:  
**Random.NextSingle(random name)**

Examples:

```
>debugpp! yes;  
>import Random;  
Imported [Random]  
>Random.Create(r);  
>Random.Next(r)(0)(10);  
Result = 2  
>array x;  
>Random.NextBytes(r)(x)(5);  
>writearray x;  
-----Array x-----  
[0] # 5  
[1] # 121  
[2] # 226  
[3] # 108  
[4] # 61
```

## Console

Methods:

<b>ForegroundColor</b>	<b>Beep</b>
<b>BackgroundColor</b>	<b>Clear</b>
<b>ForegroundPromptColor</b>	<b>SetCursorPosition</b>
<b>DefaultColors</b>	<b>GetCursorPosition</b>
<b>Write</b>	

Sets the foreground color of the console:

**Console.ForegroundColor(color)**

Sets the background color of the console:

**Console.BackgroundColor(color)**

Sets the prompt foreground color of the console:

**Console.ForegroundPromptColor(color)**

Sets the default foreground, background and ForegroundPromptColor color of the console:

**Console.DefaultColors()**

Writes the text representation of the specified value or values to the standard output stream: **Console.Write [(format)](string)(string)**

Plays the sound of a beep through the console speaker:

**Console.Beep (frequency)(duration)**

**frequency** - 37 to 32767 hertz

**duration** - msec

Clears the console buffer and corresponding console window of display information:

**Console.Clear()**

Sets the position of the cursor:

**Console.SetCursorPosition(left column cursor position)(top row cursor position)**

Gets the position of the cursor:

**Console.GetCursorPosition ()**

Returns '**left column cursor position, top row cursor position**'

See examples in examples\Console.

## Vector

For using with library MathNet.Numerics and others. Using Vector and Matrix libraries significantly increases program performance.

Methods:

```
Vector.Create ("vector_name")(length)(type)
type:= double|float|decimal|bool|int|uint|long|ulong|string
types in accordance with value types in
https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-types/built-in-types
```

```
Vector.Get(vector_name)(index);
Vector.Set(vector_name)(index)(value);
Vector.Add("vector_name")( ""ppl_array"" )
```

Write to line - "row"

Write not nullable data to column - "col"

Write all data to column - "col0"

```
Vector.Write("vector_name")(["row"|"col"|"col0"])
```

```
Vector.WriteNames()
```

```
Vector.Delete("vector_name")
```

```
Vector.DeleteAll()
```

### Examples:

```
>import Vector;
>array v[] = {1,2,3,4,5};
>call Vector.Create ("V",5,int);
>call Vector.Add("V",getname(v));
> call Vector.Write("V");
=====vector V=====
1  2  3  4  5
>call Vector.Set("V",0,0);
> call Vector.Write("V",col);
=====vector V=====
[1]  2
[2]  3
[3]  4
[4]  5
>call Vector.Delete("V");
```

See examples in **examples\MatrixVector**.

## Matrix

For using with library MathNet.Numerics and others.

Methods:

```

Create ("matrix_name")(rows)(columns)(type)
type:= double | float | decimal | bool | int | uint | long | ulong | string
types in accordance with value types in
https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/builtin-
types/built-in-types
Get("matrix_name")(index_row)(index_column)
Set("matrix_name")(index_row)(index_column)(value)
AddArrayToRow ("matrix_name")(row)("")ppl_array")
AddArrayToColumn ("matrix_name")(column)("")ppl_array")
Write to line - "row"
Write not nullable data to column - "col"
Write all data to column - "col0"

Write("matrix_name")(["row" | "col" | "col0"])
WriteNames()
Delete("matrix_name")
DeleteAll()
Rotate("matrix_name")("cw" | "ccw") - for square matrix only

```

Example:

```

>import Matrix;
>call Matrix.Create ("A",3,3,float);
>array r1[] = {1,2,3};
>array r2[] = {4,5,6};
>array r3[] = {7,8,9};
>call Matrix.AddArrayToRow ("A",0, getname(r1));
>call Matrix.AddArrayToRow ("A",1, getname(r2));
>call Matrix.AddArrayToRow ("A",2, getname(r3));
>call Matrix.Write("A");
>call Matrix.Delete("A");

```

See examples in **examples\MatrixVector**.



## MN\_Numerics

For using MathNet.Numerics.dll

Methods:

```
Matrix("matrix_name")(rows)(columns)           // like as Matrix.CreateDouble
Vector("vector_name")(length)                   // like as Vector.CreateDouble
AddRowToMatrix("matrix_name")("ppl_array")       // like as Matrix.AddRow
AddColumnToMatrix("matrix_name")("ppl_array")    // like as Matrix.AddColumn
AddDataToVector("vector_name")("ppl_array")      // like as Vector.Add
```

Linear Equation Systems:

See detailed information: <https://numerics.mathdotnet.com/LinearEquations.html>

```
Solve("matrix_name")("vector_name")("ppl_array_result")
```

```
DeleteAll() // delete all matrix and name
```

```
DeleteMatrix("matrix_name")
```

```
DeleteVector("vector_name")
```

For operations with vectors and matrices It is possible to use methods from

MN\_Numerics.Matrix and MN\_Numerics.Vector

or from

Matrix and Vector, **but not together.**

Example: (see examples\mnn\lesrow2.scr)

```
//linear equation systems
// AX = B
// Creation rows as "ppl_array"s
// Creation Matrix.matrix
// Creation Vector.vector
import Matrix;
import Vector;
import MN_Numerics;
Matrix.DeleteAll();
Vector.DeleteAll();
write("-----Creation Matrix.matrix & Vector.vector-----");
call Matrix.Create("A",3,3,double);
array row1[] = {3,2,-1};
array row2[] = {2,-2,4};
array row3[] = {-1,0.5,-1};
call Matrix.AddArrayToRow("A",0,getname(row1)); // fill matrix
call Matrix.AddArrayToRow("A",1,getname(row2));
call Matrix.AddArrayToRow("A",2,getname(row3));

call Vector.Create("B",3,double);
array vector[] = {1,-2,0}; // create vector as "ppl_array"
call Vector.Add("B",getname(vector)); // fill vector
```

```
array X[length(vector)] = 0; // create result as "ppl_array"
call MN_Numerics.Solve("A","B",getname(X));
writearray X;
Vector.Delete("B");
results:
-----Array X-----
[0] #          1
[1] #        -1.9999999999999996
[2] #        -1.9999999999999993
```

**Constants:** to get list of constants from MathNet.Numerics:  
**>MN\_Numerics.help();**

Examples:

```
>debugppl yes
>import MN_Numerics;
>MN_Numerics.Pi()
result = 3.141592653589793
>MN_Numerics.E()
result = 2.718281828459045
```

## DataFrame

DataFrame is a table with named columns, columns may be defined with different types, number of rows and columns is not limited.

Methods:

<b>Create</b>	<b>SetWidthForAll</b>
<b>SetRow</b>	<b>SetColumn</b>
<b>Write</b>	<b>ClearColumns</b>
<b>Save</b>	<b>Read</b>
<b>InsertRows</b>	<b>AddRows</b>
<b>InsertColumns</b>	<b>AddColumns</b>
<b>RemoveRows</b>	<b>RemoveColumns</b>
<b>Sort</b>	<b>Reverse</b>
<b>SelectRows</b>	<b>UnSelectRows</b>

Delete DataFrame - **del df\_name**

**df\_name** – DataFrame name

1. Example

```
>import DataFrame
Imported [DataFrame]
>DataFrame.Create(MyDataFrame)(2)(One)(Two)(Three)
-----Variables and arrays-----
-N4 MyDataFrame [Node]
---N5 Settings [Node]
---N5 One [Array 2]
---N5 Two [Array 2]
---N5 Three [Array 2]
>DataFrame.Write(MyDataFrame)
```

```
One Two Three
0
1
```

**DataFrame.Create** creates node <df\_name>.Settings:

```
>d MyDataFrame.Settings
-----Variables and arrays-----
-N5  Settings    [Node]
---L0 RowSelectedFrom
---L1 RowSelectedTo
---L2 PrintEmptyRows [yes]
---L3 RowsLength    [8]
---L4 ReallocIncrement [10]
---L5 CityType      [Text]
---L6 CityWidth     [12]
---L7 PopulationType [Number]
---L8 PopulationWidth [12]
---L9 AreaType      [Text]
---L10 AreaWidth    [12]
---L11 ElevationType [Text]
---L12 ElevationWidth [12]
---L13 CodeType     [Text]
---L14 CodeWidth    [12]
---L15 DensityType  [Text]
---L16 DensityWidth [12]
```

**RowSelectedFrom** and **RowSelectedTo** used in the following methods:

Read,Save,Write

**PrintEmptyRows** used in Write.

**RowsLength** set automatically as number of rows.

**ReallocIncrement** used in Create and AddRows.

<column name>**Type** set in code and used in Read and Sort.

<column name>**Width** set in code and used in Write.

Creates Dataframe:


**DataFrame.Create([df\_name]) [(number rows)(column1)(column2)(column3)...**

**default df\_name – DF**

**default number of rows – 10**

**default column names – from A to Z**

**Example:**

A screenshot of a CPPL console window. The title bar says 'CPPL'. The console shows the following commands and output:

```
Imported [DataFrame]
>DataFrame.Create()
>DataFrame.Write()
```

The output is a table with 26 columns labeled A through Z and 10 rows labeled 0 through 9. All cells in the table are empty.

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0																										
1																										
2																										
3																										
4																										
5																										
6																										
7																										
8																										
9																										

Sets same width for all columns to display DataFrame by DataFrame.Write:

**DataFrame.SetWidthForAll([df\_name])([width])**

**default name – DF**

**default with = 12**

**Example:**

**DataFrame.SetWidthForAll(14)**

Sets value for each column for defined row:

**DataFrame.SetRow(df\_name)(row index)(value column1)( value column2)...**

Sets value for each row for defined column:

**DataFrame.SetColumn(df\_name)(column)(value row1)(value row2)...**

Displays DataFrame full contents or only contents of defined columns:

**DataFrame.Write([df\_name])([column)(column)...) ]**

To display contents of specific rows:

**set <df\_name>.Settings.RowSelectedFrom = value;**

**set <df\_name>.Settings.RowSelectedTo = value | \*;**

**"\*" – to end**

**or by method [SelectRows](#).**

To set same width for all columns:

**set <df\_name>.Settings.<column name>Width = width**

To enable or disable print empty rows:

```
set <df_name>.Settings.PrintEmptyRows = yes|no
```

Clears contents of all DataFrame or specified columns:

```
DataFrame.ClearColumns(df_name)[(column)(column)...
```

Save Dataframe full contents in format csv or [data](#) or contents of defined columns only in format .csv

```
DataFrame.Save(df_name)(filename.csv|.data)[(column)( column)]...
```

Read Dataframe full contents in format csv or [data](#) or contents of defined columns only in format .csv:

```
DataFrame.Read(df_name)(filename.csv|.data)[(column)( column)]...
```

To set type data for any column:

```
set <df_name>.Settings.<column name>Type = Text|Number
```

For each cell in column with type "Number" input data will be test, in case of error in cell contents will be written "**\*error**".

Inserts number of rows by index:

```
DataFrame.InsertRows(df_name)(index)[(number of rows)]
```

By default number of added rows= 1

Adds number of rows at the end:

```
DataFrame.AddRows([df_name])[ (number of rows)]
```

By default df\_name = DF

By default number of added rows = 10

Insert one or several named columns before specified column:

```
DataFrame.InsertColumns(df_name) (specified column)(column)(column)...
```

Adds number of named columns at the end:

```
DataFrame.AddColumns(df_name)(column1)(column2)...
```

Removes rows:

**RemoveRows(df\_name)** – remove all rows

**RemoveRows(df\_name)[(number\_of\_row)]** – remove 1 row

**RemoveRows(df\_name)(number\_from)(\*)** - remove rows  
between number\_from to end

**RemoveRows(df\_name)(number\_from)(number\_to)** - remove rows  
between number\_from – number\_end

Removes named columns and their Type and Width in Settings:

```
RemoveColumns(df_name)[(column1)(column2)...
```

Removes all columns and their Type and Width in Settings:

**RemoveColumns(df\_name)**

Sorts all contents by specified column in ascending or descending order:

**DataFrame.Sort(df\_name)(ascend | descend)(column)**

See examples df8.scr and df9.scr(wrong results for digital data when Type = Text).

Reverses all contents by specified column:

**DataFrame.Reverse(df\_name)(column)**

Select one row only:

**DataFrame.SelectRows(df\_name)(select\_from)**

Select rows select\_from – to end

**DataFrame.SelectRows(df\_name)(select\_from)(\*)**

Select rows between select\_from – select\_to:

**DataFrame.SelectRows(df\_name)(select\_from)(select\_to)**

Unselect rows:

**DataFrame.UnSelectRows(df\_name)**

**Examples:**

```
Using data from DataFrame:
for(i,0,Length)
  write#("{0}    {1}",DF.City[i], DF.Area[i]);

write#("Average Elevation: {0}",
      Array.Average("DF.Elevation"));
```

**Example:**

File: examples\df\products.csv

Bagel,140,310,Medium

Biscuit ,86,480,High

Jaffa cake,48,370,Med-High

Bread white,96,240,Medium

Bread wholemeal,88,220,LowMed

Chapatis,250,240,Medium

Cornflakes,130,300,Med-High

Program: examples\df\df8.scr

```
import DataFrame;
```

```
DataFrame.Create(Products) (0) (Bread&Cereals) (Size) (per100grams)
                        (energy);
```

```
set Products.Settings.Bread&CerealsWidth = 20;
```

```
DataFrame.Read(Products) (examples\df\products.csv);
```

```
DataFrame.Write(Products);
```

```
DataFrame.Sort(Products) (ascend) (per100grams);
```

```
DataFrame.Write(Products);
```

```
>rc examples\df\df8.scr
code: scr
Info: [FuncImport] the library [DataFrame] is already loaded
DataFrame [Products] added [7] rows
-----Variables and arrays-----
-N4   Products      [Node]
---N5   Settings    [Node]
---N5   Bread&Cereals [Array 7]
---N5   Size        [Array 7]
---N5   per100grams  [Array 7]
---N5   energy       [Array 7]
```

	Bread&Cereals	Size	per100grams	energy
0	Bagel	140	310	Medium
1	Biscuit	86	480	High
2	Jaffa cake	48	370	Med-High
3	Bread white	96	240	Medium
4	Bread wholemeal	88	220	LowMed
5	Chapatis	250	240	Medium
6	Cornflakes	130	300	Med-High

	Bread&Cereals	Size	per100grams	energy
0	Bread wholemeal	88	220	LowMed
1	Bread white	96	240	Medium
2	Chapatis	250	240	Medium
3	Cornflakes	130	300	Med-High
4	Bagel	140	310	Medium
5	Jaffa cake	48	370	Med-High
6	Biscuit	86	480	High

```
>
```



Examples of using DataFrame methods in directory: **examples\df**

df1.scr - methods Read, Save

df2.scr - methods Read, RemoveColumns, Read, Save

df3.scr - methods AddColumns

df4.scr - methods DataFrame with default name DF

df5.scr - methods ClearColumns

df6.scr - methods RemoveRows, RemoveColumns

df7.scr - methods InsertRows, InsertColumns, SetRow, SetColumn, Sort, Reverse

df8.scr - methods Create, Read, Write, ascending and descending Sort, Reverse

df9.scr – methods Create, Read, Write, ascending Sort for Type = Text and Type Number

## Statistics

For using MathNet.Numerics.dll

See details in -

<https://numerics.mathdotnet.com/api/MathNet.Numerics.Statistics/ArrayStatistics.htm>

Methods:

<b>Covariance</b>	<b>FiveNumberSummary</b>
<b>GMean</b>	<b>HMean</b>
<b>Maximum</b>	<b>Mean</b>
<b>MeanStandardDeviation</b>	<b>Median</b>
<b>Minimum</b>	<b>OrderStatistic</b>
<b>Percentile</b>	<b>PopulationCovariance</b>
<b>PopulationStandardDeviation</b>	<b>PopulationVariance</b>
<b>QuantileCustom</b>	<b>Quantile</b>
<b>RanksInplace</b>	<b>RootMeanSquare</b>
<b>StandardDeviation</b>	<b>Variance</b>

Formats:

```
Statistics.help([name])
Statistics.Covariance("\"sample1\")\"(\"sample2\")
Statistics.FiveNumberSummary(\"sample_name\")(\"result_array5\")
Statistics.GMean(\"array_ppl\")
Statistics.HMean(\"array_ppl\")
Statistics.Maximum(\"array_ppl\")
Statistics.Mean(\"array_ppl\")
Statistics.MeanStandardDeviation(\"array_ppl\")
Statistics.Median(\"array_ppl\")
Statistics.Minimum(\"array_ppl\")
Statistics.OrderStatistic(\"array_ppl\")(order)
Statistics.Percentile(\"array_ppl\")(selector)
Statistics.FuncCovariance(\"sample1\")(\"sample2\")
Statistics.PopulationStandardDeviation(\"array_ppl\")
Statistics.PopulationVariance(\"array_ppl\")
Statistics.QuantileCustom(\"array_ppl\")(tau)(definition)
Statistics.Quantile(\"array_ppl\")(tau)
Statistics.Ranks(\"array_ppl\")(\"rank_array_ppl\")(definition)
Statistics.RootMeanSquare(\"array_ppl\")
Statistics.StandardDeviation(\"array_ppl\")
Statistics.Variance(\"array_ppl\")
```

Example: (examples\Statistics\test.scr)

```
import Statistics;
recreate yes;
write#("Statistics Array Tests");

array sample1[] = {2.1,2.5,3.6,4};
array sample2[] = {8,10,12,14};
var covariance = Statistics.Covariance("sample1")("sample2");
write#("Covariance = {0}",covariance);

var population_covariance = Statistics.PopulationCovariance("sample1")("sample2");
write#("PopulationCovariance = {0}",population_covariance);

array arr[] = {5,9,3,1,7};
var gm = Statistics.GMean("arr");
var hm = Statistics.HMean("arr");
var msd = Statistics.MeanStandardDeviation("arr");

write#("GeometricMean = {0}",gm);
write#("HarmonicMean = {0}",hm);
write#("Mean, StandardDeviation = {0}",msd);

array arr[] = {3,2,5, 7, 6, 4, 6, 9,6, 8,7};
array FiveNumberSummary[5];
call Statistics.FiveNumberSummary("arr", "FiveNumberSummary");
writearray FiveNumberSummary;
write#("min = {0}",FiveNumberSummary[0]);
write#("low_quartile = {0}",FiveNumberSummary[1]);
write#("median = {0}",FiveNumberSummary[2]);
write#("upper_quartile = {0}",FiveNumberSummary[3]);
write#("max = {0}",FiveNumberSummary[4]);
write#("quartile_range = {0}",FiveNumberSummary[3] - FiveNumberSummary[1]);
write#();
var max = Statistics.Maximum("arr");
write#("max = {0}",max);

var min = Statistics.Minimum("arr");
write#("min = {0}",min);

var mean = Statistics.Mean("arr");
write#("mean = {0}",mean);

var order_statistic = Statistics.OrderStatistic("arr")(3);
write#("order_statistic = {0}",order_statistic);

var variance = Statistics.Variance("arr");
```

```
write#("variance = {0}",variance);

var population_variance = Statistics.PopulationVariance("arr");
write#("population_variance = {0}",population_variance);

var median = Statistics.Median("arr");
write#("median = {0}",median);

var percentile = Statistics.Percentile("arr")(50);
write#("percentile = {0}",percentile);

array arr[] = {5,9,3,1,7};
var standard_deviation = Statistics.StandardDeviation("arr");
write#("standard_deviation = {0}",standard_deviation);

var population_standard_deviation = Statistics.PopulationStandardDeviation("arr");
write#("population_standard_deviation = {0}",population_standard_deviation);

var quantile_customR1 = Statistics.QuantileCustom("arr")(0)(R1);
write#("quantile_customR1 = {0}",quantile_customR1);

var quantile_customR8 = Statistics.QuantileCustom("arr")(0)(R8);
write#("quantile_customR8 = {0}",quantile_customR8);

var quantile = Statistics.Quantile("arr")(0);
write#("quantile = {0}",quantile);

array ranks;
Statistics.Ranks("arr")(Average)("ranks");
writearray ranks;

var rms = Statistics.RootMeanSquare("arr");
write#("rms = {0}",rms);
```

## Structure of User's DLL

Directory Template is the example for creation user's DLL, see Template.cs.

Example:

```
>import Template
>Template.sum(1) (2)
result = 3

>Template.help
help
sum
>Template.help(sum)
    Returns sum of two double-precision floating-point numbers:
    Template.sum(double d1) (double d2)
```

Add in Project Dependencies the project **PPL**

Utility **createulc.exe** creates code for User's DLL .

**-creation code without methods:**

**createulc.exe <name user DLL> [path]**

Example:

```
createulc.exe MyLib
=====see result here=====
using System;
using System.Collections.Generic;
namespace PPLNS
{
    public class MyLib : AbstractClass
    {
        // ppl & help_dict in Abstract Class
        //public PPL ppl;
        //Dictionary<string, string> help_dict = new Dictionary<string,
            string>();

        public MyLib(PPL ppl)
        {
            this.ppl = ppl;
        }
        //=====
        public void AddToKeywordDictionary()
        {
            keyword_dict = new Dictionary<string, PPL.OperatorDelegate>();
            keyword_dict.Add("help", FuncHelp);
            keyword_dict.Add("keyword", FuncKeyword);
            // add here other methods & their keywords
            //...
```

```
// add here short help
//help_dict.Add("keyword","short help lines, divided by EndOfLine");
//...
try
{
    if (ppl.ImportList.ContainsKey("MyLib") == false)
    {
        foreach (KeyValuePair<string, PPL.OperatorDelegate> pair in keyword_dict)
            ppl.processing.keyword_dict.Add("MyLib." + pair.Key, pair.Value);
        ppl.ImportList.Add("MyLib", this);
    }
}
catch (Exception io)
{
}
}
//=====
public bool FuncKeyword(List<string> parameters, ref string result, Composite node = null)
{
    try
    {
        //...
    }
    catch (Exception ex)
    {
        ppl.print("Error: ...");
        return false;
    }
    return true;
}
}
}
```

-creation code with methods:

**createulc.exe**

When utility createulc.exe runs without arguments all data is defined in file **Config.cfg**

**Example:**

**name = Test**

**// fullpath where to save generated file or empty**

**path =**

**methods = Sum,Sub,Mult,Div**

**createulc.exe generates 2 files:**

- **<name>.cs** , this file must be added to user's dll project
- **<name>.json** , this file must be added to directory JsonHelp for Assistant.exe

## Examples of code

```
See Examples\scr\Eratosphenes.scr
mode scr
```

[illegible]

Examples\scr\erato.scr

This samples significantly improves performance because all calculations are performed in Erato.DLL and data are saved by Vector.DLL.

```
// calculations in library Erato.dll
import Vector;
import Erato;
debugppl yes;
Vector.DeleteAll();

var m = 1000;
var len = m + 1;
array primes[len];
for (k,0,len)
    set primes[k] = k;
call Vector.Create("VPrimes",m + 1,int);
call Vector.Add("VPrimes",getname(primes));

call Erato.Solve("VPrimes");
var output = "";
var tmp;
for (i,0,len)
{
    set tmp = Vector.Get("VPrimes")(i);
    if (tmp != 0)
        set output = String.Concat(output)(tmp)(",");
}

var index = length(output) - 1;
set output = String.Remove(output)(index)(1);
writeln("{0}",output);
```

The following example performs copying elements from two dimensional storage to one dimensional array

see examples\scr\copyto.scr

```
// copy row elements from first column to last column
// prepare before call destination array
function CopyRowElementsToArray(src,row,first_element,last_element,dst)
{
    write#(src={0} row={1} first_element={2} last_element={3} dst={4})
        (getname(src), row, first_element, last_element, getname(dst));

    for(i, first_element, last_element + 1)
    {
        set dst[i] = sget(src)(row)(i);
    }
}
```



```
}
//=====
// copy column elements from first row to last row
// prepare before call destination array function
CopyColumnElementsToArray(src,column,first_element,last_element,dst)
{
    write#{src={0} column={1} first_element={2} last_element={3} dst={4}}
        (getname(src), column, first_element, last_element, getname(dst));

    for(i, first_element, last_element + 1)
    {
        set dst[i] = sget(src)(i)(column);
    }
}
//=====

import String;
storage(src)(8)(8);
var tmp = 0;
for(i,0,8)
{
    for(j,0,8)
    {
        PlusPlus(tmp);
        sset(src)(i)(j)(tmp);
    }
}
swrite(src);

array dst_row[6];
write#("function CopyRowElementsToArray");
call CopyRowElementsToArray(src,1, 0, 5, dst_row);

var output = "";
var index;

for(i,0,6)
{
    set output = String.Concat(output)(dst_row[i])(",");
};

set index = length(output) - 1;
set output = String.Remove(output)(index)(1); //remove the latest ','
write#("{0}", output );

set output = "";
array dst_column[8];
write#("function CopyColumnElementsToArray");
```

```
call CopyColumnElementsToArray(src, 7, 0, 7, dst_column);

for(i,0,8)
{
    set output = String.Concat(output)(dst_column[i])(",");
};

set index = length(output) - 1;
set output = String.Remove(output)(index)(1); //remove the latest ','
write("{0}")(output );
```

>rc examples\scr\copyto.scr;

results:

	0	1	2	3	4	5	6	7
-----NS.Global.src-----								
[0]	0	1	2	3	4	5	6	7
[1]	8	9	10	11	12	13	14	15
[2]	16	17	18	19	20	21	22	23
[3]	24	25	26	27	28	29	30	31
[4]	32	33	34	35	36	37	38	39
[5]	40	41	42	43	44	45	46	47
[6]	48	49	50	51	52	53	54	55
[7]	56	57	58	59	60	61	62	63

```
function CopyRowElementsToArray
src=src row=1 first_element =0 last_element=5 dst=dst_row
8,9,10,11,12,13
function CopyColumnElementsToArray
src=src column=7 first_element =0 last_element=7 dst=dst_column
7,15,23,31,39,47,55,63
```

Open console window:

**cmd**

and run:

**examples.bat**

**callfunc.bat**

with numerous examples of code.

## References

1. Polymorphic Programming Language

[https://en.wikipedia.org/wiki/Polymorphic\\_Programming\\_Language](https://en.wikipedia.org/wiki/Polymorphic_Programming_Language)

1969 Thomas A. Standish

2. Prototypical Programming Language

<https://www.mathstat.dal.ca/~selinger/ppl/>

2000, Ari Lamstein and Peter Selinger

3. Practical Programming Language

<https://www.ppl-lang.dev/index.html>

4. Introducing Gen, a new PPL language by MIT

Probabilistic Programming Language

<https://becominghuman.ai/introducing-gen-a-new-ppl-language-by-mit-f77397eeff3>

Gen it is packet for Julia

2019, Alexandre Dall Alba

5. Piped Processing Language

<https://opendistro.github.io/for-elasticsearch-docs/docs/ppl/>