DIATraceExtractor V0.2.11: release report (2026-10-14)

Versions. This report accompanies release **V0.2.11** of `DIATraceExtractor` (okohlbacher/dia-trace-extract-prototype). The extraction has not changed since V0.2 (commit 663dc39 = cb466f0 + the report); V0.2.1–V0.2.7 added the `-scheme B` preset, macOS and Windows support, three defect fixes, a faster mzML ingest (V0.2.7: positional reads and an unbounded in-order commit, output byte-identical) and this report's corrections; V0.2.8–V0.2.11 changed no source file, only the Windows build and the install rules, and added binary packages for five platforms (Appendix A). **Every cluster measurement was re-run with the V0.2.11 binary** (`results/v0.2.11/`, `scripts/cluster_bench_v0211.sh`, on `dax` on 2026-10-14): the thread series, the full libraries, the Astral pair table with all four configurations of ours, the diaPASEF comparisons and costs, and the tolerance screens. Its Astral traces (A-V0.2 and B) are bit-identical to those of cb466f0 (V0.2), on which the galleries and the §4 rule emulation were computed, and its calibration reproduces the offsets and widths used there, so those carry over unchanged. Two results moved: the A-V0.1 and P rows of §3, whose archived runs came from a pre-release binary with an older calibration (now ±0.6 points), and the diaPASEF defaults, which now use the m/z-dependent MS1 model (§3). The laptop series (§6) is V0.2.7's, the same source as V0.2.11 on macOS.

What it is. `DIATraceExtractor` is an OpenMS TOPP tool (C++23, OpenMS develop) that extracts DIA fragment and precursor-isotope traces (XICs) from a predicted spectral library and writes them as Parquet or TSV. It calibrates retention time and mass against the run itself, needs no identifications, and does no scoring. This report gathers what has been measured about the quality of its traces and its speed against DIA-NN 1.7.12 and OpenSWATH on two instrument classes, an Orbitrap Astral and a timsTOF SCP (diaPASEF), the design decisions those measurements led to, and what is still open. Details live in the dossier (`00-dossier.md`), the extraction description (`EXTRACTION.md`) and the backlog (`BACKLOG.md`).


Verdict in one paragraph. At equal extraction rules the three tools produce the same traces, on both instruments; the differences between them are rule choices. Ours are the best-supported ones: a mass offset measured from the run (every data set here needs it, by 1–5 ppm, and the timsTOF MS1 needs an m/z-dependent one), tolerances expressed in multiples of the measured error width, and an MS1 window at the corrected m/z, which at DIA-NN's own width captures 98% of the true signal at 1% interference where DIA-NN's export captures 92% at 5% and OpenSWATH 100% at 22%. The extraction runs 19–28× faster than DIA-NN and 55–136× faster than OpenSWATH on the same run and library, in 2.7 GiB, with byte-identical output at 1 and 64 threads and, on run 01, from any of the three readers (fast mzML, OpenMS mzML, mzPeak); on a MacBook Pro (M4 Max) the same run takes 3.3 s at 16 cores, with OpenSWATH at 120 s. Two things are open and both concern the width of the window, not its centre: the tolerance multiple is set per instrument class from an identification screen rather than measured from the run, because the calibration anchors cannot see the interference that sets the optimum; and the MS1 multiple of 4σ is on the narrow side (93% of the modelled true signal captured, §4) and should move to 5–6σ once re-screened.

1. Data, libraries, references

	Orbitrap Astral	timsTOF SCP (diaPASEF)
data set	ProteoBench DIA ion entrapment module: `LFQ_Astral_DIA_15min_50ng_Human_01–03` (PXD070049), 15 min, 50 ng, 5.8 GB mzML each	ProteoBench diaPASEF quantification module: conditions A and B, sample Alpha 01 (PXD062685), 25 ng; `.d` converted to mzPeak, and by this tool to mzML
library	DIALibGen (0.11.0, commit 6f26790; libraries named v0.11.1), human (3.5 M precursors) and entrapment (7.0 M); RT model tuned on DIA-NN's IDs of run 01 (`-rt_mode minutes`)	DIALibGen, HYE mixed species, 4.15 M precursors; predicted RT (`-rt_mode auto`)
reference traces	DIA-NN 1.7.12 (last open-source version, `--xic` export patched), OpenSwathWorkflow (OpenMS develop)	DIA-NN 1.7.12 on our mzML export (1.7.12 reads no `.d`)
restriction for comparisons	DIA-NN's 1% FDR IDs (78–93 k precursors)	DIA-NN's 1% FDR IDs (54,557 A01; 55,665 B01)

Sources, accessions and converters: Appendix B. DIA-NN exports traces only while searching, so its times include the search; OpenSWATH's include its scoring.


2. How the extraction works




- **Run grid.** Every centroid of the run goes into one memory-mapped pool (m/z as uint32 at 1e-5 Th, intensity as float32: 8 bytes per peak), indexed by isolation window and DIA cycle, with MS1 on its own scan axis. Three readers feed it: a fast mzML parser, the OpenMS mzML reader, and the mzpeak-openms library for mzPeak files. All three order tied centroids identically, so the traces are byte-identical whichever reader loaded the run.
- **Ion mobility (diaPASEF).** A diaPASEF MS2 frame is one spectrum that covers several isolation windows, each active over its own 1/K0 band, and holds the centroids of every TIMS scan, so one ion appears once per scan it spans. The reader uses the mobility in two steps and then integrates it out: each centroid is assigned to the isolation window whose mobility band contains it (the bands come from the frame's precursor descriptions), which restores the window selectivity a flat read of the frame would lose; then, within a window, the scans are collapsed: centroids within 15 ppm of each other are summed and placed at their intensity-weighted m/z. The grid then holds one ordinary spectrum per window and cycle and everything downstream is the same as on the Orbitrap. MS1 frames are collapsed over the whole mobility range in the same way. The library's predicted CCS column is not used: a precursor's trace integrates every mobility at which its fragments appear inside the window's band. The mzML export (`-out_mzml`) hands DIA-NN the same collapsed frames, so the comparisons in §3 are between extraction rules, not between mobility

treatments. Mobility as an extraction axis (filtering a precursor's fragments to its predicted 1/K0, or mobility-resolved traces) is the next step for this instrument class and is not part of V0.2.

- **Calibration** (`EXTRACTION.md` §3). A panel of 5% of the library (every k-th row, never the `-ids` subset) is searched for co-eluting fragment apexes: a strict first pass over the whole run yields anchors for a robust LOWESS RT map; a relaxed second pass within ±max(4σ, 30 s) of the map refines it. The apex centroids of the strict anchors give the mass model: a median offset, or a line offset + slope × m/z when the m/z dependence is material (new in V0.2; it matters only on the timsTOF MS1, +15 ppm per 1000 Th; on Astral the fitted slopes are under 1 ppm per 1000 Th and change nothing measurable, `EXTRACTION.md`), and the error width as 1.4826 × MAD of the residuals. Tolerances are multiples of that width.
- **Extraction.** Each precursor's fragments and MS1 isotopes are extracted within ±60 s of the mapped RT (or a measured window, `-rt_window 0`), by a merge join of the sorted target windows against each spectrum's centroids, taking the most intense centroid per window (DIA-NN's rule, `-aggregation max`) or their sum (OpenSWATH's, `sum`).
- **Output.** Traces as Parquet (`-out`, one row per trace, sharded) or as a long TSV (`-out_tsv`), with the axes file (`-out_axes`: global cycle axis, exact acquisition times per window, MS1 scan times), run statistics as JSON (`-out_stats`), the calibration anchors as TSV (`-out_calibration`, reusable as `-rt_anchors`), and the loaded run as a centroided mzML (`-out_mzml`, one spectrum per isolation window).
- **Scheduling.** One worker pool runs library reading, extraction, encoding and writing as task classes rebalanced by pipeline pressure, with in-order issue and an ordered commit, so the output does not depend on the thread count.





The two extraction schemes, A and B. The reference engines differ in a handful of rules, and the tool can follow either set, so that each comparison measures the rules and not the implementation:


rule	A (DIA-NN's rules; the default)	B (OpenSWATH's rules)
value per spectrum	the most intense centroid in the m/z window (`-aggregation max`)	the sum of all centroids in the window (`sum`); the whole column is one preset, `-scheme B`
mass correction	offsets (and the m/z-dependent term) measured from the run (`-mass_calibration auto`)	none: the window sits at the library m/z
tolerance	multiples of the measured widths (`-mz_sigma_ms2`, `-mz_sigma_ms1`), or fixed ppm	DIA-NN's optimised MS2 accuracy for both levels, as the benchmark gave OpenSWATH (`-mz_tol`, `-mz_tol_ms1`)
MS1 isotopes	M+k at m/z + k · 1.00336 / z	M+k at m/z + k · 1.00336 regardless of charge (`-ms1_isotope_spacing unit`)
RT window, MS1 axis	±60 s around the mapped library RT; MS1 at its own scans	the same

Scheme B is a single preset (`-scheme B` , V0.2.1) because its three rules were easy to half-apply: once the measured mass correction became the default, a B command without `-mass_calibration off` extracted at the corrected m/z, and its parity with OpenSWATH fell from 95% to 64% of MS2 traces at r > 0.9 before this was caught (Appendix C). Three configurations of A appear below and are named throughout: **A-V0.2**, the defaults of this release (MS2 9σ, MS1 4σ on Astral); **A-V0.1**, the previous release's fixed rule (MS2 ±6 ppm, MS1 ±2.1 ppm around the measured constant offsets), on which the three-way comparison and the shape metrics of §3–§4 were run; and **P** (parity), A with both tolerances set to DIA-NN's optimised accuracy. Scheme B exists to show that the tool reproduces OpenSWATH's traces; its rules are not recommended (§4). Everything else is shared: the run grid, the RT map, the merge join, the output.

3. Are the traces the same? (both instruments, DIA-NN's IDs)

Astral, run 01, shared tuned library, all 79,953 DIA-NN IDs, every library fragment (`results/v0.2.11/astral/cmpA.tsv` , `cmpB.tsv` , `cmpAV01.tsv` , `cmpP.tsv` ; V0.2.11):


pair	MS2 median r	MS2 r > 0.9	MS1 M+0 median r
ours B vs OpenSWATH	0.9999	95.3%	0.9995
ours P (DIA-NN's tolerances) vs DIA-NN	1.0000	91.4%	0.954
ours A-V0.1 vs DIA-NN	1.0000	91.6%	0.979
ours A-V0.2 (defaults) vs DIA-NN	0.9997	83.1%	0.977
DIA-NN vs OpenSWATH	0.971	62.7%	0.953



(The figure pools runs 01–03 with an earlier configuration, both tolerances at DIA-NN's accuracy and MS1 on the cycle axis, dossier §2; the shape of the distributions is the point.) Ours B reproduces OpenSWATH nearly exactly; ours A reproduces DIA-NN at MS2. The two reference engines disagree with each other more than either disagrees with its matching configuration of ours. The remaining MS2 tail of P against DIA-NN (9% of traces below r = 0.9 in the table; 3.5% of the traces non-zero in both engines, dossier §3.2) is entirely its float32 quadratic window centre, shifted by about 0.5 ppm from ours: emulating that arithmetic reproduces DIA-NN's traces in a 3,000-precursor sample with none of 34,923 traces differing at r < 0.99 or L1 > 0.01 (dossier §3.2). It is a DIA-NN rule choice, and its quadratic describes the true mass error worse than a constant does. At the defaults, A-V0.2's

wider MS2 window (±7.9 ppm against DIA-NN's ±5.9) lowers the share of traces at r > 0.9 to 83%, by construction of the comparison; §4 shows what the wider window does to the traces themselves.

A random sample of the traces, all four arms. The figure shows 12 of 50 randomly drawn precursors (seed 20261010) as mirrored pairs: ours A-V0.2 against DIA-NN, ours B against OpenSWATH, and OpenSWATH against DIA-NN, the top library fragment above and MS1 M+0 below, each trace scaled to its maximum inside DIA-NN's exported span (grey). The full 50 are in `figures/gallery_v02/trace_mirror_random.png`, the same precursors overlaid in `trace_gallery_by_mode.png`, and one figure per mode in `trace_gallery_mode_*.png` (`scripts/trace_gallery_features.py`, `trace_gallery.py`, `trace_gallery_mirror.py`).



Each of the 73,350 precursors with traces in all four arms is assigned one divergence mode from the per-trace metrics (first matching rule wins; thresholds anchored on the B-vs-OpenSWATH re-implementation noise floor):

mode	share	in the random 50
all engines agree	19.0%	9
minor differences	27.1%	16
MS1 differs, ours A vs DIA-NN (MS2 agrees)	25.6%	10
MS2 shape differs, DIA-NN higher	11.5%	9
MS2 shape differs, OpenSWATH higher	3.6%	1
DIA-NN's XIC span off-centre (truncated common span)	6.2%	3
low signal / noisy	5.9%	2
scale only (sum vs max)	1.2%	0

No mode is caused by an RT shift: all engines read the same spectra. The "MS2 shape differs" modes are the OpenSWATH window centre (§4) and DIA-NN's quadratic centre; the "MS1 differs" mode is DIA-NN's MS1 export at the uncorrected m/z against our corrected, narrow window (§4), visible in the figure as DIA-NN's MS1 trace carrying extra peaks ours does not. The galleries were regenerated for this release (the 2026-10-10 versions in `figures/` show the earlier configuration of the correlation figure).

timsTOF diaPASEF, runs A01 and B01, DIA-NN 1.7.12 on our mzML export, DIA-NN's IDs, every library fragment (`results/v0.2.11/diapasef/cmp_*.tsv`; V0.2.11). Calibration finds 775 / 710 anchors in these 25 ng samples (342–374 used for the mass model), MS2 width 2.7 ppm; the MS1 error carries an m/z slope of +13–15 ppm per 1000 Th, so the defaults use the m/z-dependent model, MS1 width 2.2 ppm (3.2 ppm constant):

ours vs DIA-NN	MS2 median r	MS2 r > 0.9	MS1 r > 0.9
A01, defaults (4σ: MS2 ±10.8, MS1 ±8.9 ppm, m/z-dependent)	0.992	86.0%	57%
A01, defaults with the constant MS1 model (MS1 ±12.9 ppm)	0.992	86.0%	63%
A01, at DIA-NN's ±11.8 ppm	0.9994	91.9%	61%
B01, defaults (4σ: MS2 ±10.6, MS1 ±8.7 ppm)	0.974	76.0%	59%
B01, at ±11.8 ppm (DIA-NN: ±12.6)	0.995	89.2%	64%

At equal tolerance the engines agree on diaPASEF as on Astral; at the defaults the slightly narrower window costs a few points, again by construction. The MS1 agreement of 57–64% looked like a defect and is not: where both engines have signal the values are identical, and each has zeros where the other has signal, so the two windows sit at different centres. Placing our MS1 window at the uncorrected library m/z with DIA-NN's MS2 accuracy raises the agreement to 79%, and widening that uncorrected window to ±20 ppm drops it to 43% (`cmp_A01_ms1raw11.8.tsv`, `cmp_A01_ms1raw20.tsv`, top 6 fragments): DIA-NN's export rule of §4, visible here because the MS1 offset is 3.5 ppm plus the m/z slope instead of Astral's 1.3 ppm. The m/z-dependent model moves our MS1 centre further from the uncorrected one, which is why it lowers the agreement from 63% to 57%. Our MS1 traces are the mass-corrected ones.

4. Which rules are right? (re-extraction from the raw centroids, 3,000 IDs)

How this was assessed. There is no ground truth for a trace, so the rules were judged on the centroids themselves. For a random sample of 3,000 DIA-NN-identified precursors of Astral run 01, every centroid within ±25 ppm of each fragment and MS1 isotope target was recorded at every point of the trace (`scripts/quality_reextract.py`, reading the mzML directly). A mass-error model was fitted to the apex centroids of the top-6 fragments of the confident IDs: a mean μ(m/z, intensity), quadratic in m/z with an upward drift for strong centroids, and a width σ(intensity) = √(0.83² + 70²/I)

ppm, i.e. 2.4 ppm at 10^3 and 0.86 ppm at 10^5. A centroid is counted as true signal when it lies within 3σ(I) of μ. Each engine's rule (window centre, width, max or sum) is then applied to the recorded centroids; **capture** is the share of the true signal in the peak region (apex ±4 cycles) that the rule returns, **interference** the share of what it returns that is not true signal (an upper bound, since the tails of the error distribution hold real signal too). Shape metrics are computed on the same re-extracted traces: **co-elution** is the mean pairwise Pearson r of a precursor's fragment traces over ±4 cycles around the apex, **cosine at apex** the cosine between the square-rooted apex intensities and the library intensities, **dropouts** the share of fragments without signal at the apex. The rule emulation was validated first: for every engine it reproduces the engine's own exported traces with a median r of 1.0 (`scripts/quality_sample.py`, `scripts/quality_v02_rules.py`, `results/analysis/quality/`; details in `analysis/trace_quality.md`).

MS2 (DIA-NN's accuracy ±5.9 ppm; ours A at the V0.2 defaults, 9σ = ±7.9 ppm around the measured offset with its m/z term):


rule	capture	interference	co-elution	cosine at apex	dropouts
ours A (V0.2 defaults, max, ±7.9 ppm)	**99.9%**	4.7%	0.521	0.920	14.8%
DIA-NN (quadratic centre, max, ±5.9 ppm)	99.5%	2.8%	0.522	0.919	14.9%
ours B = OpenSWATH (no correction, sum, ±5.9 ppm)	97.3%	3.1%	0.467	0.903	16.9%

Ours A and DIA-NN give the same trace shapes; A's wider window trades 1.9 points of interference for the last 0.4% of signal (at ±5.9 ppm around our offset it is 99.6% / 2.9%, indistinguishable from DIA-NN). B's loss is its centre: with no correction, the ±5.9 ppm window ends only 2.7 ppm beyond the true −3.2 ppm offset. Max versus sum is irrelevant on Astral MS2: at most 4×10^{-5} of the points hold two centroids in one window.


MS1, M+0 (peak region apex ±6 MS1 scans; truth model 3σ(I) around the MS1 median, σ 0.85 ppm):

rule	capture	interference
ours A (V0.2 defaults: measured offset with m/z term, max, 4σ = ±1.43 ppm)	92.6%	**0.0%**
ours A at DIA-NN's width (measured offset, ±2.13 ppm)	**98.0%**	0.9%
DIA-NN export (uncorrected m/z, max, ±2.13 ppm)	91.6%	5.4%
ours B = OpenSWATH (no correction, sum, ±5.9 ppm)	100%	22%

The corrected centre is what matters: at DIA-NN's own width it captures 98% at 0.9% interference where DIA-NN's uncorrected export captures 92% at 5.4%, and the wide OpenSWATH window admits a quarter of its peak intensity as interference. The 4σ default is on the narrow side by this truth model: the width measured on the anchors (0.36 ppm) comes from strong apex centroids, while weak MS1 centroids scatter more (the intensity dependence of the errors, `EXTRACTION.md`), so ±1.43 ppm leaves 7% of the modelled true signal outside. At ±2.1 ppm around our offset (A-V0.1), MS1-to-fragment co-elution on the exports ranks ours (0.886) above DIA-NN (0.880) and OpenSWATH (0.826); the 4σ export has not been shape-scored. A 5–6σ MS1 default is the change this points at. OpenSWATH additionally places isotope k at m/z + k·1.00336 without dividing by the charge, so its M+1 and M+2 traces of charge ≥ 2 precursors are a different ion.



5. Trace quality as a function of the tolerance (both instruments)



The DIA-NN-identified precursors of each run extracted at k × σ, k = 1 … 12, and scored on the traces (`scripts/tolerance_screen.py`, V0.2.11, `results/v0.2.11/tolscreen/`; σ as measured by the calibration of the time, with the constant mass model: Astral 0.92 / 0.40 ppm, timsTOF 2.66 / 3.38 ppm for MS2 / MS1; window centres from the V0.2.11 calibration). The optima are those of the original screen (binary 4934ea5, `results/tolscreen/`); the V0.2 calibration raises Astral's co-elution at every k (0.23 against 0.19 at the optimum):

	MS2 co-elution optimum	MS1 co-elution optimum	DIA-NN's own accuracy
Astral run 01	k = 8–10 (±7.4–9.2 ppm)	k = 4 (±1.6 ppm)	6.4σ (±5.9 ppm)
timsTOF A01	k = 4–5 (±10.6–13.3 ppm)	k = 4 (±13.5 ppm)	4.4σ (±11.8 ppm)

On Astral the MS2 curve saturates (heavy error tail, dropouts keep falling); on timsTOF it peaks and falls (Gaussian errors, interference costs beyond 5σ). DIA-NN's optimised accuracy sits at each instrument's optimum. The screen's Astral MS2 σ of 0.92 is the constant model's; the V0.2 linear model gives 0.88, hence ±7.9 ppm for 9σ in §3–§4. MS1 peaks at 4σ on both instruments, but the timsTOF MS1 width has since dropped from 3.38 to 2.2 ppm with the m/z-dependent model, so the same ±13.5 ppm optimum is 6σ of the new width: the MS1 multiple has to be re-screened (§4).


Can the calibration find the multiple by itself? Not as a rule. The anchors' own co-elution curve does peak at the Astral optimum (k = 8), but every anchor-based criterion tried rises monotonically to 8σ on timsTOF too: the all-fragment co-elution curve of the anchors, the same on the weaker half of the anchors, on their weak fragments only, and on both; and the anchor yield at a 1% decoy-calibrated false rate, which the shifted-fragment decoys make meaningless (0–5 decoys per run). Anchors are present precursors whose fragments stay correlated as the window widens; the screen's optimum comes from interference in weak and absent precursors, a population the calibration does not have. **Decision:** the multiples are set per instrument class from the run's metadata (MS2 9σ Orbitrap/Astral, 4σ timsTOF and other TOF, 6σ with a warning when unknown; MS1 4σ), as explicit

options (`-mz_sigma_ms2`, `-mz_sigma_ms1`; `-mz_tol*` for fixed ppm). A measured criterion needs a population containing absent peptides, i.e. peptide decoys from the library generator (backlog).

6. Performance

Machine: 2 × AMD EPYC 9654 (`dax`: 192 cores, SMT, 2.3 TB), shared node at a load of 3–11 (≤ 0.03 per hardware thread) during the V0.2.11 runs; inputs on local `/scratch`; one run per point unless stated; peak RSS from `/usr/bin/time`.

Runtime vs threads, Astral run 01, shared tuned library (82,333 precursors, all fragments); ours V0.2.11 (`results/v0.2.11/threads/`), DIA-NN and OpenSWATH from the cb466f0 series with unchanged binaries (`results/threads_cb466f0/`):



threads	ours A (defaults)	ours B (OpenSWATH rules)	DIA-NN 1.7.12	OpenSwathWorkflow
1	12.5 s / 2.3 GiB	12.0 s / 2.4 GiB	–	–
2	6.8 s	6.6 s	–	–
4	4.0 s / 2.4 GiB	4.0 s / 2.4 GiB	115 s / 1.7 GiB	227 s / 10.5 GiB
8	2.6 s	2.3 s	59 s	189 s
16	1.6 s	1.6 s	34 s	183 s
32	1.3 s	1.3 s	26 s	183 s
64	1.4 s / 2.6 GiB	1.2 s / 2.7 GiB	27 s / 3.3 GiB	182 s / 14.1 GiB

Ours is 29× faster than DIA-NN at 4 threads and 19–22× from 16 threads up, and 57–147× faster than OpenSWATH. Ours flattens beyond 32 threads at this library size: the tool's own stages take 0.7 s at 64 threads (ingest 0.25 s, calibration 0.05 s, extraction 0.36 s; tool total 0.98 s), the remaining 0.4 s is process start-up and teardown; B, which skips the calibration, is 0.1 s faster. OpenSWATH stops scaling at 8 threads while its memory grows to 14 GiB. Ours read the inputs from local disk, the references from the network file system (Appendix C); the references were not run below 4 threads. Against the cb466f0 series the V0.2.7 ingest changes are within the run-to-run spread on Linux (64 threads: 1.44 s for cb466f0, 1.28 s for V0.2.7 at a load of about 50, 1.35 s for V0.2.11 on the quiet node), as expected: libstdc++ never had the small-read problem described for the laptop below.


Full libraries, Astral run 01, 64 threads, top 6 fragments, V0.2 defaults, V0.2.11 binary (`results/v0.2.11/full/`):

library	tool total (wall incl. start-up), 2 runs	ingest	calibration	extraction	peak RSS	traces
human, 3.49 M precursors	5.0–5.1 s (5.4–5.5 s)	0.3 s	0.4–0.5 s	2.9–3.1 s	3.8 GiB	31.3 M
entrapment, 7.0 M precursors	8.1–8.4 s (8.6–8.8 s)	0.3 s	0.9–1.0 s	5.4–5.7 s	4.7 GiB	63.0 M

Measured on `dax` at a load of 5–11; V0.2.7 had measured 5.7–5.8 s and 8.0–9.3 s at a load of 45–55, cb466f0 5.6–5.9 s and 9.1 s at a load of about 21, and 6d26c49 8.6–9.0 s on the entrapment library on a quieter node (dossier §4). The thread table above uses `/usr/bin/time` wall clock, this one the tool's own total.

diaPASEF (A01 and B01, 4.15 M-precursor library, 32 threads, V0.2.11, `results/v0.2.11/diapasef/odia_*_all.log`): 44 s each (45 s wall incl. start-up), 15.5 GiB peak RSS, 36.7 M traces; the mzPeak per-spectrum read and the mobility collapse take 27 s of it, the calibration 4–5 s, the extraction 12 s. The peak falls in the ingest, while the calibration panel is extracted concurrently, and varies between runs (13.5–16.5 GiB over the archived runs).

On a laptop (MacBook Pro, Apple M4 Max: 12 performance + 4 efficiency cores, no SMT, 128 GiB, macOS 26.6, inputs on the internal SSD, Homebrew libomp; Appendix C). Same run and shared library, V0.2.7 binary (318e5aa, `results/macos-benchmark/v0.2.7/`), mean of two repeats on mains power (repeats within 2 %):



threads	ours A	ours B	OpenSwathWorkflow
1	6.2 s / 1.9 GiB	5.9 s / 2.0 GiB	–
2	3.2 s	3.1 s	–
4	1.7 s	1.6 s	–
8	0.94 s	0.89 s	–
12 (performance cores)	0.74 s	0.69 s	–
16	0.70 s / 2.2 GiB	0.66 s / 2.2 GiB	120 s / 12.8 GiB

The full 7.0 M-precursor library takes 14.2–15.3 s at 16 threads in 4.0 GiB (ingest 0.3 s, extraction about 9.6 s at 11.6 active cores, the rest calibration panel and final drain). Per core the laptop is the faster machine, and in absolute terms it now matches the node: 0.70 s at 16 cores against 0.98 s at 64 threads on the node (OpenSWATH: 120 s against 183 s); ours A speeds up 8.9× from 1 to 16 threads.

The laptop's V0.2.3 series (3.3 s at 16 threads, 41 s at 1 thread, 19–23 s of system time) exposed what V0.2.7 fixes (`12-macos-benchmark-note.md`): libc++'s `ifstream::read` refills a 4 KiB buffer with one `read()` per 4 KiB, and macOS serialises concurrent small reads of one file in the kernel, so the two passes over the 5.8 GB mzML (~2.9 M syscalls) cost 21 s of system time at 16 threads and kept the ingest at about 3 s regardless of the thread count (libstdc++ reads large requests directly, so the node never showed it); and the ordered chunk pipeline's look-ahead of 32 chunks kept the workers waiting on the in-order commit 85 % of the time, on Linux as well. Both passes now use positional reads (`platform::FileReader`), and the fast parser's look-ahead is unbounded (a parked chunk holds only metadata; +40 MB peak RSS). Ingest at 16 laptop threads 2.9 → 0.27 s, 1 thread 41 → 6.2 s overall; traces and axes byte-identical to V0.2.3 at 1 and 16 threads. The laptop had also exposed

three defects, all present on Linux too; the first two were fixed on the laptop (tag V0.2.3), the third on the node (V0.2.4):

- `--help` aborted (an unregistered TOPP subsection, since `calibration:mass_model` became a visible option on 2026-10-12; `--helphelp` had aborted on every build);
- every run aborted after writing its output, because OpenMP workers hand their thread-local buffer caches back to a pool that a static destructor had already torn down; glibc tolerates the dead mutex, libc++ throws. The pool is now never destroyed;
- `-threads 1` fell back to the serial OpenMS mzML parser instead of the chunk parser with one worker: 70 s instead of 14 s on the node for the shared library (`results/threads_cb466f0/t1/odiaA_serial_parser.log` vs `odiaA.log`); 41 s instead of 6.2 s on the laptop.

What the speed rests on beyond the design of §2 (dossier §4, `06-parallel-efficiency.md`, `07-contention-diagnosis.md`): the parsers decode straight into the peak pool; a bucket index over m/z skips gaps in the merge join; trace and Arrow buffers are recycled with a per-thread cache; 32 Parquet parts are written by their own tasks. The library-load transient (decoded row groups, parts and the joined copy coexisting) and the mzPeak reader's serialised decode (scales to 10–14 cores) are the known remaining costs.

7. Reproduction

- Code: https://github.com/okohlbacher/dia-trace-extract-prototype, release tag `V0.2.11` (this report is attached to the release); build instructions in Appendix A, data sources in Appendix B, command lines in Appendix C.
- Benchmarks: `scripts/benchmark_refined.sh` (three-way comparison on a shared recalibrated library), `scripts/bench_threads.sh` (thread series), `scripts/bench_macos.sh` (laptop), `scripts/plot_machine_scaling.py`, `scripts/compare_traces.py` (pairwise metrics), `scripts/quality_reextract.py`, `quality_sample.py` and `quality_v02_rules.py` (§4), `scripts/tolerance_screen.py` and `plot_tolerance_screen.py` (§5), `scripts/plot_thread_scaling.py` (§6), `scripts/doc_figures.py` (§2 figures). Mass-error dumps: `ODIA_DUMP_MASS_ERRORS=file`.
- Inputs: Appendix B; libraries in `library/` (DIALibGen 0.11.0 + 6f26790, `library/generate.sh`, `library/hye_timstof.log`).
- Tests: `ctest` in the build directory (7 tests: TraML extraction, OpenSWATH parity, byte-level Parquet compare).

Appendix A: repository and installation

Repository. https://github.com/okohlbacher/dia-trace-extract-prototype, tag `V0.2.11`. History: V0.2 (663dc39) the extraction as benchmarked; V0.2.1 the `-scheme` preset; V0.2.2 macOS portability; V0.2.3 the `--help` and exit-time fixes (laptop branch); V0.2.4 the one-thread ingest fix and the laptop results; V0.2.5 the report's version stamp; V0.2.6 release packages for Linux, macOS and Windows (platform layer, release CI); V0.2.7 the mzML ingest with positional reads and an unbounded in-order commit, and the re-measured §6; V0.2.8 release builds for five platforms; V0.2.9 self-contained Windows packages (x86_64, arm64); V0.2.10 a relocatable macOS package; V0.2.11 the first macOS package signed with the project's Developer ID and notarized. The mzPeak reader is the submodule `external/mzpeak` (okohlbacher/mzpeak-openms, tag `partitioned-read-2026-10-11`); the library generator is okohlbacher/DIALibGen (0.11.0, commit 6f26790 on branch `compact-parquet-plain-strings`, which also carries the build fix for current OpenMS develop).

Binary releases. Every tag is built, tested (ctest plus an extraction from the installed folder in a clean environment) and packaged by `.github/workflows/release.yml` against the OpenMS commit pinned in `ci/openms.lock`. The GitHub release carries self-contained folders with the tool, the libraries it links and OpenMS's shared data:

platform	package	run
Linux x86_64, aarch64 (glibc ≥ 2.39)	`DIATraceExtractor-0.2.11-linux-<arch>.tar.gz`	`bin/DIATraceExtractor`
macOS Apple silicon	`…-macos-arm64.tar.gz`, `.dmg`	`bin/DIATraceExtractor`
Windows x86_64, arm64	`…-windows-<arch>.zip`	`bin\DIATraceExtractor.exe`

```
brew tap okohlbacher/odia && brew install diatraceextractor      # macOS; the tap tracks the
latest release
```

The macOS package is signed with the Developer ID (hardened runtime), notarized, and the `.dmg` stapled; from a tarball or Homebrew the first start can take minutes while macOS checks each bundled library online once (a tarball cannot carry the ticket). The Windows packages bundle the Visual C++ and OpenMP runtimes but are not code-signed yet, so SmartScreen warns on first start.

Building from source. Requirements. Linux, GCC ≥ 13, CMake ≥ 3.24, Ninja; an OpenMS develop (≥ 3.7) build tree with its vcpkg dependencies, which provide Arrow/Parquet and, with `boost-json` and `boost-program-options` added to the OpenMS vcpkg manifest, the Boost ≥ 1.89 the mzPeak library needs (another `BoostConfig.cmake` directory can be given with `-DMZPEAK_BOOST_DIR`). Python 3 with pyarrow, pandas, numpy and matplotlib (`tools/pyenv` here) for the scripts; `markdown` and `weasyprint` for the PDF.

```
git clone https://github.com/okohlbacher/dia-trace-extract-prototype.git && cd dia-trace-
extract-prototype
git checkout V0.2.11
git submodule update --init
# OpenMS develop, built with its vcpkg manifest (here at OpenMS/OpenMS-build via `cmake --
preset linux-x64-release`)
O=$PWD/OpenMS/OpenMS-build
cmake -S . -B build -G Ninja -DCMAKE_BUILD_TYPE=Release -DCMAKE_PREFIX_PATH="$O;$O/
vcpkg_installed/x64-linux-dynamic"
cmake --build build -j 16
ctest --test-dir build        # 7 tests: TraML extraction, OpenSWATH parity, byte-level Parquet
compare
```

macOS (Apple silicon) from source. Supported since V0.2.2 (the Linux-only calls are guarded). `scripts/bench_macos.sh` builds OpenMS develop (its `macos-arm64-release` preset, Homebrew libomp; 1–3 h the first time) and the tool, fetches the inputs and runs the benchmark, one phase at a time or `all`; the ctest suite passes on macOS (7/7).

Use.

```
# defaults: RT map, mass offsets and tolerances measured from the run; +-60 s around the
library RT
# (-rt_mode minutes: tuned libraries carry run minutes; auto: predicted RT, the map is fitted
from the run)
build/DIATraceExtractor -in run.mzML -lib library.parquet -rt_mode minutes -threads 64 \
  -out traces.parquet -out_stats stats.json -out_calibration anchors.tsv
build/DIATraceExtractor -in run.mzpeak -lib library.parquet -rt_mode auto -threads 64 -out
traces.parquet
build/DIATraceExtractor -in run.mzpeak -out_mzml run.mzML            # the loaded run as
centroided mzML, for other tools
build/DIATraceExtractor --help                                       # all options, including
calibration:*
```

Input formats: mzML (indexed, centroided) and mzPeak; libraries as DIALibGen compact Parquet, DIA-NN/OpenSWATH TSV, TraML or PQP.

Appendix B: data sets

Orbitrap Astral (ProteoBench DIA ion entrapment module). Three single-species human runs of the "LFQ Benchmark Dataset - Generation Beta" (Van Puyvelde et al., Dhaenens lab, Ghent; ProteomeXchange **PXD070049**, https://www.ebi.ac.uk/pride/archive/projects/PXD070049): `LFQ_Astral_DIA_15min_50ng_Human_01/02/03.raw`, Orbitrap Astral, 15-min gradient, 50 ng. ProteoBench mirrors them with the module's search database:

file	source
`LFQ_Astral_DIA_15min_50ng_Human_01.raw` (3.1 GB), `_02.raw`, `_03.raw`	https://proteobench.cubimed.rub.de/raw DIA-astral-entrapment/ (also `all_data_Entrapment_DIA_Astral.ta` 5.6 GB)
`ProteoBenchFASTA_Entrapment_Human_with_contaminants_entrapment_pep.zip` (2,841,736 peptide-level entries: human targets, contaminants and entrapment peptides, 1:1)	https://proteobench.cubimed.rub.de/fas
`UP000005640_9606.fasta` (UniProt human reference proteome, 20,652 entries; the human library)	https://www.uniprot.org/proteomes/ UP000005640

The `.raw` files were converted to centroided, indexed mzML with OpenMS `FileConverter` from the same OpenMS develop build (Thermo raw read through its ThermoRawFileParser bridge, vendor centroiding; `benchmark-data/DIA-astral-entrapment/mzML/convert_*.log`); mzPeak variants were made with mzpeak-convert 0.17.2 / 0.18.0 and with this tool's `MzMLToMzPeak`.

timsTOF SCP diaPASEF (ProteoBench DIA quantification, precursor-ion level, diaPASEF module). Three-species mixture (human, yeast, E. coli commercial digests in the proportions of Van Puyvelde et al., 2022, Scientific Data 9:126, https://www.nature.com/articles/s41597-022-01216-6; expected log2 A/B: human 0, yeast −1, E. coli +2), 25 ng in triplicate, Bruker timsTOF SCP with an UltiMate 3000 RS nanoLC and a 25 cm IonOpticks Aurora column, diaPASEF with precursor m/z 400–1000, 1/K0 0.64–1.37, 0.96 s cycle. ProteomeXchange **PXD062685** (announced by the module; at the time of writing the files are served by ProteoBench):

file	source
`ttSCP_diaPASEF_Condition_A_Sample_Alpha_01_11494.d.zip` (7.3 GB), `..._Condition_B_Sample_Alpha_01_11496.d.zip` (7.1 GB); replicates 02/03 of both conditions available, not used	https://proteobench.cubimed.rub.de/raws/diaPASEF/
`ProteoBenchFASTA_MixedSpecies_HYE.zip` (31,889 entries: three proteomes plus contaminants prefixed `Cont_`, Frankenfield et al., J. Proteome Res. 2022)	https://proteobench.cubimed.rub.de/fasta/ProteoBenchFASTA_MixedSpecies_HYE.zip

The `.d` folders were converted with mzpeak-convert 0.18.0 (`benchmark-data/diaPASEF/convert_*.log`); the mzML files DIA-NN read are this tool's `-out_mzml` export of the loaded grid.

Reference software. DIA-NN 1.7.12 (https://github.com/vdemichev/DiaNN, release 1.7.12, the last open-source version; built here with a one-line fix to its `--xic` export, `tools/DiaNN-1.7.12/`); OpenSwathWorkflow from the OpenMS develop build used for the tool itself; DIALibGen 0.11.0 + 6f26790 (https://github.com/okohlbacher/DIALibGen) with AlphaPeptDeep ONNX models for the predicted libraries.

Appendix C: command lines

Paths: `$P` = the repository, `$S` = `/scratch/$USER/odia-bench` (inputs staged from `benchmark-data/` and `library/`), `$X` = `build-stream/DIATraceExtractor` at the commit named, `$DIANN` = `tools/DiaNN-1.7.12/diann-1.7.12-xicfix`, `$OSW` = `OpenMS/OpenMS-build/bin/OpenSwathWorkflow`. The libraries in each tool's format come from `scripts/lib_to_diann17_tsv.py` (`--rt_scale 1`) and `scripts/lib_to_openswath_tsv.py` (`--rt_scale 60`). DIA-NN's XICs are converted with `scripts/`

`diann17_xic_to_parquet.py`, OpenSWATH's with `TextExporter -xic:mode explode`; the pairwise metrics come from `scripts/compare_traces.py`.

V0.2.11 re-run (`results/v0.2.11/`). `scripts/cluster_bench_v0211.sh` repeats every extraction of ours below with the V0.2.11 binary (`X=bin-releases/DIATraceExtractor-0.2.11`, sha256 85120b9d…; `STEPS` selects: 1 thread series, 2 full libraries, 3 Astral A-V0.2/B with `scripts/same_traces.py` against the cb466f0 outputs, 4 diaPASEF, 5 Astral A-V0.1/P, 6 tolerance screens) and recomputes the comparisons against the archived DIA-NN and OpenSWATH traces. A-V0.1 is `-mz_tol 6 -mz_tol_ms1 2.114775 -calibration:mass_model constant` (the MS1 width of the archived run).

Astral, three-way comparison on the shared tuned library (§3, §4; `RECAL=tuned LIB=library/proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01.parquet X=build-stream/DIATraceExtractor scripts/benchmark_refined.sh 01|02|03 64`, binary cbad9dd, A-V0.1 for ours A). Run 01 shown; runs 02 and 03 differ only in the run and the library's `_ids_runNN` suffix.

```
# DIA-NN 1.7.12, round 1 on the predicted library (gives the IDs that restrict the shared
library), then round 2 with XICs
$DIANN --f $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML --lib library/diann17/
proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01.tsv \
       --out report.tsv --temp temp --threads 64 --verbose 1 --qvalue 0.01
$DIANN --f $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML --lib lib_diann17.tsv --out
report.tsv --temp temp \
       --threads 64 --verbose 1 --qvalue 0.01 --xic 60
# ours A-V0.1 (MS2 +-6 ppm, MS1 measured), ours P (DIA-NN parity: both tolerances = DIA-NN's
5.9051 ppm), ours B (OpenSWATH rules)
$X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib library/refined/
proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01_ids_run01.parquet \
   -rt_mode minutes -rt_window 60 -top_fragments 0 -mz_tol 6 -mz_tol_ms1 0 -aggregation max -
mass_calibration auto -threads 64 -out odiaA.parquet -out_stats odiaA.json
$X ... -mz_tol 5.9051 -mz_tol_ms1 5.9051 -aggregation max -mass_calibration auto -threads 64 -
out odiaP.parquet
$X ... -mz_tol 5.9051 -mz_tol_ms1 5.9051 -scheme B -threads 64 -out odiaB.parquet        #
V0.2.1; before: -mass_calibration off -aggregation sum -ms1_isotope_spacing unit
# OpenSwathWorkflow (full window = 2 x DIA-NN's accuracy)
$OSW -in benchmark-data/DIA-astral-entrapment/mzML/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -tr
lib_openswath.tsv -out_chrom osw.xic -out_features osw.featureXML \
     -rt_extraction_window 120 -mz_extraction_window 11.8102 -mz_extraction_window_unit ppm -
mz_extraction_window_ms1 11.8102 -mz_extraction_window_ms1_unit ppm \
     -ms1_isotopes 2 -Calibration:auto_irt:enabled false -threads 64
```

Astral, runtime vs threads (§6; `ODIA_ONLY=1 REF=results/threads scripts/bench_threads.sh results/threads_cb466f0 4 8 16 32 64`, binary V0.2.11, `results/v0.2.11/threads/`; V0.2.7 in `results/threads_v0.2.7_d963cb5/`, the cb466f0 series in `results/threads_cb466f0/`). `$t` = 1 … 64; DIA-NN and OpenSWATH as above with `--threads $t` / `-threads $t` (`results/threads/`, unchanged binaries, reading the mzML from `benchmark-data/` on the network file system rather than `$S`).

```
# ours A: the V0.2 defaults (tolerances by instrument class, m/z-dependent offset when
material)
$X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib $S/input/
proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01_ids_run01.parquet \
   -rt_mode minutes -rt_window 60 -top_fragments 0 -threads $t -out $S/out/t$t/odiaA.parquet
# ours B
$X ... -rt_mode minutes -rt_window 60 -top_fragments 0 -mz_tol 5.9051 -mz_tol_ms1 5.9051 -
scheme B -threads $t -out $S/out/t$t/odiaB.parquet
```

Astral, full libraries (§6; `results/v0.2.11/full/`, binary V0.2.11, top 6 fragments, 2 runs each; earlier: `results/full_v0.2.7_318e5aa/`, `results/full_cb466f0/`).

```
$X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib library/
human_UP000005640_astral_nce25_v0.11.1_tuned_run01.parquet -rt_mode minutes -threads 64 -out
$S/out/full_human.parquet
```

```
$X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib $S/input/
proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01.parquet -rt_mode minutes -threads 64 -
out $S/out/full_entrap.parquet
```

Astral, trace galleries and the V0.2 pair table (§3; `results/gallery_v02/`, binary cb466f0, traces bit-identical to V0.2.11's, `results/v0.2.11/astral/same_as_cb466f0.txt`; rule B as `-scheme B`, §2).

```
 $X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib $S/input/
proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01_ids_run01.parquet \
   -rt_mode minutes -rt_window 60 -top_fragments 0 -threads 32 -out results/gallery_v02/
odiaA.parquet -out_stats results/gallery_v02/odiaA.json
$X ... -mz_tol 5.9051 -mz_tol_ms1 5.9051 -scheme B -threads 32 -out results/gallery_v02/
odiaB.parquet
tools/pyenv/bin/python scripts/compare_traces.py --odia results/gallery_v02/odiaA.parquet --
axes results/gallery_v02/odiaA.axes.parquet \
    --diann results/gallery_v02/diann/diann_xic.parquet --openswath results/gallery_v02/
osw_traces.parquet --out results/gallery_v02/cmpA.tsv
tools/pyenv/bin/python scripts/trace_gallery_features.py results/gallery_v02 results/analysis/
gallery_v02/features_run01.parquet
tools/pyenv/bin/python scripts/trace_gallery.py results/gallery_v02 results/analysis/
gallery_v02/features_run01.parquet docs/figures/gallery_v02 results/analysis/gallery_v02/
gallery_run01
tools/pyenv/bin/python scripts/trace_gallery_mirror.py results/gallery_v02 results/analysis/
gallery_v02/gallery_run01_selection.tsv docs/figures/gallery_v02 --sample random
```

Laptop series (§6; `scripts/bench_macos.sh bench`, binary V0.2.7 = 318e5aa, on mains power, `OMP_WAIT_POLICY=PASSIVE`; machine and defects: `docs/12-macos-benchmark-note.md`). The same ours A / ours B commands as the thread series with `$t` in 1 2 4 8 12 16, timed with `/usr/bin/time -l`; the full library at 16 threads; `RUN_OSW=1` for the OpenSwathWorkflow run (same options, `-threads 16`). Results: `results/macos-benchmark/v0.2.7/` (tarball, `bench-v0.2.7b.log`; the V0.2.3 series in `results/macos-benchmark/`), summarised in `docs/figures/laptop_m4max_summary.tsv`.

Astral, mass-error structure and the linear-vs-constant check (`EXTRACTION.md`, mass model; binary 4e89acc and its parent).

```
 ODIA_DUMP_MASS_ERRORS=astral01.tsv $X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib
$S/input/proteobench_entrapment_astral_nce25_v0.11.1_tuned_run01.parquet -rt_mode minutes -
threads 48 -out ...
$X -in $S/input/LFQ_Astral_DIA_15min_50ng_Human_01.mzML -lib library/refined/
proteobench_entrapment_astral_nce25_v0.11.1_shared_run01.parquet -rt_mode minutes -ids results/
tolscreen/astral_run01_ids.txt -threads 32 -out astral01_lin.parquet
$X ... -calibration:mass_model constant -out astral01_const.parquet
```

Tolerance screen (§5; `scripts/tolerance_screen.py`, binary V0.2.11 via `--extractor`, `results/v0.2.11/tolscreen/`; first run with 4934ea5). The script runs the extractor once per k with `-mz_tol k*sigma_ms2 -mz_tol_ms1 k*sigma_ms1 -top_fragments 0 -ids ...` and scores the traces.

```
 tools/pyenv/bin/python scripts/tolerance_screen.py --run $S/input/
LFQ_Astral_DIA_15min_50ng_Human_01.mzML \
    --lib library/refined/proteobench_entrapment_astral_nce25_v0.11.1_shared_run01.parquet --
ids results/tolscreen/astral_run01_ids.txt \
    --sigma-ms2 0.92 --sigma-ms1 0.40 --rt_mode minutes --out results/tolscreen/astral_run01
tools/pyenv/bin/python scripts/tolerance_screen.py --run $S/input/diapasef/A01.mzpeak --lib
library/hye_timstof.parquet --ids results/diapasef/diann_A01_ids.txt \
    --sigma-ms2 2.66 --sigma-ms1 3.38 --rt_mode auto --out results/tolscreen/timstof_A01
tools/pyenv/bin/python scripts/plot_tolerance_screen.py docs/figures/tolerance_screen "Astral
run 01=results/tolscreen/astral_run01.tsv:6.4" "timsTOF A01=results/tolscreen/timstof_A01.tsv:
4.4"
```

timsTOF diaPASEF (§3, §6; `results/v0.2.11/diapasef/`, earlier runs and DIA-NN in `results/diapasef/`). `.d` to mzPeak with mzpeak-convert 0.18.0; the mzML for DIA-NN is this tool's export of the loaded grid; `B01` identical with the B-condition files.

```
/ceph/ibmi/abi/oliver/bin/mzpeak-convert ttSCP_diaPASEF_Condition_A_Sample_Alpha_01_11494.d -o
A01.mzpeak
$X -in $S/input/diapasef/A01.mzpeak -out_mzml $S/input/diapasef/A01.mzML -threads 32
# frames split per window, TIMS scans collapsed within 15 ppm
$DIANN --f $S/input/diapasef/A01.mzML --lib library/diann17/hye_timstof.tsv --out report.tsv --
temp temp --threads 32 --verbose 1 --qvalue 0.01 --xic 60
# ours, all precursors (cost figures; `-out_calibration` for the anchors), then on DIA-NN's IDs
at the defaults (4 sigma) and at DIA-NN's accuracy
$X -in $S/input/diapasef/A01.mzpeak -lib library/hye_timstof.parquet -rt_mode auto -threads 32
-out odia_A01.parquet -out_stats odia_A01.json -out_calibration odia_A01.anchors.tsv
$X -in $S/input/diapasef/A01.mzpeak -lib library/hye_timstof.parquet -rt_mode auto -ids
results/diapasef/diann_A01_ids.txt -top_fragments 0 -threads 32 -out odia_A01_idsdef.parquet
$X ... -ids results/diapasef/diann_A01_ids.txt -top_fragments 0 -mz_tol 11.8 -mz_tol_ms1 11.8 -
threads 32 -out odia_A01_idsP.parquet
$X ... -ids results/diapasef/diann_A01_ids.txt -top_fragments 0 -calibration:mass_model
constant -threads 32 -out odia_A01_idsconst.parquet
# MS1 window probe around our offset (+-4, 7, 20, 30 ppm) and the uncorrected-centre test that
explains DIA-NN's MS1 export
$X ... -ids results/diapasef/diann_A01_ids.txt -top_fragments 0 -mz_tol 11.8 -mz_tol_ms1 7 -out
odia_A01_ms1_7.parquet
$X -in $S/input/diapasef/A01.mzpeak -lib library/hye_timstof.parquet -rt_mode auto -
mass_calibration off -mz_offset -4.6 -mz_tol 10.8 -mz_offset_ms1 0 -mz_tol_ms1 11.8 \
   -ids results/diapasef/diann_A01_ids.txt -threads 24 -out timstof_A01_ms1raw11.8.parquet
```

Libraries. `library/generate.sh human|entrapment` (DIALibGen, Astral NCE 25); the timsTOF library as recorded in `library/hye_timstof.log`; the tuned RT models with `DIALibGen -mode tune` on DIA-NN's run-01 IDs (`library/*.log`); the `_ids_runNN` and `_shared_runNN` libraries with `scripts/filter_library.py` on DIA-NN's report (`scripts/benchmark_refined.sh`, step 2).