Cortex Cloud Platform APIs

Copyright Â© Palo Alto Networks

Copyright Â© Palo Alto Networks

1. Cortex Cloud APIs

1.1. Create a new API key

1.2. Get started with Cortex Cloud APIs

1.3. Get your Cortex API key ID

1.4. Get your FQDN

1.5. Make your first API call

1.6. Run XQL query APIs

1.7. Understand Cortex Cloud licenses

1.8. API Release Notes for Cortex Cloud

1.8.1. Cortex Cloud 2.1

1.8.2. Cortex Cloud 2.0

2. APIs

2.1. Cortex Cloud Platform APIs

2.1.1. Preface

2.1.1.1. Servers

2.1.2. API Keys

2.1.2.1. Get existing API keys

2.1.2.2. Generate an API key

2.1.2.3. Delete API keys

2.1.3. Asset groups

2.1.3.1. Get all or filtered asset groups

2.1.3.2. Create an Asset Group

2.1.3.3. Update an Asset Group

2.1.3.4. Delete an Asset Group

2.1.4. Asset inventory

2.1.4.1. Get all or filtered assets

2.1.4.2. Get asset by ID

2.1.4.3. Get raw fields of asset by ID

2.1.4.4. Get schema of asset inventory

2.1.4.5. Get enum values of specified field

2.1.5. Attack surface management

2.1.5.1. Get External Service

2.1.5.2. Get All Services

2.1.5.3. Get vulnerability tests

2.1.5.4. Bulk Update Vulnerability Tests

2.1.6. Audit log

2.1.6.1. Get Audit Management Log

2.1.6.2. Get Audit Agent Report

2.1.7. Authentication settings

2.1.7.1. Create authentication settings for IdP SSO or metadata URL

2.1.7.2. Update authentication settings

2.1.7.3. Delete authentication settings by domain

2.1.7.4. Get authentication settings for all configured domains

2.1.7.5. Get IdP metadata

2.1.8. BIOCs

2.1.8.1. Get BIOCs

2.1.8.2. Insert or update BIOCs

2.1.8.3. Delete BIOCs

2.1.9. Cases

2.1.9.1. Retrieve cases based on filters

2.1.9.2. Update existing case

2.1.9.3. Retrieve Case Artifacts by Case Id

2.1.9.4. Get War Room entries

2.1.9.5. Add War Room entries

2.1.10. Correlation Rules

2.1.10.1. Get Correlation Rules

2.1.10.2. Insert or update Correlation Rules

2.1.10.3. Delete Correlation Rules

2.1.11. Cortex CLI

2.1.11.1. Get the latest version of the Cortex CLI

2.1.12. Dashboards

2.1.12.1. Get dashboards

2.1.12.2. Insert or update dashboards

2.1.12.3. Delete dashboards

2.1.13. Dataset Management

2.1.13.1. Add Dataset

2.1.13.2. Delete a dataset

2.1.13.3. Get all datasets

2.1.14. Endpoint Management

2.1.14.1. Get Distribution version

2.1.14.2. Get all Endpoints

2.1.14.3. Get Policy

2.1.14.4. Delete Endpoints

2.1.14.5. Create distributions

2.1.14.6. Get Distributions

2.1.14.7. Get Violations
2.1.14.8. Get Distribution status
2.1.14.9. Get Distribution URL
2.1.14.10. Set an Endpoint Alias
2.1.14.11. Assign Tags
2.1.14.12. Remove Tags
2.1.14.13. Get Endpoint
2.1.14.14. Initiate Forensics Triage
2.1.14.15. Delete Tags Permanently
2.1.14.16. Upgrade Agents
2.1.14.17. Get endpoint security profiles
2.1.14.18. Get Legacy Exceptions Modules
2.1.14.19. Fetch Legacy Exception Rules
2.1.14.20. Add Legacy Exception Rule
2.1.14.21. Edit Legacy Exception Rule
2.1.14.22. Delete Legacy Exception Rules
2.1.14.23. Add Prevention Profile
2.1.14.24. Add Signer CN to Allowlist
2.1.14.25. Edit Prevention Profile
2.1.14.26. Get Prevention Profile Modules
2.1.14.27. Edit prevention policy rules

2.1.15. IOCs
2.1.15.1. Get Indicators (IOCs)
2.1.15.2. Insert or update IOCs
2.1.15.3. Delete Indicators (IOCs)

2.1.16. Issues
2.1.16.1. Create a new issue
2.1.16.2. Retrieve issues based on filters
2.1.16.3. Update existing issue
2.1.16.4. Retrieve issue schema
2.1.16.5. Create a new issue exception
2.1.16.6. Disable an issue exception
2.1.16.7. Retrieve issue exceptions based on filters

2.1.17. Lookup Datasets
2.1.17.1. Add or update data in a lookup dataset
2.1.17.2. Remove data from a lookup dataset
2.1.17.3. Get data from a lookup dataset

2.1.18. Playbooks
2.1.18.1. Get a playbook
2.1.18.2. Insert or update playbooks
2.1.18.3. Delete a playbook

2.1.19. Profiles
2.1.19.1. Get endpoint security profiles

2.1.20. Query Library
2.1.20.1. Get XQL Queries
2.1.20.2. Insert or update XQL queries
2.1.20.3. Delete XQL Queries

2.1.21. Response Action
2.1.21.1. Restore File
2.1.21.2. File Retrieval Details
2.1.21.3. Allow List Files
2.1.21.4. Get Quarantine Status
2.1.21.5. Quarantine Files
2.1.21.6. Block List Files
2.1.21.7. Unisolate Endpoints
2.1.21.8. Cancel Scan Endpoints
2.1.21.9. Scan Endpoints
2.1.21.10. Get Action Status
2.1.21.11. Retrieve File
2.1.21.12. Isolate Endpoints
2.1.21.13. Get triage presets

2.1.22. Scheduled Queries
2.1.22.1. Get scheduled queries
2.1.22.2. Insert or update scheduled queries
2.1.22.3. Delete a scheduled query

2.1.23. Script execution
2.1.23.1. Run Snippet Code Script
2.1.23.2. Run Script
2.1.23.3. Get Script Metadata
2.1.23.4. Get Script Execution Status
2.1.23.5. Get Scripts
2.1.23.6. Get Script Execution Results
2.1.23.7. Get Script Execution Result Files
2.1.23.8. Get Script Code

2.1.24. Scripts
2.1.24.1. Get a script
2.1.24.2. Insert or update a script
2.1.24.3. Delete a script

2.1.25. Syslog servers
2.1.25.1. Create a syslog integration
2.1.25.2. Get all or filtered syslog servers
2.1.25.3. Update a syslog integration
2.1.25.4. Delete all or filtered syslog integrations
2.1.25.5. Test syslog integration

2.1.26. System management
2.1.26.1. System Health Check
2.1.26.2. Get Tenant Info

2.1.26.3. Get Users
2.1.26.4. Get Roles
2.1.26.5. Get User Groups
2.1.26.6. Set a User Role
2.1.26.7. Get Risk Score
2.1.26.8. Get Risky Users
2.1.26.9. Get Risky Hosts
2.1.27. Widgets
2.1.27.1. Get widgets
2.1.27.2. Insert or update widgets
2.1.27.3. Delete widgets
2.1.28. XQL query
2.1.28.1. Start an XQL query
2.1.28.2. Get XQL query results
2.1.28.3. Get XQL query Quota
2.1.28.4. Get XQL query results Stream
2.1.29. XQL user datasets
2.1.29.1. Define an XQL user dataset
2.1.29.2. Get created XQL user datasets
2.1.29.3. Delete an XQL user dataset
2.2. Agent Configuration Settings API
2.2.1. Preface
2.2.1.1. Servers
2.2.1.2. Authentication methods
2.2.1.2.1. Default authentication
2.2.2. Agent Configurations
2.2.2.1. Retrieve content management settings
2.2.2.2. Update content management settings
2.2.2.3. Retrieve agent status timeout settings
2.2.2.4. Update agent status timeout settings
2.2.2.5. Retrieve agent auto-upgrade settings
2.2.2.6. Update agent auto-upgrade settings
2.2.2.7. Retrieve WildFire analysis settings
2.2.2.8. Update WildFire analysis settings
2.2.2.9. Retrieve informative BTP issues settings
2.2.2.10. Update informative BTP issues settings
2.2.2.11. Retrieve log collection settings
2.2.2.12. Update log collection settings
2.2.2.13. Retrieve action center expiration settings
2.2.2.14. Update action center expiration settings
2.2.2.15. Retrieve critical environment versions settings
2.2.2.16. Update critical environment versions settings
2.2.2.17. Retrieve advanced analysis settings
2.2.2.18. Update advanced analysis settings
2.2.2.19. Retrieve endpoint administration cleanup settings
2.2.2.20. Update endpoint administration cleanup settings
2.3. Cortex Cloud Alert Notification Rules REST APIs
2.3.1. Preface
2.3.1.1. Servers
2.3.2. Alert Notification Rules
2.3.2.1. List all rules
2.3.2.2. Create a new rule
2.3.2.3. Retrieve a specific alert notification rule
2.3.2.4. Delete an existing Alert Notification Rule
2.3.2.5. Edit an existing Alert Notification Rule
2.3.2.6. Edit the status of an existing Alert Notification Rule
2.4. ASPM, CICD and Application Security APIs
2.4.1. Preface
2.4.1.1. Servers
2.4.1.2. Authentication methods
2.4.1.2.1. Default authentication
2.4.2. Billing
2.4.2.1. Get Billing Contributors
2.4.3. Applications
2.4.3.1. Get an application configuration
2.4.3.2. Create an application
2.4.3.3. Get applications
2.4.3.4. Get an application
2.4.3.5. Update an application
2.4.3.6. Delete an application
2.4.4. Policies
2.4.4.1. Create an AppSec policy
2.4.4.1.1. Limitations
2.4.4.1.1.1. Trigger and Action Constraints by Finding Type
2.4.4.1.1.2. General Policy Constraints
2.4.4.2. List AppSec policies
2.4.4.3. Get an AppSec policy
2.4.4.4. Update an AppSec policy
2.4.4.5. Delete an AppSec policy
2.4.4.6. Supported Condition Fields
2.4.4.7. Supported Scope Fields
2.4.4.8. Supported Condition Fields
2.4.4.9. Supported Scope Fields
2.4.5. Rules
2.4.5.1. Get AppSec rules

2.4.5.2. Create an AppSec rule
2.4.5.2.1. Create an Application Security Rule
2.4.5.3. Get an AppSec rule
2.4.5.4. Modify an AppSec rule
2.4.5.5. Delete an AppSec rule
2.4.5.6. Get AppSec rule labels
2.4.5.7. Create an AppSec rule validation
2.4.6. Repositories
2.4.6.1. Get repositories
2.4.6.2. Get a repository
2.4.6.3. Get a repository scan configuration
2.4.6.4. Update a repository scan configuration
2.4.6.5. Get AppSec repository branches
2.4.6.6. Update an AppSec repository branch
2.4.7. Data Sources
2.4.7.1. Get all Data Sources
2.4.7.2. Create AppSec Data Sources
2.4.7.3. Get an AppSec Data Source
2.4.7.4. Update an AppSec Data Source
2.4.7.5. Delete an AppSec Data Source
2.4.7.6. 3rd Party AppSec Collector
2.4.7.6.1. Prerequisites
2.4.7.6.2. Limitations
2.4.8. Scan management
2.4.8.1. Get unscanned AppSec scan management repositories
2.4.8.2. Get AppSec branch periodic scans
2.4.8.3. Get AppSec Pull Request scans
2.4.8.4. Get AppSec CI scans
2.4.8.5. List AppSec scan issues
2.4.8.6. List AppSec scan findings
2.4.8.7. Rerun a repository scan
2.4.9. SBOM management
2.4.9.1. Get an SBOM for the specified repository
2.4.9.2. Get all SBOMs for the specified organization
2.4.10. Remediations
2.4.10.1. Get Fix Suggestion
2.4.10.2. Trigger Fix Pull Request
2.4.10.3. Get Fix Status
2.4.11. Criteria
2.4.11.1. Get all criteria
2.4.11.2. Get a Criteria by ID
2.4.11.3. Delete a Criteria
2.4.11.4. Create a Criteria
2.5. Get Asset Compliance Results API
2.5.1. Preface
2.5.1.1. Servers
2.5.1.2. Authentication methods
2.5.1.2.1. Default authentication
2.5.2. Control Findings
2.5.2.1. Get asset compliance results
2.6. Cortex Cloud Logging and Collection Service Management APIs
2.6.1. Preface
2.6.1.1. Servers
2.6.2. CLCS Management
2.6.2.1. List connected NGFW devices
2.6.2.2. Disconnect NGFW devices from CLCS
2.7. Cloud Onboarding APIs
2.7.1. Preface
2.7.1.1. Servers
2.7.1.2. Authentication methods
2.7.2. Cloud instance management
2.7.2.1. Create a cloud onboarding integration template
2.7.2.2. Get cloud instance details
2.7.2.3. Get all or filtered cloud instances
2.7.2.4. Edit a cloud instance
2.7.2.5. Enable or disable cloud instances
2.7.2.6. Delete the specified cloud instances
2.7.2.7. Get identifier roles for cloud instance
2.7.3. Cloud account management
2.7.3.1. Get accounts in the specified cloud instances
2.7.3.2. Enable or disable cloud accounts
2.7.4. Outpost management
2.7.4.1. Create an outpost template
2.7.4.2. Edit an outpost
2.7.4.3. Get all or filtered outposts
2.7.5. General
2.7.5.1. Get available regions for a CSP
2.7.5.2. Get approved Azure tenants
2.8. Cloud Infrastructure Entitlement Management APIs
2.8.1. Preface
2.8.1.1. Servers
2.8.2. CIEM access
2.8.2.1. Search CIEM Access

2.9. Compliance Controls API
2.9.1. Preface
2.9.1.1. Servers
2.9.1.2. Authentication methods
2.9.1.2.1. Default authentication
2.9.2. Assessment profiles
2.9.2.1. Get assessment profiles
2.9.2.2. Get assessment profile by ID
2.9.2.3. Add assessment profile
2.9.2.4. Edit assessment profile
2.9.2.5. Delete assessment profile
2.9.3. Assessment results
2.9.3.1. Get assessment profile results
2.9.4. Controls
2.9.4.1. Get compliance controls
2.9.4.2. Get compliance control by ID
2.9.4.3. Add new control
2.9.4.4. Edit existing control
2.9.4.5. Delete control
2.9.4.6. Get control by revision
2.9.5. Rules
2.9.5.1. Add compliance rules to a compliance control
2.9.5.2. Delete rules from control
2.9.6. Categories
2.9.6.1. Get categories and subcategories
2.9.7. Results
2.9.7.1. Get control failed results
2.9.7.2. Get rule failed results
2.9.8. Reports
2.9.8.1. Get compliance reports
2.9.9. Standards
2.9.9.1. Get compliance standards
2.9.9.2. Get single standard by ID
2.9.9.3. Add new standard
2.9.9.4. Edit existing standard
2.9.9.5. Delete standard
2.9.10. Compliance Assets
2.9.10.1. Get compliance assets
2.10. Policies
2.10.1. Preface
2.10.2. Cloud Security Policies
2.10.2.1. Create Cloud Security Policy
2.10.2.2. List Cloud Security Policies
2.10.2.3. Get Cloud Security Policy
2.10.2.4. Update Cloud Security Policy
2.10.2.5. Delete Cloud Security Policy
2.11. Cloud Workload Protection APIs
2.11.1. Preface
2.11.1.1. Servers
2.11.1.2. Authentication methods
2.11.2. Policies
2.11.2.1. Get CWP Policies (v2)
2.11.2.2. Add CWP Policies (v2)
2.11.2.3. Get a CWP Policy by ID (v2)
2.11.2.4. Update a CWP Policy by ID (v2)
2.11.2.5. Get CWP Policies (v1)
2.11.2.6. Add CWP Policies (v1)
2.11.2.7. Get a CWP Policy by ID (v1)
2.11.2.8. Delete a CWP Policy by ID (v1)
2.11.2.9. Update a CWP Policy by ID (v1)
2.11.3. SBOM
2.11.3.1. Get the SBOM of the specified asset
2.11.4. Registry Onboarding
2.11.4.1. Create a registry connector
2.11.4.2. Get a registry connector
2.11.4.3. Update a registry connector
2.11.4.4. Delete a registry connector
2.12. Disable Injection and Prevention Rules Public API
2.12.1. Preface
2.12.1.1. Servers
2.12.2. Default
2.12.2.1. Get Disable Injection and Prevention rules
2.12.2.2. Add Disable Injection and Prevention rule
2.12.2.3. Disable Disable Injection and Prevention Rules
2.13. Disable Prevention Rule Public APIs
2.13.1. Preface
2.13.1.1. Servers
2.13.2. Default
2.13.2.1. Get Disable Prevention Rules
2.13.2.2. Get Disable Prevention Modules
2.13.2.3. Add Disable Prevention Rule
2.13.2.4. Edit Disable Prevention Rule

2.13.2.5. Delete Disable Prevention Rules

2.14. Data Security Posture Management APIs

2.14.1. Preface

2.14.1.1. Servers

2.14.2. Inventory

2.14.2.1. Get data pattern inventory

2.14.2.2. Get field inventory details

2.14.2.3. Get file inventory details

2.15. Detection Rules Management API

2.15.1. Preface

2.15.1.1. Servers

2.15.1.2. Authentication methods

2.15.2. Detection Rules

2.15.2.1. Create Detection Rule

2.15.2.2. Get Detection Rules

2.15.2.3. Get Rule By Id

2.15.2.4. Update Detection Rule

2.15.2.5. Delete Detection Rule

2.16. Cortex Cloud External Application Management API

2.16.1. Preface

2.16.1.1. Servers

2.16.1.2. Authentication methods

2.16.2. External Applications

2.16.2.1. Create a new application

2.16.2.2. List all applications

2.16.2.3. Update an existing application (full replacement)

2.16.2.4. Delete an application

2.16.2.5. Get External Application details by ID

2.17. Managed Services APIs

2.17.1. Preface

2.17.1.1. Authentication

2.17.1.2. Supported Tenants

2.17.1.3. Timestamps

2.17.1.3.1. Servers

2.17.1.4. Authentication methods

2.17.2. Comments

2.17.2.1. Add a comment to an MTH/MDR report

2.17.2.2. Get comments for MTH/MDR reports

2.17.3. Status

2.17.3.1. Update report status

2.17.4. Assignment

2.17.4.1. Update report assignment

2.17.5. Reports

2.17.5.1. Get reports by source ID

2.17.5.2. Get reports by incident ID

2.18. NetScan Public API

2.18.1. Preface

2.18.1.1. Servers

2.18.2. Vulnerability Network Scan Management

2.18.2.1. Launch a scan run

2.18.2.2. Get scan run status

2.18.2.3. Launch a scan run by definition ID

2.18.2.4. Get scan run status by ID

2.18.2.5. Create a scan definition

2.18.2.6. Send a command to a running scan

2.19. Cortex Platform IAM APIs

2.19.1. Preface

2.19.1.1. Servers

2.19.1.2. Authentication methods

2.19.2. Roles

2.19.2.1. List all roles

2.19.2.2. Create a new role

2.19.2.3. Delete an existing role

2.19.2.4. List all permission configs

2.19.3. User Groups

2.19.3.1. List all user groups

2.19.3.2. Create a new user group

2.19.3.3. Edit an existing user group

2.19.3.4. Delete an existing user group

2.19.4. Scopes

2.19.4.1. Retrieve an existing scope

2.19.4.2. Edit an existing scope

2.19.5. User

2.19.5.1. List all users

2.19.5.2. Get user

2.19.5.3. Edit an existing user

2.19.6. API Keys

2.19.6.1. Get API Key

2.19.6.2. Edit an API key

2.20. Vulnerability Intelligence public APIs

2.20.1. Preface

2.20.1.1. Servers
2.20.1.2. Authentication methods
2.20.2. Vulnerabilities
2.20.2.1. Get list of vulnerabilities
2.20.2.2. Get vulnerability details
2.20.3. Affected software
2.20.3.1. Get affected software
2.21. Vulnerability Management APIs
2.21.1. Preface
2.21.1.1. Servers
2.21.1.2. Default authentication
2.21.2. Vulnerability Management
2.21.2.1. Get Policies List
2.21.2.2. Create Policy Public
2.21.2.3. Update Policy
2.21.2.4. Get Policy By ID
2.21.2.5. Delete Policy
2.21.2.6. Trigger Scan for an AssetId
2.21.3. Bring Your Own Scanner
2.21.3.1. Submit assets and vulnerabilities from an external scanner
2.21.3.2. Poll the status of a BYOS import job
2.21.4. Vulnerability Findings
2.21.4.1. List vulnerability findings (paginated)
2.21.4.2. Get a single vulnerability finding by platform ID
2.21.5. Snapshot
2.21.5.1. Bulk export vulnerability findings snapshot

1 | Cortex Cloud APIs

1.1 | Create a new API key

1. In Cortex, navigate to **Settings** > **Configurations** > **Integrations** > **API Keys** > **New Key**.
2. In the **Role** tab, perform the following:
    1. Under **Security Level**, select the type of API Key you want to generate: **Advanced** or **Standard**. The Advanced API key hashes the key using a nonce, a random string, and a timestamp to prevent replay attacks. cURL does not support this but it is suitable with scripts.
    2. Under **Role**, select the desired level of access for this key. You can select from predefined roles or custom roles. Roles are available according to what was defined in either the Cortex Gateway or Cortex XSIAM Access Management. You can view the configuration of the role selected by expanding the sections under Components. For more information, see Assign user roles and groups.
    3. (Optional) Under **Comment**, provide a comment that describes the purpose of the API key.
    4. (Optional) If you want to define a time limit on the API key authentication, select **Enable Expiration Date**, and select the expiration date and time. You can track the expiration date of each API key in the **API Keys** page. In addition, Cortex Cloud displays a API Key Expiration notification in the Notification Center one week and one day prior to the defined expiration date.
3. (Optional) To configure and manage granular scoping for Scope-Based Access Control (SBAC), click the **Scope** tab, and under **Scope Definition**, expand the scoping areas that you want to grant the user role access to for this API by clicking the chevron icon (>) beside the scoping area title. For more information, see Manage API keys.
4. **Generate** the API Key.
5. Copy the API key, and then click **Close**. This value represents your unique `Authorization:{key}`.

    warning

    You will not be able to view the API Key again after you complete this step. Ensure that you copy it before closing the notification.

1.2 | Get started with Cortex Cloud APIs

Before you can begin using Cortex Cloud APIs, you must generate the following items in Cortex Cloud:

Value	Description
API Key	The API Key is your unique identifier used as the `Authorization:{key}` header required for authenticating API calls. Depending on your desired security level, you can generate two types of API keys, Advanced or Standard, from Cortex.
API Key ID	The API Key ID is your unique token used to authenticate the API Key. The header used when running an API call is `x-xdr-auth-id:{key_id}`.
FQDN	The FQDN is a unique host and domain name associated with each tenant.

Cortex Cloud API URIs are made up of your tenant's FQDN, the API name, and endpoint path. For example, `https://api-{fqdn}/xsiam/public/v1/{endpoint_path}/.`

The following steps describe how to generate the necessary key values and run your first API call:

1. Create a new API key.
2. Get your Cortex Cloud API key ID.
3. Get your FQDN.
4. Make your first API call.

1.3 | Get your Cortex API key ID

1. In the API Keys table, locate the **ID** field.
2. Note your corresponding **ID** number. This value represents the `x-xdr-auth-id:{key_id}` token.

1.4 | Get your FQDN

1. In Cortex Cloud, navigate to **Settings** > **Configurations** > **Integrations** > **API Keys**.
2. Click **Copy API URL**.
3. Your FQDN is saved in the clipboard. You must use the FQDN as part of the URL in every API call. For example: `https://api-company.us.com/xsoar/public/v1/{endpoint_path}/`.

You can use the **CURL Example** URL to run the APIs.

1.5 | Make your first API call

The following examples vary depending on the type of key you select.

You can test authentication with Advanced API keys using the provided Python 3 example. With Standard API keys, use either the cURL example or the Python 3 example. Don't forget to replace the example variables with your unique API key, API key ID, and FQDN tenant. After you verify authentication, you can begin making API calls.

Standard Key cURL Example

```
curl -X POST https://api-{fqdn}/public_api/v1/{name of api}/{name of call}/
-H "x-xdr-auth-id:{key_id}"
-H "Authorization:{key}"
-H "Content-Type:application/json"
-d '{}'
```

Standard Key Python 3 Example

```
import requests
    def test_standard_authentication(api_key_id, api_key):
    headers = {
        "x-xdr-auth-id": str(api_key_id),
        "Authorization": api_key
    }
    parameters = {}
    res = requests.post(url="https://api-{fqdn}/public_api/v1/{name of api}/{name of call}",
                                            headers=headers,
                                            json=parameters)
    return res
```

Advanced Key Python 3 Example

```
import requests

from datetime import datetime, timezone
import secrets
import string
import hashlib
import requests

def test_advanced_authentication(api_key_id, api_key):
   # Generate a 64 bytes random string
    nonce = "".join([secrets.choice(string.ascii_letters + string.digits) for _ in range(64)])
    # Get the current timestamp as milliseconds.
    timestamp = int(datetime.now(timezone.utc).timestamp()) * 1000
    # Generate the auth key:
    auth_key = "%s%s%s" % (api_key, nonce, timestamp)
    # Convert to bytes object
    auth_key = auth_key.encode("utf-8")
    # Calculate sha256:
    api_key_hash = hashlib.sha256(auth_key).hexdigest()
    # Generate HTTP call headers
    headers = {
        "x-xdr-timestamp": str(timestamp),
        "x-xdr-nonce": nonce,
        "x-xdr-auth-id": str(api_key_id),
        "Authorization": api_key_hash
    }
    parameters = {}
    res = requests.post(url="https://api-{fqdn}/public_api/v1/{name of api}/{name of call}",
                                            headers=headers,
                                            json=parameters)
    return res
```

1.6 | Run XQL query APIs

Cortex Cloud enables you to run XQL queries on your data sources using a series of APIs. To execute XQL APIs you must have:

- Valid API Key and API Key ID that include the Instance Administrator role permissions.
- Available query quota.

Query quota is made up of query units that enable you to run XQL APIs. Each XQL API query entails a cost of query units calculated according to the complexity and number of search results. The query cost for each API query is displayed in the **Get Query Results** API. You can also track the query cost per XQL API search, overall usage, and remaining quota in Cortex Cloud or by running a **Get XQL Query Quota** API. Cortex Cloud provides a free daily quota relative to your license size for you to run XQL API queries.

> info
>
> **Note**: You will be able to purchase additional query units in future Cortex Cloud versions.

To execute a XQL API, you need to run a series of APIs. Each API requires a response value from the previous API to continue. This allows you to track the number of XQL queries you want to run, which in turn helps you manage your daily quota. Queries called without enough quota will fail. To ensure you don't surpass your quota, Cortex Cloud allows you to run up to four API queries in parallel.

Run the following APIs to call an XQL query:

1. Start an XQL Queryâ€ Run an XQL query. Response returns a unique execution ID used to retrieve the results by the Get XQL Query Results API.
2. Get XQL Query Resultsâ€ Retrieve XQL query results. API displays up to 1,000 results. If query generated more than 1,000 results, the response returns a unique stream ID used to retrieve additional results by the Get XQL Query Results Stream API.
3. Get XQL Query Results Streamâ€ Retrieve XQL query with more than 1,000 results.

1.7 | Understand Cortex Cloud licenses

This Cortex Cloud documentation is relevant for Cortex Cloud Runtime Security and Cortex Cloud Posture Management. It is important to check the license requirements for each API. Each API includes information on which licenses and add-ons are necessary to run the API.

To read more about Cortex Cloud licensing, see Understand license plans in Cloud Runtime Security and Understand license plans in Cloud Posture Management.

1.8 | API Release Notes for Cortex Cloud

- Cortex Cloud 2.1
- Cortex Cloud 2.0

1.8.1 | Cortex Cloud 2.1

Product Name	Details
Agent Configurations	No Changes in this release.
Application Security (AppSec)	Updated Schemas - `AppsecPolicyTriggersandActions`: Added `ciImage` and `imageRegistry` trigger configurations. - `ConditionOperators`: Added `CONTAINS_IN_LIST`, `JSON_WILDCARD`, `RANGE`, and `RELATIVE_TIMESTAMP`. - `CreateRequest`: Added `enabled`, `suggestionId`, and `userSbac`. - `FindingType`: Updated enum values (e.g., `VULNERABILITY`, `CODE_WEAKNESS`). - `Integration`: Added `scanTypes`, `statusDetails`, and `tenantId`. - `Policy`: Added `overrideIssueSeverity`, `scopeFields`, `suggestionHash`, and `suggestionId`. Schemas Added - `BillingErrorResponse`: Error schema for billing-related endpoints. - `ConditionValue`: Structured value for range and key-value matching. - `EmailOrigin`: Enum for user email sources (`API`, `GIT`). - `IntegrationStatusDetails`: Detailed status for data source components. - `RepositoryUser`: Detailed schema for repository contributors. - `Transporter`: Configuration for secure communication with private data sources. - `UnifiedAction`: Consolidated enum for all possible policy actions. Paths Added - `GET /public_api/appsec/v1/billing/contributors`: Retrieve active contributors for billing. - `POST /public_api/appsec/v1/collectors/{collectorId}`: Upload 3rd party SARIF findings. Updated Paths - `GET /public_api/appsec/v1/data_source_instances`: Added filtering by type/category. - `POST /public_api/appsec/v1/policies`: Detailed rules for finding types.
Asset Compliance	No Changes in this release.
CIEM	No Changes in this release.

Product Name	Details
Cloud Onboarding	Updated Schemas - `CreateInstanceTemplateRequestData`: Added `ALIBABA_CLOUD` and `gcp_workspace`. - `EditInstanceRequestData`: Added `ALIBABA_CLOUD`, `connector_name`, and `gcp_workspace`. - `InstanceAdditionalCapabilities`: Added `automation`, `automation_log_level`, and `kubernetes_security`. Schemas Added - `AccountItem`: Added schema for cloud account items. - `EditOutpostRequest`: Added schema for outpost edit requests. - `EditOutpostRequestData`: Added schema for outpost edit request data. - `InstanceListItem`: Added schema for cloud instance list items. Updated Paths - Terminology shift from "integration instance" to "cloud instance" across all endpoints. - `POST /public_api/v1/cloud_onboarding/edit_outpost`: Updated request/response schemas.
Compliance	No Changes in this release.
Cortex Cloud Platform	Updated Schemas - `ErrorResponse`: Standardized error structure. Schemas Added - `CreateIssueException`: Schema for creating issue exceptions. - `IssueException`: Full object representation for issue exceptions. - `EditPreventionPolicyRequest`: Wrapper for prevention policy edit requests. - `EditPreventionPolicyRequestData`: List of rule edits to apply. - `PreventionPolicyEditParameters`: Parameters for editing prevention rules. - `TargetFilter`: Structured condition tree for targeting endpoints. - `SearchCondition`: Individual filter criteria. - `SuccessResponse`: Simple boolean success indicator. Paths Added - `POST /public_api/v1/issue_exceptions/`: Create issue exceptions. - `POST /public_api/v1/issue_exceptions/disable/`: Disable exceptions. - `POST /public_api/v1/issue_exceptions/search/`: Search exceptions. - `POST /public_api/v1/policies/prevention/edit`: Atomic prevention rule edits. Updated Paths - `POST /public_api/v1/distributions/create`: Added `caas_embedded` package type.
CSPM Policies	No Changes in this release.
CWP	No Changes in this release.
Detection Rules	No Changes in this release.
IAM Platform	No Changes in this release.
Vulnerability Intelligence	Updated Schemas - `VulnerabilityFinding`: Comprehensive schema for CVE/asset records. Schemas Added - `FilterBlock`: Logical filter block supporting AND/OR connectors. - `FilterTriplet`: Individual filter condition. - `FindingsErrorResponse`: Standardized error response. - `FindingsSortObject`: Sort criteria for findings. - `GetVulnerabilityFindingByIdResponse`: Response for single finding lookups. - `GetVulnerabilityFindingsRequest`: Request for paginated searches. - `GetVulnerabilityFindingsResponse`: Response for paginated searches. - `GetVulnerabilityFindingsSnapshotRequest`: Parameters for bulk snapshot exports. - `TimeframeAbsolute`: Absolute time range schema. Paths Added - `POST /vulnerability-management/v1/vulnerability-finding/search/`: Paginated search. - `POST /vulnerability-management/v1/vulnerability-finding/snapshot/`: Bulk export (NDJSON). - `POST /vulnerability-management/v1/vulnerability-finding/{platform_id}`: Get finding by ID.

1.8.2 | Cortex Cloud 2.0

Product Name	Details
Application Security	Schemas Added - `ApplicationAssetSelectionFilter`: Defines filter criteria to dynamically select application assets. - `ApplicationAssetSelectionFilterValues`: Container for filter values used to match application assets (orgUrl, repositoryId, projectUrl, etc.). - `ManualAndRunCriteriaApplicationAssetSelectionFilter`: Specific filter for manual and run criteria. - `ApplicationMetadataCode`: Metadata for code-based assets, including business owner and criticality. - `BusinessOwnerMetaData`: Enum for business owner types (`organizationOwner`, `projectOwner`, etc.). - `CodeCriteriaConfig`: Configuration for code-based criteria, including unification settings. - `CriteriaDTOCode`: Detailed data transfer object for code criteria. - `IACSecurity`: Configuration for Infrastructure as Code (IaC) security scanners. - `secretsSecurity`: Configuration for secrets security scanners. - `CriteriaType.Code`: Enum for criteria types. Updated Schemas - `ApplicationAssetSelection`: Updated description and properties. - `ApplicationConfigurationSettings`: Added `sla` (Service Level Agreement) configurations for different severity levels (CRITICAL, HIGH, MEDIUM, LOW). - `CreateApplicationRequest`: Updated required fields and added detailed descriptions for owners (DevOps, Dev, Product Manager). - `DetectionRule`: Extensive updates to properties including `detectionMethod`, `frameworks`, and `scanner`. - `ExtendedFields`: Added `unifyAcrossProviders` and `unifyWithinProvider` flags. - `FrameworkName`: Expanded enum with many new values (e.g., `CI_CD_GITHUB_REPO`, `TERRAFORMPLAN`, `OPENAPI`). Paths Added - None Updated Paths - GET `/public_api/appsec/v1/application`: Updated descriptions and added mandatory `Authorization` and `x-xdr-auth-id` headers. - POST `/public_api/appsec/v1/application`: Updated descriptions and added mandatory `Authorization` and `x-xdr-auth-id` headers.
Cloud Onboarding	Updated Schemas - `CreateInstanceTemplateRequestData`: Added `cloud_partition` field (COMMERCIAL/GOV) to `request_data`. - `CreateOutpostTemplateRequestData`: Added `cloud_partition` field (COMMERCIAL/GOV) to `request_data`. - `EditInstanceRequestData`: Added `cloud_partition` field (COMMERCIAL/GOV) to `request_data`. - `ListCloudProviderRegionsRequestData`: Added `cloud_partition` field (COMMERCIAL/GOV) to `request_data`. - `ListCloudProviderRegionsResponse`: Changed `reply` type from `object` to `array` and updated its items to include `name`, `value`, and `type`. Schemas Added - None Paths Added - None Updated Paths - POST `/public_api/v1/cloud_onboarding/create_instance_template`: Updated request body examples to include `cloud_partition`. - POST `/public_api/v1/cloud_onboarding/edit_instance`: Updated request body examples to include `cloud_partition`. - POST `/public_api/v1/cloud_onboarding/get_azure_approved_tenants`: Added `cloud_parition` to the request body schema. - POST `/public_api/v1/cloud_onboarding/get_instance_details`: Updated summary from "Get integration instance details" to "Get cloud instance details" and updated response examples to include `cloud_partition`. Note: The primary change in this version is the introduction of the `cloud_partition` parameter across onboarding APIs to support both `COMMERCIAL` and `GOV` (government) cloud environments.

Product Name	Details
Compliance	No Changes in this release.
Cortex Cloud Platform	The following new APIs have been added under Endpoint Management: - `POST /public_api/v1/distributions/get_distributions` - `POST /public_api/v1/endpoints/get_profiles` - `POST /public_api/v1/legacy_exceptions/get_modules` - `POST /public_api/v1/legacy_exceptions/fetch` - `POST /public_api/v1/legacy_exceptions/add` - `POST /public_api/v1/legacy_exceptions/edit` - `POST /public_api/v1/legacy_exceptions/delete` Updated Paths - POST /public_api/v1/distributions/create: Updated serverless support
Cloud CIEM	No Changes in this release.
Compute(CWP)	The following new APIs have been added: - `POST /public_api/v1/cwp/registry_onboarding/instances` - `GET /public_api/v1/cwp/registry_onboarding/instances/{connectorID}` - `PUT /public_api/v1/cwp/registry_onboarding/instances/{connectorID}` - `DELETE /public_api/v1/cwp/registry_onboarding/instances/{connectorID}`
Detection Rules Management	The following new APIs have been added: - `POST /public_api/v1/rule` - `POST /public_api/v1/rule/search` - `GET /public_api/v1/rule/{id}` - `PATCH /public_api/v1/rule/{id}` - `DELETE /public_api/v1/rule/{id}`
Disable Prevention Rule	The following new APIs have been added: - `POST /public_api/v1/disable_prevention/get_modules` - `POST /public_api/v1/disable_prevention/fetch` - `POST /public_api/v1/disable_prevention/edit` - `POST /public_api/v1/disable_prevention/add` - `POST /public_api/v1/disable_prevention/delete`
Disable Injection and Prevention Rules	The following new APIs have been added: - `POST /public_api/v1/disable_injection_prevention_rules/fetch` - `POST /public_api/v1/disable_injection_prevention_rules/add` - `POST /public_api/v1/disable_injection_prevention_rules/disable`
DSPM	No Changes in this release.

Product Name	Details
IAM Platform	Schemas Added - `AssetGroup` - `AssetsScope` - `AssetsScopeRequest` - `CasesIssuesScope` - `CasesIssuesScopeRequest` - `DatasetFilter` - `DatasetsRowsScope` - `EndpointGroupsScope` - `EndpointGroupsScopeRequest` - `EndpointTagsScope` - `EndpointTagsScopeRequest` - `EndpointsScope` - `EndpointsScopeRequest` - `Role` - `Tag` Updated Schemas - `UnauthorizedImproperPermissions`: Updated example and properties for the `reply` object; added `data` and `reply` to required fields. - `ApiKeyEditRequest`: Updated descriptions for `comment`, `roles`, and `security_level`. - `RoleCreateRequest`: Updated description for `request_data`. - `ScopeEditRequest`: Added `request_data` properties including `assets`, `cases_issues`, `datasets_rows`, `endpoints`, `tagless_scope`, and `tags_scope`. - `UserEditRequest`: Updated descriptions for `is_hidden`, `phone_number`, `role_id`, `status`, `user_first_name`, `user_groups`, and `user_last_name`. - `UserGroupCreateRequest`: Updated descriptions for `description`, `group_name`, `idp_groups`, `nested_group_ids`, `role_id`, and `users`. - `UserGroupEditRequest`: Updated descriptions for `description`, `group_name`, `idp_groups`, `nested_group_ids`, `role_id`, and `users`. Paths Added - None Updated Paths - `/platform/iam/v1/api-key/{api_key_id}`: Updated GET response schema and PUT request body description. - `/platform/iam/v1/role`: Updated GET response schema (now uses `Role` schema) and POST request body description. - `/platform/iam/v1/role/permission-config`: Updated GET response schema. - `/platform/iam/v1/scope/{entity_type}/{entity_id}`: Updated GET response schema and PUT request body description. - `/platform/iam/v1/user`: Updated GET response schema. - `/platform/iam/v1/user-group`: Updated GET response schema and POST request body description. - `/platform/iam/v1/user-group/{group_id}`: Updated GET response schema and PUT request body description.
Managed Services	The following new APIs have been added: - `POST /public_api/v1/mth/child/add_comment` - `POST /public_api/v1/mth/child/get_comments` - `POST /public_api/v1/mth/child/report/update/assign` - `POST /public_api/v1/mth/child/get_reports_by_source_id` - `POST /public_api/v1/mth/child/get_reports_by_incident_id`
Platform External Application	The following new APIs have been added: - `GET /platform/integration/v1/external-application` - `GET /platform/integration/v1/external-application/{application_id}` - `DELETE /platform/integration/v1/external-application/{application_type}/id/{application_id}`
Platform Notifications	The following new APIs have been added: - `GET /platform/notifications/v1/list-rules` - `POST /platform/notifications/v1/rule` - `GET /platform/notifications/v1/rule/{rule_uuid}` - `PUT /platform/notifications/v1/update-rule-status/{rule_uuid}`
Trusted Images	No Changes in this release.

Product Name	Details
UVEM	Schemas Added - `ScanRequest`: Request model for triggering a vulnerability scan. - `ScanResponse`: Response model for scan trigger operation. - `ScannerType`: Enum for vulnerability scanner types (`CORTEX_NETWORK_SCANNER`, `CORTEX_XDR_AGENT`, `CORTEX_XDR_AGENTLESS`). Updated Schemas - `CreatePolicy`: Refined property definitions for `policy_type`, `severity`, and `status` using `allOf`. - `Filter-Input`: Refined `paging` property definition using `allOf`. - `PolicyView`: Refined `POLICY_TYPE` and `SEVERITY` property definitions using `allOf`. Paths Added - POST `/public_api/vulnerability-management/v1/scan` Updated Paths - `/public_api/uvm_public/v1/create_policy`: Added description to `requestBody`. - `/public_api/uvm_public/v1/list_policies`: Added description to `requestBody`. - `/public_api/uvm_public/v1/update_policy/{id}`: Added description to `requestBody`.
Vulnerability	No Changes in this release.

2 | APIs

2.1 | Cortex Cloud Platform APIs

2.1.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Using the Cortex Platform APIs, you can configure and manage authentication settings, datasets, cases, issues, and script executions. Additionally, the APIs allow you to run XQL queries and perform various other operations across the platform.

The license requirements for each API are listed individually.

Version: Cortex Cloud

2.1.1.1 | Servers

https://api-yourfqdn

2.1.2 | API Keys

APIs for managing API keys

2.1.2.1 | Get existing API keys

post /public_api/v1/api_keys/get_api_keys

Get a list of API keys filtered by expiration date, role, or ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ authorization String required

api_key

Example:
`DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm`
▼ x-xdr-auth-id String required

api_key_id

Example: `2841`
▼ x-xdr-timestamp String required

timestamp in milliseconds

Example: `xXdrTimestamp_example`

▼ x-xdr-nonce String required

64 byte random string

Example: `xXdrNonce_example`

▼ x-child-tenant-id String required

child tenant ID

Example: `xChildTenantId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
-H 'x-xdr-auth-id: 2841' -H 'x-xdr-timestamp: xXdrTimestamp_example' -H 'x-xdr-nonce: xXdrNonce_example' -H 'x-child-
tenant-id: xChildTenantId_example'
'https://api-yourfqdn/public_api/v1/api_keys/get_api_keys'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}" headers = { 'authorization':
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
'x-xdr-auth-id': "2841", 'x-xdr-timestamp': "SOME_STRING_VALUE", 'x-xdr-nonce': "SOME_STRING_VALUE", 'x-child-tenant-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/api_keys/get_api_keys", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/api_keys/get_api_keys") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["authorization"] =
'DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request["x-xdr-auth-id"] = '2841' request["x-xdr-timestamp"] = 'SOME_STRING_VALUE' request["x-xdr-nonce"] =
'SOME_STRING_VALUE' request["x-child-tenant-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "expiration", "operator": "gte", "value": 0 }
] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/api_keys/get_api_keys"); xhr.setRequestHeader("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
xhr.setRequestHeader("x-xdr-auth-id", "2841"); xhr.setRequestHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-nonce", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-child-tenant-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/api_keys/get_api_keys")
.header("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
.header("x-xdr-auth-id", "2841") .header("x-xdr-timestamp", "SOME_STRING_VALUE") .header("x-xdr-nonce",
"SOME_STRING_VALUE") .header("x-child-tenant-id", "SOME_STRING_VALUE") .header("content-type", "application/json")
.body("{\"request_data\":{\"filters\":[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}") .asString();
import Foundation let headers = [ "authorization":
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
"x-xdr-auth-id": "2841", "x-xdr-timestamp": "SOME_STRING_VALUE", "x-xdr-nonce": "SOME_STRING_VALUE", "x-child-tenant-
id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [
"field": "expiration", "operator": "gte", "value": 0 ] ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/api_keys/get_api_keys")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/api_keys/get_api_keys", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}", CURLOPT_HTTPHEADER => [ "authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
```

"content-type: application/json", "x-child-tenant-id: SOME_STRING_VALUE", "x-xdr-auth-id: 2841", "x-xdr-nonce: SOME_STRING_VALUE", "x-xdr-timestamp: SOME_STRING_VALUE"],]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/api_keys/get_api_keys"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "authorization: DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
headers = curl_slist_append(headers, "x-xdr-auth-id: 2841"); headers = curl_slist_append(headers, "x-xdr-timestamp: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-nonce: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-child-tenant-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/api_keys/get_api_keys"); var request = new RestRequest(Method.POST); request.AddHeader("authorization", "DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request.AddHeader("x-xdr-auth-id", "2841"); request.AddHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
request.AddHeader("x-xdr-nonce", "SOME_STRING_VALUE"); request.AddHeader("x-child-tenant-id", "SOME_STRING_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\": {\"filters\":[{\"field\":\"expiration\",\"operator\":\"gte\",\"value\":0}]}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST Get API keys and filter by expiration

{ "request_data": { "filters": [{ "field": "expiration", "operator": "gte", "value": 1721149909250 }] } }
{ "request_data": { "filters": [{ "field": "roles", "operator": "contains", "value": ["Public API Action"] }] } }
{ "request_data": { "filters": [{ "field": "id", "operator": "in", "value": [85] }] } }

Responses

OK

Body

application/json

▼ replyobject

▶ dataarray

▶ filter_countinteger

▶ total_countinteger

Note: The `total_count` value contains all API Keys, including ones that have expired.

RESPONSE

Example 1

{ "reply": { "DATA": [{ "id": 25, "creation_time": 1709544947832, "created_by": "N/A", "user_name": "Public API - 21", "roles": ["default"], "security_level": "standard", "comment": null, "expiration": 1710149747184 }, { "id": 24, "creation_time": 1709544787367, "created_by": "N/A", "user_name": "Public API - 21", "roles": ["default"], "security_level": "standard", "comment": null, "expiration": 1710149586852 }, { "id": 23, "creation_time": 1709544227320, "created_by": "N/A", "user_name": "Public API - 21", "roles": ["default"], "security_level": "standard", "comment": null, "expiration": 1710149026834 }], "FILTER_COUNT": 3, "TOTAL_COUNT": 70 } }

2.1.2.2 | Generate an API key

post /public_api/v1/api_keys/generate

Generate a new API key and define the roles assigned to it and whether the security level is standard or advanced.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ authorization String required

api_key

Example:

DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm

▼ x-xdr-auth-id String required

api_key_id

Example: `2841`

▼ x-xdr-timestamp String required

timestamp in milliseconds

Example: `xXdrTimestamp_example`

▼ x-xdr-nonce String required

64 byte random string

Example: `xXdrNonce_example`

▼ x-child-tenant-id String required

child tenant ID

Example: `xChildTenantId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
-H 'x-xdr-auth-id: 2841' -H 'x-xdr-timestamp: xXdrTimestamp_example' -H 'x-xdr-nonce: xXdrNonce_example' -H 'x-child-
tenant-id: xChildTenantId_example'
'https://api-yourfqdn/public_api/v1/api_keys/generate'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"roles\":
[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}" headers = { 'authorization':
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
'x-xdr-auth-id': "2841", 'x-xdr-timestamp': "SOME_STRING_VALUE", 'x-xdr-nonce': "SOME_STRING_VALUE", 'x-child-tenant-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/api_keys/generate", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/api_keys/generate")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["authorization"] =
'DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request["x-xdr-auth-id"] = '2841' request["x-xdr-timestamp"] = 'SOME_STRING_VALUE' request["x-xdr-nonce"] =
'SOME_STRING_VALUE' request["x-child-tenant-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"roles\":
[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "roles": [ "string" ], "security_level": "standard", "expiration": 0,
"comment": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/api_keys/generate");
xhr.setRequestHeader("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
xhr.setRequestHeader("x-xdr-auth-id", "2841"); xhr.setRequestHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-nonce", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-child-tenant-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/api_keys/generate")
.header("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
.header("x-xdr-auth-id", "2841") .header("x-xdr-timestamp", "SOME_STRING_VALUE") .header("x-xdr-nonce",
"SOME_STRING_VALUE") .header("x-child-tenant-id", "SOME_STRING_VALUE") .header("content-type", "application/json")
.body("{\"request_data\":{\"roles\":
[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}") .asString();
import Foundation let headers = [ "authorization":
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
"x-xdr-auth-id": "2841", "x-xdr-timestamp": "SOME_STRING_VALUE", "x-xdr-nonce": "SOME_STRING_VALUE", "x-child-tenant-
id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "roles":
["string"], "security_level": "standard", "expiration": 0, "comment": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/api_keys/generate")! as URL, cachePolicy: .useProtocolCachePolicy,
```

```
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/api_keys/generate", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"roles\":
[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}", CURLOPT_HTTPHEADER => [
"authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
"content-type: application/json", "x-child-tenant-id: SOME_STRING_VALUE", "x-xdr-auth-id: 2841", "x-xdr-nonce:
SOME_STRING_VALUE", "x-xdr-timestamp: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/api_keys/generate"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
headers = curl_slist_append(headers, "x-xdr-auth-id: 2841"); headers = curl_slist_append(headers, "x-xdr-timestamp:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-nonce: SOME_STRING_VALUE"); headers =
curl_slist_append(headers, "x-child-tenant-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-
type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"request_data\":{\"roles\":
[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/api_keys/generate"); var request = new
RestRequest(Method.POST); request.AddHeader("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request.AddHeader("x-xdr-auth-id", "2841"); request.AddHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
request.AddHeader("x-xdr-nonce", "SOME_STRING_VALUE"); request.AddHeader("x-child-tenant-id", "SOME_STRING_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"roles\":[\"string\"],\"security_level\":\"standard\",\"expiration\":0,\"comment\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ rolesarray[string]required

A list of roles to be assigned to the API key.

▶ security_levelobject (Enum)required

The security level of the API key. API keys with advanced security are hashed with a nonce and timestamp, which is useful for proprietary scripts and are intended to prevent replay attacks. Standard security API keys can be used as-is and are suitable for curl.

▶ expirationinteger

Integer in timestamp epoch milliseconds. Default value is one week from the time of the API call. Maximum expiration date is six months from the time of the API call.

▶ commentstring

REQUEST Generate a standard API key

```
{ "request_data": { "roles": [ "Public API Action" ], "security_level": "standard", "comment": "Api key for John" } }
{ "request_data": { "roles": [ "Public API Action" ], "security_level": "standard", "expiration": 1725802080000,
"comment": "API key for Joe" } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ idinteger

▶ keystring

RESPONSE

Standard API key

```
{ "reply": { "id": 4267, "key": "oZFaXmXCLCdoWIXTb9ITSqUvl4OBLsUQgCeuZc5FdwMpmpY5QBn8OUePZiLMb" } }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.2.3 | Delete API keys

post /public_api/v1/api_keys/delete

Delete API keys by ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ authorization String required

api_key

Example:
`DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm`
▼ x-xdr-auth-id String required

api_key_id

Example: `2841`
▼ x-xdr-timestamp String required

timestamp in milliseconds

Example: `xXdrTimestamp_example`
▼ x-xdr-nonce String required

64 byte random string

Example: `xXdrNonce_example`
▼ x-child-tenant-id String required

child tenant ID

Example: `xChildTenantId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
-H 'x-xdr-auth-id: 2841' -H 'x-xdr-timestamp: xXdrTimestamp_example' -H 'x-xdr-nonce: xXdrNonce_example' -H 'x-child-
tenant-id: xChildTenantId_example'
'https://api-yourfqdn/public_api/v1/api_keys/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}" headers = { 'authorization':
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
'x-xdr-auth-id': "2841", 'x-xdr-timestamp': "SOME_STRING_VALUE", 'x-xdr-nonce': "SOME_STRING_VALUE", 'x-child-tenant-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/api_keys/delete",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/api_keys/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["authorization"] =
'DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request["x-xdr-auth-id"] = '2841' request["x-xdr-timestamp"] = 'SOME_STRING_VALUE' request["x-xdr-nonce"] =
'SOME_STRING_VALUE' request["x-child-tenant-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "id", "operator": "in", "value": [ 0 ] } ] }
}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function ()
{ if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/api_keys/delete"); xhr.setRequestHeader("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
```

```
xhr.setRequestHeader("x-xdr-auth-id", "2841"); xhr.setRequestHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-nonce", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-child-tenant-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/api_keys/delete")
.header("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
.header("x-xdr-auth-id", "2841") .header("x-xdr-timestamp", "SOME_STRING_VALUE") .header("x-xdr-nonce",
"SOME_STRING_VALUE") .header("x-child-tenant-id", "SOME_STRING_VALUE") .header("content-type", "application/json")
.body("{\"request_data\":{\"filters\":[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}") .asString();
import Foundation let headers = [ "authorization":
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
"x-xdr-auth-id": "2841", "x-xdr-timestamp": "SOME_STRING_VALUE", "x-xdr-nonce": "SOME_STRING_VALUE", "x-child-tenant-
id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [
"field": "id", "operator": "in", "value": [0] ] ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/api_keys/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/api_keys/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}",
CURLOPT_HTTPHEADER => [ "authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
"content-type: application/json", "x-child-tenant-id: SOME_STRING_VALUE", "x-xdr-auth-id: 2841", "x-xdr-nonce:
SOME_STRING_VALUE", "x-xdr-timestamp: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/api_keys/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "authorization:
DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7Gm
headers = curl_slist_append(headers, "x-xdr-auth-id: 2841"); headers = curl_slist_append(headers, "x-xdr-timestamp:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-nonce: SOME_STRING_VALUE"); headers =
curl_slist_append(headers, "x-child-tenant-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-
type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/api_keys/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("authorization",
"DCdIeow0xm73EwnxjPza1tdHTfZQv2eH7bTKlTPkgBHLj8aSjFzjgTE9bQUK1DidlWLrnYRhaYQ4PCIyNrNJbMUC6DOWi8ANIn1JWpMTE2neGvoDIRsKUbj6pJ1z7G
request.AddHeader("x-xdr-auth-id", "2841"); request.AddHeader("x-xdr-timestamp", "SOME_STRING_VALUE");
request.AddHeader("x-xdr-nonce", "SOME_STRING_VALUE"); request.AddHeader("x-child-tenant-id", "SOME_STRING_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"filters\":[{\"field\":\"id\",\"operator\":\"in\",\"value\":[0]}]}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "id", "operator": "in", "value": [ 121, 134 ] } ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ update_countinteger

The number of API keys deleted.

RESPONSE

Example 1

```
{ "reply": { "update_count": 2 } }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.3 | Asset groups

APIs for managing asset groups

2.1.3.1 | Get all or filtered asset groups

post /public_api/v1/asset-groups

By grouping assets based on shared attributes, you can address them collectively. Asset groups enable more efficient bulk actions and simplifies both filtering and scoping within the inventory and across the platform.

Get all or filtered asset groups.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/asset-groups'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
{\"AND\":[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}" headers
= { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/asset-groups", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/asset-groups") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}" response
= http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": { "AND": [ { "SEARCH_FIELD": "XDM.ASSET_GROUP.TYPE",
"SEARCH_TYPE": "EQ", "SEARCH_VALUE": "Dynamic" } ] }, "sort": [ { "FIELD": "XDM.ASSET_GROUP.LAST_UPDATE_TIME",
"ORDER": "DESC" } ], "search_from": 0, "search_to": 1000 } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/asset-groups");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/asset-groups")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
```

```
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": ["AND": [ [ "SEARCH_FIELD":
"XDM.ASSET_GROUP.TYPE", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "Dynamic" ] ]], "sort": [ [ "FIELD":
"XDM.ASSET_GROUP.LAST_UPDATE_TIME", "ORDER": "DESC" ] ], "search_from": 0, "search_to": 1000 ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/asset-groups")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/asset-
groups", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/asset-groups"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/asset-groups"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"XDM.ASSET_GROUP.TYPE\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"Dynamic\"}]},\"sort\":
[{\"FIELD\":\"XDM.ASSET_GROUP.LAST_UPDATE_TIME\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ filtersobject

▶ sortarray

▶ search_frominteger

▶ search_tointeger

REQUEST AndFilterForGroups

```
{ "request_data": { "filters": { "AND": [ { "SEARCH_FIELD": "XDM.ASSET_GROUP.TYPE", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "Dynamic" } ] }, "sort": [ { "FIELD": "XDM.ASSET_GROUP.LAST_UPDATE_TIME", "ORDER": "DESC" } ],
"search_from": 0, "search_to": 1000 } }
{ "request_data": { "filters": { "AND": [ { "SEARCH_FIELD": "XDM.ASSET_GROUP.TYPE", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "Dynamic" } ] }, "sort": [ { "FIELD": "XDM.ASSET_GROUP.LAST_UPDATE_TIME", "ORDER": "DESC" } ],
"search_from": 0, "search_to": 1000 } }
```

Responses

Ok

Body

application/json

[

▶ replyobject

]

RESPONSE

```
[ { "reply": { "data": [ {} ], "metadata": { "filter_count": 1, "total_count": 1000 } } } ]
```

Unauthorized

Body

application/json

[

▶ err_codeinteger

▶ err_msgstring
▶ err_extrastring
]
RESPONSE
```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Internal Server Error, Invalid Input

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.3.2 | Create an Asset Group

post /public_api/v1/asset-groups/create

Create a dynamic Asset Group by specifying the filters, or a static group to manually include individual assets.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/asset-groups/create'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}" headers
= { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/asset-groups/create", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/asset-groups/create")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "asset_group": { "group_name": "string", "group_type": "Dynamic",
"group_description": "string", "membership_predicate": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class",
"SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/asset-groups/create");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/asset-groups/create")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
```

```
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["asset_group": [ "group_name": "string",
"group_type": "Dynamic", "group_description": "string", "membership_predicate": ["AND": [ [ "SEARCH_FIELD":
"xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" ] ]] ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/asset-groups/create")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/asset-
groups/create", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT =>
30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/asset-groups/create"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/asset-groups/create"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ asset_groupobject

REQUEST a

```
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" } ], "OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] } } }
}
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" } ], "OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] } } }
}
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" } ], "OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] } } }
}
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" } ], "OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] } } }
}
```

Responses

Ok

Body

application/json

[

▶ replyobject

]

RESPONSE

```
[ { "reply": { "data": { "success": false, "asset_group_id": 1 } } } ]
```

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Internal Server Error, Invalid Input

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.3.3 | Update an Asset Group

post /public_api/v1/asset-groups/update/{group_id}

Update the Asset Group specified by Asset Group ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ group_id String required

Asset Group ID

Example: `groupId_example`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/asset-groups/update/{group_id}'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}" headers
= { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/asset-groups/update/%7Bgroup_id%7D", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/asset-
groups/update/%7Bgroup_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
```

{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "asset_group": { "group_name": "string", "group_type": "Dynamic",
"group_description": "string", "membership_predicate": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class",
"SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/asset-
groups/update/%7Bgroup_id%7D"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-
xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/asset-groups/update/%7Bgroup_id%7D")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}")
.asString();
import Foundation let headers = ["Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json"] let parameters = ["request_data": ["asset_group": ["group_name": "string",
"group_type": "Dynamic", "group_description": "string", "membership_predicate": ["AND": [["SEARCH_FIELD":
"xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other"]]]]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/asset-groups/update/%7Bgroup_id%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-yourfqdn/public_api/v1/asset-
groups/update/%7Bgroup_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}",
CURLOPT_HTTPHEADER => ["Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE"],]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/asset-groups/update/%7Bgroup_id%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/asset-groups/update/%7Bgroup_id%7D"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"asset_group\":
{\"group_name\":\"string\",\"group_type\":\"Dynamic\",\"group_description\":\"string\",\"membership_predicate\":
{\"AND\":[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]}}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);

Body parameters

application/json

▼ request_dataobject

▶ asset_groupobject

REQUEST a

{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] } } }
}
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] } } }
}
{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example",
"membership_predicate": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE":
"Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] } } }
}

{ "request_data": { "asset_group": { "group_name": "example", "group_type": "Dynamic", "group_description": "example", "membership_predicate": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] } } } }

Responses

Ok

Body
application/json
[
▶ replyobject
]
RESPONSE
[{ "reply": { "data": { "success": false } } }]

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
[{ "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" }]

Internal Server Error, Invalid Input

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
[{ "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" }]

2.1.3.4 | Delete an Asset Group

post /public_api/v1/asset-groups/delete/{group_id}

Delete the Asset Group specified by Asset Group ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ group_id String required

Asset Group ID

Example: `groupId_example`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/asset-groups/delete/{group_id}'
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("POST", "/public_api/v1/asset-
groups/delete/%7Bgroup_id%7D", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/asset-
groups/delete/%7Bgroup_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/asset-
groups/delete/%7Bgroup_id%7D"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-
xdr-auth-id", "SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/asset-groups/delete/%7Bgroup_id%7D")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/asset-
groups/delete/%7Bgroup_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/asset-
groups/delete/%7Bgroup_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/asset-groups/delete/%7Bgroup_id%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/asset-groups/delete/%7Bgroup_id%7D"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ replyobject
]
RESPONSE

```
[ { "reply": { "data": { "success": false } } } ]
```

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Internal Server Error, Invalid Input

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.4 | Asset inventory

APIs for managing assets in the asset inventory

2.1.4.1 | Get all or filtered assets

post /public_api/v1/assets

Retrieve detailed information about all assets within your environment, including enterprise, multi-cloud, code, and external surfaces.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/assets", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/assets") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "filters": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ",
"SEARCH_VALUE": "Other" } ] }, "on_demand_fields": [ "xdm.host.ipv4_addresses" ], "sort": [ { "FIELD":
"xdm.asset.name", "ORDER": "DESC" } ], "search_from": 0, "search_to": 1000 }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/assets");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/assets") .header("Authorization",
"SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("
{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "filters": ["AND": [ [ "SEARCH_FIELD": "xdm.asset.type.class",
"SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" ] ]], "on_demand_fields": ["xdm.host.ipv4_addresses"], "sort": [ [
"FIELD": "xdm.asset.name", "ORDER": "DESC" ] ], "search_from": 0, "search_to": 1000 ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/assets")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
```

```
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/assets",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"filters\":
{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers,
"Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers
= curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"filters\":{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets"); var request = new RestRequest(Method.POST);
request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"filters\":
{\"AND\":
[{\"SEARCH_FIELD\":\"xdm.asset.type.class\",\"SEARCH_TYPE\":\"NEQ\",\"SEARCH_VALUE\":\"Other\"}]},\"on_demand_fields\":
[\"xdm.host.ipv4_addresses\"],\"sort\":
[{\"FIELD\":\"xdm.asset.name\",\"ORDER\":\"DESC\"}],\"search_from\":0,\"search_to\":1000}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ filtersobject

Any of AndFilter

▶ ANDarrayrequired

▶ ORarrayrequired

▼ on_demand_fieldsarray[string]

▼ sortarray

[

▶ FIELDstring

The field according to which you want the results to be sorted.

▶ ORDERstring (Enum)

Sort order. Valid values include:

- `ASC` (ascending order)
- `DESC` (descending order)

]

▼ search_frominteger

An integer representing the starting offset within the query result set from which you want assets returned.

▼ search_tointeger

An integer representing the end offset within the result set after which you do not want assets returned.
Assets in the asset inventory that are indexed higher than this value are not returned in the final results set.

Example:`1000`

REQUEST a

```
{ "filters": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ],
"OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] },
"on_demand_fields": [ "xdm.host.ipv4_addresses" ], "sort": [ { "FIELD": "xdm.asset.name", "ORDER": "DESC" } ],
"search_from": 0, "search_to": 1000 }
```


```
{ "filters": { "AND": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ],
"OR": [ { "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" } ] },
"on_demand_fields": [ "xdm.host.ipv4_addresses" ], "sort": [ { "FIELD": "xdm.asset.name", "ORDER": "DESC" } ],
"search_from": 0, "search_to": 1000 }
```

{ "filters": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] }, "on_demand_fields": ["xdm.host.ipv4_addresses"], "sort": [{ "FIELD": "xdm.asset.name", "ORDER": "DESC" }], "search_from": 0, "search_to": 1000 }
{ "filters": { "AND": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }], "OR": [{ "SEARCH_FIELD": "xdm.asset.type.class", "SEARCH_TYPE": "NEQ", "SEARCH_VALUE": "Other" }] }, "on_demand_fields": ["xdm.host.ipv4_addresses"], "sort": [{ "FIELD": "xdm.asset.name", "ORDER": "DESC" }], "search_from": 0, "search_to": 1000 }

Responses

Ok

Body
application/json
▼ replyobject
▶ dataarray
▶ metadataobject
RESPONSE
Example 1
{ "reply": { "data": [{ "issues_breakdown": { "critical": 0, "high": 0, "low": 0, "medium": 0 }, "xdm.asset.first_observed": 1747834085000, "xdm.asset.cloud.region": null, "xdm.asset.last_observed": 1748399709000, "issues_critical": 0, "xdm.asset.strong_id": "172.16.33.51", "xdm.asset.type.category": "Device", "xdm.asset.name": null, "xdm.asset.type.name": "Generic Device", "cases_breakdown": { "critical": 0, "high": 0, "low": 0, "medium": 0 }, "xdm.asset.provider": "ON_PREM", "xdm.asset.type.class": "Compute", "xdm.asset.id": "fffd007cff1c15f3a0d152ae630df9630ce00e39bc66811a9fa9b6457a788afc", "xdm.asset.type.id": "GENERIC_DEVICE", "cases_critical": 0, "xdm.asset.group_ids": [], "xdm.asset.realm": "Other", "xdm.host.ipv4_addresses": ["172.16.33.51"] }], "metadata": { "filter_count": 1, "total_count": 915 } } }

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
[{ "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" }]

Internal Server Error, Invalid Input

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
[{ "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" }]

2.1.4.2 | Get asset by ID

get /public_api/v1/assets/{id}

Retrieve detailed information about the asset specified by asset ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required

Asset ID

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/{id}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET", "/public_api/v1/assets/%7Bid%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/assets/%7Bid%7D")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/assets/%7Bid%7D");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/assets/%7Bid%7D")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/%7Bid%7D")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/%7Bid%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/%7Bid%7D"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body

application/json

▼ dataarray

[

▶ xdm.asset.last_observedinteger

Timestamp of when the asset was last observed

▶ xdm.asset.cloud.regionstring

Region of the cloud asset

▶ xdm.asset.idstring

Asset ID

▶ xdm.asset.providerstring

▶ xdm.asset.first_observedinteger

Timestamp of when the asset was first observed

▶ xdm.asset.type.namestring

Represents the provider-specific name for a particular asset within a category
▶ xdm.asset.strong_idstring
▶ xdm.asset.namestring

Asset name

▶ xdm.asset.type.classstring

The highest-level grouping of assets based on their general purpose or domain. It is a broad classification that defines the overall function of the assets.

▶ xdm.asset.type.idstring

Asset type ID

▶ xdm.asset.type.categorystring

A more detailed grouping within a class. It categorizes assets based on their normalized function or common type, regardless of the provider or implementation.

▶ issues_criticalinteger
▶ xdm.asset.realmstring
▶ xdm.asset.group_idsarray[string]

List of asset group IDs

▶ cases_breakdownobject
▶ issues_breakdownobject
▶ cases_criticalinteger
▶ xdm.host.ipv4_addressesarray[string]
]
▼ metadataobject
▶ filter_countinteger
▶ total_countinteger
RESPONSE
Example 1

```
{ "reply": { "data": [ { "xdm.asset.last_observed": 1748399709000, "xdm.asset.cloud.region": null, "xdm.asset.id":
"fffd007cff1c15f3a0d132ae630df9630fe00e39bc66813a9fa9b6457a786afc", "xdm.asset.provider": "ON_PREM",
"xdm.asset.first_observed": 1747834085000, "xdm.asset.type.name": "Generic Device", "xdm.asset.strong_id":
"172.16.33.51", "xdm.asset.name": null, "xdm.asset.type.class": "Compute", "xdm.asset.type.id": "GENERIC_DEVICE",
"xdm.asset.type.category": "Device", "issues_critical": 0, "xdm.asset.realm": "Other", "xdm.asset.group_ids": [],
"cases_breakdown": { "critical": 0, "high": 0, "low": 0, "medium": 0 }, "issues_breakdown": { "critical": 0, "high":
0, "low": 0, "medium": 0 }, "cases_critical": 0, "xdm.host.ipv4_addresses": [ "172.16.33.51" ] } ], "metadata": {
"filter_count": 1, "total_count": 915 } } }
```


Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```


Asset Not Found

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 404, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```


Internal Server Error

Body
application/json
[

▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.4.3 | Get raw fields of asset by ID

get /public_api/v1/assets/{id}/raw_fields

Get the raw fields of the asset specified by asset ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required

Asset ID

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/{id}/raw_fields'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET",
"/public_api/v1/assets/%7Bid%7D/raw_fields", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields"); struct curl_slist *headers = NULL; headers =
```

```
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/%7Bid%7D/raw_fields"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ replyobject
▶ dataarray
▶ metadataobject
RESPONSE
Example 1

```
{ "reply": { "data": [ { "xdm__asset__raw_fields": { "Platform Discovery": { "Adjustable": false, "Description": "The maximum number of times that you can call model inference in one minute for Anthropic Claude 3.5 Sonnet. The quota considers the combined sum of Converse, ConverseStream, InvokeModel and InvokeModelWithResponseStream.", "GlobalQuota": false, "QuotaAppliedAtLevel": "ACCOUNT", "QuotaArn": "arn:aws:servicequotas:ap-south-1:384346710675:bedrock/L-F457545D", "QuotaCode": "L-F457545D", "QuotaName": "Cross-region InvokeModel requests per minute for Anthropic Claude 3.5 Sonnet", "ServiceCode": "bedrock", "ServiceName": "Amazon Bedrock", "Unit": "None", "Value": 100 } } } ], "metadata": { "filter_count": 1, "total_count": 921 } } }
```

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Asset Not Found

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 404, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

Internal Server Error

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.4.4 | Get schema of asset inventory

get /public_api/v1/assets/schema

Get the schema of the asset inventory, including the field names, pretty field names, and field type for every entry in the data model.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/schema'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET", "/public_api/v1/assets/schema",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/assets/schema") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/assets/schema");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/assets/schema")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/schema")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/schema", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/schema"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/schema"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```
Responses

Ok

Body
application/json
[
▶ replyobject
]
RESPONSE
Example 1

```
{ "reply": { "DATA": [ { "field_name": "xdm.asset.id", "field_pretty_name": "Asset ID", "data_type": "TEXT" }, {
"field_name": "xdm.asset.name", "field_pretty_name": "Name", "data_type": "TEXT" }, { "field_name":
"xdm.asset.provider", "field_pretty_name": "Provider", "data_type": "ENUM" }, { "field_name": "xdm.asset.type.class",
"field_pretty_name": "Class", "data_type": "ENUM" } ] } }
```


Unauthorized

Body
application/json
[

▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Internal Server Error

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE
```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.4.5 | Get enum values of specified field

get /public_api/v1/assets/enum/{field_name}

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ field_name String required

Field name - must be of type Enum

Example: `fieldName_example`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/enum/{field_name}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET",
"/public_api/v1/assets/enum/%7Bfield_name%7D", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/enum/%7Bfield_name%7D"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ replyobject
]
RESPONSE
Example 1

```
{ "reply": { "DATA": [ { "NAME": "ACTIVE_DIRECTORY", "PRETTY_NAME": "Active Directory" }, { "NAME": "AKAMAI",
"PRETTY_NAME": "Akamai" }, { "NAME": "ALIBABA_CLOUD", "PRETTY_NAME": "Alibaba Cloud" } ] } }
```

Unauthorized

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "example" } ]
```

Internal Server Error

Body
application/json
[
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
]
RESPONSE

```
[ { "err_code": 500, "err_msg": "An unexpected behavior occurred by Cortex Pubic API", "err_extra": "example" } ]
```

2.1.5 | Attack surface management

APIs for attack surface management

2.1.5.1 | Get External Service

post /public_api/v1/assets/get_external_service

Get service details according to the service ID. You can send up to 20 IDs.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/get_external_service'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"service_id_list\":[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/assets/get_external_service", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/assets/get_external_service") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"service_id_list\":[\"string\"]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "service_id_list": [ "string" ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/assets/get_external_service"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/assets/get_external_service")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"service_id_list\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["service_id_list": ["string"]]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/get_external_service")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/get_external_service", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"service_id_list\":[\"string\"]}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/get_external_service"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"service_id_list\":
[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/get_external_service"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"service_id_list\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

A dictionary containing the API request fields.

▶ service_id_listarray[string]

Represents the service ID you want to get details for.

REQUEST

```
{ "request_data": { "service_id_list": [ "example" ] } }
```

Responses

OK

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ detailsarray

Service details according to the service ID.

RESPONSE

```
{ "reply": { "details": [ { "service_id": "example", "service_name": "example", "service_type": "example",
"ip_address": [ "example" ], "domain": [ {} ], "externally_detected_providers": [ "example" ], "is_active": "example",
"first_observed": 0, "last_observed": 0, "port": 0, "protocol": "example", "active_classifications": [ "example" ],
"inactive_classifications": [ {} ], "discovery_type": "example", "business_units": [ "example" ],
"externally_inferred_vulnerability_score": {}, "externally_inferred_cves": [ {} ], "details": { "serviceKey":
"example", "serviceKeyType": "example", "businessUnits": [ { "name": "example" } ], "providerDetails": [ { "name":
"example", "firstObserved": 0, "lastObserved": 0 } ], "certificates": [ { "certificate": { "issuer": "example",
"issuerAlternativeNames": "example", "issuerCountry": "example", "issuerEmail": "example", "issuerLocality":
"example", "issuerName": "example", "issuerOrg": "example", "formattedIssuerOrg": "example", "issuerOrgUnit":
"example", "issuerState": "example", "publicKey": "example", "publicKeyAlgorithm": "example", "publicKeyRsaExponent":
0, "signatureAlgorithm": "example", "subject": "example", "subjectAlternativeNames": "example", "subjectCountry":
"example", "subjectEmail": "example", "subjectLocality": "example", "subjectName": "example", "subjectOrg": "example",
"subjectOrgUnit": "example", "subjectState": "example", "serialNumber": "example", "validNotBefore": 0,
"validNotAfter": 0, "version": "example", "publicKeyBits": 0, "publicKeyModulus": "example", "publicKeySpki":
"example", "sha1Fingerprint": "example", "sha256Fingerprint": "example", "md5Fingerprint": "example" },
"activityStatus": "example", "lastObserved": 0, "firstObserved": 0 } ], "domains": [ {} ], "ips": [ { "ip": "example",
"protocol": "example", "provider": "example", "geolocation": { "latitude": 0, "longitude": 0, "countryCode":
"example", "city": "example", "regionCode": "example", "timeZone": 0 }, "activityStatus": "example", "lastObserved":
0, "firstObserved": 0 } ], "classifications": [ { "name": "example", "activityStatus": "example", "values": [ {
"jsonValue": "example", "firstObserved": 0, "lastObserved": 0 } ], "firstObserved": 0, "lastObserved": 0 } ],
"tlsVersions": [ { "tlsVersion": "example", "cipherSuite": "example", "firstObserved": 0, "lastObserved": 0,
"activityStatus": "example" } ], "inferredCvesObserved": [ {} ], "enrichedObservationSource": "example", "ip_ranges":
{} } } ] } }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.5.2 | Get All Services

post /public_api/v1/assets/get_external_services

Get a complete or filtered list of all your external services.

The maximum result limit is 500.

Request headers
▼ authorization String required

api-key

Example: `authorization_example`
▼ x-xdr-auth-id String required

api-key-id

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/get_external_services'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}" headers = { 'authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/assets/get_external_services", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/assets/get_external_services") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": { "field": "active_classifications", "operator":
"contains", "value": "string" }, "vulnerability_test_results": true, "search_from": 0, "search_to": 5000, "sort": {
"keyword": "string", "field": "string" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/assets/get_external_services"); xhr.setRequestHeader("authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/assets/get_external_services")
.header("authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}") .asString();
import Foundation let headers = [ "authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ "field":
"active_classifications", "operator": "contains", "value": "string" ], "vulnerability_test_results": true,
"search_from": 0, "search_to": 5000, "sort": [ "keyword": "string", "field": "string" ] ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/assets/get_external_services")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/get_external_services", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
```

```
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/get_external_services"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/get_external_services"); var request = new
RestRequest(Method.POST); request.AddHeader("authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":
{\"field\":\"active_classifications\",\"operator\":\"contains\",\"value\":\"string\"},\"vulnerability_test_results\":true,\"sea
{\"keyword\":\"string\",\"field\":\"string\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersobject

An array of filter fields.

▶ vulnerability_test_resultsboolean (Enum)

Use this field with the value `true` to get vulnerability test results for the last 14 days for each service. Using this field will slow down the endpoint.

▶ search_frominteger

An integer representing the start offset index of results.

▶ search_tointeger

An integer representing the start offset index of results. Use this field to specify the number of results on a page when using page token pagination.

▶ sortobject

Identifies the sort order for the result set.

REQUEST Example with page token

```
{ "request_data": { "filters": [ { "field": "string", "operator": "string", "value": "string" } ], "use_page_token":
true } }
{ "request_data": { "filters": [ { "field": "discovery_type", "operator": "in", "value": [ "colocated_on_ip",
"directly_discovery" ] }, { "field": "service_name", "operator": "contains", "value": "apache" } ], "search_from": 0,
"search_to": 500 } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ total_countinteger

▶ result_countinteger

▶ external_servicesarray

RESPONSE Example 1

```
{ "reply": { "total_count": 0, "result_count": 0, "external_services": [ { "service_id": "string", "service_name":
"string", "service_type": "string", "ip_address": [ "string" ], "domain": [ "string" ],
"externally_detected_providers": [ "string" ], "is_active": "string", "first_observed": 0, "last_observed": 0, "port":
0, "protocol": "string", "active_classifications": [ "string" ], "inactive_classifications": [ "string" ],
"discovery_type": "string", "business_units": [ "string" ], "externally_inferred_vulnerability_score": "null",
"externally_inferred_cves": [ {} ], "tls_versions": [ {} ], "inferred_cves_observed": [ {} ],
"cloud_management_status": "null" } ] } }
{ "reply": { "total_count": 2, "result_count": 2, "external_services": [ { "service_id": "<service_id>",
"service_name": "Server", "service_type": "AServer", "ip_address": [ "<ip_address>" ], "domain": [],
"externally_detected_providers": [ "On Prem" ], "is_active": "Active", "first_observed": 1647152340000,
"last_observed": 1649499420000, "port": 8009, "protocol": "TCP", "active_classifications": [ "AServer" ],
```

"inactive_classifications": [], "discovery_type": "DirectlyDiscovered", "business_units": ["Business Unit 1"], "externally_inferred_vulnerability_score": "null", "externally_inferred_cves": [], "tls_versions": [], "inferred_cves_observed": [] }, { "service_id": "<service_id>", "service_name": "HTTP Server", "service_type": "HttpServer", "ip_address": ["ip_address"], "domain": ["email.test.org"], "externally_detected_providers": ["Demo"], "is_active": "Inactive", "first_observed": 1647087420000, "last_observed": 1647087420000, "port": 80, "protocol": "TCP", "active_classifications": [], "inactive_classifications": ["HttpServer", "NginxWebServer", "ServerSoftware"], "discovery_type": "ColocatedOnIp", "business_units": ["Test - Import-Export"], "externally_inferred_vulnerability_score": "null", "externally_inferred_cves": [], "cloud_management_status": "null" }] } }

Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.5.3 | Get vulnerability tests

post /public_api/v1/assets/get_vulnerability_tests

Get a complete or filtered list of vulnerability tests. Results include details about each test, including the number of services confirmed vulnerable.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/assets/get_vulnerability_tests", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "string", "value": "string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"string", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/assets/get_vulnerability_tests")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/get_vulnerability_tests", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/get_vulnerability_tests"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"string\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example

```
{ "request_data": { "filters": [ { "field": "name", "operator": "contains", "value": "apache" } ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ total_countinteger

▶ result_countinteger

▶ vulnerability_testsarray

RESPONSE

Example


```
{ "reply": { "total_count": 1, "result_count": 1, "vulnerability_tests": [ { "id": "69527826-e1c5-42d8-b8d8-
2c2005b75cbe", "name": "Apache Solr DataImportHandler Code Injection Vulnerability", "vulnerability_ids": [ "CVE-2019-
0193" ], "description": "Apache Solr, a popular open-source search platform built on Apache Lucene, is affected by a
remote code execution vulnerability. Solr's DataImportHandler (DIH), an optional module widely used to import data
from databases and other sources, allows the entire DIH configuration to come from a request's \"dataConfig\"
parameter. The debug mode of the DIH admin screen uses this feature for convenient debugging and development of a DIH
configuration. However, since a DIH configuration can contain scripts, this parameter poses a security risk. The
affected products can potentially be exposed to the public internet, making them vulnerable to exploitation.\n",
"status": "DISABLED", "vendor_names": [ "apache" ], "affected_software": [ { "NAME":
"cpe:2.3:a:apache:solr:*:*:*:*:*:*:*:*", "VERSION_START_INCLUDING": null, "VERSION_START_EXCLUDING": null,
"VERSION_END_INCLUDING": null, "VERSION_END_EXCLUDING": "8.2.0", "VENDOR": "apache", "PRODUCT": "solr", "VERSION": "*"
} ], "severity_score": 7.2, "cwe_ids": [ "CWE-94" ], "epss_score": 0.9605, "references": [
"https://issues.apache.org/jira/browse/SOLR-13669" ], "remediation_guidance": "Exploiting this vulnerability may lead
```

to remote code execution, which could compromise the security and integrity of the affected system. To address this issue, follow these steps:\n\n1. Upgrade to Apache Solr 8.2.0 or later, which is secure by default.\n2. Alternatively, edit the solrconfig.xml to configure all DataImportHandler usages with an \"invariants\" section listing the \"dataConfig\" parameter set to an empty string.\n3. Ensure your network settings are configured so that only trusted traffic communicates with Solr, especially to the DIH request handler. This is a best practice for all Solr installations.\n\nBy implementing these fixes and mitigations, you can protect your Apache Solr installation from the remote code execution vulnerability described in CVE-2019-0193.\n", "first_published": 1699326060000, "created": 1711058940000, "count_vulnerable_services": null }] } }

2.1.5.4 | Bulk Update Vulnerability Tests

post /public_api/v1/assets/bulk_update_vulnerability_tests

Enable or disable vulnerability tests.

To view vulnerability test results, use the Get All Services or Get Service Details endpoints.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"test_names\":[\"string\"],\"status\":\"Enabled\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/assets/bulk_update_vulnerability_tests", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"test_names\":[\"string\"],\"status\":\"Enabled\"}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "test_names": [ "string" ], "status": "Enabled" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"test_names\":[\"string\"],\"status\":\"Enabled\"}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "test_names": ["string"], "status": "Enabled" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
```

```
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"test_names\":
[\"string\"],\"status\":\"Enabled\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-
auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json");
curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"test_names\":[\"string\"],\"status\":\"Enabled\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/bulk_update_vulnerability_tests"); var request
= new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-
auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"test_names\":[\"string\"],\"status\":\"Enabled\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ test_namesarray[string]

Names of tests, for example ["test1", "test2", "test3"]

▶ statusstring (Enum)

REQUEST

Example 1

```
{ "request_data": { "test_names": [ "Apache Solr DataImportHandler Code Injection Vulnerability" ], "status":
"Enabled" } }
```

Responses

OK

2.1.6 | Audit log

APIs for audit logs

2.1.6.1 | Get Audit Management Log

post /public_api/v1/audits/management_logs

Get audit management logs.

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 100.
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json,application/xml'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/audits/management_logs'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
```

```
"/public_api/v1/audits/management_logs", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/audits/management_logs") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "email", "operator": "in", "value": "string" }
], "search_from": 0, "search_to": 100, "sort": { "field": "type", "keyword": "asc" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/audits/management_logs"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/audits/management_logs")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "email", "operator":
"in", "value": "string" ] ], "search_from": 0, "search_to": 100, "sort": [ "field": "type", "keyword": "asc" ] ]] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/audits/management_logs")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/audits/management_logs", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-
type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/audits/management_logs"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/audits/management_logs"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":
[{\"field\":\"email\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields. An empty dictionary returns all results.

▶ filtersarray

Array of filter fields.

▶ search_frominteger

An integer representing the starting offset within the query result set from which you want management logs returned. Management logs are returned as a zero-based list. Any log indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

An integer representing the end offset within the result set after which you do not want management logs returned. Logs in the management log list that are indexed higher than this value are not returned in the final results set. Defaults to 100, which returns all logs to the end of the list.

▶ sortobject

Identifies the sort order for the result set. By default the sort is defined as creation-time and desc.

REQUEST Request all management logs from older to newer

```
{ "request_data": { "search_from": 0, "search_to": 100, "sort": { "field": "timestamp", "keyword": "asc" } } }
{ "request_data": {} }
{ "request_data": { "search_from": 0, "search_to": 100, "sort": { "field": "timestamp", "keyword": "asc" }, "filters":
[ { "field": "type", "operator": "in", "value": [ "AUTH" ] }, { "field": "sub_type", "operator": "in", "value": [
"login" ] }, { "field": "result", "operator": "in", "value": [ "SUCCESS" ] }, { "field": "timestamp", "operator":
"gte", "value": 1565074114053 } ] } }
```

Responses

Successful response

Body
application/json

▼ replyobject

JSON object containing the query result.

▶ total_countinteger

Number of total results of this filter without paging.

▶ result_countinteger

Number of returned items.

▶ dataarray

List of audit items.

RESPONSE
example-1

```
{ "reply": { "total_count": 1, "result_count": 1, "data": [ { "AUDIT_ID": 1, "AUDIT_OWNER_NAME": "User Name",
"AUDIT_OWNER_EMAIL": "username@paloaltonetworks.com", "AUDIT_ASSET_JSON": "{}", "AUDIT_ASSET_NAMES": "",
"AUDIT_HOSTNAME": "", "AUDIT_RESULT": "SUCCESS", "AUDIT_REASON": "", "AUDIT_DESCRIPTION": "", "AUDIT_ENTITY": "AUTH",
"AUDIT_ENTITY_SUBTYPE": "Login", "AUDIT_SESSION_ID": 382303947890, "AUDIT_CASE_ID": 473829372, "AUDIT_INSERT_TIME":
1565074114053, "AUDIT_SEVERITY": "SEV_020_LOW", "AUDIT_LINK": null, "AUDIT_SOURCE_IP": "31.174.156.148",
"AUDIT_USER_AGENT": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0
Safari/537.36", "AUDIT_USER_ROLES": [ "Account Admin" ], "AUDIT_ADDITIONAL_INFORMATION": { "endpoint_names": [ "WIN-
fgo6762G" ], "endpoint_count": 1 }, "AUDIT_OBJECT_ID": null } ] } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

RESPONSE

```
<root/>
```

2.1.6.2 | Get Audit Agent Report

post /public_api/v1/audits/agents_reports

Get agent event reports.

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 100.
- Offset is the zero-based number of cases from the start of the result set.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/audits/agents_reports'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/audits/agents_reports",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/audits/agents_reports") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"type\",\"keyword\":\"asc\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id", "operator": "in", "value": [
"string" ] } ], "search_from": 0, "search_to": 100, "sort": { "field": "type", "keyword": "asc" } } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/audits/agents_reports"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/audits/agents_reports")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"type\",\"keyword\":\"asc\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id",
"operator": "in", "value": ["string"] ] ], "search_from": 0, "search_to": 100, "sort": [ "field": "type", "keyword":
"asc" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/audits/agents_reports")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
```

```
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/audits/agents_reports", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-
type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/audits/agents_reports"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"type\",\"keyword\":\"asc\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/audits/agents_reports"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"type\",\"keyword\":\"asc\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields. An empty dictionary returns all results.

▶ filtersarray

An array of filter fields.

▶ search_frominteger

An integer representing the starting offset within the query result set from which you want agent reports returned. Reports are returned as a zero-based list. Any report indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

An integer representing the end offset within the result set after which you do not want agent reports returned. Reports in the agent report list that are indexed higher than this value are not returned in the final results set. Defaults to 100, which returns all reports to the end of the list.

▶ sortobject

Identifies the sort order for the result set.

REQUEST Request all results

```
{ "request_data": {} }
{ "request_data": { "filters": [ { "field": "trapsversion", "operator": "in", "value": [ "<version value>", "<version
value>" ] }, { "field": "timestamp", "operator": "gte", "value": 0 }, { "field": "domain", "operator": "in", "value":
[ "WORKGROUP" ] } ], "sort": { "field": "timestamp", "keyword": "asc" } } }
```

Responses

OK

Body

application/json

▼ replyobject

JSON object containing the query result.

▶ total_countinteger

Number of total results of this filter without paging.

▶ result_countinteger

Number of returned items.

▶ dataarray

List of audit items.
RESPONSE
{ "reply": { "total_count": 0, "result_count": 0, "data": [{ "TIMESTAMP": 0.1, "RECEIVEDTIME": 0.1, "ENDPOINTID": "example", "ENDPOINTNAME": "example", "DOMAIN": "example", "TRAPSVERSION": "example", "CATEGORY": "example", "TYPE": "example", "SUBTYPE": "example", "RESULT": "example", "REASON": "example", "DESCRIPTION": "example" }] } }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, ID, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.7 | Authentication settings

APIs for authentication settings, such as IdP and SSO

2.1.7.1 | Create authentication settings for IdP SSO or metadata URL

post /public_api/v1/authentication-settings/create

Create authentication settings for IdP SSO or metadata URL. You must include either the `metadata_url` field or all of the following fields: `idp_sso_url`, `idp_issuer`, and `idp_certificate`.

You must have **Instance Administrator** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/authentication-settings/create'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/authentication-settings/create", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/authentication-
settings/create") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "default_role": "string", "is_account_role": false,
"domain": "string", "mappings": { "email": "string", "firstname": "string", "lastname": "string", "group_name":
"string" }, "advanced_settings": { "relay_state": "string", "idp_single_logout_url": "string",
"service_provider_public_cert": "string", "service_provider_private_key": "string", "authn_context_enabled": false,
"force_authn": false }, "idp_sso_url": "string", "idp_certificate": "string", "idp_issuer": "string", "metadata_url":
"string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/authentication-settings/create"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/authentication-settings/create")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "name": "string", "default_role": "string",
"is_account_role": false, "domain": "string", "mappings": [ "email": "string", "firstname": "string", "lastname":
"string", "group_name": "string" ], "advanced_settings": [ "relay_state": "string", "idp_single_logout_url": "string",
"service_provider_public_cert": "string", "service_provider_private_key": "string", "authn_context_enabled": false,
"force_authn": false ], "idp_sso_url": "string", "idp_certificate": "string", "idp_issuer": "string", "metadata_url":
"string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/authentication-settings/create")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/authentication-settings/create", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/authentication-settings/create"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
```

```
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/authentication-settings/create"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"domain\":\"string\",\"mappings\":
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ namestringrequired

The name of the SSO integration.

▶ default_rolestring

The default role automatically assigned to every user who authenticates to Cortex using SAML. This is an inherited role and is not the same as a direct role assigned to the user.

If a role with the same name exists on both Cortex Gateway and the tenant, the role will mapped to the role from the tenant. If you want to use specifically the role from Cortex Gateway, use the `is_account_role` parameter set to `true`.

▶ is_account_roleboolean

Whether the role was created in Cortex Gateway or in the tenant. When the value is `true`, the role was created in Cortex Gateway.

▶ domainstring

When configuring the first SSO, this parameter should be included as empty because it is the default SSO and has a fixed, read-only value. For additional SSOs, specify this IdP with an email domain (user@). When logging in, users are redirected to the IdP associated with their email domain or to the default IdP if no association exists.

▶ mappingsobject

These IdP attribute mappings are dependent on your organizationâ€ s IdP.

▶ advanced_settingsobject

The advanced settings are optional to configure and some are specific for a particular IdP.

▶ idp_sso_urlstring

The login URL of your IdP and should be copied from your SAML integration configuration on the IdP. For example:

- Okta: https://cortex-test.okta.com/app/cortex-test/eacbt6b2jj08CasdUQ7sdf15d7/sso/SAML
- Microsoft Azure: https://login.microsoftonline.com/6a5a9780-96a4-41ef-bf45-0535d8a70025/saml2

▶ idp_certificatestring

The Idp's public X.509 digital certificate in PEM format for verification, which is copied from your organization's IdP.

▶ idp_issuerstring

The unique identifier of the IdP issuing SAML assertions, which is copied from your organization's IdP.

▶ metadata_urlstring

The metadata URL provides information about hte IdP's capabilities, endpoints, keys, and more. For example:

- Okta: https://cortex-test.okta.com/app/exkbuuzw77Bh04V6M6b8/sso/saml/metadata
- Microsoft Azure: https://login.microsoftonline.com/6a5a9780-96a4-41ef-bf45-0535d8a70025/saml2/metadata

REQUEST

Example 1

```
{ "request_data": { "name": "IdP configuration", "default_role": "Analyst", "domain": "my-test-domain.com",
"mappings": { "email": "user@company.com", "firstname": "John", "lastname": "Smith", "group_name": "analysts" },
"idp_sso_url": "https://cortex-test.okta.com/app/cortex-test/xxxxxxx/sso/SAML", "idp_certificate":
"MY_CERTIFICATE_FROM_OKTA", "idp_issuer": "https://cortex-test.okta.com/idp", "advanced_settings": {},
"is_account_role": true } }
```

Responses

OK

Body
application/json
▼ replyboolean
RESPONSE
Example 1
```
{ "reply": true }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.



RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.7.2 | Update authentication settings

post /public_api/v1/authentication-settings/update

Update existing authentication settings. To update the default domain, include empty value for both `current_domain_value` and `new_domain_value`.

You must have **Instance Administrator** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
```

```
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/authentication-settings/update'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/authentication-settings/update", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/authentication-
settings/update") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "default_role": "string", "is_account_role": false,
"current_domain_value": "string", "new_domain_value": "string", "mappings": { "email": "string", "firstname":
"string", "lastname": "string", "group_name": "string" }, "advanced_settings": { "relay_state": "string",
"idp_single_logout_url": "string", "service_provider_public_cert": "string", "service_provider_private_key": "string",
"authn_context_enabled": false, "force_authn": false }, "idp_sso_url": "string", "idp_certificate": "string",
"idp_issuer": "string", "metadata_url": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/authentication-
settings/update"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/authentication-settings/update")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "name": "string", "default_role": "string",
"is_account_role": false, "current_domain_value": "string", "new_domain_value": "string", "mappings": [ "email":
"string", "firstname": "string", "lastname": "string", "group_name": "string" ], "advanced_settings": [ "relay_state":
"string", "idp_single_logout_url": "string", "service_provider_public_cert": "string", "service_provider_private_key":
"string", "authn_context_enabled": false, "force_authn": false ], "idp_sso_url": "string", "idp_certificate":
"string", "idp_issuer": "string", "metadata_url": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/authentication-settings/update")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/authentication-settings/update", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/authentication-settings/update"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
```

{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/authentication-settings/update"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"name\":\"string\",\"default_role\":\"string\",\"is_account_role\":false,\"current_domain_value\":\"string\",\"new_domain_val
{\"email\":\"string\",\"firstname\":\"string\",\"lastname\":\"string\",\"group_name\":\"string\"},\"advanced_settings\":
{\"relay_state\":\"string\",\"idp_single_logout_url\":\"string\",\"service_provider_public_cert\":\"string\",\"service_provider
ParameterType.RequestBody); IRestResponse response = client.Execute(request);

Body parameters

application/json

▼ request_dataobject

▶ namestringrequired

The name of the SSO integration.

▶ default_rolestring

The default role automatically assigned to every user who authenticates to Cortex using SAML. This is an inherited role and is not the same as a direct role assigned to the user.

If a role with the same name exists on both Cortex Gateway and the tenant, the role will mapped to the role from the tenant. If you want to use specifically the role from Cortex Gateway, use the `is_account_role` parameter set to `true`.

▶ is_account_roleboolean

Whether the role was created in Cortex Gateway or in the tenant. When the value is `true`, the role was created in Cortex Gateway.

▶ current_domain_valuestring

The domain whose authentication settings you want to update.

▶ new_domain_valuestring

If you want to update the domain value, include a new unique domain.

▶ mappingsobject

These IdP attribute mappings are dependent on your organization's IdP.

▶ advanced_settingsobject

The advanced settings are optional to configure and some are specific for a particular IdP.

▶ idp_sso_urlstring

The URL of your IdP's SSO, which is a fixed, read-only value based on your tenant's URL. If you are using this parameter, you must also specify: `idp_certificate` and `idp_issuer`.

▶ idp_certificatestring

The Idp's public X.509 digital certificate in PEM format for verification, which is copied from your organization's IdP.

▶ idp_issuerstring

The unique identifier of the IdP issuing SAML assertions, which is copied from your organization's IdP.

▶ metadata_urlstring

Specify your IdP SSO URL, which is a fixed, read-only value based on your tenant's URL.

REQUEST

Example 1

{ "request_data": { "name": "IDP configuration", "default_role": "Analyst", "current_domain_value": "my-test-domain.com", "new_domain_value": "my-test-domain.org", "mappings": { "email": "user@company.com", "firstname": "John", "lastname": "Smith", "group_name": "analysts" }, "idp_sso_url": "https://cortex-test.okta.com/app/cortex-test/xxxxxxx/sso/SAML", "idp_certificate": "========MY_UPDATED_TEST_CERTIFICATE_FROM_OKTA======", "idp_issuer": "https://cortex-test.okta.com/idp", "advanced_settings": {}, "is_account_role": true } }

Responses

OK

Body

application/json
▼ replyboolean
RESPONSE
```
{ "reply": false }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.7.3 | Delete authentication settings by domain

post /public_api/v1/authentication-settings/delete

Delete all authentication settings for the specified domain.

**Note: ** The first configuration on the tenant is the default configuration and cannot be deleted.

You must have **Instance Administrator** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/authentication-settings/delete'
```

```
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"domain\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/authentication-settings/delete", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/authentication-
settings/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":{\"domain\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "domain": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/authentication-
settings/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/authentication-settings/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"domain\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["domain": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/authentication-settings/delete")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/authentication-settings/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"domain\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/authentication-settings/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"domain\":\"string\"}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/authentication-settings/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"domain\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ domainstring

The domain whose authentication settings you want to delete.

REQUEST

Example 1

```
{ "request_data": { "domain": "my-test-domain.org" } }
```

Responses

OK

Body

application/json

▼ replyboolean

RESPONSE

Example 1

```
{ "reply": true }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.7.4 | Get authentication settings for all configured domains

post /public_api/v1/authentication-settings/get/settings

Get all the authentication settings for every configured domain in the tenant.

You must have **Instance Administrator** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/authentication-settings/get/settings'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/authentication-settings/get/settings", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/authentication-
settings/get/settings") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":{}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/authentication-
settings/get/settings"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/authentication-
settings/get/settings") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE")
.header("content-type", "application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/authentication-settings/get/settings")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/authentication-settings/get/settings", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/authentication-settings/get/settings"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/authentication-settings/get/settings"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

REQUEST

```
{ "request_data": {} }
```

Responses

OK

Body

application/json

▼ replyarray

[

▶ tenant_idstring

▶ namestring

▶ domainstring

▶ idp_enabledboolean

▶ default_rolestring

▶ is_account_rolestring

▶ idp_certificatestring

▶ idp_issuerstring

▶ idp_sso_urlstring

▶ metadata_urlstring

▶ mappingsobject

▶ advanced_settingsobject

▶ sp_entity_idstring

▶ sp_logout_urlstring

▶ sp_urlstring

]

RESPONSE

Example 1


```
{ "reply": [ { "tenant_id": "9949042437653", "name": "SSO Integration", "domain": "", "idp_enabled": true,
"default_role": null, "is_account_role": null, "idp_certificate": "certificate", "idp_issuer": "http://test.com",
"idp_sso_url": "http://test.com/", "metadata_url": "", "mappings": { "email": "user@company.com", "firstname": "John",
```

"group_name": "Users", "lastname": "Smith" }, "advanced_settings": { "authn_context_enabled": false, "force_authn": null, "idp_single_logout_url": "", "relay_state": "", "service_provider_private_key": "", "service_provider_public_cert": "" }, "sp_entity_id": "https://tenant.cortex.us.paloaltonetworks.com", "sp_logout_url": "https://tenant.cortex.us.paloaltonetworks.com/idp/logout", "sp_url": "https://tenant.cortex.us.paloaltonetworks.com/idp/saml" }] }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.7.5 | Get IdP metadata

post /public_api/v1/authentication-settings/get/metadata

Get the metadata for all IdPs.

You must have **Instance Administrator** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/authentication-settings/get/metadata'
```

```
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/authentication-settings/get/metadata", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/authentication-
settings/get/metadata") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE'
request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":{}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/authentication-
settings/get/metadata"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/authentication-
settings/get/metadata") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE")
.header("content-type", "application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/authentication-settings/get/metadata")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/authentication-settings/get/metadata", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/authentication-settings/get/metadata"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/authentication-settings/get/metadata"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

REQUEST

```
{ "request_data": {} }
```

Responses

OK

Body

application/json

▼ replyobject

▶ sp_entity_idstring

▶ sp_logout_urlstring

▶ sp_urlstring

▶ tenant_idstring

RESPONSE

Example 1

```
{ "reply": { "sp_entity_id": "https://tenant.cortex.us.paloaltonetworks.com", "sp_logout_url":
"https://tenant.cortex.us.paloaltonetworks.com/idp/logout", "sp_url":
"https://tenant.cortex.us.paloaltonetworks.com/idp/saml", "tenant_id": "9949042437653" } }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.8 | BIOCs

APIs for managing BIOCs

2.1.8.1 | Get BIOCs

post /public_api/v1/bioc/get

Return a list of BIOCs. You can return all BIOCs or filter results. You can also return extended results with all details included.- The response is concatenated using AND condition (OR is not supported).

- The maximum result set size is >100.
- Offset is the zero-based number of incidents from the start of the result set.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/bioc/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}" headers = {
```

```
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/bioc/get", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/bioc/get") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "extended_view": true, "filters": [ { "field": "name", "operator":
"EQ", "value": "string" } ], "search_from": 0, "search_to": 0 } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/bioc/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/bioc/get") .header("Authorization",
"SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("
{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "extended_view": true, "filters": [ [
"field": "name", "operator": "EQ", "value": "string" ] ], "search_from": 0, "search_to": 0 ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/bioc/get")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/bioc/get",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/bioc/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/bioc/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ extended_viewboolean

▶ filtersarray

An array of filter fields.

▶ search_frominteger

Integer representing the starting offset within the query result set from which you want BIOCs returned. BIOCs are returned as a zero-based list. Any BIOC indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

Integer representing the end offset within the result set after which you do not want BIOCs returned. BIOCs in the BIOC list that are indexed higher than this value are not returned in the final results set. Defaults to >100, which returns all BIOCs to the end of the list.

REQUEST

Example 1


```
{ "request_data": { "extended_view": false } }
```


Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsarray

[

▶ rule_idinteger

▶ namestring

▶ typestring

▶ severitystring

▶ commentstring

▶ statusstring

▶ is_xqlboolean

▶ indicatorobject

▶ mitre_tactic_id_and_namearray[string]

▶ mitre_technique_id_and_namearray[string]

]

▼ objects_typestring

RESPONSE

Example 1


```
{ "objects_count": 2, "objects": [ { "rule_id": 376, "name": "TestDataSourceTags", "type": "OTHER", "severity":
"SEV_030_MEDIUM", "comment": "", "status": "DISABLED", "is_xql": false, "indicator": { "runOnCGO": true,
"investigationType": "PROCESS_EXECUTION_EVENT", "investigation": { "PROCESS_EXECUTION_EVENT": { "filter": { "AND": [ {
"SEARCH_FIELD": "action_process_username", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "guyk", "EXTRA_FIELDS": [],
"isExtended": false } ] } } } }, "mitre_tactic_id_and_name": [], "mitre_technique_id_and_name": [] }, { "rule_id":
421, "name": "new_bioc_test", "type": "EXECUTION", "severity": "SEV_020_LOW", "comment": "", "status": "ENABLED",
"is_xql": true, "indicator": "dataset = xdr_data | filter event_type = 1 and actor_process_image_name =
\"SDFDSGFHFN\"", "mitre_tactic_id_and_name": [ "12 - Tactic", "45 - Another Tactic" ], "mitre_technique_id_and_name":
[ "123 - Test", "12 - Another Test" ] } ], "objects_type": "bioc" }
```


Bad Request. Got invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.8.2 | Insert or update BIOCs

post /public_api/v1/bioc/insert

Insert new BIOCs or update existing BIOCs.

Note: The BIOC `rule_id` is tenant specific and can't be used across tenants. Inserting BIOCs with the same `rule_id` as an existing BIOC on that tenant will overwrite the existing BIOC.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/bioc/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-
type': "application/json" } conn.request("POST", "/public_api/v1/bioc/insert", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/bioc/insert") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": [ { "rule_id": 0, "name": "string", "type": "OTHER", "severity":
"SEV_010_INFO", "comment": "string", "status": "enabled", "is_xql": true, "indicator": { "property1": null,
"property2": null }, "mitre_tactic_id_and_name": [ "string" ], "mitre_technique_id_and_name": [ "string" ] } ] });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/bioc/insert"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/bioc/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ [ "rule_id": 0, "name": "string", "type":
"OTHER", "severity": "SEV_010_INFO", "comment": "string", "status": "enabled", "is_xql": true, "indicator": [
"property1": , "property2": ], "mitre_tactic_id_and_name": ["string"], "mitre_technique_id_and_name": ["string"] ] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/bioc/insert")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
```

```
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/bioc/insert",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-
xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/bioc/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/bioc/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"type\":\"OTHER\",\"severity\":\"SEV_010_INFO\",\"comment\":\"string\",\"status\":\"enable
{\"property1\":null,\"property2\":null},\"mitre_tactic_id_and_name\":[\"string\"],\"mitre_technique_id_and_name\":
[\"string\"]}]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataarrayrequired

[

▶ rule_idinteger

▶ namestring

BIOC name.

▶ typeobject (Enum)

BIOC type.

▶ severityobject (Enum)

BIOC severity.

▶ commentstring

▶ statusobject (Enum)

BIOC status.

▶ is_xqlboolean

▶ indicatorobject

▶ mitre_tactic_id_and_namearray[string]

▶ mitre_technique_id_and_namearray[string]

]

REQUEST

Example 1

```
{ "request_data": [ { "name": "TestBIOC", "type": "EXECUTION", "severity": "SEV_020_LOW", "comment": "", "status":
"ENABLED", "is_xql": false, "indicator": { "runOnCGO": true, "investigationType": "FILE_EVENT", "investigation": {
"FILE_EVENT": { "filter": { "AND": [ { "OR": [ { "SEARCH_FIELD": "event_sub_type", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "1", "isExtended": false }, { "SEARCH_FIELD": "event_sub_type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE":
"2", "isExtended": false }, { "SEARCH_FIELD": "event_sub_type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "3",
"isExtended": false }, { "SEARCH_FIELD": "event_sub_type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "5", "isExtended":
false }, { "SEARCH_FIELD": "event_sub_type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "6", "isExtended": false } ] }, {
"SEARCH_FIELD": "action_file_name", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "aaaaaa", "EXTRA_FIELDS": [], "isExtended":
false } ] } } } }, "mitre_tactic_id_and_name": [ "" ], "mitre_technique_id_and_name": [ "" ] } ] }
```

Responses

OK

Body

application/json

▼ added_objectsarray

List of BIOC objects added.

[
▶ idinteger
▶ statusstring
]
▼ updated_objectsarray

List of BIOC objects updated.

[
▶ idinteger
▶ statusstring
]
▼ errorsarray[string]

A list of errors.

RESPONSE
Example 1

```
{ "added_objects": [ { "id": 34, "status": "Created a new BIOC rule with the ID: 34 successfully" } ],
"updated_objects": [], "errors": [] }
```


Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.8.3 | Delete BIOCs

post /public_api/v1/bioc/delete

Delete BIOCs selected by filter.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/bioc/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-
auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/bioc/delete",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/bioc/delete") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "EQ", "value": true } ] }
}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function ()
{ if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/bioc/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/bioc/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"EQ", "value": true ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/bioc/delete")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/bioc/delete",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/bioc/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/bioc/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":true}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```
Body parameters
application/json
▼ request_dataobjectrequired
▶ filtersarray

An array of filter fields.

REQUEST

Example 1


```
{ "request_data": { "extended_view": false, "filters": [ { "field": "severity", "operator": "EQ", "value": "SEV_020_LOW" } ] } }
```


Responses

OK

Body
application/json

▼ objects_countinteger

Number of BIOC objects deleted.

▼ objectsarray[integer]

RESPONSE

Example 1


```
{ "objects_count": 3, "objects": [ 1, 3, 7 ] }
```


Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.9 | Cases

APIs for managing cases

2.1.9.1 | Retrieve cases based on filters

post /public_api/v1/case/search

This endpoint retrieves a list of cases that match the specified filter criteria. It supports filtering by `case_id`, `case_domain`, `status_progress`, `severity`, and `creation_time`, along with sorting and pagination.

Request Body:

- `request_data`: Object containing filter criteria
  - `filters`: Array of filter objects
    - `field`: String (enum: 'case_id', 'case_domain', 'severity', 'creation_time', 'status_progress')
    - `operator`: String (enum: 'in', 'gte', 'lte')
    - `value`: Array of integers/strings or single integer
- `search_from`: Integer (default: 0) - Starting index for pagination
- `search_to`: Integer (default: 100) - Ending index for pagination
- `sort`: Object for sorting results
  - `field`: String (enum: 'creation_time', 'severity', 'case_id')
  - `keyword`: String (enum: 'asc', 'desc') - Sort order

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/case/search'
-d ''
```
Body parameters
required
application/json
▼ request_dataobject
▶ filtersarray
▶ search_frominteger

Starting index for pagination.

▶ search_tointeger

Ending index for pagination.

▶ sortobject
REQUEST a
```
{ "request_data": { "filters": [ { "field": "case_id", "operator": "in", "value": [ 0 ] } ], "search_from": 0,
"search_to": 0, "sort": { "field": "case_id", "keyword": "asc" } } }
{ "request_data": { "filters": [ { "field": "case_id", "operator": "in", "value": [ "example" ] } ], "search_from": 0,
"search_to": 0, "sort": { "field": "case_id", "keyword": "asc" } } }
{ "request_data": { "filters": [ { "field": "case_id", "operator": "in", "value": 0 } ], "search_from": 0,
"search_to": 0, "sort": { "field": "case_id", "keyword": "asc" } } }
```
Responses

Successful response with cases

Body
application/json
▼ replyobject
▶ TOTAL_COUNTinteger
▶ FILTER_COUNTinteger
▶ DATAarray
RESPONSE
```
{ "reply": { "TOTAL_COUNT": 0, "FILTER_COUNT": 0, "DATA": [ { "case_id": "123", "creation_time": "2024-02-
26T12:34:56Z", "owner": "CWP", "case_domain": "SECURITY", "auto_resolve_case": false, "custom_fields": { "priority":
"High", "incident_id": "INC98765" }, "status_progress": "UNDER_INVESTIGATION", "resolve_reason": "RESOLVED_OTHER",
"resolve_comment": "Case has been marked as a false positive.", "last_modified": 1708950896000, "score": 85,
"severity": "HIGH", "description": "Unauthorized access detected", "scoring_type": "Risk-Based", "assigned_to":
"U56789", "assigned_to_name": "JaneSmith", "is_cloud": true, "is_automated": false, "issues": [ "123" ], "assets": [
"6f1d9b9361f8a6964bf3e79e6667e5fe" ], "artifacts": [ "12345" ] } ] } }
```

Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE

```
{ "error": "Invalid request data" }
```

Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE

```
{ "error": "Unauthorized request" }
```

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE

```
{ "error": "Internal server error" }
```

2.1.9.2 | Update existing case

post /public_api/v1/case/update/{case-id}

Update an existing case in the system. Users can only update one case at a time.

- At least one of the following fields is mandatory:
  - case_id

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ case-id Integer required

Numeric ID of the case to update

Example: `56`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/case/update/{case-id}'
-d ''
```

Body parameters
required
application/json
▼ request_dataobject
▶ update_dataobject
REQUEST

```
{ "request_data": { "update_data": { "status_progress": "RESOLVED", "resolve_reason": "RESOLVED_OTHER",
"resolve_comment": "Case has been marked as a false positive." } } }
```

Responses

Case updated successfully

Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE
```
{ "error": "Invalid request data" }
```

Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE
```
{ "error": "Unauthorized request" }
```

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE
```
{ "error": "Internal server error" }
```

2.1.9.3 | Retrieve Case Artifacts by Case Id

get /public_api/v1/case/artifacts/{case-id}

This endpoint retrieves the artifacts for a given case_id

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ case-id Integer required

Numeric ID of the case

Example: `56`
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/case/artifacts/{case-id}'
```
Responses

Successful response with cases

Body
application/json
▼ replyobject
▶ TOTAL_COUNTinteger
▶ FILTER_COUNTinteger
▶ DATAarray
RESPONSE
```
{ "reply": { "TOTAL_COUNT": 0, "FILTER_COUNT": 0, "DATA": [ { "case_id": 1234, "network_artifacts": { "DATA": [ {
"artifact_id": "A12345", "file_name": "test", "file_sha256": "1111", "file_signature_status": "SIGNATURE_UNAVAILABLE",
"file_wildfire_verdict": "BENIGN", "is_malicious": true, "is_manual": false, "is_process": false, "low_confidence":
```

false, "type": "HASH" }], "TOTAL_COUNT": 10 }, "file_artifacts": { "DATA": [{ "artifact_id": "A12345", "file_name": "test", "file_sha256": "1111", "file_signature_status": "SIGNATURE_UNAVAILABLE", "file_wildfire_verdict": "BENIGN", "is_malicious": true, "is_manual": false, "is_process": false, "low_confidence": false, "type": "HASH" }], "TOTAL_COUNT": 10 } }] } }

Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE
{ "error": "Invalid request data" }

Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE
{ "error": "Unauthorized request" }

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE
{ "error": "Internal server error" }

2.1.9.4 | Get War Room entries

post /public_api/v1/entries/get

Get the War Room entries for a specific case or alert. You can filter by timestamp, ID, and tags. You can also choose which type of entries you want to retrieve (notes, chat, attachments...). The response depends on what type of entry you choose to retrieve.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/entries/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"id\":\"string\",\"filter\": {\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\": [\"tags\"],\"tags\":[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/entries/get", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/entries/get") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"id\":\"string\",\"filter\": {\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\": [\"tags\"],\"tags\":[\"string\"]}}" response = http.request(request) puts response.read_body

```
const data = JSON.stringify({ "id": "string", "filter": { "firstID": "string", "lastID": "string", "pagesize": 0,
"fromTime": "string", "categories": [ "tags" ], "tags": [ "string" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/entries/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/entries/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"id\":\"string\",\"filter\":
{\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\":
[\"tags\"],\"tags\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "id": "string", "filter": [ "firstID": "string", "lastID":
"string", "pagesize": 0, "fromTime": "string", "categories": ["tags"], "tags": ["string"] ] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/entries/get")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/entries/get",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"id\":\"string\",\"filter\":
{\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\":
[\"tags\"],\"tags\":[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/entries/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"id\":\"string\",\"filter\":
{\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\":
[\"tags\"],\"tags\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/entries/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"id\":\"string\",\"filter\":
{\"firstID\":\"string\",\"lastID\":\"string\",\"pagesize\":0,\"fromTime\":\"string\",\"categories\":
[\"tags\"],\"tags\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ idstring

The ID of the case or alert you want to get the War Room entries of. For a case ID, prepend "CASE-" to the case ID. For example, if the case ID is 3, the value of `id` should be `CASE-3`. For alert IDs, just put the ID. For example, if the alert ID is 3, the value of `id` should be `3`.

▼ filterobject

▶ firstIDstring

Return results starting from the investigation ID in `firstID` until the last investigation ID.

▶ lastIDstring

Return results starting from the first investigation ID until the investigation ID in `lastID`.

▶ pagesizeinteger

Filter the results by the number of entries you want returned. `"pagesize": 0` returns all the results.

▶ fromTimestring

RFC3339 timestamp. Filter results from the time the entry is created until the latest entry.

▶ categoriesarray[string]

The categories you want to filter and the results you want to receive:

- `tags`: Tags added to the investigation.
- `chats`: Communication between team members in the form of chat messages.
- `notes`: Any entries marked as notes.
- `attachments`: Any files uploaded to the War Room in a playbook, script, or by the analyst.
- `incidentInfo`: The case history.
- `commandAndResults`: Command and return the result of the command.
- `playbookTaskResult`: Return the task result.
- `playbookTaskStartAndDone`: Task and return the task result.
- `playbookErrors`: When there are no playbook errors, the response returned is `0`.

▶ tagsarray[string]

If using the filter category of `tags`, include the tags you want to filter by.

REQUEST

```
{ "id": "example", "filter": { "firstID": "example", "lastID": "example", "pagesize": 0, "fromTime": "example",
"categories": [ "tags" ], "tags": [ "example" ] } }
```

Responses

OK

Body
application/json

▼ totalinteger
▼ dataarray
[
▶ idstring
▶ modifiedstring
▶ createdstring
▶ userstring
▶ parentContentstring
▶ contentsstring
▶ formatstring
▶ investigationIdstring
▶ categorystring
▶ isTodoboolean
▶ tagsarray[string]
]

RESPONSE Filter by entry tags

```
{ "total": 2, "data": [ { "id": "f1db36f0-d00f-4470-818f-c6911d392f76@INCIDENT-1", "modified": "2025-01-
02T10:17:57.738577545Z", "created": "2025-01-01T13:15:48.302901Z", "user": "", "parentContent": "!markAsNote
entryIDs=\"1\"", "contents": "done", "format": "text", "investigationId": "INCIDENT-1", "category": "artifact",
"isTodo": false, "tags": [ "john100" ] }, { "id": "0d6a01a4-58b5-4121-8db7-c371e38284db@INCIDENT-1", "modified":
"2025-01-02T10:22:26.6396269Z", "created": "2025-01-02T09:11:51.747644Z", "user": "", "contents": "'aaaaaa'",
"format": "text", "investigationId": "INCIDENT-1", "category": "artifact", "isTodo": false, "tags": [ "john200" ] } ]
}
{ "total": 2, "data": [ { "id": "39101423-126c-4438-80d0-6c19dcd20f2e@INCIDENT-1", "modified": "2024-12-
31T10:08:54.656397851Z", "created": "2024-12-31T10:08:54.656257Z", "user": "", "contents": "testing", "format":
"markdown", "investigationId": "INCIDENT-1", "category": "chat", "isTodo": false }, { "id": "dbef4f98-a115-46c1-8e7c-
b8e17ff98683@INCIDENT-1", "modified": "2025-01-02T09:52:06.239744361Z", "created": "2025-01-02T09:52:06.239717Z",
"user": "", "contents": "testing 2", "format": "markdown", "investigationId": "INCIDENT-1", "category": "chat",
"isTodo": false } ] }
{ "total": 2, "data": [ { "id": "8040c9b3-cbd7-4ac5-8178-46fb4f9e85cb@INCIDENT-2", "modified": "2025-01-
01T14:38:52.945021634Z", "created": "2025-01-01T14:38:52.945006Z", "user": "user@company.com", "contents": "very
important notes", "format": "markdown", "investigationId": "INCIDENT-2", "category": "chat", "note": true, "isTodo":
false }, { "id": "bb011b05-b9a4-45b1-8355-38d1673ea520@INCIDENT-2", "modified": "2025-01-01T14:39:08.577516148Z",
"created": "2025-01-01T14:39:08.5775Z", "user": "user@company.com", "contents": "even more important notes", "format":
"markdown", "investigationId": "INCIDENT-2", "category": "chat", "note": true, "isTodo": false } ] }
{ "total": 0, "data": [ { "id": "string", "modified": "string", "created": "string", "user": "string",
"parentContent": "string", "contents": "string", "format": "string", "investigationId": "string", "category":
"string", "isTodo": true, "tags": [ "string" ] } ] }
```

Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.9.5 | Add War Room entries

post /public_api/v1/entries/insert

Add an entry to the cases or alert War Room, including data. Note: This endpoint only adds entries to existing War Rooms; it does not create them. Ensure that the War Room already exists before making this request.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/entries/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"id\":\"string\",\"data\":\"string\"}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/entries/insert",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/entries/insert") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"id\":\"string\",\"data\":\"string\"}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "id": "string", "data": "string" }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/entries/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/entries/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"id\":\"string\",\"data\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "id": "string", "data": "string" ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/entries/insert")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/entries/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"id\":\"string\",\"data\":\"string\"}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/entries/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"id\":\"string\",\"data\":\"string\"}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/entries/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"id\":\"string\",\"data\":\"string\"}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ idstring

The ID of the case or issue for which you want to add a War Room entry. For a case ID, prepend "CASE-" to the case ID. For example, if the case ID is 3, the value of `id` should be `CASE-3`. For alert IDs, just put the ID. For example, if the alert ID is 3, the value of `id` should be `3`.

▼ datastring

The data you want to add or the command you want to run in the War Room.

REQUEST Insert command to alert War Room

```
{ "id": "1", "data": "!Print value=1000" }
{ "id": "CASE-1", "data": "!Print value=1" }
```

Responses

OK

Body

application/json

▼ idstring
▼ versioninteger
▼ cacheVersninteger
▼ modifiedstring
▼ sizeInBytesinteger
▼ typeinteger
▼ createdstring
▼ incidentCreationTimestring
▼ investigationCreationTimestring
▼ retryTimestring
▼ userstring
▼ errorSourcestring
▼ contentsstring
▼ formatstring
▼ investigationIdstring
▼ filestring
▼ fileIDstring
▼ parentIdstring
▼ pinnedboolean
▼ fileMetadataobject

▼ parentContentobject
▼ parentEntryTruncatedboolean
▼ systemstring
▼ reputationsobject
▼ categorystring
▼ noteboolean
▼ isTodoboolean
▼ tagsstring
▼ tagsRawstring
▼ startDatestring
▼ timesinteger
▼ recurrentboolean
▼ endingDatestring
▼ timezoneOffsetinteger
▼ cronViewboolean
▼ scheduledboolean
▼ scheduledEntryGuidstring
▼ entryTaskobject
▼ taskIdstring
▼ playbookIdstring
▼ reputationSizeinteger
▼ contentsSizeinteger
▼ brandstring
▼ InstanceIDstring
▼ IndicatorTimelineinteger
▼ Relationshipsstring
▼ mirroredboolean

RESPONSE

Example 1


```
{ "id": "b30fadee-53e3-4859-8c79-fa328ba7b4fd@1", "version": 1, "cacheVersn": 0, "modified": "2025-01-
29T13:48:41.591466357Z", "sizeInBytes": 0, "type": 1, "created": "2025-01-29T13:48:41.591444333Z",
"incidentCreationTime": "2025-01-29T13:48:41.591444333Z", "investigationCreationTime": "2024-12-25T14:43:07.697Z",
"retryTime": "0001-01-01T00:00:00Z", "user": "", "errorSource": "", "contents": "!Print value=1", "format": "text",
"investigationId": "1", "file": "", "fileID": "", "parentId": "", "pinned": false, "fileMetadata": null,
"parentContent": null, "parentEntryTruncated": false, "system": "", "reputations": null, "category": "chat", "note":
false, "isTodo": false, "tags": null, "tagsRaw": null, "startDate": "0001-01-01T00:00:00Z", "times": 0, "recurrent":
false, "endingDate": "0001-01-01T00:00:00Z", "timezoneOffset": 0, "cronView": false, "scheduled": false,
"scheduledEntryGuid": "", "entryTask": null, "taskId": "", "playbookId": "", "reputationSize": 0, "contentsSize": 14,
"brand": "none", "InstanceID": "", "IndicatorTimeline": null, "Relationships": null, "mirrored": false }
```


Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.10 | Correlation Rules

APIs for managing Correlation Rules

2.1.10.1 | Get Correlation Rules

post /public_api/v1/correlations/get

Return a list of correlation rules. You can return all correlation rules or filter results. You can also return extended results with all details included.

- The response is concatenated using AND condition (OR is not supported).
- The maximum result set size is >100.
- Offset is the zero-based number of incidents from the start of the result set.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/correlations/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/correlations/get", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/correlations/get")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "extended_view": true, "filters": [ { "field": "name", "operator":
"EQ", "value": "string" } ], "search_from": 0, "search_to": 0 } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/correlations/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/correlations/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "extended_view": true, "filters": [ [
"field": "name", "operator": "EQ", "value": "string" ] ], "search_from": 0, "search_to": 0 ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/correlations/get")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
```

```
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/correlations/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/correlations/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/correlations/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ extended_viewboolean

▶ filtersarray

An array of filter fields.

▶ search_frominteger

Integer representing the starting offset within the query result set from which you want correlation rules returned. Correlation rules are returned as a zero-based list. Any correlation rule indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

Integer representing the end offset within the result set after which you do not want BIOCs returned. BIOCs in the BIOC list that are indexed higher than this value are not returned in the final results set. Defaults to >100, which returns all BIOCs to the end of the list.

REQUEST

Example 1

```
{ "request_data": { "extended_view": false } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsarray

[

▶ idinteger

▶ namestring

▶ severitystring

▶ xql_querystring

▶ is_enabledstring

▶ descriptionstring

▶ alert_namestring

▶ alert_categorystring

▶ alert_fieldsobject

▶ execution_modestring

▶ search_windowstring

▶ simple_schedulestring

▶ timezonestring

▶ crontabstring

▶ suppression_enabledboolean

▶ suppression_fieldsarray[string]

▶ datasetstring
▶ mitre_defsobject
▶ drilldown_query_timeframestring
▶ mapping_strategystring
]
▼ objects_typestring
RESPONSE
Example 1
{ "objects_count": 2, "objects": [{ "id": 1, "name": "Test", "severity": "SEV_040_HIGH", "xql_query": "dataset = xdr_data | filter event_type = 1", "is_enabled": "DISABLED", "description": "", "alert_name": "Test", "alert_category": "User Defined", "alert_description": null, "alert_fields": { "agent_hostname": null, "action_local_ip": null, "action_remote_ip": null, "action_remote_port": null, "agent_device_domain": null, "actor_effective_username": null, "actor_process_image_name": null, "actor_process_image_path": null, "actor_process_command_line": null, "actor_process_image_sha256": null }, "execution_mode": "SCHEDULED", "search_window": "10 minutes", "simple_schedule": "10 minutes", "timezone": "Asia/Jerusalem", "crontab": "*/10 * * * *", "suppression_enabled": false, "suppression_duration": null, "suppression_fields": null, "dataset": "alerts", "user_defined_severity": null, "user_defined_category": "event_type", "mitre_defs": {}, "investigation_query_link": null, "drilldown_query_timeframe": "ALERT", "mapping_strategy": "AUTO" }, { "id": 28, "name": "AnotherTest", "severity": "SEV_030_MEDIUM", "xql_query": "dataset = xdr_data | fields event_type, action_process_username, uuid, action_boot_time | comp values(*) as * by action_process_username\n", "is_enabled": "ENABLED", "description": "Some description", "alert_name": "Test Alert", "alert_category": "DISCOVERY", "alert_description": "Test", "alert_fields": {}, "execution_mode": "SCHEDULED", "search_window": "1 hours", "simple_schedule": "10 minutes", "timezone": "Asia/Jerusalem", "crontab": "*/10 * * * *", "suppression_enabled": true, "suppression_duration": "1 hours", "suppression_fields": ["event_type"], "dataset": "alerts", "user_defined_severity": null, "user_defined_category": null, "mitre_defs": { "TA0005 - Defense Evasion": ["T1014 - Rootkit"] }, "investigation_query_link": "dataset = xdr_data | fields event_type, action_process_username, uuid, action_boot_time | comp values(*) as * by action_process_username", "drilldown_query_timeframe": "ALERT", "mapping_strategy": "CUSTOM" }], "objects_type": "correlations" }

Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.10.2 | Insert or update Correlation Rules

post /public_api/v1/correlations/insert

Insert new Correlation Rules or update existing Correlation Rules.

Note: The Correlation Rule `id` is tenant specific and can't be used across tenants. Inserting Correlation Rules with the same `id` as an existing Correlation Rule on that tenant will overwrite the existing Correlation Rule.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/correlations/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/correlations/insert", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/correlations/insert")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": [ { "rule_id": 0, "name": "string", "severity": "SEV_010_INFO",
"xql_query": "string", "is_enabled": true, "description": "string", "alert_name": "string", "alert_category": "OTHER",
"alert_description": "string", "alert_fields": { "property1": null, "property2": null }, "execution_mode":
"SCHEDULED", "search_window": "\"2 hours\"", "simple_schedule": "\"5 minutes\"", "timezone": "\"Asia/Jerusalem\"",
"crontab": "\"*/10 * * * *\"", "suppression_enabled": true, "suppression_duration": "\"1 hours\"",
"suppression_fields": [ "\"event_type\"" ], "dataset": "string", "user_defined_severity": "string",
"user_defined_category": "string", "mitre_defs": { "property1": null, "property2": null }, "investigation_query_link":
"string", "drilldown_query_timeframe": "QUERY", "mapping_strategy": "AUTO" } ] }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/correlations/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/correlations/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
```

```
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ [ "rule_id": 0, "name": "string", "severity":
"SEV_010_INFO", "xql_query": "string", "is_enabled": true, "description": "string", "alert_name": "string",
"alert_category": "OTHER", "alert_description": "string", "alert_fields": [ "property1": , "property2": ],
"execution_mode": "SCHEDULED", "search_window": "\"2 hours\"", "simple_schedule": "\"5 minutes\"", "timezone":
"\"Asia/Jerusalem\"", "crontab": "\"*/10 * * * *\"", "suppression_enabled": true, "suppression_duration": "\"1
hours\"", "suppression_fields": ["\"event_type\""], "dataset": "string", "user_defined_severity": "string",
"user_defined_category": "string", "mitre_defs": [ "property1": , "property2": ], "investigation_query_link":
"string", "drilldown_query_timeframe": "QUERY", "mapping_strategy": "AUTO" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/correlations/insert")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/correlations/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/correlations/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/correlations/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
[{\"rule_id\":0,\"name\":\"string\",\"severity\":\"SEV_010_INFO\",\"xql_query\":\"string\",\"is_enabled\":true,\"description\":
{\"property1\":null,\"property2\":null},\"execution_mode\":\"SCHEDULED\",\"search_window\":\"\\\"2
hours\\\"\",\"simple_schedule\":\"\\\"5 minutes\\\"\",\"timezone\":\"\\\"Asia/Jerusalem\\\"\",\"crontab\":\"\\\"*/10 *
* * *\\\"\",\"suppression_enabled\":true,\"suppression_duration\":\"\\\"1 hours\\\"\",\"suppression_fields\":
[\"\\\"event_type\\\"\"],\"dataset\":\"string\",\"user_defined_severity\":\"string\",\"user_defined_category\":\"string\",\"mit
{\"property1\":null,\"property2\":null},\"investigation_query_link\":\"string\",\"drilldown_query_timeframe\":\"QUERY\",\"mappi
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```


Body parameters

application/json

▼ request_dataarrayrequired

[

▶ rule_idinteger

▶ namestring

Correlation rule name.

▶ severityobject (Enum)

Correlation rule severity.

▶ xql_querystring

Correlation rule XQL query.

▶ is_enabledboolean

Whether the correlation rule is enabled or disabled.

▶ descriptionstring

Correlation rule description.

▶ alert_namestring

Alert name.

▶ alert_categoryobject (Enum)

Alert category.

▶ alert_descriptionstring

Alert description.

▶ alert_fieldsobject

Alert fields.

▶ execution_modeobject (Enum)

Correlation rule execution mode.

▶ search_windowstring

Search window.

▶ simple_schedulestring

Correlation rule simple schedule.

▶ timezonestring

Correlation rule timezone.

▶ crontabstring

Linux scheduling for correlation rule.

▶ suppression_enabledboolean
▶ suppression_durationstring
▶ suppression_fieldsarray[string]
▶ datasetstring
▶ user_defined_severitystring
▶ user_defined_categorystring
▶ mitre_defsobject
▶ investigation_query_linkstring
▶ drilldown_query_timeframeobject (Enum)
▶ mapping_strategyobject (Enum)

]

REQUEST

Example 1


```
{ "request_data": [ { "rule_id": 28, "name": "Test", "severity": "SEV_030_MEDIUM", "xql_query": "dataset = xdr_data | fields event_type, action_process_username, uuid, action_boot_time | comp values(*) as * by action_process_username\n", "is_enabled": "true", "description": "RTESRTESTestret", "alert_name": "Test", "alert_category": "DISCOVERY", "alert_description": "Test", "alert_fields": {}, "execution_mode": "REAL_TIME", "search_window": "1 hours", "simple_schedule": "10 minutes", "timezone": "Asia/Jerusalem", "crontab": "*/10 * * * *", "suppression_enabled": true, "suppression_duration": "1 hours", "suppression_fields": [ "event_type" ], "dataset": "alerts", "user_defined_severity": null, "user_defined_category": null, "mitre_defs": { "TA0005 - Defense Evasion": [ "T1014 - Rootkit" ] }, "investigation_query_link": "dataset = xdr_data | fields event_type, action_process_username, uuid, action_boot_time | comp values(*) as * by action_process_username", "drilldown_query_timeframe": "ALERT", "mapping_strategy": "AUTO" } ] }
```


Responses

OK

Body

application/json
▼ added_objectsarray

List of Correlation Rule objects added.

[
▶ idinteger
▶ statusstring
]
▼ updated_objectsarray

List of Correlation Rule objects updated.

[
▶ idinteger
▶ statusstring
]
▼ errorsarray[string]

List of error messages, if there are any.

RESPONSE
Example 1

```
{ "added_objects": [], "updated_objects": [ { "id": 28 }, { "status": "Updated the correlation rule with the ID: 28 successfully" } ], "errors": [] }
```


Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.10.3 | Delete Correlation Rules

post /public_api/v1/correlations/delete

Delete correlation rules selected by filter.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/correlations/delete'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/correlations/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/correlations/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" response = http.request(request) puts
response.read_body
```

```
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "EQ", "value": "string" }
] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/correlations/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/correlations/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"EQ", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/correlations/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/correlations/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/correlations/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/correlations/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"EQ\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobjectrequired
▶ filtersarray

An array of filter fields.

REQUEST
Example 1

```
{ "request_data": { "extended_view": false, "filters": [ { "field": "rule_id", "operator": "EQ", "value": 28 } ] } }
```

Responses

OK

Body
application/json
▼ objects_countinteger
▼ objectsarray[integer]
RESPONSE
Example 1

```
{ "objects_count": 1, "objects": [ 28 ] }
```


Bad Request. Got invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.11 | Cortex CLI

APIs for managing the Cortex CLI

2.1.11.1 | Get the latest version of the Cortex CLI

get /public_api/v1/cli/releases/version

Get the latest version of Cortex CLI

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/cli/releases/version'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET", "/public_api/v1/cli/releases/version",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cli/releases/version") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/cli/releases/version");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/cli/releases/version")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/cli/releases/version")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cli/releases/version", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cli/releases/version"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cli/releases/version"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Success

Body

application/json

▼ versionstringrequired

Cortex CLI version

Example:`"v1.2.3"`

RESPONSE

```
{ "version": "v1.2.3" }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Service had unexpected internal error

2.1.12 | Dashboards

APIs for managing Dashboards

2.1.12.1 | Get dashboards

post /public_api/v1/dashboards/get

Get dashboard details by filtering based on the dashboard name, dashboard ID, time the dashboard was generated, or dashboard source.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dashboards/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/dashboards/get", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/dashboards/get") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "dashboard_id", "operator": "EQ", "value":
"string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/dashboards/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dashboards/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "dashboard_id",
"operator": "EQ", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/dashboards/get")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/dashboards/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
```

```
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/dashboards/get"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/dashboards/get"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "name", "value": "Incident by Severity", "operator": "EQ" }, { "field": "source", "value": "John Doe", "operator": "EQ" } ] } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsarray

[

▶ dashboards_dataarray

▶ widgets_dataarray

]

▼ objects_typestring

RESPONSE

Example 1


```
{ "objects_count": 2, "objects": [ { "dashboards_data": [ { "name": "John Doe", "description": null, "status": "ENABLED", "layout": [ { "id": "row-9847", "data": [ { "key": "FAKE_KEY", "data": { "type": "Pie", "width": 5435435, "height": 451 } }, { "key": "incidentsByAssignment", "data": { "type": "Bar", "width": 33.333333333333336, "height": 451 } }, { "key": "incidentsHistory", "data": { "type": "Timeline", "width": 33.333333333333336, "height": 451, "time_frame": { "relativeTime": 86400000 }, "alerts_or_incidents": "incident" } } ] }, { "id": "row-2618", "data": [ { "key": "xql_1683289526210", "data": { "type": "Custom XQL", "width": 33.333333333333336, "height": 11111, "params": [ { "name": "name", "value": "orik" } ], "phrase": "dataset = drilldown | filter name = $name\n| view graph type = gauge subtype = radial header = \"User Score\" yaxis = score maxscalerange = 100 headerfontsize = 25 ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "gauge", "commands": [ { "command": { "op": "=", "name": "subtype", "value": "radial" } }, { "command": { "op": "=", "name": "header", "value": "\"User Score\"" } }, { "command": { "op": "=", "name": "yaxis", "value": "score" } }, { "command": { "op": "=", "name": "maxscalerange", "value": "100" } }, { "command": { "op": "=", "name": "headerfontsize", "value": "25" } } ] } } }, { "key": "topIncidentsByAlertSeverity", "data": { "type": "Table", "width": 33.333333333333336, "height": 408 } }, { "key": "hostsBySeverity", "data": { "type": "Table", "width": 33.333333333333336, "height": 408 } } ] } ], "default_dashboard_id": 132131, "global_id": "47052a2b17db4d799c4c5da38d203600", "metadata": { "params": [] } } ], "widgets_data": [ { "widget_key": "xql_1683289526210", "title": "Drilldown | User Score", "creation_time": 1687877496472, "description": "", "data": { "params": [ { "name": "name", "value": "orik" } ], "phrase": "dataset = drilldown | filter name = $name\n| view graph type = gauge subtype = radial header = \"User Score\" yaxis = score maxscalerange = 100 headerfontsize = 25 ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "gauge", "commands": [ { "command": { "op": "=", "name": "subtype", "value": "radial" } }, { "command": { "op": "=", "name": "header", "value": "\"User Score\"" } }, { "command": { "op": "=", "name": "yaxis", "value": "score" } }, { "command": { "op": "=", "name": "maxscalerange", "value": "100" } }, { "command": { "op": "=", "name": "headerfontsize", "value": "25" } } ] } }, "support_time_range": true, "additional_info": { "query_tables": [ "drilldown" ], "query_uses_library": false }, "creator_mail": "user@company.com" } ] }, { "dashboards_data": [ { "name": "John Doe", "description": null, "status": "ENABLED", "layout": [ { "id": "row-9847", "data": [ { "key": "FAKE_KEY", "data": { "type": "Pie", "width": 5435435, "height": 451 } }, { "key": "incidentsByAssignment", "data": { "type": "Bar", "width": 33.333333333333336, "height": 451 } }, { "key": "incidentsHistory", "data": { "type": "Timeline", "width": 33.333333333333336, "height": 451, "time_frame": { "relativeTime": 86400000 }, "alerts_or_incidents": "incident" } } ] }, { "id": "row-2618", "data": [ { "key": "xql_1683289526210", "data": {
```

"type": "Custom XQL", "width": 33.333333333333336, "height": 11111, "params": [{ "name": "name", "value": "orik" }], "phrase": "dataset = drilldown | filter name = $name\n| view graph type = gauge subtype = radial header = \"User Score\" yaxis = score maxscalerange = 100 headerfontsize = 25 ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "gauge", "commands": [{ "command": { "op": "=", "name": "subtype", "value": "radial" } }, { "command": { "op": "=", "name": "header", "value": "\"User Score\"" } }, { "command": { "op": "=", "name": "yaxis", "value": "score" } }, { "command": { "op": "=", "name": "maxscalerange", "value": "100" } }, { "command": { "op": "=", "name": "headerfontsize", "value": "25" } }] } } }, { "key": "topIncidentsByAlertSeverity", "data": { "type": "Table", "width": 33.333333333333336, "height": 408 } }, { "key": "hostsBySeverity", "data": { "type": "Table", "width": 33.333333333333336, "height": 408 } }] }], "default_dashboard_id": 132131, "global_id": "27f78777b427452eb54974d3c14bf67a", "metadata": { "params": [] } }], "widgets_data": [{ "widget_key": "xql_1683289526210", "title": "Drilldown | User Score", "creation_time": 1687877496472, "description": "", "data": { "params": [{ "name": "name", "value": "orik" }], "phrase": "dataset = drilldown | filter name = $name\n| view graph type = gauge subtype = radial header = \"User Score\" yaxis = score maxscalerange = 100 headerfontsize = 25 ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "gauge", "commands": [{ "command": { "op": "=", "name": "subtype", "value": "radial" } }, { "command": { "op": "=", "name": "header", "value": "\"User Score\"" } }, { "command": { "op": "=", "name": "yaxis", "value": "score" } }, { "command": { "op": "=", "name": "maxscalerange", "value": "100" } }, { "command": { "op": "=", "name": "headerfontsize", "value": "25" } }] } }, "support_time_range": true, "additional_info": { "query_tables": ["drilldown"], "query_uses_library": false }, "creator_mail": "user@company.com" }] }], "objects_type": "dashboards" }

Invalid field or operator.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.12.2 | Insert or update dashboards

post /public_api/v1/dashboards/insert

Add or update the dashboards retrieved by the Get dashboards API.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dashboards/insert'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dashboards_data\":[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":
[{\"id\":\"string\",\"data\":[{\"key\":\"string\",\"data\":
{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/dashboards/insert", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/dashboards/insert")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"dashboards_data\":
[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":[{\"id\":\"string\",\"data\":
[{\"key\":\"string\",\"data\":{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "dashboards_data": [ { "name": "string", "description": "string",
"status": "string", "layout": [ { "id": "string", "data": [ { "key": "string", "data": { "type": "string", "width": 0,
"height": 0, "time_frame": { "relativeTime": 0 }, "alerts_or_incidents": "string" } } ] } ], "default_dashboard_id":
0, "global_id": "string", "metadata": { "params": [ {} ] } } ], "widgets_data": [ { "widget_key": "string", "title":
"string", "creation_time": 0, "description": "string", "data": { "phrase": "string", "time_frame": { "relativeTime": 0
}, "viewOptions": { "type": "string", "commands": [ {} ] } }, "support_time_range": true, "additional_info": {
"query_tables": [ "string" ], "query_uses_library": true }, "creator_mail": "string" } ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/dashboards/insert"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dashboards/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"dashboards_data\":
[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":[{\"id\":\"string\",\"data\":
[{\"key\":\"string\",\"data\":{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dashboards_data": [ [ "name": "string",
"description": "string", "status": "string", "layout": [ [ "id": "string", "data": [ [ "key": "string", "data": [
"type": "string", "width": 0, "height": 0, "time_frame": ["relativeTime": 0], "alerts_or_incidents": "string" ] ] ] ]
], "default_dashboard_id": 0, "global_id": "string", "metadata": ["params": [[]]] ] ], "widgets_data": [ [
"widget_key": "string", "title": "string", "creation_time": 0, "description": "string", "data": [ "phrase": "string",
"time_frame": ["relativeTime": 0], "viewOptions": [ "type": "string", "commands": [[]] ] ], "support_time_range":
true, "additional_info": [ "query_tables": ["string"], "query_uses_library": true ], "creator_mail": "string" ] ] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/dashboards/insert")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/dashboards/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
```

```
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"dashboards_data\":
[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":[{\"id\":\"string\",\"data\":
[{\"key\":\"string\",\"data\":{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/dashboards/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"dashboards_data\":
[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":[{\"id\":\"string\",\"data\":
[{\"key\":\"string\",\"data\":{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/dashboards/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dashboards_data\":
[{\"name\":\"string\",\"description\":\"string\",\"status\":\"string\",\"layout\":[{\"id\":\"string\",\"data\":
[{\"key\":\"string\",\"data\":{\"type\":\"string\",\"width\":0,\"height\":0,\"time_frame\":
{\"relativeTime\":0},\"alerts_or_incidents\":\"string\"}}]}],\"default_dashboard_id\":0,\"global_id\":\"string\",\"metadata\":
{\"params\":[{}]}}],\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ dashboards_dataarray

An array of dashboard details as retrieved by the Get dashboards API.

▶ widgets_dataarray

An array of relevant XQL widget details as retrieved by the Get dashboards API.

REQUEST

Example 1


```
{ "request_data": { "dashboards_data": [ { "name": "John Doe", "description": null, "status": "ENABLED", "layout": [ {
"id": "row-5867", "data": [ { "key": "FAKE_KEY", "data": { "type": "Pie", "width": 5435435, "height": 451 } }, {
"key": "incidentsByAssignment", "data": { "type": "Bar", "width": 33, "height": 451 } }, { "key": "incidentsHistory",
"data": { "type": "Timeline", "width": 33, "height": 451, "time_frame": { "relativeTime": 86400000 },
"alerts_or_incidents": "incident" } } ] }, { "id": "row-3678", "data": [ { "key": "xql_1583269521210", "data": {
"type": "Custom XQL", "width": 33, "height": 11111, "params": [ { "name": "name", "value": "orik" } ], "phrase":
"dataset = drilldown | filter name = $name\n| view graph type = gauge subtype = radial header = \"User Score\" yaxis =
score maxscalerange = 100 headerfontsize = 25 ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type":
"gauge", "commands": [ { "command": { "op": "=", "name": "subtype", "value": "radial" } }, { "command": { "op": "=",
"name": "header", "value": "\"User Score\"" } }, { "command": { "op": "=", "name": "yaxis", "value": "score" } }, {
"command": { "op": "=", "name": "maxscalerange", "value": "100" } }, { "command": { "op": "=", "name":
"headerfontsize", "value": "25" } } ] } } }, { "key": "topIncidentsByAlertSeverity", "data": { "type": "Table",
"width": 33, "height": 408 } }, { "key": "hostsBySeverity", "data": { "type": "Table", "width": 33, "height": 408 } }
] } ], "default_dashboard_id": 132131, "global_id": "47052a2b17db4d799c4c5da38d203600", "metadata": { "params": [] } }
] } }
```

Responses

OK

Body
application/json
▼ added_objectsarray

Array listing the the global ID and internal ID of the objects added.

[
▶ global_idstring
▶ internal_idinteger
]
▼ updated_objectsarray

Array listing the the global ID and internal ID of the objects updated.

[
▶ global_idstring
▶ internal_idinteger
]
▼ errorsarray

List of errors including the global ID and the error message.

[
▶ global_idstring
▶ errorstring
]
RESPONSE
Example 1

```
{ "added_objects": [ { "global_id": "47052a2b47db4d899c4c5da32d203700", "internal_id": 37 } ], "updated_objects": [ { "global_id": "27f78778b427452ed54974d6c14cf67a", "internal_id": 44 } ], "errors": [ { "global_id": "a62ed1dag81741fc948720e2a1be2801", "error": "This is the reason for the failure." } ] }
```

2.1.12.3 | Delete dashboards

post /public_api/v1/dashboards/delete

Delete the dashboards retrieved by the Get dashboards API.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dashboards/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/dashboards/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/dashboards/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "dashboard_id", "operator": "EQ", "value": "string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/dashboards/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dashboards/delete") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "dashboard_id", "operator": "EQ", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/dashboards/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/dashboards/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/dashboards/delete"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/dashboards/delete"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"dashboard_id\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "dashboard_id", "value": 132131, "operator": "EQ" } ] } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsobject

▶ succeeded_itemsarray

List of the global ID and internal ID of dashboards successfully deleted.

▶ failures_itemsarray

List of global IDs and internal IDs that were not deleted and the error messages explaining why.

RESPONSE

Example 1

{ "objects_count": 3, "objects": { "succeeded_items": [{ "global_id": "47052a2b17db4e799c4c5db38d603600", "internal_id": 27 }, { "global_id": "a62ab1daf82741fc948760e2e1be2401", "internal_id": 31 }], "failures_items": [{ "global_id": "25f78778b427452ec54974d3c14bf67a", "internal_id": 55, "error": "Dashboard is not allowed to be deleted." }] } }

Invalid field or operator.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.13 | Dataset Management

APIs for managing datasets

2.1.13.1 | Add Dataset

post /public_api/v1/xql/add_dataset

Add a dataset of type `lookup` with the specified name and schema.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/add_dataset'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\":
{\"property1\":\"text\",\"property2\":\"text\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/xql/add_dataset",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/xql/add_dataset")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\":
{\"property1\":\"text\",\"property2\":\"text\"}}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "dataset_type": "string", "dataset_schema": { "property1": "text", "property2": "text" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/add_dataset"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/add_dataset") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\": {\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\": {\"property1\":\"text\",\"property2\":\"text\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string", "dataset_type": "string", "dataset_schema": [ "property1": "text", "property2": "text" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/xql/add_dataset")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/xql/add_dataset", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\": {\"property1\":\"text\",\"property2\":\"text\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/xql/add_dataset"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\": {\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\": {\"property1\":\"text\",\"property2\":\"text\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/add_dataset"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"dataset_name\":\"string\",\"dataset_type\":\"string\",\"dataset_schema\": {\"property1\":\"text\",\"property2\":\"text\"}}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ dataset_namestringrequired

The designated name of the dataset.

▶ dataset_typestringrequired

Dataset type. Currently only `lookup` is supported.

▶ dataset_schemaobjectrequired

The schema of the dataset in a comma-separated list of JSON pairs where the key is the field name and the value is the field type.

REQUEST

Example 1

```
{ "request_data": { "dataset_name": "users", "dataset_schema": { "uid": "text", "username": "text", "zipcode": "number", "salary": "number", "is_admin": "bool", "birthday": "datetime" }, "dataset_type": "lookup" } }
```

Responses

OK

Body

application/json

▼ dataset_namestring

Name of the dataset added.

RESPONSE

```
{ "dataset_name": "example" }
```

2.1.13.2 | Delete a dataset

post /public_api/v2/xql/delete_dataset

Delete a dataset with the specified name. The following dataset types can be deleted: Lookup, Raw, User, Snapshot, and Correlation. You can only delete a dataset with dependencies by setting `force` to TRUE.

Note: The System dataset and other protected datasets cannot be deleted.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v2/xql/delete_dataset'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dataset_name\":\"string\",\"force\":true}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v2/xql/delete_dataset",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v2/xql/delete_dataset")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"dataset_name\":\"string\",\"force\":true}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "force": true } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v2/xql/delete_dataset"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v2/xql/delete_dataset")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"dataset_name\":\"string\",\"force\":true}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string", "force": true ]] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v2/xql/delete_dataset")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v2/xql/delete_dataset", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"dataset_name\":\"string\",\"force\":true}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v2/xql/delete_dataset"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
```

```
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"dataset_name\":\"string\",\"force\":true}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v2/xql/delete_dataset"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dataset_name\":\"string\",\"force\":true}}", ParameterType.RequestBody); IRestResponse response
= client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ dataset_namestringrequired

The name of the dataset to be deleted.

▶ forceboolean

Warning: Setting this to `True` forces deletion even when there are dependencies.

REQUEST

Example 1

```
{ "request_data": { "dataset_name": "users", "force": "yes" } }
```

Responses

OK

2.1.13.3 | Get all datasets

post /public_api/v1/xql/get_datasets

Retrieve a list of all the datasets and their properties.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/get_datasets'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/xql/get_datasets", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/xql/get_datasets")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/get_datasets");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/get_datasets")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/xql/get_datasets")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/xql/get_datasets", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/xql/get_datasets"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/get_datasets"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

REQUEST

```
{ "request_data": {} }
```

Responses

OK

Body

application/json

▼ replyarray

[

▶ dataset_namestring

Dataset name.

▶ typestring

Dataset type. Can be one of the following: `System`, `Lookup`, `Raw`, `User`, `Snapshot`, `Correlation`, `System Audit`.

▶ log_update_typestring

Log update type. Can be one of the following: `Logs` (event logs are updated continuously), `State` (the current state is updated periodically).

▶ last_updatedinteger

Integer in timestamp epoch milliseconds. When the data in the dataset was last updated.

▶ total_days_storedinteger

Number of dats the data is stored in the tenant, which is comprised of `hot_range` + `cold_range`.

▶ hot_rangeobject

The time period of the hot storage from the start date to the end date.

▶ cold_rangeobject

The time period of the cold storage from the start date to the end date.

▶ total_size_storedinteger

Actual size of the data (in bytes) that is stored in the tenant. This number is dependent on the events stored in the hot storage. For the xdr_data dataset, where the first 31 days of storage are included with your license, the first 31 days are not included in the the `total_size_stored` number.

▶ average_daily_sizeinteger

Average daily amount stored (in bytes) in the tenant. This number is dependent on the events stored in the hot storage.

▶ total_eventsinteger

Number of total events/logs that are stored in the tenant. This number is dependent on the events stored in the hot storage.

▶ average_event_sizeinteger

Average size (in bytes) of a single event in the dataset (`total_size_stored` divided by the `total_events`). This number is dependent on the events stored in the hot storage.

▶ ttlinteger

Time to live. Defines when lookup entries expire and are removed automatically from the lookup dataset.

▶ default_query_targetboolean

whether the dataset is configured to use as your default query target in XQL Search, so when you write your queries you do not need to define a dataset. Can be one of the following: `True`, `False`.

]
RESPONSE
Example 1

```
{ "reply": [ { "Dataset Name": "xdr_data", "Type": "SYSTEM", "Log Update Type": "LOGS", "Last Updated": null, "Total Days Stored": null, "Hot Range": { "from": 1715299200000, "to": 1716595200000 }, "Cold Range": {}, "Total Size Stored": null, "Average Daily Size": null, "Total Events": null, "Average Event Size": null, "TTL": null, "Default Query Target": "FALSE" }, { "Dataset Name": "host_inventory", "Type": "SYSTEM", "Log Update Type": "LOGS", "Last Updated": null, "Total Days Stored": null, "Hot Range": {}, "Cold Range": {}, "Total Size Stored": null, "Average Daily Size": null, "Total Events": null, "Average Event Size": null, "TTL": null, "Default Query Target": "FALSE" }, { "Dataset Name": "host_users_to_groups", "Type": "SYSTEM", "Log Update Type": "LOGS", "Last Updated": null, "Total Days Stored": null, "Hot Range": {}, "Cold Range": {}, "Total Size Stored": null, "Average Daily Size": null, "Total Events": null, "Average Event Size": null, "TTL": null, "Default Query Target": "FALSE" } ] }
```

2.1.14 | Endpoint Management

APIs for managing endpoints

2.1.14.1 | Get Distribution version

post /public_api/v1/distributions/get_versions

Get a list of all the agent versions to use for creating a distribution list.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/distributions/get_versions'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/distributions/get_versions", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/distributions/get_versions") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/distributions/get_versions"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/distributions/get_versions")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/distributions/get_versions")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/distributions/get_versions", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/distributions/get_versions"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/distributions/get_versions"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
Object
application/json
REQUEST

```
{}
```

Responses

Successful response

Body
application/json
▼ replyobject
▶ windowsarray[string]

List of Windows agent versions.

▶ linuxarray[string]

List of Linux agent versions.

▶ macosarray[string]

List of Mac agent versions.

RESPONSE

```
{ "reply": { "windows": [ "example" ], "linux": [ "example" ], "macos": [ "example" ] } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.14.2 | Get all Endpoints

post /public_api/v1/endpoints/get_endpoints

Gets a list of all of your endpoints. The response is concatenated using AND condition (OR is not supported).

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/get_endpoints'
-d ''
```
```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/get_endpoints", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```
```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/get_endpoints") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{}" response = http.request(request) puts response.read_body
```
```
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/get_endpoints");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```
```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/get_endpoints")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/endpoints/get_endpoints")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/get_endpoints", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/get_endpoints"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/get_endpoints"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

```
{}
```

Responses

Successful response

Body

application/json

▼ replyarray

[

▶ agent_idstring

▶ agent_statusstring

▶ operational_statusstring

▶ host_namestring

▶ agent_typestring

▶ iparray[string]

▶ last_seeninteger

▶ tagsobject

▶ usersarray[string]

]

RESPONSE

example-1

```
{ "reply": [ { "agent_id": "<agent_id>", "agent_status": "DISCONNECTED", "operational_status": "PROTECTED",
"host_name": "<hostname>", "agent_type": "Workstation", "ip": [ "<ip_address>" ], "last_seen": 1678012587521, "tags":
{ "server_tags": [], "endpoint_tags": [] }, "users": [ "user" ] } ] }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.3 | Get Policy

post /public_api/v1/endpoints/get_policy

Get the policy name for a specific endpoint.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/get_policy'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"endpoint_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/endpoints/get_policy", payload, headers) res
= conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/get_policy") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"endpoint_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "endpoint_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/get_policy");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/get_policy")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"endpoint_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["endpoint_id": "string"]] as [String : Any]
let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/get_policy")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
```

```
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/endpoints/get_policy", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"endpoint_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/endpoints/get_policy"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\": {\"endpoint_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/get_policy"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"endpoint_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ endpoint_idstringrequired

Endpoint ID.

REQUEST

example-1

```
{ "request_data": { "endpoint_id": "<endpoint ID>" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ policy_namestring

Name of the policy allocated with the endpoint.

RESPONSE

example-1

```
{ "reply": { "policy_name": "Windows Default" } }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.4 | Delete Endpoints

post /public_api/v1/endpoints/delete

Delete selected endpoints in Cortex Cloud. You can delete up to 1000 endpoints.

Note: Endpoints are deleted from Cortex Cloud UI, however they still exist in the database.

When filtering by multiple fields:

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 1000.
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"in\",\"value\":[\"string\"]}]}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"in\",\"value\":[\"string\"]}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "string", "operator": "in", "value": [
"string" ] } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/delete");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"string\",\"operator\":\"in\",\"value\":
[\"string\"]}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "string", "operator":
```

```
"in", "value": ["string"] ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/endpoints/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"string\",\"operator\":\"in\",\"value\":[\"string\"]}]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/endpoints/delete"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"string\",\"operator\":\"in\",\"value\":[\"string\"]}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/delete"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"string\",\"operator\":\"in\",\"value\":[\"string\"]}]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ filtersarray

Array of filter fields.

REQUEST

example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] } ] } }
```

Responses

Successful response

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.



▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.14.5 | Create distributions

post /public_api/v1/distributions/create

Create an installation package. This is an async call that returns the distribution ID; it does not mean that the creation succeeded. To confirm the package has been created, check the status of the distribution by running the **Get Distribution Status** API.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/distributions/create'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}"
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/distributions/create", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/distributions/create") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "platform": "windows", "package_type": "string",
"agent_version": "string", "windows_version": "string", "linux_version": "string", "macos_version": "string",
"deployment_platform": "string", "default_namespace": "string", "node_selector": { "property1": null, "property2":
null }, "proxy": [ "string" ], "cluster_name": "string", "run_on_master_node": true, "run_on_all_nodes": true,
"description": "string", "endpoint_tags": [ "string" ], "yaml_preferences": { "runtime": "Node.js", "deployment_type":
"embedded", "cloud_provider": "aws", "restrictions_profile": "string" } } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/distributions/create");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/distributions/create")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
```

```
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "name": "string", "platform": "windows",
"package_type": "string", "agent_version": "string", "windows_version": "string", "linux_version": "string",
"macos_version": "string", "deployment_platform": "string", "default_namespace": "string", "node_selector": [
"property1": , "property2": ], "proxy": ["string"], "cluster_name": "string", "run_on_master_node": true,
"run_on_all_nodes": true, "description": "string", "endpoint_tags": ["string"], "yaml_preferences": [ "runtime":
"Node.js", "deployment_type": "embedded", "cloud_provider": "aws", "restrictions_profile": "string" ] ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/distributions/create")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/distributions/create", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/distributions/create"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/distributions/create"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"name\":\"string\",\"platform\":\"windows\",\"package_type\":\"string\",\"agent_version\":\"string\",\"windows_version\":\"st
{\"property1\":null,\"property2\":null},\"proxy\":
[\"string\"],\"cluster_name\":\"string\",\"run_on_master_node\":true,\"run_on_all_nodes\":true,\"description\":\"string\",\"end
[\"string\"],\"yaml_preferences\":
{\"runtime\":\"Node.js\",\"deployment_type\":\"embedded\",\"cloud_provider\":\"aws\",\"restrictions_profile\":\"string\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ namestringrequired

The name of the installation package.

▶ platformstring (Enum)

The installation platform.

▶ package_typestringrequired

A string representing the type of package to create. Each JSON object must contain *one* of the following keywords:

- `standalone`: Installation for a new agent. When using this, you must include the `platform` field with one of the following values: `windows`, `linux`, `macos`, `android`, `kubernetes`, `helm`.
- `upgrade`: Upgrade of an agent from ESM. When using this, you must include the `agent_version` field with one of the following values: `windows_version`, `linux_version`, or `macos_version`.
- `serverless`: Create a serverless distribution. When using this, you must include the `yaml_preferences` field with the following properties: `runtime` (Node.js or python), `deployment_type` (embedded or layers), `cloud_provider` (aws), and `restrictions_profile` (Serverless restrictions profile ID).
- `caas_embedded`: Container-embedded XDR agent installation using the CaaS Generic Installer (Linux dockerfile-based deployment).

▶ agent_versionstringrequired

Use `agent_version` when creating a standalone installer. The value should be the agent version number.

▶ windows_versionstring

Use `windows_version` when creating an upgrade package. The value is the relevant version number.

▶ linux_versionstring

Use `linux_version` when creating an upgrade package. The value is the relevant version number.

▶ macos_versionstring

Use `macos_version` when creating an upgrade package. The value is the relevant version number.

▶ deployment_platformstringrequired

When the `package_type` is `kubernetes` or `helm`, use the `deployment_platform` to indicate the type of platform. Valid values include:

- `standard`
- `openshift`
- `gcos`
- `bottlerocket`
- `gke_autopilot`

▶ default_namespacestringrequired

The default namespace

▶ node_selectorobject

The node selector in the following format: `"node_selector": {"key": "val"}'

▶ proxyarray[string]
▶ cluster_namestring

Cluster name

▶ run_on_master_nodebooleanrequired

Whether or not to run on the master node.

▶ run_on_all_nodesbooleanrequired

Whether or not to run on all nodes.

▶ descriptionstring

A description for the distribution package.

▶ endpoint_tagsarray[string]

List of endpoint tags to associate with the distribution package. Tags must already exist in the system.

▶ yaml_preferencesobject

Configuration for serverless distributions.

REQUEST New Installation example

```
{ "request_data": { "name": "<installation package name>", "package_type": "upgrade", "agent_version":
"windows_version", "deployment_platform": "standard", "default_namespace": "cortex-xdr", "run_on_master_node": true,
"run_on_all_nodes": false, "endpoint_tags": [ "Administrator", "DevTeam" ], "description": "Created using Public APIs"
} }
{ "request_data": { "name": "Upgrade package", "package_type": "upgrade", "agent_version": "windows_version",
"deployment_platform": "standard", "default_namespace": "cortex-xdr", "run_on_master_node": true, "run_on_all_nodes":
false, "endpoint_tags": [ "Administrator", "DevTeam" ], "description": "Created using Public APIs" } }
```

{ "request_data": { "name": "PAPI Dist K8s", "description": "Created using PAPI", "endpoint_tags": ["new-tag"], "package_type": "kubernetes", "platform": "linux", "agent_version": "8.8.0.10594", "deployment_platform": "standard", "default_namespace": "cortex-xdr", "node_selector": { "key": "val" }, "proxy": ["10.10.10.1:8080"], "cluster_name": "some_name", "run_on_master_node": true, "run_on_all_nodes": false } }
{ "request_data": { "name": "Serverless distribution", "package_type": "serverless", "description": "Description", "agent_version": "{version}", "platform": "serverless", "deployment_platform": "standard", "default_namespace": "cortex-xdr", "run_on_master_node": false, "run_on_all_nodes": false, "yaml_preferences": { "runtime": "Node.js", "deployment_type": "embedded", "cloud_provider": "aws", "restrictions_profile": "28" } } }
Responses

Successful response

Body
application/json
▼ replyobject
▶ distribution_idstring

Installation package ID.

RESPONSE
{ "reply": { "distribution_id": "example" } }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.14.6 | Get Distributions

post /public_api/v1/distributions/get_distributions

Retrieves a paginated list of existing agent installations and metadata based on optional filters and sorting criteria.

This endpoint allows you to:

- Retrieve existing agent installations or filter by specific criteria
- Paginate through large result sets
- Sort results by any field in ascending or descending order
- Get total count and filtered count of agent installations

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/distributions/get_distributions'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"search_from\":0,\"search_to\":10,\"sort\":{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/distributions/get_distributions", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/distributions/get_distributions") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"search_from\":0,\"search_to\":10,\"sort\":{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "search_from": 0, "search_to": 10, "sort": { "field":
"distribution_id", "keyword": "desc" }, "filters": [ { "field": "platform", "operator": "eq", "value": "ios" } ] } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/distributions/get_distributions"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/distributions/get_distributions")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"search_from\":0,\"search_to\":10,\"sort\":{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "search_from": 0,
"search_to": 10, "sort": [ "field": "distribution_id", "keyword": "desc" ], "filters": [ [ "field": "platform",
"operator": "eq", "value": "ios" ] ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/distributions/get_distributions")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/distributions/get_distributions", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
```

```
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"search_from\":0,\"search_to\":10,\"sort\":
{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/distributions/get_distributions"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"search_from\":0,\"search_to\":10,\"sort\":
{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/distributions/get_distributions"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"search_from\":0,\"search_to\":10,\"sort\":
{\"field\":\"distribution_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"platform\",\"operator\":\"eq\",\"value\":\"ios\"}]}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

Request body containing pagination, sorting, and filtering parameters.

▶ search_frominteger

Starting index for pagination (zero-based). Defines the offset from which to begin returning results.

▶ search_tointeger

Ending index for pagination (exclusive). Defines the maximum number of results to return (`search_to` - `search_from`). The maximum allowed value is <=100. Requests exceeding this limit will return a 400 error.

▶ sortobject

Sorting criteria for query results.

▶ filtersarray

Array of filter conditions to apply. Multiple filters are combined with either `AND` or `OR` logic.

REQUEST

Sorting and all filter options

```
{ "request_data": { "search_from": 0, "search_to": 5, "sort": { "field": "distribution_id", "keyword": "asc" },
"filters": [ { "field": "distribution_id", "operator": "eq", "value": "068bcaad02974ac5b223bfa786e7573c" }, { "field":
"name", "operator": "contains", "value": "macos-369121" }, { "field": "description", "operator": "contains", "value":
"Production-ready macos agent installer with enhanced monitoring capabilities" }, { "field": "package_type",
"operator": "eq", "value": "standalone" }, { "field": "platform", "operator": "eq", "value": "macos" }, { "field":
"agent_version", "operator": "contains", "value": "9.1." }, { "field": "status", "operator": "eq", "value":
"completed" } ] } }
```

Responses

Successful response containing the list of distributions matching the criteria

Body

application/json

Response object containing the list of distributions and metadata

▼ replyobjectrequired

Container object for the response data

▶ dataarray

Array of distribution objects matching the filter criteria

▶ filter_countinteger

Number of distributions returned in the current response after applying filters.

▶ total_countinteger

Total number of distributions available in the system without filters.

RESPONSE

Example 1


```
{ "reply": { "data": [ { "distribution_id": "068bcaad02974ac5b223bfa786e7573c", "name": "macos-369121", "description":
"Production-ready macos agent installer with enhanced monitoring capabilities", "package_type": "standalone",
"platform": "macos", "agent_version": "9.1.0.9877", "status": "completed", "tags": [ "production", "stable" ],
"eol_time": 1735689600, "created_by": "John Doe", "creation_time": 1704067200, "modification_time": 1704153600,
"supported_packages": [ "pkg" ] } ], "filter_count": 1, "total_count": 10 } }
```


Bad Request - Invalid request parameters or malformed JSON

Body
application/json
▼ replyobject
▶ err_codeinteger

Numeric error code returned by the API.

▶ err_msgstring

Human-readable summary of the error.

▶ err_extrastring

Detailed description of the error, including the cause and how to resolve it when applicable.

RESPONSE Example 1


```
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra":
"Unsupported operator 'contains' for field platform" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API.", "err_extra": "Search
size must fulfill the requirement: 0 < search_size <= 100" } }
```


Internal Server Error - An unexpected error occurred on the server

Body
application/json
▼ replyobject
▶ err_codeinteger

Numeric error code returned by the API.

▶ err_msgstring

Human-readable summary of the error.

▶ err_extrastring

Detailed description of the error, including the cause and how to resolve it when applicable.

RESPONSE Example 1


```
{ "reply": { "err_code": 500, "err_msg": "An unexpected error occurred by XDR public API", "err_extra": "Invalid value
'serverless_functions' for field platform" } }
{ "reply": { "err_code": 500, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "Invalid
parameter names: creation_time" } }
```

2.1.14.7 | Get Violations

post /public_api/v1/device_control/get_violations

Gets a list of device control violations filtered by selected fields. You can retrieve up to 100 violations.

When filtering by multiple fields:

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 100.
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/device_control/get_violations'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[0]}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/device_control/get_violations", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/device_control/get_violations") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[0]}],\"search_from\":0,\"search_to\":0,\"sort\":{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ 0 ] } ], "search_from": 0, "search_to": 0, "sort": { "field": "endpoint_id_list", "value": "asc" } } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/device_control/get_violations"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/device_control/get_violations")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[0]}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": [0] ] ], "search_from": 0, "search_to": 0, "sort": [ "field": "endpoint_id_list", "value":
"asc" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/device_control/get_violations")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/device_control/get_violations", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[0]}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/device_control/get_violations"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[0]}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/device_control/get_violations"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[0]}],\"search_from\":0,\"search_to\":0,\"sort\":{\"field\":\"endpoint_id_list\",\"value\":\"asc\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

An empty object returns all results.

▶ filtersarray

Provides an array of filter fields.

▶ search_frominteger

Integer representing the starting offset within the query result set from which you want violations returned. Violations are returned as a zero-based list. Any violation indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

An integer representing the end of offset within the result set after which you do not want violations returned. Violations in the violation list that are indexed higher than this value are not returned in the final results set. Defaults to zero, which returns all alerts to the end of the list.

▶ sortobject

Identifies the sort order for the result set.

REQUEST Request all results

```
{ "request_data": {} }
{ "request_data": { "filters": [ { "field": "type", "operator": "in", "value": [ "disk drive" ] } ], "search_to": 1 }
}
```

Responses

Successful response

Body
application/json
▼ replyobject
▶ total_countinteger

Number of total results of this filter without paging.

▶ result_countinteger

Number of alerts actually returned as a result.

▶ violationsarray

RESPONSE

```
{ "reply": { "total_count": 0, "result_count": 0, "violations": [ { "hostname": "example", "username": "example",
"ip": "example", "timestamp": 0, "violation_id": 0, "type": "example", "vendor_id": "example", "vendor": "example",
"product_id": "example", "product": "example", "serial": "example", "endpoint_id": "example" } ] } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.8 | Get Distribution status

post /public_api/v1/distributions/get_status

Check the status of the installation package.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/distributions/get_status'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"distribution_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/distributions/get_status", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/distributions/get_status") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"distribution_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "distribution_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/distributions/get_status"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/distributions/get_status")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"distribution_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["distribution_id": "string"]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
```

```
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/distributions/get_status")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/distributions/get_status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"distribution_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/distributions/get_status"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\": {\"distribution_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/distributions/get_status"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"distribution_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ distribution_idstringrequired

The installation package ID.

REQUEST

```
{ "request_data": { "distribution_id": "example" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ statusstring

The status of the installation package.

RESPONSE

```
{ "reply": { "status": "example" } }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.9 | Get Distribution URL

post /public_api/v1/distributions/get_dist_url

Get the distribution URL for downloading the installation package.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/distributions/get_dist_url'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"distribution_id\":\"string\",\"package_type\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/distributions/get_dist_url", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/distributions/get_dist_url") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"distribution_id\":\"string\",\"package_type\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "distribution_id": "string", "package_type": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/distributions/get_dist_url"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/distributions/get_dist_url") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"distribution_id\":\"string\",\"package_type\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "distribution_id": "string", "package_type": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/distributions/get_dist_url")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/distributions/get_dist_url", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"distribution_id\":\"string\",\"package_type\":\"string\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/distributions/get_dist_url"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"distribution_id\":\"string\",\"package_type\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/distributions/get_dist_url"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"distribution_id\":\"string\",\"package_type\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ distribution_idstringrequired

Installation package ID.

▶ package_typestringrequired

A string representing the type of installation package. Select *one* of the following valid keywords and values:

- `upgrade` Package type should match the distribution type or platform:
- `sh`: x86_64 Linux SH installer
- `rpm`: x86_64 Linux RPM installer
- `deb`: x86_64 Linux DEB installer
- `aarch64_sh`: aarch64 Linux SH installer
- `aarch64_rpm`: aarch64 Linux RPM installer
- `aarch64_deb`: aarch64 Linux DEB installer
- `pkg`: Mac
- `x86`: Windows
- `x64`: Windows

REQUEST

example-1

```
{ "request_data": { "distribution_id": "<distribution ID>", "package_type": "x86" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ distribution_urlstring

URL for downloading the installation package.

RESPONSE

example-1

```
{ "reply": { "distribution_url": "<DOWNLOAD_URL>" } }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.14.10 | Set an Endpoint Alias

post /public_api/v1/endpoints/update_agent_name

Set or modify an Alias field for your endpoints.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/update_agent_name'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"alias\":\"string\"}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/endpoints/update_agent_name", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/update_agent_name") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"alias\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "alias": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/update_agent_name"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/update_agent_name")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"alias\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "alias": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/endpoints/update_agent_name")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/update_agent_name", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"alias\":\"string\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/update_agent_name"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"alias\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/update_agent_name"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"alias\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ filtersarray

An array of filter fields.

▶ aliasstring

The alias name you want to set or modify.

Note: If you send an empty field, the current alias name is deleted.

REQUEST

example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<distribution_id>" ] }
], "alias": "<alias_name>" } }
```

Responses

Successful response

Body

application/json

true=The alias name was set or modified successfully.

▼ boolean

true=The alias name was set or modified successfully.

RESPONSE

```
false
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.11 | Assign Tags

post /public_api/v1/tags/agents/assign

Assign one or more tags to one or more endpoints.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/tags/agents/assign'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/tags/agents/assign", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/tags/agents/assign")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}" response =
http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id", "operator": "in", "value": [ "string" ] } ], "tag": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/tags/agents/assign"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/tags/agents/assign") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id", "operator": "in", "value": ["string"] ] ], "tag": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/tags/agents/assign")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/tags/agents/assign", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/tags/agents/assign"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/tags/agents/assign"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ filtersarray

An array of filter fields.

▶ tagstring

The tag you want to assign.

REQUEST

example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<distribution_id>" ] } ], "tag": "<tag_name>" } }
```

Responses

Successful response

Body

application/json

true=The tag name was assigned successfully.

▼ boolean

true=The tag name was assigned successfully.

RESPONSE

```
false
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

x Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.14.12 | Remove Tags

post /public_api/v1/tags/agents/remove

Remove one or more tags from one or more endpoints.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/tags/agents/remove'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/tags/agents/remove", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/tags/agents/remove")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "tag": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/tags/agents/remove");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/tags/agents/remove")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "tag": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/tags/agents/remove")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/tags/agents/remove", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"tag\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/tags/agents/remove"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"tag\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/tags/agents/remove"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"tag\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the following API request fields.

▶ filtersarray

Array of filter fields.

▶ tagstring

The tag you want to remove.

REQUEST

example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<distribution_id>" ] }
], "tag": "<tag_name>" } }
```

Responses

Successful response

Body

application/json

true=tag name removed successfully.

▼ boolean

true=tag name removed successfully.

RESPONSE
`false`

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json



The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.14.13 | Get Endpoint

post /public_api/v1/endpoints/get_endpoint

Gets a list of filtered endpoints.

- The response is concatenated using AND condition (OR is not supported).
- The maximum result set size is 100.
- Offset is the zero-based number of endpoints from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/get_endpoint'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/get_endpoint", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/get_endpoint") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
"string" } ], "search_from": 0, "search_to": 0, "sort": { "field": "endpoint_id", "keyword": "ASC" } } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/get_endpoint"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/get_endpoint")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": "string" ] ], "search_from": 0, "search_to": 0, "sort": [ "field": "endpoint_id",
"keyword": "ASC" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: [])
let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/get_endpoint")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/get_endpoint", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/get_endpoint"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/get_endpoint"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":\"string\"}],\"search_from\":0,\"search_to\":0,\"sort\":
{\"field\":\"endpoint_id\",\"keyword\":\"ASC\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

An empty dictionary returns all results.

▶ filtersarray

Array of filter fields.

▶ search_frominteger

Represents the start offset within the query result set from which you want endpoints returned.

Endpoints are returned as a zero-based list. Any endpoint indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

Represents the end offset within the result set after which you do not want endpoints returned.

Endpoint in the endpoint list that is indexed higher than this value is not returned in the final results set. Defaults to 100, which returns all endpoints to the end of the list.

▶ sortobject

Identifies the sort order for the result set.

REQUEST Request filtered results

```
{ "request_data": { "search_from": 0, "search_to": 1, "sort": { "field": "endpoint_id", "keyword": "asc" }, "filters":
[ { "field": "group_name", "operator": "in", "value": [ "Test-Group-01" ] }, { "field": "endpoint_status", "operator":
"in", "value": [ "disconnected" ] }, { "field": "dist_name", "operator": "in", "value": [ "papi-test" ] }, { "field":
"scan_status", "operator": "in", "value": [ "none", "pending", "in_progress", "pending_cancellation", "aborted",
"success", "canceled", "error" ] } ] } }
{ "request_data": {} }
{ "request_data": { "filters": [ { "field": "cloud_provider", "operator": "in", "value": [ "aws" ] }, { "field":
"cloud_region", "operator": "in", "value": [ "us-east-1", "us-west-2" ] } ] } }
```

Responses

OK

Body
application/json

▼ replyobject

JSON object containing the query result.

▶ total_countinteger

Number of total results of this filter without paging.

▶ result_countinteger

Number of endpoints actually returned as result.

▶ endpointsarray

A list of endpoints.

RESPONSE

Example 1

```
{ "reply": { "total_count": 1, "result_count": 1, "endpoints": [ { "endpoint_id": "<endpoint ID>", "endpoint_name": "
<endpoint name>", "endpointTags": "<tag name>", "endpoint_type": "<endpoint type>", "endpoint_status": "CONNECTED",
"operational_status_details": [ { "title": "XDR Data Collection not running or not sent", "reason": "Linux kernel
version is not supported" }, { "title": "BTP not working", "reason": "Linux kernel version is not supported" }, {
"title": "Antimalware flow is asynchronous", "reason": "Linux kernel version is not supported" }, { "title": "Local
privilege escalation", "reason": "Linux kernel version is not supported" } ], "os_type": "AGENT_OS_WINDOWS",
"os_version": "8.0.xxx", "ip": [ "<IP address>" ], "ipv6": [], "public_ip": "<IP address>", "users": [ "XDR" ],
"domain": "WORKGROUP", "alias": "", "first_seen": 1606218761377, "last_seen": 1606218769163, "content_version": "",
"installation_package": "XDR", "active_directory": null, "install_date": 1606218762089, "endpoint_version": "
<version>", "is_isolated": "AGENT_UNISOLATED", "isolated_date": null, "group_name": [], "operational_status":
"PARTIALLY_PROTECTED", "scan_status": "SCAN_STATUS_NONE", "content_release_timestamp": 1636285746000,
"last_content_update_time": 1636381954285, "content_status": "up_to_date", "operating_system": "Debian 10.11",
"mac_address": [ "42:00:00:00:00:00" ], "assigned_prevention_policy": "Linux Default", "assigned_extensions_policy":
"" } ] } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.14.14 | Initiate Forensics Triage

post /public_api/v1/triage_endpoint

Initiate forensics triage for the specified agents.

- Maximum of 10 concurrent triage actions at a time.
- Specified agents must have Forensics License enabled.
- Specified agents must be the same OS, Windows or macOS, but not a mixture of both.
- Specified configuration must have type "Online = True".

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/triage_endpoint'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"agent_ids\":[\"string\"],\"collector_uuid\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/triage_endpoint", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/triage_endpoint") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"agent_ids\":[\"string\"],\"collector_uuid\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "agent_ids": ["string"], "collector_uuid": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-

```
yourfqdn/public_api/v1/triage_endpoint"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/triage_endpoint")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"agent_ids\":[\"string\"],\"collector_uuid\":\"string\"}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "agent_ids": ["string"], "collector_uuid":
"string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/triage_endpoint")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/triage_endpoint", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"agent_ids\":[\"string\"],\"collector_uuid\":\"string\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/triage_endpoint"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"agent_ids\":
[\"string\"],\"collector_uuid\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/triage_endpoint"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"agent_ids\":[\"string\"],\"collector_uuid\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ agent_idsarray[string]required

List of agents to run forensics triage on.

▶ collector_uuidstring

UUID of the triage configuration. If none is specified, the default configuration is used for this action.

REQUEST

```
{ "request_data": { "agent_ids": [ "example" ], "collector_uuid": "example" } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ group_action_idinteger

Unique ID for triage action.

▶ successful_agent_idsarray[string]

List of agent IDs that successfully received the triage action.

▶ unsuccessful_agent_idsarray

List of agent IDs that did not successfully receive the triage action.

RESPONSE

Example 1

```
{ "reply": { "group_action_id": 325, "successful_agent_ids": [ "5111c5eb93944e2f97674db4f36b4211" ],
"unsuccessful_agent_ids": [] } }
```

Bad Request

Unauthorized

Payment Required

Forbidden

Internal Server Error

2.1.14.15 | Delete Tags Permanently

post /public_api/v1/tags/agents/delete_permanently

Permanently delete one or more endpoint tags from the system. Tags that are currently assigned to endpoints cannot be deleted. A maximum of 10 tags can be deleted per API call.

Required role: Admin

Required license: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/tags/agents/delete_permanently'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"tags\":
[\"string\"],\"reason\":\"stringstringstringst\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/tags/agents/delete_permanently", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/tags/agents/delete_permanently") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"tags\":[\"string\"],\"reason\":\"stringstringstringst\"}}" response =
http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "tags": [ "string" ], "reason": "stringstringstringst" } }); const xhr
= new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/tags/agents/delete_permanently"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/tags/agents/delete_permanently")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"tags\":[\"string\"],\"reason\":\"stringstringstringst\"}}")
.asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "tags": ["string"], "reason":
"stringstringstringst" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/tags/agents/delete_permanently")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/tags/agents/delete_permanently", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"tags\":[\"string\"],\"reason\":\"stringstringstringst\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/tags/agents/delete_permanently"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"tags\":
[\"string\"],\"reason\":\"stringstringstringst\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/tags/agents/delete_permanently"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"tags\":[\"string\"],\"reason\":\"stringstringstringst\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ tagsarray[string]required

List of tag names to permanently delete from the system.

▶ reasonstring

Reason for deleting the tags.

REQUEST

```
{ "request_data": { "tags": [ "example" ], "reason": "example" } }
```

Responses

Successful response â€ tags were permanently deleted from the system.

Body

application/json

▼ replyobject

▶ messagestring

Success message confirming the tags were deleted.

RESPONSE

success

```
{ "reply": { "message": "Tags were successfully deleted from the system" } }
```

Bad Request. The request failed validation or the specified tags could not be deleted.

Body

application/json

▼ replyobject

▶ err_codeinteger

▶ err_msgstring

Error message describing why the tags could not be deleted.

▶ err_extrastring

Additional error context.

RESPONSE empty-tags-list

```
{ "reply": { "err_code": 400, "err_msg": "Failed to delete tags permanently - \"tags\" input is mandatory and cannot
be an empty list", "err_extra": "" } }
{ "reply": { "err_code": 400, "err_msg": "Failed to delete tags permanently. The following tags were not found:
invalid_tag", "err_extra": "" } }
{ "reply": { "err_code": 400, "err_msg": "Failed to delete tags permanently. The following tags were not found:
invalid_tag. The following tags are assigned to one or more endpoints: unassigned_tag.", "err_extra": "" } }
{ "reply": { "err_code": 400, "err_msg": "Failed to delete tags permanently. The following tags are assigned to one or
more endpoints: unassigned_tag.", "err_extra": "" } }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. Missing required license.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.14.16 | Upgrade Agents

post /public_api/v1/endpoints/upgrade

Creates an upgrade action for the specified endpoints to upgrade their agents to the target versions.

You can specify target versions per operating system and optionally define a timeframe window for the upgrade.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/upgrade'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"endpoint_ids\":
[\"string\"],\"target_versions\":{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":
{\"upgrade_timeframe_days\":
[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/endpoints/upgrade", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/upgrade")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"endpoint_ids\":
[\"string\"],\"target_versions\":{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":
{\"upgrade_timeframe_days\":
[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "endpoint_ids": [ "string" ], "target_versions": { "property1":
"string", "property2": "string" }, "upgrade_timeframe_window": { "upgrade_timeframe_days": [ "string" ],
"upgrade_timeframe_start_time": "string", "upgrade_timeframe_end_time": "string" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/upgrade"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/upgrade")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"endpoint_ids\":[\"string\"],\"target_versions\":
{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":{\"upgrade_timeframe_days\":
[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "endpoint_ids": ["string"], "target_versions": [ "property1": "string", "property2": "string" ], "upgrade_timeframe_window": [ "upgrade_timeframe_days": ["string"], "upgrade_timeframe_start_time": "string", "upgrade_timeframe_end_time": "string" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/upgrade")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/endpoints/upgrade", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"endpoint_ids\":[\"string\"],\"target_versions\":{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":{\"upgrade_timeframe_days\":[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/endpoints/upgrade"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"endpoint_ids\":[\"string\"],\"target_versions\":{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":{\"upgrade_timeframe_days\":[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/upgrade"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"endpoint_ids\":[\"string\"],\"target_versions\":{\"property1\":\"string\",\"property2\":\"string\"},\"upgrade_timeframe_window\":{\"upgrade_timeframe_days\":[\"string\"],\"upgrade_timeframe_start_time\":\"string\",\"upgrade_timeframe_end_time\":\"string\"}}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ endpoint_idsarray[string]required

List of endpoint IDs to upgrade.

▶ target_versionsobjectrequired

Dictionary mapping OS types to target agent versions. Valid keys: `windows`, `linux`, `macos`.

▶ upgrade_timeframe_windowobject

Optional timeframe window to schedule the upgrade.

REQUEST Upgrade specific endpoints

```
{ "request_data": { "endpoint_ids": [ "endpoint_id_1", "endpoint_id_2" ], "target_versions": { "windows": "8.6.0.1234", "linux": "8.6.0.5678" } } }
{ "request_data": { "endpoint_ids": [ "endpoint_id_1" ], "target_versions": { "windows": "8.6.0.1234", "macos": "8.6.0.9012" }, "upgrade_timeframe_window": { "upgrade_timeframe_days": [ "monday", "wednesday", "friday" ], "upgrade_timeframe_start_time": "02:00", "upgrade_timeframe_end_time": "06:00" } } }
```

Responses

Successful response

Body

application/json

▼ replyobject

JSON object containing the upgrade action result.

▶ summarystring

A summary message of the operation result.

▶ detailsarray[string]

Detailed eligibility or error messages per OS type.

RESPONSE

Successful upgrade


```
{ "reply": { "summary": "Upgrade action created successfully.", "details": [ "Windows: 2 endpoints queued for upgrade to 8.6.0.1234", "Linux: 1 endpoint queued for upgrade to 8.6.0.5678" ] } }
```


Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.14.17 | Get endpoint security profiles

post /public_api/v1/endpoints/get_profiles

Returns a list of endpoint security profiles of the requested type. Optionally filters by a list of profile IDs.

Required permission: `profiles_view`

Notes:

- File-Integrity-Monitoring (FIM) extension profiles are omitted when FIM is disabled for the profile's OS type.
- `is_in_user_scope` and `at_risk` are removed from every profile object before the response is returned.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/get_profiles'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"type\":\"prevention\",\"profile_ids\":[1]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/get_profiles", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/get_profiles") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": { "type": "prevention", "profile_ids": [ 1 ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/get_profiles"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/get_profiles")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "type": "prevention", "profile_ids": [1] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/get_profiles")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/get_profiles", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/get_profiles"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"type\":\"prevention\",\"profile_ids\":[1]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/get_profiles"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}", ParameterType.RequestBody); IRestResponse response
= client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

Parameters for the `get_profiles` call

▶ typestring (Enum)required

The category of profiles to retrieve.

- `prevention` â€ standard endpoint prevention profiles managed by `ProfilesService` (malware, exploit, restrictions, agent-settings, exceptions, etc.)
- `extension` â€ device-control and host-firewall profiles managed by `DeviceControlProfilesService`

▶ profile_idsarray[integer]

Optional list of profile IDs to filter by. When omitted or `null`, all profiles of the requested type are returned. When provided, only profiles whose `id` is in this list are returned. Must be a JSON array; passing a non-array value yields HTTP 400.

REQUEST Fetch all prevention profiles

```
{ "request_data": { "type": "prevention" } }
{ "request_data": { "type": "extension", "profile_ids": [ 1, 42, 99 ] } }
```

Responses

OK. Profiles retrieved successfully

Body
application/json

Successful response envelope

▼ replyarray

List of matching profile objects.

[
▶ idintegerint64

Internal numeric profile ID

▶ uuidstring

Globally unique profile identifier (UUID v4)

▶ namestring

Human-readable profile name.

▶ typestring (Enum)

Target operating system

▶ is_defaultboolean

Whether this is the system-managed default profile for its type and OS

▶ is_globalboolean

Whether this profile is a global (cross-tenant) profile

▶ is_disabledboolean

Whether this profile is currently disabled

▶ associated_targetsarray[string]

Human-readable list of policy rule targets (endpoint groups, tags, and so on.) that reference this profile, rendered as UI-friendly strings. `null` when the profile is not referenced by any policy rule.

▶ usage_countintegerint32

Number of policy rules that reference this profile

▶ descriptionstring

Optional free-text description of the profile

▶ created_bystring

Internal identifier (email or system name) of the creator

▶ created_by_prettystring

Display name of the creator

▶ creation_timeintegerint64

Profile creation timestamp in Unix epoch milliseconds

▶ modified_bystring

Internal identifier of the last modifier

▶ modified_by_prettystring

Display name of the last modifier

▶ modification_timeintegerint64

Last modification timestamp in Unix epoch milliseconds

▶ modulesobject

JSON object containing the profile's security module configuration. The schema varies by `type` and `platform`. Common top-level keys are module names (for example, `malware`, `exploit`, `agent_settings`), each containing mode and sub-option settings.

]
RESPONSE
Example 1

```
{ "reply": [ { "id": 1, "uuid": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "name": "Default Malware Profile", "type":
"MALWARE", "platform": "AGENT_OS_WINDOWS", "is_default": true, "is_global": false, "is_disabled": false,
"associated_targets": [ "All endpoints" ], "usage_count": 5, "description": "Default anti-malware profile for
Windows", "created_by": "system", "created_by_pretty": "Palo Alto Networks", "creation_time": 1700000000000,
"modified_by": "admin@example.com", "modified_by_pretty": "Admin User", "modification_time": 1710000000000, "modules":
{ "malware": { "mode": "prevent" } } }, { "id": 2, "uuid": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "name": "Custom
Exploit Profile", "type": "EXPLOIT", "platform": "AGENT_OS_MAC", "is_default": false, "is_global": false,
"is_disabled": false, "associated_targets": [ "macOS Servers" ], "usage_count": 2, "description": null, "created_by":
"admin@example.com", "created_by_pretty": "Admin User", "creation_time": 1705000000000, "modified_by":
"admin@example.com", "modified_by_pretty": "Admin User", "modification_time": 1705000000000, "modules": {} } ] }
```


Bad request. Possible causes:

- `type` field is missing (`TypeIsMandatory`)
- `type` value is not `prevention` or `extension` (`TypeNotSupported`)
- `profile_ids` is provided but is not a list (`ProfileIDsMustBeAList`)
- Any internal error during profile retrieval (`GeneralError`)

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE type field not provided

```
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "type is mandatory" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "type 'unknown' is not supported.
Valid types: ('prevention', 'extension')" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "profile_ids must be a list" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "General error" } }
```


Unauthorized â€ missing or invalid API-key headers

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE

```
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }
```


Forbidden. Possible causes:

- The API key does not have the `profiles_view` permission
- The feature flag `ALPHAFEATURES_PUBLIC_API_GET_POLICIES` is disabled
- The tenant is a secondary HA replica

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE
```
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

2.1.14.18 | Get Legacy Exceptions Modules

post /public_api/v1/legacy_exceptions/get_modules

Get a list of supported legacy exception modules available in the tenant. Each module entry includes its `module_id`, supported `platforms`, and the `conditions_definition` schema that must be used when creating or editing a legacy exception rule for that module.

Note: No request body required. Send an empty body.

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/legacy_exceptions/get_modules'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/legacy_exceptions/get_modules", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/legacy_exceptions/get_modules") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/legacy_exceptions/get_modules"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/legacy_exceptions/get_modules")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/legacy_exceptions/get_modules")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/legacy_exceptions/get_modules", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/legacy_exceptions/get_modules"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/legacy_exceptions/get_modules"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

```
{}
```

Responses

OK

Body

application/json

▼ replyarray

[

▶ module_idinteger

Unique numeric identifier for the module. Use as the **module** field in add/edit requests.

▶ pretty_namestring

Full display name including profile type category

▶ titlestring

Short title of the module.

▶ labelstring

Label describing what the exception allow-lists (for example, "Files / Folders in Allow List").

▶ profile_typestring

Category of the protection profile this module belongs to.

▶ platformsarray[string]

List of platforms this module supports. Only use these platforms in add/edit requests for this module.

▶ conditions_definitionobject

Schema definition for the `conditions` object required when creating or editing a legacy exception rule for this module. Each key is a condition field name, and its value describes the expected schema and a human-readable description.

]
RESPONSE
Example 1

```
{ "reply": [ { "module_id": 1, "pretty_name": "Malware > Respond to Malicious Causality Chains", "title": "Respond to Malicious Causality Chains", "label": "Allow List of Remote Ipv4/ipv6 Ip Address, Range or Cidr", "profile_type": "Malware", "platforms": [ "Windows", "macOS" ], "conditions_definition": { "remoteIpsWhitelist": { "schema": { "type": "array", "items": { "type": "string" }, "minItems": 1 }, "description": "List of valid Ipv4/ipv6 Ip Address, Ranges or Cidrs" } } } ] }
```


Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.14.19 | Fetch Legacy Exception Rules

post /public_api/v1/legacy_exceptions/fetch

Retrieves a paginated list of Legacy Exception rules for agents based on optional filters and sorting criteria.

This endpoint allows you to:

- Retrieve all rules or filter by specific criteria
- Sort results by any field in ascending or descending order
- Paginate through large result sets
- Get total count and filtered count of rules

Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/legacy_exceptions/fetch'
-d '{ "request_data" : { "search_from" : 0, "sort" : { "field" : "id", "keyword" : "desc" }, "filters" : [ { "field" :
"id", "value" : "value", "operator" : "eq" }, { "field" : "id", "value" : "value", "operator" : "eq" } ], "search_to"
: 1 } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/legacy_exceptions/fetch", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/legacy_exceptions/fetch") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
```

```
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "search_from": 0, "search_to": 1, "sort": { "field": "id", "keyword":
"desc" }, "filters": [ { "field": "id", "operator": "eq", "value": "string" } ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/legacy_exceptions/fetch"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/legacy_exceptions/fetch")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "search_from": 0,
"search_to": 1, "sort": [ "field": "id", "keyword": "desc" ], "filters": [ [ "field": "id", "operator": "eq", "value":
"string" ] ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/legacy_exceptions/fetch")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/legacy_exceptions/fetch", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":
{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/legacy_exceptions/fetch"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/legacy_exceptions/fetch"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":
{\"field\":\"id\",\"keyword\":\"desc\"},\"filters\":[{\"field\":\"id\",\"operator\":\"eq\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

Request body containing pagination, sorting, and filtering parameters.

▶ search_frominteger

Starting index for pagination (zero-based). Defines the offset from which to begin returning results.

▶ search_tointeger

Ending index for pagination (exclusive). Defines the maximum number of results to return (search_to - search_from).

▶ sortobject

Defines sorting criteria for query results.

▶ filtersarray

List of filter conditions. Multiple filters are combined with AND logic.

REQUEST

Example 1


```
{ "request_data": { "search_from": 0, "search_to": 10, "sort": { "field": "id", "keyword": "desc" }, "filters": [ { "field": "status", "operator": "eq", "value": "ENABLED" }, { "field": "platform", "operator": "eq", "value": "Windows" } ] } }
```


Responses

OK

Body

application/json

A legacy exception record as returned by the fetch API.

▼ replyobject

▶ DATAarray

▶ FILTER_COUNTinteger

The number of rules returned in the current response after applying filters.

▶ TOTAL_COUNTinteger

The total number of rules available that match the filter criteria, regardless of pagination.

RESPONSE

Example 1


```
{ "reply": { "DATA": [ { "id": "d9c06bfa3f9b45a7a0196244e68d181d", "rule_name": "Legacy Exception Rule 1", "platform": "Linux", "conditions": "Process Name = Another test process AND Modules = Disable Injection OR Process Name = Test process AND Modules = Child Process Protection", "module": 43, "module_name": "Exceptions > Process Exceptions", "description": "rule 1", "generating_alert_id": null, "created_by": "John Doe", "modification_time": 1772111647000, "user_email": "john.doe@example.com", "status": "ENABLED", "profile_ids": [ 27 ], "associated_targets": [ "Any" ], "is_in_user_scope": true }, { "id": "0a2661779a2d4a87b051158ea47f0022", "rule_name": "Legacy Exception Rule 2", "platform": "Windows", "conditions": "Remote IP Address : 192.168.1.45", "module": 1, "module_name": "Malware > Respond to Malicious Causality Chains", "description": "test", "generating_alert_id": null, "created_by": "Jane Doe", "modification_time": 1772089294000, "user_email": "jane.doe@example.com", "status": "ENABLED", "profile_ids": [ 29 ], "associated_targets": [], "is_in_user_scope": true } ], "FILTER_COUNT": 2, "TOTAL_COUNT": 2 } }
```


Bad Request

Body

application/json

▼ replyobject

▶ err_codeinteger

HTTP error code.

▶ err_msgstring

High-level error message

▶ err_extrastring

Detailed error information describing the specific validation failures.

RESPONSE

Example 1


```
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "invalid request - operator contains is unsupported for rule_name, conditions is not supported for filtering, module_name is not supported for filtering, description is not supported for filtering, value Enabled is not valid for field status, modification_time is not supported for filtering, profiles is not supported for filtering, generating_alert_id is not supported for filtering" } }
```

2.1.14.20 | Add Legacy Exception Rule

post /public_api/v1/legacy_exceptions/add

Create a new legacy exception rule.

Prerequisites:

- Use `/public_api/v1/legacy_exceptions/get_modules` endpoint to search available `module` IDs, supported `platforms`, and the required `conditions` structure.
- Use `/public_api/v1/endpoints/get_profiles` to search existing profile IDs to pass as `profile_ids`.
- New profiles can be created via `/public_api/v1/profiles/prevention/add`.

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl


```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/legacy_exceptions/add'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/legacy_exceptions/add", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/legacy_exceptions/add") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "platform": "Windows", "module": 1, "profile_ids": [
0 ], "status": "string", "scope": "string", "description": "string", "conditions": {} } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/legacy_exceptions/add"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/legacy_exceptions/add")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "name": "string",
"platform": "Windows", "module": 1, "profile_ids": [0], "status": "string", "scope": "string", "description":
"string", "conditions": [] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/legacy_exceptions/add")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/legacy_exceptions/add", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}", CURLOPT_HTTPHEADER =>
[ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/legacy_exceptions/add"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/legacy_exceptions/add"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"name\":\"string\",\"platform\":\"Windows\",\"module\":1,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

Request body for creating a legacy exception rule.

▶ namestringrequired

Name for the legacy exception rule.

▶ platformstringrequired

Target platform for the exception. Must be one of the platforms supported by the chosen module (see `/public_api/v1/legacy_exceptions/get_modules` endpoint response).

▶ moduleintegerrequired

Numeric ID of the protection module to create the exception for. Get valid module IDs from `/public_api/v1/legacy_exceptions/get_modules` endpoint.

▶ profile_idsarray[integer]required

List of prevention profile IDs this exception rule applies to. Use `/public_api/v1/endpoints/get_profiles` endpoint to find existing profile IDs.

- For `scope: PROFILE`: provide one or more profile IDs (e.g. `[29]`)
- For `scope: GLOBAL`: must be an empty array `[]`

▶ statusstringrequired

Status of the rule. Allowed values: `ENABLED` or `DISABLED`.

▶ scopestringrequired

Scope of the exception:

- `PROFILE` â€ exception applies to specific prevention profiles listed in `profile_ids`
- `GLOBAL` â€ exception applies globally; `profile_ids` must be `[]` and the module must be an Exception-type module

▶ descriptionstring

Optional description of the exception rule.

▶ conditionsobjectrequired

The conditions structure depends on the chosen `module`. Use `/public_api/v1/legacy_exceptions/get_modules` endpoint to get the `conditions_definition` for each module.

REQUEST Example 1

```
{ "request_data": { "name": "Test Legacy Exception rule 1", "platform": "Windows", "module": 1, "profile_ids": [ 29 ],
"status": "ENABLED", "scope": "PROFILE", "description": "my legacy rule desc", "conditions": { "remoteIpsWhitelist": [
"192.168.1.45" ] } } }
{ "request_data": { "name": "Test kpep legacy rule", "platform": "macOS", "module": 43, "profile_ids": [ 53 ],
"status": "ENABLED", "scope": "PROFILE", "description": "my legacy desc rule 2", "conditions": { "process_exceptions":
[ { "processName": "test\\test.exe", "modules": [ { "moduleId": 141, "moduleName": "Kernel Privilege Escalation
Protection" } ] } ] } } }
```

Responses

OK

Body
application/json
▼ replystring

The ID of the newly created legacy exception rule.

Example: `"f87c6f24205249d896677ab63626d4f4"`
RESPONSE
Example 1

```
{ "reply": "f87c6f24205249d896677ab63626d4f4" }
```

2.1.14.21 | Edit Legacy Exception Rule

post /public_api/v1/legacy_exceptions/edit

Update an existing legacy exception rule.

Prerequisites:

To get the required fields:

- Use `/public_api/v1/legacy_exceptions/fetch` to retrieve existing exception details.
- The `id` field in the fetch API response corresponds to `exception_id` in this request.
- The `rule_name` field in the fetch API response corresponds to `name` in this request.
- The `scope` field is not returned by the fetch API. Use `"PROFILE"` if `profile_ids` is non-empty in the fetch response; use `"GLOBAL"` if `profile_ids` is `[]`.

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/legacy_exceptions/edit'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/legacy_exceptions/edit", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/legacy_exceptions/edit") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "exception_id": "string", "update_data": { "name": "string",
"platform": "string", "module": 0, "profile_ids": [ 0 ], "status": "string", "scope": "string", "description":
"string", "conditions": {} } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/legacy_exceptions/edit");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/legacy_exceptions/edit")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "exception_id":
"string", "update_data": [ "name": "string", "platform": "string", "module": 0, "profile_ids": [0], "status":
"string", "scope": "string", "description": "string", "conditions": [] ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/legacy_exceptions/edit")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/legacy_exceptions/edit", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}", CURLOPT_HTTPHEADER =>
[ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/legacy_exceptions/edit"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/legacy_exceptions/edit"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"exception_id\":\"string\",\"update_data\":
{\"name\":\"string\",\"platform\":\"string\",\"module\":0,\"profile_ids\":
[0],\"status\":\"string\",\"scope\":\"string\",\"description\":\"string\",\"conditions\":{}}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json
▼ request_dataobject

Request body for editing or updating an existing legacy exception rule.

▶ exception_idstringrequired

The ID of the legacy exception to edit. Corresponds to the `id` field returned by the fetch API.

▶ update_dataobject
REQUEST Example 1

```
{ "request_data": { "exception_id": "f87c6f24205249d896677ab63626d4f4", "update_data": { "name": "Edit legacy exception rule", "platform": "Windows", "module": 1, "profile_ids": [ 29 ], "status": "DISABLED", "scope": "PROFILE", "description": "my legacy desc", "conditions": { "remoteIpsWhitelist": [ "192.168.1.45", "10.0.0.10-10.0.0.20" ] } } }
}
{ "request_data": { "exception_id": "d9c06bfa3f9b45a7a0196244e68d181d", "update_data": { "name": "Edit legacy exception rule 1", "platform": "Linux", "module": 43, "profile_ids": [ 26 ], "status": "ENABLED", "scope": "PROFILE", "description": "test 3", "conditions": { "process_exceptions": [ { "processName": "Test process 1", "modules": [ { "moduleId": 67, "moduleName": "Disable Injection" } ] }, { "processName": "Test process 2", "modules": [ { "moduleId": 63, "moduleName": "Child Process Protection" } ] }, { "processName": "Test process 3", "modules": [ { "moduleId": 65, "moduleName": "Brute Force Protection" } ] } ] } } } }
```

Responses

OK

Body
application/json
▼ replystring

The ID of the edited legacy exception rule.

Example: `"f87c6f24205249d896677ab63626d4f4"`
RESPONSE
Example 1

```
{ "reply": "f87c6f24205249d896677ab63626d4f4" }
```

2.1.14.22 | Delete Legacy Exception Rules

post /public_api/v1/legacy_exceptions/delete

Deletes one or more legacy exception rules by their IDs.

Use `/public_api/v1/legacy_exceptions/fetch` endpoint to retrieve the `id` values of the exceptions you want to delete.

Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/legacy_exceptions/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"exception_ids\":
[\"f87c6f24205249d896677ab63626d4f4\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
```

```
"/public_api/v1/legacy_exceptions/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/legacy_exceptions/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"exception_ids\":[\"f87c6f24205249d896677ab63626d4f4\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "exception_ids": [ "f87c6f24205249d896677ab63626d4f4" ] } }); const
xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/legacy_exceptions/delete"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/legacy_exceptions/delete")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"exception_ids\":[\"f87c6f24205249d896677ab63626d4f4\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["exception_ids":
["f87c6f24205249d896677ab63626d4f4"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/legacy_exceptions/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/legacy_exceptions/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"exception_ids\":[\"f87c6f24205249d896677ab63626d4f4\"]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/legacy_exceptions/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"exception_ids\":[\"f87c6f24205249d896677ab63626d4f4\"]}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/legacy_exceptions/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"exception_ids\":
[\"f87c6f24205249d896677ab63626d4f4\"]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ exception_idsarray[string]required

List of legacy exception IDs to delete. Corresponds to the `id` field returned by the fetch API.

REQUEST

Example 1

```
{ "request_data": { "exception_ids": [ "f87c6f24205249d896677ab63626d4f4" ] } }
```

Responses

OK

Body
application/json
▼ replyinteger

The number of successfully deleted legacy exception rules.

Example:1
RESPONSE
Example 1
```
{ "reply": 1 }
```

2.1.14.23 | Add Prevention Profile

post /public_api/v1/profiles/prevention/add

Create a new prevention profile with specified configuration.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/profiles/prevention/add'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/profiles/prevention/add", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/profiles/prevention/add") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "name": "Windows_Malware_Prevention", "profile_type": "malware", "platform": "windows",
"description": "Standard prevention profile for Windows endpoints", "modules": { "wildfire": { "status": "enabled" },
"behavioral_threat_protection": { "status": "enabled" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/profiles/prevention/add");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/profiles/prevention/add")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "name": "Windows_Malware_Prevention", "profile_type":
"malware", "platform": "windows", "description": "Standard prevention profile for Windows endpoints", "modules": [
```

```
"wildfire": ["status": "enabled"], "behavioral_threat_protection": ["status": "enabled"] ] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/profiles/prevention/add")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/profiles/prevention/add", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/profiles/prevention/add"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/profiles/prevention/add"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"
{\"name\":\"Windows_Malware_Prevention\",\"profile_type\":\"malware\",\"platform\":\"windows\",\"description\":\"Standard
prevention profile for Windows endpoints\",\"modules\":{\"wildfire\":
{\"status\":\"enabled\"},\"behavioral_threat_protection\":{\"status\":\"enabled\"}}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ namestringrequired

Name of the profile.

▼ profile_typestringrequired

Type of the prevention profile.

▼ platformstringrequired

Platform (OS) for the profile.

▼ descriptionstring

Optional description of the profile.

▼ modulesobjectrequired

Configuration modules for the profile.

▶ Additional propertiesobject

REQUEST

```
{ "name": "Windows_Malware_Prevention", "profile_type": "malware", "platform": "windows", "description": "Standard
prevention profile for Windows endpoints", "modules": { "wildfire": { "status": "enabled" },
"behavioral_threat_protection": { "status": "enabled" } } }
```

Responses

Successful response

Body

application/json

▼ replyinteger

The ID of the newly created profile.

RESPONSE

```
{ "reply": 12345 }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.14.24 | Add Signer CN to Allowlist

post /public_api/v1/profiles/add_signer_cn_to_allowlist

Add one or more signer common names to the allowlist of a specific Windows malware prevention profile. This endpoint only works on Windows Malware profiles.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation, O=Microsoft Corporation,
L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara, S=California, C=US\"]}"
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/profiles/add_signer_cn_to_allowlist", payload, headers) res
= conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation, O=Microsoft
Corporation, L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara,
S=California, C=US\"]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "profile_name": "Windows_Malware_Prevention", "signers": [ "CN=Microsoft Corporation,
O=Microsoft Corporation, L=Redmond, S=Washington, C=US", "CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara,
S=California, C=US" ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation,
O=Microsoft Corporation, L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara,
S=California, C=US\"]}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "profile_name": "Windows_Malware_Prevention", "signers":
["CN=Microsoft Corporation, O=Microsoft Corporation, L=Redmond, S=Washington, C=US", "CN=Palo Alto Networks, O=Palo
Alto Networks, L=Santa Clara, S=California, C=US"] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist")! as URL, cachePolicy:
```

```
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation, O=Microsoft Corporation, L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara, S=California, C=US\"]}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation, O=Microsoft Corporation, L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara, S=California, C=US\"]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/profiles/add_signer_cn_to_allowlist"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"profile_name\":\"Windows_Malware_Prevention\",\"signers\":[\"CN=Microsoft Corporation, O=Microsoft Corporation, L=Redmond, S=Washington, C=US\",\"CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara, S=California, C=US\"]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ profile_namestringrequired

The name of the Windows malware prevention profile. Cannot be 'Default'.

▼ signersobjectrequired

A single signer CN string or a list of signer CN strings to add. Total signers cap is 1000.

One of a
▶ string

A single signer CN string or a list of signer CN strings to add. Total signers cap is 1000.

Array
REQUEST

```
{ "profile_name": "Windows_Malware_Prevention", "signers": [ "CN=Microsoft Corporation, O=Microsoft Corporation, L=Redmond, S=Washington, C=US", "CN=Palo Alto Networks, O=Palo Alto Networks, L=Santa Clara, S=California, C=US" ] }
```

Responses

Successful response

Body
application/json
▼ replyobject
RESPONSE

```
{ "reply": null }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.14.25 | Edit Prevention Profile

post /public_api/v1/profiles/prevention/edit

Update an existing prevention profile with new configuration. At least one field in update_data (name, description, or modules) must be provided.

Note: Default profiles cannot be edited.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/profiles/prevention/edit'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"profile_id\":12345,\"update_data\":{\"description\":\"Updated description for the profile\",\"modules\":
{\"wildfire\":{\"status\":\"enabled\"}}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/profiles/prevention/edit", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/profiles/prevention/edit") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"profile_id\":12345,\"update_data\":{\"description\":\"Updated description for the
profile\",\"modules\":{\"wildfire\":{\"status\":\"enabled\"}}}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "profile_id": 12345, "update_data": { "description": "Updated description for the
profile", "modules": { "wildfire": { "status": "enabled" } } } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/profiles/prevention/edit"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/profiles/prevention/edit")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"profile_id\":12345,\"update_data\":{\"description\":\"Updated description for the
profile\",\"modules\":{\"wildfire\":{\"status\":\"enabled\"}}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "profile_id": 12345, "update_data": [ "description": "Updated
description for the profile", "modules": ["wildfire": ["status": "enabled"]] ] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/profiles/prevention/edit")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/profiles/prevention/edit", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"profile_id\":12345,\"update_data\":{\"description\":\"Updated description for the
profile\",\"modules\":{\"wildfire\":{\"status\":\"enabled\"}}}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/profiles/prevention/edit"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"profile_id\":12345,\"update_data\":
{\"description\":\"Updated description for the profile\",\"modules\":{\"wildfire\":{\"status\":\"enabled\"}}}}");
CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/profiles/prevention/edit"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"profile_id\":12345,\"update_data\":{\"description\":\"Updated description for the profile\",\"modules\":
{\"wildfire\":{\"status\":\"enabled\"}}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json
▼ profile_idintegerrequired

The ID of the profile to edit.

▼ update_dataobjectrequired
▶ namestring
▶ descriptionstring
▶ modulesobject

Updated configuration modules for the profile.

REQUEST
```
{ "profile_id": 12345, "update_data": { "description": "Updated description for the profile", "modules": { "wildfire":
{ "status": "enabled" } } } }
```
Responses

Successful response

Body
application/json
▼ replyboolean

True if the profile was successfully updated.

RESPONSE
```
{ "reply": true }
```

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.14.26 | Get Prevention Profile Modules

post /public_api/v1/profiles/prevention/get_modules

Get a list of modules for a specific prevention profile type and platform.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/profiles/prevention/get_modules'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"profile_type\":\"malware\",\"platform\":\"windows\"}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-
auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
```

```
"/public_api/v1/profiles/prevention/get_modules", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/profiles/prevention/get_modules") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"profile_type\":\"malware\",\"platform\":\"windows\"}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "profile_type": "malware", "platform": "windows" }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/profiles/prevention/get_modules"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/profiles/prevention/get_modules")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"profile_type\":\"malware\",\"platform\":\"windows\"}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [ "profile_type": "malware", "platform": "windows" ] as [String
: Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/profiles/prevention/get_modules")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/profiles/prevention/get_modules", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"profile_type\":\"malware\",\"platform\":\"windows\"}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/profiles/prevention/get_modules"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"profile_type\":\"malware\",\"platform\":\"windows\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/profiles/prevention/get_modules"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"profile_type\":\"malware\",\"platform\":\"windows\"}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

required

application/json

▼ profile_typestringrequired

The type of prevention profile.

▼ platformstringrequired

The platform (OS) for the profile.

REQUEST

```
{ "profile_type": "malware", "platform": "windows" }
```

Responses

Successful response

Body

application/json

▼ replyarray

[

]

RESPONSE

```
{ "reply": [ { "id": "additionalProcesses", "profile_type": "Exploit", "platform": "macOS", "pretty_name": "Exploit
Protection for Additional Processes", "schema": { "type": "object", "properties": { "mode": { "type": "string",
```

"enum": ["block", "report", "disabled"], "description": "Action Mode" }, "processes": { "type": "array", "items": { "type": "string", "description": "Path Array" } } }, "required": ["mode", "processes"], "additionalProperties": false } }] }

Bad Request. Invalid Input.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal Server Error.

2.1.14.27 | Edit prevention policy rules

post /public_api/v1/policies/prevention/edit

Updates one or more prevention policy rules. Each item in `edit_requests` specifies a rule by its 32-character hexadecimal UUID and includes the fields to modify. Only explicitly provided (non-null) fields are updated; all others remain unchanged.

Constraints

- The default (catch-all) rule (`is_any = true`) cannot be modified for `name`, `description`, or `target_filter`.
- Profile IDs must exist, correspond to the correct profile type (exploit, malware, restrictions, agent_settings, or exceptions), and match the OS platform of the target rule.
- Updates are applied atomically. If the policy has been modified since it was last retrieved, the request fails with a `409 Conflict` error due to stale data.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/policies/prevention/edit'
-d '{ "request_data" : { "edit_requests" : [ { "restrictions_id" : 5, "exceptions_id" : 7, "target_filter" : {
"filterData" : { "AND" : [ { "field" : "hostname", "value" : "DESKTOP-ABC123", "operator" : "EQ" }, { "field" :
"hostname", "value" : "DESKTOP-ABC123", "operator" : "EQ" } ] } }, "exploit_id" : 10, "malware_id" : 42,
"agent_settings_id" : 3, "name" : "My Custom Prevention Rule", "description" : "Applies to all Windows workstations in
Group A", "id" : "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4" }, { "restrictions_id" : 5, "exceptions_id" : 7, "target_filter" :
{ "filterData" : { "AND" : [ { "field" : "hostname", "value" : "DESKTOP-ABC123", "operator" : "EQ" }, { "field" :
"hostname", "value" : "DESKTOP-ABC123", "operator" : "EQ" } ] } }, "exploit_id" : 10, "malware_id" : 42,
"agent_settings_id" : 3, "name" : "My Custom Prevention Rule", "description" : "Applies to all Windows workstations in
Group A", "id" : "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4" } ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"edit_requests\":
[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My Custom Prevention Rule\",\"description\":\"Applies to all
Windows workstations in Group A\",\"target_filter\":{\"filterData\":{\"AND\":
[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}"
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/policies/prevention/edit", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/policies/prevention/edit") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"edit_requests\":[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My
Custom Prevention Rule\",\"description\":\"Applies to all Windows workstations in Group A\",\"target_filter\":
{\"filterData\":{\"AND\":[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
```

```
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "edit_requests": [ { "id": "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "name":
"My Custom Prevention Rule", "description": "Applies to all Windows workstations in Group A", "target_filter": {
"filterData": { "AND": [ { "field": "hostname", "operator": "EQ", "value": "DESKTOP-ABC123" } ] } }, "exploit_id": 10,
"malware_id": 42, "restrictions_id": 5, "agent_settings_id": 3, "exceptions_id": 7 } ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/policies/prevention/edit"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/policies/prevention/edit")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"edit_requests\":
[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My Custom Prevention Rule\",\"description\":\"Applies to all
Windows workstations in Group A\",\"target_filter\":{\"filterData\":{\"AND\":
[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["edit_requests": [ [ "id":
"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "name": "My Custom Prevention Rule", "description": "Applies to all Windows
workstations in Group A", "target_filter": ["filterData": ["AND": [ [ "field": "hostname", "operator": "EQ", "value":
"DESKTOP-ABC123" ] ]]], "exploit_id": 10, "malware_id": 42, "restrictions_id": 5, "agent_settings_id": 3,
"exceptions_id": 7 ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/policies/prevention/edit")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/policies/prevention/edit", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"edit_requests\":
[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My Custom Prevention Rule\",\"description\":\"Applies to all
Windows workstations in Group A\",\"target_filter\":{\"filterData\":{\"AND\":
[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/policies/prevention/edit"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"edit_requests\":
[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My Custom Prevention Rule\",\"description\":\"Applies to all
Windows workstations in Group A\",\"target_filter\":{\"filterData\":{\"AND\":
[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/policies/prevention/edit"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"edit_requests\":[{\"id\":\"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4\",\"name\":\"My Custom Prevention
Rule\",\"description\":\"Applies to all Windows workstations in Group A\",\"target_filter\":{\"filterData\":{\"AND\":
[{\"field\":\"hostname\",\"operator\":\"EQ\",\"value\":\"DESKTOP-
ABC123\"}]}},\"exploit_id\":10,\"malware_id\":42,\"restrictions_id\":5,\"agent_settings_id\":3,\"exceptions_id\":7}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```


Body parameters

required

application/json

▼ request_dataobject

▶ edit_requestsarrayrequired

List of policy rule edits to apply. All edits are validated before any change is persisted.

REQUEST rename_rule

```
{ "request_data": { "edit_requests": [ { "id": "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "name": "Updated Rule Name",
"malware_id": 42 } ] } }
{ "request_data": { "edit_requests": [ { "id": "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "target_filter": { "filterData": {
"AND": [ { "field": "hostname", "operator": "EQ", "value": "DESKTOP-ABC123" } ] } } } ] } }
{ "request_data": { "edit_requests": [ { "id": "a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "exploit_id": 10,
"restrictions_id": 5 }, { "id": "b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4e5", "description": "Updated description" } ] } }
```

Responses

All requested edits were applied successfully.

Body
application/json
▼ replyboolean

Always `true` on success.

Example:`true`

RESPONSE

```
{ "reply": true }
```

Bad request. Possible causes include:

- Missing required parameters (for example, `edit_requests` or `id`).
- Invalid field values (for example, incorrect type or empty string).
- Invalid `target_filter` structure.
- Unsupported filter field.
- Invalid operator for the specified filter field.
- Invalid value for the specified filter field.
- Attempt to modify metadata or `target_filter` of the default (catch-all) rule.
- Profile type does not match the expected type for the slot.
- Profile OS does not match the rule's platform.

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-aligned error code.

▶ err_msgstring

Human-readable error message.

▶ err_extraobject

Additional context about the error (field names, IDs, invalid values, etc.). Shape varies by error type.

RESPONSE missing_edit_requests

```
{ "reply": { "err_code": 400, "err_msg": "A mandatory parameter is missing.", "err_extra": { "field_name":
"edit_requests" } } }
{ "reply": { "err_code": 400, "err_msg": "A mandatory parameter is missing.", "err_extra": { "field_name": "id" } } }
{ "reply": { "err_code": 400, "err_msg": "Invalid target filter fields in target filter", "err_extra": { "rule_id":
"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "invalid_fields": [ "unsupported_field" ] } } }
{ "reply": { "err_code": 400, "err_msg": "This policy rule edit operation is not allowed", "err_extra": { "rule_id":
"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "reason": "Default rule metadata cannot be edited" } } }
```

A referenced rule ID or profile ID was not found.

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-aligned error code.

▶ err_msgstring

Human-readable error message.

▶ err_extraobject

Additional context about the error (field names, IDs, invalid values, etc.). Shape varies by error type.

RESPONSE rule_not_found

```
{ "reply": { "err_code": 404, "err_msg": "The specified rule was not found.", "err_extra": { "rule_id":
"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4" } } }
{ "reply": { "err_code": 404, "err_msg": "The profile ID was not found", "err_extra": { "rule_id":
"a1b2c3d4e5f6a1b2c3d4e5f6a1b2c3d4", "profile_id": 99 } } }
```

Stale data conflict. The policy was modified by another actor since it was last read. Retry the operation.

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-aligned error code.

▶ err_msgstring

Human-readable error message.

▶ err_extraobject

Additional context about the error (field names, IDs, invalid values, etc.). Shape varies by error type.

RESPONSE

```
{ "reply": { "err_code": 409, "err_msg": "The policy update failed because the policy was changed since the last read.
Retry the operation.\n" } }
```

Internal server error. The policy update failed for an unexpected reason, or the saved policy failed internal validation.

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-aligned error code.

▶ err_msgstring

Human-readable error message.

▶ err_extraobject

Additional context about the error (field names, IDs, invalid values, etc.). Shape varies by error type.

RESPONSE

```
{ "reply": { "err_code": 400, "err_msg": "A mandatory parameter is missing.", "err_extra": {} } }
```

2.1.15 | IOCs

APIs for managing IOCs

2.1.15.1 | Get Indicators (IOCs)

post /public_api/v1/indicators/get

Get a list of IOCs. You can return all IOCs or filter results. You can also return extended results with all details included.

- The response is concatenated using AND condition (OR is not supported).
- The maximum result set size is >100.
- Offset is the zero-based number of incidents from the start of the result set.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/indicators/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"extended_view\":true,\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":
[null]}],\"search_from\":0,\"search_to\":0}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/indicators/get",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/indicators/get") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":[null]}],\"search_from\":0,\"search_to\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "extended_view": true, "filters": [ { "field": "indicator",
"operator": "EQ", "value": [ null ] } ], "search_from": 0, "search_to": 0 } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/indicators/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/indicators/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":[null]}],\"search_from\":0,\"search_to\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "extended_view": true, "filters": [ [
"field": "indicator", "operator": "EQ", "value": [] ] ], "search_from": 0, "search_to": 0 ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/indicators/get")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/indicators/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"extended_view\":true,\"filters\":
[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":[null]}],\"search_from\":0,\"search_to\":0}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/indicators/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"extended_view\":true,\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":
[null]}],\"search_from\":0,\"search_to\":0}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/indicators/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"extended_view\":true,\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":
[null]}],\"search_from\":0,\"search_to\":0}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ extended_viewboolean

▶ filtersarray

An array of filter fields.

▶ search_frominteger

Integer representing the starting offset within the query result set from which you want indicators returned. Indicators are returned as a zero-based list. Any indicator indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

Integer representing the end offset within the result set after which you do not want indicators returned. Indicators in the indicator list that are indexed higher than this value are not returned in the final results set. Defaults to >100, which returns all indicators to the end of the list.

REQUEST

Example 1


```
{ "request_data": { "extended_view": false, "filters": [ { "field": "rule_id", "operator": "IN", "value": [ 57 ] } ] }
}
```


Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsarray

[

▶ rule_idinteger

▶ indicatorstring

▶ typestring

▶ severitystring

▶ expiration_dateinteger

▶ commentstring

]

▼ objects_typestring

RESPONSE

Example 1


```
{ "objects_count": 1, "objects": [ { "rule_id": 57, "indicator": "virus1.exe", "type": "FILENAME", "severity":
"SEV_040_HIGH", "expiration_date": -1, "comment": "test", "reputation": null, "reliability": null } ], "objects_type":
"indicator" }
```


Bad Request. Got invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.15.2 | Insert or update IOCs

post /public_api/v1/indicators/insert

Insert new IOCs or update existing IOCs.

Note: The IOC `rule_id` is tenant specific and can't be used across tenants. Inserting IOCs with the same `rule_id` as an existing IOC on that tenant will overwrite the existing IOC.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/indicators/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/indicators/insert", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/indicators/insert")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": [ { "rule_id": 0, "indicator": "string", "type": "HASH", "severity":
"SEV_010_INFO", "expiration_date": 0, "default_expiration_enabled": true, "comment": "string", "reputation": "GOOD",
"reliability": "A" } ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/indicators/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/indicators/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ [ "rule_id": 0, "indicator": "string",
"type": "HASH", "severity": "SEV_010_INFO", "expiration_date": 0, "default_expiration_enabled": true, "comment":
"string", "reputation": "GOOD", "reliability": "A" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/indicators/insert")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/indicators/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
```

```
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/indicators/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/indicators/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
[{\"rule_id\":0,\"indicator\":\"string\",\"type\":\"HASH\",\"severity\":\"SEV_010_INFO\",\"expiration_date\":0,\"default_expira
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataarrayrequired

[

▶ rule_idnumber

▶ indicatorstring

▶ typeobject (Enum)

▶ severityobject (Enum)

▶ expiration_dateinteger

▶ default_expiration_enabledboolean

▶ commentstring

▶ reputationobject (Enum)

▶ reliabilityobject (Enum)

]

REQUEST

Example 1

```
{ "request_data": [ { "indicator": "virus1.exe", "type": "FILENAME", "severity": "SEV_040_HIGH", "expiration_date":
1234567891234, "default_expiration_enabled": false, "comment": "teststeststsetesteste", "reputation": null,
"reliability": null }, { "indicator": "test.exe", "type": "FILENAME", "severity": "SEV_030_MEDIUM", "expiration_date":
1234567891234, "default_expiration_enabled": true, "reputation": null, "reliability": null } ] }
```

Responses

OK

Body

application/json

▼ added_objectsarray

List of IOC objects added.

[

▶ idinteger

▶ statusstring

]

▼ updated_objectsarray

List of IOC objects updated.

[

▶ idinteger

▶ statusstring

]

▼ errorsarray[string]

List of errors, if any.

RESPONSE

Example 1

```
{ "added_objects": [ { "id": 69, "status": "Created a new IOC rule with the ID: 69 successfully" } ],
"updated_objects": [ { "id": 57, "status": "Updated the IOC rule with the indicator: 'virus1.exe' successfully" } ],
"errors": [] }
```

Bad Request. Got invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.15.3 | Delete Indicators (IOCs)

post /public_api/v1/indicators/delete

Delete IOCs selected by filter.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/indicators/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-
xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/indicators/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/indicators/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}" response = http.request(request) puts
response.read_body
```

```
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "indicator", "operator": "EQ", "value": 0 } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/indicators/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/indicators/delete") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "indicator", "operator": "EQ", "value": 0 ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/indicators/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/indicators/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/indicators/delete"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/indicators/delete"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"indicator\",\"operator\":\"EQ\",\"value\":0}]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example 1

```
{ "request_data": { "extended_view": false, "filters": [ { "field": "rule_id", "operator": "EQ", "value": 57 } ] } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

▼ objectsarray[integer]

RESPONSE

Example 1

```
{ "objects_count": 1, "objects": [ 57 ] }
```

Bad Request. Got invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.16 | Issues

APIs for managing issues

2.1.16.1 | Create a new issue

post /public_api/v1/issue

This endpoint allows users to create a new issue by providing the necessary details. Users can only create one issue at a time.

- The request must include the following required fields:
  - `name`
  - `description`
  - `observation_time`
  - `domain`
  - `category`

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue'
-d ''
```

Body parameters
required
application/json
▼ request_dataobject
▶ issueobject
REQUEST create_basic_issue

{ "request_data": { "issue": { "name": "Unauthorized Access Detected", "description": "An unauthorized login attempt was detected from an unknown IP address.", "observation_time": 1700000000000, "domain": "SECURITY", "category": "CONFIGURATION", "severity": "HIGH" } } }
{ "request_data": { "issue": { "name": "Publicly Exposed Database", "description": "PostgreSQL database instance is publicly accessible on port 5432.", "observation_time": 1700000000000, "domain": "Cloud Security", "category": "CONFIGURATION", "severity": "CRITICAL", "owner": "CWP", "type": "Cloud Security", "remediation": "Restrict database access to private subnets only.", "impact": "Potential unauthorized access to sensitive data.", "extended_description": "The database instance has a security group allowing inbound traffic from 0.0.0.0/0 on port 5432.", "initial_evidence": "Security group sg-12345 allows inbound TCP/5432 from 0.0.0.0/0", "asset_ids": ["asset-db-001"], "mitre_tactics": ["TA0001"], "mitre_techniques": ["T1190"], "tags": ["critical", "database", "public-access"], "assigned_to": "security_team_lead", "assigned_to_pretty": "Alice Smith", "is_starred": true, "is_excluded": false } } }
Responses

Issue created successfully

Body
application/json
▼ external_idstring
▼ detection_methodstring
RESPONSE
{ "external_id": "7c96737d50f74c7b9487450426e9eafb", "detection_method": "CREATE_ALERT_PUBLIC_API" }

Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE
{ "error": "Invalid request data" }

Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE
{ "error": "Unauthorized request" }

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE
{ "error": "Internal server error" }

2.1.16.2 | Retrieve issues based on filters

post /public_api/v1/issue/search

This endpoint retrieves a list of issues that match the specified filter criteria. It supports filtering along with sorting and pagination.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue/search'
-d ''
```

Body parameters
required
application/json
▼ request_dataobject
▶ filtersarray
▼ search_frominteger

Starting index for pagination.

▼ search_tointeger

Ending index for pagination.

Default:`100`
▼ sortobject
▶ fieldstring (Enum)
▶ keywordstring (Enum)

Sort order (ascending or descending).

▼ include_fieldsarray[string]

A list of fields to include in the response.

- `normalized_fields`: Includes normalized fields in the response.
- `custom_fields`: Includes custom user-defined fields in the response.
- By default these fields will not be part of response payload.

REQUEST search_by_severity

```
{ "request_data": { "filters": [ { "field": "severity", "operator": "in", "value": [ "HIGH", "CRITICAL" ] } ] },
"search_from": 0, "search_to": 50, "sort": { "field": "observation_time", "keyword": "desc" } }
{ "request_data": { "filters": [ { "field": "_insert_time", "operator": "gte", "value": 1700000000000 }, { "field":
"_insert_time", "operator": "lte", "value": 1700100000000 } ] }, "search_from": 0, "search_to": 100 }
{ "request_data": { "filters": [ { "field": "status.progress", "operator": "eq", "value": "New" }, { "field":
"issue_domain", "operator": "in", "value": [ "Cloud Security" ] } ] }, "search_from": 0, "search_to": 100,
"include_fields": [ "normalized_fields", "custom_fields" ] }
{ "request_data": { "filters": [ { "field": "id", "operator": "in", "value": [ 123, 456, 789 ] } ] } }
{ "request_data": { "filters": [ { "field": "detection.method", "operator": "in", "value": [ "CSPM_SCANNER",
"CREATE_ALERT_PUBLIC_API" ] } ] }, "sort": { "field": "severity", "keyword": "desc" } }
{ "request_data": { "filters": [ { "field": "asset_names", "operator": "in", "value": [ "my-server-01", "my-database-
prod" ] }, { "field": "asset_cloud_account_names", "operator": "in", "value": [ "production-account" ] } ] } }
```

Responses

Successful response with issues

Body
application/json
▼ replyobject
▶ total_countinteger
▶ result_countinteger
▶ issuesarray

RESPONSE

```
{ "reply": { "total_count": 1500, "result_count": 2, "issues": [ { "_insert_time": "2024-01-15T10:30:00Z", "owner":
"CWP", "external_id": "abc-12345-def", "name": "Publicly Exposed Storage Bucket", "description": "S3 bucket my-data-
bucket is publicly accessible", "observation_time": 1705312200000, "domain": "Cloud Security", "detection_method":
"CSPM_SCANNER", "detection_rule_id": "RULE-S3-PUBLIC", "category": "CONFIGURATION", "finding_ids": [ "f1a2b3c4d5" ],
"asset_ids": [ "a8d24e796ef264a33e6e84c707ff2f67" ], "asset_names": [ "my-data-bucket" ], "asset_group_ids": [ 5, 42
], "asset_classes": [ "Data" ], "asset_categories": [ "Storage Bucket" ], "asset_regions": [ "us-east-1" ],
"asset_providers": [ "AWS" ], "asset_accounts": [ "883588134481" ], "asset_types": [ "S3 Bucket" ],
"asset_external_provider_ids": [ "arn:aws:s3:::my-data-bucket" ], "asset_cloud_account_names": [ "production-account"
], "mitre_tactics": [ "TA0001 - Initial Access" ], "mitre_techniques": [ "T1190 - Exploit Public-Facing Application"
], "type": "Cloud Security", "remediation": "Restrict public access on the S3 bucket", "extended_description": "The
bucket allows unauthenticated read access to all objects.", "impact": "Potential data exposure of sensitive customer
records", "id": 12345, "last_modified": 1705315800000, "tags": [ "critical", "data-exposure" ], "is_excluded": false,
```

"is_starred": true, "assigned_to": "alice.smith@example.com", "assigned_to_pretty": "Alice Smith", "status": "New", "severity": "HIGH", "case_ids": [101], "is_excepted": false, "action_status": "pending" }] } }

Bad request

Body
application/json
▼ errorstring
Example:"Invalid request data"
RESPONSE
{ "error": "Invalid request data" }

Unauthorized access

Body
application/json
▼ errorstring
Example:"Unauthorized request"
RESPONSE
{ "error": "Unauthorized request" }

Internal server error

Body
application/json
▼ errorstring
Example:"Internal server error"
RESPONSE
{ "error": "Internal server error" }

2.1.16.3 | Update existing issue

post /public_api/v1/issue/{issue-id}

Update an existing issue in the system. Users can only update one issue at a time.

- At least one of the following fields is mandatory:
  - severity
  - status

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ issue-id Integer required

Numeric ID of the user to get

Example: 56
Request headers
▼ Authorization String required

{api_key}

Example: authorization_example
▼ x-xdr-auth-id String required

{api_key_id}

Example: xXdrAuthId_example
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue/{issue-id}'
-d ''
```
Body parameters
required
application/json
▼ request_dataobject
▶ update_dataobject

At least one of `severity` or `status` must be provided. When setting `status` to `Resolved`, the `status_resolution_reason` field is required.

REQUEST update_severity_only

```
{ "request_data": { "update_data": { "severity": "CRITICAL" } } }
{ "request_data": { "update_data": { "status": "In Progress" } } }
{ "request_data": { "update_data": { "status": "Resolved", "status_resolution_reason": "RESOLVED_FALSE_POSITIVE",
"status_resolution_comment": "Verified this is a false positive after investigation." } } }
{ "request_data": { "update_data": { "severity": "HIGH", "status": "Resolved", "status_resolution_reason":
"RESOLVED_KNOWN_ISSUE", "status_resolution_comment": "Known issue tracked in internal ticket." } } }
```

Responses

Issues updated successfully

Bad request

Body
application/json
▼ errorstring
Example: `"Invalid request data"`
RESPONSE

```
{ "error": "Invalid request data" }
```

Unauthorized access

Body
application/json
▼ errorstring
Example: `"Unauthorized request"`
RESPONSE

```
{ "error": "Unauthorized request" }
```

Internal server error

Body
application/json
▼ errorstring
Example: `"Internal server error"`
RESPONSE

```
{ "error": "Internal server error" }
```

2.1.16.4 | Retrieve issue schema

post /public_api/v1/issue/schema

This endpoint retrieves the schema definition for issues, including core fields, normalized fields, and custom fields. Each field includes its name, pretty name, and data type.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/issue/schema'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") conn.request("POST",
"/public_api/v1/issue/schema") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/issue/schema") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/issue/schema");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/issue/schema") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/issue/schema")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/issue/schema", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/issue/schema"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/issue/schema"); var request = new
RestRequest(Method.POST); IRestResponse response = client.Execute(request);
```

Responses

Successful response with issue schema

Body
application/json
▼ replyobject
▶ dataarray
RESPONSE


```
{ "reply": { "data": [ { "field_name": "xdm.issue.name", "field_pretty_name": "Name", "data_type": "TEXT" }, {
"field_name": "xdm.issue.a_normalized_field", "field_pretty_name": "A normalized field", "data_type": "TEXT" }, {
"field_name": "my_custom_field", "field_pretty_name": "My custom field", "data_type": "boolean" } ] } }
```


Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE


```
{ "error": "Unauthorized request" }
```


Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE


```
{ "error": "Internal server error" }
```

2.1.16.5 | Create a new issue exception

post /public_api/v1/issue_exceptions/

This endpoint allows users to create a new issue exception by providing the necessary details. Users can only create one exception at a time.

- The request must include the following required fields:
  - `name`
  - `rule`
  - `justification_text`
  - `justification_category`
  - `expiration_ts`
  - `approver_email`
- Optional fields:
  - `external_exception_id`

If the tenant has approval required enabled, the `approver_email` field is mandatory and the exception will be created with `Pending Status` status. Otherwise, the exception is `Self Approved` automatically.

The `requestor_name` and `requestor_email` fields are automatically populated from the API key context.

Required permission: `Exception Management Admin View/Edit`, `Exception Approver Admin View/Edit`

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}
Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue_exceptions/'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-
type': "application/json" } conn.request("POST", "%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/", payload, headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"]
= 'application/json' request.body = "{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "external_exception_id": "string", "rule": "string",
"justification_text": "string", "justification_category": "COMPENSATING_CONTROL", "approval_justification": "string",
"approver_email": "string", "expiration_ts": "2019-08-24T14:15:22Z" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "name": "string", "external_exception_id":
"string", "rule": "string", "justification_text": "string", "justification_category": "COMPENSATING_CONTROL",
"approval_justification": "string", "approver_email": "string", "expiration_ts": "2019-08-24T14:15:22Z" ]] as [String
: Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json",
"x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl);
if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
```

```
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"name\":\"string\",\"external_exception_id\":\"string\",\"rule\":\"string\",\"justification_text\":\"string\",\"justification
08-24T14:15:22Z\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

Request data for creating a new issue exception.

▶ namestringrequired

Human-readable name for the exception

▶ external_exception_idstring

Optional external tracking ID for the exception

▶ rulestringrequired

JSON-encoded filter rule defining which issues this exception applies to. Uses the standard Cortex filter format with AND/OR structure.

▶ justification_textstringrequired

Free-text justification explaining why this exception is needed

▶ justification_categorystring (Enum)required

Category of justification for the exception

▶ approval_justificationstring

Free-text justification explaining why this exception is approved or rejected

▶ approver_emailstringrequired

Email of the designated approver. Required when the tenant has approval workflow enabled. Must match a registered approver.

▶ expiration_tsstringrequireddate-time

Expiration date/time for the exception. Accepts ISO 8601 date-time or date-only format. Date-only values are normalized to end-of-day UTC (23:59:59).

REQUEST basic_issue_exception

```
{ "request_data": { "name": "CVE-2024-1234 Exception for legacy hosts", "rule": "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"cve_id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"CVE-2024-1234\"}]}}", "justification_text":
"Legacy hosts scheduled for decommission in Q2", "justification_category": "RISK_ACCEPTED", "approver_email":
"security-lead@example.com", "expiration_ts": "2025-06-30" } }
{ "request_data": { "name": "Compensating control for CVE-2024-5678", "external_exception_id": "JIRA-SEC-4567",
"rule": "{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"cve_id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"CVE-2024-
5678\"}]}}", "justification_text": "WAF rule deployed as compensating control", "justification_category":
"COMPENSATING_CONTROL", "approver_email": "security-lead@example.com", "expiration_ts": "2025-12-31T23:59:59Z" } }
{ "request_data": { "name": "CVE-2024-1234 Exception for legacy hosts", "rule": "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"cve_id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"CVE-2024-1234\"}]}}", "justification_text":
"Legacy hosts scheduled for decommission in Q2", "justification_category": "RISK_ACCEPTED", "expiration_ts": "2025-06-
30" } }
```

Responses

Exception created successfully

Body

application/json

▼ replyobject

▶ exception_idinteger

ID of the newly created exception

RESPONSE

default

```
{ "reply": { "exception_id": 42 } }
```

Bad request

Body

application/json

▼ errorstring

Example:`"Invalid request data"`
RESPONSE
```
{ "error": "Invalid request data" }
```

Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE
```
{ "error": "Unauthorized request" }
```

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE
```
{ "error": "Internal server error" }
```

2.1.16.6 | Disable an issue exception

post /public_api/v1/issue_exceptions/disable/

This endpoint allows users to disable an existing issue exception. This will trigger a reversion scan to restore matching issues that were previously suppressed by this exception. A disabled exception cannot be reactivated.

Required permission: `Exception Management Admin View/Edit`, `Exception Approver Admin View/Edit`

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue_exceptions/disable/'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"exception_id\":0}}"
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"]
= 'application/json' request.body = "{\"request_data\":{\"exception_id\":0}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "exception_id": 0 } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
```

```
"application/json") .body("{\"request_data\":{\"exception_id\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["exception_id": 0]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"exception_id\":0}}", CURLOPT_HTTPHEADER
=> [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"exception_id\":0}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/disable/"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"exception_id\":0}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ exception_idintegerrequired

ID of the issue exception to disable

REQUEST
default

```
{ "request_data": { "exception_id": 26 } }
```

Responses

Exception disabled successfully

Body
application/json
▼ replyobject
▶ rows_affectedinteger

Number of database rows affected

▶ statusstring

New status of the exception

RESPONSE
default

```
{ "reply": { "rows_affected": 1, "status": "DISABLED" } }
```

Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE

```
{ "error": "Invalid request data" }
```

Unauthorized access

Body
application/json
▼ errorstring

Example:`"Unauthorized request"`
RESPONSE
```
{ "error": "Unauthorized request" }
```

Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE
```
{ "error": "Internal server error" }
```

2.1.16.7 | Retrieve issue exceptions based on filters

post /public_api/v1/issue_exceptions/search/

This endpoint retrieves a list of issue exceptions that match the specified filter criteria. It supports filtering along with sorting and pagination.

Required permission: `Exception Management Admin View`, `Exception Approver Admin View`

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/issue_exceptions/search/'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"]
= 'application/json' request.body = "{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": { "SEARCH_FIELD": "EXCEPTION_ID", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "string" }, "search_from": 0, "search_to": 100, "sort": { "FIELD": "string", "ORDER": "ASC" } } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ "SEARCH_FIELD": "EXCEPTION_ID",
```

```
"SEARCH_TYPE": "EQ", "SEARCH_VALUE": "string" ], "search_from": 0, "search_to": 100, "sort": [ "FIELD": "string",
"ORDER": "ASC" ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: [])
let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-
type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7B%7Bfqdn%7D%7D/public_api/v1/issue_exceptions/search/"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":
{\"SEARCH_FIELD\":\"EXCEPTION_ID\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"string\"},\"search_from\":0,\"search_to\":100,\"so
{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```


Body parameters

application/json

▼ request_dataobject

▶ filtersobject

Filter criteria using AND/OR structure. Each filter condition contains SEARCH_FIELD, SEARCH_TYPE, and SEARCH_VALUE.

▶ search_frominteger

Starting index for pagination.

▶ search_tointeger

Ending index for pagination.

▶ sortobject

Sort configuration

REQUEST default_search


```
{ "request_data": {} }
{ "request_data": { "filters": { "AND": [ { "SEARCH_FIELD": "STATUS", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "APPROVED"
} ] }, "search_from": 0, "search_to": 50, "sort": { "FIELD": "EXCEPTION_ID", "ORDER": "DESC" } } }
{ "request_data": { "filters": { "AND": [ { "SEARCH_FIELD": "NAME", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "CVE-
2024" } ] }, "search_from": 0, "search_to": 25 } }
```


Responses

Exceptions retrieved successfully

Body

application/json

▼ replyobject

▶ exceptionsarray

List of matching exception objects

▶ filter_countinteger

Number of exceptions matching the applied filters

▶ total_countinteger

Total number of exceptions (ignoring filters)
RESPONSE
default

```
{ "reply": { "exceptions": [ { "exception_id": 1, "external_exception_id": null, "name": "CVE-2024-1234 Exception",
"status": "APPROVED", "rule": "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"cve_id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"CVE-2024-1234\"}]}}", "pretty_rule": "
[\"cve_id = CVE-2024-1234\"]", "justification_text": "Risk accepted for legacy hosts", "justification_category":
"RISK_ACCEPTED", "approval_justification": null, "requestor_name": "John Doe", "requestor_email":
"john.doe@example.com", "approver_email": "security-lead@example.com", "approver_name": "Jane Smith", "created_ts":
"2025-01-15T10:30:00Z", "modified_ts": "2025-01-15T10:30:00Z", "approval_ts": "2025-01-15T11:00:00Z", "expiration_ts":
"2025-06-30T23:59:59Z", "impacted_issues_count": 150, "backward_scan_status": "COMPLETED", "backward_scan_ts": "2025-
01-15T11:05:00Z", "reversion_scan_status": null, "reversion_scan_ts": null } ], "filter_count": 1, "total_count": 10 }
}
```


Bad request

Body
application/json
▼ errorstring
Example:`"Invalid request data"`
RESPONSE

```
{ "error": "Invalid request data" }
```


Unauthorized access

Body
application/json
▼ errorstring
Example:`"Unauthorized request"`
RESPONSE

```
{ "error": "Unauthorized request" }
```


Internal server error

Body
application/json
▼ errorstring
Example:`"Internal server error"`
RESPONSE

```
{ "error": "Internal server error" }
```

2.1.17 | Lookup Datasets

APIs for lookup datasets

2.1.17.1 | Add or update data in a lookup dataset

post /public_api/v1/xql/lookups/add_data

Add or update data in a lookup dataset.

When updating data, any field not specified in the `data` field, but specified on at least one of the rows, will be set to `None`.

The `/public_api/xql/lookups/add_data/` endpoint does not support concurrent edits. Sending concurrent calls to this endpoint can cause data to be unintentionally overwritten or deleted. To allow sufficient time for each API call to complete its operation before initiating another one, assume that 1000 entries can be added per API every 10 seconds.

**Note: **

- The maximum size of a lookup dataset is 50 MB. Attempting to exceed this limit will fail.
- Requests time out after three minutes.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}
Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/lookups/add_data'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/xql/lookups/add_data", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/xql/lookups/add_data") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "key_fields": [ "string" ], "data": {
"property1": "string", "property2": "string" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/lookups/add_data");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/lookups/add_data")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string", "key_fields":
["string"], "data": [ "property1": "string", "property2": "string" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/lookups/add_data")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/lookups/add_data", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/lookups/add_data"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/lookups/add_data"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dataset_name\":\"string\",\"key_fields\":[\"string\"],\"data\":
{\"property1\":\"string\",\"property2\":\"string\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject
▶ dataset_namestringrequired

Unique dataset name

▶ key_fieldsarray[string]

The fields used to identify existing records. If there is not an exact match to the key_fields specified, a new row is created. When you specify `key_fields`, these fields are mandatory in data entries. When `key_fields` are not specified, existing data entries are not updated, and new entries are added with the specified data.

▶ dataobjectrequired

Key-value pairs of data entries.

REQUEST
Example 1
```
{ "request_data": { "dataset_name": "users", "key_fields": [ "uid", "username" ], "data": [ { "uid": "123abc", "username": "john", "zipcode": 58672, "salary": 5.1, "is_admin": false, "birthday": "31-05-1982T10:22:45Z" }, { "uid": "124abc", "username": "jane", "zipcode": 58642, "salary": 5000000, "is_admin": true, "birthday": "31-03-1982T10:22:45Z" } ] } }
```
Responses

OK

Body
application/json
▼ addedinteger
▼ updatedinteger
▼ skippedinteger
RESPONSE
```
{ "added": 0, "updated": 0, "skipped": 0 }
```

2.1.17.2 | Remove data from a lookup dataset

post /public_api/v1/xql/lookups/remove_data

Remove data from a dataset based on the specified parameters. If any one of the filter sets are not found, the API does not delete any data.

The `/public_api/xql/lookups/remove_data/` endpoint does not support concurrent edits. Sending concurrent calls to this endpoint can cause data to be unintentionally overwritten or deleted. To allow sufficient time for each API call to complete its operation before initiating another one, assume that 1000 entries can be added per API every 10 seconds.

Note:

- All lookup entries matching any of the filter blocks are deleted. To match a filter block, a lookup entry must match all the specified fields as if there were an `AND` operator between them.
- Requests time out after three minutes.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/lookups/remove_data'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"dataset_name\":\"string\",\"filters\":{\"property1\":\"string\",\"property2\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/xql/lookups/remove_data", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/xql/lookups/remove_data") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
```

```
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
{\"property1\":\"string\",\"property2\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "filters": { "property1": "string",
"property2": "string" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/lookups/remove_data");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/lookups/remove_data")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
{\"property1\":\"string\",\"property2\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string", "filters": [
"property1": "string", "property2": "string" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/lookups/remove_data")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/lookups/remove_data", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
{\"property1\":\"string\",\"property2\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/lookups/remove_data"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"dataset_name\":\"string\",\"filters\":{\"property1\":\"string\",\"property2\":\"string\"}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/lookups/remove_data"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dataset_name\":\"string\",\"filters\":{\"property1\":\"string\",\"property2\":\"string\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject
▶ dataset_namestringrequired

The name of the dataset to delete.

▶ filtersobjectrequired

Key-value pairs of fields to query in datasets. A lookup entry must match all the specified fields as if there were an **AND** operator between them. You can use one or more fields, up to the number of fields in the schema.

REQUEST
Example 1

```
{ "request_data": { "dataset_name": "users", "filters": [ { "uid": "123", "username": "john" }, { "uid": "124",
"zipcode": 58672 } ] } }
```

Responses

OK

Body
application/json
▼ deletedinteger

Number of entries deleted successfully.

RESPONSE

```
{ "deleted": 0 }
```

2.1.17.3 | Get data from a lookup dataset

post /public_api/v1/xql/lookups/get_data

Get data from a lookup dataset according to the specified filter fields. All lookup entries matching any of the filter blocks are returned. To match a filter block, a lookup entry must match all the specified fields as if there were an `AND` operator between them. If no filters are specified, return all lookup entries.

Note:

- The maximum number of entries returned is 10,000.
- Requests time out after three minutes.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/lookups/get_data'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dataset_name\":\"string\",\"filters\":[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}" headers
= { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/xql/lookups/get_data", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/xql/lookups/get_data") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "filters": [ { "property1": "string",
"property2": "string" } ], "limit": 0 } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/lookups/get_data");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/lookups/get_data")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string", "filters": [ [
"property1": "string", "property2": "string" ] ], "limit": 0 ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/lookups/get_data")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/lookups/get_data", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
```

```
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/lookups/get_data"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"dataset_name\":\"string\",\"filters\":[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/lookups/get_data"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dataset_name\":\"string\",\"filters\":
[{\"property1\":\"string\",\"property2\":\"string\"}],\"limit\":0}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ dataset_namestringrequired

Name of the dataset to query.

▶ filtersarray

Key-value pairs of fields to query in a dataset. A lookup entry must match all the specified fields as if there were an `AND` operator between them. You can use one or more fields, up to the number of fields in the schema.

▶ limitinteger

The maximum number of results to return. If this is not specified, return all lookup entries that match the filter criteria.

REQUEST

Example 1

```
{ "request_data": { "dataset_name": "users", "filters": [ { "uid": "123", "username": "john" }, { "department": "dev",
"zipcode": "58674" } ], "limit": 20 } }
```

Responses

OK

Body

application/json

▼ dataobject

▶ Additional propertiesstring

▼ filter_countinteger

Number of entries that match the filter.

▼ total_countinteger

Total number of entries.

RESPONSE

Example 1

```
{ "reply": { "data": [ { "uid": "uid5", "salary": 5.1, "zipcode": 70005, "birthday": 386418165000, "is_admin": true,
"username": "username5", "_insert_time": 1718807765000, "_update_time": 1718807765000, "_collector_name": "Console",
"_collector_type": "Console" }, { "uid": "uid6", "salary": 6.1, "zipcode": 70006, "birthday": 386418165000,
"is_admin": true, "username": "username6", "_insert_time": 1718807765000, "_update_time": 1718807765000,
"_collector_name": "Console", "_collector_type": "Console" } ], "filter count": 2, "total count": 10 } }
```

2.1.18 | Playbooks

APIs for managing playbooks

2.1.18.1 | Get a playbook

post /public_api/v1/playbooks/get

Get a playbook by filtering based on its name or ID. The playbook's YAML is returned in a ZIP file.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/playbooks/get'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/playbooks/get",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/playbooks/get") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "filter": { "field": "id", "value": "string" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/playbooks/get"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/playbooks/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filter": [ "field": "id", "value": "string"
]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/playbooks/get")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/playbooks/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", CURLOPT_HTTPHEADER =>
[ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/playbooks/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/playbooks/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filterobject

Filter fields.
REQUEST
Example 1
```
{ "request_data": { "filter": { "field": "name", "value": "Phishingplaybook" } } }
```
Responses

OK

2.1.18.2 | Insert or update playbooks

post /public_api/v1/playbooks/insert

Add or update a playbook by passing the YAML in a ZIP file.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
Form parameters
▼ file File
format: binary
Example: `BINARY_DATA_HERE`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/playbooks/insert'
-F 'file=@</path/to/file>'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "----
-011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n----
-011000010111000001101001--\r\n" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE" } conn.request("POST", "/public_api/v1/playbooks/insert", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/playbooks/insert")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request.body = "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n----
-011000010111000001101001--\r\n" response = http.request(request) puts response.read_body
const data = new FormData(); data.append("file", "string"); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/playbooks/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/playbooks/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"multipart/form-data; boundary=---011000010111000001101001") .body("-----011000010111000001101001\r\nContent-
Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "multipart/form-data" ] let parameters = [ [ "name": "file", "value": "string" ] ] let boundary = "--
-011000010111000001101001" var body = "" var error: NSError? = nil for param in parameters { let paramName =
param["name"]! body += "--\(boundary)\r\n" body += "Content-Disposition:form-data; name=\"\(paramName)\"" if let
filename = param["fileName"] { let contentType = param["content-type"]! let fileContent = String(contentsOfFile:
filename, encoding: String.Encoding.utf8) if (error != nil) { print(error) } body += "; filename=\"\(filename)\"\r\n"
body += "Content-Type: \(contentType)\r\n\r\n" body += fileContent } else if let paramValue = param["value"] { body +=
"\r\n\r\n\(paramValue)" } } let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/playbooks/insert")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
```

```
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/playbooks/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "-----011000010111000001101001\r\nContent-Disposition: form-data;
name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: multipart/form-data; boundary=---011000010111000001101001", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/playbooks/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: multipart/form-data; boundary=--
-011000010111000001101001"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-
----011000010111000001101001--\r\n"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/playbooks/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "multipart/form-data; boundary=---011000010111000001101001");
request.AddParameter("multipart/form-data; boundary=---011000010111000001101001", "----
-011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n----
-011000010111000001101001--\r\n", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Responses

OK

Body
application/json
▼ objects_countinteger

The number of playbooks identified and attempted to be added.

▼ objectsobject
▶ failures_itemsarray

This field in the response indicates that the playbook IDs listed failed to be added.

RESPONSE

```
{ "objects_count": 0, "objects": { "failures_items": [ { "error": "example", "id": "example" } ] } }
```

2.1.18.3 | Delete a playbook

post /public_api/v1/playbooks/delete

Delete a playbook by filtering based on its name or ID.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/playbooks/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
```

```
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/playbooks/delete",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/playbooks/delete")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filter": { "field": "id", "value": "string" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/playbooks/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/playbooks/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filter": [ "field": "id", "value": "string"
]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/playbooks/delete")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/playbooks/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", CURLOPT_HTTPHEADER =>
[ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/playbooks/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/playbooks/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filterobject

Filter fields.

REQUEST

Example 1

```
{ "request_data": { "filter": { "field": "name", "value": "Phishingplaybook" } } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

The number of playbooks identified and attempted to be deleted.

▼ objectsobject

▶ failures_itemsarray

This field in the response indicates that the playbook IDs listed failed to be deleted.

▶ succeeded_itemsarray

This field in the response indicates that the playbook IDs listed were successfully deleted.
RESPONSE

```
{ "objects_count": 0, "objects": { "failures_items": [ { "error": "example", "id": "example" } ], "succeeded_items": [
{ "id": "example" } ] } }
```

2.1.19 | Profiles

2.1.19.1 | Get endpoint security profiles

post /public_api/v1/endpoints/get_profiles

Returns a list of endpoint security profiles of the requested type. Optionally filters by a list of profile IDs.

Required permission: `profiles_view`

Notes:

- File-Integrity-Monitoring (FIM) extension profiles are omitted when FIM is disabled for the profile's OS type.
- `is_in_user_scope` and `at_risk` are removed from every profile object before the response is returned.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/get_profiles'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"type\":\"prevention\",\"profile_ids\":[1]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/get_profiles", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/get_profiles") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": { "type": "prevention", "profile_ids": [ 1 ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/get_profiles"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/get_profiles")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "type": "prevention", "profile_ids": [1] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/get_profiles")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/get_profiles", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
```

```
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/get_profiles"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"type\":\"prevention\",\"profile_ids\":[1]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/get_profiles"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"type\":\"prevention\",\"profile_ids\":[1]}}", ParameterType.RequestBody); IRestResponse response
= client.Execute(request);
```

Body parameters
application/json

▼ request_dataobject

Parameters for the `get_profiles` call

▶ typestring (Enum)required

The category of profiles to retrieve.

- `prevention` â€ standard endpoint prevention profiles managed by `ProfilesService` (malware, exploit, restrictions, agent-settings, exceptions, etc.)
- `extension` â€ device-control and host-firewall profiles managed by `DeviceControlProfilesService`

▶ profile_idsarray[integer]

Optional list of profile IDs to filter by. When omitted or `null`, all profiles of the requested type are returned. When provided, only profiles whose `id` is in this list are returned. Must be a JSON array; passing a non-array value yields HTTP 400.

REQUEST Fetch all prevention profiles

```
{ "request_data": { "type": "prevention" } }
{ "request_data": { "type": "extension", "profile_ids": [ 1, 42, 99 ] } }
```

Responses

OK. Profiles retrieved successfully

Body
application/json

Successful response envelope

▼ replyarray

List of matching profile objects.

[
▶ idintegerint64

Internal numeric profile ID

▶ uuidstring

Globally unique profile identifier (UUID v4)

▶ namestring

Human-readable profile name.

▶ typestring (Enum)

Target operating system

▶ is_defaultboolean

Whether this is the system-managed default profile for its type and OS

▶ is_globalboolean

Whether this profile is a global (cross-tenant) profile

▶ is_disabledboolean

Whether this profile is currently disabled

▶ associated_targetsarray[string]

Human-readable list of policy rule targets (endpoint groups, tags, and so on.) that reference this profile, rendered as UI-friendly strings. `null` when the profile is not referenced by any policy rule.

▶ usage_countintegerint32

Number of policy rules that reference this profile

▶ descriptionstring

Optional free-text description of the profile

▶ created_bystring

Internal identifier (email or system name) of the creator

▶ created_by_prettystring

Display name of the creator

▶ creation_timeintegerint64

Profile creation timestamp in Unix epoch milliseconds

▶ modified_bystring

Internal identifier of the last modifier

▶ modified_by_prettystring

Display name of the last modifier

▶ modification_timeintegerint64

Last modification timestamp in Unix epoch milliseconds

▶ modulesobject

JSON object containing the profile's security module configuration. The schema varies by `type` and `platform`. Common top-level keys are module names (for example, `malware`, `exploit`, `agent_settings`), each containing mode and sub-option settings.

]
RESPONSE
Example 1

```
{ "reply": [ { "id": 1, "uuid": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "name": "Default Malware Profile", "type":
"MALWARE", "platform": "AGENT_OS_WINDOWS", "is_default": true, "is_global": false, "is_disabled": false,
"associated_targets": [ "All endpoints" ], "usage_count": 5, "description": "Default anti-malware profile for
Windows", "created_by": "system", "created_by_pretty": "Palo Alto Networks", "creation_time": 1700000000000,
"modified_by": "admin@example.com", "modified_by_pretty": "Admin User", "modification_time": 1710000000000, "modules":
{ "malware": { "mode": "prevent" } } }, { "id": 2, "uuid": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "name": "Custom
Exploit Profile", "type": "EXPLOIT", "platform": "AGENT_OS_MAC", "is_default": false, "is_global": false,
"is_disabled": false, "associated_targets": [ "macOS Servers" ], "usage_count": 2, "description": null, "created_by":
"admin@example.com", "created_by_pretty": "Admin User", "creation_time": 1705000000000, "modified_by":
"admin@example.com", "modified_by_pretty": "Admin User", "modification_time": 1705000000000, "modules": {} } ] }
```


Bad request. Possible causes:

- `type` field is missing (`TypeIsMandatory`)
- `type` value is not `prevention` or `extension` (`TypeNotSupported`)
- `profile_ids` is provided but is not a list (`ProfileIDsMustBeAList`)
- Any internal error during profile retrieval (`GeneralError`)

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE type field not provided


```
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "type is mandatory" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "type 'unknown' is not supported.
Valid types: ('prevention', 'extension')" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "profile_ids must be a list" } }
{ "reply": { "err_code": 400, "err_msg": "PROFILES_PUBLIC_API_ERROR", "err_extra": "General error" } }
```


Unauthorized â€ missing or invalid API-key headers

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE


```
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }
```


Forbidden. Possible causes:

- The API key does not have the `profiles_view` permission
- The feature flag `ALPHAFEATURES_PUBLIC_API_GET_POLICIES` is disabled
- The tenant is a secondary HA replica

Body
application/json
▼ replyobject
▶ err_codeinteger

HTTP-equivalent error code

▶ err_msgstring

Short error category string

▶ err_extrastring

Human-readable detail explaining the specific error

RESPONSE


```
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }
```


Internal Server Error

2.1.20 | Query Library

APIs for managing XQL query libraries

2.1.20.1 | Get XQL Queries

post /public_api/xql_library/get

Retrieve a detailed list of XQL query libraries. You can filter by list of query names or by list of query tags.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json,Example 1,With extended view'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/xql_library/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"extended_view\":false,\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/xql_library/get", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/xql_library/get") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"extended_view\":false,\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "extended_view": false, "xql_query_names": [ "string" ],
"xql_query_tags": [ "string" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/xql_library/get");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/xql_library/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"extended_view\":false,\"xql_query_names\":
[\"string\"],\"xql_query_tags\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "extended_view": false, "xql_query_names":
["string"], "xql_query_tags": ["string"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/xql_library/get")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/xql_library/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"extended_view\":false,\"xql_query_names\":[\"string\"],\"xql_query_tags\":
[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-
auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/xql_library/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"extended_view\":false,\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/xql_library/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"extended_view\":false,\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ extended_viewboolean

Whether to retrieve the detailed information on each XQL query.

▶ xql_query_namesarray[string]

An array of XQL query names to search for. Note: If searching by **xql_query_names**, you cannot search by **xql_query_tags** in the same call.

▶ xql_query_tagsarray[string]

An array of XQL tag names to search for. Note: If searching by **xql_query_tags**, you cannot search by **xql_query_names** in the same call.

REQUEST Get all XQL libraries in extended view

```
{ "request_data": { "extended_view": "True" } }
{ "request_data": {} }
{ "request_data": { "xql_query_names": [ "KILLER", "Rare Executions of PSEXEC", "Top 10 Users failing to log in" ] } }
{ "request_data": { "xql_query_tags": [ "perf", "perf2" ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ queries_countinteger

▶ xql_queriesarray

RESPONSE

```
{ "reply": { "queries_count": 0, "xql_queries": [ { "id": 0, "name": "example", "description": "example",
"query_text": "example", "created_at": 0, "created_by": "example", "created_by_pretty": "example", "query_metadata": {
"is_valid": false, "query_calls": [ {} ], "is_datamodel": false, "query_tables": [ "example" ], "query_presets": [ {}
] }, "is_private": false, "labels": [ "example" ] } ] } }
```

RESPONSE

```
[Example 1 content]
```

RESPONSE

```
[With extended view content]
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.20.2 | Insert or update XQL queries

post /public_api/xql_library/insert

Insert new XQL queries or update existing XQL queries.

Note: You should use unique `xql_query_name` for each XQL query on a given tenant.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json,Example 1'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/xql_library/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"xql_queries_override\":false,\"xql_queries\":
[{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/xql_library/insert", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/xql_library/insert")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"xql_queries_override\":false,\"xql_queries\":
[{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "xql_queries_override": false, "xql_queries": [ { "xql_query":
"string", "xql_query_name": "string" } ], "xql_query_tags": [ "string" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/xql_library/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/xql_library/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"xql_queries_override\":false,\"xql_queries\":
[{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "xql_queries_override": false, "xql_queries":
[ [ "xql_query": "string", "xql_query_name": "string" ] ], "xql_query_tags": ["string"] ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/xql_library/insert")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/xql_library/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"xql_queries_override\":false,\"xql_queries\":
[{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/xql_library/insert"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\": {\"xql_queries_override\":false,\"xql_queries\": [{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/xql_library/insert"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"xql_queries_override\":false,\"xql_queries\": [{\"xql_query\":\"string\",\"xql_query_name\":\"string\"}],\"xql_query_tags\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ xql_queries_overrideboolean

When the `xql_query_name` already exists on the tenant, this field defines whether or not to overwrite the existing XQL query with the new content. When `true`, the query will be overwritten. When `false`, the query will not be updated and an error will be returned.

▶ xql_queriesarrayrequired

▶ xql_query_tagsarray[string]

XQL query tags are optional

REQUEST

Example 1

```
{ "request_data": { "xql_queries_override": true, "xql_queries": [ { "xql_query": "dataset = xdr_data |limit 1", "xql_query_name": "test_ql1" }, { "xql_query": "dataset = xdr_data |limit 2", "xql_query_name": "test_ql11" }, { "xql_query": "dataset = xdr_data |limit 2", "xql_query_name": "test_ql11" } ], "xql_query_tags": [ "tag2", "tag202" ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ xql_queries_addedarray[string]

List of XQL queries that were added.

▶ xql_queries_updatedarray[string]

List of XQL queries that were updated.

▶ errorsarray[string]

List of errors received from additions/updates.

RESPONSE

```
{ "reply": { "xql_queries_added": [ "example" ], "xql_queries_updated": [ "example" ], "errors": [ "example" ] } }
```

RESPONSE

```
[Example 1 content]
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.



Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.20.3 | Delete XQL Queries

post /public_api/xql_library/delete

Delete XQL queries. You can filter by list of query names or by list of query tags.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json,Example 1'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/xql_library/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/xql_library/delete", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/xql_library/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "xql_query_names": [ "string" ], "xql_query_tags": [ "string" ] } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/xql_library/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/xql_library/delete") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "xql_query_names": ["string"],
```

```
"xql_query_tags": ["string"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/xql_library/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/xql_library/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/xql_library/delete"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/xql_library/delete"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"xql_query_names\":[\"string\"],\"xql_query_tags\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ xql_query_namesarray[string]

List of XQL query names to delete. Note: If searching by **xql_query_names**, you cannot search by **xql_query_tags** in the same call.

▶ xql_query_tagsarray[string]

List of XQL query tags. Note: If searching by **xql_query_tags**, you cannot search by **xql_query_names** in the same call.

REQUEST Delete XQL libraries by query names

```
{ "request_data": { "xql_query_names": [ "KILLER", "Rare Executions of PSEXEC", "Top 10 Users failing to log in" ] } }
{ "request_data": { "xql_query_tags": [ "perf", "perf2" ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ queries_countinteger

▶ xql_query_namesarray[string]

▶ errorsarray

RESPONSE

```
{ "reply": { "queries_count": 0, "xql_query_names": [ "example" ], "errors": [ {} ] } }
```

RESPONSE

```
[Example 1 content]
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21 | Response Action

APIs for response actions

2.1.21.1 | Restore File

post /public_api/v1/endpoints/restore

Restore a quarantined file on a requested endpoints. When filtering by multiple fields:

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 100.
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/restore'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/restore", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/restore")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "file_hash": "string", "endpoint_id": "string", "incident_id": 0 } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/endpoints/restore"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
```

```
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/restore")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "file_hash": "string", "endpoint_id":
"string", "incident_id": 0 ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/endpoints/restore")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/restore", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/restore"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/restore"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"file_hash\":\"string\",\"endpoint_id\":\"string\",\"incident_id\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ file_hashstringrequired

String that represents the file in hash. Hash must be a valid SHA256.

▶ endpoint_idstring

String that represents the endpoint ID. Note: if it is not specified, the request will run restore on all endpoints which relate to the quarantined file you defined.

▶ incident_idinteger

String representing the case ID. When included in the request, the Restore File action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST

example-1

```
{ "request_data": { "file_hash": "<hash value>", "incident_id": 302 } }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ action_idstring

▶ endpoints_countstring

RESPONSE

example-1

```
{ "reply": { "action_id": "<action ID>", "status": 1, "endpoints_count": "673" } }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.21.2 | File Retrieval Details

post /public_api/v1/actions/file_retrieval_details

View the API required to call in order to download the file retrieved by the **Retrieve File** API request according to the action ID.

The response contains a file hash you need to download and then unzip to view:

1. Download the file.

```
curl -XPOST "https://api-{fqdn}/public_api/v1/download/<api_value>"
-H "x-xdr-auth-id:{API_KEY_ID}"
-H "Authorization:{API_KEY}"
-H 'Content-Type:application/json'
--output /tmp/file.zip
```

2. Unzip the file: `unzip /tmp/file.zip`

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/actions/file_retrieval_details'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"group_action_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
```

```
"/public_api/v1/actions/file_retrieval_details", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/actions/file_retrieval_details") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"group_action_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "group_action_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/actions/file_retrieval_details"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/actions/file_retrieval_details")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"group_action_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["group_action_id": "string"]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/actions/file_retrieval_details")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/actions/file_retrieval_details", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"group_action_id\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/actions/file_retrieval_details"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"group_action_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/actions/file_retrieval_details"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"group_action_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ group_action_idstringrequired

The action ID of the Retrieve File API response.

REQUEST

example-1

```
{ "request_data": { "group_action_id": "<action ID>" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ dataobject

RESPONSE

Example 1

```
{ "reply": { "data": { "<endpoint_ID>": "https://api-{fqdn}/public_api/v1/download/<api_value>" } } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21.3 | Allow List Files

post /public_api/v1/hash_exceptions/allowlist

Add files which do not exist in the allow or block lists to an allow list.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/hash_exceptions/allowlist", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
```

```
request.body = "{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "hash_list": [ "string" ], "comment": "string", "incident_id": 0 } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/hash_exceptions/allowlist"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "hash_list": ["string"], "comment": "string",
"incident_id": 0 ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: [])
let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/hash_exceptions/allowlist", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"hash_list\":
[\"string\"],\"comment\":\"string\",\"incident_id\":0}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"hash_list\":
[\"string\"],\"comment\":\"string\",\"incident_id\":0}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/hash_exceptions/allowlist"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ hash_listarray[string]required

A list of hashed files you want to add to the allow list. Hash must be a valid SH256.

▶ commentstring

Additional information regarding the action.

▶ incident_idinteger

The case ID related to the hash. When included in the request, the **Allow List** action will appear in the **Cortex Cloud Case View Timeline** tab.

REQUEST

example-1

```
{ "request_data": { "hash_list": [ "032196FB1A---DFCF69E5D553F0", "365296EB1B---FCF29E5D553E4", "365296EB1B---
FCF69E3D553E4", "365296EB1B---FCF69E5D553D4", "365296EB1B---FCF79E5D553D4" ], "comment": "test", "incident_id": 5 } }
```

Responses

Successful response

Body

application/json

true=File successfully added to the allow list.

▼ boolean

true=File successfully added to the allow list.
RESPONSE
```
false
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.21.4 | Get Quarantine Status

post /public_api/v1/quarantine/status

Retrieve the quarantine status for specified files.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/quarantine/status'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"files\":
[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}" headers = { 'Authorization':
```

```
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/quarantine/status", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/quarantine/status")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"files\":
[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": { "files": [ { "endpoint_id": "string", "file_path": "string",
"file_hash": "string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/quarantine/status");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/quarantine/status")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"files\":
[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["files": [ [ "endpoint_id": "string",
"file_path": "string", "file_hash": "string" ] ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/quarantine/status")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/quarantine/status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"files\":
[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/quarantine/status"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"files\":
[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/quarantine/status"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"files\":[{\"endpoint_id\":\"string\",\"file_path\":\"string\",\"file_hash\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ filesarrayrequired

Array of endpoint IDs, filepaths, and file hash.

REQUEST

example-1

```
{ "request_data": { "files": [ { "endpoint_id": "<endpoint ID>", "file_path": "C:\\<file path>\\test_x64.msi",
"file_hash": "<hash value>" } ] } }
```

Responses

Successful response

Body

application/json

▼ replyarray

[

▶ endpoint_idstring

Endpoint ID.

▶ file_pathstring

File path.

▶ file_hashstring

File hash.

▶ statusboolean

The file's status. True: The file is quarantined. False: The file is not quarantined.

]
RESPONSE
example-1
{ "reply": [{ "endpoint_id": "<endpoint ID>", "file_path": "C:\\<file path>\\test_x64.msi", "file_hash": "<hash value>", "status": false }] }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21.5 | Quarantine Files

post /public_api/v1/endpoints/quarantine

Quarantine file on selected endpoints. You can select up to 1000 endpoints.

Note: A success response means that the request reached the defined endpoints, however if the file was not found there, no quarantine action will take place. To ensure if the file has been quarantined, check the Cortex XDR Action Center.

When filtering by multiple fields:

- Response is concatenated using AND condition (OR is not supported).
- Maximum result set size is 1000.
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/quarantine'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/quarantine", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/quarantine") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "file_path": "string", "file_hash": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/quarantine");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/quarantine")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "file_path": "string", "file_hash": "string" ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/quarantine")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/quarantine", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/quarantine"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/quarantine"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"file_path\":\"string\",\"file_hash\":\"string\"}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarrayrequired

An array of filter fields.

▶ file_pathstringrequired

The path of the file you want to quarantine. You must enter a proper path and not symbolic links.

▶ file_hashstringrequired

Case ID. When included in the request, the **Quarantine File** action will appear in the **Cortex Cloud Case View Timeline** tab.

REQUEST
example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] } ],
"file_path": "C:\\<file path>\\test_x64.msi", "file_hash": "<hash value>" } }
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of action to quarantine selected endpoints. Response only indicates the request was successfully sent to the endpoint. To track if the file quarantine succeeded either:

- In Cortex XDR console, navigate to **Response** > **Action Center** and search for the action ID. Make sure the **Action ID** field is selected in the table **Layout** settings.
- Send a **Get Action Status** API request.

▶ statusstring

Integer representing whether the action:

- 1: succeeded
- 0: failed

▶ endpoints_countstring

Number of endpoints included in the request.

RESPONSE
example-1

```
{ "reply": { "action_id": "[ID value]", "status": "1", "endpoints_count": "673" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE



{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.21.6 | Block List Files

post /public_api/v1/hash_exceptions/blocklist

Add files which do not exist in the allow or block lists to a block list. You can view the block list in the UI at Investigation & Response > Response > Action Center > Block List.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/hash_exceptions/blocklist'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"hash_list\":
[\"string\"],\"comment\":\"string\",\"incident_id\":0}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-
auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/hash_exceptions/blocklist", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/hash_exceptions/blocklist") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "hash_list": [ "string" ], "comment": "string", "incident_id": 0 } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/hash_exceptions/blocklist"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/hash_exceptions/blocklist")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "hash_list": ["string"], "comment": "string",
"incident_id": 0 ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: [])
let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/hash_exceptions/blocklist")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/hash_exceptions/blocklist", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"hash_list\":
[\"string\"],\"comment\":\"string\",\"incident_id\":0}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/hash_exceptions/blocklist"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"hash_list\":
[\"string\"],\"comment\":\"string\",\"incident_id\":0}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/hash_exceptions/blocklist"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"hash_list\":[\"string\"],\"comment\":\"string\",\"incident_id\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ hash_listarray[string]required

A list of hashed files you want add to a block list. Hash must be a valid SH256.

▶ commentstring

Additional information regarding the action.

▶ incident_idinteger

The case ID related to the hash. When included in the request, the Block List action appears in the Cortex Cloud Case View Timeline tab.

REQUEST

example-1

```
{ "request_data": { "hash_list": [ "032196FB1A---DFCF69E5D553F0", "365296EB1B---FCF69E7D553E4", "365296EB1B---
FCF69E5D523E4", "365296EB1B---FCF69E5D553D4", "365296EB1B---FCF63E5D553D4" ], "comment": "test", "incident_id": 5 } }
```

Responses

Successful response

Body

application/json

true=File successfully added to block list.

▼ boolean

true=File successfully added to block list.

RESPONSE

```
false
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.21.7 | Unisolate Endpoints

post /public_api/v1/endpoints/unisolate

Reverse the isolation of one or more endpoints in single request.

Note: You can only send a request with either `endpoint_id` to unisolate one endpoint or with filters to unisolate more than one endpoint. An error is raised if you try to use both `endpoint_id` and the filters.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/unisolate'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/unisolate", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/unisolate")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
```

```
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "endpoint_id": "string", "incident_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/unisolate");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/unisolate")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "endpoint_id": "string", "incident_id": "string" ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/unisolate")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/unisolate", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/unisolate"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/unisolate"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarray

An array of filter fields for unisolating a number of endpoints at once. Note: This field is only required if unisolating more than one endpoint.

▶ endpoint_idstringrequired

The ID of the endpoint to unisolate.

Note: this field is only required if unisolating one endpoint.

▶ incident_idstring

Case ID. When included in the request, the **Unisolate Endpoints** action will appear in the **Cortex Cloud Case View Timeline** tab.

REQUEST Unisolate one endpoint

```
{ "request_data": { "endpoint_id": "<endpoint ID>" } }
```

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "IN", "value": [ "<endpoint_id_1>", "
<endpoint_id_2>", "<endpoint_id_3>" ] } ] } }
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of the action to unisolate selected endpoints. Response only indicates the request was successfully sent to the endpoint. To track if the endpoint was restored either:

- In the Cortex XDR console, navigate to **Response** > **Action Center** > **Isolation** and search for the action ID. Make sure the **Action ID** field is selected in the table **Layout** settings.
- Send a **Get Action Status** API request.

▶ endpoints_countstring

Number of endpoints included in the request.

RESPONSE
example-1

```
{ "reply": { "action_id": "<action ID>", "status": "1", "endpoints_count": "673" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21.8 | Cancel Scan Endpoints

post /public_api/v1/endpoints/abort_scan

Cancel the scan of selected endpoints. A scan can only be aborted if the selected endpoints are in Pending or in Progress status.

When filtering by multiple fields:

- Response is concatenated using AND condition (OR is not supported).
- Offset is the zero-based number of endpoints from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.
Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/abort_scan'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"incident_id\":\"string\"}}" headers =
{ 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/endpoints/abort_scan", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/abort_scan") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"incident_id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "incident_id": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/abort_scan");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/abort_scan")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"incident_id\":\"string\"}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "incident_id": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/endpoints/abort_scan")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/abort_scan", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"incident_id\":\"string\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/abort_scan"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/abort_scan"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersobjectrequired

An array of filter fields to filter which endpoints to cancel scanning. To cancel scan of all endpoints, use the value "all".

▶ incident_idstring

Case ID. When included in the request, the **Cancel Scan Endpoints** action will appear in the **Cortex Cloud Case View Timeline** tab.

REQUEST To cancel scan of all endpoints

```
{ "request_data": { "filters": "all" } }
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] }, { "field": "dist_name", "operator": "in", "value": [ "WinInstaller" ] }, { "field": "group_name", "operator": "in", "value": [ "test" ] }, { "field": "scan_status", "operator": "in", "value": [ "none", "pending", "in_progress", "pending_cancellation", "aborted", "success" ] }, { "field": "group_name", "operator": "in", "value": [ "test" ] } ] }
}
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of action to cancel scan selected endpoints. Response only indicates the request was successfully sent to the endpoint. To track if the scan succeeded either:

- In Cortex XDR console, navigate to **Response** > **Action Center** and search for the action ID. Make sure the **Action ID** field is selected in the table Layout settings.
- Send a **Get Action Status** API request.

▶ endpoints_countstring

Number of endpoints included in the request.

RESPONSE

```
{ "reply": { "action_id": "example", "endpoints_count": "example" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21.9 | Scan Endpoints

post /public_api/v1/endpoints/scan

Run a scan on selected endpoints.

- Response is concatenated using AND condition (OR is not supported).
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/scan'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"filters\":\"all\",\"incident_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/endpoints/scan", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/scan") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\": {\"filters\":\"all\",\"incident_id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": "all", "incident_id": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/scan"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/scan") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":\"all\",\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "filters": "all", "incident_id": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/scan")! as URL, cachePolicy:
```

```
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/scan", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":\"all\",\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/scan"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"filters\":\"all\",\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/scan"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":\"all\",\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersstring (Enum)required

An array of filter fields. To scan all endpoints, use the value `all`.

▶ incident_idstring

Case ID. When included in the request, the Scan Endpoints action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST Scan all endpoints

```
{ "request_data": { "filters": "all" } }
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] }, {
"field": "dist_name", "operator": "in", "value": [ "WinInstaller" ] }, { "field": "group_name", "operator": "in",
"value": [ "test\"" ] }, { "field": "scan_status", "operator": "in", "value": [ "none", "pending", "in_progress",
"pending_cancellation", "aborted", "success" ] }, { "field": "group_name", "operator": "in", "value": [ "test" ] } ] }
}
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of action to scan selected endpoints. Response only indicates the request was successfully sent to the endpoint. To track if the scan was successful either:

- In Cortex XDR console, navigate to Response > Action Center > All Actions and search for the action ID. Make sure the Action ID field is selected in the table Layout settings.
- Send a Get Action Status API request.

▶ endpoints_countstring

Number of endpoints included in the request.

RESPONSE

```
{ "reply": { "action_id": "example", "endpoints_count": "example" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.21.10 | Get Action Status

post /public_api/v1/actions/get_action_status

Retrieve the status of the requested actions according to the action ID.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/actions/get_action_status'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"group_action_id\":0}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/actions/get_action_status", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/actions/get_action_status") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"group_action_id\":0}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "group_action_id": 0 } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
```

```
yourfqdn/public_api/v1/actions/get_action_status"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/actions/get_action_status")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"group_action_id\":0}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["group_action_id": 0]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/actions/get_action_status")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/actions/get_action_status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"group_action_id\":0}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/actions/get_action_status"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"group_action_id\":0}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/actions/get_action_status"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"group_action_id\":0}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ group_action_idintegerrequired

Action ID of the selected request.

REQUEST

example-1

```
{ "request_data": { "group_action_id": 123456789 } }
```

Responses

Successful response

Body

application/json

▼ replyobject

JSON object containing the query result.

▶ dataobject

RESPONSE

example-1

```
{ "reply": { "data": { "<agent ID>": "COMPLETED_SUCCESSFULLY" } } }
```

Bad Request. Got an invalid JSON.

Body

application/json

▼ replyobject

▶ dataobject

JSON object containing the query result.

▶ errorReasonsobject

Returns all error messages the agent returns to allow for easier analysis.

RESPONSE

Example 1


```
{ "reply": { "data": { "5a763600a3e44928a94ba84b6088380f": "FAILED" }, "errorReasons": {
"5a763600a3e44928a94ba84b6088380f": { "errorData": "{\"reportIds\":
[\"0ca3c1ace7694fcd8b44b735e5ba6c04\"],\"errorText\":\"\"}", "terminated_by": "instance_id", "errorDescription":
"Element not found.\r\n", "terminate_result": [ { "path": null, "status": 1 } ] } } } }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

▼ replyobject

▶ dataobject

JSON object containing the query result.

▶ errorReasonsobject

Returns all error messages the agent returns to allow for easier analysis.

RESPONSE

Example 1


```
{ "reply": { "data": { "5a763600a3e44928a94ba84b6088380f": "FAILED" }, "errorReasons": {
"5a763600a3e44928a94ba84b6088380f": { "errorData": "{\"reportIds\":
[\"0ca3c1ace7694fcd8b44b735e5ba6c04\"],\"errorText\":\"\"}", "terminated_by": "instance_id", "errorDescription":
"Element not found.\r\n", "terminate_result": [ { "path": null, "status": 1 } ] } } } }
```


Unauthorized access. User does not have the required license type to run this API.

Body

application/json

▼ replyobject

▶ dataobject

JSON object containing the query result.

▶ errorReasonsobject

Returns all error messages the agent returns to allow for easier analysis.

RESPONSE

Example 1


```
{ "reply": { "data": { "5a763600a3e44928a94ba84b6088380f": "FAILED" }, "errorReasons": {
"5a763600a3e44928a94ba84b6088380f": { "errorData": "{\"reportIds\":
[\"0ca3c1ace7694fcd8b44b735e5ba6c04\"],\"errorText\":\"\"}", "terminated_by": "instance_id", "errorDescription":
"Element not found.\r\n", "terminate_result": [ { "path": null, "status": 1 } ] } } } }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body

application/json

▼ replyobject

▶ dataobject

JSON object containing the query result.

▶ errorReasonsobject

Returns all error messages the agent returns to allow for easier analysis.

RESPONSE

Example 1


```
{ "reply": { "data": { "5a763600a3e44928a94ba84b6088380f": "FAILED" }, "errorReasons": {
"5a763600a3e44928a94ba84b6088380f": { "errorData": "{\"reportIds\":
[\"0ca3c1ace7694fcd8b44b735e5ba6c04\"],\"errorText\":\"\"}", "terminated_by": "instance_id", "errorDescription":
"Element not found.\r\n", "terminate_result": [ { "path": null, "status": 1 } ] } } } }
```


Internal server error. A unified status for API communication type errors.

Body

application/json

▼ replyobject

▶ dataobject

JSON object containing the query result.
▶ errorReasonsobject

Returns all error messages the agent returns to allow for easier analysis.

RESPONSE
Example 1

```
{ "reply": { "data": { "5a763600a3e44928a94ba84b6088380f": "FAILED" }, "errorReasons": {
"5a763600a3e44928a94ba84b6088380f": { "errorData": "{\"reportIds\":
[\"0ca3c1ace7694fcd8b44b735e5ba6c04\"],\"errorText\":\"\"}", "terminated_by": "instance_id", "errorDescription":
"Element not found.\r\n", "terminate_result": [ { "path": null, "status": 1 } ] } } } }
```

2.1.21.11 | Retrieve File

post /public_api/v1/endpoints/file_retrieval

Retrieve files from selected endpoints. You can retrieve up to 20 files, from no more than 10 endpoints.

- Response is concatenated using AND condition (OR is not supported).
- Offset is the zero-based number of cases from the start of the result set.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/file_retrieval'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"files\":{\"windows\":
[\"string\"],\"linux\":[\"string\"],\"macos\":[\"string\"]},\"incident_id\":\"string\"}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/file_retrieval", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/endpoints/file_retrieval") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"files\":{\"windows\":[\"string\"],\"linux\":[\"string\"],\"macos\":
[\"string\"]},\"incident_id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "files": { "windows": [ "string" ], "linux": [ "string" ], "macos": [ "string" ] }, "incident_id":
"string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/endpoints/file_retrieval"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/file_retrieval")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"files\":{\"windows\":
[\"string\"],\"linux\":[\"string\"],\"macos\":[\"string\"]},\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
```

```
"operator": "in", "value": ["string"] ] ], "files": [ "windows": ["string"], "linux": ["string"], "macos": ["string"] ], "incident_id": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/file_retrieval")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/endpoints/file_retrieval", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"files\":{\"windows\":[\"string\"],\"linux\":[\"string\"],\"macos\":[\"string\"]},\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/endpoints/file_retrieval"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"files\":{\"windows\":[\"string\"],\"linux\":[\"string\"],\"macos\":[\"string\"]},\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/file_retrieval"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":[\"string\"]}],\"files\":{\"windows\":[\"string\"],\"linux\":[\"string\"],\"macos\":[\"string\"]},\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarrayrequired

An array of filter fields.

▶ filesobjectrequired

One of the operating system types must be included.

▶ incident_idstring

Case ID. When included in the request, the Retrieve File action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "example" ] } ], "files": { "windows": [ "example" ], "linux": [ "example" ], "macos": [ "example" ] }, "incident_id": "example" } }
```

Responses

OK

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of action to retrieve files from selected endpoints. Response only indicates the request was successfully sent to the endpoint. To track if the file was retrieved successfully either: in the Cortex XDR console, navigate to Response > Action Center > Isolation and search for the action ID. Make sure the Action ID field is selected in the table Layout settings by selecting the three vertical dots. To view the file, send a File Retrieval Details request.

▶ statusstring
▶ endpoints_countstring

Number of endpoints included in the request.
RESPONSE

```
{ "reply": { "action_id": "example", "status": "example", "endpoints_count": "example" } }
```

Bad Request

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal server error. A unified status for API communication type errors.

2.1.21.12 | Isolate Endpoints

post /public_api/v1/endpoints/isolate

Isolate one or more endpoints in a single request. Request is limited to 1000 endpoints.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Security, you need the Cortex Cloud Runtime Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/endpoints/isolate'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/endpoints/isolate", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/endpoints/isolate")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "endpoint_id": "string", "incident_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/endpoints/isolate");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/endpoints/isolate")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "endpoint_id": "string", "incident_id": "string" ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/endpoints/isolate")! as URL, cachePolicy: .useProtocolCachePolicy,
```

```
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/endpoints/isolate", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/endpoints/isolate"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/endpoints/isolate"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"endpoint_id\":\"string\",\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarray

Array of filtered fields for isolating a number of endpoints at once. Note: Only required if isolating more than one endpoint.

▶ endpoint_idstringrequired

Identifies the endpoint to isolate. Note: Only required if isolating one endpoint.

▶ incident_idstring

The case ID. When included in the request, the Isolate Endpoints action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST Isolate one endpoint

```
{ "request_data": { "endpoint_id": "<endpoint ID>" } }
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID 1>", "
<endpoint ID 2>", "<endpoint ID 3>" ] } ] } }
```

Responses

OK

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

Action ID to scan selected endpoints. The response only indicates the request was successfully sent to the endpoint. To track if the isolation succeeded either:

- In the Cortex XDR console, navigate to Response > Action Center > Isolation and search for the action ID. Make sure the Action ID field is selected in the table Layout settings by selecting the vertical ellipses.
- Send a Get Action Status request.

▶ endpoints_countstring

Number of endpoints included in the request.

RESPONSE

Example 1

```
{ "reply": { "action_id": "<action ID>", "status": "1", "endpoints_count": "673" } }
```

Bad Request. Got an invalid JSON.

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, ID, or other invalid authentication parameters.

Unauthorized access. User does not have the required license type to run this API.

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Internal server error. A unified status for API communication type errors.

2.1.21.13 | Get triage presets

post /public_api/v1/get_triage_presets

Get all triage preset information including triage name, platform, description, created by, and triage type.

Required license: In Cortex Cloud Runtime Security, requires the Forensics add-on. Not supported in Cortex Cloud Posture Management.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/get_triage_presets'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/get_triage_presets", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/get_triage_presets")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/get_triage_presets");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/get_triage_presets")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/get_triage_presets")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/get_triage_presets", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-
type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/get_triage_presets"); struct curl_slist *headers = NULL; headers =
```

```
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/get_triage_presets"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

REQUEST

```
{ "request_data": {} }
```

Responses

OK

Body

application/json

▼ replyobject

▶ triage_presetsarray

RESPONSE

Example 1

```
{ "reply": { "triage_presets": [ { "uuid": "374ecf0457c944c39791e5a60d1a6d24", "name": "XDR Default", "os": "MACOS",
"description": "Default macOS Triage configuration included with the XDR Forensics add-on", "created_by":
"user@company.com", "type": "Online / Offline" }, { "uuid": "ea7a5d3ff52d41629e96fbd1d5f68535", "name": "XDR Default",
"os": "WINDOWS", "description": "Default Triage configuration included with XDR Forensics add-on", "created_by":
"user@company.com", "type": "Online / Offline" } ] } }
```

2.1.22 | Scheduled Queries

APIs for managing scheduled queries

2.1.22.1 | Get scheduled queries

post /public_api/v1/scheduled_queries/list

Return a list of scheduled queries. You can return all scheduled queries or filter results. You can also return extended results with all details included.

You must have Instance Administrator permissions to run this endpoint.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json,Retrieve all scheduled queries,Retrieve all scheduled queries with extended view'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scheduled_queries/list'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-
type': "application/json" } conn.request("POST", "/public_api/v1/scheduled_queries/list", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scheduled_queries/list") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "query_def_id", "operator": "EQ", "value":
"string" } ], "extended_view": false, "list_ids": [ "string" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/scheduled_queries/list");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scheduled_queries/list")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "query_def_id",
"operator": "EQ", "value": "string" ] ], "extended_view": false, "list_ids": ["string"] ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/scheduled_queries/list")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scheduled_queries/list", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-
auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scheduled_queries/list"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scheduled_queries/list"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":
[{\"field\":\"query_def_id\",\"operator\":\"EQ\",\"value\":\"string\"}],\"extended_view\":false,\"list_ids\":
[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

▶ extended_viewboolean

Display the extended view of the queries, which includes additional fields. If this is `false`, the response does not include `total_count` or `result_count`. Extended fields may change in future versions.

▶ list_idsarray[string]

List of scheduled query IDs to retrieve.

REQUEST Get all scheduled queries in extended view

```
{ "request_data": { "extended_view": "True" } }
{ "request_data": {} }
{ "request_data": { "list_ids": [ "qc_1683029855_18777", "qc_1678276807_6621" ] } }
{ "request_data": { "filters": [ { "field": "query_def_id", "operator": "EQ", "value": "qc_1683029855_18777" } ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ dataarray

▶ filter_countinteger

▶ total_countinteger

RESPONSE


```
{ "reply": { "data": [ { "query_def_id": "example", "query_definition_name": "example", "xql": "example", "timeframe": { "relativeTime": "example" }, "schedule": { "run_date": 0, "trigger_type": "example" }, "tenants": {}, "enable": false } ], "filter_count": 0, "total_count": 0 } }
```


RESPONSE

```
[Retrieve all scheduled queries content]
```

RESPONSE

```
[Retrieve all scheduled queries with extended view content]
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.22.2 | Insert or update scheduled queries

post /public_api/v1/scheduled_queries/insert

Insert new scheduled queries or update existing scheduled queries.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scheduled_queries/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":{\"relativeTime\":0},\"schedule\":
{\"trigger_type\":\"string\",\"run_date\":0}}]}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/scheduled_queries/insert", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scheduled_queries/insert") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":
{\"relativeTime\":0},\"schedule\":{\"trigger_type\":\"string\",\"run_date\":0}}]}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": [ { "query_definition_name": "string", "xql": "string", "timeframe": {
"relativeTime": 0 }, "schedule": { "trigger_type": "string", "run_date": 0 } } ] }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scheduled_queries/insert"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scheduled_queries/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":
{\"relativeTime\":0},\"schedule\":{\"trigger_type\":\"string\",\"run_date\":0}}]}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ [ "query_definition_name": "string", "xql":
"string", "timeframe": ["relativeTime": 0], "schedule": [ "trigger_type": "string", "run_date": 0 ] ] ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/scheduled_queries/insert")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scheduled_queries/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":{\"relativeTime\":0},\"schedule\":
{\"trigger_type\":\"string\",\"run_date\":0}}]}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scheduled_queries/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":{\"relativeTime\":0},\"schedule\":
{\"trigger_type\":\"string\",\"run_date\":0}}]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scheduled_queries/insert"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":[{\"query_definition_name\":\"string\",\"xql\":\"string\",\"timeframe\":
{\"relativeTime\":0},\"schedule\":{\"trigger_type\":\"string\",\"run_date\":0}}]}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataarrayrequired

[

▶ query_definition_namestringrequired

Note: You should use a unique `query_definition_name` for each scheduled query on each tenant.

▶ xqlstringrequired

▶ timeframeobjectrequired

▶ scheduleobject

]

REQUEST

Example 1


```
{ "request_data": [ { "query_definition_name": "debug_john_api", "xql": "dataset = xdr_data | limit 10", "timeframe": { "relativeTime": 46400000 }, "schedule": { "trigger_type": "date", "run_date": 4677621540000 } } ] }
```


Responses

OK

Body

application/json

▼ replyobject

Upon successful insert or update, the reply returns each individual query_id with the query definitions. If the insert or update failed, the reply will include the scheduled query name and the error message.

▶ <query_id>object

The query_id of the scheduled query that was inserted or updated.

RESPONSE

Example 1


```
{ "reply": { "qc_0123456789_01": { "query_definition_name": "test_1", "xql": "dataset = xdr_data | limit 1", "timeframe": { "relativeTime": 86400000 }, "schedule": { "trigger_type": "date", "run_date": 1824072062000 } }, "qc_0123456789_02": { "query_definition_name": "test_2", "xql": "dataset = xdr_data | limit 1", "timeframe": { "relativeTime": 86400000 }, "schedule": { "trigger_type": "date", "run_date": 1824072062000 } } } }
```


Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.22.3 | Delete a scheduled query

post /public_api/v1/scheduled_queries/delete

Delete scheduled queries.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json,Example 1'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scheduled_queries/delete'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":[\"string\"]}"
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/scheduled_queries/delete", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scheduled_queries/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":[\"string\"]}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": [ "string" ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/scheduled_queries/delete");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scheduled_queries/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":[\"string\"]}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/scheduled_queries/delete")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scheduled_queries/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":[\"string\"]}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scheduled_queries/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":[\"string\"]}"); CURLcode
ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/scheduled_queries/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":[\"string\"]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json
▼ request_dataarray[string]required
REQUEST
Example 1
```
{ "request_data": [ "qc_1683461522_18780", "qc_1677754986_6539", "avram" ] }
```
Responses

OK

Body
application/json
▼ replyarray
[
▶ scheduled_query_idstring

Each JSON pair in the response is the scheduled query ID and the results of the deletion request.

]
RESPONSE
```
{ "reply": [ { "scheduled_query_id": "example" } ] }
```
RESPONSE
```
[Example 1 content]
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.23 | Script execution

APIs executing script

2.1.23.1 | Run Snippet Code Script

post /public_api/v1/scripts/run_snippet_code_script

Initiate a new endpoint script execution action using provided snippet code. Cortex XDR supports sending your request in Base64.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/run_snippet_code_script'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/scripts/run_snippet_code_script", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/run_snippet_code_script") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "timeout": 600, "snippet_code": "string", "incident_id": "string" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/run_snippet_code_script"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/run_snippet_code_script")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "timeout": 600, "snippet_code": "string", "incident_id": "string" ]] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/run_snippet_code_script")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/run_snippet_code_script", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/run_snippet_code_script"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
```

```
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/run_snippet_code_script"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"timeout\":600,\"snippet_code\":\"string\",\"incident_id\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarrayrequired

An array of filter fields for running the script on a number of endpoints at once.

▶ timeoutinteger

The timeout in seconds for this execution. Default value is 600.

▶ snippet_codestringrequired

Section of a script you want to initiate on an endpoint.

▶ incident_idstring

Case ID. When included in the request, the Run Snippet Code Script action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST
example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] } ],
"snippet_code": "print (\"7\")" } }
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idstring

ID of the action initiated. ID will be used as a reference to track in the action center.

▶ endpoints_countinteger

Number of endpoints the action was initiated on.

RESPONSE
example-1

```
{ "reply": { "action_id": "<action ID>", "endpoints_count": 21 } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.23.2 | Run Script

post /public_api/v1/scripts/run_script

Initiate a new endpoint script execution action using a script from the script library. The script can be run on up to 1000 endpoints.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/run_script'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/scripts/run_script", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/scripts/run_script")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value":
[ "string" ] } ], "script_uid": "string", "parameters_values": { "x": "string", "y": 0 }, "timeout": 600,
"incident_id": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/scripts/run_script");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/run_script")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
```

```
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "endpoint_id_list",
"operator": "in", "value": ["string"] ] ], "script_uid": "string", "parameters_values": [ "x": "string", "y": 0 ],
"timeout": 600, "incident_id": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/scripts/run_script")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/run_script", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/run_script"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/run_script"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"endpoint_id_list\",\"operator\":\"in\",\"value\":
[\"string\"]}],\"script_uid\":\"string\",\"parameters_values\":
{\"x\":\"string\",\"y\":0},\"timeout\":600,\"incident_id\":\"string\"}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ filtersarrayrequired

Array of filter fields for running the script on a number of endpoints at once.

▶ script_uidstringrequired

GUID, unique identifier of the script, returned by the Get Scripts API per script.

▶ parameters_valuesobject

Dictionary containing the parameter name, `key`, and its value for this execution, `value`.

You can obtain these values by running Get Script Metadata API.

▶ timeoutinteger

Timeout in seconds for this execution. Default value is 600.

▶ incident_idstring

Case ID. When included in the request, the Run Script action will appear in the Cortex Cloud Case View Timeline tab.

REQUEST

example-1

```
{ "request_data": { "filters": [ { "field": "endpoint_id_list", "operator": "in", "value": [ "<endpoint ID>" ] } ],
"script_uid": "<unique ID>", "parameters_values": { "x": "param input as returned in Get Script Metadata", "y": 4 } }
}
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ action_idinteger

ID of the action initiated. ID will be used as a reference to track in the action center.

▶ endpoints_countinteger

Number of endpoints the action was initiated on.

▶ statusinteger

Integer representing whether the action:

- 1: succeeded
- 0: failed

RESPONSE
example-1

```
{ "reply": { "action_id": 22519813685366, "status": 1, "endpoints_count": 1 } }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.23.3 | Get Script Metadata

post /public_api/v1/scripts/get_script_metadata

Get the full definitions of a specific script in the scripts library.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_script_metadata'
-d ''
```
```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"script_uid\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/get_script_metadata", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```
```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/get_script_metadata") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"script_uid\":\"string\"}}" response = http.request(request) puts
response.read_body
```
```
const data = JSON.stringify({ "request_data": { "script_uid": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get_script_metadata"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```
```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/get_script_metadata")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"script_uid\":\"string\"}}") .asString();
```
```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["script_uid": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/get_script_metadata")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```
```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_script_metadata", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"script_uid\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
```
```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_script_metadata"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"script_uid\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
```
```
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_script_metadata"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"script_uid\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ script_uidstringrequired

Unique identifier of the script, returned by the Get Scripts API per script.

REQUEST
example-1
{ "request_data": { "script_uid": "<unique ID>" } }
Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ script_idstring

Script ID.

▶ namestring

Name of script.

▶ descriptionstring

Description of script.

▶ modification_dateinteger

Timestamp of when the script was last modified.

▶ created_bystring

Name of the user who created the script.

▶ is_high_riskboolean

Whether the script has a high-risk outcome.

▶ windows_supportedboolean

Whether the script can be executed on Windows OS.

▶ linux_supportedboolean

Whether the script can be executed on Linux OS.

▶ macos_supportedboolean

Whether the script can be executed on macOS.

▶ script_uidstring

GUID, global ID of the script, used toidentify the script when executing.

▶ entry_pointstring

name of the entry point selected for the script defined as `run`.

▶ script_inputarray
▶ script_output_typestring (Enum)

Type of output.

▶ script_output_dictionary_definitionsarray

When the `script_output_type` is a dictionary an array with `friendly_name`, `name`, and `type` for each output is returned. The field is empty in all other cases.

RESPONSE When entry_point is returned as run
{ "reply": { "script_id": "<script ID>", "name": "list_directories", "description": "List all directories under path", "modification_date": 1585074627259, "created_by": "Palo Alto Networks", "is_high_risk": false, "windows_supported": true, "linux_supported": true, "macos_supported": true, "script_uid": "<unique ID>", "entry_point": "run", "script_input": [{ "name": "path", "type": "string" }, { "friendly_name": "Number of levels", "name": "num_levels", "type": "integer" }], "script_output_type": "dictionary", "script_output_dictionary_definitions": [{ "friendly_name": "Number Of Processes", "name": "output_2", "type": "integer" }, { "friendly_name": "Name", "name": "output_1", "type": "string" }] } }

{ "reply": { "script_id": "<script ID>", "name": "list_directories", "description": "List all directories under path", "modification_date": 1585074627259, "created_by": "Palo Alto Networks", "is_high_risk": false, "windows_supported": true, "linux_supported": true, "macos_supported": true, "script_uid": "<unique ID>" } }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.23.4 | Get Script Execution Status

post /public_api/v1/scripts/get_script_execution_status

Retrieve the status of a script execution action.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_script_execution_status'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"action_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
```

```
'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/get_script_execution_status",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_status") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"action_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "action_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_status"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/get_script_execution_status")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"action_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["action_id": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/get_script_execution_status")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"action_id\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_script_execution_status"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"action_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_script_execution_status"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"action_id\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ action_idstringrequired

Identifier of the action, can be found in Cortex XDR console Response > Action Center > Action ID field.

REQUEST

example-1

```
{ "request_data": { "action_id": "<action ID>" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

JSON object containing the query result.

▶ general_statusstring

General status of the action, considering the status of all the endpoints.

▶ endpoints_pendinginteger

Number of endpoints in pending status.

▶ endpoints_canceledinteger

Number of endpoints in 'canceled' status.

▶ endpoints_in_progressinteger

Number of endpoints in 'in progress' status.

▶ endpoints_timeoutinteger

Number of endpoints in 'timeout' status.

▶ endpoints_failedinteger

Number of endpoints in 'failed' status.

▶ endpoints_completed_successfullyinteger

Number of endpoints in 'completed successfully' status.

▶ endpoints_pending_abortinteger

Number of endpoints in 'pending abort' status.

▶ endpoints_abortedinteger

Number of endpoints in 'aborted' status.

▶ endpoints_expiredinteger

Number of endpoints in 'expired' status.

▶ error_messagestring

Error message regarding permissions for running APIs or stating that the action doesnâ€ t exist.

RESPONSE
example-1

```
{ "reply": { "general_status": "PENDING", "endpoints_pending": 1, "endpoints_canceled": 0, "endpoints_in_progress": 0,
"endpoints_timeout": 0, "endpoints_failed": 0, "endpoints_completed_successfully": 0, "endpoints_pending_abort": 0,
"endpoints_aborted": 0, "endpoints_expired": 0 } }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.23.5 | Get Scripts

post /public_api/v1/scripts/get_scripts

Get a list of scripts available in the scripts library.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_scripts'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"in\",\"value\":[\"string\"]}]}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/scripts/get_scripts", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/scripts/get_scripts")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"in\",\"value\":[\"string\"]}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "in", "value": [ "string"
] } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/scripts/get_scripts"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/get_scripts")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"in\",\"value\":
[\"string\"]}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"in", "value": ["string"] ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/scripts/get_scripts")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_scripts", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"in\",\"value\":
[\"string\"]}]}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-
xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_scripts"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"in\",\"value\":[\"string\"]}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_scripts"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"in\",\"value\":[\"string\"]}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields. An empty dictionary returns all results.

▶ filtersarrayrequired

An array of filter fields.

REQUEST Request all results

```
{ "request_data": {} }
{ "request_data": { "filters": [ { "field": "is_high_risk", "operator": "in", "value": [ "false" ] } ] } }
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ total_countinteger

Number of total results of this filter without paging.

▶ result_countinteger

Number of scripts returned as result.

▶ scriptsarray

An array of scripts.

RESPONSE
example-1

```
{ "reply": { "total_count": 129, "result_count": 24, "scripts": [ { "script_id": "<script ID>", "name":
"list_directories", "description": "List all directories under path", "modification_date": 1585074627259,
"created_by": "Palo Alto Networks", "is_high_risk": false, "windows_supported": true, "linux_supported": true,
"macos_supported": true, "script_uid": "<unique ID>" }, { "script_id": "<script ID>", "name": "test 1", "description":
"test", "modification_date": 1583052236449, "created_by": "User 1", "is_high_risk": false, "windows_supported": true,
"linux_supported": false, "macos_supported": false, "script_uid": "<unique ID>" }, { "script_id": "<script ID>",
"name": "test 2", "description": "test 2", "modification_date": 1582709343498, "created_by": "User 2", "is_high_risk":
false, "windows_supported": true, "linux_supported": true, "macos_supported": true, "script_uid": "<unique ID>" } ] }
}
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.



Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.23.6 | Get Script Execution Results

post /public_api/v1/scripts/get_script_execution_results

Retrieve the results of a script execution action.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"action_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/get_script_execution_results",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"action_id\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "action_id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results") .header("Authorization", "SOME_STRING_VALUE")
.header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"action_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["action_id": "string"]] as [String : Any] let
```

```
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"action_id\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"action_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-
id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"action_id\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ action_idstringrequired

Action ID. This can be found in the Cortex XDR console Response > Action Center > Action ID field.

REQUEST

example-1

```
{ "request_data": { "action_id": "<action_id>" } }
```

Responses

Successful response

Body

application/json

▼ replyobject

JSON object containing the query result.

▶ script_namestring

Name of the script executed.

▶ script_descriptionstring

Description of the script executed.

▶ script_parametersarray

For each input parameter used in this execution, an array of `name` and `value`.

▶ date_createdstring

Timestamp in which the action was initiated.

▶ scopestring

Number of endpoints included in this action according to the filter used to select them.

▶ error_messagestring

Error message regarding permissions for running APIs.

▶ resultsarray

For each endpoint Cortex XDR displays any returned value by the script. The number of the results and their name are dynamic per script.

RESPONSE

example-1


```
{ "reply": { "script_name": "snippet script", "script_description": "", "script_parameters": [], "date_created":
"2020-03-29 13:21:59", "scope": "win_10and 21 other endpoints", "error_message": "", "results": [ { "endpoint_name": "
<name>", "endpoint_ip_address": [ "<IP address>" ], "endpoint_status": "LOST", "domain": "aaaa", "endpoint_id": "
<endpoint ID>", "execution_status": "PENDING", "standard_output": null, "retrieved_files": 0, "failed_files": 0,
"retention_date": null }, { "endpoint_name": "<name>", "endpoint_ip_address": [ "<IP address>" ], "endpoint_status":
"LOST", "domain": "<domain name>", "endpoint_id": "<endpoint ID>", "execution_status": "PENDING", "standard_output":
null, "retrieved_files": 0, "failed_files": 0, "retention_date": null }, { "endpoint_name": "<name>",
"endpoint_ip_address": [ "<IP address>" ], "endpoint_status": "DISCONNECTED", "domain": "WORKGROUP", "endpoint_id": "
<endpoint ID>", "execution_status": "PENDING", "standard_output": null, "retrieved_files": 0, "failed_files": 0,
"retention_date": null } ] } }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.23.7 | Get Script Execution Result Files

post /public_api/v1/scripts/get_script_execution_results_files

Get the files retrieved from a specific endpoint during a script execution.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results_files'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-
id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/scripts/get_script_execution_results_files", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results_files") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"]
= 'application/json' request.body = "{\"request_data\":{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "action_id": "string", "endpoint_id": "string" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results_files"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results_files") .header("Authorization", "SOME_STRING_VALUE")
.header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "action_id": "string", "endpoint_id":
"string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results_files")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_script_execution_results_files", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results_files"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-
auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json");
curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_script_execution_results_files"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-
xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"action_id\":\"string\",\"endpoint_id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ action_idstringrequired

Identifier of the action, can be found in Cortex XDR console Response > Action Center > Action ID field.

▶ endpoint_idstringrequired

Endpoint ID.

REQUEST

```
{ "request_data": { "action_id": "example", "endpoint_id": "example" } }
```

Responses

Successful response

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ datastring

A signed public link to a zip file containing the retrieved files. Link expires after 10 minutes.

RESPONSE
example-1

```
{ "reply": { "DATA": "https://example-link" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.23.8 | Get Script Code

post /public_api/v1/scripts/get_script_code

Get the code of a specific script in the script library.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}
Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get_script_code'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"script_uid\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/get_script_code", payload, headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/scripts/get_script_code") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"script_uid\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "script_uid": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get_script_code"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/get_script_code")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"script_uid\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["script_uid": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/get_script_code")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/get_script_code", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"script_uid\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get_script_code"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"script_uid\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get_script_code"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"script_uid\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ script_uidstringrequired

Unique identifier of the script, returned by the Get Scripts API per script.

REQUEST
example-1
```
{ "request_data": { "script_uid": "<unique ID>" } }
```

Responses

Successful response

Body
application/json
▼ replystring

JSON object containing the query result.

RESPONSE
example-1

```
{ "reply": "import os\nimport sys\nimport traceback\n\n\ndef run(path, num_levels):\n\tpath =
os.path.expanduser(path)\n\tpath = os.path.expandvars(path)\n\treturn scan_directory_recursive(path,
num_levels)\n\n\ndef scan_directory_recursive(directory, level):\n\tif level == 0:\n\t\treturn []\n\n\tsubfolders =
[]\n\ttry:\n\t\twith os.scandir(directory) as entries:\n\t\t\tfor f in entries:\n\t\t\t\ttry:\n\t\t\t\t\tif
f.is_dir():\n\t\t\t\t\t\tsubfolders.append(f.path)\n\t\t\t\texcept
(OSError,PermissionError):\n\t\t\t\t\tsys.stderr.write(f\"Failed access <{f.path}>\\n\")\n\n\tfor folder in
list(subfolders):\n\t\t subfolders.extend(scan_directory_recursive(folder, level-1))\n\texcept
Exception:\n\tsys.stderr.write(f\"Failed scanning directory: <{directory}>, error:
{traceback.format_exc()}\")\n\n\treturn subfolders\n" }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.24 | Scripts

APIs for managing scripts

2.1.24.1 | Get a script

post /public_api/v1/scripts/get

Get a script by filtering based on its name or ID. The script's YAML is returned in a ZIP file.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/zip'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/get", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/scripts/get") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filter": { "field": "id", "value": "string" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/get"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filter": [ "field": "id", "value": "string"
]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/get")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/scripts/get",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filterobject

Filter fields.

REQUEST
Example 1
```
{ "request_data": { "filter": { "field": "name", "value": "PhishingScript" } } }
```
Responses

OK

Body
application/zip
RESPONSE
```
[application/zip content]
```

2.1.24.2 | Insert or update a script

post /public_api/v1/scripts/insert

Update or add a script by passing the YAML in a ZIP file.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
Form parameters
▼ file File

The script in YAML in a zipped file.

format: binary
Example: `BINARY_DATA_HERE`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/insert'
-F 'file=@</path/to/file>'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "----
-011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n----
-011000010111000001101001--\r\n" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE" } conn.request("POST", "/public_api/v1/scripts/insert", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/scripts/insert") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request.body = "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n----
-011000010111000001101001--\r\n" response = http.request(request) puts response.read_body
const data = new FormData(); data.append("file", "string"); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/scripts/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"multipart/form-data; boundary=---011000010111000001101001") .body("-----011000010111000001101001\r\nContent-
Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "multipart/form-data" ] let parameters = [ [ "name": "file", "value": "string" ] ] let boundary = "--
-011000010111000001101001" var body = "" var error: NSError? = nil for param in parameters { let paramName =
param["name"]! body += "--\(boundary)\r\n" body += "Content-Disposition:form-data; name=\"\(paramName)\"" if let
filename = param["fileName"] { let contentType = param["content-type"]! let fileContent = String(contentsOfFile:
filename, encoding: String.Encoding.utf8) if (error != nil) { print(error) } body += "; filename=\"\(filename)\"\r\n"
```

```
body += "Content-Type: \(contentType)\r\n\r\n" body += fileContent } else if let paramValue = param["value"] { body += "\r\n\r\n\(paramValue)" } } let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/insert")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/scripts/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: multipart/form-data; boundary=---011000010111000001101001", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/scripts/insert"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: multipart/form-data; boundary=---011000010111000001101001"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/insert"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "multipart/form-data; boundary=---011000010111000001101001"); request.AddParameter("multipart/form-data; boundary=---011000010111000001101001", "-----011000010111000001101001\r\nContent-Disposition: form-data; name=\"file\"\r\n\r\nstring\r\n-----011000010111000001101001--\r\n", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Responses

OK

Body
application/json
▼ objects_countinteger

The number of scripts identified and attempted to be added.

▼ objectsobject
▶ failures_itemsarray

This field in the response indicates that the script IDs listed failed to be added.

RESPONSE

```
{ "objects_count": 0, "objects": { "failures_items": [ { "error": "example", "id": "example" } ] } }
```

2.1.24.3 | Delete a script

post /public_api/v1/scripts/delete

Delete a script by filtering based on its name or ID.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
```

```
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/scripts/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/scripts/delete",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/scripts/delete") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filter": { "field": "id", "value": "string" } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/scripts/delete"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/scripts/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filter": [ "field": "id", "value": "string"
]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/scripts/delete")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/scripts/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", CURLOPT_HTTPHEADER =>
[ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/scripts/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filter\":
{\"field\":\"id\",\"value\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/scripts/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filter\":{\"field\":\"id\",\"value\":\"string\"}}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filterobject

Filter fields.

REQUEST

Example 1

```
{ "request_data": { "filters": { "field": "name", "value": "Phishingplaybook" } } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

The number of scripts identified and attempted to be deleted.

▼ objectsobject

▶ failures_itemsarray

This field in the response indicates that the script IDs listed failed to be deleted.

▶ succeeded_itemsarray

This field in the response indicates that the script IDs listed were successfully deleted.

RESPONSE

```
{ "objects_count": 0, "objects": { "failures_items": [ { "error": "example", "id": "example" } ], "succeeded_items": [ { "id": "example" } ] } }
```

2.1.25 | Syslog servers

APIs for managing syslog servers

2.1.25.1 | Create a syslog integration

post /public_api/v1/integrations/syslog/create

Create a new syslog integration.

You must have **View/Edit Alert Notification** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/integrations/syslog/create'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/integrations/syslog/create", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/integrations/syslog/create") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "address": "string", "port": 0, "protocol": "TCP",
"facility": "string", "security_info": { "certificate_name": "string", "ignore_cert_errors": true,
"certificate_content": "string" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/integrations/syslog/create"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/integrations/syslog/create")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
```

```
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "name": "string", "address": "string",
"port": 0, "protocol": "TCP", "facility": "string", "security_info": [ "certificate_name": "string",
"ignore_cert_errors": true, "certificate_content": "string" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/integrations/syslog/create")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/integrations/syslog/create", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/integrations/syslog/create"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/integrations/syslog/create"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"name\":\"string\",\"address\":\"string\",\"port\":0,\"protocol\":\"TCP\",\"facility\":\"string\",\"security_info\":
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

A dictionary containing the API request fields.

▶ namestring

Unique name for the syslog server integration.

▶ addressstring

IP address or fully qualified domain name (FQDN) of the syslog server.

▶ portinteger

The port number on which the syslog server listens for messages.

▶ protocolstring (Enum)

Select a method of communication:

- TCP: No validation is made on the connection with the syslog server. However, if an error occurred with the domain used to make the connection, the Test connection will fail.
- UDP: No error checking, error correction, or acknowledgment. No validation is done for the connection or when sending data.
- TLS: Cortex validates the syslog server certificate and uses the certificate signature and public key to encrypt the data sent over the connection.

▶ facilitystring

Choose one of the syslog standard values. The value maps to how your syslog server uses the facility field to manage messages. For details on the facility field, see RFC 5424.

▶ security_infoobject

The `security_info` parameters are necessary only when `protocol` is `TLS`.

REQUEST Example 1

```
{ "request_data": { "address": "xdr-splunk-qa.traps.company.com", "facility": "FAC_USER", "name":
"Syslog_PAPI_Test_7H55R76T", "port": 5006, "protocol": "TCP", "security_info": "None" } }
{ "request_data": { "address": "xdr-splunk-qa.traps.paloaltonetworks.com", "facility": "FAC_USER", "name":
"Syslog_PAPI_Test_2QYH3VGS", "port": 5002, "protocol": "TLS", "security_info": { "ignore_cert_errors": false } } }
```

Responses

OK

Body
application/json
▼ syslog_integration_idinteger
▼ namestring
RESPONSE
Example 1

```
{ "syslog_integration_id": 630, "name": "Test PAPI" }
```

Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.25.2 | Get all or filtered syslog servers

post /public_api/v1/integrations/syslog/get

Get a complete or filtered list of syslog servers.

You must have **View Alert Notification** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}
Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/integrations/syslog/get'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/integrations/syslog/get", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/integrations/syslog/get") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "eq", "value": "string" }
] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/integrations/syslog/get"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/integrations/syslog/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"eq", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/integrations/syslog/get")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/integrations/syslog/get", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/integrations/syslog/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/integrations/syslog/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```
Body parameters
application/json
▼ request_dataobjectrequired

A dictionary containing the API request fields. An empty dictionary returns all results.

▶ filtersarray

Array of filter fields. Each JSON object must contain a field, operator, and value.

REQUEST Example 1

```
{ "request_data": { "filters": [ { "field": "id", "operator": "eq", "value": 632 } ] } }
{ "request_data": { "filters": [ { "field": "status", "operator": "eq", "value": "ACTIVE" } ] } }
```

Responses

OK

Body
application/json
▼ objects_countinteger

The number of syslog servers that are returned.

▼ objectsarray

The syslog server details.

[
▶ SYSLOG_INTEGRATION_IDinteger
▶ SYSLOG_INTEGRATION_NAMEstring

Syslog server integration name.

▶ SYSLOG_INTEGRATION_ADDRESSstring

IP address or fully qualified domain name (FQDN) of the syslog server.

▶ SYSLOG_INTEGRATION_PORTinteger

The port number on which the syslog server listens for messages.

▶ SYSLOG_INTEGRATION_PROTOCOLstring

The communication protocol:

- TCP: No validation is made on the connection with the syslog server. However, if an error occurred with the domain used to make the connection, the Test connection will fail.
- UDP: No error checking, error correction, or acknowledgment. No validation is done for the connection or when sending data.
- TLS: Cortex validates the syslog server certificate and uses the certificate signature and public key to encrypt the data sent over the connection.

▶ FACILITYstring
▶ SYSLOG_INTEGRATION_STATUSstring
▶ SYSLOG_INTEGRATION_ERRORstring
▶ SYSLOG_INTEGRATION_CERTIFICATE_NAMEstring
▶ SYSLOG_INTEGRATION_IGNORE_CERTIFICATE_ERRORstring
]
RESPONSE

```
{ "objects_count": 0, "objects": [ { "SYSLOG_INTEGRATION_ID": 0, "SYSLOG_INTEGRATION_NAME": "example",
"SYSLOG_INTEGRATION_ADDRESS": "example", "SYSLOG_INTEGRATION_PORT": 0, "SYSLOG_INTEGRATION_PROTOCOL": "example",
"FACILITY": "example", "SYSLOG_INTEGRATION_STATUS": "example", "SYSLOG_INTEGRATION_ERROR": "example",
"SYSLOG_INTEGRATION_CERTIFICATE_NAME": "example", "SYSLOG_INTEGRATION_IGNORE_CERTIFICATE_ERROR": "example" } ] }
```


Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.25.3 | Update a syslog integration

post /public_api/v1/integrations/syslog/update

Update the details of the specified syslog integration.

You must have View/Edit Alert Notification permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/integrations/syslog/update'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/integrations/syslog/update", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/integrations/syslog/update") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "syslog_id": "string", "name": "string", "address": "string", "port":
"string", "protocol": "TCP", "facility": "string", "security_info": { "certificate_name": "string",
"ignore_cert_errors": true, "certificate_content": "string" } } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/integrations/syslog/update"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/integrations/syslog/update")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "syslog_id": "string", "name": "string",
"address": "string", "port": "string", "protocol": "TCP", "facility": "string", "security_info": [ "certificate_name":
"string", "ignore_cert_errors": true, "certificate_content": "string" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/integrations/syslog/update")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/integrations/syslog/update", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/integrations/syslog/update"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/integrations/syslog/update"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ syslog_idstringrequired

ID of the syslog server

▶ namestring

Unique name for the syslog server integration.

▶ addressstring

IP address or fully qualified domain name (FQDN) of the syslog server.

▶ portstring

The port number on which the syslog server listens for messages.

▶ protocolstring (Enum)

Select a method of communication:

- `TCP`: No validation is made on the connection with the syslog server. However, if an error occurred with the domain used to make the connection, the Test connection will fail.
- `UDP`: No error checking, error correction, or acknowledgment. No validation is done for the connection or when sending data.
- `TLS`: Cortex validates the syslog server certificate and uses the certificate signature and public key to encrypt the data sent over the connection.

▶ facilitystring

Choose one of the syslog standard values. The value maps to how your syslog server uses the facility field to manage messages. For details on the facility field, see RFC 5424.

▶ security_infoobject

The `security_info` parameters are relevant only when `protocol` is `TLS`.

REQUEST

Example 1

```
{ "request_data": { "syslog_id": "123456789", "name": "Test PAPI", "address": "34.24.11.16", "port": "1234",
"protocol": "TLS", "facility": "FAC_USER", "security_info": { "certificate_name": "wf-verdict-service.key.pem",
"ignore_cert_errors": false, "certificate_content": "<binary string of the cert>" } } }
```

Responses

OK

Body
application/json

▼ replyboolean

Whether the update was successful.

RESPONSE

```
{ "reply": false }
```

Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.25.4 | Delete all or filtered syslog integrations

post /public_api/v1/integrations/syslog/delete

Delete all the syslog integrations or the ones who match the filter criteria.

You must have **View/Edit Alert Notification** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/integrations/syslog/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/integrations/syslog/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/integrations/syslog/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "eq", "value": "string" }
] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/integrations/syslog/delete"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/integrations/syslog/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "name", "operator":
"eq", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/integrations/syslog/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/integrations/syslog/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/integrations/syslog/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/integrations/syslog/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

A dictionary containing the API request fields. An empty dictionary deletes all syslog servers.

▶ filtersarray

Array of filter fields. Each JSON object must contain a field, operator, and value.

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "name", "operator": "EQ", "value": "Default syslog server" } ] } }
```

Responses

OK

Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.



RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.25.5 | Test syslog integration

post /public_api/v1/integrations/syslog/test

Tests a syslog integration's validity.

You must have **View Alert Notification** permissions to run this endpoint.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
```

```
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/integrations/syslog/test'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/integrations/syslog/test", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/integrations/syslog/test") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "syslog_id": "string", "name": "string", "address": "string", "port":
"string", "protocol": "TCP", "facility": "string", "security_info": { "certificate_name": "string",
"ignore_cert_errors": true, "certificate_content": "string" } } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/integrations/syslog/test"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/integrations/syslog/test")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "syslog_id": "string", "name": "string",
"address": "string", "port": "string", "protocol": "TCP", "facility": "string", "security_info": [ "certificate_name":
"string", "ignore_cert_errors": true, "certificate_content": "string" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/integrations/syslog/test")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/integrations/syslog/test", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/integrations/syslog/test"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/integrations/syslog/test"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
{\"syslog_id\":\"string\",\"name\":\"string\",\"address\":\"string\",\"port\":\"string\",\"protocol\":\"TCP\",\"facility\":\"st
{\"certificate_name\":\"string\",\"ignore_cert_errors\":true,\"certificate_content\":\"string\"}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobjectrequired

A dictionary containing the API request fields.

▶ syslog_idstring

If you include the `syslog_id` of an existing syslog integration, it will try to load the certificate data from the database to test the existing syslog integration.

▶ namestring

Unique name for the syslog server integration.

▶ addressstring

IP address or fully qualified domain name (FQDN) of the syslog server.

▶ portstring

The port number on which the syslog server listens for messages.

▶ protocolstring (Enum)

Select a method of communication:

- `TCP`: No validation is made on the connection with the syslog server. However, if an error occurred with the domain used to make the connection, the Test connection will fail.
- `UDP`: No error checking, error correction, or acknowledgment. No validation is done for the connection or when sending data.
- `TLS`: Cortex validates the syslog server certificate and uses the certificate signature and public key to encrypt the data sent over the connection.

▶ facilitystring

Choose one of the syslog standard values. The value maps to how your syslog server uses the facility field to manage messages. For details on the facility field, see RFC 5424.

▶ security_infoobject

The `security_info` parameters are relevant only when `protocol` is `TLS`.

REQUEST
Example 1
```
{ "request_data": { "name": "Test PAPI", "address": "34.24.11.16", "port": "1234", "protocol": "TLS", "facility": "FAC_USER" } }
```
Responses

OK

Bad Request

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Payment Required

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.
RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

2.1.26 | System management

APIs for system management

2.1.26.1 | System Health Check

get /public_api/v1/healthcheck

Perform a health check of your Cortex Cloud environment.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/healthcheck'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE" } conn.request("GET", "/public_api/v1/healthcheck",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/healthcheck") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/healthcheck");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/healthcheck") .header("Authorization",
"SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE" ] let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/healthcheck")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/healthcheck",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/healthcheck"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/healthcheck"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

OK

Body
application/json
▼ statusstring

The condition of your Cortex environment.

RESPONSE

```
{ "status": "example" }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.26.2 | Get Tenant Info

post /public_api/v1/system/get_tenant_info

Get your tenant license information.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
```

```
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/system/get_tenant_info'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/system/get_tenant_info", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/system/get_tenant_info") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/system/get_tenant_info");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/system/get_tenant_info")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/system/get_tenant_info")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/system/get_tenant_info", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE",
"content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/system/get_tenant_info"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/system/get_tenant_info"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

REQUEST

```
{ "request_data": {} }
```

Responses

OK

Body

application/json

▼ replyobject

List of available licenses, number of devices, and purchased add-ons on your tenant.

- ▶ xsiam_premium_expirationinteger
- ▶ purchased_xsiam_premiumobject
- ▶ pro_per_endpoint_expirationinteger
- ▶ purchased_pro_per_endpointobject
- ▶ data_enabled_pro_per_endpointinteger
- ▶ prevent_expirationinteger
- ▶ purchased_preventinteger
- ▶ installed_preventinteger

▶ pro_gb_expirationinteger
▶ purchased_pro_gbobject
▶ installed_pro_gbinteger
▶ compute_unit_expirationinteger
▶ purchased_compute_unitinteger
▶ host_insights_expirationinteger
▶ enabled_host_insightsinteger
▶ purchased_host_insightsinteger
▶ forensics_expirationinteger
▶ enabled_forensicsinteger
▶ pro_cloud_expirationinteger
▶ purchased_pro_cloudobject
▶ installed_pro_cloudinteger
▶ data_enabled_pro_cloudinteger
▶ identity_threat_expirationinteger
▶ xth_expirationinteger
▶ purchased_xthinteger
▶ threat_intelligence_management_expirationinteger
▶ purchased_threat_intelligence_managementinteger
▶ attack_surface_management_expirationinteger
▶ purchased_attack_surface_managementinteger
▶ xsiam_ep_hot_expirationstring
▶ purchased_xsiam_ep_hotinteger
▶ xsiam_ep_cold_expirationstring
▶ purchased_xsiam_ep_coldinteger
▶ xsiam_gb_hot_expirationstring
▶ purchased_xsiam_gb_hotinteger
▶ xsiam_gb_cold_expirationstring
▶ purchased_xsiam_gb_coldinteger

RESPONSE Example 1


```
{ "reply": { "xsiam_premium_expiration": 12478046378, "purchased_xsiam_premium": { "users": 100, "gb": 100, "agents": 500 }, "pro_per_endpoint_expiration": 12478046378, "purchased_pro_per_endpoint": { "agents": 200 }, "data_enabled_pro_per_endpoint": 26, "prevent_expiration": 0, "purchased_prevent": 0, "installed_prevent": 27, "pro_tb_expiration": 12478046378, "purchased_pro_gb": { "gb": 1 }, "installed_pro_tb": 0, "compute_unit_expiration": 0, "purchased_compute_unit": 16, "host_insights_expiration": 12478046378, "enabled_host_insights": 26, "purchased_host_insights": 400, "forensics_expiration": 0, "enabled_forensics": 12 } }
{ "reply": { "pro_cloud_expiration": 0, "purchased_pro_cloud": 0, "installed_pro_cloud": 4, "data_enabled_pro_cloud": 4, "pro_per_endpoint_expiration": "Nov 7th 2025 07:59:59", "purchased_pro_per_endpoint": { "agents": 200 }, "data_enabled_pro_per_endpoint": 4, "prevent_expiration": 0, "purchased_prevent": 0, "installed_prevent": 4, "pro_gb_expiration": "Nov 8th 2027 07:59:59", "purchased_pro_gb": { "gb": 33 }, "identity_threat_expiration": "Aug 13th 2023 11:03:41", "compute_unit_expiration": "Nov 7th 2025 07:59:59", "purchased_compute_unit": 50, "host_insights_expiration": "Nov 8th 2027 07:59:59", "enabled_host_insights": 8, "purchased_host_insights": 250, "forensics_expiration": 0, "enabled_forensics": 4, "xsiam_ep_hot_expiration": "Jan 2nd 2024 23:59:59", "purchased_xsiam_ep_hot": 2 } }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.26.3 | Get Users

post /public_api/v1/rbac/get_users

Retrieve a list of the current users in your environment.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/rbac/get_users'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/rbac/get_users", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/rbac/get_users") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/rbac/get_users");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/rbac/get_users")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/rbac/get_users")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/rbac/get_users", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
```

```
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/rbac/get_users"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/rbac/get_users"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

```
{}
```

Responses

OK

Body

application/json

▼ replyarray

JSON object containing the query result.

[

▶ user_emailstring

Email address of the user.

▶ user_first_namestring

First name of the user.

▶ user_last_namestring

Last name of the user.

▶ role_namestring

Role name associated with the user.

▶ last_logged_ininteger

Timestamp of when the user last logged in.

▶ user_typestring

Type of user.

▶ groupsarray

Name of user groups associated with the user, if applicable.

▶ scopearray

Name of scope associated with the user, if applicable.

]

RESPONSE

Example 1

```
{ "reply": [ { "user_email": "user1@acme.com", "user_first_name": "<first name>", "user_last_name": "<last name>",
"role_name": "Account Admin", "last_logged_in": 1640024700241, "user_type": "CSP", "groups": [], "scope": [] }, {
"user_email": "user2@acme.com", "user_first_name": "<first name>", "user_last_name": "<last name>", "role_name":
"Account Admin", "last_logged_in": null, "user_type": "CSP", "groups": [], "scope": [] }, { "user_email":
"user3@acme.com", "user_first_name": "<first name>", "user_last_name": "<last name>", "role_name": "Investigator",
"last_logged_in": null, "user_type": "CSP", "groups": [], "scope": [] } ] }
```

Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.26.4 | Get Roles

post /public_api/v1/rbac/get_roles

Retrieve information about one or more roles created in your environment.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/rbac/get_roles'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"role_names\":[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/rbac/get_roles", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/rbac/get_roles") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"role_names\":[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "role_names": [ "string" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/rbac/get_roles");
```

```
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/rbac/get_roles")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"role_names\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["role_names": ["string"]]] as [String : Any]
let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/rbac/get_roles")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/rbac/get_roles", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"role_names\":[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/rbac/get_roles"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"role_names\":
[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/rbac/get_roles"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"role_names\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

A dictionary containing the API request fields.

▶ role_namesarray[string]

List of one or more role names in your environment for which you want detailed information.

REQUEST

Example 1

```
{ "request_data": { "role_names": [ "Role1", "Role2" ] } }
```

Responses

OK

Body

application/json

▼ replyarray

JSON object containing the query result.

[

▶ pretty_namestring

Name of the role as it appears in the Management Console.

▶ permissionsarray[string]

List of permissions associated with this role.

▶ insert_timeinteger

Timestamp of when the Role was created.

▶ update_timeinteger

Timestamp of when the Role was last updated.

▶ created_bystring

Email of the user who created the Role.

▶ descriptionstring

Description of the Role, if available.

▶ groupsarray[string]

Group names associated with the Role.

▶ usersarray[string]

Email addresses of users associated with the Role.

]

RESPONSE

Example 1


```
{ "reply": [ { "pretty_name": "Role1", "permissions": [ "Reports", "Playbooks", "Datasets Access Control",
"Dashboards", "Scripts" ], "insert_time": 1658315576844, "update_time": 0, "created_by": "user1@acme.com",
"description": "", "groups": [ "group1", "group2" ], "users": [] }, { "pretty_name": "Role2", "permissions": [
"Dashboards", "Datasets Access Control" ], "insert_time": 1661435660656, "update_time": 0, "created_by":
"user1@acme.com", "description": "", "groups": [], "users": [] } ] }
```


Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.26.5 | Get User Groups

post /public_api/v1/rbac/get_user_group

Retrieve a list of the current user emails associated with one or more user groups in your environment.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/rbac/get_user_group'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"group_names\":
[\"string\"]}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-
type': "application/json" } conn.request("POST", "/public_api/v1/rbac/get_user_group", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/rbac/get_user_group")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"group_names\":[\"string\"]}}"
response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "group_names": [ "string" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/rbac/get_user_group");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/rbac/get_user_group")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"group_names\":[\"string\"]}}") .asString();
```

```
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["group_names": ["string"]]] as [String : Any]
let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/rbac/get_user_group")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/rbac/get_user_group", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"group_names\":[\"string\"]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/rbac/get_user_group"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"group_names\":
[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/rbac/get_user_group"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"group_names\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

A dictionary containing the API request fields.

▶ group_namesarray[string]

List of one or more user group names for which you want the associated users.

REQUEST

Example 1

```
{ "request_data": { "group_names": [ "Group1", "Group2" ] } }
```

Responses

OK

Body
application/json
▼ replyarray

JSON object containing the query result.

[
▶ group_namestring

Name of the User Group.

▶ descriptionstring

Description of the User Group, if available.

▶ pretty_namestring

Name of the User Group as it appears in the Management Console.

▶ insert_timeinteger

Timestamp of when the User Group was created.

▶ update_timeinteger

Timestamp of when the User Group was last updated.

▶ user_emailarray[string]

List of email addresses belonging to the users associated with the User Group.

▶ sourcestring

Type of User Group.

]
RESPONSE
Example 1

```
{ "reply": [ { "group_name": "Group1", "description": null, "pretty_name": "Investigator", "insert_time": 1661170832341, "update_time": 1661171650679, "user_email": [ "user1@acme.com", "user2@pacme.com", "user3@acme.com", "user4@acme.com", "user5@acme.com" ], "source": "Custom" }, { "group_name": "Group2", "description": null, "pretty_name": "Instance Administrator", "insert_time": 1660830450590, "update_time": 1661171631589, "user_email": [ "user1@acme.com", "user2@acme.com", "user3@acme.com", "user4@acme.com" ], "source": "Custom" } ] }
```


Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

2.1.26.6 | Set a User Role

post /public_api/v1/rbac/set_user_role

Add or remove one or more users from a role.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}
Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/rbac/set_user_role'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"user_emails\":
[\"string\"],\"role_name\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/rbac/set_user_role",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/rbac/set_user_role")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"user_emails\":
[\"string\"],\"role_name\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "user_emails": [ "string" ], "role_name": "string" } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/rbac/set_user_role"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/rbac/set_user_role")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"user_emails\":[\"string\"],\"role_name\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "user_emails": ["string"], "role_name":
"string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/rbac/set_user_role")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/rbac/set_user_role", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"user_emails\":[\"string\"],\"role_name\":\"string\"}}", CURLOPT_HTTPHEADER
=> [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/rbac/set_user_role"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"user_emails\":
[\"string\"],\"role_name\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/rbac/set_user_role"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"user_emails\":[\"string\"],\"role_name\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ user_emailsarray[string]

List of one or more user emails of users you want to add to or remove from a role.

▶ role_namestring

Name of the role you want to add a user to. Send an empty field to remove the user.

REQUEST

Example 1

```
{ "request_data": { "user_emails": [ "user1@acme.com", "user2@acme.com" ], "role_name": "Role1" } }
```

Responses

OK

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ update_countstring

Number of updated users.

RESPONSE

Example 1

```
{ "reply": { "update_count": "2" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal Server Error

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.26.7 | Get Risk Score

post /public_api/v1/get_risk_score

Retrieve the risk score of a specific user or endpoint in your environment, along with the reason for the score.

Request headers
▼ Authorization String required

{api_key}
Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/get_risk_score'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/get_risk_score", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/get_risk_score") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"id\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/get_risk_score");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/get_risk_score")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"id\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["id": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/get_risk_score")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/get_risk_score", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/get_risk_score"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"id\":\"string\"}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/get_risk_score"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"id\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject

A dictionary containing the API request fields.

▶ idstringrequired

Unique ID of a specific user or endpoint.

- User ID should be in the following format: `netBIOS/samAccount`
- Endpoint ID is the Cortex Agent ID.

You can only request one ID at a time.
REQUEST
Example 1
```
{ "request_data": { "id": "<user or endpoint ID>" } }
```
Responses

OK

Body
application/json
▼ replyobject

JSON object containing the query result.

▶ typestring

Form of identification element.

▶ idstring

Identification value of the type field.

▶ scoreinteger

The score assigned to the type.

▶ norm_risk_scoreinteger

Normalization of the risk score.

▶ risk_levelstring (Enum)

The risk level.

▶ reasonsarray

Details describing when and which case name affected the score.

▶ emailstring

Email address.

RESPONSE
Example 1
```
{ "reply": { "type": "user", "id": "user2_9fa235", "score": 100, "norm_risk_score": 800, "risk_level": "HIGH",
"reasons": [ { "date created": "2023-01-31", "description": "'Encoded VBScript executed' generated by XDR BIOC
detected on host acme3 involving user user2_9fa235", "severity": "SEV_050_CRITICAL", "status": "STATUS_010_NEW",
"points": 95 } ], "email": "user@company.com" } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.26.8 | Get Risky Users

post /public_api/v1/get_risky_users

Retrieve a list of users with the highest risk score in your environment along with the reason affecting each score.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/get_risky_users'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/get_risky_users", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/get_risky_users") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{}" response = http.request(request) puts response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/get_risky_users"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/get_risky_users") .header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = [] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/get_risky_users")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/get_risky_users", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/get_risky_users"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/get_risky_users"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

```
{}
```

Responses

OK

Body

application/json

▼ replyarray

JSON object containing the query result.

[

▶ typestring

Form of identification element.

▶ idstring

Identification value of the type field.

▶ scoreinteger

The score assigned to the user.

▶ norm_risk_scoreinteger

Normalization of the risk score.

▶ risk_levelstring (Enum)

The risk level.

▶ reasonsarray

Details describing when and which case name affected the user score.

▶ emailstring

Email address.

]

RESPONSE

Example 1


```
{ "reply": [ { "type": "user", "id": "acme1_9fa235", "score": 100, "norm_risk_score": 800, "risk_level": "HIGH", "reasons": [ { "date created": "2023-01-31", "description": "'Encoded VBScript executed' generated by XDR BIOC detected on host acme_agent-6a7b involving user acme1_9fa235", "severity": "SEV_050_CRITICAL", "status": "STATUS_010_NEW", "points": 95 } ], "email": "user@company.com" }, { "type": "user", "id": "acme2_d40b59", "score": 100, "norm_risk_score": 800, "risk_level": "HIGH", "reasons": [ { "date created": "2023-01-26", "description": "'Kernel Privilege Escalation' along with 4 other alerts generated by XDR Analytics BIOC, XDR Analytics and XDR Agent detected on 3 hosts involving 3 users", "severity": "SEV_040_HIGH", "status": "STATUS_010_NEW", "points": 95 } ] }, { "type": "user", "id": "acme3_3a509d", "score": 15, "norm_risk_score": 100, "risk_level": "LOW", "reasons": [ { "date created": "2023-02-13", "description": "'First successful SSO connection from a country in organization' generated by XDR Analytics BIOC involving user acme3", "severity": "SEV_020_LOW", "status": "STATUS_010_NEW", "points": 15 } ], "email": "user@company.com" }, { "type": "user", "id": "acme4_207a4e", "score": 0, "norm_risk_score": 0, "risk_level": "LOW", "reasons": [], "email": "user@company.com" } ] }
```


Bad Request. Got an invalid JSON.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.
Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.26.9 | Get Risky Hosts

post /public_api/v1/get_risky_hosts

Retrieve a list of endpoints with the highest risk score in your environment along with the reason for each score.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/get_risky_hosts'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/get_risky_hosts", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/get_risky_hosts")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/get_risky_hosts");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/get_risky_hosts")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/get_risky_hosts")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/get_risky_hosts", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/get_risky_hosts"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/get_risky_hosts"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
Object
application/json
REQUEST

```
{}
```

Responses

OK

Body
application/json
▼ replyarray

JSON object containing the query result.

[
▶ typestring

Form of identification element.

▶ idstring

Identification value of the type field.

▶ scoreinteger

The score assigned to the endpoint.

▶ norm_risk_scoreinteger

Normalization of the risk score.

▶ risk_levelstring (Enum)

The risk level.

▶ reasonsarray

Details describing when and which case name affected the endpoint score.

]
RESPONSE
Example 1

```
{ "reply": [ { "type": "host", "id": "host1", "score": 100, "norm_risk_score": 800, "risk_level": "HIGH", "reasons": [
{ "date_created": "2023-01-26", "description": "'Kernel Privilege Escalation' along with 4 other alerts generated by
```

XDR Analytics BIOC, XDR Analytics and XDR Agent detected on 3 hosts involving 3 users", "severity": "SEV_040_HIGH", "status": "STATUS_010_NEW", "points": 95 }] }] }

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"
▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.27 | Widgets

APIs for managing widgets

2.1.27.1 | Get widgets

post /public_api/v1/widgets/get

Get widget details by filtering based on the widget title and widget creator.

Note: The endpoint only returns XQL widgets and not predefined widgets.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/widgets/get'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/widgets/get", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/widgets/get") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "title", "operator": "EQ", "value": "string" }
] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/widgets/get"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/widgets/get")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "title", "operator":
"EQ", "value": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/widgets/get")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/widgets/get",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"filters\":[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER
=> [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/widgets/get"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/widgets/get"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"title\",\"operator\":\"EQ\",\"value\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields.

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "title", "value": "Widget A", "operator": "EQ" }, { "field": "created_by",
"value": "John Doe", "operator": "EQ" } ] } }
```

Responses

OK

Body

application/json

▼ objects_countinteger

Number of widgets returned.

▼ objectsarray
[
▶ widgets_dataarray
]
▼ objects_typestring
RESPONSE
Example 1

```
{ "objects_count": 2, "objects": [ { "widgets_data": [ { "widget_key": "xql_1646052681403", "title": "Widget A",
"creation_time": 1653303166334, "description": null, "data": { "phrase": "cold_dataset = endpoints", "time_frame": {
"relativeTime": 86400000 }, "viewOptions": { "type": "table", "commands": [] } }, "support_time_range": true,
"additional_info": { "query_tables": [ "endpoints" ], "query_uses_library": false }, "creator_mail":
"user@company.com" } ] }, { "widgets_data": [ { "widget_key": "xql_1346826725701", "title": "Widget B",
"creation_time": 1653302483610, "description": null, "data": { "phrase": "dataset = endpoints ", "time_frame": {
"relativeTime": 86400000 }, "viewOptions": { "type": "table", "commands": [] }, "gridRawStorageInfo": { "sort": null,
"coldefs": {}, "rowHeight": "{\"rowHeight\":\"regular\",\"gridRowsHeight\":\"medium-row\"}", "columnWidth": null } },
"support_time_range": true, "additional_info": { "query_tables": [ "endpoints" ], "query_uses_library": false },
"creator_mail": "user@company.com" } ] } ], "objects_type": "widgets" }
```


Invalid field or operator.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.27.2 | Insert or update widgets

post /public_api/v1/widgets/insert

Update or add the widgets retrieved by the Get widgets API.

You must have Instance Administrator permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/widgets/insert'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":[{\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
```

```
[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":
{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/widgets/insert", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/widgets/insert") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":[{\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":
{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": [ { "widgets_data": [ { "widget_key": "string", "title": "string",
"creation_time": 0, "description": "string", "data": { "phrase": "string", "time_frame": { "relativeTime": 0 },
"viewOptions": { "type": "string", "commands": [ {} ] }, "gridRawStorageInfo": { "sort": "string", "coldefs": {},
"rowHeight": "string", "columnWidth": 0 } }, "support_time_range": true, "additional_info": { "query_tables": [
"string" ], "query_uses_library": true }, "creator_mail": "string" } ] } ] }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/widgets/insert");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/widgets/insert")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":[{\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":
{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [["widgets_data": [ [ "widget_key": "string",
"title": "string", "creation_time": 0, "description": "string", "data": [ "phrase": "string", "time_frame":
["relativeTime": 0], "viewOptions": [ "type": "string", "commands": [[]] ], "gridRawStorageInfo": [ "sort": "string",
"coldefs": [], "rowHeight": "string", "columnWidth": 0 ] ], "support_time_range": true, "additional_info": [
"query_tables": ["string"], "query_uses_library": true ], "creator_mail": "string" ] ]]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/widgets/insert")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/widgets/insert", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":[{\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":
{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":
[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/widgets/insert"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":[{\"widgets_data\":
[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":
{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":
[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":
```

{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/widgets/insert"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":[{\"widgets_data\":[{\"widget_key\":\"string\",\"title\":\"string\",\"creation_time\":0,\"description\":\"string\",\"data\":{\"phrase\":\"string\",\"time_frame\":{\"relativeTime\":0},\"viewOptions\":{\"type\":\"string\",\"commands\":[{}]},\"gridRawStorageInfo\":{\"sort\":\"string\",\"coldefs\":{},\"rowHeight\":\"string\",\"columnWidth\":0}},\"support_time_range\":true,\"additional_info\":{\"query_tables\":[\"string\"],\"query_uses_library\":true},\"creator_mail\":\"string\"}]}]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);

Body parameters

application/json

▼ request_dataarray

[

▶ widgets_dataarray

An array of widget details as retrieved by the Get widgets API.

]

REQUEST

Example 1

{ "request_data": [{ "widgets_data": [{ "widget_key": "xql_1646052681403", "title": "Widget A", "creation_time": 1653303166334, "description": null, "data": { "phrase": "cold_dataset = endpoints", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "table", "commands": [] } }, "support_time_range": true, "additional_info": { "query_tables": ["endpoints"], "query_uses_library": false }, "creator_mail": "user@company.com" }] }, { "widgets_data": [{ "widget_key": "xql_1346826725701", "title": "Widget B", "creation_time": 1653302483610, "description": null, "data": { "phrase": "dataset = endpoints ", "time_frame": { "relativeTime": 86400000 }, "viewOptions": { "type": "table", "commands": [] }, "gridRawStorageInfo": { "sort": null, "coldefs": {}, "rowHeight": "{\"rowHeight\":\"regular\",\"gridRowsHeight\":\"medium-row\"}", "columnWidth": null } }, "support_time_range": true, "additional_info": { "query_tables": ["endpoints"], "query_uses_library": false }, "creator_mail": "user@company.com" }] }] }

Responses

OK

Body

application/json

▼ added_objectsarray

List of widget keys and titles for all widgets successfully added.

[

▶ keystring

▶ titlestring

]

▼ updated_objectsarray

List of widget keys and titles for all widgets successfully updated.

[

▶ keystring

▶ titlestring

]

▼ errorsarray

List of widget keys and error messages for all widgets that failed to be added or updated.

[

▶ keystring

▶ errorstring

]

RESPONSE

Example 1

{ "added_objects": [{ "key": "xql_1626053781409", "title": "Widget 1" }], "updated_objects": [{ "key": "xql_1636815725608", "title": "Widget 45" }], "errors": [{ "key": "xql_1651607948383", "error": "Failed importing widget" }] }

2.1.27.3 | Delete widgets

post /public_api/v1/widgets/delete

Delete the widgets retrieved by the Get widgets API.

You must have **Instance Administrator** permissions to run this endpoint.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/widgets/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/widgets/delete", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/widgets/delete") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "created_by", "value": "EQ", "operator":
"string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/widgets/delete");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/widgets/delete")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["filters": [ [ "field": "created_by", "value":
"EQ", "operator": "string" ] ]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/widgets/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/widgets/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/widgets/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
```

```
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/widgets/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"created_by\",\"value\":\"EQ\",\"operator\":\"string\"}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobjectrequired
▶ filtersarray

An array of filter fields.

REQUEST
Example 1

```
{ "request_data": { "filters": [ { "field": "title", "value": "Widget A", "operator": "EQ" }, { "field": "created_by",
"value": "John Doe", "operator": "EQ" } ] } }
```

Responses

OK

Body
application/json
▼ objects_countinteger

Number of widgets deleted.

▼ objectsarray[string]

List of widget IDs of widgets successfully deleted.

RESPONSE
Example 1

```
{ "objects_count": 3, "objects": [ "xql_1656052681401", "xql_1636816727601", "xql_1653607348382" ] }
```

Invalid field or operator.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```

2.1.28 | XQL query

Run XQL queries on your data sources using a series of APIs.

2.1.28.1 | Start an XQL query

post /public_api/v1/xql/start_xql_query

Execute an XQL query.

For more information on how to run XQL queries, see *Running XQL query APIs*.

Note

To ensure you don't surpass your quota, Cortex Cloud allows you to run up to four API queries in parallel.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/start_xql_query'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"query\":\"dataset=xdr_data | fields event_id, event_type, event_sub_type | limit 3\",\"tenants\":[],\"timeframe\":
{\"from\":1598907600000,\"to\":1599080399000}}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id':
"SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/xql/start_xql_query",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/xql/start_xql_query")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"query\":\"dataset=xdr_data | fields
event_id, event_type, event_sub_type | limit 3\",\"tenants\":[],\"timeframe\":
{\"from\":1598907600000,\"to\":1599080399000}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "query": "dataset=xdr_data | fields event_id, event_type,
event_sub_type | limit 3", "tenants": [], "timeframe": { "from": 1598907600000, "to": 1599080399000 } } }); const xhr
= new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/xql/start_xql_query"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/start_xql_query")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"query\":\"dataset=xdr_data | fields event_id, event_type,
event_sub_type | limit 3\",\"tenants\":[],\"timeframe\":{\"from\":1598907600000,\"to\":1599080399000}}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "query": "dataset=xdr_data | fields event_id,
event_type, event_sub_type | limit 3", "tenants": [], "timeframe": [ "from": 1598907600000, "to": 1599080399000 ] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/xql/start_xql_query")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/start_xql_query", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"query\":\"dataset=xdr_data | fields event_id, event_type, event_sub_type |
limit 3\",\"tenants\":[],\"timeframe\":{\"from\":1598907600000,\"to\":1599080399000}}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/start_xql_query"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"query\":\"dataset=xdr_data | fields event_id, event_type, event_sub_type | limit 3\",\"tenants\":[],\"timeframe\":
{\"from\":1598907600000,\"to\":1599080399000}}}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/start_xql_query"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"query\":\"dataset=xdr_data | fields event_id, event_type, event_sub_type | limit 3\",\"tenants\":[],\"timeframe\":{\"from\":1598907600000,\"to\":1599080399000}}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ querystringrequired

String of the XQL query.

▶ tenantsarray[string]

Note: This is only used when querying tenants managed by Managed Security Services Providers (MSSP).

List of strings used for running APIs on local and Managed Security tenants. Valid values:

- For single tenant (local tenant) query, enter a single-item list with your tenant_id. Additional valid values are, empty list ([]) or null (default).
- For multi-tenant investigations (Managed Security parent who investigate children and/or local), enter multi-item list with the required tenant_id. List of IDs can contain the parent, children, or both parent and children.

▶ timeframeobject

Integer in timestamp epoch milliseconds. Valid values include:

- Absolute Unix timestamp representing a date period: {"from" : 1598907600000, "to" : 1599080399000} = date period: 31/08/20 09:00:00 PM UTC - 02/09/20 8:59:59 PM UTC
- Relative Unix timestamp representing the last 24 hours: {"relativeTime": 86400000} = (24 * 60 * 60 * 1000 = 86400000).

REQUEST default

```
{ "request_data": { "query": "dataset=xdr_data | fields event_id, event_type, event_sub_type | limit 3", "tenants": [], "timeframe": { "from": 1598907600000, "to": 1599080399000 } } }
{ "request_data": { "query": "dataset=xdr_data | fields event_id, event_type, event_sub_type | limit 3", "tenants": [ "431509831", "401387390" ], "timeframe": { "from": 1598907600000, "to": 1599080399000 } } }
```

Responses

Successful response

Body

application/json

▼ replystring

RESPONSE

Example 1

```
{ "reply": "ad21c1e1492d4c_667_inv" }
```

Bad Request. Invalid JSON.

Body

application/json

▼ replyobject

▶ err_codeinteger

▶ err_msgstring

▶ err_extraobject

RESPONSE

Example 1

```
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": { "err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 1 } } }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

▼ replyobject

▶ err_codeinteger

▶ err_msgstring

▶ err_extraobject

RESPONSE

Example 1

{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": { "err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 1 } } }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": { "err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 1 } } }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": { "err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 1 } } }

Internal server error. A unified status for API communication type errors.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": { "err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 1 } } }

2.1.28.2 | Get XQL query results

post /public_api/v1/xql/get_query_results

Retrieve results of an executed XQL query API.

Note: This endpoint only works on XQL queries initiated by `/public_api/v1/xql/start_xql_query/`.

Maximum result set size is 1000. The API does not support pagination, therefore, you can set values to determine the result size limitation and how to wait for the results. To view response with greater than 1000 results you must call **Get XQL query results Stream**.

For more information on how to run XQL queries, see *Running XQL query APIs*.

> Note
>
> To ensure you don't surpass your quota, Cortex Cloud allows you to run up to four API queries in parallel.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/get_query_results'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/xql/get_query_results", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/xql/get_query_results") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "query_id": "061880b4867446_4356_inv", "pending_flag": true, "limit":
100, "format": "json" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/get_query_results");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/get_query_results")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "query_id": "061880b4867446_4356_inv",
"pending_flag": true, "limit": 100, "format": "json" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/get_query_results")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/get_query_results", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}",
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/get_query_results"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/get_query_results"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":
```

```
{\"query_id\":\"061880b4867446_4356_inv\",\"pending_flag\":true,\"limit\":100,\"format\":\"json\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ query_idstringrequired

String representing the unique execution ID generated by the response to Start an XQL query API. You can also enter the execution ID of a query generated in Cortex XDR and listed in the Query Center table.

▶ pending_flagboolean

Boolean flag indicating whether the API call should operate in synchronous/blocking mode, or in asynchronous/non-blocking mode. Valid Values:

- True (default): The call returns immediately with one of the following options:

1. PENDING status indicating query hasn't yet completed or results are not yet ready to be returned. Need to execute the API call again.
2. SUCCESS/FAIL status

- False: The API will block until query completes and results are ready to be returned.

▶ limitinteger

Integer representing the maximum number of results to return. If the 'limit' is not specified or if 'limit' is greater than 1000 and the query yields more than 1000 valid results, a `stream id` will be generated for use in the *Get XQL query results Stream** API. In the context of multi-tenant investigations, when you specify the parameter value (x), it will return x results across all tenants combined, rather than x results for each individual tenant. For example, if there are y tenants participating in the investigation, the maximum number of results returned can be x*y (up to the limit of 1,000,000).

▶ formatstring (Enum)

The type of response output.

REQUEST default

```
{ "request_data": { "query_id": "061880b4867446_4356_inv", "pending_flag": true, "limit": 100, "format": "json" } }
```


```
{ "request_data": { "query_id": "061880b4867446_4356_inv", "pending_flag": true, "limit": 100, "format": "json" } }
```


Responses

Successful response

Body

application/json

▼ replyobject

▶ statusstring

▶ number_of_resultsinteger

▶ query_costobject

▶ remaining_quotanumber

▶ resultsobject

RESPONSE pending_flag=true

```
{ "reply": { "status": "PENDING" } }
```

```
{ "reply": { "status": "SUCCESS", "number_of_results": 3, "query_cost": { "tenant_id_1": 0.001596388888888889 },
"remaining_quota": 4.998403611111111, "results": { "data": [ { "event_id": "eventID1", "_vendor": "PANW", "_product":
"Fusion", "insert_timestamp": 1621541825324, "_time": 1621541523000, "event_type": "STORY", "event_sub_type": "NULL"
}, { "event_id": "eventID2", "_vendor": "PANW", "_product": "Fusion", "insert_timestamp": 1621541825326, "_time":
1621541528000, "event_type": "STORY", "event_sub_type": "NULL" }, { "event_id": "eventID3", "_vendor": "PANW",
"_product": "Fusion", "insert_timestamp": 1621541825325, "_time": 1621541517000, "event_type": "STORY",
"event_sub_type": "NULL" } ] } } }
```

```
{ "reply": { "status": "SUCCESS", "number_of_results": 6, "query_cost": { "tenant_id_1": 0.001596388888888889,
"tenant_id_2": 0.00179989 }, "remaining_quota": 4.995007332222222, "results": { "data": [ { "event_id": "eventID1",
"_vendor": "PANW", "_product": "Fusion", "insert_timestamp": 1621541825324, "_time": 1621541523000, "event_type":
"STORY", "event_sub_type": "NULL" }, { "event_id": "eventID2", "_vendor": "PANW", "_product": "Fusion",
"insert_timestamp": 1621541825326, "_time": 1621541528000, "event_type": "STORY", "event_sub_type": "NULL" }, {
"event_id": "eventID3", "_vendor": "PANW", "_product": "Fusion", "insert_timestamp": 1621541825325, "_time":
1621541517000, "event_type": "STORY", "event_sub_type": "NULL" }, { "event_id": "eventID4", "_vendor": "PANW",
"_product": "Fusion", "insert_timestamp": 1621541825324, "_time": 1621541523000, "event_type": "STORY",
"event_sub_type": "NULL" }, { "event_id": "eventID5", "_vendor": "PANW", "_product": "Fusion", "insert_timestamp":
1621541825326, "_time": 1621541528000, "event_type": "STORY", "event_sub_type": "NULL" }, { "event_id": "eventID6",
"_vendor": "PANW", "_product": "Fusion", "insert_timestamp": 1621541825325, "_time": 1621541517000, "event_type":
"STORY", "event_sub_type": "NULL" } ] } } }
```

```
{ "reply": { "status": "SUCCESS", "number_of_results": 1000000, "query_cost": { "tenant_id_1": 0.011742777777777777 },
"remaining_quota": 4.984442777777778, "results": { "stream_id": "streamID" } } }
```

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.
▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.28.3 | Get XQL query Quota

post /public_api/v1/xql/get_quota

Retrieve the amount of query quota available and used.

Note: This endpoint only works on XQL queries initiated by `/public_api/v1/xql/start_xql_query/`.

For more information on how to run XQL queries, see *Running XQL query APIs*.

> Note
>
> To ensure you don't surpass your quota, Cortex Cloud allows you to run up to four API queries in parallel.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/xql/get_quota'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" }
```

```
conn.request("POST", "/public_api/v1/xql/get_quota", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/xql/get_quota") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/xql/get_quota");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/get_quota")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": []] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/get_quota")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/get_quota", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-
type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/get_quota"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/get_quota"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

default

```
{ "request_data": {} }
```

Responses

Successful response

Body

application/json

▼ replyobject

▶ license_quotainteger

▶ additional_purchased_quotainteger

▶ used_quotanumber

▶ eval_quotainteger

▶ total_daily_running_queriesinteger

The number of daily active queries. This value is reset nightly.

▶ total_daily_concurrent_rejected_queriesinteger

The number of daily queries rejected due to too many concurrent XQL queries being run through the API. This value is reset nightly.

▶ current_concurrent_active_queriesobject

Currently running XQL queries with their current duration.

▶ current_concurrent_active_queries_countinteger

The number of active queries currently running.

▶ max_daily_concurrent_active_query_countinteger

The maximum number of queries that ran concurrently today on this tenant. This value is reset nightly.

RESPONSE

example-1


```
{ "reply": { "license_quota": 5, "additional_purchased_quota": 0, "used_quota": 0, "eval_quota": 0,
"total_daily_running_queries": 4, "total_daily_concurrent_rejected_queries": 8, "current_concurrent_active_queries": {
"debee6b0c41f47_911_inv": { "xql": "config timeframe = 1mo | dataset=xdr_data | limit 1000000", "duration": 61 } },
"current_concurrent_active_queries_count": 1, "max_daily_concurrent_active_query_count": 4 } }
```


Bad Request. Got an invalid JSON.

Body

application/json

▼ replyobject

▶ err_codeinteger

▶ err_msgstring

▶ err_extraobject

RESPONSE

Example 1


```
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing XDR - XQL query", "err_extra": {
"err_msg": "reached max allowed amount of parallel running queries. please wait for some queries to finish and submit
your query again", "query_cost": 0, "remaining_quota": 5, "total_daily_running_queries": 4,
"total_daily_concurrent_rejected_queries": 1 } } }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body

application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`

▼ err_extrastring

Additional information describing the error.

RESPONSE


```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.28.4 | Get XQL query results Stream

post /public_api/v1/xql/get_query_results_stream

Retrieve XQL query results with more than 1000 results.

Note: This endpoint only works on XQL queries initiated by `/public_api/v1/xql/start_xql_query/`.

Response is returned as chunked (Transfer-Encoding: chunked). To retrieve a compressed gzipped response (Content-Encoding: gzip), in your header add Accept-Encoding: gzip.

For more information on how to run XQL queries, see *Running XQL query APIs*.

> Note
>
> To ensure you don't surpass your quota, Cortex Cloud allows you to run up to four API queries in parallel.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

▼ Accept-Encoding String

For retrieving a compressed gzipped response

Example: `acceptEncoding_example`
Default: `gzip`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example' -H 'Accept-Encoding:
acceptEncoding_example'
'https://api-yourfqdn/public_api/v1/xql/get_query_results_stream'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"stream_id\":\"563c5e24-====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'Accept-Encoding': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/xql/get_query_results_stream", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/xql/get_query_results_stream") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["Accept-Encoding"] = 'SOME_STRING_VALUE'
request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"stream_id\":\"563c5e24-
====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "stream_id": "563c5e24-====-9a1f8139d3c5", "is_gzip_compressed": true }
}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function ()
{ if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/xql/get_query_results_stream"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("Accept-Encoding",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/xql/get_query_results_stream")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("Accept-Encoding",
"SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"stream_id\":\"563c5e24-
====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE", "Accept-
Encoding": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = ["request_data": [ "stream_id":
"563c5e24-====-9a1f8139d3c5", "is_gzip_compressed": true ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/xql/get_query_results_stream")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/xql/get_query_results_stream", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"stream_id\":\"563c5e24-
====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}", CURLOPT_HTTPHEADER => [ "Accept-Encoding: SOME_STRING_VALUE",
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/xql/get_query_results_stream"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "Accept-Encoding: SOME_STRING_VALUE"); headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"stream_id\":\"563c5e24-
====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/xql/get_query_results_stream"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("Accept-Encoding", "SOME_STRING_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"stream_id\":\"563c5e24-
====-9a1f8139d3c5\",\"is_gzip_compressed\":true}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json

▼ request_dataobject
▶ stream_idstringrequired

String representing the unique ID generate by the response to **Get XQL query results** API.

▶ is_gzip_compressedboolean

A boolean flag.

REQUEST
default

```
{ "request_data": { "stream_id": "563c5e24-====-9a1f8139d3c5", "is_gzip_compressed": true } }
```

Responses

Successful response

Bad Request. Got an invalid JSON.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE

```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input
'|alter2'\"}", "err_extra": "example" }
```


Unauthorized access. User does not have the required license type to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.
RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

Internal server error. A unified status for API communication type errors.

Body
application/json

The query result upon error.

▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

Example:`"{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}"`
▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "{\"line\": 1, \"column\": 19, \"message\": \"no viable alternative at input '|alter2'\"}", "err_extra": "example" }
```

2.1.29 | XQL user datasets

APIs for managing XQL user datasets.

2.1.29.1 | Define an XQL user dataset

post /public_api/v1/dataset/define_dataset

Define an XQL user dataset based on an existing BigQuery table created by the user.

Note: BigQuery table must be an existing table under public_access_user.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

These APIs are only applicable from within the XSIAM Notebook environment.

Request headers
▼ Authorization String required

{api_key}
Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dataset/define_dataset'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"table_name\":\"string\"}}" headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/dataset/define_dataset", payload, headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/dataset/define_dataset") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"table_name\":\"string\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "table_name": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/dataset/define_dataset");
xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE"); xhr.setRequestHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dataset/define_dataset")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"table_name\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": ["table_name": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/dataset/define_dataset")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/dataset/define_dataset", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"table_name\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/dataset/define_dataset"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"table_name\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/dataset/define_dataset"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"table_name\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
application/json
▼ request_dataobject
▶ table_namestringrequired

An existing BigQuery table name that was created by the user.

REQUEST
```
{ "request_data": { "table_name": "example" } }
```
Responses

OK

2.1.29.2 | Get created XQL user datasets

post /public_api/v1/dataset/get_created_datasets

Retrieve a list of all XQL user datasets created using the Cortex SDK.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

These APIs are only applicable from within the XSIAM Notebook environment.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dataset/get_created_datasets'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/dataset/get_created_datasets", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/dataset/get_created_datasets") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{}" response = http.request(request) puts response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/dataset/get_created_datasets"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dataset/get_created_datasets")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = [] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/dataset/get_created_datasets")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/dataset/get_created_datasets", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type:
application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/dataset/get_created_datasets"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/dataset/get_created_datasets"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
Object
application/json
REQUEST

```
{}
```

Responses

OK

Body
application/json
▼ datasetsarray[string]

A list of created datasets.

RESPONSE

```
{ "datasets": [ "example" ] }
```

2.1.29.3 | Delete an XQL user dataset

post /public_api/v1/dataset/delete_dataset

Delete an XQL user dataset that was created by the Cortex SDK.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

These APIs are only applicable from within the XSIAM Notebook environment.

Request headers
▼ Authorization String required

{api_key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/v1/dataset/delete_dataset'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}" headers = { 'Authorization': "SOME_STRING_VALUE",
'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/dataset/delete_dataset", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/dataset/delete_dataset") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "dataset_name": "string", "delete_underlying_bq_table": false } });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/dataset/delete_dataset"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/dataset/delete_dataset")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
```

```
"application/json") .body("{\"request_data\":{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}")
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "dataset_name": "string",
"delete_underlying_bq_table": false ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/dataset/delete_dataset")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/dataset/delete_dataset", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}", CURLOPT_HTTPHEADER => [ "Authorization:
SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/dataset/delete_dataset"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/dataset/delete_dataset"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"dataset_name\":\"string\",\"delete_underlying_bq_table\":false}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobject

▶ dataset_namestringrequired

The dataset name to be deleted.

▶ delete_underlying_bq_tableboolean

Define whether or not to delete the BigQuery table related to the dataset.

REQUEST

```
{ "request_data": { "dataset_name": "example", "delete_underlying_bq_table": false } }
```

Responses

OK

Body

application/json

RESPONSE

```
{}
```

2.2 | Agent Configuration Settings API

2.2.1 | Preface

Manage global agent configuration settings for your Cortex Cloud environment. These endpoints allow you to retrieve and update settings that control agent behavior across content management, auto-upgrades, status timeouts, analysis options, and administrative cleanup.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: 1.0.0

2.2.1.1 | Servers

https://api-yourfqdn

2.2.1.2 | Authentication methods

▼ api-key-header-x-xdr-auth-id
Api Key "x-xdr-auth-id"

The API key ID.

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.

▼ api-key-header-authorization
Api Key "Authorization"

The API key.

Authorized requests to the API should use: **Authorization** inside **a header** with the access token.

2.2.1.2.1 | Default authentication

Please note that this documentation assumes a minimum level of authentication is required, unless explicitly stated otherwise.
It is essential to ensure that any of the following authentication mechanisms are in place to access the API endpoints:

- api-key-header-x-xdr-auth-id=[], api-key-header-authorization

2.2.2 | Agent Configurations

Endpoints for managing global agent configuration settings. Each configuration area has a paired get/set endpoint pattern. Use the GET endpoint to retrieve current settings and the POST endpoint to update them.

2.2.2.1 | Retrieve content management settings

get /public_api/v1/configurations/agent/content_management

Returns the current content management configuration for the tenant, including bandwidth control and minor content version update settings.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/content_management'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/content_management", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/content_management") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/content_management"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/content_management") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/content_management")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/content_management", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/content_management"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/content_management"); var request
= new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```

Responses

Successful response containing the current content management configuration.

Body
application/json

Current content management configuration settings.

▼ enable_bandwidth_controlboolean

Indicates whether bandwidth control is currently enabled for content downloads.

Example:`true`

▼ bandwidth_in_mbpsinteger

The current maximum bandwidth in megabits per second allocated for content downloads.

Example:`100`

▼ enable_minor_content_version_updatesboolean

Indicates whether automatic minor content version updates are currently enabled.

Example:`true`

RESPONSE

```
{ "enable_bandwidth_control": true, "bandwidth_in_mbps": 100, "enable_minor_content_version_updates": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.2 | Update content management settings

post /public_api/v1/configurations/agent/content_management/set

Updates the content management configuration for the tenant. Changes to bandwidth control and content version settings take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/content_management/set'
-d '{ "enable_minor_content_version_updates" : true, "bandwidth_in_mbps" : 100, "enable_bandwidth_control" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}" headers =
{ 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/content_management/set", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/content_management/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}" response
= http.request(request) puts response.read_body
const data = JSON.stringify({ "enable_bandwidth_control": true, "bandwidth_in_mbps": 100,
"enable_minor_content_version_updates": true }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/content_management/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/content_management/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = [ "enable_bandwidth_control": true, "bandwidth_in_mbps": 100, "enable_minor_content_version_updates":
true ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/configurations/agent/content_management/set")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/content_management/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/content_management/set"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/content_management/set"); var
request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"enable_bandwidth_control\":true,\"bandwidth_in_mbps\":100,\"enable_minor_content_version_updates\":true}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

Request payload for updating content management configuration.

▼ enable_bandwidth_controlbooleanrequired

Set to `true` to enable bandwidth control for content downloads.

Example:`true`

▼ bandwidth_in_mbpsintegerrequired

Specify the desired maximum bandwidth in megabits per second for content downloads. Must be at least 1.

Example:`100`

▼ enable_minor_content_version_updatesboolean

Set to `true` to enable automatic minor content version updates.

Example:`true`

REQUEST

```
{ "enable_bandwidth_control": true, "bandwidth_in_mbps": 100, "enable_minor_content_version_updates": true }
```

Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`

RESPONSE

```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.3 | Retrieve agent status timeout settings

get /public_api/v1/configurations/agent/agent_status

Returns the current agent status configuration for the tenant, including license revocation timeout and agent deletion retention period.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
```

```
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/agent_status'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/agent_status", headers=headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/configurations/agent/agent_status")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/agent_status")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/agent_status"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/agent_status"); var request = new
RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```

Responses

Successful response containing the current agent status configuration.

Body
application/json

Current agent status timeout configuration.

▼ license_revocation_after_lost_connectioninteger

The current number of days after which the license is revoked when an agent loses connection.

Example:`30`

▼ agent_deletion_retentioninteger

The current number of days agent data is retained before automatic deletion after disconnection.

Example:`90`

RESPONSE

```
{ "license_revocation_after_lost_connection": 30, "agent_deletion_retention": 90 }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.
RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.4 | Update agent status timeout settings

post /public_api/v1/configurations/agent/agent_status/set

Updates the agent status configuration for the tenant. Changes to license revocation and deletion retention settings take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/agent_status/set'
-d '{ "license_revocation_after_lost_connection" : 30, "agent_deletion_retention" : 90 }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/agent_status/set", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status/set") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "license_revocation_after_lost_connection": 30, "agent_deletion_retention": 90 }); const
xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("
{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = [ "license_revocation_after_lost_connection": 30, "agent_deletion_retention": 90 ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/agent_status/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/agent_status/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/agent_status/set"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
```

```
CURLOPT_POSTFIELDS, "{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}"); CURLcode ret
= curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/agent_status/set"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "
{\"license_revocation_after_lost_connection\":30,\"agent_deletion_retention\":90}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating agent status timeout configuration.

▼ license_revocation_after_lost_connectionintegerrequired

Specify the number of days after which the license should be revoked when an agent loses connection.

Example:`30`
▼ agent_deletion_retentionintegerrequired

Specify the number of days to retain agent data before automatic deletion after disconnection.

Example:`90`
REQUEST

```
{ "license_revocation_after_lost_connection": 30, "agent_deletion_retention": 90 }
```

Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE

```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.5 | Retrieve agent auto-upgrade settings

get /public_api/v1/configurations/agent/auto_upgrade

Returns the current agent auto upgrade configuration for the tenant, including the number of parallel upgrades allowed.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/auto_upgrade", headers=headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade"); var request = new
RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```
Responses

Successful response containing the current auto-upgrade configuration.

Body
application/json

Current agent auto-upgrade configuration.

▼ amount_of_parallel_upgradesinteger

The current maximum number of agents that can be upgraded simultaneously.

Example:10
RESPONSE
```
{ "amount_of_parallel_upgrades": 10 }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.6 | Update agent auto-upgrade settings

post /public_api/v1/configurations/agent/auto_upgrade/set

Updates the agent auto upgrade configuration for the tenant. Changes to parallel upgrade limits take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set'
-d '{ "amount_of_parallel_upgrades" : 10 }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"amount_of_parallel_upgrades\":10}"
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/auto_upgrade/set", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"amount_of_parallel_upgrades\":10}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "amount_of_parallel_upgrades": 10 }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"amount_of_parallel_upgrades\":10}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["amount_of_parallel_upgrades": 10] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"amount_of_parallel_upgrades\":10}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
```

```
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"amount_of_parallel_upgrades\":10}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/auto_upgrade/set"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"amount_of_parallel_upgrades\":10}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating agent auto-upgrade configuration.

▼ amount_of_parallel_upgradesintegerrequired

Specify the desired maximum number of agents to upgrade simultaneously.

Example:`10`
REQUEST
```
{ "amount_of_parallel_upgrades": 10 }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.7 | Retrieve WildFire analysis settings

get /public_api/v1/configurations/agent/wildfire_analysis

Returns the current WildFire analysis configuration for the tenant, including scoring settings for benign verdicts.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
```

```
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/wildfire_analysis", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis"); var request
= new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```

Responses

Successful response containing the current WildFire analysis configuration.

Body
application/json

Current WildFire analysis configuration.

▼ enable_wildfire_analysis_scoring_for_benign_verdictsboolean

Indicates whether WildFire analysis scoring is currently applied to files that received a benign verdict.

RESPONSE

```
{ "enable_wildfire_analysis_scoring_for_benign_verdicts": false }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.



RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.8 | Update WildFire analysis settings

post /public_api/v1/configurations/agent/wildfire_analysis/set

Updates the WildFire analysis configuration for the tenant. Changes to analysis scoring settings take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set'
-d '{ "enable_wildfire_analysis_scoring_for_benign_verdicts" : false }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/configurations/agent/wildfire_analysis/set",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "enable_wildfire_analysis_scoring_for_benign_verdicts": false }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["enable_wildfire_analysis_scoring_for_benign_verdicts": false] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}"); CURLcode ret =
curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/wildfire_analysis/set"); var
request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"enable_wildfire_analysis_scoring_for_benign_verdicts\":false}", ParameterType.RequestBody); IRestResponse response
= client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating WildFire analysis configuration.

▼ enable_wildfire_analysis_scoring_for_benign_verdictsbooleanrequired

Set to `true` to enable WildFire analysis scoring for files that received a benign verdict.

REQUEST
```
{ "enable_wildfire_analysis_scoring_for_benign_verdicts": false }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.9 | Retrieve informative BTP issues settings

get /public_api/v1/configurations/agent/informative_btp_issues

Returns the current configuration for displaying unique and informative BTP (Behavioral Threat Protection) rules.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
```

```
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/informative_btp_issues", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues"); var
request = new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response
= client.Execute(request);
```

Responses

Successful response containing the current BTP issues configuration.

Body
application/json

Current informative BTP issues display configuration.

▼ display_unique_and_informative_btp_rulesboolean

Indicates whether unique and informative Behavioral Threat Protection (BTP) rules are currently displayed in the console.

Example:`true`
RESPONSE

```
{ "display_unique_and_informative_btp_rules": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.



RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.10 | Update informative BTP issues settings

post /public_api/v1/configurations/agent/informative_btp_issues/set

Updates the configuration for displaying unique and informative BTP (Behavioral Threat Protection) rules. Changes take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set'
-d '{ "display_unique_and_informative_btp_rules" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"display_unique_and_informative_btp_rules\":true}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/configurations/agent/informative_btp_issues/set", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"display_unique_and_informative_btp_rules\":true}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "display_unique_and_informative_btp_rules": true }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"display_unique_and_informative_btp_rules\":true}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["display_unique_and_informative_btp_rules": true] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"display_unique_and_informative_btp_rules\":true}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"display_unique_and_informative_btp_rules\":true}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/informative_btp_issues/set"); var
request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
```

```
{\"display_unique_and_informative_btp_rules\":true}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating informative BTP issues display configuration.

▼ display_unique_and_informative_btp_rulesbooleanrequired

Set to `true` to display unique and informative Behavioral Threat Protection (BTP) rules in the console.

Example:`true`
REQUEST

```
{ "display_unique_and_informative_btp_rules": true }
```

Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE

```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.
RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.11 | Retrieve log collection settings

get /public_api/v1/configurations/agent/cortex_xdr_log_collection

Returns the current Cortex XDR log collection configuration for the tenant.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection'
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/cortex_xdr_log_collection", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection"); var
request = new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response
= client.Execute(request);
```

Responses

Successful response containing the current log collection configuration.

Body
application/json

Current Cortex XDR log collection configuration.

▼ allow_logs_collectionboolean

Indicates whether agents are currently allowed to collect and send diagnostic logs.

Example:`true`
RESPONSE

```
{ "allow_logs_collection": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.12 | Update log collection settings

post /public_api/v1/configurations/agent/cortex_xdr_log_collection/set

Updates the Cortex XDR log collection configuration for the tenant. Changes take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set'
-d '{ "allow_logs_collection" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"allow_logs_collection\":true}"
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/cortex_xdr_log_collection/set", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"allow_logs_collection\":true}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "allow_logs_collection": true }); const xhr = new XMLHttpRequest(); xhr.withCredentials
= true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"allow_logs_collection\":true}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["allow_logs_collection": true] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"allow_logs_collection\":true}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"allow_logs_collection\":true}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/cortex_xdr_log_collection/set");
var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"allow_logs_collection\":true}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required
application/json

Request payload for updating Cortex XDR log collection configuration.

▼ allow_logs_collectionbooleanrequired

Set to `true` to allow agents to collect and send diagnostic logs.

Example:`true`
REQUEST
```
{ "allow_logs_collection": true }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.13 | Retrieve action center expiration settings

get /public_api/v1/configurations/agent/action_center_expiration

Returns the current action center expiration settings for authorized actions, specifying timeout durations in hours.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/action_center_expiration", headers=headers) res =
```

```
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration"); var
request = new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response
= client.Execute(request);
```

Responses

Successful response containing the current action center expiration settings.

Body
application/json

Current action center expiration settings. Keys represent action types and values represent the current expiration durations in hours.

▶ Additional propertiesinteger

The current expiration duration in hours for the specified action type.

RESPONSE

```
{ "isolate": 72, "scan": 24 }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.14 | Update action center expiration settings

post /public_api/v1/configurations/agent/action_center_expiration/set

Updates the action center expiration settings for authorized actions. Timeout values are specified in hours. Changes take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"isolate\":72,\"scan\":24}" headers
= { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/action_center_expiration/set", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"isolate\":72,\"scan\":24}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "isolate": 72, "scan": 24 }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"isolate\":72,\"scan\":24}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = [ "isolate": 72, "scan": 24 ] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"isolate\":72,\"scan\":24}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"isolate\":72,\"scan\":24}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/action_center_expiration/set");
var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"isolate\":72,\"scan\":24}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

map[String, Integer]

required

application/json

Request payload for updating action center expiration settings. Specify action types as keys and desired expiration durations in hours as values.

▶ Additional propertiesinteger

Specify the desired expiration duration in hours for the action type.

REQUEST
```
{ "isolate": 72, "scan": 24 }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.15 | Retrieve critical environment versions settings

get /public_api/v1/configurations/agent/critical_environment_versions

Returns the current configuration for critical environment version monitoring.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/critical_environment_versions", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions");
var request = new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse
response = client.Execute(request);
```

Responses

Successful response containing the current critical environment versions configuration.

Body
application/json

Current critical environment versions configuration.

▼ enabled_critical_environment_versionsboolean

Indicates whether version enforcement is currently enabled for agents in critical environments.

Example:`true`
RESPONSE

```
{ "enabled_critical_environment_versions": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.2.2.16 | Update critical environment versions settings

post /public_api/v1/configurations/agent/critical_environment_versions/set

Updates the configuration for critical environment version monitoring. Changes take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set'
-d '{ "enabled_critical_environment_versions" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"enabled_critical_environment_versions\":true}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/configurations/agent/critical_environment_versions/set",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["x-xdr-auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"enabled_critical_environment_versions\":true}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "enabled_critical_environment_versions": true }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("
{\"enabled_critical_environment_versions\":true}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["enabled_critical_environment_versions": true] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"enabled_critical_environment_versions\":true}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"enabled_critical_environment_versions\":true}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-
yourfqdn/public_api/v1/configurations/agent/critical_environment_versions/set"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"enabled_critical_environment_versions\":true}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```
Body parameters
required
application/json

Request payload for updating critical environment versions configuration.

▼ enabled_critical_environment_versionsbooleanrequired

Set to `true` to enable version enforcement for agents in critical environments.

Example:`true`
REQUEST
```
{ "enabled_critical_environment_versions": true }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.17 | Retrieve advanced analysis settings

get /public_api/v1/configurations/agent/advanced_analysis

Returns the current advanced analysis configuration for the tenant, including automatic file upload and exception application settings.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/advanced_analysis", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
```

```
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis"); var request
= new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```

Responses

Successful response containing the current advanced analysis configuration.

Body
application/json

Current advanced analysis configuration.

▼ automatically_upload_defined_issue_data_filesboolean

Indicates whether defined issue data files are currently uploaded automatically for analysis.

Example:`true`

▼ automatically_apply_advanced_analysis_exceptionsboolean

Indicates whether advanced analysis exceptions are currently applied automatically.

RESPONSE

```
{ "automatically_upload_defined_issue_data_files": true, "automatically_apply_advanced_analysis_exceptions": false }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.18 | Update advanced analysis settings

post /public_api/v1/configurations/agent/advanced_analysis/set

Updates the advanced analysis configuration for the tenant. Changes to file upload and exception settings take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set'
-d '{ "automatically_upload_defined_issue_data_files" : true, "automatically_apply_advanced_analysis_exceptions" :
false }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}"
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/advanced_analysis/set", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "automatically_upload_defined_issue_data_files": true,
"automatically_apply_advanced_analysis_exceptions": false }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = [ "automatically_upload_defined_issue_data_files": true,
"automatically_apply_advanced_analysis_exceptions": false ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "
```

```
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/advanced_analysis/set"); var
request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"automatically_upload_defined_issue_data_files\":true,\"automatically_apply_advanced_analysis_exceptions\":false}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating advanced analysis configuration.

▼ automatically_upload_defined_issue_data_filesbooleanrequired

Set to `true` to automatically upload defined issue data files for analysis.

Example:`true`
▼ automatically_apply_advanced_analysis_exceptionsbooleanrequired

Set to `true` to automatically apply advanced analysis exceptions.

REQUEST
```
{ "automatically_upload_defined_issue_data_files": true, "automatically_apply_advanced_analysis_exceptions": false }
```
Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`
RESPONSE
```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.19 | Retrieve endpoint administration cleanup settings

get /public_api/v1/configurations/agent/endpoint_administration_cleanup

Returns the current endpoint administration cleanup configuration, including periodic duplicate cleanup settings and matching criteria.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE"
} conn.request("GET", "/public_api/v1/configurations/agent/endpoint_administration_cleanup", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .asString();
import Foundation let headers = ["x-xdr-auth-id": "REPLACE_KEY_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup"); var request = new
RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); IRestResponse response =
client.Execute(request);
```

Responses

Successful response containing the current cleanup configuration.

Body
application/json

Current endpoint administration cleanup configuration.

▼ periodic_duplicate_cleanupboolean

Indicates whether periodic cleanup of duplicate endpoints is currently enabled.

Example:`true`
▼ host_nameboolean

Indicates whether hostname is currently used as a criterion for identifying duplicate endpoints. Null when periodic cleanup is disabled.

Example:`true`
▼ ipboolean

Indicates whether IP address is currently used as a criterion for identifying duplicate endpoints. Null when periodic cleanup is disabled.

Example:`true`
▼ macboolean

Indicates whether MAC address is currently used as a criterion for identifying duplicate endpoints. Null when periodic cleanup is disabled.

▼ time_interval_hoursinteger (Enum)

The current time interval in hours between cleanup runs. Null when periodic cleanup is disabled. Valid values: `1` (hourly), `6` (every 6 hours), `24` (daily), `168` (weekly).

Example:`24`
Allowed values:1624168
RESPONSE

```
{ "periodic_duplicate_cleanup": true, "host_name": true, "ip": true, "mac": false, "time_interval_hours": 24 }
```


Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```


Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```


Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }

2.2.2.20 | Update endpoint administration cleanup settings

post /public_api/v1/configurations/agent/endpoint_administration_cleanup/set

Updates the endpoint administration cleanup configuration. Changes to duplicate cleanup settings take effect immediately.

Requires appropriate RBAC permissions for agent settings management.

Authentication: api-key-header-x-xdr-auth-id Api Key "x-xdr-auth-id"

Authentication: api-key-header-authorization Api Key "Authorization"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "x-xdr-auth-id: [[apiKey]]" \
-H "Authorization: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set'
-d '{ "time_interval_hours" : 24, "ip" : true, "periodic_duplicate_cleanup" : true, "host_name" : true, "mac" : false
}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}" headers
= { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/configurations/agent/endpoint_administration_cleanup/set", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["x-xdr-auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "
{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "periodic_duplicate_cleanup": true, "host_name": true, "ip": true, "mac": false,
"time_interval_hours": 24 }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
```

```
yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let parameters = [ "periodic_duplicate_cleanup": true, "host_name": true, "ip": true, "mac": false, "time_interval_hours": 24 ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/configurations/agent/endpoint_administration_cleanup/set"); var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"periodic_duplicate_cleanup\":true,\"host_name\":true,\"ip\":true,\"mac\":false,\"time_interval_hours\":24}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request payload for updating endpoint administration cleanup configuration.

▼ periodic_duplicate_cleanupbooleanrequired

Set to `true` to enable periodic cleanup of duplicate endpoints.

Example:`true`

▼ host_nameboolean

Set to `true` to use hostname as a criterion for identifying duplicate endpoints. Set to null to ignore this criterion.

Example:`true`

▼ ipboolean

Set to `true` to use IP address as a criterion for identifying duplicate endpoints. Set to null to ignore this criterion.

Example:`true`

▼ macboolean

Set to `true` to use MAC address as a criterion for identifying duplicate endpoints. Set to null to ignore this criterion.

▼ time_interval_hoursinteger (Enum)

Specify the desired time interval in hours between cleanup runs. Set to null when disabling periodic cleanup. Valid values: `1` (hourly), `6` (every 6 hours), `24` (daily), `168` (weekly).

Example:`24`
Allowed values:1624168
REQUEST

```
{ "periodic_duplicate_cleanup": true, "host_name": true, "ip": true, "mac": false, "time_interval_hours": 24 }
```

Responses

Successful response indicating the configuration was updated.

Body
application/json

Standard success response for configuration update operations.

▼ replyboolean

Indicates whether the operation completed successfully.

Example:`true`

RESPONSE

```
{ "reply": true }
```

Bad request. The request was malformed or contained invalid parameters.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Unauthorized. Authentication credentials are missing or invalid.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Forbidden. The API key does not have the required permissions.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

Internal server error.

Body
application/json

Standard error response returned when a request fails.

▼ replyobject

Error details container.

▶ err_codeinteger

Numeric error code identifying the type of error.

▶ err_msgstring

Human-readable error message describing what went wrong.

▶ err_extrastring

Additional context about the error, if available.

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Internal server error", "err_extra": "Additional error context" } }
```

2.3 | Cortex Cloud Alert Notification Rules REST APIs

2.3.1 | Preface

This OpenAPI Specification provides documentation about new Alert Notification Rules APIs for Cortex Cloud. With these endpoints, you can create, read, update, disable, and delete alert notification rules. These APIs are intended to be accessed via API keys. Therefore, the key must have the RBAC permission `alert_notifications` for list & read operations and permission `alert_notifications_action` for create, edit, enable/disable, & delete operations.

Version: Cortex Cloud

2.3.1.1 | Servers

https://api-{fqdn}

2.3.2 | Alert Notification Rules

Operations for managing rules including creation, editing, enabling/disabling, deletion, and listing rules.

2.3.2.1 | List all rules

get /platform/notifications/v1/list-rules

This endpoint retrieves a list of alert notification rules and returns their attributes. The meaning behind all attributes in this response could be found in the `Rule` schema. Please note that the field `legacy_mail_format` is set to False for all rules that were not created in legacy Xpanse environments.

CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/list-rules'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/notifications/v1/list-rules") res = conn.getresponse() data = res.read() print(data.decode("utf-
```

```
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/list-rules"); var request = new RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved rules

Body
application/json
▼ dataarray
[
▶ namestring

Name of the rule

▶ rule_uuidstring

The unique identifier of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestring

A required value from the LogForwardType Enum.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: `Africa/Abidjan`, `Africa/Accra`, `Africa/Addis_Ababa`, `Africa/Algiers`, `Africa/Asmara`, `Africa/Asmera`, `Africa/Bamako`, `Africa/Bangui`, `Africa/Banjul`, `Africa/Bissau`, `Africa/Blantyre`, `Africa/Brazzaville`, `Africa/Bujumbura`, `Africa/Cairo`, `Africa/Casablanca`, `Africa/Ceuta`, `Africa/Conakry`, `Africa/Dakar`, `Africa/Dar_es_Salaam`, `Africa/Djibouti`, `Africa/Douala`, `Africa/El_Aaiun`, `Africa/Freetown`, `Africa/Gaborone`, `Africa/Harare`, `Africa/Johannesburg`, `Africa/Juba`, `Africa/Kampala`, `Africa/Khartoum`, `Africa/Kigali`, `Africa/Kinshasa`, `Africa/Lagos`, `Africa/Libreville`, `Africa/Lome`, `Africa/Luanda`, `Africa/Lubumbashi`, `Africa/Lusaka`, `Africa/Malabo`, `Africa/Maputo`, `Africa/Maseru`, `Africa/Mbabane`, `Africa/Mogadishu`,

Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Timbuktu, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/ComodRivadavia, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Atka, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Buenos_Aires, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Catamarca, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Coral_Harbour, America/Cordoba, America/Costa_Rica, America/Coyhaique, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Ensenada, America/Fort_Nelson, America/Fort_Wayne, America/Fortaleza, America/Glace_Bay, America/Godthab, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Indianapolis, America/Inuvik, America/Iqaluit, America/Jamaica, America/Jujuy, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Knox_IN, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Louisville, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Mendoza, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montreal, America/Montserrat, America/Nassau, America/New_York, America/Nipigon, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Pangnirtung, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Acre, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rainy_River, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Rosario, America/Santa_Isabel, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Shiprock, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Thunder_Bay, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Virgin, America/Whitehorse, America/Winnipeg, America/Yakutat, America/Yellowknife, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/South_Pole, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Ashkhabad, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Calcutta, Asia/Chita, Asia/Choibalsan, Asia/Chongqing, Asia/Chungking, Asia/Colombo, Asia/Dacca, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Harbin, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Istanbul, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kashgar, Asia/Kathmandu, Asia/Katmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macao, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Rangoon, Asia/Riyadh, Asia/Saigon, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Tel_Aviv, Asia/Thimbu, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ujung_Pandang, Asia/Ulaanbaatar, Asia/Ulan_Bator, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faeroe, Atlantic/Faroe, Atlantic/Jan_Mayen, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/ACT, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Canberra, Australia/Currie, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/LHI, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/NSW, Australia/North, Australia/Perth, Australia/Queensland, Australia/South, Australia/Sydney, Australia/Tasmania, Australia/Victoria, Australia/West, Australia/Yancowinna, Brazil/Acre, Brazil/DeNoronha, Brazil/East, Brazil/West, CET, CST6CDT, Canada/Atlantic, Canada/Central, Canada/Eastern, Canada/Mountain, Canada/Newfoundland, Canada/Pacific, Canada/Saskatchewan, Canada/Yukon, Chile/Continental, Chile/EasterIsland, Cuba, EET, EST, EST5EDT, Egypt, Eire, Etc/GMT, Etc/GMT+0, Etc/GMT+1, Etc/GMT+10, Etc/GMT+11, Etc/GMT+12, Etc/GMT+2, Etc/GMT+3, Etc/GMT+4, Etc/GMT+5, Etc/GMT+6, Etc/GMT+7, Etc/GMT+8, Etc/GMT+9, Etc/GMT-0, Etc/GMT-1, Etc/GMT-10, Etc/GMT-11, Etc/GMT-12, Etc/GMT-13, Etc/GMT-14, Etc/GMT-2, Etc/GMT-3, Etc/GMT-4, Etc/GMT-5, Etc/GMT-6, Etc/GMT-7, Etc/GMT-8, Etc/GMT-9, Etc/GMT0, Etc/Greenwich, Etc/UCT, Etc/UTC, Etc/Universal, Etc/Zulu, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belfast, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich,



HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for mail integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI. Note: the `legacy_alert` format is not permissible for Slack.

▶ created_bystring

This string indicates the user or api-key responsible for creating the notification rule.

▶ created_atintegerint64

This value represents the timestamp when the notification rule was created.

▶ modified_atintegerint64

This value represents the timestamp when the notification rule was last modified.

▶ enabledboolean

A flag indicating whether the notification rule is currently active and enabled.

]

▼ metadataobject

Metadata for the response

Free-Form object

RESPONSE


```
{ "data": [ { "rule_uuid": "5b0082c2-c0e3-4cad-b354-415d496ad995", "name": "Test Rule 1", "description": "This is a
description placeholder", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": false } ] } }, "applications": [ "1111-TeSt-1223-09ID-415305650" ], "forward_source": {},
"forward_type": "alert", "time_zone": "Pacific/Nauru", "slack_format": "issue", "syslog_format": "issue",
"mail_format": "issue", "created_by": "testuser@paloaltonetworks.com", "created_at": 1764873308164, "modified_at":
1764873308164, "enabled": true }, { "rule_uuid": "5b0082c2-c0e3-4c2d-b354-415d496ad990", "name": "Test Rule 2",
"description": "another test description", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "severity",
"SEARCH_TYPE": "EQ", "SEARCH_VALUE": "SEV_040_HIGH" } ] } }, "applications": [ "2222-TeSt-1223-09ID-415305650" ],
"forward_source": { "email": { "aggregation": 1200, "distribution_list": [ "testuser@gmail.com" ],
"legacy_mail_format": false } }, "forward_type": "alert", "time_zone": "Pacific/Nauru", "slack_format": "issue",
"syslog_format": "standard_alert", "mail_format": "issue", "created_by": "testuser@paloaltonetworks.com",
"created_at": 1764878761056, "modified_at": 1764878761056, "enabled": true } ], "metadata": { "total_count": 2 } }
```


Body

application/json

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body

application/json

▼ replyobject

▶ err_msgstring

▶ err_extrastring

▶ err_codeinteger

RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }
```

2.3.2.2 | Create a new rule

post /platform/notifications/v1/rule

This endpoint allows the user to create a new alert notification rule and specify its attributes. To see the possible `forward_type` values, please check the relevant enum named `LogForwardType` for additional information. The `forward_source` attribute is where a user would define email, Slack, and Syslog configurations; the required formats for these fields are documented in the `RuleCreateRequest` schema. The `applications` attribute is a list of external applications application IDs (webhook, AWS S3, AWS SQS, and Splunk). The `mail_format`, `syslog_format`, and `slack_format` attributes represent whether the user would like the notifications for these integrations to be issues or alerts formats; more information is provided in the `RuleCreateRequest` schema.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/rule'
-d '{ "request_data" : { "name" : "Test Rule 01", "description" : "a description for the test rule", "forward_type" : "alert", "filter" : { "filter" : { "AND" : [ { "SEARCH_FIELD" : "is_whitelisted", "SEARCH_TYPE" : "EQ", "SEARCH_VALUE" : false } ] } }, "forward_source" : { "email" : { "distribution_list" : [ "testuser@paloaltonetworks.com" ], "aggregation" : 1000 }, "syslog" : { "id" : 1 }, "slack" : { "channels" : [ "slack-test-channel1" ] } }, "applications" : [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "time_zone" : "Pacific/Nauru", "mail_format" : "issue", "syslog_format" : "standard_alert", "slack_format" : "issue" } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
headers = { 'content-type': "application/json" } conn.request("POST", "%7Bfqdn%7D/platform/notifications/v1/rule", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "Test Rule 01", "description": "a description for the test rule", "forward_type": "alert", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false } ] } }, "forward_source": { "email": { "distribution_list": [ "testuser@paloaltonetworks.com" ], "aggregation": 1000 }, "syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-channel1" ] } }, "applications": [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "time_zone": "Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-/%7Bfqdn%7D/platform/notifications/v1/rule"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule")
.header("content-type", "application/json") .body("{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
.asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "name": "Test Rule 01", "description": "a description for the test rule", "forward_type": "alert", "filter": ["filter": ["AND": [ [
```

```
"SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false ] ]]], "forward_source": [ "email": [
"distribution_list": ["testuser@paloaltonetworks.com"], "aggregation": 1000 ], "syslog": ["id": 1], "slack":
["channels": ["slack-test-channel1"]] ], "applications": ["63e3ad1f-0efc-401d-90dd-a305ab6053a4"], "time_zone":
"Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue" ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/notifications/v1/rule")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description for the
test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a
description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule"); var request = new
RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description
for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json

Enumerates the rule creation request schema for Alert Notifications

▼ request_dataobject
▶ namestringrequired

Name of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestringrequired

A required value from the LogForwardType Enum.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: `Africa/Abidjan`, `Africa/Accra`, `Africa/Addis_Ababa`, `Africa/Algiers`, `Africa/Asmara`, `Africa/Asmera`, `Africa/Bamako`, `Africa/Bangui`, `Africa/Banjul`, `Africa/Bissau`, `Africa/Blantyre`, `Africa/Brazzaville`, `Africa/Bujumbura`, `Africa/Cairo`, `Africa/Casablanca`, `Africa/Ceuta`, `Africa/Conakry`, `Africa/Dakar`, `Africa/Dar_es_Salaam`, `Africa/Djibouti`, `Africa/Douala`, `Africa/El_Aaiun`, `Africa/Freetown`, `Africa/Gaborone`, `Africa/Harare`, `Africa/Johannesburg`, `Africa/Juba`, `Africa/Kampala`, `Africa/Khartoum`, `Africa/Kigali`, `Africa/Kinshasa`, `Africa/Lagos`, `Africa/Libreville`, `Africa/Lome`, `Africa/Luanda`, `Africa/Lubumbashi`, `Africa/Lusaka`, `Africa/Malabo`, `Africa/Maputo`, `Africa/Maseru`, `Africa/Mbabane`, `Africa/Mogadishu`, `Africa/Monrovia`, `Africa/Nairobi`, `Africa/Ndjamena`, `Africa/Niamey`, `Africa/Nouakchott`, `Africa/Ouagadougou`, `Africa/Porto-Novo`, `Africa/Sao_Tome`, `Africa/Timbuktu`, `Africa/Tripoli`, `Africa/Tunis`, `Africa/Windhoek`, `America/Adak`, `America/Anchorage`, `America/Anguilla`, `America/Antigua`, `America/Araguaina`, `America/Argentina/Buenos_Aires`, `America/Argentina/Catamarca`, `America/Argentina/ComodRivadavia`, `America/Argentina/Cordoba`, `America/Argentina/Jujuy`, `America/Argentina/La_Rioja`, `America/Argentina/Mendoza`, `America/Argentina/Rio_Gallegos`, `America/Argentina/Salta`, `America/Argentina/San_Juan`, `America/Argentina/San_Luis`, `America/Argentina/Tucuman`, `America/Argentina/Ushuaia`, `America/Aruba`, `America/Asuncion`, `America/Atikokan`, `America/Atka`, `America/Bahia`, `America/Bahia_Banderas`, `America/Barbados`, `America/Belem`, `America/Belize`, `America/Blanc-Sablon`, `America/Boa_Vista`, `America/Bogota`, `America/Boise`, `America/Buenos_Aires`, `America/Cambridge_Bay`, `America/Campo_Grande`, `America/Cancun`, `America/Caracas`, `America/Catamarca`, `America/Cayenne`, `America/Cayman`, `America/Chicago`, `America/Chihuahua`, `America/Ciudad_Juarez`, `America/Coral_Harbour`, `America/Cordoba`, `America/Costa_Rica`, `America/Coyhaique`, `America/Creston`, `America/Cuiaba`, `America/Curacao`, `America/Danmarkshavn`, `America/Dawson`, `America/Dawson_Creek`, `America/Denver`, `America/Detroit`, `America/Dominica`, `America/Edmonton`, `America/Eirunepe`, `America/El_Salvador`, `America/Ensenada`, `America/Fort_Nelson`, `America/Fort_Wayne`, `America/Fortaleza`, `America/Glace_Bay`, `America/Godthab`, `America/Goose_Bay`, `America/Grand_Turk`, `America/Grenada`, `America/Guadeloupe`, `America/Guatemala`, `America/Guayaquil`, `America/Guyana`, `America/Halifax`, `America/Havana`, `America/Hermosillo`, `America/Indiana/Indianapolis`, `America/Indiana/Knox`, `America/Indiana/Marengo`, `America/Indiana/Petersburg`, `America/Indiana/Tell_City`, `America/Indiana/Vevay`, `America/Indiana/Vincennes`, `America/Indiana/Winamac`, `America/Indianapolis`, `America/Inuvik`, `America/Iqaluit`, `America/Jamaica`, `America/Jujuy`, `America/Juneau`, `America/Kentucky/Louisville`, `America/Kentucky/Monticello`, `America/Knox_IN`, `America/Kralendijk`, `America/La_Paz`, `America/Lima`, `America/Los_Angeles`, `America/Louisville`, `America/Lower_Princes`, `America/Maceio`, `America/Managua`, `America/Manaus`, `America/Marigot`, `America/Martinique`, `America/Matamoros`, `America/Mazatlan`, `America/Mendoza`, `America/Menominee`, `America/Merida`, `America/Metlakatla`, `America/Mexico_City`, `America/Miquelon`, `America/Moncton`, `America/Monterrey`, `America/Montevideo`, `America/Montreal`, `America/Montserrat`, `America/Nassau`, `America/New_York`, `America/Nipigon`, `America/Nome`, `America/Noronha`, `America/North_Dakota/Beulah`, `America/North_Dakota/Center`, `America/North_Dakota/New_Salem`, `America/Nuuk`, `America/Ojinaga`, `America/Panama`, `America/Pangnirtung`, `America/Paramaribo`, `America/Phoenix`, `America/Port-au-Prince`, `America/Port_of_Spain`, `America/Porto_Acre`, `America/Porto_Velho`, `America/Puerto_Rico`, `America/Punta_Arenas`, `America/Rainy_River`, `America/Rankin_Inlet`, `America/Recife`, `America/Regina`, `America/Resolute`, `America/Rio_Branco`, `America/Rosario`, `America/Santa_Isabel`, `America/Santarem`, `America/Santiago`, `America/Santo_Domingo`, `America/Sao_Paulo`, `America/Scoresbysund`, `America/Shiprock`, `America/Sitka`, `America/St_Barthelemy`, `America/St_Johns`, `America/St_Kitts`, `America/St_Lucia`, `America/St_Thomas`, `America/St_Vincent`, `America/Swift_Current`, `America/Tegucigalpa`, `America/Thule`, `America/Thunder_Bay`, `America/Tijuana`, `America/Toronto`, `America/Tortola`, `America/Vancouver`, `America/Virgin`, `America/Whitehorse`, `America/Winnipeg`, `America/Yakutat`, `America/Yellowknife`, `Antarctica/Casey`, `Antarctica/Davis`, `Antarctica/DumontDUrville`, `Antarctica/Macquarie`, `Antarctica/Mawson`, `Antarctica/McMurdo`, `Antarctica/Palmer`, `Antarctica/Rothera`, `Antarctica/South_Pole`, `Antarctica/Syowa`, `Antarctica/Troll`, `Antarctica/Vostok`, `Arctic/Longyearbyen`, `Asia/Aden`, `Asia/Almaty`, `Asia/Amman`, `Asia/Anadyr`, `Asia/Aqtau`, `Asia/Aqtobe`, `Asia/Ashgabat`, `Asia/Ashkhabad`, `Asia/Atyrau`, `Asia/Baghdad`, `Asia/Bahrain`, `Asia/Baku`, `Asia/Bangkok`, `Asia/Barnaul`, `Asia/Beirut`, `Asia/Bishkek`, `Asia/Brunei`, `Asia/Calcutta`, `Asia/Chita`, `Asia/Choibalsan`, `Asia/Chongqing`, `Asia/Chungking`, `Asia/Colombo`, `Asia/Dacca`, `Asia/Damascus`, `Asia/Dhaka`, `Asia/Dili`, `Asia/Dubai`, `Asia/Dushanbe`, `Asia/Famagusta`, `Asia/Gaza`, `Asia/Harbin`, `Asia/Hebron`, `Asia/Ho_Chi_Minh`, `Asia/Hong_Kong`, `Asia/Hovd`, `Asia/Irkutsk`, `Asia/Istanbul`, `Asia/Jakarta`, `Asia/Jayapura`, `Asia/Jerusalem`, `Asia/Kabul`, `Asia/Kamchatka`, `Asia/Karachi`, `Asia/Kashgar`, `Asia/Kathmandu`, `Asia/Katmandu`, `Asia/Khandyga`, `Asia/Kolkata`, `Asia/Krasnoyarsk`, `Asia/Kuala_Lumpur`, `Asia/Kuching`, `Asia/Kuwait`, `Asia/Macao`, `Asia/Macau`, `Asia/Magadan`, `Asia/Makassar`, `Asia/Manila`, `Asia/Muscat`, `Asia/Nicosia`, `Asia/Novokuznetsk`, `Asia/Novosibirsk`, `Asia/Omsk`, `Asia/Oral`, `Asia/Phnom_Penh`, `Asia/Pontianak`, `Asia/Pyongyang`, `Asia/Qatar`, `Asia/Qostanay`, `Asia/Qyzylorda`, `Asia/Rangoon`, `Asia/Riyadh`, `Asia/Saigon`, `Asia/Sakhalin`, `Asia/Samarkand`, `Asia/Seoul`, `Asia/Shanghai`, `Asia/Singapore`, `Asia/Srednekolymsk`, `Asia/Taipei`, `Asia/Tashkent`, `Asia/Tbilisi`, `Asia/Tehran`, `Asia/Tel_Aviv`, `Asia/Thimbu`, `Asia/Thimphu`, `Asia/Tokyo`, `Asia/Tomsk`, `Asia/Ujung_Pandang`, `Asia/Ulaanbaatar`, `Asia/Ulan_Bator`, `Asia/Urumqi`, `Asia/Ust-Nera`, `Asia/Vientiane`, `Asia/Vladivostok`, `Asia/Yakutsk`, `Asia/Yangon`, `Asia/Yekaterinburg`, `Asia/Yerevan`, `Atlantic/Azores`, `Atlantic/Bermuda`, `Atlantic/Canary`, `Atlantic/Cape_Verde`, `Atlantic/Faeroe`, `Atlantic/Faroe`, `Atlantic/Jan_Mayen`, `Atlantic/Madeira`, `Atlantic/Reykjavik`, `Atlantic/South_Georgia`, `Atlantic/St_Helena`, `Atlantic/Stanley`, `Australia/ACT`, `Australia/Adelaide`, `Australia/Brisbane`, `Australia/Broken_Hill`, `Australia/Canberra`, `Australia/Currie`, `Australia/Darwin`, `Australia/Eucla`, `Australia/Hobart`, `Australia/LHI`, `Australia/Lindeman`, `Australia/Lord_Howe`, `Australia/Melbourne`, `Australia/NSW`, `Australia/North`, `Australia/Perth`, `Australia/Queensland`, `Australia/South`, `Australia/Sydney`, `Australia/Tasmania`, `Australia/Victoria`, `Australia/West`, `Australia/Yancowinna`, `Brazil/Acre`, `Brazil/DeNoronha`, `Brazil/East`, `Brazil/West`, `CET`, `CST6CDT`, `Canada/Atlantic`, `Canada/Central`, `Canada/Eastern`, `Canada/Mountain`, `Canada/Newfoundland`, `Canada/Pacific`, `Canada/Saskatchewan`, `Canada/Yukon`, `Chile/Continental`, `Chile/EasterIsland`, `Cuba`, `EET`, `EST`, `EST5EDT`, `Egypt`, `Eire`, `Etc/GMT`, `Etc/GMT+0`, `Etc/GMT+1`, `Etc/GMT+10`, `Etc/GMT+11`, `Etc/GMT+12`, `Etc/GMT+2`, `Etc/GMT+3`, `Etc/GMT+4`, `Etc/GMT+5`, `Etc/GMT+6`, `Etc/GMT+7`, `Etc/GMT+8`, `Etc/GMT+9`, `Etc/GMT-0`, `Etc/GMT-1`, `Etc/GMT-10`, `Etc/GMT-11`, `Etc/GMT-12`, `Etc/GMT-13`, `Etc/GMT-14`, `Etc/GMT-2`, `Etc/GMT-3`, `Etc/GMT-4`, `Etc/GMT-5`, `Etc/GMT-6`, `Etc/GMT-7`, `Etc/GMT-8`, `Etc/GMT-9`, `Etc/GMT0`, `Etc/Greenwich`, `Etc/UCT`, `Etc/UTC`, `Etc/Universal`, `Etc/Zulu`, `Europe/Amsterdam`, `Europe/Andorra`, `Europe/Astrakhan`, `Europe/Athens`, `Europe/Belfast`, `Europe/Belgrade`, `Europe/Berlin`,

Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich, HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for mail integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.Not: the `legacy_alert` format is not permissible for Slack.

REQUEST

```
{ "request_data": { "name": "Test Rule 01", "description": "a description for the test rule", "forward_type": "alert", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false } ] } }, "forward_source": { "email": { "distribution_list": [ "testuser@paloaltonetworks.com" ], "aggregation": 1000 }, "syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-channel1" ] } }, "applications": [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "time_zone": "Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue" } }
```

Responses

Body

application/json

▼ dataobject

▶ namestring

Name of the rule

▶ rule_uuidstring

The unique identifier of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestring

A required value from the LogForwardType Enum.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: `Africa/Abidjan`, `Africa/Accra`, `Africa/Addis_Ababa`, `Africa/Algiers`, `Africa/Asmara`, `Africa/Asmera`, `Africa/Bamako`, `Africa/Bangui`, `Africa/Banjul`, `Africa/Bissau`, `Africa/Blantyre`, `Africa/Brazzaville`, `Africa/Bujumbura`, `Africa/Cairo`, `Africa/Casablanca`, `Africa/Ceuta`, `Africa/Conakry`, `Africa/Dakar`, `Africa/Dar_es_Salaam`, `Africa/Djibouti`, `Africa/Douala`, `Africa/El_Aaiun`, `Africa/Freetown`, `Africa/Gaborone`, `Africa/Harare`, `Africa/Johannesburg`, `Africa/Juba`, `Africa/Kampala`, `Africa/Khartoum`, `Africa/Kigali`, `Africa/Kinshasa`, `Africa/Lagos`, `Africa/Libreville`, `Africa/Lome`, `Africa/Luanda`, `Africa/Lubumbashi`, `Africa/Lusaka`, `Africa/Malabo`, `Africa/Maputo`, `Africa/Maseru`, `Africa/Mbabane`, `Africa/Mogadishu`, `Africa/Monrovia`, `Africa/Nairobi`, `Africa/Ndjamena`, `Africa/Niamey`, `Africa/Nouakchott`, `Africa/Ouagadougou`, `Africa/Porto-Novo`, `Africa/Sao_Tome`, `Africa/Timbuktu`, `Africa/Tripoli`, `Africa/Tunis`, `Africa/Windhoek`, `America/Adak`, `America/Anchorage`, `America/Anguilla`, `America/Antigua`, `America/Araguaina`, `America/Argentina/Buenos_Aires`, `America/Argentina/Catamarca`, `America/Argentina/ComodRivadavia`, `America/Argentina/Cordoba`, `America/Argentina/Jujuy`, `America/Argentina/La_Rioja`, `America/Argentina/Mendoza`, `America/Argentina/Rio_Gallegos`, `America/Argentina/Salta`, `America/Argentina/San_Juan`, `America/Argentina/San_Luis`, `America/Argentina/Tucuman`, `America/Argentina/Ushuaia`, `America/Aruba`, `America/Asuncion`, `America/Atikokan`, `America/Atka`, `America/Bahia`, `America/Bahia_Banderas`, `America/Barbados`, `America/Belem`, `America/Belize`, `America/Blanc-Sablon`, `America/Boa_Vista`, `America/Bogota`, `America/Boise`, `America/Buenos_Aires`, `America/Cambridge_Bay`, `America/Campo_Grande`, `America/Cancun`, `America/Caracas`, `America/Catamarca`, `America/Cayenne`, `America/Cayman`, `America/Chicago`, `America/Chihuahua`, `America/Ciudad_Juarez`, `America/Coral_Harbour`, `America/Cordoba`, `America/Costa_Rica`, `America/Coyhaique`, `America/Creston`, `America/Cuiaba`, `America/Curacao`, `America/Danmarkshavn`, `America/Dawson`, `America/Dawson_Creek`, `America/Denver`, `America/Detroit`, `America/Dominica`, `America/Edmonton`, `America/Eirunepe`, `America/El_Salvador`, `America/Ensenada`, `America/Fort_Nelson`, `America/Fort_Wayne`, `America/Fortaleza`, `America/Glace_Bay`, `America/Godthab`, `America/Goose_Bay`, `America/Grand_Turk`, `America/Grenada`, `America/Guadeloupe`, `America/Guatemala`, `America/Guayaquil`, `America/Guyana`, `America/Halifax`, `America/Havana`, `America/Hermosillo`, `America/Indiana/Indianapolis`, `America/Indiana/Knox`, `America/Indiana/Marengo`, `America/Indiana/Petersburg`, `America/Indiana/Tell_City`, `America/Indiana/Vevay`, `America/Indiana/Vincennes`, `America/Indiana/Winamac`, `America/Indianapolis`, `America/Inuvik`, `America/Iqaluit`, `America/Jamaica`, `America/Jujuy`, `America/Juneau`, `America/Kentucky/Louisville`, `America/Kentucky/Monticello`, `America/Knox_IN`, `America/Kralendijk`, `America/La_Paz`, `America/Lima`, `America/Los_Angeles`, `America/Louisville`, `America/Lower_Princes`, `America/Maceio`, `America/Managua`, `America/Manaus`, `America/Marigot`, `America/Martinique`, `America/Matamoros`, `America/Mazatlan`, `America/Mendoza`, `America/Menominee`, `America/Merida`, `America/Metlakatla`, `America/Mexico_City`, `America/Miquelon`, `America/Moncton`, `America/Monterrey`, `America/Montevideo`, `America/Montreal`, `America/Montserrat`, `America/Nassau`, `America/New_York`, `America/Nipigon`, `America/Nome`, `America/Noronha`, `America/North_Dakota/Beulah`, `America/North_Dakota/Center`, `America/North_Dakota/New_Salem`, `America/Nuuk`, `America/Ojinaga`, `America/Panama`, `America/Pangnirtung`, `America/Paramaribo`, `America/Phoenix`, `America/Port-au-Prince`, `America/Port_of_Spain`, `America/Porto_Acre`, `America/Porto_Velho`, `America/Puerto_Rico`, `America/Punta_Arenas`, `America/Rainy_River`, `America/Rankin_Inlet`, `America/Recife`, `America/Regina`, `America/Resolute`, `America/Rio_Branco`, `America/Rosario`, `America/Santa_Isabel`, `America/Santarem`, `America/Santiago`, `America/Santo_Domingo`, `America/Sao_Paulo`, `America/Scoresbysund`, `America/Shiprock`, `America/Sitka`, `America/St_Barthelemy`, `America/St_Johns`, `America/St_Kitts`, `America/St_Lucia`, `America/St_Thomas`, `America/St_Vincent`, `America/Swift_Current`, `America/Tegucigalpa`, `America/Thule`, `America/Thunder_Bay`, `America/Tijuana`, `America/Toronto`, `America/Tortola`, `America/Vancouver`, `America/Virgin`, `America/Whitehorse`, `America/Winnipeg`, `America/Yakutat`, `America/Yellowknife`, `Antarctica/Casey`, `Antarctica/Davis`, `Antarctica/DumontDUrville`, `Antarctica/Macquarie`, `Antarctica/Mawson`, `Antarctica/McMurdo`, `Antarctica/Palmer`, `Antarctica/Rothera`, `Antarctica/South_Pole`, `Antarctica/Syowa`, `Antarctica/Troll`, `Antarctica/Vostok`, `Arctic/Longyearbyen`, `Asia/Aden`, `Asia/Almaty`, `Asia/Amman`, `Asia/Anadyr`, `Asia/Aqtau`, `Asia/Aqtobe`, `Asia/Ashgabat`, `Asia/Ashkhabad`, `Asia/Atyrau`, `Asia/Baghdad`, `Asia/Bahrain`, `Asia/Baku`, `Asia/Bangkok`, `Asia/Barnaul`, `Asia/Beirut`, `Asia/Bishkek`, `Asia/Brunei`, `Asia/Calcutta`, `Asia/Chita`, `Asia/Choibalsan`, `Asia/Chongqing`, `Asia/Chungking`, `Asia/Colombo`, `Asia/Dacca`, `Asia/Damascus`, `Asia/Dhaka`, `Asia/Dili`, `Asia/Dubai`, `Asia/Dushanbe`, `Asia/Famagusta`, `Asia/Gaza`, `Asia/Harbin`, `Asia/Hebron`, `Asia/Ho_Chi_Minh`, `Asia/Hong_Kong`, `Asia/Hovd`, `Asia/Irkutsk`, `Asia/Istanbul`, `Asia/Jakarta`, `Asia/Jayapura`, `Asia/Jerusalem`, `Asia/Kabul`, `Asia/Kamchatka`, `Asia/Karachi`, `Asia/Kashgar`, `Asia/Kathmandu`, `Asia/Katmandu`, `Asia/Khandyga`, `Asia/Kolkata`, `Asia/Krasnoyarsk`, `Asia/Kuala_Lumpur`, `Asia/Kuching`, `Asia/Kuwait`, `Asia/Macao`, `Asia/Macau`, `Asia/Magadan`, `Asia/Makassar`, `Asia/Manila`, `Asia/Muscat`, `Asia/Nicosia`, `Asia/Novokuznetsk`, `Asia/Novosibirsk`, `Asia/Omsk`, `Asia/Oral`, `Asia/Phnom_Penh`, `Asia/Pontianak`, `Asia/Pyongyang`, `Asia/Qatar`, `Asia/Qostanay`, `Asia/Qyzylorda`, `Asia/Rangoon`, `Asia/Riyadh`, `Asia/Saigon`, `Asia/Sakhalin`, `Asia/Samarkand`, `Asia/Seoul`, `Asia/Shanghai`, `Asia/Singapore`, `Asia/Srednekolymsk`, `Asia/Taipei`, `Asia/Tashkent`, `Asia/Tbilisi`, `Asia/Tehran`, `Asia/Tel_Aviv`, `Asia/Thimbu`, `Asia/Thimphu`, `Asia/Tokyo`, `Asia/Tomsk`, `Asia/Ujung_Pandang`, `Asia/Ulaanbaatar`, `Asia/Ulan_Bator`, `Asia/Urumqi`, `Asia/Ust-Nera`, `Asia/Vientiane`, `Asia/Vladivostok`, `Asia/Yakutsk`, `Asia/Yangon`, `Asia/Yekaterinburg`, `Asia/Yerevan`, `Atlantic/Azores`, `Atlantic/Bermuda`, `Atlantic/Canary`, `Atlantic/Cape_Verde`, `Atlantic/Faeroe`, `Atlantic/Faroe`, `Atlantic/Jan_Mayen`, `Atlantic/Madeira`, `Atlantic/Reykjavik`, `Atlantic/South_Georgia`, `Atlantic/St_Helena`, `Atlantic/Stanley`, `Australia/ACT`, `Australia/Adelaide`, `Australia/Brisbane`, `Australia/Broken_Hill`, `Australia/Canberra`, `Australia/Currie`, `Australia/Darwin`, `Australia/Eucla`, `Australia/Hobart`, `Australia/LHI`, `Australia/Lindeman`, `Australia/Lord_Howe`, `Australia/Melbourne`, `Australia/NSW`, `Australia/North`, `Australia/Perth`, `Australia/Queensland`, `Australia/South`, `Australia/Sydney`, `Australia/Tasmania`, `Australia/Victoria`, `Australia/West`, `Australia/Yancowinna`, `Brazil/Acre`, `Brazil/DeNoronha`, `Brazil/East`, `Brazil/West`, `CET`, `CST6CDT`, `Canada/Atlantic`, `Canada/Central`, `Canada/Eastern`, `Canada/Mountain`, `Canada/Newfoundland`, `Canada/Pacific`, `Canada/Saskatchewan`, `Canada/Yukon`, `Chile/Continental`, `Chile/EasterIsland`, `Cuba`, `EET`, `EST`, `EST5EDT`, `Egypt`, `Eire`, `Etc/GMT`, `Etc/GMT+0`, `Etc/GMT+1`, `Etc/GMT+10`, `Etc/GMT+11`, `Etc/GMT+12`, `Etc/GMT+2`, `Etc/GMT+3`, `Etc/GMT+4`, `Etc/GMT+5`, `Etc/GMT+6`, `Etc/GMT+7`,

Etc/GMT+8, Etc/GMT+9, Etc/GMT-0, Etc/GMT-1, Etc/GMT-10, Etc/GMT-11, Etc/GMT-12, Etc/GMT-13, Etc/GMT-14, Etc/GMT-2, Etc/GMT-3, Etc/GMT-4, Etc/GMT-5, Etc/GMT-6, Etc/GMT-7, Etc/GMT-8, Etc/GMT-9, Etc/GMT0, Etc/Greenwich, Etc/UCT, Etc/UTC, Etc/Universal, Etc/Zulu, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belfast, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich, HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for mail integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI. Note: the `legacy_alert` format is not permissible for Slack.

▶ created_bystring

This string indicates the user or api-key responsible for creating the notification rule.

▶ created_atintegerint64

This value represents the timestamp when the notification rule was created.

▶ modified_atintegerint64

This value represents the timestamp when the notification rule was last modified.

▶ enabledboolean

A flag indicating whether the notification rule is currently active and enabled.

RESPONSE


```
{ "data": { "rule_uuid": "3053ad1f-0efc-305d-90dd-a305ab4153a4", "name": "Test Rule 01", "description": "a description for the test rule", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false } ] } }, "applications": [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "forward_source": { "email": { "distribution_list": [ "testuser@paloaltonetworks.com" ], "aggregation": 1000, "legacy_mail_format": false }, "syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-channel1" ] } }, "forward_type": "alert", "time_zone": "Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue", "created_by": "testuser@paloaltonetworks.com", "created_at": 1764958056697, "modified_at": 1764958056697, "enabled": true } }
```


Body

application/json

▼ dataobject

▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject

RESPONSE

{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "The mail format field provided is invalid.", "err_code": 400 } } }

Body
application/json
RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }

2.3.2.3 | Retrieve a specific alert notification rule

get /platform/notifications/v1/rule/{rule_uuid}

This endpoint retrieves an alert notification rule and returns its attributes. The meaning behind all attributes in this response could be found in the `Rule` schema. Please note that the field `legacy_mail_format` is set to False for all rules that were not created in legacy Xpanse environments.

Path parameters
▼ rule_uuid String required

Full rule uuid of the Alert Notification Rule

Example: `3053ad1f-0efc-305d-90dd-a305ab4153a4`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/rule/{rule_uuid}'
```
```
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4") res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
```
```
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
```
```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET",
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4"); xhr.send(data);
```
```
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-
305d-90dd-a305ab4153a4") .asString();
```
```
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
```
```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4", CURLOPT_RETURNTRANSFER
=> true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION =>
CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```
```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4"); CURLcode ret =
curl_easy_perform(hnd);
```
```
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-
a305ab4153a4"); var request = new RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```
Responses

Successfully retrieved rule

Body
application/json
▼ dataobject

Enumerates the various attributes of an alert notification rule that is returned via numerous flows.

▶ namestring

Name of the rule

▶ rule_uuidstring

The unique identifier of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestring

A required value from the LogForwardType Enum.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: `Africa/Abidjan`, `Africa/Accra`, `Africa/Addis_Ababa`, `Africa/Algiers`, `Africa/Asmara`, `Africa/Asmera`, `Africa/Bamako`, `Africa/Bangui`, `Africa/Banjul`, `Africa/Bissau`, `Africa/Blantyre`, `Africa/Brazzaville`, `Africa/Bujumbura`, `Africa/Cairo`, `Africa/Casablanca`, `Africa/Ceuta`, `Africa/Conakry`, `Africa/Dakar`, `Africa/Dar_es_Salaam`, `Africa/Djibouti`, `Africa/Douala`, `Africa/El_Aaiun`, `Africa/Freetown`, `Africa/Gaborone`, `Africa/Harare`, `Africa/Johannesburg`, `Africa/Juba`, `Africa/Kampala`, `Africa/Khartoum`, `Africa/Kigali`, `Africa/Kinshasa`, `Africa/Lagos`, `Africa/Libreville`, `Africa/Lome`, `Africa/Luanda`, `Africa/Lubumbashi`, `Africa/Lusaka`, `Africa/Malabo`, `Africa/Maputo`, `Africa/Maseru`, `Africa/Mbabane`, `Africa/Mogadishu`, `Africa/Monrovia`, `Africa/Nairobi`, `Africa/Ndjamena`, `Africa/Niamey`, `Africa/Nouakchott`, `Africa/Ouagadougou`, `Africa/Porto-Novo`, `Africa/Sao_Tome`, `Africa/Timbuktu`, `Africa/Tripoli`, `Africa/Tunis`, `Africa/Windhoek`, `America/Adak`, `America/Anchorage`, `America/Anguilla`, `America/Antigua`, `America/Araguaina`, `America/Argentina/Buenos_Aires`, `America/Argentina/Catamarca`, `America/Argentina/ComodRivadavia`, `America/Argentina/Cordoba`, `America/Argentina/Jujuy`, `America/Argentina/La_Rioja`, `America/Argentina/Mendoza`, `America/Argentina/Rio_Gallegos`, `America/Argentina/Salta`, `America/Argentina/San_Juan`, `America/Argentina/San_Luis`, `America/Argentina/Tucuman`, `America/Argentina/Ushuaia`, `America/Aruba`, `America/Asuncion`, `America/Atikokan`, `America/Atka`, `America/Bahia`, `America/Bahia_Banderas`, `America/Barbados`, `America/Belem`, `America/Belize`, `America/Blanc-Sablon`, `America/Boa_Vista`, `America/Bogota`, `America/Boise`, `America/Buenos_Aires`, `America/Cambridge_Bay`, `America/Campo_Grande`, `America/Cancun`, `America/Caracas`, `America/Catamarca`, `America/Cayenne`, `America/Cayman`, `America/Chicago`, `America/Chihuahua`, `America/Ciudad_Juarez`, `America/Coral_Harbour`, `America/Cordoba`, `America/Costa_Rica`, `America/Coyhaique`, `America/Creston`, `America/Cuiaba`, `America/Curacao`, `America/Danmarkshavn`, `America/Dawson`, `America/Dawson_Creek`, `America/Denver`, `America/Detroit`, `America/Dominica`, `America/Edmonton`, `America/Eirunepe`, `America/El_Salvador`, `America/Ensenada`, `America/Fort_Nelson`, `America/Fort_Wayne`, `America/Fortaleza`, `America/Glace_Bay`, `America/Godthab`, `America/Goose_Bay`, `America/Grand_Turk`, `America/Grenada`, `America/Guadeloupe`, `America/Guatemala`, `America/Guayaquil`, `America/Guyana`, `America/Halifax`, `America/Havana`, `America/Hermosillo`, `America/Indiana/Indianapolis`, `America/Indiana/Knox`, `America/Indiana/Marengo`, `America/Indiana/Petersburg`, `America/Indiana/Tell_City`, `America/Indiana/Vevay`, `America/Indiana/Vincennes`, `America/Indiana/Winamac`, `America/Indianapolis`, `America/Inuvik`, `America/Iqaluit`, `America/Jamaica`, `America/Jujuy`, `America/Juneau`, `America/Kentucky/Louisville`, `America/Kentucky/Monticello`, `America/Knox_IN`, `America/Kralendijk`, `America/La_Paz`, `America/Lima`, `America/Los_Angeles`, `America/Louisville`, `America/Lower_Princes`, `America/Maceio`, `America/Managua`, `America/Manaus`, `America/Marigot`, `America/Martinique`, `America/Matamoros`, `America/Mazatlan`, `America/Mendoza`, `America/Menominee`, `America/Merida`, `America/Metlakatla`, `America/Mexico_City`, `America/Miquelon`, `America/Moncton`, `America/Monterrey`, `America/Montevideo`, `America/Montreal`, `America/Montserrat`, `America/Nassau`, `America/New_York`, `America/Nipigon`, `America/Nome`, `America/Noronha`, `America/North_Dakota/Beulah`, `America/North_Dakota/Center`, `America/North_Dakota/New_Salem`, `America/Nuuk`, `America/Ojinaga`, `America/Panama`, `America/Pangnirtung`, `America/Paramaribo`, `America/Phoenix`, `America/Port-au-Prince`, `America/Port_of_Spain`, `America/Porto_Acre`, `America/Porto_Velho`, `America/Puerto_Rico`, `America/Punta_Arenas`, `America/Rainy_River`, `America/Rankin_Inlet`, `America/Recife`, `America/Regina`, `America/Resolute`, `America/Rio_Branco`, `America/Rosario`, `America/Santa_Isabel`, `America/Santarem`, `America/Santiago`,

America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Shiprock, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Thunder_Bay, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Virgin, America/Whitehorse, America/Winnipeg, America/Yakutat, America/Yellowknife, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/South_Pole, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Ashkhabad, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Calcutta, Asia/Chita, Asia/Choibalsan, Asia/Chongqing, Asia/Chungking, Asia/Colombo, Asia/Dacca, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Harbin, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Istanbul, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kashgar, Asia/Kathmandu, Asia/Katmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macao, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Rangoon, Asia/Riyadh, Asia/Saigon, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Tel_Aviv, Asia/Thimbu, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ujung_Pandang, Asia/Ulaanbaatar, Asia/Ulan_Bator, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faeroe, Atlantic/Faroe, Atlantic/Jan_Mayen, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/ACT, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Canberra, Australia/Currie, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/LHI, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/NSW, Australia/North, Australia/Perth, Australia/Queensland, Australia/South, Australia/Sydney, Australia/Tasmania, Australia/Victoria, Australia/West, Australia/Yancowinna, Brazil/Acre, Brazil/DeNoronha, Brazil/East, Brazil/West, CET, CST6CDT, Canada/Atlantic, Canada/Central, Canada/Eastern, Canada/Mountain, Canada/Newfoundland, Canada/Pacific, Canada/Saskatchewan, Canada/Yukon, Chile/Continental, Chile/EasterIsland, Cuba, EET, EST, EST5EDT, Egypt, Eire, Etc/GMT, Etc/GMT+0, Etc/GMT+1, Etc/GMT+10, Etc/GMT+11, Etc/GMT+12, Etc/GMT+2, Etc/GMT+3, Etc/GMT+4, Etc/GMT+5, Etc/GMT+6, Etc/GMT+7, Etc/GMT+8, Etc/GMT+9, Etc/GMT-0, Etc/GMT-1, Etc/GMT-10, Etc/GMT-11, Etc/GMT-12, Etc/GMT-13, Etc/GMT-14, Etc/GMT-2, Etc/GMT-3, Etc/GMT-4, Etc/GMT-5, Etc/GMT-6, Etc/GMT-7, Etc/GMT-8, Etc/GMT-9, Etc/GMT0, Etc/Greenwich, Etc/UCT, Etc/UTC, Etc/Universal, Etc/Zulu, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belfast, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich, HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for mail integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI. Note: the `legacy_alert` format is not permissible for Slack.

▶ created_bystring

This string indicates the user or api-key responsible for creating the notification rule.

▶ created_atintegerint64

This value represents the timestamp when the notification rule was created.

▶ modified_atintegerint64

This value represents the timestamp when the notification rule was last modified.

▶ enabledboolean

A flag indicating whether the notification rule is currently active and enabled.

RESPONSE


```
{ "data": { "rule_uuid": "3053ad1f-0efc-305d-90dd-a305ab4153a4", "name": "Test Rule 1", "description": "This is a
description placeholder", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": false } ] } }, "applications": [ "1111-TeSt-1223-09ID-415305650" ], "forward_source": {},
"forward_type": "alert", "time_zone": "Pacific/Nauru", "slack_format": "issue", "syslog_format": "issue",
"mail_format": "issue", "created_by": "testuser@paloaltonetworks.com", "created_at": 1764873308164, "modified_at":
1764873308164, "enabled": true } }
```


Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject

RESPONSE


```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Alert
notification with rule uuid 3056ad1f-0efc-305d-90dd-a305ab4153a4 was not found.", "err_code": 400 } } }
```


Body
application/json

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger

RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.3.2.4 | Delete an existing Alert Notification Rule

delete /platform/notifications/v1/rule/{rule_uuid}

Allows the user to delete an existing Alert Notification Rule by its unique identifier.

Path parameters
▼ rule_uuid String required

Full rule uuid of the Alert Notification Rule

Example: `3053ad1f-0efc-305d-90dd-a305ab4153a4`

CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/rule/{rule_uuid}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("DELETE",
"%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4") res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Delete.new(url) response = http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE",
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-
305d-90dd-a305ab4153a4") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE" let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4", CURLOPT_RETURNTRANSFER
=> true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION =>
CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "DELETE", ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-a305ab4153a4"); CURLcode
ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/3053ad1f-0efc-305d-90dd-
a305ab4153a4"); var request = new RestRequest(Method.DELETE); IRestResponse response = client.Execute(request);
```

Responses

Body
application/json
RESPONSE

```
null
```

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Alert
notification rule id 305 was not found.", "err_code": 400 } } }
```

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.3.2.5 | Edit an existing Alert Notification Rule

put /platform/notifications/v1/rule/{rule_uuid}

This endpoint allows the user to edit an alert notification rule and specify its new attributes. To see the possible `forward_type` values, please check the relevant enum schema named `LogForwardType`. The `forward_source` attribute is where a user would define email, Slack, and Syslog configurations; the required formats are specified in the `RuleEditRequest`schema. The `applications` attribute is a list of external applications application IDs (webhook, AWS S3, AWS SQS, and Splunk). The `mail_format`, `syslog_format`, and `slack_format` attributes represent whether the user would like the notifications for these integrations to be issues or alerts formats; more information is provided in the `RuleEditRequest` schema. Please note that you can only edit a rule that is in an `Enabled` state.

Path parameters

▼ rule_uuid String required

Full rule uuid of the Alert Notification Rule

Example: `ruleUuid_example`

CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/rule/{rule_uuid}'
-d '{ "request_data" : { "name" : "Test Rule 01", "description" : "a description for the test rule", "forward_type" :
"alert", "filter" : { "filter" : { "AND" : [ { "SEARCH_FIELD" : "is_whitelisted", "SEARCH_TYPE" : "EQ", "SEARCH_VALUE"
: false } ] } }, "forward_source" : { "email" : { "distribution_list" : [ "testuser@paloaltonetworks.com" ],
"aggregation" : 1000 }, "syslog" : { "id" : 1 }, "slack" : { "channels" : [ "slack-test-channel1" ] } },
"applications" : [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "time_zone" : "Pacific/Nauru", "mail_format" : "issue",
"syslog_format" : "standard_alert", "slack_format" : "issue" } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"name\":\"Test Rule
01\",\"description\":\"a description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
headers = { 'content-type': "application/json" } conn.request("PUT",
"%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["content-
type"] = 'application/json' request.body = "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a
description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "name": "Test Rule 01", "description": "a description for the test
rule", "forward_type": "alert", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE":
"EQ", "SEARCH_VALUE": false } ] } }, "forward_source": { "email": { "distribution_list": [
"testuser@paloaltonetworks.com" ], "aggregation": 1000 }, "syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-
channel1" ] } }, "applications": [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "time_zone": "Pacific/Nauru",
"mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("PUT",
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D")
.header("content-type", "application/json") .body("{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a
description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
.asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "name": "Test
Rule 01", "description": "a description for the test rule", "forward_type": "alert", "filter": ["filter": ["AND": [ [
"SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false ] ]]], "forward_source": [ "email": [
"distribution_list": ["testuser@paloaltonetworks.com"], "aggregation": 1000 ], "syslog": ["id": 1], "slack":
["channels": ["slack-test-channel1"]] ], "applications": ["63e3ad1f-0efc-401d-90dd-a305ab6053a4"], "time_zone":
"Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue" ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "{\"request_data\":{\"name\":\"Test Rule
01\",\"description\":\"a description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a
description for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/rule/%7Brule_uuid%7D"); var request =
new RestRequest(Method.PUT); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"name\":\"Test Rule 01\",\"description\":\"a description
for the test rule\",\"forward_type\":\"alert\",\"filter\":{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"is_whitelisted\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":false}]}},\"forward_source\":{\"email\":
{\"distribution_list\":[\"testuser@paloaltonetworks.com\"],\"aggregation\":1000},\"syslog\":{\"id\":1},\"slack\":
{\"channels\":[\"slack-test-channel1\"]}},\"applications\":[\"63e3ad1f-0efc-401d-90dd-
a305ab6053a4\"],\"time_zone\":\"Pacific/Nauru\",\"mail_format\":\"issue\",\"syslog_format\":\"standard_alert\",\"slack_format\"
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json

Enumerates the various attributes required for editing an existing notification rule

▼ request_dataobject
▶ namestringrequired

Name of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestringrequired

A required value from the LogForwardType Enum. It must be the same as its current forward_type as this field is not mutable during edits.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: `Africa/Abidjan`, `Africa/Accra`, `Africa/Addis_Ababa`, `Africa/Algiers`, `Africa/Asmara`, `Africa/Asmera`, `Africa/Bamako`, `Africa/Bangui`, `Africa/Banjul`, `Africa/Bissau`, `Africa/Blantyre`, `Africa/Brazzaville`, `Africa/Bujumbura`, `Africa/Cairo`, `Africa/Casablanca`, `Africa/Ceuta`, `Africa/Conakry`, `Africa/Dakar`, `Africa/Dar_es_Salaam`, `Africa/Djibouti`, `Africa/Douala`, `Africa/El_Aaiun`, `Africa/Freetown`, `Africa/Gaborone`, `Africa/Harare`, `Africa/Johannesburg`, `Africa/Juba`, `Africa/Kampala`, `Africa/Khartoum`, `Africa/Kigali`, `Africa/Kinshasa`, `Africa/Lagos`, `Africa/Libreville`, `Africa/Lome`, `Africa/Luanda`, `Africa/Lubumbashi`, `Africa/Lusaka`, `Africa/Malabo`, `Africa/Maputo`, `Africa/Maseru`, `Africa/Mbabane`, `Africa/Mogadishu`, `Africa/Monrovia`, `Africa/Nairobi`, `Africa/Ndjamena`, `Africa/Niamey`, `Africa/Nouakchott`, `Africa/Ouagadougou`, `Africa/Porto-Novo`,

Africa/Sao_Tome, Africa/Timbuktu, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/ComodRivadavia, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Atka, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Buenos_Aires, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Catamarca, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Coral_Harbour, America/Cordoba, America/Costa_Rica, America/Coyhaique, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Ensenada, America/Fort_Nelson, America/Fort_Wayne, America/Fortaleza, America/Glace_Bay, America/Godthab, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Indianapolis, America/Inuvik, America/Iqaluit, America/Jamaica, America/Jujuy, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Knox_IN, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Louisville, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Mendoza, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montreal, America/Montserrat, America/Nassau, America/New_York, America/Nipigon, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Pangnirtung, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Acre, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rainy_River, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Rosario, America/Santa_Isabel, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Shiprock, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Thunder_Bay, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Virgin, America/Whitehorse, America/Winnipeg, America/Yakutat, America/Yellowknife, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/South_Pole, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Ashkhabad, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Calcutta, Asia/Chita, Asia/Choibalsan, Asia/Chongqing, Asia/Chungking, Asia/Colombo, Asia/Dacca, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Harbin, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Istanbul, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kashgar, Asia/Kathmandu, Asia/Katmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macao, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Rangoon, Asia/Riyadh, Asia/Saigon, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Tel_Aviv, Asia/Thimbu, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ujung_Pandang, Asia/Ulaanbaatar, Asia/Ulan_Bator, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faeroe, Atlantic/Faroe, Atlantic/Jan_Mayen, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/ACT, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Canberra, Australia/Currie, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/LHI, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/NSW, Australia/North, Australia/Perth, Australia/Queensland, Australia/South, Australia/Sydney, Australia/Tasmania, Australia/Victoria, Australia/West, Australia/Yancowinna, Brazil/Acre, Brazil/DeNoronha, Brazil/East, Brazil/West, CET, CST6CDT, Canada/Atlantic, Canada/Central, Canada/Eastern, Canada/Mountain, Canada/Newfoundland, Canada/Pacific, Canada/Saskatchewan, Canada/Yukon, Chile/Continental, Chile/EasterIsland, Cuba, EET, EST, EST5EDT, Egypt, Eire, Etc/GMT, Etc/GMT+0, Etc/GMT+1, Etc/GMT+10, Etc/GMT+11, Etc/GMT+12, Etc/GMT+2, Etc/GMT+3, Etc/GMT+4, Etc/GMT+5, Etc/GMT+6, Etc/GMT+7, Etc/GMT+8, Etc/GMT+9, Etc/GMT-0, Etc/GMT-1, Etc/GMT-10, Etc/GMT-11, Etc/GMT-12, Etc/GMT-13, Etc/GMT-14, Etc/GMT-2, Etc/GMT-3, Etc/GMT-4, Etc/GMT-5, Etc/GMT-6, Etc/GMT-7, Etc/GMT-8, Etc/GMT-9, Etc/GMT0, Etc/Greenwich, Etc/UCT, Etc/UTC, Etc/Universal, Etc/Zulu, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belfast, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich, HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen,



Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.Not: the `legacy_alert` format is not permissible for Slack.

REQUEST


```
{ "request_data": { "name": "Test Rule 01", "description": "a description for the test rule", "forward_type": "alert",
"filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false } ] }
}, "forward_source": { "email": { "distribution_list": [ "testuser@paloaltonetworks.com" ], "aggregation": 1000 },
"syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-channel1" ] } }, "applications": [ "63e3ad1f-0efc-401d-
90dd-a305ab6053a4" ], "time_zone": "Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert",
"slack_format": "issue" } }
```


Responses

Body

application/json

▼ dataobject

▶ namestring

Name of the rule

▶ rule_uuidstring

The unique identifier of the rule

▶ descriptionstring

Optional description of the rule

▶ forward_typestring

A required value from the LogForwardType Enum.

▶ filterobject

An object containing the various attributes of the filter that will be applied to the given alert notification rule. Please refer to the `BaseFilterExample` and `ComplexFilterExample` schemas to gather further information on this field. A user can also derive a filter by utilizing the JSON export functionality when defining a rule via the UI.

▶ forward_sourceobject

This JSON object provides the user with the ability to specify configurations for Email, Slack, and Syslog outputs.

▶ applicationsarray[string]

List of valid application IDs (AWS SQS, AWS S3, Splunk, and webhook integrations). These can be found by utilizing the List External Applications API.

▶ time_zonestring

This string indicates which time zone the rule will be associated with. If the field is not passed in, the default value will be UTC. The following are valid time zone options: Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Asmera, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala,

Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Timbuktu, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/ComodRivadavia, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Atka, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Buenos_Aires, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Catamarca, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Coral_Harbour, America/Cordoba, America/Costa_Rica, America/Coyhaique, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Ensenada, America/Fort_Nelson, America/Fort_Wayne, America/Fortaleza, America/Glace_Bay, America/Godthab, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Indianapolis, America/Inuvik, America/Iqaluit, America/Jamaica, America/Jujuy, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Knox_IN, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Louisville, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Mendoza, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montreal, America/Montserrat, America/Nassau, America/New_York, America/Nipigon, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Pangnirtung, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Acre, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rainy_River, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Rosario, America/Santa_Isabel, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Shiprock, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Thunder_Bay, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Virgin, America/Whitehorse, America/Winnipeg, America/Yakutat, America/Yellowknife, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/South_Pole, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Ashkhabad, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Calcutta, Asia/Chita, Asia/Choibalsan, Asia/Chongqing, Asia/Chungking, Asia/Colombo, Asia/Dacca, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Harbin, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Istanbul, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kashgar, Asia/Kathmandu, Asia/Katmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macao, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Rangoon, Asia/Riyadh, Asia/Saigon, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Tel_Aviv, Asia/Thimbu, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ujung_Pandang, Asia/Ulaanbaatar, Asia/Ulan_Bator, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faeroe, Atlantic/Faroe, Atlantic/Jan_Mayen, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/ACT, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Canberra, Australia/Currie, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/LHI, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/NSW, Australia/North, Australia/Perth, Australia/Queensland, Australia/South, Australia/Sydney, Australia/Tasmania, Australia/Victoria, Australia/West, Australia/Yancowinna, Brazil/Acre, Brazil/DeNoronha, Brazil/East, Brazil/West, CET, CST6CDT, Canada/Atlantic, Canada/Central, Canada/Eastern, Canada/Mountain, Canada/Newfoundland, Canada/Pacific, Canada/Saskatchewan, Canada/Yukon, Chile/Continental, Chile/EasterIsland, Cuba, EET, EST, EST5EDT, Egypt, Eire, Etc/GMT, Etc/GMT+0, Etc/GMT+1, Etc/GMT+10, Etc/GMT+11, Etc/GMT+12, Etc/GMT+2, Etc/GMT+3, Etc/GMT+4, Etc/GMT+5, Etc/GMT+6, Etc/GMT+7, Etc/GMT+8, Etc/GMT+9, Etc/GMT-0, Etc/GMT-1, Etc/GMT-10, Etc/GMT-11, Etc/GMT-12, Etc/GMT-13, Etc/GMT-14, Etc/GMT-2, Etc/GMT-3, Etc/GMT-4, Etc/GMT-5, Etc/GMT-6, Etc/GMT-7, Etc/GMT-8, Etc/GMT-9, Etc/GMT0, Etc/Greenwich, Etc/UCT, Etc/UTC, Etc/Universal, Etc/Zulu, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belfast, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kiev, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Nicosia, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo,



Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Tiraspol, Europe/Ulyanovsk, Europe/Uzhgorod, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zaporozhye, Europe/Zurich, GB, GB-Eire, GMT, GMT+0, GMT-0, GMT0, Greenwich, HST, Hongkong, Iceland, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Iran, Israel, Jamaica, Japan, Kwajalein, Libya, MET, MST, MST7MDT, Mexico/BajaNorte, Mexico/BajaSur, Mexico/General, NZ, NZ-CHAT, Navajo, PRC, PST8PDT, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Enderbury, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Johnston, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Ponape, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Samoa, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Truk, Pacific/Wake, Pacific/Wallis, Pacific/Yap, Poland, Portugal, ROC, ROK, Singapore, Turkey, UCT, US/Alaska, US/Aleutian, US/Arizona, US/Central, US/East-Indiana, US/Eastern, US/Hawaii, US/Indiana-Starke, US/Michigan, US/Mountain, US/Pacific, US/Samoa, UTC, Universal, W-SU, WET, Zulu

▶ mail_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for mail integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ syslog_formatstring

This string indicates whether the rule will use the `issue`, `standard_alert`, or `legacy_alert` format for Syslog integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI.

▶ slack_formatstring

This string indicates whether the rule will use the `issue` or `standard_alert` format for Slack integration. This string is strictly to be used with the `alert` log forwarding type. It is not applicable for other log forwarding types. The value fields are analogous to those visible on the UI. Note: the `legacy_alert` format is not permissible for Slack.

▶ created_bystring

This string indicates the user or api-key responsible for creating the notification rule.

▶ created_atintegerint64

This value represents the timestamp when the notification rule was created.

▶ modified_atintegerint64

This value represents the timestamp when the notification rule was last modified.

▶ enabledboolean

A flag indicating whether the notification rule is currently active and enabled.

RESPONSE


```
{ "data": { "rule_uuid": "3053ad1f-0efc-305d-90dd-a305ab4153a4", "name": "Test Rule 01", "description": "a description for the test rule", "filter": { "filter": { "AND": [ { "SEARCH_FIELD": "is_whitelisted", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": false } ] } }, "applications": [ "63e3ad1f-0efc-401d-90dd-a305ab6053a4" ], "forward_source": { "email": { "distribution_list": [ "testuser@paloaltonetworks.com" ], "aggregation": 1000, "legacy_mail_format": false }, "syslog": { "id": 1 }, "slack": { "channels": [ "slack-test-channel1" ] } }, "forward_type": "alert", "time_zone": "Pacific/Nauru", "mail_format": "issue", "syslog_format": "standard_alert", "slack_format": "issue", "created_by": "testuser@paloaltonetworks.com", "created_at": 1764958056697, "modified_at": 1764958056697, "enabled": true } }
```


Body

application/json

▼ dataobject

▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject

RESPONSE


```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "The mail format field provided is invalid.", "err_code": 400 } } }
```


Body

application/json

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body

application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }
```

2.3.2.6 | Edit the status of an existing Alert Notification Rule

patch /platform/notifications/v1/update-rule-status/{rule_uuid}

This endpoint allows a user to modify a rule's status without requiring a full update. A user can either enable or disable an Alert Notification Rule.

Path parameters
▼ rule_uuid String required

Full rule uuid of the Alert Notification Rule

Example: `3053ad1f-0efc-305d-90dd-a305ab4153a4`
CLIENT REQUEST Bash+curl

```
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/notifications/v1/update-rule-status/{rule_uuid}'
-d '{ "request_data" : { "status" : "enable" } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"status\":\"enable\"}}"
headers = { 'content-type': "application/json" } conn.request("PATCH", "%7Bfqdn%7D/platform/notifications/v1/update-
rule-status/3053ad1f-0efc-305d-90dd-a305ab4153a4", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-status/3053ad1f-0efc-305d-90dd-a305ab4153a4") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Patch.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"status\":\"enable\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "status": "enable" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("PATCH", "https://api-/%7Bfqdn%7D/platform/notifications/v1/update-
rule-status/3053ad1f-0efc-305d-90dd-a305ab4153a4"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-
status/3053ad1f-0efc-305d-90dd-a305ab4153a4") .header("content-type", "application/json") .body("{\"request_data\":
{\"status\":\"enable\"}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": ["status":
"enable"]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-
status/3053ad1f-0efc-305d-90dd-a305ab4153a4")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "PATCH" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-status/3053ad1f-0efc-305d-90dd-a305ab4153a4",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "PATCH", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"status\":\"enable\"}}", CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]); $response
= curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else {
echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-status/3053ad1f-0efc-305d-90dd-
a305ab4153a4"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"status\":\"enable\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/notifications/v1/update-rule-status/3053ad1f-0efc-305d-
90dd-a305ab4153a4"); var request = new RestRequest(Method.PATCH); request.AddHeader("content-type",
```

```
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"status\":\"enable\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json

Enumerates the various para meters required for updating the status of a rule

▼ request_dataobject
▶ statusstringrequired

Value of updated status {enable|disable}

REQUEST

```
{ "request_data": { "status": "enable" } }
```

Responses

Body
application/json
RESPONSE

```
null
```

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Alert
notification rule id 305 was not found.", "err_code": 400 } } }
```

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.4 | ASPM, CICD and Application Security APIs

2.4.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Enhance your security operations and automation capabilities using the ASPM, CICD and Application Security APIs to optimize the management of applications, repositories, data sources, rules, policies, and scans.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: Cortex Cloud 2.1

2.4.1.1 | Servers

https://api-yourfqdn

2.4.1.2 | Authentication methods

▼ XDRAuth
Api Key "x-xdr-auth-id"

API Key ID for authentication

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.
▼ XDRAuthToken
Api Key "Authorization"

API Key for authentication

Authorized requests to the API should use: **Authorization** inside **a header** with the access token.

2.4.1.2.1 | Default authentication

Please note that this documentation assumes a minimum level of authentication is required, unless explicitly stated otherwise.
It is essential to ensure that any of the following authentication mechanisms are in place to access the API endpoints:

- XDRAuth=[], XDRAuthToken

2.4.2 | Billing

APIs for managing billing contributors

2.4.2.1 | Get Billing Contributors

get /public_api/appsec/v1/billing/contributors

Returns a list of unique repository users who are considered **active contributors** for billing calculations.

An active contributor is defined as a unique (by email), non-bot human user who has committed code within the last 90 days to a billable, non-archived repository that has at least one security scanner enabled.

> **Note:** You must have the **Instance Administrator** permissions to run this endpoint.
>
> **Required license**:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/billing/contributors'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("GET", "/public_api/appsec/v1/billing/contributors",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/billing/contributors") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'your_api_key_here' request["x-xdr-auth-id"] = '1' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/billing/contributors"); xhr.setRequestHeader("Authorization", "your_api_key_here");
xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/billing/contributors")
.header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/billing/contributors")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
```

```
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/appsec/v1/billing/contributors", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "x-xdr-auth-id: 1" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/billing/contributors"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/billing/contributors"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-id", "1"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ lastCommitDatestring

The date and time of the user's most recent commit. Used to determine contributor activity. **Note:** Only users who committed within the last 90 days are considered active contributors for billing.

▶ namestringrequired

The display name of the repository user.

▶ userNamestring

The username of the repository user on the VCS platform.

▶ emailstringrequired

The email address associated with the user. This value is used to uniquely identify contributors across repositories. Emails associated with bots or automated accounts (for example, action@github.com or *@users.noreply.github.com) are excluded.

▶ repositoryIdstringrequired

The unique identifier of the repository associated with the user. The repository must be billable (not archived and with at least one security scanner enabled).

▶ creationDatestringrequired

The date and time when the user record was created in the system.

▶ rolestring (Enum)

The permission level of the user within the repository.

▶ hasMfaboolean

Indicates whether the user has multi-factor authentication (MFA) enabled on their VCS account.

▶ teamsarray[string]

The names of the teams in the VCS organization that the user belongs to.

▶ isGuestboolean

Indicates whether the user is a guest (external collaborator) in the repository.

▶ isContributorboolean

Indicates whether the user is an active contributor.

▶ isAdminboolean

Indicates whether the user has admin permissions for the repository.

▶ emailOriginstring (Enum)

The source from which the user's email address was obtained.

▶ uniqueVcsIdstring

A unique identifier assigned to the user by the VCS platform. Used to correlate the user across repositories and systems.
]
RESPONSE
Example 1
[{ "name": "Jane Doe", "userName": "janedoe", "email": "janedoe@example.com", "repositoryId": "a1b2c3d4e5f6a7b8c9d0e1f2a", "creationDate": "2025-06-01T08:00:00.000Z", "lastCommitDate": "2025-02-15T10:30:00.000Z", "role": "WRITE", "hasMfa": true, "teams": ["backend-team", "security-team"], "isGuest": false, "isContributor": true, "isAdmin": false, "emailOrigin": "GIT", "uniqueVcsId": "vcs-user-67890" }, { "name": "John Smith", "userName": "johnsmith", "email": "johnsmith@example.com", "repositoryId": "repo-xyz-67890", "creationDate": "2025-03-15T12:00:00.000Z", "lastCommitDate": "2025-01-20T14:45:00.000Z", "role": "DEVELOPER", "hasMfa": false, "teams": ["frontend-team"], "isGuest": false, "isContributor": true, "isAdmin": false, "emailOrigin": "API", "uniqueVcsId": "vcs-user-11223" }]

Bad Request - The request was malformed or contains invalid parameters.

Body
application/json
▼ replyobject
▶ err_codeinteger

The HTTP status code of the error.

▶ err_msgstring

A short description of the error type.

▶ err_extrastring

A detailed message explaining the cause of the error.

RESPONSE
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }

Unauthorized - The request is unauthenticated. Pass the correct auth credentials.

Body
application/json
▼ replyobject
▶ err_codeinteger

The HTTP status code of the error.

▶ err_msgstring

A short description of the error type.

▶ err_extrastring

A detailed message explaining the cause of the error.

RESPONSE
Example 1
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Forbidden - Access to the resource is prohibited. Try with different auth credentials.

Body
application/json
▼ replyobject
▶ err_codeinteger

The HTTP status code of the error.

▶ err_msgstring

A short description of the error type.

▶ err_extrastring

A detailed message explaining the cause of the error.

RESPONSE
Example 1
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }

Not Found - The requested resource could not be found.

Body
application/json
▼ replyobject
▶ err_codeinteger

The HTTP status code of the error.

▶ err_msgstring

A short description of the error type.

▶ err_extrastring

A detailed message explaining the cause of the error.

RESPONSE
```
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

2.4.3 | Applications

APIs for managing applications

2.4.3.1 | Get an application configuration

get /public_api/appsec/v1/application/configuration

Retrieves the application configuration settings.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example:
```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/configuration'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/application/configuration", headers=headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/configuration") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/application/configuration"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/application/configuration")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/configuration")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/configuration", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/configuration"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/configuration"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json

▼ keepApplicationRefreshboolean

Indicates if the system is configured to automatically and periodically refresh the application's metadata and asset data.

▼ areSbomIssuesConsideredNewboolean

Indicates if findings from Software Bill of Materials (SBOM) scans are treated as brand-new issues for tracking and compliance purposes.

▼ slaobject

Contains the Service Level Agreement (SLA) configurations, defining the resolution timeframes for various severity levels.

▶ CRITICALobject

Defines the SLA target days for issues classified as CRITICAL severity.

▶ HIGHobject

Defines the SLA target days for issues classified as HIGH severity.

▶ MEDIUMobject

Defines the SLA target days for issues classified as MEDIUM severity.

▶ LOWobject

Defines the SLA target days for issues classified as LOW severity.

▶ approachingobject

Defines the early warning threshold that triggers notifications before an SLA is officially breached.

RESPONSE

Example 1

```
{ "keepApplicationRefresh": true, "areSbomIssuesConsideredNew": true, "sla": { "CRITICAL": { "targetDays": 7 },
"HIGH": { "targetDays": 14 }, "MEDIUM": { "targetDays": 30 }, "LOW": { "targetDays": 90 }, "approaching": {
"targetDays": 5 } } }
```

2.4.3.2 | Create an application

post /public_api/appsec/v1/application

Creates a new application asset based on the provided details, such as name, criticality, and asset selection.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application'
-d '{ "productManager" : [ "productManager", "productManager" ], "assetSelection" : { "filter" : { "values" : [
"values", "values" ] }, "assetIds" : [ "assetIds", "assetIds" ] }, "businessUnit" : "businessUnit", "name" : "name",
"description" : "description", "devOwner" : [ "devOwner", "devOwner" ], "devOpsOwner" : [ "devOpsOwner", "devOpsOwner"
], "businessOwner" : [ "businessOwner", "businessOwner" ] }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/application", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/application")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "string", "businessCriticality": "Critical", "businessUnit": "string",
"creationType": "Auto", "description": "string", "compliance": "PCI-DSS", "businessOwner": [ "string" ], "devOwner": [
"string" ], "devOpsOwner": [ "string" ], "productManager": [ "string" ], "assetSelection": { "selectionType":
"filter", "section": "code", "filter": { "values": [ "string" ], "provider": "CIRCLE_CI", "filterType": "REPOSITORY"
}, "assetIds": [ "string" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/appsec/v1/application");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/application")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
```

```
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "name": "string",
"businessCriticality": "Critical", "businessUnit": "string", "creationType": "Auto", "description": "string",
"compliance": "PCI-DSS", "businessOwner": ["string"], "devOwner": ["string"], "devOpsOwner": ["string"],
"productManager": ["string"], "assetSelection": [ "selectionType": "filter", "section": "code", "filter": [ "values":
["string"], "provider": "CIRCLE_CI", "filterType": "REPOSITORY" ], "assetIds": ["string"] ] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/application")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"name\":\"string\",\"businessCriticality\":\"Critical\",\"businessUnit\":\"string\",\"creationType\":\"Auto\",\"description\"
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"],\"assetSelection\":{\"selectionType\":\"filter\",\"section\":\"code\",\"filter\":{\"values\":
[\"string\"],\"provider\":\"CIRCLE_CI\",\"filterType\":\"REPOSITORY\"},\"assetIds\":[\"string\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```


Body parameters

required

application/json

▼ namestringrequired

A unique name for the application asset.

▼ businessCriticalitystring (Enum)required

The operational importance of the asset.

Allowed values:"Critical""High""Medium""Low"

▼ businessUnitstring

Business unit responsible for the asset.

▼ creationTypestring (Enum)required

Defines how the application asset is created.
Allowed values:"Auto""Manual"
▼ descriptionstring

A brief description of the asset's purpose.

▼ compliancestring (Enum)

The compliance status or requirement category for an asset.

Allowed values:"PCI-DSS""ISO 27001""SOX""NIST""GDPR""CCPA""HIPAA""FedRAMP"
▼ businessOwnerarray[string]

A list of stakeholders responsible for the asset from the business side.

▼ devOwnerarray[string]

A list of primary developers or engineering leads responsible for the code.

▼ devOpsOwnerarray[string]

A list of SRE or DevOps engineers managing the infrastructure.

▼ productManagerarray[string]

A list of product managers responsible for overseeing the application asset.

▼ assetSelectionobject

Define the logic for how specific technical assets must be linked to this application.

▶ selectionTypestring (Enum)required

Method to select application assets.

▶ sectionstring (Enum)required

Identifies the functional section to which the asset selection applies.

▶ filterobject

Defines filter criteria to dynamically select application assets. This field supports one of the supported application asset selection filter types.

▶ assetIdsarray[string]

A list of unique identifiers representing the assets to be included.

REQUEST
Example 1

```
{ "name": "test-app", "businessCriticality": "Low", "businessUnit": "string", "creationType": "Auto", "description":
"string", "businessOwner": [], "devOwner": [], "devOpsOwner": [], "productManager": [], "assetSelection": {
"selectionType": "filter", "section": "code", "filter": { "values": [
"928aa0b599d2df33978d958e96d146fc299ac68f02fda5cc376440f41452c2e0" ], "provider": "GITHUB", "filterType": "REPOSITORY"
}, "assetIds": [] } }
```

Responses

Ok

Body
application/json
▼ statusbooleanrequired

Displays the status of the application.

Default:`true`
▼ applicationIdstring

Displays the Asset ID of the application.

Example:`"a7dc11ea688c73dbbc759459ba661d7f7a7edaad229a3fdb50701b6548535f5b"`
RESPONSE

```
{ "status": false, "applicationId": "a7dc11ea688c73dbbc759459ba661d7f7a7edaad229a3fdb50701b6548535f5b" }
```


Not Found

Body
application/json
▼ errorCodestring

Displays the error code.
Example:`"\"errorCode\": \"_NotFoundError\""`
▼ messagestring

Displays the error message.

Example:`"\"message\": \"Some assets do not exist in the database.\""`
RESPONSE

```
{ "errorCode": "\"errorCode\": \"_NotFoundError\"", "message": "\"message\": \"Some assets do not exist in the database.\"" }
```


Conflict. Occurs when an application with the specified name already exists.

Resolution

Provide a unique name for the application.

Body
application/json
▼ errorCodestring

Displays the error code.

Example:`"\"errorCode\": \"_ConflictError\""`
▼ messagestring

Displays the error message.

Example:`"\"message\": \"Application already exists\""`
RESPONSE
Example 1

```
{ "error": "string", "message": "string" }
```


Internal Server Error. Occurs when the server encounters an unexpected condition that prevents it from fulfilling the request.

Resolution

This is a server-side issue. No action is required from you. If the problem persists, try again later.

Body
application/json
▼ errorCodestring
Default:`"InternalServerError"`
▼ messagestring
Default:`"Internal Server Error"`
RESPONSE

```
{ "errorCode": "example", "message": "example" }
```

2.4.3.3 | Get applications

get /public_api/appsec/v1/application

Retrieves a list of all application assets using pagination.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ page Double

Page number of the results to retrieve for pagination.

double
Example: `1.2`
▼ pageSize Double

Number of records returned per page.

double
Example: `1.2`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application?page=1.2&pageSize=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/application?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/application?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/application?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/application?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE", CURLOPT_RETURNTRANSFER
=> true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION =>
CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE"); var request = new RestRequest(Method.GET);
request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```
Responses

Ok

Body
application/json

▼ dataarrayrequired

[

▶ criteriaIdstring

A unique identifier of the criteria.

▶ criteriaNamestring

Name of the criteria.

▶ risknumberdouble

Calculated risk score associated with the criteria or asset.

▶ idstring

Unique identifier of the resource.

▶ strongIdstring

Globally unique, immutable identifier for the resource.

▶ namestring

Name of the application asset.

▶ descriptionstring

Description providing additional details about the asset.

▶ exposuresarray[string]

▶ coveragenumberdouble

Represents the level of coverage applied to the asset.

▶ businessCriticalitystring (Enum)

The operational importance of the asset.

▶ businessUnitstring

Business unit responsible for the asset.

▶ creationTypestring (Enum)required

Defines how the application asset is created.

▶ businessOwnerarray[string]

Business owners responsible for the asset.

▶ devOwnerarray[string]

Development owners responsible for building and maintaining the asset.

▶ devOpsOwnerarray[string]

DevOps owners responsible for deployment and operations.

▶ productManagerarray[string]

Product managers responsible for the asset.

▶ dataGovernancestring (Enum)

Type of data governance applied to the asset.

▶ compliancestring (Enum)

The compliance status or requirement category for an asset.

▶ environmentsstring

Environment in which the asset is deployed (for example, development, staging, or production).

▶ assetsCountnumberdouble

Total number of assets included in the response.

▶ configobject

Configuration settings associated with the application.
▶ updatedAtstringdate-time

Date and time when the configuration was last updated.

▶ deletedAtstringdate-time

Date and time when the configuration was deleted.

▶ enrichStatusstring (Enum)

Indicates whether asset enrichment is currently in progress.

▶ unifyAcrossProvidersboolean

If multiple applications share the same name at the chosen group-by level (org, project, or repository), they are merged across providers to form a single unified application.

▶ unifyWithinProviderboolean

Repositories with the same name at the selected group-by level (org, project, or repository) are consolidated into a single application within the selected provider.

]
▼ hasNextbooleanrequired

Indicates whether additional results are available beyond the current page.
RESPONSE

```
{ "data": [ { "criteriaId": "example", "criteriaName": "example", "risk": 0.1, "id": "example", "strongId": "example",
"name": "example", "description": "example", "exposures": [ "DeployedToProduction" ], "coverage": 0.1,
"businessCriticality": "Critical", "businessUnit": "example", "creationType": "Auto", "businessOwner": [ "example" ],
"devOwner": [ "example" ], "devOpsOwner": [ "example" ], "productManager": [ "example" ], "dataGovernance": "PII",
"compliance": "PCI-DSS", "environments": "example", "assetsCount": 0.1, "config": { "lastRefreshDate": "2020-01-
01T12:00:00Z", "assetSelection": { "selectionType": "filter", "section": "code", "filter": "example", "assetIds": [
"example" ] } }, "updatedAt": "2020-01-01T12:00:00Z", "deletedAt": "2020-01-01T12:00:00Z", "enrichStatus":
"IN_PROGRESS", "unifyAcrossProviders": false, "unifyWithinProvider": false } ], "hasNext": false }
```

2.4.3.4 | Get an application

get /public_api/appsec/v1/application/{applicationId}

Retrieves detailed information for a specific application asset using its unique ID.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Path parameters
▼ applicationId String required

Unique ID of the Application

Example: `applicationId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/{applicationId}'
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/application/%7BapplicationId%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); var request
= new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json

Exposure attributes associated with the asset.

▼ criteriaIdstring

A unique identifier of the criteria.

▼ criteriaNamestring

Name of the criteria.

▼ risknumberdouble

Calculated risk score associated with the criteria or asset.

▼ idstring

Unique identifier of the resource.

▼ strongIdstring

Globally unique, immutable identifier for the resource.
▼ namestring

Name of the application asset.

▼ descriptionstring

Description providing additional details about the asset.

▼ exposuresarray[string]
▼ coveragenumberdouble

Represents the level of coverage applied to the asset.

▼ businessCriticalitystring (Enum)

The operational importance of the asset.

Allowed values:"Critical""High""Medium""Low"
▼ businessUnitstring

Business unit responsible for the asset.

▼ creationTypestring (Enum)required

Defines how the application asset is created.

Allowed values:"Auto""Manual"
▼ businessOwnerarray[string]

Business owners responsible for the asset.

▼ devOwnerarray[string]

Development owners responsible for building and maintaining the asset.

▼ devOpsOwnerarray[string]

DevOps owners responsible for deployment and operations.

▼ productManagerarray[string]

Product managers responsible for the asset.

▼ dataGovernancestring (Enum)

Type of data governance applied to the asset.

Allowed values:"PII""PCI""Financial""PHI""Sensitive"
▼ compliancestring (Enum)

The compliance status or requirement category for an asset.

Allowed values:"PCI-DSS""ISO 27001""SOX""NIST""GDPR""CCPA""HIPAA""FedRAMP"
▼ environmentsstring

Environment in which the asset is deployed (for example, development, staging, or production).

▼ assetsCountnumberdouble

Total number of assets included in the response.

▼ configobject

Configuration settings associated with the application.

▶ lastRefreshDatestringdate-time

Date and time when the application data was last refreshed.

▶ assetSelectionobject

Define the logic for how specific technical assets must be linked to this application.

▼ updatedAtstringdate-time

Date and time when the configuration was last updated.

▼ deletedAtstringdate-time

Date and time when the configuration was deleted.

▼ enrichStatusstring (Enum)

Indicates whether asset enrichment is currently in progress.

Allowed values:"IN_PROGRESS""NOT_IN_PROGRESS"
▼ unifyAcrossProvidersboolean

If multiple applications share the same name at the chosen group-by level (org, project, or repository), they are merged across providers to form a single unified application.

▼ unifyWithinProviderboolean

Repositories with the same name at the selected group-by level (org, project, or repository) are consolidated into a single application within the selected provider.

RESPONSE

Example 1


```
{ "criteriaId": "string", "risk": -1.7976931348623157e+308, "id": "string", "strongId": "string", "name": "string",
"description": "string", "exposures": [ "DeployedToProduction" ], "coverage": -1.7976931348623157e+308,
"businessCriticality": "Critical", "businessUnit": "string", "creationType": "Auto", "businessOwner": [ "string" ],
"devOwner": [ "string" ], "devOpsOwner": [ "string" ], "productManager": [ "string" ], "environments": "string",
"assetsCount": -1.7976931348623157e+308, "config": { "lastRefreshDate": "2019-08-24T14:15:22Z", "assetSelection": {
"selectionType": "filter", "section": "code", "filter": { "values": [ "string" ], "provider": "CIRCLE_CI",
"filterType": "REPOSITORY" }, "assetIds": [ "string" ] } }, "updatedAt": "2019-08-24T14:15:22Z", "deletedAt": "2019-
08-24T14:15:22Z", "enrichStatus": "IN_PROGRESS" }
```

2.4.3.5 | Update an application

put /public_api/appsec/v1/application/{applicationId}

Updates the attributes of an existing application asset identified by its unique ID.

> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Path parameters

▼ applicationId String required

Unique ID of the Application

Example: `applicationId_example`

Request headers

▼ x-cas-trace-id String

Example: `xCasTraceId_example`

▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl


```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-cas-trace-id: xCasTraceId_example' -H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/{applicationId}'
-d '{ "creationType" : "Auto", "productManager" : [ "productManager", "productManager" ], "businessUnit" :
"businessUnit", "businessCriticality" : "Critical", "description" : "description", "devOwner" : [ "devOwner",
"devOwner" ], "devOpsOwner" : [ "devOpsOwner", "devOpsOwner" ], "businessOwner" : [ "businessOwner", "businessOwner" ]
}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}" headers = { 'x-cas-trace-id': "SOME_STRING_VALUE", 'Authorization':
```

```
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("PUT",
"/public_api/appsec/v1/application/%7BapplicationId%7D", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["x-cas-trace-id"] =
'SOME_STRING_VALUE' request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "businessCriticality": "Critical", "creationType": "Auto", "businessUnit": "string",
"description": "string", "compliance": "PCI-DSS", "businessOwner": [ "string" ], "devOwner": [ "string" ],
"devOpsOwner": [ "string" ], "productManager": [ "string" ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials
= true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); xhr.setRequestHeader("x-cas-trace-id",
"SOME_STRING_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") .header("x-cas-trace-id", "SOME_STRING_VALUE")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}") .asString();
import Foundation let headers = [ "x-cas-trace-id": "SOME_STRING_VALUE", "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "businessCriticality": "Critical",
"creationType": "Auto", "businessUnit": "string", "description": "string", "compliance": "PCI-DSS", "businessOwner":
["string"], "devOwner": ["string"], "devOpsOwner": ["string"], "productManager": ["string"] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-cas-trace-id: SOME_STRING_VALUE", "x-xdr-auth-id: 241" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-cas-trace-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers,
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); var request
= new RestRequest(Method.PUT); request.AddHeader("x-cas-trace-id", "SOME_STRING_VALUE");
```

```
request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"businessCriticality\":\"Critical\",\"creationType\":\"Auto\",\"businessUnit\":\"string\",\"description\":\"string\",\"compli
DSS\",\"businessOwner\":[\"string\"],\"devOwner\":[\"string\"],\"devOpsOwner\":[\"string\"],\"productManager\":
[\"string\"]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ businessCriticalitystring (Enum)

The operational importance of the asset.

Allowed values:"Critical""High""Medium""Low"
▼ creationTypestring (Enum)

How the asset was created.

Allowed values:"Auto""Manual"
▼ businessUnitstring

Business unit responsible for the asset.

▼ descriptionstring

Description providing additional details about the asset.

▼ compliancestring (Enum)

The compliance status or requirement category for an asset.

Allowed values:"PCI-DSS""ISO 27001""SOX""NIST""GDPR""CCPA""HIPAA""FedRAMP"
▼ businessOwnerarray[string]

Business owners responsible for the asset.

▼ devOwnerarray[string]

Development owners responsible for building and maintaining the asset.

▼ devOpsOwnerarray[string]

DevOps owners responsible for deployment and operations.

▼ productManagerarray[string]

Product managers responsible for the asset.

REQUEST

```
{ "businessCriticality": "Critical", "creationType": "Auto", "businessUnit": "example", "description": "example",
"compliance": "PCI-DSS", "businessOwner": [ "example" ], "devOwner": [ "example" ], "devOpsOwner": [ "example" ],
"productManager": [ "example" ] }
```

Responses

Ok

Body
application/json
▼ statusbooleanrequired

Displays the status of the application.

Default:`true`
▼ applicationIdstring

Displays the Asset ID of the application.

Example:`"a7dc11ea688c73dbbc759459ba661d7f7a7edaad229a3fdb50701b6548535f5b"`
RESPONSE

```
{ "status": false, "applicationId": "a7dc11ea688c73dbbc759459ba661d7f7a7edaad229a3fdb50701b6548535f5b" }
```

2.4.3.6 | Delete an application

delete /public_api/appsec/v1/application/{applicationId}

Deletes a specific application asset identified by its unique ID.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Path parameters

▼ applicationId String required

Unique ID of the Application

Example: `applicationId_example`

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/{applicationId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("DELETE", "/public_api/appsec/v1/application/%7BapplicationId%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/%7BapplicationId%7D"); var request
= new RestRequest(Method.DELETE); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ messagestringrequired
RESPONSE

```
{ "message": "example" }
```

2.4.4 | Policies

APIs for managing policies

2.4.4.1 | Create an AppSec policy

post /public_api/appsec/v1/policies

Creates a new Application Security policy.

An application security policy defines how a system responds to application security threats. Each policy consists of **Conditions**, **Scope**, **Triggers**, and **Actions**.

Triggers determine the execution context, such as a Pull Request, CI pipeline, registry scan, or periodic code scan, while **Actions** are executed only when both the **Condition** and **Scope** criteria are met.

Actions can include generating a remediation issue for detection or actively blocking threats within the PR or CI workflow.

> **Note:** To block threats in the CI workflow, you must integrate the Cortex CLI into your pipeline.
>
> **Required license:**
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

2.4.4.1.1 | Limitations

Be aware of the following limitations when creating policies:

2.4.4.1.1.1 | Trigger and Action Constraints by Finding Type

2. **Code & Image scanners Finding Types** (for example, `IAC_MISCONFIGURATION`, `SECRETS`, `VULNERABILITY`, `LICENSES`, `OPERATIONAL_RISK`, `CODE_WEAKNESS`, and `MALWARE`)

- For **scope filters**, only the following parameters are supported:
  - Category
  - Asset Type
  - Provider
  - Business Application Names
  - Application Business Criticality
  - Application Business Owner
  - Tags
  - Image Names
  - Source Branch
  - Repository Name
  - Repository Id
  - Is Public Repository
  - Has Deployed Assets
  - Has Internet-exposed deployed assets
  - Has deployed assets with Access to sensitive data
  - Has deployed assets with privileged capabilities
  - Repository labels
  - Image Architecture
  - Organization URL
- The `category` parameter only supports `Application`, `Container Image` and `Repository` values.
- Setting the `overrideIssueSeverity` parameter is mandatory when `ciImage` or `imageRegistry` actions are enabled.

3. **CI/CD Risks Finding Type** (`CICD_RISKS`)

- Only the Code **Periodic Scan** trigger is supported.
- Only the **reportIssue** action is available.
- For **conditions**, the `category` parameter supports only the following values:
  - Category
  - Application
  - CI/CD Instance
  - CI/CD Pipeline
  - VCS Collaborator
  - VCS Organization
- For **scope filters**, only the following parameters are supported:
  - Asset Type
  - Provider
  - Tags
  - Business Application Names
  - Application Business Criticality
  - CI/CD Instance Name
  - CI/CD Instance Id
  - CI/CD Pipeline Name
  - CI/CD Pipeline Id
  - VCS Collaborator Name
  - VCS Collaborator Email
  - VCS Collaborator MFA Enabled
  - VCS Collaborator Last Observed
  - VCS Organization Name
  - Repository Name
  - Repository Id
  - Is Public Repository

4. **Drift Finding Type** (`DRIFT`)

- Only the Code **Periodic Scan** trigger is supported.
- Only the **reportIssue** action is available.
- For **conditions**, the `category` parameter only supports `Application` and `Repository` values.
- For **scope filters**, only the following parameters are supported:
  - Category
  - Provider
  - Business Application Names
  - Application Business Criticality
  - Application Business Owner
  - Cloud Account
  - Cloud Region
  - Repository Name
  - Repository Id
  - Is Public Repository
  - Has Deployed Assets
  - Has Internet-exposed deployed assets
  - Has deployed assets with Access to sensitive data
  - Has deployed assets with privileged capabilities

2.4.4.1.1.2 | General Policy Constraints

1. **Third-Party Integration Data**
   - For ingested data from third-party integrations:
     - Only the **periodic** scan trigger is supported, along with the `ingestedData` action that must be explicitly configured.
2. **Multiple Finding Types in Conditions**
   - When selecting multiple `Finding Type` values within a single condition, only common filters across those types are available.
   - To use filters specific to a `Finding Type`, add another condition group that is separated by the **OR** operator.
3. **Condition and Scope Depth**
   - The UI supports up to **2 levels** of depth for conditions and scope.
   - The API allows up to **10 levels** of depth for more complex policy configurations.
4. **Scope vs. Asset Groups**
   - You must define either a **scope** (detailed asset filters) or specify **assetGroupIds**, but **not** both in the same policy.
   - If both fields are defined (contain values), then only the **assetGroupIds** will be applied and the **scope** will be ignored.
5. **Empty Results during Configuration**
   - `Conditions` and `scope` filters may return **empty results** during policy configuration.
   - Policies can still be saved for future use.
   - Once the policies are active, they will evaluate the conditions and trigger defined actions if matching results are found.

Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/policies'
-d '{ "userSbac" : [ 6.027456183070403, 6.027456183070403 ], "suggestionId" : "suggestionId", "scope" : { "OR" : [ {
"OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true }, { "OR" : [
null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true } ], "SEARCH_FIELD" :
"SEARCH_FIELD", "AND" : [ { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true } ] }, "name" : "name", "description" : "description", "assetGroupIds" : [ 0.8008281904610115,
0.8008281904610115 ], "conditions" : { "OR" : [ { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [
```

```
null, null ], "SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null
], "SEARCH_VALUE" : true } ], "SEARCH_FIELD" : "SEARCH_FIELD", "AND" : [ { "OR" : [ null, null ], "SEARCH_FIELD" :
"Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding
Type", "AND" : [ null, null ], "SEARCH_VALUE" : true } ], "SEARCH_VALUE" : true }, "triggers" : { "pr" : { "isEnabled"
: true, "actions" : { "reportIssue" : true, "blockPr" : true, "reportPrComment" : true }, "overrideIssueSeverity" :
"Critical" }, "imageRegistry" : { "isEnabled" : true, "actions" : { "reportIssue" : true }, "overrideIssueSeverity" :
"Critical" }, "periodic" : { "isEnabled" : true, "actions" : { "reportIssue" : true }, "overrideIssueSeverity" :
"Critical" }, "ciImage" : { "isEnabled" : true, "actions" : { "reportIssue" : true, "blockCicd" : true, "reportCicd" :
true }, "overrideIssueSeverity" : "Critical" }, "cicd" : { "isEnabled" : true, "actions" : { "reportIssue" : true,
"blockCicd" : true, "reportCicd" : true }, "overrideIssueSeverity" : "Critical" } }, "enabled" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}" headers = { 'Authorization': "your_api_key_here", 'x-xdr-auth-
id': "1", 'content-type': "application/json" } conn.request("POST", "/public_api/appsec/v1/policies", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/policies")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1'
request["content-type"] = 'application/json' request.body = "{\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
```

```
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "conditions": { "SEARCH_FIELD": "string", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE":
true, "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null
], "OR": [ null ] } ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE":
true, "AND": [ null ], "OR": [ null ] } ] } ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ] } ] }, "description": "string", "name":
"string", "scope": { "SEARCH_FIELD": "string", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ {
"SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ {
"SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ]
} ] } ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ {
"SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ]
} ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ],
"OR": [ null ] } ] } ] }, "triggers": { "cicd": { "actions": { "blockCicd": true, "reportCicd": true, "reportIssue":
true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "ciImage": { "actions": { "blockCicd": true,
"reportCicd": true, "reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "imageRegistry":
{ "actions": { "reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "periodic": {
"actions": { "reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "pr": { "actions": {
"blockPr": true, "reportIssue": true, "reportPrComment": true }, "isEnabled": true, "overrideIssueSeverity":
"Critical" } }, "enabled": true, "assetGroupIds": [ 0.1 ], "suggestionId": "string", "userSbac": [ 0.1 ] }); const xhr
= new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/appsec/v1/policies"); xhr.setRequestHeader("Authorization", "your_api_key_here");
xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/policies")
.header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .header("content-type",
"application/json") .body("{\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1", "content-type":
"application/json" ] let parameters = [ "conditions": [ "SEARCH_FIELD": "string", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE":
true, "AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [],
"OR": [] ] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND":
[], "OR": [] ] ] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true,
"AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []
] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR":
[] ] ] ] ] ], "description": "string", "name": "string", "scope": [ "SEARCH_FIELD": "string", "SEARCH_TYPE":
```

```
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE":
true, "AND": [], "OR": [] ] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [], "OR": [] ] ] ] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [], "OR": [] ] ], "OR": [ [ "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": [] ] ] ] ], "triggers": [ "cicd": [ "actions": [
"blockCicd": true, "reportCicd": true, "reportIssue": true ], "isEnabled": true, "overrideIssueSeverity": "Critical"
], "ciImage": [ "actions": [ "blockCicd": true, "reportCicd": true, "reportIssue": true ], "isEnabled": true,
"overrideIssueSeverity": "Critical" ], "imageRegistry": [ "actions": ["reportIssue": true], "isEnabled": true,
"overrideIssueSeverity": "Critical" ], "periodic": [ "actions": ["reportIssue": true], "isEnabled": true,
"overrideIssueSeverity": "Critical" ], "pr": [ "actions": [ "blockPr": true, "reportIssue": true, "reportPrComment":
true ], "isEnabled": true, "overrideIssueSeverity": "Critical" ] ], "enabled": true, "assetGroupIds": [0.1],
"suggestionId": "string", "userSbac": [0.1] ] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/policies")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/policies", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS =>
10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here",
"content-type: application/json", "x-xdr-auth-id: 1" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/policies"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-auth-id:
1"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
```

```
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/policies"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-id",
"1"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"conditions\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"description\":\"string\",\"name\":\"string\",\"scope\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[0.1],\"suggestionId\":\"string\",\"userSbac\":[0.1]}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```


Body parameters
required
application/json

Define the Application Security policy.

Notes:

- The `policyType` field is auto-assigned by the API based on the `Finding Type` in conditions, it is not set in the request body.
- The `conditions` and `scope` fields are required. The `scope` can be set to `{}` for global scope."

▼ conditionsobject

Defines the specific criteria (conditions) that will trigger the policy. You can combine multiple conditions to create complex rules for when the policy should be applied. If you combine multiple `Finding Type` values using `OR`, only the common fields across those types will be valid.

Note:

- When used in `AND`, all conditions within this array must be met.
- When used in `OR`, at least one condition within this array must be met.
- Selecting `Finding Type` determines which condition fields you can configure. Each `Finding Type` supports a specific set of condition fields. To see which fields are allowed for each type, see the Supported Condition Fields table.

2.4.4.2 | List AppSec policies

get /public_api/appsec/v1/policies

Retrieves a list of all Application Security policies. You can filter the results by finding types, actions, status, triggers, and custom policy flag.

> **Required license**:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
Query parameters
▼ findingTypes array[FindingType]

Type of security finding that the policy targets.

▼ actions array[UnifiedAction]

Filter policies by action types

▼ status PolicyStatus

Filter policies by status

▼ triggers array[Trigger]

Filter policies by trigger types

▼ isCustom Boolean

Filter by custom policies (`true`) or system-provided policies (`false`)

Example: `true`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/policies?findingTypes=&actions=&status=&triggers=&isCustom=true'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("GET", "/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' response =
http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
.header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
your_api_key_here", "x-xdr-auth-id: 1" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers =
curl_slist_append(headers, "x-xdr-auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/policies?
findingTypes=SOME_ARRAY_VALUE&actions=SOME_ARRAY_VALUE&status=SOME_STRING_VALUE&triggers=SOME_ARRAY_VALUE&isCustom=SOME_BOOLEAN
var request = new RestRequest(Method.GET); request.AddHeader("Authorization", "your_api_key_here");
request.AddHeader("x-xdr-auth-id", "1"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ dateCreatedstring

The date and time when the policy was created

▶ suggestionHashstring

Unique identifier for the suggested policy

▶ conditionsobject

Condition or scope filter for the policy.

▶ descriptionstring

Description of the policy

▶ idstringrequired

Unique identifier for the policy

▶ namestringrequired

Name of the policy

▶ scopeobject

Condition or scope filter for the policy.

▶ triggersobject

Defines when the AppSec policy should be evaluated. Configure triggers for periodic code scans, Pull Requests (PRs), CI Code scan, CI image scans, and Registry image scans. At least one trigger must have `isEnabled` set to `true`.

▶ dateDeletedstring

The date and time when the policy was deleted

▶ deletedBystring

The user or system that deleted the policy

▶ relatedDetectionRulesarray[string]required

List of related detection rules

▶ assetGroupIdsarray[number]

List of asset groups to which the policy applies. If the array is empty, the policy applies to all asset groups.

▶ suggestionIdstring

Unique identifier for the suggested policy

▶ createdBystringrequired

The user or system that created the policy

▶ dateModifiedstring

The date and time when the policy was last modified

▶ isClonableboolean

Indicates if the policy is cloneable

▶ isCustombooleanrequired

Indicates if the policy is a custom policy or a system-provided policy

▶ isEditableboolean

Indicates if the policy is editable

▶ lastTriggeredstring

The date and time when the policy was last triggered

▶ modifiedBystring

The user or system that last modified the policy

▶ overrideIssueSeverityobject (Enum)

Set the severity of the issue and override the system severity. If not used, system severity is kept.

▶ policyTypestring

Indicates the policy type. Auto-assigned by the API based on the `Finding Type` in conditions. Possible values:

- `code_image_scanners`: for VULNERABILITY, IAC_MISCONFIGURATION, SECRETS, CODE_WEAKNESS, LICENSES, OPERATIONAL_RISK, MALWARE
- `cicd_configuration_scanners`: for CICD_RISKS
- `drift_detection_scanners`: for DRIFT

▶ scopeFieldsobject

Defines all valid scope fields grouped by category for code, CI/CD, drift, and common contexts.

▶ statusstring (Enum)required

Current status of the policy.

▶ versionnumberrequireddouble

The version of the policy - goes up by one every policy update

]
RESPONSE
Example 1

```
[ { "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "name": "Block Build and Pull Request on Valid secrets",
"description": "Block Build and Pull Request on Valid secrets in public repository", "status": "disabled", "isCustom":
false, "triggers": { "periodic": { "isEnabled": false, "actions": { "reportIssue": false } }, "pr": { "isEnabled":
true, "actions": { "reportIssue": false, "reportPrComment": false, "blockPr": true } }, "cicd": { "isEnabled": true,
"actions": { "reportIssue": false, "reportCicd": false, "blockCicd": true } }, "ciImage": { "isEnabled": false,
"actions": { "reportIssue": false, "reportCicd": false, "blockCicd": false } }, "imageRegistry": { "isEnabled": false,
"actions": { "reportIssue": false } } }, "isClonable": true, "isEditable": false, "policyType": "code_image_scanners",
"conditions": { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "SECRETS" }, {
"SEARCH_FIELD": "Secret Validity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VALID" } ] }, "relatedDetectionRules": [],
"scope": { "AND": [ { "SEARCH_FIELD": "is_public_repository", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": true } ] },
"createdBy": "system", "modifiedBy": null, "deletedBy": null, "version": 1, "assetGroupIds": [] } ]
```

2.4.4.3 | Get an AppSec policy

get /public_api/appsec/v1/policies/{policyId}

Retrieves detailed information for a specific Application Security policy using its unique policy ID.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters

▼ policyId String required

Unique identifier for the policy

Example: `d4e5f6a7-b8c9-0123-def0-1234567890ab`

Request headers

▼ Authorization String required

{api_key}

Example: `your_api_key_here`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/policies/{policyId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("GET", "/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-
def0-1234567890ab", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-
b8c9-0123-def0-1234567890ab"); xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-
xdr-auth-id", "1"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-
def0-1234567890ab") .header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-
1234567890ab")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "x-xdr-auth-id: 1" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers,
"x-xdr-auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-
1234567890ab"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization", "your_api_key_here");
request.AddHeader("x-xdr-auth-id", "1"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body

application/json

▼ dateCreatedstring

The date and time when the policy was created

▼ suggestionHashstring

Unique identifier for the suggested policy

▼ conditionsobject

Condition or scope filter for the policy.

▶ SEARCH_FIELDstringrequired

Field the condition filter matches.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

The value compared against. The type of this field will differ depending on the `SEARCH_FIELD` that was specified.

▶ ANDarray
▶ ORarray
▼ descriptionstring

Description of the policy

▼ idstringrequired

Unique identifier for the policy

▼ namestringrequired

Name of the policy

▼ scopeobject

Condition or scope filter for the policy.

▶ SEARCH_FIELDstringrequired

Field the condition filter matches.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

The value compared against. The type of this field will differ depending on the `SEARCH_FIELD` that was specified.

▶ ANDarray
▶ ORarray
▼ triggersobject

Defines when the AppSec policy should be evaluated. Configure triggers for periodic code scans, Pull Requests (PRs), CI Code scan, CI image scans, and Registry image scans. At least one trigger must have `isEnabled` set to `true`.

▶ cicdobject

Configuration for the CI Code trigger. If `true`, the policy is evaluated on CI/CD pipeline events.

▶ ciImageobject

Configuration for the CI image trigger. If `true`, the policy is evaluated during CI image scans.

▶ imageRegistryobject

Configuration for the image registry trigger. If `true`, the policy is evaluated during registry image scans.

▶ periodicobject

Configuration for the periodic code scan (scheduled) trigger. If `true`, the policy is evaluated.

▶ probject

Configuration for the pull request (PR) trigger. If `true`, the policy is evaluated on Pull Request (PR) events

▼ dateDeletedstring

The date and time when the policy was deleted

▼ deletedBystring

The user or system that deleted the policy

▼ relatedDetectionRulesarray[string]required

List of related detection rules

▼ assetGroupIdsarray[number]

List of asset groups to which the policy applies. If the array is empty, the policy applies to all asset groups.

▼ suggestionIdstring

Unique identifier for the suggested policy

▼ createdBystringrequired

The user or system that created the policy

▼ dateModifiedstring

The date and time when the policy was last modified

▼ isClonableboolean

Indicates if the policy is cloneable

▼ isCustombooleanrequired

Indicates if the policy is a custom policy or a system-provided policy

▼ isEditableboolean

Indicates if the policy is editable

▼ lastTriggeredstring

The date and time when the policy was last triggered

▼ modifiedBystring

The user or system that last modified the policy

▼ overrideIssueSeverityobject (Enum)

Set the severity of the issue and override the system severity. If not used, system severity is kept.

Allowed values:"Critical""High""Medium""Low"
▼ policyTypestring

Indicates the policy type. Auto-assigned by the API based on the `Finding Type` in conditions. Possible values:

- `code_image_scanners`: for VULNERABILITY, IAC_MISCONFIGURATION, SECRETS, CODE_WEAKNESS, LICENSES, OPERATIONAL_RISK, MALWARE
- `cicd_configuration_scanners`: for CICD_RISKS
- `drift_detection_scanners`: for DRIFT

▼ scopeFieldsobject

Defines all valid scope fields grouped by category for code, CI/CD, drift, and common contexts.

▶ applicationsScopeFieldsarrayrequired

Fields that apply applications scopes.

▶ cicdOnlyScopeFieldsarrayrequired

Fields that only apply to CI/CD related scope keys.

▶ codeOnlyScopeFieldsarrayrequired

Fields that only apply to code repository scope keys.

▶ commonScopeFieldsarrayrequired

Fields that apply to both code and CI/CD scopes.

▶ defaultScopeFieldsarrayrequired

Fields that comes as default in the finding.

▶ driftOnlyScopeFieldsarrayrequired

Fields that only apply to IAC drift scope keys.

▼ statusstring (Enum)required

Current status of the policy.

Default:"enabled"
Allowed values:"disabled""enabled"
▼ versionnumberrequireddouble

The version of the policy - goes up by one every policy update
RESPONSE Custom Policy created via API


```
{ "id": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "name": "Image scan policy with all triggers", "description": "Detects vulnerabilities, secrets, and malware with CI Image Scan and Registry Image Scan triggers enabled.", "status": "enabled", "isCustom": true, "triggers": { "periodic": { "isEnabled": false, "overrideIssueSeverity": null, "actions": { "reportIssue": false } }, "pr": { "isEnabled": false, "overrideIssueSeverity": null, "actions": { "reportIssue": false, "reportPrComment": false, "blockPr": false } }, "cicd": { "isEnabled": false, "overrideIssueSeverity": null, "actions": { "reportIssue": false, "reportCicd": false, "blockCicd": false } }, "ciImage": { "isEnabled": true, "overrideIssueSeverity": "Medium", "actions": { "reportIssue": true, "reportCicd": false, "blockCicd": true } }, "imageRegistry": { "isEnabled": true, "overrideIssueSeverity": "Low", "actions": { "reportIssue": true } } }, "isClonable": true, "isEditable": true, "policyType": "code_image_scanners", "conditions": { "OR": [ { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "SECRETS" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" } ] }, { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VULNERABILITY" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] }, { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "MALWARE" } ] } ] }, "relatedDetectionRules": [], "scope": {}, "dateCreated": "2025-06-15T09:30:00.000Z", "createdBy": "API Token 1", "dateModified": "2025-06-15T09:30:00.000Z", "modifiedBy": "API Token 1", "deletedBy": null, "version": 1, "assetGroupIds": [] }
{ "id": "c3d4e5f6-a7b8-9012-cdef-123456789012", "name": "Create issues on findings of High and above severity", "description": "Create issues on findings of High and above severity", "status": "disabled", "isCustom": false, "triggers": { "periodic": { "isEnabled": true, "actions": { "reportIssue": true } }, "pr": { "isEnabled": true, "actions": { "reportIssue": true, "reportPrComment": true, "blockPr": true } }, "cicd": { "isEnabled": true, "actions": { "reportIssue": true, "reportCicd": true, "blockCicd": true } }, "ciImage": { "isEnabled": false, "actions": { "reportIssue": false, "reportCicd": false, "blockCicd": false } }, "imageRegistry": { "isEnabled": false, "actions": { "reportIssue": false } } }, "isClonable": true, "isEditable": false, "policyType": "code_image_scanners", "conditions": { "AND": [ { "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "IAC_MISCONFIGURATION" }, { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VULNERABILITY" }, { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "LICENSES" }, { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "SECRETS" }, { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CODE_WEAKNESS" }, { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "OPERATIONAL_RISK" } ] }, { "OR": [ { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] } ] }, "relatedDetectionRules": [], "scope": {}, "createdBy": "system", "modifiedBy": null, "deletedBy": null, "version": 1, "assetGroupIds": [] }
```

2.4.4.4 | Update an AppSec policy

put /public_api/appsec/v1/policies/{policyId}

Updates an existing Application Security policy by policy ID. Use this endpoint to modify the policyâ€ s Conditions, Scope, Triggers or Actions.

> Note: To block threats in the CI workflow, you must integrate the Cortex CLI into your pipeline.
>
> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ policyId String required

Unique identifier for the policy

Example: d4e5f6a7-b8c9-0123-def0-1234567890ab
Request headers
▼ Authorization String required

{api_key}

Example: your_api_key_here
▼ x-xdr-auth-id String required

{api_key_id}

Example: 1

CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/policies/{policyId}'
-d '{ "userSbac" : [ 6.027456183070403, 6.027456183070403 ], "suggestionId" : "suggestionId", "scope" : { "OR" : [ {
"OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true }, { "OR" : [
null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true } ], "SEARCH_FIELD" :
"SEARCH_FIELD", "AND" : [ { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true } ] }, "name" : "name", "relatedDetectionRules" : [ "relatedDetectionRules",
"relatedDetectionRules" ], "description" : "description", "assetGroupIds" : [ 0.8008281904610115, 0.8008281904610115
], "conditions" : { "OR" : [ { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding Type", "AND" : [ null, null ],
"SEARCH_VALUE" : true } ], "SEARCH_FIELD" : "SEARCH_FIELD", "AND" : [ { "OR" : [ null, null ], "SEARCH_FIELD" :
"Finding Type", "AND" : [ null, null ], "SEARCH_VALUE" : true }, { "OR" : [ null, null ], "SEARCH_FIELD" : "Finding
Type", "AND" : [ null, null ], "SEARCH_VALUE" : true } ], "SEARCH_VALUE" : true }, "triggers" : { "pr" : { "isEnabled"
: true, "actions" : { "reportIssue" : true, "blockPr" : true, "reportPrComment" : true }, "overrideIssueSeverity" :
"Critical" }, "imageRegistry" : { "isEnabled" : true, "actions" : { "reportIssue" : true }, "overrideIssueSeverity" :
"Critical" }, "periodic" : { "isEnabled" : true, "actions" : { "reportIssue" : true }, "overrideIssueSeverity" :
"Critical" }, "ciImage" : { "isEnabled" : true, "actions" : { "reportIssue" : true, "blockCicd" : true, "reportCicd" :
true }, "overrideIssueSeverity" : "Critical" }, "cicd" : { "isEnabled" : true, "actions" : { "reportIssue" : true,
"blockCicd" : true, "reportCicd" : true }, "overrideIssueSeverity" : "Critical" } }, "enabled" : true }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}" headers = {
'Authorization': "your_api_key_here", 'x-xdr-auth-id': "1", 'content-type': "application/json" } conn.request("PUT",
"/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab", payload, headers) res = conn.getresponse() data
= res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url)
request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' request["content-type"] =
'application/json' request.body = "{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
```

```
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "string", "description": "string", "conditions": { "SEARCH_FIELD": "string",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS",
"SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ] } ], "OR": [ { "SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ { "SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ] } ] },
"scope": { "SEARCH_FIELD": "string", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ { "SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ] } ], "OR":
[ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ { "SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ] } ], "OR": [ {
"SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [ null ], "OR": [ null ]
} ] } ] }, "triggers": { "cicd": { "actions": { "blockCicd": true, "reportCicd": true, "reportIssue": true },
"isEnabled": true, "overrideIssueSeverity": "Critical" }, "ciImage": { "actions": { "blockCicd": true, "reportCicd":
true, "reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "imageRegistry": { "actions": {
"reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "periodic": { "actions": {
"reportIssue": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" }, "pr": { "actions": { "blockPr": true,
"reportIssue": true, "reportPrComment": true }, "isEnabled": true, "overrideIssueSeverity": "Critical" } },
"relatedDetectionRules": [ "string" ], "enabled": true, "suggestionId": "string", "assetGroupIds": [ 0.1 ],
"userSbac": [ 0.1 ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-
b8c9-0123-def0-1234567890ab"); xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-
xdr-auth-id", "1"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-
def0-1234567890ab") .header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .header("content-
type", "application/json") .body("{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
```

{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}") .asString();
import Foundation let headers = ["Authorization": "your_api_key_here", "x-xdr-auth-id": "1", "content-type":
"application/json"] let parameters = ["name": "string", "description": "string", "conditions": ["SEARCH_FIELD":
"string", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding Type", "SEARCH_TYPE":
"ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]], "OR": [["SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]]], "OR": [["SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]], "OR": [["SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]]]], "scope": [
"SEARCH_FIELD": "string", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]], "OR": [["SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]]]], "OR": [["SEARCH_FIELD":
"Finding Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [["SEARCH_FIELD": "Finding Type",
"SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]], "OR": [["SEARCH_FIELD": "Finding
Type", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": true, "AND": [], "OR": []]]]], "triggers": ["cicd": [
"actions": ["blockCicd": true, "reportCicd": true, "reportIssue": true], "isEnabled": true, "overrideIssueSeverity":
"Critical"], "ciImage": ["actions": ["blockCicd": true, "reportCicd": true, "reportIssue": true], "isEnabled":
true, "overrideIssueSeverity": "Critical"], "imageRegistry": ["actions": ["reportIssue": true], "isEnabled": true,
"overrideIssueSeverity": "Critical"], "periodic": ["actions": ["reportIssue": true], "isEnabled": true,
"overrideIssueSeverity": "Critical"], "pr": ["actions": ["blockPr": true, "reportIssue": true, "reportPrComment":
true], "isEnabled": true, "overrideIssueSeverity": "Critical"]], "relatedDetectionRules": ["string"], "enabled":
true, "suggestionId": "string", "assetGroupIds": [0.1], "userSbac": [0.1]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}",
CURLOPT_HTTPHEADER => ["Authorization: your_api_key_here", "content-type: application/json", "x-xdr-auth-id: 1"],

```
]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers,
"x-xdr-auth-id: 1"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}"); CURLcode ret
= curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-
1234567890ab"); var request = new RestRequest(Method.PUT); request.AddHeader("Authorization", "your_api_key_here");
request.AddHeader("x-xdr-auth-id", "1"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"name\":\"string\",\"description\":\"string\",\"conditions\":
{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"scope\":{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":
[null],\"OR\":[null]}]}],\"OR\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[{\"SEARCH_FIELD\":\"Finding
Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":[null]}],\"OR\":
[{\"SEARCH_FIELD\":\"Finding Type\",\"SEARCH_TYPE\":\"ARRAY_CONTAINS\",\"SEARCH_VALUE\":true,\"AND\":[null],\"OR\":
[null]}]}]},\"triggers\":{\"cicd\":{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"ciIm
{\"actions\":
{\"blockCicd\":true,\"reportCicd\":true,\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"imag
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"periodic\":
{\"actions\":{\"reportIssue\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"},\"pr\":{\"actions\":
{\"blockPr\":true,\"reportIssue\":true,\"reportPrComment\":true},\"isEnabled\":true,\"overrideIssueSeverity\":\"Critical\"}},\"
[\"string\"],\"enabled\":true,\"suggestionId\":\"string\",\"assetGroupIds\":[0.1],\"userSbac\":[0.1]}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

Partial_BasePolicyRequest

required

application/json

▼ namestring

A unique name for the AppSec policy.

▼ descriptionstring

A brief description of the AppSec policy's purpose.

▼ conditionsobject

Defines the specific criteria (conditions) that will trigger the policy. You can combine multiple conditions to create complex rules for when the policy should be applied. If you combine multiple `Finding Type` values using `OR`, only the common fields across those types will be valid.

Note:

- When used in `AND`, all conditions within this array must be met.
- When used in `OR`, at least one condition within this array must be met.
- Selecting `Finding Type` determines which condition fields you can configure. Each `Finding Type` supports a specific set of condition fields. To see which fields are allowed for each type, see the Supported Condition Fields table.

2.4.4.5 | Delete an AppSec policy

delete /public_api/appsec/v1/policies/{policyId}

Deletes an Application Security policy by its policy ID.

> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ policyId String required

Unique identifier for the policy

Example: `d4e5f6a7-b8c9-0123-def0-1234567890ab`
Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/policies/{policyId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("DELETE", "/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-
def0-1234567890ab", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url)
request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-
b8c9-0123-def0-1234567890ab"); xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-
xdr-auth-id", "1"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-
def0-1234567890ab") .header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-
1234567890ab")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
```

```
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "x-xdr-auth-id: 1" ],
]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-1234567890ab"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers =
curl_slist_append(headers, "x-xdr-auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/policies/d4e5f6a7-b8c9-0123-def0-
1234567890ab"); var request = new RestRequest(Method.DELETE); request.AddHeader("Authorization", "your_api_key_here");
request.AddHeader("x-xdr-auth-id", "1"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ messagestringrequired
RESPONSE
Example 1

```
{ "message": "Policy 'd4e5f6a7-b8c9-0123-def0-1234567890ab' was successfully deleted" }
```

2.4.4.6 | Supported Condition Fields

▼

This table defines the available fields for building policy conditions when you select `Finding Type` option.

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Affected Software	Affected Software	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
AppSec Rule	AppSec Rule	ENUM	EQ, NEQ	Dynamic (loaded from detection rules)
AppSec Rule Category	AppSec Rule Category	ENUM	EQ, NEQ	Dynamic (loaded from detection rules)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
AppSec Rule Label	AppSec Rule Label	ARRAY	EQ, NEQ	Dynamic (loaded from detection rules)
Backlog Status	Backlog Status	ENUM	EQ, NEQ	Backlog, New
Base Image Vulnerability	Base Image Vulnerability	BOOLEAN	EQ, NEQ	true, false
Compliance Controls	Compliance Controls	ENUM	CONTAINS, NCONTAINS	Dynamic (loaded from compliance rules)
Compliance Standards	Compliance Standards	ENUM	CONTAINS, NCONTAINS	Dynamic (loaded from compliance rules)
CVE Description	CVE Description	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
CVE Fix Available Date	CVE Fix Available Date	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE, RELATIVE_TIMESTAMP	Timestamp / relative timestamp
CVE ID	CVE ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp CVE-2021-44228)
CVE Publish Date	CVE Publish Date	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE, RELATIVE_TIMESTAMP	Timestamp / relative timestamp
CVE Risk Factors	CVE Risk Factors	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Critical severity, High severity, Medium severity Has fix, Remote executio DoS - Low, DoS - High, Recent vulnerability, Exp exists - in the wild, Explo exists - POC, Attack complexity: low, Attack vector: network
CVSS	CVSS	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric 0.0â€ 10.0
CVSS Severity	CVSS Severity	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric
CWE ID	CWE ID	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp CWE-79, CWE-89)
Deprecated	Deprecated	BOOLEAN	EQ, NEQ	true (Yes), false (No)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Detection Method	Detection Method	ENUM	EQ, NEQ	Dynamic
EPSS	EPSS	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric 0.0â€ 1.0
Exploit Level	Exploit Level	ENUM	EQ, NEQ	Dynamic
Exploitable	Exploitable	BOOLEAN	EQ, NEQ	true, false
File Group ID	File Group ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 1001)
File Group Name	File Group Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp sudo, docker, users)
File Line	File Line	INT	EQ, NEQ, LT, LTE, GT, GTE	Numeric
File Name	File Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING



Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
File Owner ID	File Owner ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 0 for root)
File Owner Name	File Owner Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp root, admin, www-data)
File Path	File Path	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
File Permissions - group	File Permissions - group	STRING	EQ, NEQ	Free STRING (for examp r, rw, rwx)
File Permissions - others	File Permissions - others	STRING	EQ, NEQ	Free STRING (for examp rw)
File Permissions - owner	File Permissions - owner	STRING	EQ, NEQ	Free STRING (for examp rwx, rw, r)
File SHA256	File SHA256	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (SHA-256 hash)
File Size	File Size	INT	EQ, NEQ, LT, LTE, GT, GTE	Numeric
Finding Category	Finding Category	ENUM	EQ, NEQ	Configuration, Vulnerabil Malware, Identity, Data, Code, Posture, Brand Protection
Finding ID	Finding ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Finding Type	Finding Type	ENUM	EQ	CICD_RISKS, VULNERABILITY, SECRETS, IAC_MISCONFIGURATIO CODE_WEAKNESS, LICENSES, OPERATIONAL_RISK, MALWARE, DRIFT
Fix Versions	Fix Versions	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp 1.2.4, 2.0.1)
Grace Period	Grace Period	INT	EQ	Numeric (days)
Has A Fix	Has A Fix	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Has An Automated Fix	Has An Automated Fix	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Iac Tag	Iac Tag	JSON	JSON_WILDCARD, JSON_WILDCARD_NOT	JSON key-value (for example, {"key": "Environment", "value": "Production"})
Image Provider	Image Provider	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Docker Hub, JFrog Artifactory, AWS ECR)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Is AI/ML	Is AI/ML	BOOLEAN	EQ, NEQ	true, false
Is derived	Is derived	BOOLEAN	EQ, NEQ	true, false
Is Kev	Is Kev	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Is Root	Is Root	BOOLEAN	EQ, NEQ	true, false
Language	Language	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Java, Python, Go, JavaScript)
Layer ID	Layer ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (SHA-256 hash)
License Category	License Category	ENUM	EQ, NEQ	Weak copyleft, Strong copyleft, Non permissive
License Type	License Type	ENUM	EQ, NEQ	Artistic-1.0, Artistic-2.0, APSL, AGPL-1.0, AGPL-3.0, GPL-2.0, LGPL-2.0, LGPL-2.1, LGPL-3.0, MP 1.1, MPL-2.0, EPL-1.0, E 2.0, CDDL-1.0, BUSL-1.1 MS-RL, OSL-3.0, CC-BY-SA-4.0, and more
Maintained	Maintained	ENUM	EQ, NEQ	Infrequently Maintained, Moderately Maintained, Frequently Maintained

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Malware Verdict	Malware Verdict	ENUM	EQ, NEQ	Malware, Grayware
Operating System	Operating System	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Linux, Windows)
Operating System Distribution	Operating System Distribution	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Ubuntu, RedHat, Debian
Operating System Distro Release	Operating System Distro Release	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 22.04, 8.5)
Operating System Family	Operating System Family	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Debian-based, RHEL-based)
OWASP Category	OWASP Category	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp A01:2021-Broken Acces Control)
Package Dependency	Package Dependency	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Package Deprecated	Package Deprecated	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Package File Creation Time	Package File Creation Time	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE	Timestamp
Package Licenses	Package Licenses	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp MIT, Apache 2.0)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Package Maintained	Package Maintained	ENUM	EQ, NEQ	Infrequently Maintained, Moderately Maintained, Frequently Maintained
Package Name	Package Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp openssl, lodash, log4j-core)
Package Operational Risk	Package Operational Risk	ENUM	EQ, NEQ	Low, Medium, High
Package Popularity	Package Popularity	ENUM	EQ, NEQ	Low, Medium, High
Package PURL	Package PURL	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp pkg:npm/lodash@4.17.2
Package Type	Package Type	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp npm, PyPI, Maven, Go)
Package Version	Package Version	STRING	EQ, NEQ, LT, GT	Free STRING (for examp 1.2.3, <2.0.0)
PackageName	PackageName	STRING	N/A (hidden)	Free STRING
PackageVersion	PackageVersion	STRING	N/A (hidden)	Free STRING
Platform ID	Platform ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp x86_64, arm64)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Popularity	Popularity	ENUM	EQ, NEQ	Low, Medium, High
Provider	Provider	ENUM	EQ, NEQ	Gitlab CI, Azure Pipelines Github Actions, Circle CI Jenkins
Remediation	Remediation	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Repository File Path	Repository File Path	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Respect Developer Suppression	Respect Developer Suppression	ENUM	EQ	true (Yes), false (No)
Risk Factors	Risk Factors	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
RiskFactors	RiskFactors	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Critical severity, High severity, Medium severity Has fix, Remote executio DoS - Low, DoS - High, Recent vulnerability, Exp exists - in the wild, Explo exists - POC, Attack complexity: low, Attack vector: network

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Secret Type	Secret Type	ENUM	EQ, NEQ	Dynamic
Secret Validity	Secret Validity	ENUM	EQ, NEQ	No Validation, Privileged, Valid, Invalid, Unavailabl
Severity	Severity	ENUM	EQ, NEQ	Critical, High, Medium, L
Software Package Name	Software Package Name	STRING	N/A (hidden)	Free STRING
Software Package Version	Software Package Version	STRING	N/A (hidden)	Free STRING
Source	Source	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp semgrep, checkmarx)
Type ID	Type ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

▶ SEARCH_FIELDstringrequired

Defines the field the condition filter should match. To see which fields are allowed for each type, see the Supported Condition Fields table.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

Value that the condition filter must match. The type of this field will differ depending on the `SEARCH_FIELD` that you specified.

▶ ANDarray
▶ ORarray
▼ descriptionstring

A brief description of the AppSec policy's purpose.

▼ namestringrequired

A unique name for the AppSec policy.

▼ scopeobject

Defines the type of assets to be evaluated by the policy (the scope). You can combine multiple conditions to create complex rules for when the policy should be applied.

Note:

- When used in `AND`, all conditions within this array must be met.
- When used in `OR`, at least one condition within this array must be met.
- Cannot be used if `assetGroupIds` are set.

2.4.4.7 | Supported Scope Fields

▼

This table defines the available fields for building policy scopes that target specific assets.

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
Application Business Criticality	application_business_criticality	ENUM	EQ, NEQ	CRITICAL, HIGH,
Application Business Owner	application_business_owner	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Asset Type	asset_type_name	ENUM	EQ, NEQ	BUILD_IMAGE, B BUSINESS_APPL CIRCLE_CI_REPO ORTEX_CLI_REP GITHUB_ACTION GITHUB_ENTERP GITHUB_REPOSI GITLAB_REPOSI GITLAB_SELF_M GOOGLE_CLOUD HCP_TFC_RUN_T HCP_TFE_RUN_T JENKINS_REPOS
Asset Type	asset_type_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Business Application Names	business_application_names	STRING	ARRAY_CONTAINS, ARRAY_NOT_CONTAINS, NIS_EMPTY	(No predefined lis
Category	category	ENUM	EQ, NEQ	APPLICATION, C REPOSITORY, CI CICD_PIPELINE, VCS_ORGANIZAT
CI/CD Instance Id	cicd_instance_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
CI/CD Instance Name	cicd_instance_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
CI/CD Pipeline Id	cicd_pipeline_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
CI/CD Pipeline Name	cicd_pipeline_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Cloud Account	cloud_account	STRING	EQ, NEQ, CONTAINS	(No predefined lis
Cloud Region	cloud_region	STRING	EQ, NEQ, CONTAINS	(No predefined lis
Has Deployed Assets	has_deployed_assets	BOOLEAN	EQ, NEQ	true, false
Has deployed assets with Access to sensitive data	has_access_sensitive_data	BOOLEAN	EQ, NEQ	true, false
Has deployed assets with privileged capabilities	has_leverage_privileged_capabilities	BOOLEAN	EQ, NEQ	true, false
Has Internet-exposed deployed assets	has_internet_exposed	BOOLEAN	EQ, NEQ	true, false
Image Architecture	image_architecture	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Image Names	image_names	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Is Public Repository	is_public_repository	BOOLEAN	EQ, NEQ	true, false

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
Organization URL	organization_url	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Provider	repository_provider	ENUM	EQ, NEQ	ACTIVE_DIRECTO ALIBABA_CLOUD AWS_CODE_BUI AZURE AZURE_C AZURE_PIPELINE BITBUCKET BITB CHARTER_COMM CHECKMARX CI CORTEX_CLI DA DOCKER_HUB FA GITHUB GITHUB_ GITHUB_ENTERP GITLAB_CONTAI GITLAB_SELF_MA HCP_TFC_RUN_T HCP_TFE_RUN_T INCAPSULA JEN JFROG_ARTIFAC MICROSOFT_OFI OKTA ON_PREM RACKSPACE SEM SONARQUBE SO
Repository Id	repository_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Repository labels	repository_labels	ENUM	ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	ARCHIVED, PRIV
Repository Name	repository_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Source Branch	source_branch	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Tags	asset_tags	STRING	WILDCARD, NOT_WILDCARD	(No predefined lis

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
VCS Collaborator Email	collaborator_email	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
VCS Collaborator Last Observed	collaborator_inactive_days	STRING	EQ, NEQ, LTE, GTE	(No predefined lis
VCS Collaborator MFA Enabled	collaborator_mfa_enabled	BOOLEAN	EQ, NEQ	TRUE, FALSE
VCS Collaborator Name	collaborator_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
VCS Organization Name	repository_organization_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis

▶ SEARCH_FIELDstringrequired

Defines the field the matching criteria filter should match. To see which fields are allowed for each type, see the Supported Scope Fields table.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

Value that the condition filter must match. The type of this field will differ depending on the `SEARCH_FIELD` that you specified.

▶ ANDarray
▶ ORarray
▼ triggersobject

Defines when the AppSec policy should be evaluated. Configure triggers for periodic code scans, Pull Requests (PRs), CI Code scan, CI image scans, and Registry image scans. At least one trigger must have `isEnabled` set to `true`.

▶ cicdobject

Configuration for the CI Code trigger. If `true`, the policy is evaluated on CI/CD pipeline events.

▶ ciImageobject

Configuration for the CI image trigger. If `true`, the policy is evaluated during CI image scans.

▶ imageRegistryobject

Configuration for the image registry trigger. If `true`, the policy is evaluated during registry image scans.

▶ periodicobject

Configuration for the periodic code scan (scheduled) trigger. If `true`, the policy is evaluated.

▶ probject

Configuration for the pull request (PR) trigger. If `true`, the policy is evaluated on Pull Request (PR) events

▼ enabledboolean

Whether the policy is enabled upon creation.

▼ assetGroupIdsarray[number]

A list of asset group IDs that the policy should apply to. If the list is empty, the policy applies globally, unless other scope conditions are defined. **Note** : Cannot be used with the **scope** parameter.

▼ suggestionIdstring

Unique identifier for the suggested policy to link this policy to.

▼ userSbacarray[number]

Asset group IDs representing the user's scoped-based access control (SBAC) permissions at the time the policy is created. Controls which asset groups the policy applies to based on the creator's access. When empty, the policy applies to all user scoped asset groups.

REQUEST Code and Image Scanners Policy


```
{ "name": "Critical vulnerabilities in code deployed to internet-exposed assets", "description": "Detects critical and high-severity vulnerabilities on deployed assets with internet exposure.", "conditions": { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VULNERABILITY" }, { "OR": [ { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] } ] }, "scope": { "AND": [ { "SEARCH_FIELD": "has_internet_exposed", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": true } ] }, "assetGroupIds": [], "triggers": { "periodic": { "isEnabled": true, "actions": { "reportIssue": true } }, "pr": { "isEnabled": true, "actions": { "reportIssue": true, "blockPr": true, "reportPrComment": true }, "overrideIssueSeverity": null }, "cicd": { "isEnabled": true, "actions": { "reportIssue": true, "blockCicd": true, "reportCicd": true }, "overrideIssueSeverity": null }, "ciImage": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "imageRegistry": { "isEnabled": false, "actions": { "reportIssue": false }, "overrideIssueSeverity": null } } }
{ "name": "Critical CI/CD configuration risks", "description": "Detects critical and high severity CI/CD risks across pipelines and instances.", "conditions": { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CICD_RISKS" }, { "OR": [ { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" } ] } ] }, "scope": { "AND": [ { "SEARCH_FIELD": "repository_provider", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "GITHUB" } ] }, "assetGroupIds": [], "triggers": { "periodic": { "isEnabled": true, "actions": { "reportIssue": true } }, "pr": { "isEnabled": false, "actions": { "reportIssue": false, "blockPr": false, "reportPrComment": false }, "overrideIssueSeverity": null }, "cicd": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "ciImage": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "imageRegistry": { "isEnabled": false, "actions": { "reportIssue": false }, "overrideIssueSeverity": null } } }
{ "name": "Critical IaC drift detection", "description": "Detects critical and high severity IaC drift findings between deployed infrastructure and IaC definitions.", "conditions": { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "DRIFT" }, { "OR": [ { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] } ] }, "scope": {}, "triggers": { "periodic": { "isEnabled": true, "actions": { "reportIssue": true }, "overrideIssueSeverity": "Critical" }, "pr": { "isEnabled": false, "actions": { "reportIssue": false, "blockPr": false, "reportPrComment": false }, "overrideIssueSeverity": null }, "cicd": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "ciImage": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "imageRegistry": { "isEnabled": false, "actions": { "reportIssue": false }, "overrideIssueSeverity": null } } }
{ "name": "Image scan policy", "description": "Detects vulnerabilities, secrets, and malware with CI Image Scan and Registry Image Scan triggers enabled.", "conditions": { "OR": [ { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "SECRETS" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" } ] }, { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VULNERABILITY" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] }, { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "MALWARE" } ] } ] }, "scope": {}, "triggers": { "periodic": { "isEnabled": false, "actions": { "reportIssue": false }, "overrideIssueSeverity": null }, "pr": { "isEnabled": false, "actions": { "reportIssue": false, "blockPr": false, "reportPrComment": false }, "overrideIssueSeverity": null }, "cicd": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "ciImage": { "isEnabled": true, "actions": { "reportIssue": true, "blockCicd": true, "reportCicd": false }, "overrideIssueSeverity": "Medium" }, "imageRegistry": { "isEnabled": true, "actions": { "reportIssue": true }, "overrideIssueSeverity": "Low" } } }
```


Responses

No content

Bad Request

The error occurs when the server cannot process the request due to client-side errors in the request body. The error is returned when:

- Required fields are missing
- Field values are invalid (for example, incorrect `SEARCH_TYPE` for the given `SEARCH_FIELD`)
- The JSON request body is not structured properly (invalid payload structure)

Body
application/json
▼ errorstring

The HTTP error category. Indicates the general type of error that occurred.

▼ messagestring

A human-readable message with specific details about why the request failed.

RESPONSE
Example 1
```
{ "error": "Bad Request", "message": "Invalid value for 'name': must not be empty." }
```

Conflict.

Resolution

Use a unique policy name that does not match any existing policy.

Body
application/json
▼ errorstring

The HTTP error category. Indicates the general type of error that occurred.

▼ messagestring

A human-readable message with specific details about why the request failed.

RESPONSE
Example 1
```
{ "error": "Conflict", "message": "A policy with the name 'Critical vulnerabilities on internet-exposed assets'
already exists." }
```

Internal Server Error

Body
application/json
▼ errorstring

The HTTP error category. Indicates the general type of error that occurred.

▼ messagestring

A human-readable message with specific details about why the request failed.

RESPONSE
Example 1
```
{ "error": "Internal Server Error", "message": "An unexpected error occurred. Please try again later." }
```

2.4.4.8 | Supported Condition Fields

▼

This table defines the available fields for building policy conditions when you select `Finding Type` option.

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Affected Software	Affected Software	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
AppSec Rule	AppSec Rule	ENUM	EQ, NEQ	Dynamic (loaded from detection rules)
AppSec Rule Category	AppSec Rule Category	ENUM	EQ, NEQ	Dynamic (loaded from detection rules)
AppSec Rule Label	AppSec Rule Label	ARRAY	EQ, NEQ	Dynamic (loaded from detection rules)
Backlog Status	Backlog Status	ENUM	EQ, NEQ	Backlog, New
Base Image Vulnerability	Base Image Vulnerability	BOOLEAN	EQ, NEQ	true, false
Compliance Controls	Compliance Controls	ENUM	CONTAINS, NCONTAINS	Dynamic (loaded from compliance rules)
Compliance Standards	Compliance Standards	ENUM	CONTAINS, NCONTAINS	Dynamic (loaded from compliance rules)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
CVE Description	CVE Description	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
CVE Fix Available Date	CVE Fix Available Date	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE, RELATIVE_TIMESTAMP	Timestamp / relative timestamp
CVE ID	CVE ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp CVE-2021-44228)
CVE Publish Date	CVE Publish Date	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE, RELATIVE_TIMESTAMP	Timestamp / relative timestamp
CVE Risk Factors	CVE Risk Factors	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Critical severity, High severity, Medium severity Has fix, Remote executio DoS - Low, DoS - High, Recent vulnerability, Exp exists - in the wild, Explo exists - POC, Attack complexity: low, Attack vector: network
CVSS	CVSS	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric 0.0â€ 10.0
CVSS Severity	CVSS Severity	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
CWE ID	CWE ID	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp CWE-79, CWE-89)
Deprecated	Deprecated	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Detection Method	Detection Method	ENUM	EQ, NEQ	Dynamic
EPSS	EPSS	FLOAT	EQ, NEQ, LT, LTE, GT, GTE	Numeric 0.0â€ 1.0
Exploit Level	Exploit Level	ENUM	EQ, NEQ	Dynamic
Exploitable	Exploitable	BOOLEAN	EQ, NEQ	true, false
File Group ID	File Group ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 1001)
File Group Name	File Group Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp sudo, docker, users)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
File Line	File Line	INT	EQ, NEQ, LT, LTE, GT, GTE	Numeric
File Name	File Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
File Owner ID	File Owner ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 0 for root)
File Owner Name	File Owner Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp root, admin, www-data)
File Path	File Path	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
File Permissions - group	File Permissions - group	STRING	EQ, NEQ	Free STRING (for examp r, rw, rwx)
File Permissions - others	File Permissions - others	STRING	EQ, NEQ	Free STRING (for examp rw)
File Permissions - owner	File Permissions - owner	STRING	EQ, NEQ	Free STRING (for examp rwx, rw, r)
File SHA256	File SHA256	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (SHA-256 hash)
File Size	File Size	INT	EQ, NEQ, LT, LTE, GT, GTE	Numeric

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Finding Category	Finding Category	ENUM	EQ, NEQ	Configuration, Vulnerabil Malware, Identity, Data, Code, Posture, Brand Protection
Finding ID	Finding ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Finding Type	Finding Type	ENUM	EQ	CICD_RISKS, VULNERABILITY, SECRETS, IAC_MISCONFIGURATIO CODE_WEAKNESS, LICENSES, OPERATIONAL_RISK, MALWARE, DRIFT
Fix Versions	Fix Versions	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp 1.2.4, 2.0.1)
Grace Period	Grace Period	INT	EQ	Numeric (days)
Has A Fix	Has A Fix	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Has An Automated Fix	Has An Automated Fix	BOOLEAN	EQ, NEQ	true (Yes), false (No)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Iac Tag	Iac Tag	JSON	JSON_WILDCARD, JSON_WILDCARD_NOT	JSON key-value (for example, {"key": "Environment", "value": "Production"})
Image Provider	Image Provider	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Docker Hub, JFrog Artifactory, AWS ECR)
Is AI/ML	Is AI/ML	BOOLEAN	EQ, NEQ	true, false
Is derived	Is derived	BOOLEAN	EQ, NEQ	true, false
Is Kev	Is Kev	BOOLEAN	EQ, NEQ	true (Yes), false (No)
Is Root	Is Root	BOOLEAN	EQ, NEQ	true, false
Language	Language	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Java, Python, Go, JavaScript)
Layer ID	Layer ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (SHA-256 hash)
License Category	License Category	ENUM	EQ, NEQ	Weak copyleft, Strong copyleft, Non permissive

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
License Type	License Type	ENUM	EQ, NEQ	Artistic-1.0, Artistic-2.0, APSL, AGPL-1.0, AGPL-3.0, GPL-2.0, LGPL-2.0, LGPL-2.1, LGPL-3.0, MP 1.1, MPL-2.0, EPL-1.0, E 2.0, CDDL-1.0, BUSL-1.1 MS-RL, OSL-3.0, CC-BY-SA-4.0, and more
Maintained	Maintained	ENUM	EQ, NEQ	Infrequently Maintained, Moderately Maintained, Frequently Maintained
Malware Verdict	Malware Verdict	ENUM	EQ, NEQ	Malware, Grayware
Operating System	Operating System	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Linux, Windows)
Operating System Distribution	Operating System Distribution	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Ubuntu, RedHat, Debian
Operating System Distro Release	Operating System Distro Release	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp 22.04, 8.5)
Operating System Family	Operating System Family	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp Debian-based, RHEL-based)
OWASP Category	OWASP Category	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp A01:2021-Broken Acces Control)
Package Dependency	Package Dependency	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Package Deprecated	Package Deprecated	BOOLEAN	EQ, NEQ	true (Yes), false (No)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
Package File Creation Time	Package File Creation Time	TIMESTAMP	EQ, NEQ, LT, LTE, GT, GTE	Timestamp
Package Licenses	Package Licenses	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Free STRING (for examp MIT, Apache 2.0)
Package Maintained	Package Maintained	ENUM	EQ, NEQ	Infrequently Maintained, Moderately Maintained, Frequently Maintained
Package Name	Package Name	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp openssl, lodash, log4j-core)
Package Operational Risk	Package Operational Risk	ENUM	EQ, NEQ	Low, Medium, High
Package Popularity	Package Popularity	ENUM	EQ, NEQ	Low, Medium, High
Package PURL	Package PURL	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp pkg:npm/lodash@4.17.2
Package Type	Package Type	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp npm, PyPI, Maven, Go)
Package Version	Package Version	STRING	EQ, NEQ, LT, GT	Free STRING (for examp 1.2.3, <2.0.0)

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
PackageName	PackageName	STRING	N/A (hidden)	Free STRING
PackageVersion	PackageVersion	STRING	N/A (hidden)	Free STRING
Platform ID	Platform ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp x86_64, arm64)
Popularity	Popularity	ENUM	EQ, NEQ	Low, Medium, High
Provider	Provider	ENUM	EQ, NEQ	Gitlab CI, Azure Pipelines Github Actions, Circle CI Jenkins
Remediation	Remediation	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Repository File Path	Repository File Path	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING
Respect Developer Suppression	Respect Developer Suppression	ENUM	EQ	true (Yes), false (No)
Risk Factors	Risk Factors	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed SEARCH_TYPE Values	Possible SEARCH_VAL
RiskFactors	RiskFactors	ARRAY	EQ, NEQ, ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	Critical severity, High severity, Medium severity Has fix, Remote executio DoS - Low, DoS - High, Recent vulnerability, Exp exists - in the wild, Explo exists - POC, Attack complexity: low, Attack vector: network
Secret Type	Secret Type	ENUM	EQ, NEQ	Dynamic
Secret Validity	Secret Validity	ENUM	EQ, NEQ	No Validation, Privileged, Valid, Invalid, Unavailabl
Severity	Severity	ENUM	EQ, NEQ	Critical, High, Medium, L
Software Package Name	Software Package Name	STRING	N/A (hidden)	Free STRING
Software Package Version	Software Package Version	STRING	N/A (hidden)	Free STRING
Source	Source	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING (for examp semgrep, checkmarx)
Type ID	Type ID	STRING	EQ, NEQ, CONTAINS, NCONTAINS	Free STRING

▶ SEARCH_FIELDstringrequired

Defines the field the condition filter should match. To see which fields are allowed for each type, see the Supported Condition Fields table.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

Value that the condition filter must match. The type of this field will differ depending on the `SEARCH_FIELD` that you specified.

▶ ANDarray

▶ ORarray

▼ scopeobject

Defines the type of assets to be evaluated by the policy (the scope). You can combine multiple conditions to create complex rules for when the policy should be applied.

Note:

- When used in `AND`, all conditions within this array must be met.
- When used in `OR`, at least one condition within this array must be met.
- Cannot be used if `assetGroupIds` are set.

2.4.4.9 | Supported Scope Fields

▼

This table defines the available fields for building policy scopes that target specific assets.

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
Application Business Criticality	application_business_criticality	ENUM	EQ, NEQ	CRITICAL, HIGH,
Application Business Owner	application_business_owner	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Asset Type	asset_type_name	ENUM	EQ, NEQ	BUILD_IMAGE, B BUSINESS_APPL CIRCLE_CI_REPO ORTEX_CLI_REP GITHUB_ACTION GITHUB_ENTERP GITHUB_REPOSI GITLAB_REPOSIT GITLAB_SELF_M GOOGLE_CLOUD HCP_TFC_RUN_T HCP_TFE_RUN_T JENKINS_REPOS
Asset Type	asset_type_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Business Application Names	business_application_names	STRING	ARRAY_CONTAINS, ARRAY_NOT_CONTAINS, NIS_EMPTY	(No predefined lis
Category	category	ENUM	EQ, NEQ	APPLICATION, C REPOSITORY, CI CICD_PIPELINE, VCS_ORGANIZAT
CI/CD Instance Id	cicd_instance_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
CI/CD Instance Name	cicd_instance_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
CI/CD Pipeline Id	cicd_pipeline_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
CI/CD Pipeline Name	cicd_pipeline_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Cloud Account	cloud_account	STRING	EQ, NEQ, CONTAINS	(No predefined lis
Cloud Region	cloud_region	STRING	EQ, NEQ, CONTAINS	(No predefined lis
Has Deployed Assets	has_deployed_assets	BOOLEAN	EQ, NEQ	true, false
Has deployed assets with Access to sensitive data	has_access_sensitive_data	BOOLEAN	EQ, NEQ	true, false
Has deployed assets with privileged capabilities	has_leverage_privileged_capabilities	BOOLEAN	EQ, NEQ	true, false
Has Internet-exposed deployed assets	has_internet_exposed	BOOLEAN	EQ, NEQ	true, false
Image Architecture	image_architecture	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Image Names	image_names	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Is Public Repository	is_public_repository	BOOLEAN	EQ, NEQ	true, false

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
Organization URL	organization_url	STRING	CONTAINS_IN_LIST, NOT_CONTAINS_IN_LIST	(No predefined lis
Provider	repository_provider	ENUM	EQ, NEQ	ACTIVE_DIRECTO ALIBABA_CLOUD AWS_CODE_BUI AZURE AZURE_C AZURE_PIPELINE BITBUCKET BITB CHARTER_COMM CHECKMARX CI CORTEX_CLI DA DOCKER_HUB FA GITHUB GITHUB_ GITHUB_ENTERP GITLAB_CONTAI GITLAB_SELF_MA HCP_TFC_RUN_T HCP_TFE_RUN_T INCAPSULA JEN JFROG_ARTIFAC MICROSOFT_OFI OKTA ON_PREM RACKSPACE SEM SONARQUBE SO
Repository Id	repository_id	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Repository labels	repository_labels	ENUM	ARRAY_CONTAINS, ARRAY_NOT_CONTAINS	ARCHIVED, PRIV
Repository Name	repository_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Source Branch	source_branch	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
Tags	asset_tags	STRING	WILDCARD, NOT_WILDCARD	(No predefined lis

Pretty Name (FIELD_PRETTY_NAME)	Field Name (SEARCH_FIELD)	Data Type (DATA_TYPE)	Allowed (SEARCH_TYPE) Values	Possible Search
VCS Collaborator Email	collaborator_email	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
VCS Collaborator Last Observed	collaborator_inactive_days	STRING	EQ, NEQ, LTE, GTE	(No predefined lis
VCS Collaborator MFA Enabled	collaborator_mfa_enabled	BOOLEAN	EQ, NEQ	TRUE, FALSE
VCS Collaborator Name	collaborator_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis
VCS Organization Name	repository_organization_name	STRING	WILDCARD, WILDCARD_NOT, CONTAINS, NCONTAINS	(No predefined lis

▶ SEARCH_FIELDstringrequired

Defines the field the matching criteria filter should match. To see which fields are allowed for each type, see the Supported Scope Fields table.

▶ SEARCH_TYPEstring (Enum)required

Condition operator for this filter.

▶ SEARCH_VALUEobjectrequired

Value that the condition filter must match. The type of this field will differ depending on the `SEARCH_FIELD` that you specified.

▶ ANDarray
▶ ORarray
▼ triggersobject

Defines when the AppSec policy should be evaluated. Configure triggers for periodic code scans, Pull Requests (PRs), CI Code scan, CI image scans, and Registry image scans. At least one trigger must have `isEnabled` set to `true`.

▶ cicdobject

Configuration for the CI Code trigger. If `true`, the policy is evaluated on CI/CD pipeline events.

▶ ciImageobject

Configuration for the CI image trigger. If `true`, the policy is evaluated during CI image scans.

▶ imageRegistryobject

Configuration for the image registry trigger. If `true`, the policy is evaluated during registry image scans.

▶ periodicobject

Configuration for the periodic code scan (scheduled) trigger. If `true`, the policy is evaluated.

▶ probject

Configuration for the pull request (PR) trigger. If `true`, the policy is evaluated on Pull Request (PR) events

▼ relatedDetectionRulesarray[string]

List of related detection rules.

▼ enabledboolean

Whether the policy is enabled.

▼ suggestionIdstring

Unique identifier for the suggested policy.

▼ assetGroupIdsarray[number]

List of asset groups to which the policy applies. If the array is empty, the policy applies to all asset groups.

▼ userSbacarray[number]

Asset group IDs representing the user's scoped-based access control (SBAC) permissions at the time the policy is modified. Controls which asset groups the policy applies to based on the modifier's access. When empty, the policy applies to all asset groups.
REQUEST
Example 1

```
{ "name": "Updated policy name", "description": "Updated policy description", "conditions": { "AND": [ { "SEARCH_FIELD": "Finding Type", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "VULNERABILITY" }, { "OR": [ { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "CRITICAL" }, { "SEARCH_FIELD": "Severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "HIGH" } ] } ] }, "scope": { "AND": [ { "SEARCH_FIELD": "has_deployed_assets", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": true } ] }, "triggers": { "periodic": { "isEnabled": true, "actions": { "reportIssue": true }, "overrideIssueSeverity": "High" }, "pr": { "isEnabled": true, "actions": { "reportIssue": true, "blockPr": true, "reportPrComment": true }, "overrideIssueSeverity": null }, "cicd": { "isEnabled": true, "actions": { "reportIssue": true, "blockCicd": false, "reportCicd": true }, "overrideIssueSeverity": null }, "ciImage": { "isEnabled": false, "actions": { "reportIssue": false, "blockCicd": false, "reportCicd": false }, "overrideIssueSeverity": null }, "imageRegistry": { "isEnabled": false, "actions": { "reportIssue": false }, "overrideIssueSeverity": null } } }
```

Responses

No content

Unprocessable Entity

Body
application/json
▼ errorCodestring

The HTTP error category. Indicates the general type of error that occurred.

▼ messagestring

A human-readable message with specific details about why the request failed. Use this message for debugging and troubleshooting.

RESPONSE Example 1

```
{ "errorCode": "_BadParamsError", "message": "The following triggers are not compatible with the policy conditions: [CI Image, Image Registry]. Allowed triggers based on conditions: [PR, CI/CD, Periodic]." }
{ "errorCode": "_BadParamsError", "message": "Conditions cannot be empty." }
```

2.4.5 | Rules

APIs for managing rules

2.4.5.1 | Get AppSec rules

get /public_api/appsec/v1/rules

Application Security rules are designed to detect security threats within your application security environment. Application Security rules identify and flag issues based on predefined criteria.

Get a list of all the Application Security rules. We recommend you use the parameters to filter the rules since there are many of them.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

▼ x-xdr-auth-id String required

{api_key_id}
Example: `241`
▼ get-scanner-rule-id Boolean

Unique identifier for a scanner rule

Example: `true`
Query parameters
▼ enabled Boolean

Whether the rule is enabled

Example: `true`
▼ isCustom Boolean
Example: `true`
▼ scanners array[Scanner]

Type of security scanner used to detect findings of this rule

▼ severities array[Severity]

The priority level assigned to findings identified by the rule

▼ frameworks array[FrameworkName]

The framework or language that the Application Security rule applies to (for example, GitHub, Terraform, JavaScript)

▼ labels array[String]

Labels assigned to the rule

▼ categories array[String]
▼ subCategories array[String]
▼ cloudProviders array[String]
Allowed values: ALIBABA_CLOUD AWS AZURE GCP IBM ORACLE OTHER
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`
▼ sortBy String
Allowed values: created_at name labels
Example: `sortBy_example`
Default: `name`
▼ sortOrder SortDirection

Sort direction
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241' -H 'get-scanner-rule-id: true'
'https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=true&isCustom=true&scanners=&severities=&frameworks=&labels=&categories=&subCategories=&cloudProviders=&offset=1.2&limi
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'get-scanner-rule-id': "SOME_BOOLEAN_VALUE" } conn.request("GET",
"/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["get-scanner-rule-id"] = 'SOME_BOOLEAN_VALUE' response =
http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("get-scanner-rule-id", "SOME_BOOLEAN_VALUE");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("get-scanner-rule-id", "SOME_BOOLEAN_VALUE") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "get-scanner-rule-id": "SOME_BOOLEAN_VALUE" ] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "get-scanner-rule-id: SOME_BOOLEAN_VALUE", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "get-scanner-
rule-id: SOME_BOOLEAN_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules?
enabled=SOME_BOOLEAN_VALUE&isCustom=SOME_BOOLEAN_VALUE&scanners=SOME_ARRAY_VALUE&severities=SOME_ARRAY_VALUE&frameworks=SOME_AR
var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("get-scanner-rule-id", "SOME_BOOLEAN_VALUE");
IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json

▼ offsetnumberdouble

▼ rulesarray

[

▶ categorystring

Custom rule IaC category.

▶ cloudProviderstring (Enum)

▶ createdAtstringdate-time

The timestamp when the AppSec rule was created.

▶ descriptionstring

The rule description.

▶ detectionMethodstring

security scanner used to detect findings of this rule.

▶ docLinkstring

A link to the Cortex documentation.
▶ domainstring

The domain associated with the rule.

▶ findingTypeIdnumberdouble

The finding type ID.

▶ frameworksarray
▶ idstring

Appsec rule ID.

▶ isCustomboolean

Indicates whether the rule is custom.

▶ isEnabledboolean

Indicates whether the rule is enabled.

▶ labelsarray[string]

Labels assigned to the rule.

▶ namestring

Name of the Appsec rule.

▶ ownerstring

Owner of the rule.

▶ scannerstring (Enum)
▶ severitystring (Enum)

Severity

▶ subCategorystring

Custom rule subcategory.

▶ updatedAtstringdate-time

The timestamp when the AppSec rule was updated.

▶ findingCategorystring (Enum)
▶ findingDocsstring
▶ mitreTacticsarray[string]

The associated MITRE ATT&CK tactics.

▶ mitreTechniquesarray[string]

The associated MITRE ATT&CK techniques.

▶ shortDescriptionstring
]
RESPONSE


```
{ "offset": 0.1, "rules": [ { "category": "example", "cloudProvider": "ALIBABA_CLOUD", "createdAt": "2020-01-
01T12:00:00Z", "description": "example", "detectionMethod": "IaC Security", "docLink": "example", "domain": "POSTURE",
"findingTypeId": 30040031, "frameworks": [ { "frameworkDetails": { "definition": "example", "definition_link":
"example", "name": "ARM", "remediation_description": "example", "remediation_ids": [ "example" ], "resource_types": [
"example" ] } } ], "id": "example", "isCustom": false, "isEnabled": false, "labels": [ "example" ], "name": "example",
"owner": "CAS", "scanner": "CICD", "severity": "CRITICAL", "subCategory": "STORAGE_BUCKETS", "updatedAt": "2020-01-
01T12:00:00Z", "findingCategory": "Code", "findingDocs": "Custom IaC rule for Public Exposure Storage Buckets",
"mitreTactics": [ "example" ], "mitreTechniques": [ "example" ], "shortDescription": "example" } ] }
```

2.4.5.2 | Create an AppSec rule

post /public_api/appsec/v1/rules

Application Security rules are designed to detect security threats within your application security environment. Application Security rules identify and flag issues based on predefined criteria.

Limitation

Rules can only be created for IaC Security and Secrets Security; creating rules for CI/CD Security is **not** supported.

Required license

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules'
-d '{ "name" : "name", "scanner" : { "definitionLink" : "definitionLink", "subCategory" : "", "definition" :
"definition:\\n cond_type: attribute\\n resource_types:\\n - aws_s3_bucket_public_access_block\\n attribute:
block_public_acls\\n operator: equals\\n value: false", "remediationDescription" : "Set block_public_acls to true in
aws_s3_bucket_public_access_block resource" }, "description" : "description", "labels" : [ "Custom-Rule", "Custom-
Rule" ] }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-Rule\"],\"scanner\":
{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST", "/public_api/appsec/v1/rules",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/rules") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-Rule\"],\"scanner\":
{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "string", "description": "string", "severity": "CRITICAL", "labels": [ "Custom-
Rule" ], "scanner": { "name": "ARM", "category": "AI_ML", "subCategory": "GUARDRAILS", "definition": "definition:\\n
cond_type: attribute\\n resource_types:\\n - aws_s3_bucket_public_access_block\\n attribute: block_public_acls\\n
operator: equals\\n value: false", "definitionLink": "string", "remediationDescription": "Set block_public_acls to
true in aws_s3_bucket_public_access_block resource" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/appsec/v1/rules");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/rules")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-Rule\"],\"scanner\":
```

{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}") .asString();
import Foundation let headers = ["Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json"] let parameters = ["name": "string", "description":
"string", "severity": "CRITICAL", "labels": ["Custom-Rule"], "scanner": ["name": "ARM", "category": "AI_ML",
"subCategory": "GUARDRAILS", "definition": "definition:\n cond_type: attribute\n resource_types:\n -
aws_s3_bucket_public_access_block\n attribute: block_public_acls\n operator: equals\n value: false", "definitionLink":
"string", "remediationDescription": "Set block_public_acls to true in aws_s3_bucket_public_access_block resource"]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/rules")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-
Rule\"],\"scanner\":
{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}", CURLOPT_HTTPHEADER => ["Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241"],]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/rules"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-Rule\"],\"scanner\":
{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"name\":\"string\",\"description\":\"string\",\"severity\":\"CRITICAL\",\"labels\":[\"Custom-Rule\"],\"scanner\":
{\"name\":\"ARM\",\"category\":\"AI_ML\",\"subCategory\":\"GUARDRAILS\",\"definition\":\"definition:\\\\n cond_type:
attribute\\\\n resource_types:\\\\n - aws_s3_bucket_public_access_block\\\\n attribute: block_public_acls\\\\n
operator: equals\\\\n value: false\",\"definitionLink\":\"string\",\"remediationDescription\":\"Set block_public_acls
to true in aws_s3_bucket_public_access_block resource\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);

Body parameters
required
application/json

Define the Application Security custom rule. The `category` option should match your selection for `scanner`.

▼ namestringrequired

A unique name for the Appsec rule.

▼ descriptionstring

Description of the rule

▼ severitystring (Enum)required

Severity

Allowed values:"CRITICAL""HIGH""LOW""MEDIUM"

▼ labelsarray[string]

Labels to be assigned to the rule

▼ scannerobjectrequired

The type of security scanner used to detect findings of this rule. Choose any one of the scanners. Allowed Values: `IAC` or `SECRETS`.

Any of IACSecurity

▶ namestring (Enum)required

Name of the configured frameworks.

▶ categorystring (Enum)

Custom rule IaC category

▶ subCategoryobject

▶ definitionstringrequired

The rule definition

▶ definitionLinkstring

http link to the definition documentation.

▶ remediationDescriptionstring

The remediation steps that will appear on the Appsec rule's findings.

▶ categorystring (Enum)

Custom rule secret category

▶ definitionstringrequired

The rule definition

▶ definitionLinkstring

http link to the documentation.

▶ remediationDescriptionstring

The remediation steps that will appear on the Appsec rule's findings.

REQUEST IaC Security Rule

```
{ "name": "S3 Bucket Public Access Check", "description": "Detects S3 buckets with public access enabled", "severity": "HIGH", "scanner": "IAC", "category": "PUBLIC", "subCategory": "STORAGE_BUCKETS", "labels": [ "Custom-Rule", "S3-Security" ], "frameworks": [ { "name": "TERRAFORM", "definition": "definition:\n cond_type: attribute\n resource_types:\n - aws_s3_bucket_public_access_block\n attribute: block_public_acls\n operator: equals\n value: false", "remediationDescription": "Set block_public_acls to true in aws_s3_bucket_public_access_block resource" } ] }
{ "name": "example secret rule", "description": "This is a secret rule description", "severity": "LOW", "scanner": "SECRETS", "labels": [ "my-label" ], "category": "API_KEYS", "frameworks": [ { "name": "GIT", "definition": "definition:\n cond_type: secrets\n value: AIza[0-9A-Za-z-_]{35}", "remediationDescription": "Revoke the GCP API key immediately through the Google Cloud Console." } ] }
```

Responses

Created

Body
application/json

Details of the Application Security rule

▼ categorystring

Custom rule IaC category.

▼ cloudProviderstring (Enum)
Allowed values:"ALIBABA_CLOUD""AWS""Azure""GCP""IBM""ORACLE""OTHER"

▼ createdAtstringdate-time

The timestamp when the AppSec rule was created.

▼ descriptionstring

The rule description.
▼ detectionMethodstring

security scanner used to detect findings of this rule.

Example:`"IaC Security"`
▼ docLinkstring

A link to the Cortex documentation.

▼ domainstring

The domain associated with the rule.

Example:`"POSTURE"`
▼ findingTypeIdnumberdouble

The finding type ID.

Example:`30040031`
▼ frameworksarray
[
▶ frameworkDetailsobject
]
▼ idstring

Appsec rule ID.

▼ isCustomboolean

Indicates whether the rule is custom.

▼ isEnabledboolean

Indicates whether the rule is enabled.

▼ labelsarray[string]

Labels assigned to the rule.

▼ namestring

Name of the Appsec rule.

▼ ownerstring

Owner of the rule.

Example:`"CAS"`
▼ scannerstring (Enum)
Allowed values:"CICD""IAC""SCA""SECRETS"
▼ severitystring (Enum)

Severity

Allowed values:"CRITICAL""HIGH""LOW""MEDIUM"
▼ subCategorystring

Custom rule subcategory.

Example:`"STORAGE_BUCKETS"`
▼ updatedAtstringdate-time

The timestamp when the AppSec rule was updated.

▼ findingCategorystring (Enum)
Allowed values:"Code""Configuration""Data""Vulnerability"
▼ findingDocsstring
Example:`"Custom IaC rule for Public Exposure Storage Buckets"`
▼ mitreTacticsarray[string]

The associated MITRE ATT&CK tactics.

▼ mitreTechniquesarray[string]

The associated MITRE ATT&CK techniques.

▼ shortDescriptionstring

RESPONSE


```
{ "category": "example", "cloudProvider": "ALIBABA_CLOUD", "createdAt": "2020-01-01T12:00:00Z", "description":
"example", "detectionMethod": "IaC Security", "docLink": "example", "domain": "POSTURE", "findingTypeId": 30040031,
"frameworks": [ { "frameworkDetails": { "definition": "example", "definition_link": "example", "name": "ARM",
"remediation_description": "example", "remediation_ids": [ "example" ], "resource_types": [ "example" ] } } ], "id":
"example", "isCustom": false, "isEnabled": false, "labels": [ "example" ], "name": "example", "owner": "CAS",
"scanner": "CICD", "severity": "CRITICAL", "subCategory": "STORAGE_BUCKETS", "updatedAt": "2020-01-01T12:00:00Z",
"findingCategory": "Code", "findingDocs": "Custom IaC rule for Public Exposure Storage Buckets", "mitreTactics": [
"example" ], "mitreTechniques": [ "example" ], "shortDescription": "example" }
```

2.4.5.3 | Get an AppSec rule

get /public_api/appsec/v1/rules/{ruleId}

Get the details of the specified Application Security rule.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ ruleId String required
Example: `ruleId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl


```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules/{ruleId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/rules/%7BruleId%7D", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
Any of a

▶ categorystring

Custom rule IaC category.

▶ cloudProviderstring (Enum)
▶ createdAtstringdate-time

The timestamp when the AppSec rule was created.

▶ descriptionstring

The rule description.

▶ detectionMethodstring

security scanner used to detect findings of this rule.

▶ docLinkstring

A link to the Cortex documentation.

▶ domainstring

The domain associated with the rule.

▶ findingTypeIdnumberdouble

The finding type ID.

▶ frameworksarray
▶ idstring

Appsec rule ID.

▶ isCustomboolean

Indicates whether the rule is custom.

▶ isEnabledboolean

Indicates whether the rule is enabled.

▶ labelsarray[string]

Labels assigned to the rule.

▶ namestring

Name of the Appsec rule.

▶ ownerstring

Owner of the rule.

▶ scannerstring (Enum)
▶ severitystring (Enum)

Severity

▶ subCategorystring

Custom rule subcategory.

▶ updatedAtstringdate-time

The timestamp when the AppSec rule was updated.

▶ findingCategorystring (Enum)
▶ findingDocsstring
▶ mitreTacticsarray[string]

The associated MITRE ATT&CK tactics.

▶ mitreTechniquesarray[string]

The associated MITRE ATT&CK techniques.

▶ shortDescriptionstring
RESPONSE


```
{ "category": "example", "cloudProvider": "ALIBABA_CLOUD", "createdAt": "2020-01-01T12:00:00Z", "description":
"example", "detectionMethod": "IaC Security", "docLink": "example", "domain": "POSTURE", "findingTypeId": 30040031,
"frameworks": [ { "frameworkDetails": { "definition": "example", "definition_link": "example", "name": "ARM",
"remediation_description": "example", "remediation_ids": [ "example" ], "resource_types": [ "example" ] } } ], "id":
"example", "isCustom": false, "isEnabled": false, "labels": [ "example" ], "name": "example", "owner": "CAS",
"scanner": "CICD", "severity": "CRITICAL", "subCategory": "STORAGE_BUCKETS", "updatedAt": "2020-01-01T12:00:00Z",
"findingCategory": "Code", "findingDocs": "Custom IaC rule for Public Exposure Storage Buckets", "mitreTactics": [
"example" ], "mitreTechniques": [ "example" ], "shortDescription": "example" }
```

2.4.5.4 | Modify an AppSec rule

patch /public_api/appsec/v1/rules/{ruleId}

Modify an existing Application Security rule. If it's an out-of-the-box rule, the only modification you can make is to add labels. For custom rules, you can modify all of the fields.

Note: To customize an out-of-the-box rule, you can create a custom rule by cloning the existing one. This allows you to make changes to the original rule according to your requirements.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ ruleId String required
Example: `ruleId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl


```
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules/{ruleId}'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"labels\":[\"string\"]}" headers =
{ 'Authorization':
```

```
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("PATCH",
"/public_api/appsec/v1/rules/%7BruleId%7D", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Patch.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"labels\":
[\"string\"]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "labels": [ "string" ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PATCH", "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"labels\":[\"string\"]}")
.asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["labels": ["string"]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PATCH" request.allHTTPHeaderFields
= headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PATCH", CURLOPT_POSTFIELDS => "{\"labels\":[\"string\"]}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"labels\":[\"string\"]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); var request = new
RestRequest(Method.PATCH); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"labels\":[\"string\"]}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

required

application/json

Any of ModifyRuleParams

▶ labelsarray[string]required

List of rule labels

▶ namestringrequired

A unique name for the Appsec rule.

▶ descriptionstring

Description of the rule

▶ severitystring (Enum)required

Severity

▶ labelsarray[string]

Labels to be assigned to the rule

▶ scannerobjectrequired

The type of security scanner used to detect findings of this rule. Choose any one of the scanners. Allowed Values: `IAC` or `SECRETS`.

REQUEST

```
{ "labels": [ "Custom-Rule" ], "name": "example", "description": "example", "severity": "CRITICAL", "scanner": { "name": "ARM", "category": "API_KEYS", "subCategory": "GUARDRAILS", "definition": "definition:\\n cond_type: secrets\\n value: AIza[0-9A-Za-z-_]{35}", "definitionLink": "example", "remediationDescription": "Revoke the GCP API key immediately through the Google Cloud Console." } }
```

Responses

Ok

Body

application/json

Updated details of the modified Application Security rule

▼ ruleobject

Details of the Application Security rule

▶ categorystring

Custom rule IaC category.

▶ cloudProviderstring (Enum)

▶ createdAtstringdate-time

The timestamp when the AppSec rule was created.

▶ descriptionstring

The rule description.

▶ detectionMethodstring

security scanner used to detect findings of this rule.

▶ docLinkstring

A link to the Cortex documentation.

▶ domainstring

The domain associated with the rule.

▶ findingTypeIdnumberdouble

The finding type ID.

▶ frameworksarray

▶ idstring

Appsec rule ID.

▶ isCustomboolean

Indicates whether the rule is custom.

▶ isEnabledboolean

Indicates whether the rule is enabled.

▶ labelsarray[string]

Labels assigned to the rule.

▶ namestring

Name of the Appsec rule.

▶ ownerstring

Owner of the rule.

▶ scannerstring (Enum)
▶ severitystring (Enum)

Severity

▶ subCategorystring

Custom rule subcategory.

▶ updatedAtstringdate-time

The timestamp when the AppSec rule was updated.

▶ findingCategorystring (Enum)
▶ findingDocsstring
▶ mitreTacticsarray[string]

The associated MITRE ATT&CK tactics.

▶ mitreTechniquesarray[string]

The associated MITRE ATT&CK techniques.

▶ shortDescriptionstring
RESPONSE

```
{ "rule": { "category": "example", "cloudProvider": "ALIBABA_CLOUD", "createdAt": "2020-01-01T12:00:00Z",
"description": "example", "detectionMethod": "IaC Security", "docLink": "example", "domain": "POSTURE",
"findingTypeId": 30040031, "frameworks": [ { "frameworkDetails": { "definition": "example", "definition_link":
"example", "name": "ARM", "remediation_description": "example", "remediation_ids": [ "example" ], "resource_types": [
"example" ] } } ], "id": "example", "isCustom": false, "isEnabled": false, "labels": [ "example" ], "name": "example",
"owner": "CAS", "scanner": "CICD", "severity": "CRITICAL", "subCategory": "STORAGE_BUCKETS", "updatedAt": "2020-01-
01T12:00:00Z", "findingCategory": "Code", "findingDocs": "Custom IaC rule for Public Exposure Storage Buckets",
"mitreTactics": [ "example" ], "mitreTechniques": [ "example" ], "shortDescription": "example" } }
```

2.4.5.5 | Delete an AppSec rule

delete /public_api/appsec/v1/rules/{ruleId}

Delete the specified Application Security rule.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ ruleId String required
Example: `ruleId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules/{ruleId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("DELETE", "/public_api/appsec/v1/rules/%7BruleId%7D", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) request["Authorization"] =
```

```
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "DELETE", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules/%7BruleId%7D"); var request = new
RestRequest(Method.DELETE); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ messagestringrequired
RESPONSE

```
{ "message": "example" }
```

2.4.5.6 | Get AppSec rule labels

get /public_api/appsec/v1/rules/rule-labels

Get a list of all of the Application Security rule labels.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules/rule-labels'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/rules/rule-labels", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/rules/rule-
labels") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE
request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/rules/rule-labels");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/rules/rule-labels")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/rules/rule-labels")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules/rule-labels", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/rules/rule-labels"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules/rule-labels"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json

A list of labels

▼ labelsarray[string]
RESPONSE

```
{ "labels": [ "example" ] }
```

2.4.5.7 | Create an AppSec rule validation

post /public_api/appsec/v1/rules/validate

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/rules/validate'
-d '{ "definition" : "definition" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
[{\"framework\":\"ARM\",\"definition\":\"string\"}]" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/rules/validate", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/rules/validate") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
[{\"framework\":\"ARM\",\"definition\":\"string\"}]" response = http.request(request) puts response.read_body
const data = JSON.stringify([ { "framework": "ARM", "definition": "string" } ]); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/appsec/v1/rules/validate");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/rules/validate")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
[{\"framework\":\"ARM\",\"definition\":\"string\"}]") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ [ "framework": "ARM", "definition":
"string" ] ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/rules/validate")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/rules/validate", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "[{\"framework\":\"ARM\",\"definition\":\"string\"}]", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/rules/validate"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

```
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
[{\"framework\":\"ARM\",\"definition\":\"string\"}]"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/rules/validate"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "[{\"framework\":\"ARM\",\"definition\":\"string\"}]",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
array[ValidateCustomRuleRequestParams]
required
application/json
[
▶ frameworkstring (Enum)required

Name of the configured frameworks.

▶ definitionstringrequired
]
REQUEST

```
[ { "framework": "ARM", "definition": "example" } ]
```

Responses

Ok

Body
application/json
Any of a
▶ frameworksErrorsarray
▶ isValidboolean
RESPONSE

```
{ "frameworksErrors": [ { "framework": "ARM", "errors": [ "example" ] } ], "isValid": false }
```

2.4.6 | Repositories

APIs for managing repository assets

2.4.6.1 | Get repositories

get /public_api/appsec/v1/repositories

Get details on all repositories integrated with Cortex Cloud Application Security, providing detailed information and insights into repository artifacts, configurations, and dependencies.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ source array[IntegrationType]
▼ search String
Example: `search_example`
▼ offset BigDecimal
Example: `8.14`
▼ limit BigDecimal
Example: `8.14`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
```

```
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories?source=&search=search_example&offset=8.14&limit=8.14'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE", headers=headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories?
source=SOME_ARRAY_VALUE&search=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ namestring

The name of the repository in the version control system (VCS)

▶ descriptionstring

Description describing the repository

▶ creationDatestring
▶ defaultBranchstring
▶ diskSizenumberdouble
▶ externalIdstring
▶ idstring

Repository ID

▶ integrationIdstring
▶ isArchivedboolean

Whether the repository is archived

▶ isBillableboolean

Whether the repository is billable

▶ isForkedboolean

Whether the repository is forked

▶ isPublicboolean

Whether the repository is public

▶ isSelectedboolean

Whether the repository is selected

▶ lastScanDatestring
▶ observationTimenumberdouble

The date the repository was last updated

▶ organizationIdstring
▶ ownerstring

Repository owner

▶ projectIdstring
▶ scanConfigurationobject

The configuration of an Application Security code scanner

▶ scannedBranchstring
▶ scannedBranchesarray
▶ sourcestring (Enum)

Type of the data source instance, indicating the external system it connects to.

▶ statusobject
▶ urlstring

URL of the repository

]
RESPONSE


```
[ { "name": "example", "description": "example", "creationDate": "example", "defaultBranch": "example", "diskSize":
0.1, "externalId": "example", "id": "example", "integrationId": "example", "isArchived": false, "isBillable": false,
"isForked": false, "isPublic": false, "isSelected": false, "lastScanDate": "example", "observationTime": 0.1,
"organizationId": "example", "owner": "example", "projectId": "example", "scanConfiguration": { "excludedPaths": [
"example" ], "prScanning": { "blockOnError": false, "isEnabled": false }, "scanners": { "GIT_HISTORY": { "isEnabled":
false, "scanOptions": { "additionalProperties": false } }, "IAC": { "isEnabled": false, "scanOptions": {
"additionalProperties": false } }, "SCA": { "isEnabled": false, "scanOptions": { "additionalProperties": false } },
"SECRETS": { "isEnabled": false, "scanOptions": { "additionalProperties": false } } }, "taggingBot": {
"tagModuleBlocks": false, "tagResourceBlocks": false } }, "scannedBranch": "example", "scannedBranches": [ {
"diskSize": 0.1, "firstScanDate": "example", "id": "example", "isPrimary": false, "lastApiCallDate": "example",
"lastCloneDate": "example", "lastCloneSha": "example", "lastScanDate": "example", "name": "example", "repositoryId":
"example" } ], "source": "AWS_CODE_BUILD", "status": { "apiRead": { "reason": "example", "status": "INVALID" },
"apiWrite": { "reason": "example", "status": "INVALID" }, "clone": { "reason": "example", "status": "INVALID" },
"connection": { "reason": "example", "status": "INVALID" }, "webhookSubscription": { "reason": "example", "status":
"INVALID" }, "token": { "reason": "example", "status": "INVALID" } }, "url": "example" } ]
```

2.4.6.2 | Get a repository

get /public_api/appsec/v1/repositories/{assetId}

Get details on the Application Security repository specified by its asset ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ assetId String required

Asset ID

Example: `assetId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories/{assetId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/repositories/%7BassetId%7D", headers=headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ namestring

The name of the repository in the version control system (VCS)

▼ descriptionstring

Description describing the repository

▼ creationDatestring
▼ defaultBranchstring
▼ diskSizenumberdouble
▼ externalIdstring
▼ idstring

Repository ID

▼ integrationIdstring
▼ isArchivedboolean

Whether the repository is archived

▼ isBillableboolean

Whether the repository is billable

▼ isForkedboolean

Whether the repository is forked

▼ isPublicboolean

Whether the repository is public

▼ isSelectedboolean

Whether the repository is selected

▼ lastScanDatestring
▼ observationTimenumberdouble

The date the repository was last updated

▼ organizationIdstring
▼ ownerstring

Repository owner

▼ projectIdstring
▼ scanConfigurationobject

The configuration of an Application Security code scanner

▶ excludedPathsarray[string]
▶ prScanningobject

Pull Request (PR) scans are initiated by events triggered by version control systems such as GitHub, GitLab, Bitbucket and Azure Repos, or via webhooks. The scan results are based on default enforcement thresholds.

▶ scannersobject

Details on each type of scanner: Branch periodic scans, CI scans, IaC scans, Secrets scans

▶ taggingBotobject
▼ scannedBranchstring
▼ scannedBranchesarray
[
▶ diskSizenumberdouble
▶ firstScanDatestring

Timestamp of the first scan performed

▶ idstring

Branch ID

▶ isPrimaryboolean

Indicates whether or not the branch is the primary branch

▶ lastApiCallDatestring
▶ lastCloneDatestring
▶ lastCloneShastring
▶ lastScanDatestring

Timestamp of the last scan execution

▶ namestring

Branch name

▶ repositoryIdstring

Repository ID

]
▼ sourcestring (Enum)

Type of the data source instance, indicating the external system it connects to.

Allowed values:"AWS_CODE_BUILD""AWS_CODE_COMMIT""AZURE_REPOS""BITBUCKET""BITBUCKET_DATACENTER""CIRCLE_CI""CIRCLE_CI_CD""COLLECTOR""CORTEX_CLI""
▼ statusobject
▶ apiReadobject
▶ apiWriteobject
▶ cloneobject
▶ connectionobject
▶ webhookSubscriptionobject
▶ tokenobject
▶ Additional propertiesobject
▼ urlstring

URL of the repository
RESPONSE


```
{ "name": "example", "description": "example", "creationDate": "example", "defaultBranch": "example", "diskSize": 0.1,
"externalId": "example", "id": "example", "integrationId": "example", "isArchived": false, "isBillable": false,
"isForked": false, "isPublic": false, "isSelected": false, "lastScanDate": "example", "observationTime": 0.1,
"organizationId": "example", "owner": "example", "projectId": "example", "scanConfiguration": { "excludedPaths": [
"example" ], "prScanning": { "blockOnError": false, "isEnabled": false }, "scanners": { "GIT_HISTORY": { "isEnabled":
false, "scanOptions": { "additionalProperties": false } }, "IAC": { "isEnabled": false, "scanOptions": {
"additionalProperties": false } }, "SCA": { "isEnabled": false, "scanOptions": { "additionalProperties": false } },
"SECRETS": { "isEnabled": false, "scanOptions": { "additionalProperties": false } } }, "taggingBot": {
"tagModuleBlocks": false, "tagResourceBlocks": false } }, "scannedBranch": "example", "scannedBranches": [ {
"diskSize": 0.1, "firstScanDate": "example", "id": "example", "isPrimary": false, "lastApiCallDate": "example",
"lastCloneDate": "example", "lastCloneSha": "example", "lastScanDate": "example", "name": "example", "repositoryId":
"example" } ], "source": "AWS_CODE_BUILD", "status": { "apiRead": { "reason": "example", "status": "INVALID" },
"apiWrite": { "reason": "example", "status": "INVALID" }, "clone": { "reason": "example", "status": "INVALID" },
"connection": { "reason": "example", "status": "INVALID" }, "webhookSubscription": { "reason": "example", "status":
"INVALID" }, "token": { "reason": "example", "status": "INVALID" } }, "url": "example" }
```

2.4.6.3 | Get a repository scan configuration

get /public_api/appsec/v1/repositories/{assetId}/scan-configuration

Get the details of an Application Security scan configuration.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management
Path parameters
▼ assetId String required
Example: `assetId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories/{assetId}/scan-configuration'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-
configuration"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
```

"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
Responses

Ok

Body
application/json

The configuration of an Application Security code scanner

▼ excludedPathsarray[string]
▼ prScanningobject

Pull Request (PR) scans are initiated by events triggered by version control systems such as GitHub, GitLab, Bitbucket and Azure Repos, or via webhooks. The scan results are based on default enforcement thresholds.

▶ blockOnErrorbooleanrequired
▶ isEnabledbooleanrequired

Indicates whether the PR scan is enabled

▼ scannersobject

Details on each type of scanner: Branch periodic scans, CI scans, IaC scans, Secrets scans

▶ GIT_HISTORYobject

Scanner configuration

▶ IACobject

Scanner configuration

▶ SCAobject

Scanner configuration

▶ SECRETSobject

Scanner configuration

▼ taggingBotobject
▶ tagModuleBlocksbooleanrequired
▶ tagResourceBlocksbooleanrequired
RESPONSE
{ "excludedPaths": ["example"], "prScanning": { "blockOnError": false, "isEnabled": false }, "scanners": {
"GIT_HISTORY": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }, "IAC": { "isEnabled": false,
"scanOptions": { "additionalProperties": false } }, "SCA": { "isEnabled": false, "scanOptions": {
"additionalProperties": false } }, "SECRETS": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }
}, "taggingBot": { "tagModuleBlocks": false, "tagResourceBlocks": false } }

2.4.6.4 | Update a repository scan configuration

put /public_api/appsec/v1/repositories/{assetId}/scan-configuration

Update the configuration of an Application Security scan.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ assetId String required
Example: `assetId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories/{assetId}/scan-configuration'
-d '{ "scanners" : { "SCA" : { "owner" : "owner", "scannedBranches" : [ { "diskSize" : 1.4658129805029452,
"lastApiCallDate" : "lastApiCallDate", "firstScanDate" : "firstScanDate", "lastCloneSha" : "lastCloneSha", "isPrimary"
: true, "name" : "name", "repositoryId" : "repositoryId", "lastScanDate" : "lastScanDate", "id" : "id",
"lastCloneDate" : "lastCloneDate" }, { "diskSize" : 1.4658129805029452, "lastApiCallDate" : "lastApiCallDate",
"firstScanDate" : "firstScanDate", "lastCloneSha" : "lastCloneSha", "isPrimary" : true, "name" : "name",
"repositoryId" : "repositoryId", "lastScanDate" : "lastScanDate", "id" : "id", "lastCloneDate" : "lastCloneDate" } ],
"scanConfiguration" : { "scanners" : { "SCA" : { "scanOptions" : { "key" : true }, "isEnabled" : true }, "GIT_HISTORY"
: { "scanOptions" : { "key" : true }, "isEnabled" : true }, "SECRETS" : { "scanOptions" : { "key" : true },
"isEnabled" : true }, "IAC" : { "scanOptions" : { "key" : true }, "isEnabled" : true } }, "taggingBot" : {
"tagModuleBlocks" : true, "tagResourceBlocks" : true }, "excludedPaths" : [ "excludedPaths", "excludedPaths" ],
"prScanning" : { "blockOnError" : true, "isEnabled" : true } }, "isArchived" : true, "defaultBranch" :
"defaultBranch", "isForked" : true, "description" : "description", "externalId" : "externalId", "integrationId" :
"integrationId", "observationTime" : 6.027456183070403, "creationDate" : "creationDate", "url" : "url", "isBillable" :
true, "organizationId" : "organizationId", "diskSize" : 0.8008281904610115, "scannedBranch" : "scannedBranch", "name"
: "name", "isSelected" : true, "isPublic" : true, "lastScanDate" : "lastScanDate", "id" : "id", "projectId" :
"projectId", "status" : { "clone" : { "reason" : "reason" }, "apiRead" : { "reason" : "reason" },
"webhookSubscription" : { "reason" : "reason" }, "connection" : { "reason" : "reason" }, "apiWrite" : { "reason" :
"reason" }, "token" : { "reason" : "reason" } } }, "SECRETS" : { "scanOptions" : { "gitHistory" : true,
"secretValidation" : true }, "isEnabled" : true }, "IAC" : { "owner" : "owner", "scannedBranches" : [ { "diskSize" :
1.4658129805029452, "lastApiCallDate" : "lastApiCallDate", "firstScanDate" : "firstScanDate", "lastCloneSha" :
"lastCloneSha", "isPrimary" : true, "name" : "name", "repositoryId" : "repositoryId", "lastScanDate" : "lastScanDate",
"id" : "id", "lastCloneDate" : "lastCloneDate" }, { "diskSize" : 1.4658129805029452, "lastApiCallDate" :
"lastApiCallDate", "firstScanDate" : "firstScanDate", "lastCloneSha" : "lastCloneSha", "isPrimary" : true, "name" :
"name", "repositoryId" : "repositoryId", "lastScanDate" : "lastScanDate", "id" : "id", "lastCloneDate" :
"lastCloneDate" } ], "scanConfiguration" : { "scanners" : { "SCA" : { "scanOptions" : { "key" : true }, "isEnabled" :
true }, "GIT_HISTORY" : { "scanOptions" : { "key" : true }, "isEnabled" : true }, "SECRETS" : { "scanOptions" : {
"key" : true }, "isEnabled" : true }, "IAC" : { "scanOptions" : { "key" : true }, "isEnabled" : true } }, "taggingBot"
: { "tagModuleBlocks" : true, "tagResourceBlocks" : true }, "excludedPaths" : [ "excludedPaths", "excludedPaths" ],
"prScanning" : { "blockOnError" : true, "isEnabled" : true } }, "isArchived" : true, "defaultBranch" :
"defaultBranch", "isForked" : true, "description" : "description", "externalId" : "externalId", "integrationId" :
"integrationId", "observationTime" : 6.027456183070403, "creationDate" : "creationDate", "url" : "url", "isBillable" :
true, "organizationId" : "organizationId", "diskSize" : 0.8008281904610115, "scannedBranch" : "scannedBranch", "name"
: "name", "isSelected" : true, "isPublic" : true, "lastScanDate" : "lastScanDate", "id" : "id", "projectId" :
"projectId", "status" : { "clone" : { "reason" : "reason" }, "apiRead" : { "reason" : "reason" },
"webhookSubscription" : { "reason" : "reason" }, "connection" : { "reason" : "reason" }, "apiWrite" : { "reason" :
"reason" }, "token" : { "reason" : "reason" } } } }, "taggingBot" : { "tagModuleBlocks" : true, "tagResourceBlocks" :
true }, "excludedPaths" : [ "excludedPaths", "excludedPaths" ], "prScanning" : { "blockOnError" : true, "isEnabled" :
true } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"excludedPaths\":
[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
```

```
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("PUT",
"/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration", payload, headers) res = conn.getresponse() data
= res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"excludedPaths\":
[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "excludedPaths": [ "string" ], "prScanning": { "blockOnError": true, "isEnabled": true
}, "taggingBot": { "tagModuleBlocks": true, "tagResourceBlocks": true }, "scanners": { "SECRETS": { "isEnabled": true,
"scanOptions": { "gitHistory": true, "secretValidation": true } }, "SCA": { "name": "string", "description": "string",
"status": { "apiRead": { "reason": "string", "status": "INVALID" }, "apiWrite": { "reason": "string", "status":
"INVALID" }, "clone": { "reason": "string", "status": "INVALID" }, "connection": { "reason": "string", "status":
"INVALID" }, "webhookSubscription": { "reason": "string", "status": "INVALID" }, "token": { "reason": "string",
"status": "INVALID" }, "property1": { "reason": "string", "status": "INVALID" }, "property2": { "reason": "string",
"status": "INVALID" } }, "creationDate": "string", "defaultBranch": "string", "diskSize": 0.1, "externalId": "string",
"id": "string", "integrationId": "string", "isArchived": true, "isBillable": true, "isForked": true, "isPublic": true,
"isSelected": true, "lastScanDate": "string", "observationTime": 0.1, "organizationId": "string", "owner": "string",
"projectId": "string", "scanConfiguration": { "excludedPaths": [ "string" ], "prScanning": { "blockOnError": true,
```

```
"isEnabled": true }, "scanners": { "GIT_HISTORY": { "isEnabled": true, "scanOptions": { "property1": true,
"property2": true } }, "IAC": { "isEnabled": true, "scanOptions": { "property1": true, "property2": true } }, "SCA": {
"isEnabled": true, "scanOptions": { "property1": true, "property2": true } }, "SECRETS": { "isEnabled": true,
"scanOptions": { "property1": true, "property2": true } } }, "taggingBot": { "tagModuleBlocks": true,
"tagResourceBlocks": true } }, "scannedBranch": "string", "scannedBranches": [ { "diskSize": 0.1, "firstScanDate":
"string", "id": "string", "isPrimary": true, "lastApiCallDate": "string", "lastCloneDate": "string", "lastCloneSha":
"string", "lastScanDate": "string", "name": "string", "repositoryId": "string" } ], "source": "AWS_CODE_BUILD", "url":
"string" }, "IAC": { "name": "string", "description": "string", "status": { "apiRead": { "reason": "string", "status":
"INVALID" }, "apiWrite": { "reason": "string", "status": "INVALID" }, "clone": { "reason": "string", "status":
"INVALID" }, "connection": { "reason": "string", "status": "INVALID" }, "webhookSubscription": { "reason": "string",
"status": "INVALID" }, "token": { "reason": "string", "status": "INVALID" }, "property1": { "reason": "string",
"status": "INVALID" }, "property2": { "reason": "string", "status": "INVALID" } }, "creationDate": "string",
"defaultBranch": "string", "diskSize": 0.1, "externalId": "string", "id": "string", "integrationId": "string",
"isArchived": true, "isBillable": true, "isForked": true, "isPublic": true, "isSelected": true, "lastScanDate":
"string", "observationTime": 0.1, "organizationId": "string", "owner": "string", "projectId": "string",
"scanConfiguration": { "excludedPaths": [ "string" ], "prScanning": { "blockOnError": true, "isEnabled": true },
"scanners": { "GIT_HISTORY": { "isEnabled": true, "scanOptions": { "property1": true, "property2": true } }, "IAC": {
"isEnabled": true, "scanOptions": { "property1": true, "property2": true } }, "SCA": { "isEnabled": true,
"scanOptions": { "property1": true, "property2": true } }, "SECRETS": { "isEnabled": true, "scanOptions": {
"property1": true, "property2": true } } }, "taggingBot": { "tagModuleBlocks": true, "tagResourceBlocks": true } },
"scannedBranch": "string", "scannedBranches": [ { "diskSize": 0.1, "firstScanDate": "string", "id": "string",
"isPrimary": true, "lastApiCallDate": "string", "lastCloneDate": "string", "lastCloneSha": "string", "lastScanDate":
"string", "name": "string", "repositoryId": "string" } ], "source": "AWS_CODE_BUILD", "url": "string" } } }); const
xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("PUT", "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"excludedPaths\":
[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
.asString();
```

```
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "excludedPaths": ["string"],
"prScanning": [ "blockOnError": true, "isEnabled": true ], "taggingBot": [ "tagModuleBlocks": true,
"tagResourceBlocks": true ], "scanners": [ "SECRETS": [ "isEnabled": true, "scanOptions": [ "gitHistory": true,
"secretValidation": true ] ], "SCA": [ "name": "string", "description": "string", "status": [ "apiRead": [ "reason":
"string", "status": "INVALID" ], "apiWrite": [ "reason": "string", "status": "INVALID" ], "clone": [ "reason":
"string", "status": "INVALID" ], "connection": [ "reason": "string", "status": "INVALID" ], "webhookSubscription": [
"reason": "string", "status": "INVALID" ], "token": [ "reason": "string", "status": "INVALID" ], "property1": [
"reason": "string", "status": "INVALID" ], "property2": [ "reason": "string", "status": "INVALID" ] ], "creationDate":
"string", "defaultBranch": "string", "diskSize": 0.1, "externalId": "string", "id": "string", "integrationId":
"string", "isArchived": true, "isBillable": true, "isForked": true, "isPublic": true, "isSelected": true,
"lastScanDate": "string", "observationTime": 0.1, "organizationId": "string", "owner": "string", "projectId":
"string", "scanConfiguration": [ "excludedPaths": ["string"], "prScanning": [ "blockOnError": true, "isEnabled": true
], "scanners": [ "GIT_HISTORY": [ "isEnabled": true, "scanOptions": [ "property1": true, "property2": true ] ], "IAC":
[ "isEnabled": true, "scanOptions": [ "property1": true, "property2": true ] ], "SCA": [ "isEnabled": true,
"scanOptions": [ "property1": true, "property2": true ] ], "SECRETS": [ "isEnabled": true, "scanOptions": [
"property1": true, "property2": true ] ] ], "taggingBot": [ "tagModuleBlocks": true, "tagResourceBlocks": true ] ],
"scannedBranch": "string", "scannedBranches": [ [ "diskSize": 0.1, "firstScanDate": "string", "id": "string",
"isPrimary": true, "lastApiCallDate": "string", "lastCloneDate": "string", "lastCloneSha": "string", "lastScanDate":
"string", "name": "string", "repositoryId": "string" ] ], "source": "AWS_CODE_BUILD", "url": "string" ], "IAC": [
"name": "string", "description": "string", "status": [ "apiRead": [ "reason": "string", "status": "INVALID" ],
"apiWrite": [ "reason": "string", "status": "INVALID" ], "clone": [ "reason": "string", "status": "INVALID" ],
"connection": [ "reason": "string", "status": "INVALID" ], "webhookSubscription": [ "reason": "string", "status":
"INVALID" ], "token": [ "reason": "string", "status": "INVALID" ], "property1": [ "reason": "string", "status":
"INVALID" ], "property2": [ "reason": "string", "status": "INVALID" ] ], "creationDate": "string", "defaultBranch":
"string", "diskSize": 0.1, "externalId": "string", "id": "string", "integrationId": "string", "isArchived": true,
"isBillable": true, "isForked": true, "isPublic": true, "isSelected": true, "lastScanDate": "string",
"observationTime": 0.1, "organizationId": "string", "owner": "string", "projectId": "string", "scanConfiguration": [
"excludedPaths": ["string"], "prScanning": [ "blockOnError": true, "isEnabled": true ], "scanners": [ "GIT_HISTORY": [
"isEnabled": true, "scanOptions": [ "property1": true, "property2": true ] ], "IAC": [ "isEnabled": true,
"scanOptions": [ "property1": true, "property2": true ] ], "SCA": [ "isEnabled": true, "scanOptions": [ "property1":
true, "property2": true ] ], "SECRETS": [ "isEnabled": true, "scanOptions": [ "property1": true, "property2": true ] ]
], "taggingBot": [ "tagModuleBlocks": true, "tagResourceBlocks": true ] ], "scannedBranch": "string",
"scannedBranches": [ [ "diskSize": 0.1, "firstScanDate": "string", "id": "string", "isPrimary": true,
"lastApiCallDate": "string", "lastCloneDate": "string", "lastCloneSha": "string", "lastScanDate": "string", "name":
"string", "repositoryId": "string" ] ], "source": "AWS_CODE_BUILD", "url": "string" ] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "{\"excludedPaths\":[\"string\"],\"prScanning\":
{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
```

{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
CURLOPT_HTTPHEADER => ["Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241"],]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-configuration"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/scan-
configuration"); var request = new RestRequest(Method.PUT); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"excludedPaths\":[\"string\"],\"prScanning\":
{\"blockOnError\":true,\"isEnabled\":true},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true},\"scanners\":{\"SECRETS\":{\"isEnabled\":true,\"scanOptions\":
{\"gitHistory\":true,\"secretValidation\":true}},\"SCA\":{\"name\":\"string\",\"description\":\"string\",\"status\":
{\"apiRead\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":

{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
{\"name\":\"string\",\"description\":\"string\",\"status\":{\"apiRead\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"apiWrite\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"clone\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"connection\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"webhookSubscription\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"token\":{\"reason\":\"string\",\"status\":\"INVALID\"},\"property1\":
{\"reason\":\"string\",\"status\":\"INVALID\"},\"property2\":
{\"reason\":\"string\",\"status\":\"INVALID\"}},\"creationDate\":\"string\",\"defaultBranch\":\"string\",\"diskSize\":0.1,\"ext
{\"excludedPaths\":[\"string\"],\"prScanning\":{\"blockOnError\":true,\"isEnabled\":true},\"scanners\":
{\"GIT_HISTORY\":{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"IAC\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SCA\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}},\"SECRETS\":
{\"isEnabled\":true,\"scanOptions\":{\"property1\":true,\"property2\":true}}},\"taggingBot\":
{\"tagModuleBlocks\":true,\"tagResourceBlocks\":true}},\"scannedBranch\":\"string\",\"scannedBranches\":
[{\"diskSize\":0.1,\"firstScanDate\":\"string\",\"id\":\"string\",\"isPrimary\":true,\"lastApiCallDate\":\"string\",\"lastClone
```
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

▼ excludedPathsarray[string]
▼ prScanningobject

Pull Request (PR) scans are initiated by events triggered by version control systems such as GitHub, GitLab, Bitbucket and Azure Repos, or via webhooks. The scan results are based on default enforcement thresholds.

▶ blockOnErrorbooleanrequired
▶ isEnabledbooleanrequired

Indicates whether the PR scan is enabled

▼ taggingBotobject
▶ tagModuleBlocksbooleanrequired
▶ tagResourceBlocksbooleanrequired
▼ scannersobject
▶ SECRETSobject
▶ SCAobject

From T, pick a set of properties whose keys are in the union K

▶ IACobject

From T, pick a set of properties whose keys are in the union K

REQUEST

{ "excludedPaths": ["example"], "prScanning": { "blockOnError": false, "isEnabled": false }, "taggingBot": {
"tagModuleBlocks": false, "tagResourceBlocks": false }, "scanners": { "SECRETS": { "isEnabled": false, "scanOptions":
{ "gitHistory": false, "secretValidation": false } }, "SCA": { "name": "example", "description": "example", "status":
{ "apiRead": { "reason": "example", "status": "INVALID" }, "apiWrite": { "reason": "example", "status": "INVALID" },
"clone": { "reason": "example", "status": "INVALID" }, "connection": { "reason": "example", "status": "INVALID" },
"webhookSubscription": { "reason": "example", "status": "INVALID" }, "token": { "reason": "example", "status":
"INVALID" } }, "creationDate": "example", "defaultBranch": "example", "diskSize": 0.1, "externalId": "example", "id":
"example", "integrationId": "example", "isArchived": false, "isBillable": false, "isForked": false, "isPublic": false,
"isSelected": false, "lastScanDate": "example", "observationTime": 0.1, "organizationId": "example", "owner":
"example", "projectId": "example", "scanConfiguration": { "excludedPaths": ["example"], "prScanning": {
"blockOnError": false, "isEnabled": false }, "scanners": { "GIT_HISTORY": { "isEnabled": false, "scanOptions": {
"additionalProperties": false } }, "IAC": { "isEnabled": false, "scanOptions": { "additionalProperties": false } },
"SCA": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }, "SECRETS": { "isEnabled": false,
"scanOptions": { "additionalProperties": false } } }, "taggingBot": { "tagModuleBlocks": false, "tagResourceBlocks":

false } }, "scannedBranch": "example", "scannedBranches": [{ "diskSize": 0.1, "firstScanDate": "example", "id": "example", "isPrimary": false, "lastApiCallDate": "example", "lastCloneDate": "example", "lastCloneSha": "example", "lastScanDate": "example", "name": "example", "repositoryId": "example" }], "source": "AWS_CODE_BUILD", "url": "example" }, "IAC": { "name": "example", "description": "example", "status": { "apiRead": { "reason": "example", "status": "INVALID" }, "apiWrite": { "reason": "example", "status": "INVALID" }, "clone": { "reason": "example", "status": "INVALID" }, "connection": { "reason": "example", "status": "INVALID" }, "webhookSubscription": { "reason": "example", "status": "INVALID" }, "token": { "reason": "example", "status": "INVALID" } }, "creationDate": "example", "defaultBranch": "example", "diskSize": 0.1, "externalId": "example", "id": "example", "integrationId": "example", "isArchived": false, "isBillable": false, "isForked": false, "isPublic": false, "isSelected": false, "lastScanDate": "example", "observationTime": 0.1, "organizationId": "example", "owner": "example", "projectId": "example", "scanConfiguration": { "excludedPaths": ["example"], "prScanning": { "blockOnError": false, "isEnabled": false }, "scanners": { "GIT_HISTORY": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }, "IAC": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }, "SCA": { "isEnabled": false, "scanOptions": { "additionalProperties": false } }, "SECRETS": { "isEnabled": false, "scanOptions": { "additionalProperties": false } } }, "taggingBot": { "tagModuleBlocks": false, "tagResourceBlocks": false } }, "scannedBranch": "example", "scannedBranches": [{ "diskSize": 0.1, "firstScanDate": "example", "id": "example", "isPrimary": false, "lastApiCallDate": "example", "lastCloneDate": "example", "lastCloneSha": "example", "lastScanDate": "example", "name": "example", "repositoryId": "example" }], "source": "AWS_CODE_BUILD", "url": "example" } } }

Responses

No content

2.4.6.5 | Get AppSec repository branches

get /public_api/appsec/v1/repositories/{assetId}/branches

Get the details of the Application Security repository branches.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters

▼ assetId String required

Example: `assetId_example`

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories/{assetId}/branches'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/repositories/%7BassetId%7D/branches",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); xhr.setRequestHeader("Authorization",
```

```
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); var
request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ diskSizenumberdouble
▶ firstScanDatestring

Timestamp of the first scan performed

▶ idstring

Branch ID

▶ isPrimaryboolean

Indicates whether or not the branch is the primary branch

▶ lastApiCallDatestring
▶ lastCloneDatestring
▶ lastCloneShastring
▶ lastScanDatestring

Timestamp of the last scan execution

▶ namestring

Branch name

▶ repositoryIdstring

Repository ID

]
RESPONSE

```
[ { "diskSize": 0.1, "firstScanDate": "example", "id": "example", "isPrimary": false, "lastApiCallDate": "example",
"lastCloneDate": "example", "lastCloneSha": "example", "lastScanDate": "example", "name": "example", "repositoryId":
"example" } ]
```

2.4.6.6 | Update an AppSec repository branch

put /public_api/appsec/v1/repositories/{assetId}/branches

Update the Application Security repository branch by indicating the primary branch.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ assetId String required
Example: `assetId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/repositories/{assetId}/branches'
-d '{ "selectedBranches" : [ "selectedBranches", "selectedBranches" ], "primaryBranch" : "primaryBranch" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"selectedBranches\":
[\"string\"],\"primaryBranch\":\"string\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("PUT",
"/public_api/appsec/v1/repositories/%7BassetId%7D/branches", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"selectedBranches\":
[\"string\"],\"primaryBranch\":\"string\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "selectedBranches": [ "string" ], "primaryBranch": "string" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("PUT", "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"selectedBranches\":
[\"string\"],\"primaryBranch\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "selectedBranches": ["string"],
"primaryBranch": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers request.httpBody = postData as
Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: {
(data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
```

```
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "{\"selectedBranches\":
[\"string\"],\"primaryBranch\":\"string\"}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"selectedBranches\":[\"string\"],\"primaryBranch\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/repositories/%7BassetId%7D/branches"); var
request = new RestRequest(Method.PUT); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"selectedBranches\":[\"string\"],\"primaryBranch\":\"string\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ selectedBranchesarray[string]required

▼ primaryBranchstringrequired

REQUEST

```
{ "selectedBranches": [ "example" ], "primaryBranch": "example" }
```

Responses

No content

2.4.7 | Data Sources

APIs for managing integrations

2.4.7.1 | Get all Data Sources

get /public_api/appsec/v1/data_source_instances

Retrieve a list of all data source instances configured in your Cortex environment. You can filter the results by data source type and category.

> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example: `your_api_key_here`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`

Query parameters

▼ type UrlIntegrationType

Type of data source instance to retrieve.

▼ type_category UrlIntegrationTypeCategory

Category of data source instances to retrieve.

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/data_source_instances?type=&type_category='
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("GET", "/public_api/appsec/v1/data_source_instances?
```

```
type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances?type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' response =
http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances?type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE");
xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/data_source_instances?
type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE") .header("Authorization", "your_api_key_here") .header("x-xdr-
auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/data_source_instances?
type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances?type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
your_api_key_here", "x-xdr-auth-id: 1" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/data_source_instances?
type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-auth-id:
1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/data_source_instances?
type=SOME_STRING_VALUE&type_category=SOME_STRING_VALUE"); var request = new RestRequest(Method.GET);
request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-id", "1"); IRestResponse
response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ creationDatestring

Date and time when the data source instance was created.

▶ domainobject

Domain configuration specifying the hostname and protocol for the data source instance

▶ idstring

Unique identifier (ID) of the data source instance.

▶ instanceVersionstring

Version of the data source instance configuration.

▶ lastUpdateDatestring

Date and time when the data source instance was last updated.

▶ scanTypesobject
▶ selectionTypestring (Enum)

Defines how repositories are selected for scanning within a data source instance.

▶ selfSignedCertificatestring

PEM-encoded self-signed certificate used for secure communication with the data source.

▶ statearray[string]

Integration state

▶ statusstring (Enum)

Current connection status of the data source instance.

- `COMPLETED` â€ The data source instance setup is complete and operational.
- `CONNECTED` â€ The data source instance is actively connected.
- `DESTROYING` â€ The data source instance is being removed.
- `DISABLED` â€ The data source instance is disabled and not actively scanning.
- `ERROR` â€ The data source instance encountered an error and requires attention.
- `PENDING` â€ The data source instance is being set up and is not yet active.
- `TEMPORARY` â€ The data source instance is in a temporary state during configuration.
- `TRANSPORTER_CONNECTION_DISABLED` â€ The transporter connection for this data source instance is disabled.
- `WARNING` â€ The data source instance is operational but has warnings that may require attention.

▶ statusDetailsobject

▶ tenantIdstring

Tenant ID that owns this data source instance.

▶ transporterobject

Transporter configuration for establishing secure communication between an on-premises or private data source and Cortex.

▶ typestring (Enum)

Type of the data source instance, indicating the external system it connects to.

▶ typeCategorystring (Enum)

Category classification of the data source instance type.

- `DEFAULT` â€ Standard data source instances such as VCS, CI/CD, and CLI integrations.
- `EXTERNAL_VENDOR_INTEGRATIONS` â€ Third-party external vendor integrations (for example, Snyk, Veracode, Semgrep, JFrog).

▶ uniqueIdentifierstring

Unique identifier of the integration

▶ repositoriesCountnumberrequireddouble

Total number of repositories associated with this data source instance.

]

RESPONSE

Example 1


```
[ { "creationDate": "2025-06-15T09:30:00.000Z", "domain": { "hostname": "github.example.com", "protocol": "https" },
"id": "a1b2c3d4e5f6a7b8c9d0e1f2", "instanceVersion": "1.0.0", "lastUpdateDate": "2025-07-20T14:15:30.000Z",
"scanTypes": { "SAST": { "isEnabled": true }, "SCA": { "isEnabled": false } }, "selectionType": "MANUAL_SELECTION",
"selfSignedCertificate": "-----BEGIN CERTIFICATE-----\nMIIBxTCCAWugAwIBAgIJAL...\n-----END CERTIFICATE-----", "state":
[ "example-org/repo-alpha", "example-org/repo-beta" ], "status": "CONNECTED", "statusDetails": { "connection": {
"status": "VALID", "message": "Connection established successfully", "timestamp": "2025-07-20T14:15:30.000Z" } },
"tenantId": "tenant-001", "transporter": { "brokerDeviceId": "broker-device-abc123", "connectionName": "on-prem-
github-connection" }, "type": "GITHUB_ENTERPRISE", "typeCategory": "DEFAULT", "uniqueIdentifier": "example-org",
"repositoriesCount": 12 }, { "creationDate": "2025-08-01T11:00:00.000Z", "domain": { "hostname": "api.example-
vendor.io", "protocol": "https" }, "id": "b2c3d4e5f6a7b8c9d0e1f2a3", "lastUpdateDate": "2025-08-10T16:45:00.000Z",
"scanTypes": { "SAST": { "isEnabled": true }, "SCA": { "isEnabled": true } }, "selectionType":
"CURRENT_STATE_AND_FUTURE", "status": "CONNECTED", "type": "SNYK", "typeCategory": "EXTERNAL_VENDOR_INTEGRATIONS",
"uniqueIdentifier": "snyk-default-org", "repositoriesCount": 5 }, { "creationDate": "2025-09-12T08:20:00.000Z", "id":
"c3d4e5f6a7b8c9d0e1f2a3b4", "lastUpdateDate": "2025-09-12T08:20:00.000Z", "status": "CONNECTED", "type": "COLLECTOR",
"uniqueIdentifier": "my-sast-collector", "repositoriesCount": 0 } ]
```

2.4.7.2 | Create AppSec Data Sources

post /public_api/appsec/v1/data_source_instances

Create a new data source instance to connect an external system to your Cortex environment.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Request headers

▼ Authorization String required

{api_key}

Example: `your_api_key_here`

▼ x-xdr-auth-id String required

{api_key_id}

Example: 1

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/data_source_instances'
-d '{ "selfSignedCertificate" : "selfSignedCertificate", "credentials" : { "password" : "password", "clientId" :
"clientId", "webhookAuthKeyId" : "webhookAuthKeyId", "webhookAuthKey" : "webhookAuthKey", "clientSecret" :
"clientSecret", "token" : "token", "refreshToken" : "refreshToken", "username" : "username" }, "domain" : { "hostname"
: "hostname" }, "transporter" : { "connectionName" : "connectionName", "brokerDeviceId" : "brokerDeviceId" },
"uniqueProperties" : "{}" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"type\":\"AWS_CODE_BUILD\",\"domain\":{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}" headers = {
'Authorization': "your_api_key_here", 'x-xdr-auth-id': "1", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/data_source_instances", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'your_api_key_here' request["x-xdr-auth-id"] = '1' request["content-type"] = 'application/json' request.body = "
{\"type\":\"AWS_CODE_BUILD\",\"domain\":{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "type": "AWS_CODE_BUILD", "domain": { "hostname": "string", "protocol": "http" },
"credentials": { "type": "OAUTH", "token": "string", "refreshToken": "string", "clientId": "string", "clientSecret":
"string", "username": "string", "password": "string", "webhookAuthKeyId": "string", "webhookAuthKey": "string" },
"uniqueProperties": {}, "transporter": { "brokerDeviceId": "string", "connectionName": "string" },
"selfSignedCertificate": "string" }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances"); xhr.setRequestHeader("Authorization", "your_api_key_here");
xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/data_source_instances")
.header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .header("content-type",
"application/json") .body("{\"type\":\"AWS_CODE_BUILD\",\"domain\":
{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1", "content-type":
"application/json" ] let parameters = [ "type": "AWS_CODE_BUILD", "domain": [ "hostname": "string", "protocol": "http"
], "credentials": [ "type": "OAUTH", "token": "string", "refreshToken": "string", "clientId": "string",
"clientSecret": "string", "username": "string", "password": "string", "webhookAuthKeyId": "string", "webhookAuthKey":
"string" ], "uniqueProperties": [], "transporter": [ "brokerDeviceId": "string", "connectionName": "string" ],
"selfSignedCertificate": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
```

```
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"type\":\"AWS_CODE_BUILD\",\"domain\":
{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}",
CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "content-type: application/json", "x-xdr-auth-id: 1" ],
]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/data_source_instances"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-auth-id:
1"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"type\":\"AWS_CODE_BUILD\",\"domain\":
{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/data_source_instances"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-id",
"1"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"type\":\"AWS_CODE_BUILD\",\"domain\":{\"hostname\":\"string\",\"protocol\":\"http\"},\"credentials\":
{\"type\":\"OAUTH\",\"token\":\"string\",\"refreshToken\":\"string\",\"clientId\":\"string\",\"clientSecret\":\"string\",\"user
{},\"transporter\":
{\"brokerDeviceId\":\"string\",\"connectionName\":\"string\"},\"selfSignedCertificate\":\"string\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Define the integration configuration

▼ typestring (Enum)required

Type of the data source instance, indicating the external system it connects to.

Allowed values:"AWS_CODE_BUILD""AWS_CODE_COMMIT""AZURE_REPOS""BITBUCKET""BITBUCKET_DATACENTER""CIRCLE_CI""CIRCLE_CI_CD""COLLECTOR""CORTEX_CLI""

▼ domainobject

Domain configuration specifying the hostname and protocol for the data source instance

▶ hostnamestringrequired

Hostname or domain name of the external data source.

▶ protocolstring (Enum)required

Communication protocol used to connect to the data source.

▼ credentialsobject

Authentication credentials required to connect to the external data source. All properties are optional to support different authentication methods.

▶ typestring (Enum)

Type of authentication method used for the data source connection.

▶ tokenstring

Authentication token, such as a personal access token (PAT), used to authenticate with the data source.

▶ refreshTokenstring

Refresh token used to obtain a new authentication token when the current one expires.

▶ clientIdstring

Client ID for OAuth-based authentication with the data source.

▶ clientSecretstring

Client secret for OAuth-based authentication with the data source.

▶ usernamestring

Username for basic authentication with the data source.

▶ passwordstring

Password for basic authentication with the data source.

▶ webhookAuthKeyIdstring

Webhook authentication key ID used for webhook-based integrations.

▶ webhookAuthKeystring

Authentication key used to validate incoming webhook requests from the data source.

▼ uniquePropertiesobject

A flexible key-value map for specifying additional properties. Keys are strings and values can be of any type.

▼ transporterobject

Transporter configuration for establishing secure communication between an on-premises or private data source and Cortex.

▶ brokerDeviceIdstringrequired

Unique identifier of the broker device used for the transporter connection.

▶ connectionNamestringrequired

Name of the transporter connection.

▼ selfSignedCertificatestring

PEM-encoded self-signed certificate for secure communication.

REQUEST Create a COLLECTOR data source

```
{ "type": "COLLECTOR", "uniqueProperties": { "name": "my-sast-collector", "detectionMethod": "SAST", "fileType": "SARIF" } }
{ "type": "SNYK", "domain": { "hostname": "api.example-vendor.io", "protocol": "https" }, "credentials": { "type": "PAT", "token": "your-personal-access-token" }, "uniqueProperties": { "organizationId": "a1b2c3d4-e5f6-7890-abcd-ef1234567890" }, "selfSignedCertificate": "-----BEGIN CERTIFICATE-----\nMIIBxTCCAWugAwIBAgIJAL...\n-----END CERTIFICATE-----" }
```

Responses

Ok

Body

application/json

Integration details

▼ creationDatestringrequired

Date and time when the data source instance was created.

▼ domainobject

Domain configuration specifying the hostname and protocol for the data source instance

▶ hostnamestringrequired

Hostname or domain name of the external data source.

▶ protocolstring (Enum)required

Communication protocol used to connect to the data source.

▼ idstringrequired

Unique identifier (ID) of the data source instance.

▼ instanceVersionstring

Version of the data source instance configuration.

▼ lastUpdateDatestringrequired

Date and time when the data source instance was last updated.

▼ scanTypesobject
▶ Additional propertiesobject

Configuration for a specific scan type within a data source instance.

▼ selectionTypestring (Enum)

Defines how repositories are selected for scanning within a data source instance.

Allowed values:"CURRENT_STATE""CURRENT_STATE_AND_FUTURE""CURRENT_STATE_PENDING""MANUAL_SELECTION"
▼ selfSignedCertificatestring

PEM-encoded self-signed certificate used for secure communication with the data source.

▼ statearray[string]

Integration state

▼ statusstring (Enum)

Current connection status of the data source instance.

- `COMPLETED` â€ The data source instance setup is complete and operational.
- `CONNECTED` â€ The data source instance is actively connected.
- `DESTROYING` â€ The data source instance is being removed.
- `DISABLED` â€ The data source instance is disabled and not actively scanning.
- `ERROR` â€ The data source instance encountered an error and requires attention.
- `PENDING` â€ The data source instance is being set up and is not yet active.
- `TEMPORARY` â€ The data source instance is in a temporary state during configuration.
- `TRANSPORTER_CONNECTION_DISABLED` â€ The transporter connection for this data source instance is disabled.
- `WARNING` â€ The data source instance is operational but has warnings that may require attention.

Allowed values:"COMPLETED""CONNECTED""DESTROYING""DISABLED""ERROR""PENDING""TEMPORARY""TRANSPORTER_CONNECTION_DISABLED""WARNING"
▼ statusDetailsobject
▶ Additional propertiesobject

Detailed status information for a specific component of the data source instance.

▼ tenantIdstring

Tenant ID that owns this data source instance.

▼ transporterobject

Transporter configuration for establishing secure communication between an on-premises or private data source and Cortex.

▶ brokerDeviceIdstringrequired

Unique identifier of the broker device used for the transporter connection.

▶ connectionNamestringrequired

Name of the transporter connection.

▼ typestring (Enum)required

Type of the data source instance, indicating the external system it connects to.

Allowed values:"AWS_CODE_BUILD""AWS_CODE_COMMIT""AZURE_REPOS""BITBUCKET""BITBUCKET_DATACENTER""CIRCLE_CI""CIRCLE_CI_CD""COLLECTOR""CORTEX_CLI"
▼ typeCategorystring (Enum)

Category classification of the data source instance type.

- `DEFAULT` â€ Standard data source instances such as VCS, CI/CD, and CLI integrations.
- `EXTERNAL_VENDOR_INTEGRATIONS` â€ Third-party external vendor integrations (for example, Snyk, Veracode, Semgrep, JFrog).

Allowed values:"DEFAULT""EXTERNAL_VENDOR_INTEGRATIONS"
▼ uniqueIdentifierstring

Unique identifier of the integration

RESPONSE

COLLECTOR creation response


```
{ "creationDate": "2025-04-02T08:20:58.381Z", "id": "d4e5f6a7b8c9d0e1f2a3b4c5", "status": "CONNECTED", "type": "COLLECTOR", "uniqueIdentifier": "my-sast-collector", "lastUpdateDate": "2025-04-02T08:20:58.381Z", "credentials": { "webhookAuthKey": "your_webhook_auth_key_shown_only_once", "webhookAuthKeyId": 1 }, "detectionMethod": "SAST", "fileType": "SARIF", "apiUrl": "https://api-yourfqdn/public_api/appsec/v1/collectors/d4e5f6a7b8c9d0e1f2a3b4c5" }
```


Validation error.

Body
application/json
▼ errorCodestring

Error code identifying the type of validation failure.

▼ messagestring

Human-readable message describing the validation error.

▼ detailsobject

Detailed validation error information, keyed by field path.

▶ Additional propertiesobject

RESPONSE Missing required type field


```
{ "errorCode": "ValidateError", "message": "Validation Failed", "details": { "body.type": { "message": "'type' is required" } } }
{ "errorCode": "_BadParamsError", "message": "Collector with name \"my-sast-collector\" already exists" }
```

2.4.7.3 | Get an AppSec Data Source

get /public_api/appsec/v1/data_source_instances/{id}

Retrieve the details of a specific data source instance identified by its ID.

> **Required license**:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ id String required

Unique ID of the data source instance to retrieve. You can retrieve this value from the `id` field in the response of List all data source instances - `/public_api/appsec/v1/data_source_instances` or Create a data source instance - `/public_api/appsec/v1/data_source_instances` endpoints.

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/data_source_instances/{id}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization': "your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("GET", "/public_api/appsec/v1/data_source_instances/%7Bid%7D", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1' response = http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); xhr.setRequestHeader("Authorization",
"your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") .header("Authorization", "your_api_key_here")
.header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "x-xdr-auth-id: 1" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-
auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); var request =
new RestRequest(Method.GET); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-
id", "1"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json

Integration details

▼ creationDatestringrequired

Date and time when the data source instance was created.

▼ domainobject

Domain configuration specifying the hostname and protocol for the data source instance

▶ hostnamestringrequired

Hostname or domain name of the external data source.

▶ protocolstring (Enum)required

Communication protocol used to connect to the data source.

▼ idstringrequired

Unique identifier (ID) of the data source instance.

▼ instanceVersionstring

Version of the data source instance configuration.

▼ lastUpdateDatestringrequired

Date and time when the data source instance was last updated.

▼ scanTypesobject
▶ Additional propertiesobject

Configuration for a specific scan type within a data source instance.

▼ selectionTypestring (Enum)

Defines how repositories are selected for scanning within a data source instance.

Allowed values:"CURRENT_STATE""CURRENT_STATE_AND_FUTURE""CURRENT_STATE_PENDING""MANUAL_SELECTION"

▼ selfSignedCertificatestring

PEM-encoded self-signed certificate used for secure communication with the data source.

▼ statearray[string]

Integration state

▼ statusstring (Enum)

Current connection status of the data source instance.

- `COMPLETED` â€ The data source instance setup is complete and operational.
- `CONNECTED` â€ The data source instance is actively connected.
- `DESTROYING` â€ The data source instance is being removed.
- `DISABLED` â€ The data source instance is disabled and not actively scanning.
- `ERROR` â€ The data source instance encountered an error and requires attention.
- `PENDING` â€ The data source instance is being set up and is not yet active.
- `TEMPORARY` â€ The data source instance is in a temporary state during configuration.
- `TRANSPORTER_CONNECTION_DISABLED` â€ The transporter connection for this data source instance is disabled.
- `WARNING` â€ The data source instance is operational but has warnings that may require attention.

Allowed values:"COMPLETED""CONNECTED""DESTROYING""DISABLED""ERROR""PENDING""TEMPORARY""TRANSPORTER_CONNECTION_DISABLED""WARNING"

▼ statusDetailsobject

▶ Additional propertiesobject

Detailed status information for a specific component of the data source instance.

▼ tenantIdstring

Tenant ID that owns this data source instance.

▼ transporterobject

Transporter configuration for establishing secure communication between an on-premises or private data source and Cortex.

▶ brokerDeviceIdstringrequired

Unique identifier of the broker device used for the transporter connection.

▶ connectionNamestringrequired

Name of the transporter connection.

▼ typestring (Enum)required

Type of the data source instance, indicating the external system it connects to.

Allowed values:"AWS_CODE_BUILD""AWS_CODE_COMMIT""AZURE_REPOS""BITBUCKET""BITBUCKET_DATACENTER""CIRCLE_CI""CIRCLE_CI_CD""COLLECTOR""CORTEX_CLI""

▼ typeCategorystring (Enum)

Category classification of the data source instance type.

- `DEFAULT` â€ Standard data source instances such as VCS, CI/CD, and CLI integrations.
- `EXTERNAL_VENDOR_INTEGRATIONS` â€ Third-party external vendor integrations (for example, Snyk, Veracode, Semgrep, JFrog).

Allowed values:"DEFAULT""EXTERNAL_VENDOR_INTEGRATIONS"

▼ uniqueIdentifierstring

Unique identifier of the integration

RESPONSE

Github Enterprise response


```
{ "creationDate": "2025-06-15T09:30:00.000Z", "domain": { "hostname": "github.example.com", "protocol": "https" },
"id": "a1b2c3d4e5f6a7b8c9d0e1f2", "instanceVersion": "1.0.0", "lastUpdateDate": "2025-07-20T14:15:30.000Z",
"scanTypes": { "SAST": { "isEnabled": true }, "SCA": { "isEnabled": false } }, "selectionType": "MANUAL_SELECTION",
"selfSignedCertificate": "-----BEGIN CERTIFICATE-----\nMIIBxTCCAWugAwIBAgIJAL...\n-----END CERTIFICATE-----", "state":
[ "example-org/repo-alpha", "example-org/repo-beta" ], "status": "CONNECTED", "statusDetails": { "connection": {
"status": "VALID", "message": "Connection established successfully", "timestamp": "2025-07-20T14:15:30.000Z" } },
"tenantId": "tenant-001", "transporter": { "brokerDeviceId": "broker-device-abc123", "connectionName": "on-prem-
github-connection" }, "type": "GITHUB_ENTERPRISE", "typeCategory": "DEFAULT", "uniqueIdentifier": "example-org" }
```


Not Found

Body

application/json
▼ errorCodestring

Error code identifying the type of error.

▼ messagestring

Human-readable message describing the error.

RESPONSE
Example 1

```
{ "errorCode": "_NotFoundError", "message": "Integration d4e5f6a7b8c9d0e1f2a3b4c5 not found" }
```

2.4.7.4 | Update an AppSec Data Source

put /public_api/appsec/v1/data_source_instances/{id}

Update the configuration of an existing data source instance.

> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ id String required

Unique ID of the data source instance to update. You can retrieve this value from the `id` field in the response of List all data source instances - `/public_api/appsec/v1/data_source_instances` or Create a data source instance - `/public_api/appsec/v1/data_source_instances` endpoints.

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/data_source_instances/{id}'
-d '{ "externalProjects" : [ { "externalBranchName" : "externalBranchName", "repoId" : "repoId", "externalProjectId" :
"externalProjectId", "branchName" : "branchName", "externalId" : "externalId" }, { "externalBranchName" :
"externalBranchName", "repoId" : "repoId", "externalProjectId" : "externalProjectId", "branchName" : "branchName",
"externalId" : "externalId" } ], "state" : [ "state", "state" ], "uniqueProperties" : "{}" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}" headers = { 'Authorization': "your_api_key_here", 'x-xdr-auth-id': "1", 'content-type': "application/json" }
conn.request("PUT", "/public_api/appsec/v1/data_source_instances/%7Bid%7D", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["Authorization"] =
'your_api_key_here' request["x-xdr-auth-id"] = '1' request["content-type"] = 'application/json' request.body = "
{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "selectionType": "CURRENT_STATE", "state": [ "string" ], "externalProjects": [ {
"branchName": "string", "externalBranchName": "string", "externalId": "string", "externalProjectId": "string",
"repoId": "string" } ], "uniqueProperties": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-
```

```
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); xhr.setRequestHeader("Authorization",
"your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") .header("Authorization", "your_api_key_here")
.header("x-xdr-auth-id", "1") .header("content-type", "application/json") .body("
{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1", "content-type":
"application/json" ] let parameters = [ "selectionType": "CURRENT_STATE", "state": ["string"], "externalProjects": [ [
"branchName": "string", "externalBranchName": "string", "externalId": "string", "externalProjectId": "string",
"repoId": "string" ] ], "uniqueProperties": [] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PUT", CURLOPT_POSTFIELDS => "{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "content-type: application/json", "x-xdr-auth-id: 1"
], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers, "x-xdr-
auth-id: 1"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); var request =
new RestRequest(Method.PUT); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-auth-
id", "1"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"selectionType\":\"CURRENT_STATE\",\"state\":[\"string\"],\"externalProjects\":
[{\"branchName\":\"string\",\"externalBranchName\":\"string\",\"externalId\":\"string\",\"externalProjectId\":\"string\",\"repo
{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Define the integration details

▼ selectionTypestring (Enum)

Defines how repositories are selected for scanning within a data source instance.

Allowed values:"CURRENT_STATE""CURRENT_STATE_AND_FUTURE""CURRENT_STATE_PENDING""MANUAL_SELECTION"
▼ statearray[string]

To update the integration for specific repositories, specify them here in the following format:

```
"state":["org1"/"repo_name1", "org2"/"repo_name2"]
```

▼ externalProjectsarray
[
▶ branchNamestringrequired

Name of the branch

▶ externalBranchNamestringrequired

Name of the external branch

▶ externalIdstringrequired

External ID
▶ externalProjectIdstringrequired

External project ID

▶ repoIdstringrequired

Repository ID

]
▼ uniquePropertiesobject

A flexible key-value map for specifying additional properties. Keys are strings and values can be of any type.
REQUEST Example 1

```
{ "selectionType": "CURRENT_STATE", "state": [ "string" ], "externalProjects": [ { "branchName": "string",
"externalBranchName": "string", "externalId": "string", "externalProjectId": "string", "repoId": "string" } ],
"uniqueProperties": {} }
{ "uniqueProperties": { "name": "my-collector-updated" } }
```

Responses

Ok

Body
application/json

Integration details

▼ creationDatestringrequired

Date and time when the data source instance was created.

▼ domainobject

Domain configuration specifying the hostname and protocol for the data source instance

▶ hostnamestringrequired

Hostname or domain name of the external data source.

▶ protocolstring (Enum)required

Communication protocol used to connect to the data source.

▼ idstringrequired

Unique identifier (ID) of the data source instance.

▼ instanceVersionstring

Version of the data source instance configuration.

▼ lastUpdateDatestringrequired

Date and time when the data source instance was last updated.

▼ scanTypesobject
▶ Additional propertiesobject

Configuration for a specific scan type within a data source instance.

▼ selectionTypestring (Enum)

Defines how repositories are selected for scanning within a data source instance.

Allowed values:"CURRENT_STATE""CURRENT_STATE_AND_FUTURE""CURRENT_STATE_PENDING""MANUAL_SELECTION"
▼ selfSignedCertificatestring

PEM-encoded self-signed certificate used for secure communication with the data source.

▼ statearray[string]

Integration state

▼ statusstring (Enum)

Current connection status of the data source instance.

- `COMPLETED` â€ The data source instance setup is complete and operational.
- `CONNECTED` â€ The data source instance is actively connected.
- `DESTROYING` â€ The data source instance is being removed.
- `DISABLED` â€ The data source instance is disabled and not actively scanning.
- `ERROR` â€ The data source instance encountered an error and requires attention.
- `PENDING` â€ The data source instance is being set up and is not yet active.
- `TEMPORARY` â€ The data source instance is in a temporary state during configuration.
- `TRANSPORTER_CONNECTION_DISABLED` â€ The transporter connection for this data source instance is disabled.
- `WARNING` â€ The data source instance is operational but has warnings that may require attention.

Allowed values:"COMPLETED""CONNECTED""DESTROYING""DISABLED""ERROR""PENDING""TEMPORARY""TRANSPORTER_CONNECTION_DISABLED""WARNING"

▼ statusDetailsobject

▶ Additional propertiesobject

Detailed status information for a specific component of the data source instance.

▼ tenantIdstring

Tenant ID that owns this data source instance.

▼ transporterobject

Transporter configuration for establishing secure communication between an on-premises or private data source and Cortex.

▶ brokerDeviceIdstringrequired

Unique identifier of the broker device used for the transporter connection.

▶ connectionNamestringrequired

Name of the transporter connection.

▼ typestring (Enum)required

Type of the data source instance, indicating the external system it connects to.

Allowed values:"AWS_CODE_BUILD""AWS_CODE_COMMIT""AZURE_REPOS""BITBUCKET""BITBUCKET_DATACENTER""CIRCLE_CI""CIRCLE_CI_CD""COLLECTOR""CORTEX_CLI""

▼ typeCategorystring (Enum)

Category classification of the data source instance type.

- `DEFAULT` â€ Standard data source instances such as VCS, CI/CD, and CLI integrations.
- `EXTERNAL_VENDOR_INTEGRATIONS` â€ Third-party external vendor integrations (for example, Snyk, Veracode, Semgrep, JFrog).

Allowed values:"DEFAULT""EXTERNAL_VENDOR_INTEGRATIONS"

▼ uniqueIdentifierstring

Unique identifier of the integration

RESPONSE Example 1


```
{ "creationDate": "2025-09-12T08:20:00.000Z", "id": "d4e5f6a7b8c9d0e1f2a3b4c5", "instanceVersion": "1.0.0",
"lastUpdateDate": "2025-10-05T16:30:00.000Z", "selectionType": "MANUAL_SELECTION", "state": [ "example-org/repo-
alpha", "example-org/repo-beta" ], "status": "CONNECTED", "type": "COLLECTOR", "typeCategory": "DEFAULT",
"uniqueIdentifier": "my-collector-updated", "detectionMethod": "SAST", "fileType": "SARIF", "apiUrl": "https://api-
yourfqdn/public_api/appsec/v1/collectors/d4e5f6a7b8c9d0e1f2a3b4c5" }
{ "creationDate": "2025-04-02T08:20:58.381Z", "id": "d4e5f6a7b8c9d0e1f2a3b4c5", "status": "CONNECTED", "type":
"COLLECTOR", "uniqueIdentifier": "my-collector-updated", "lastUpdateDate": "2025-04-02T08:21:47.023Z",
"detectionMethod": "SAST", "fileType": "SARIF", "apiUrl": "https://api-
yourfqdn/public_api/appsec/v1/collectors/d4e5f6a7b8c9d0e1f2a3b4c5" }
```


Internal Server Error

Body

application/json

▼ errorCodestring

Error code identifying the type of error.

▼ messagestring

Human-readable message describing the error.

RESPONSE

Example 1


```
{ "errorCode": "_InternalServerError", "message": "Failed to update data source instance" }
```

2.4.7.5 | Delete an AppSec Data Source

delete /public_api/appsec/v1/data_source_instances/{id}

Delete the specified data source instance from your Cortex environment.

> **Required license:**
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ id String required

Unique ID of the data source instance to delete.

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/data_source_instances/{id}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1" } conn.request("DELETE",
"/public_api/appsec/v1/data_source_instances/%7Bid%7D", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) request["Authorization"] =
'your_api_key_here' request["x-xdr-auth-id"] = '1' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); xhr.setRequestHeader("Authorization",
"your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D") .header("Authorization", "your_api_key_here")
.header("x-xdr-auth-id", "1") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1" ] let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "DELETE", CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "x-xdr-auth-id: 1" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers = curl_slist_append(headers,
"x-xdr-auth-id: 1"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/data_source_instances/%7Bid%7D"); var request =
new RestRequest(Method.DELETE); request.AddHeader("Authorization", "your_api_key_here"); request.AddHeader("x-xdr-
auth-id", "1"); IRestResponse response = client.Execute(request);
```

Responses

No content

2.4.7.6 | 3rd Party AppSec Collector

post /public_api/appsec/v1/collectors/{collectorId}

Upload SAST findings from third-party security tools to Cortex Cloud Application Security using the Collector API. This endpoint is used specifically for ingesting scan results, not for creating or configuring a generic collector.

The Collector API accepts scan results in SARIF v2.1.0 format. Once uploaded, the SARIF file is parsed to create code findings. These findings can then be elevated to issues, either manually or automatically, depending on your configured policies.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

2.4.7.6.1 | Prerequisites

1. Permissions: The following Cortex Cloud user roles or RBAC permissions are required:
   - User roles:
     - Cortex Cloud Instance Administrator
     - AppSec Administrator
   - RBAC:
     - View/Edit permissions for Data Sources configurations are required when not using a dedicated user role.
2. Repository Identification: The repository must already be onboarded in Cortex Cloud before SARIF findings for that repository can be uploaded. To identify the target repository, you must provide at least one of the following query parameters:
   - `repository_idâ€` The repository asset ID. This is the `id` field (SHA-256 hash format) returned by the `GET /public_api/appsec/v1/repositories` endpoint.
   - `repository_url â€` The repository URL (for example, `https://github.com/owner/repo`).
   - Either `repository_id` or `repository_url` must be provided. Both can be provided simultaneously. If neither is provided, the request returns a 400 error.
3. SARIF specifications: The following table outlines the mandatory and optional JSON fields required to successfully validate and ingest SAST findings.

Field	Required	Description
`version`	Yes	Must be "2.1.0"
`tool.driver.name`	Yes	Analysis tool name
`driver.rules` or `extensions[].rules`	Yes	At least one rule definition
`results[].ruleId`	Yes	Must match a defined rule `id`
`results[].message.text`	Yes	Finding description
`results[].locations[].physicalLocation.artifactLocation.uri`	Yes	File path
`results[].locations[].physicalLocation.region.startLine`	Yes	Line number
`results[].level`	Yes	`error` | `warning` | `note` | `none`. Defaults to `High`

2.4.7.6.2 | Limitations

- Maximum file size: 10 MB per request.
- SARIF version: Only SARIF v2.1.0 is supported. Files with invalid formats or schema will return a 400 error.

Path parameters
▼ collectorId String required

Unique identifier for the collector instance. This is the `id` field returned by the `GET /public_api/appsec/v1/data_source_instances?type=collector` endpoint. The collector must be of type `COLLECTOR` with `detectionMethod: SAST` and `fileType: SARIF`

Example: `col_7f2a9b4e1c3d5f8a0b6e2d4c`
Request headers
▼ Authorization String required

{api_key}

Example: `your_api_key_here`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `1`
Query parameters
▼ repository_id String required

The asset ID of the target repository. This is the `id` field (SHA-256 hash format) returned by the `GET /public_api/appsec/v1/repositories` endpoint. At least one of repository_url or repository_id must be provided. Both may be included. If neither is supplied, the request returns a 400 Bad Request.

Example: `a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8`
▼ repository_url String required

The URL of the target repository. At least one of `repository_url` or `repository_id` must be provided. Both may be included. If neither is supplied, the request returns a 400 Bad Request.

Example: `https://github.com/testapp/cves`
▼ branch String

Optional. Branch name to associate findings with. Defaults to the repository's default branch when omitted.

Example: `main`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: your_api_key_here' -H 'x-xdr-auth-id: 1'
'https://api-yourfqdn/public_api/appsec/v1/collectors/{collectorId}?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https://github.com/testapp/cves&br
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{}" headers = { 'Authorization':
"your_api_key_here", 'x-xdr-auth-id': "1", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] = 'your_api_key_here' request["x-xdr-auth-id"] = '1'
request["content-type"] = 'application/json' request.body = "{}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
xhr.setRequestHeader("Authorization", "your_api_key_here"); xhr.setRequestHeader("x-xdr-auth-id", "1");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
.header("Authorization", "your_api_key_here") .header("x-xdr-auth-id", "1") .header("content-type",
"application/json") .body("{}") .asString();
import Foundation let headers = [ "Authorization": "your_api_key_here", "x-xdr-auth-id": "1", "content-type":
"application/json" ] let parameters = [] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
```

```
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{}",
CURLOPT_HTTPHEADER => [ "Authorization: your_api_key_here", "content-type: application/json", "x-xdr-auth-id: 1" ],
]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: your_api_key_here"); headers =
curl_slist_append(headers, "x-xdr-auth-id: 1"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/collectors/col_7f2a9b4e1c3d5f8a0b6e2d4c?
repository_id=a3b8f2e1c7d4509a6b1e3f8c2d7a4b9e5f0c1d6a8b3e7f2c4d9a0b5e1f6c3d8&repository_url=https%3A%2F%2Fgithub.com%2Ftestapp
var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "your_api_key_here");
request.AddHeader("x-xdr-auth-id", "1"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

Object

application/json

REQUEST

Veracode Static Analysis


```
{ "$schema": "https://raw.githubusercontent.com/oasis-tcs/sarif-spec/master/Schemata/sarif-schema-2.1.0.json",
"version": "2.1.0", "runs": [ { "tool": { "driver": { "name": "Veracode Static Analysis Policy Scan", "rules": [ {
"id": "78", "name": "Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')",
"shortDescription": { "text": "CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command
Injection')" }, "helpUri": "https://cwe.mitre.org/data/definitions/78.html", "properties": { "category": "STATIC",
"tags": [ "STATIC" ] }, "defaultConfiguration": { "level": "error" } }, { "id": "89", "name": "Improper Neutralization
of Special Elements used in an SQL Command ('SQL Injection')", "shortDescription": { "text": "CWE-89: Improper
Neutralization of Special Elements used in an SQL Command ('SQL Injection')" }, "helpUri":
"https://cwe.mitre.org/data/definitions/89.html", "properties": { "category": "STATIC", "tags": [ "STATIC" ] },
"defaultConfiguration": { "level": "error" } } ], "version": "1.0" } }, "results": [ { "level": "error", "rank": 5,
"message": { "text": "This call to java.lang.ProcessBuilder.start() contains a command injection flaw. The argument to
the function is constructed using untrusted input. If an attacker is allowed to specify all or part of the command, it
may be possible to execute commands on the server with the privileges of the executing process." }, "locations": [ {
"physicalLocation": { "artifactLocation": { "uri": "com/scalesec/vulnado/Cowsay.java" }, "region": { "startLine": 16 }
}, "logicalLocations": [ { "name": "Cowsay.java", "fullyQualifiedName": "com.scalesec.vulnado.Cowsay.run", "kind":
"function" } ] } ], "ruleId": "78", "partialFingerprints": { "context_guid": "", "file_path": "", "procedure": "" } },
{ "level": "error", "rank": 4, "message": { "text": "This database query contains a SQL injection flaw. The call to
java.sql.Statement.executeQuery() constructs a dynamic SQL query using a variable derived from untrusted input. An
attacker could exploit this flaw to execute arbitrary SQL queries against the database." }, "locations": [ {
"physicalLocation": { "artifactLocation": { "uri": "com/scalesec/vulnado/User.java" }, "region": { "startLine": 49 }
}, "logicalLocations": [ { "name": "User.java", "fullyQualifiedName": "com.scalesec.vulnado.User.fetch", "kind":
"function" } ] } ], "ruleId": "89", "partialFingerprints": { "context_guid": "", "file_path": "", "procedure": "" } }
] } ] }
```


Responses

Returned when the SARIF file is accepted and the ingestion process has started.

Body

application/json

▼ statusstring (Enum)

Ingestion status.

Allowed values:"INGESTED""PARTIALLY_VALID"

▼ messagestring

Human-readable result message including the number of findings to be ingested.

RESPONSE

Example 1


```
{ "status": "INGESTED", "message": "SARIF file uploaded successfully. Ingestion in progress, findings may take a few
minutes to show. 1 findings will be ingested" }
```


Bad Request

Body

application/json

Error response for validation failures or bad requests.

▼ statusstring

Status of the request (for example, `INVALID`, `INGESTED_FAILED`).

▼ messagestring

Human-readable error message.

▼ errorCodestring

Error code identifying the type of error.

RESPONSE SARIF missing version field

```
{ "status": "INVALID", "message": "Validation failed: Invalid SARIF format â€  the \"version\" field is missing" }
{ "status": "INVALID", "message": "Validation failed: Invalid SARIF format â€  the rules section is empty" }
{ "status": "INGESTED_FAILED", "message": "File ingestion failed - Invalid repository id format" }
{ "errorCode": "_BadRequestError", "message": "Missing required repository identifier" }
```

Forbidden

The API key lacks required permissions. Required role: Instance Admin, AppSec Admin, or Data Sources edit permission.

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code identifying the type of error.

▶ err_msgstring

Human-readable error message.

▶ err_extrastring
RESPONSE
Example 1

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }
```

Not Found

Body
application/json
▼ errorCodestring

Error code identifying the type of error.

▼ messagestring

Human-readable error message.

RESPONSE
Collector ID does not exist.

```
{ "errorCode": "_NotFoundError", "message": "Collector 'invalid-collector-id' not found" }
```

Service Unavailable. Returned when the collector is disabled.

2.4.8 | Scan management

APIs for managing scans

2.4.8.1 | Get unscanned AppSec scan management repositories

get /public_api/appsec/v1/scans/unscanned-repositories

Get a list of Application Security repositories that have not been scanned. You can optionally filter by specifying the number of days past during which the repositories were not scanned.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}
Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
Query parameters
▼ days Double

Define the time period in days previous to now

double
Example: 1.2
Default: 7
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?days=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/unscanned-repositories?
days=SOME_NUMBER_VALUE", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?days=SOME_NUMBER_VALUE") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/scans/unscanned-
repositories?days=SOME_NUMBER_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?
days=SOME_NUMBER_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?days=SOME_NUMBER_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?days=SOME_NUMBER_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?days=SOME_NUMBER_VALUE"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/unscanned-repositories?
days=SOME_NUMBER_VALUE"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
```

```
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ organizationIdstring

Organization ID

▶ repoNamestring

Name of the repository

▶ repoIdstring

ID of the repository

]
RESPONSE

```
[ { "organizationId": "example", "repoName": "example", "repoId": "example" } ]
```

2.4.8.2 | Get AppSec branch periodic scans

get /public_api/appsec/v1/scans/periodic

Branch periodic scans are automated checks that assess the security posture of applications and infrastructure.

Get the details of branch periodic scans.

How to access branch periodic scans in the UI: Under **Modules** select **Application Security** > **Branch Periodic Scanning** (under **Scans**).

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ organizationName String
Example: `organizationName_example`
▼ repositories array[String]
▼ branchName String
Example: `branchName_example`
▼ scanHealth ScanHealthEnum
▼ days Double
double
Example: `1.2`
Default: `7`
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
```

```
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=organizationName_example&repositories=&branchName=branchName_example&scanHealth=&days=1.2&offset=1.2&limit=1.2
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/periodic?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days
var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ issuesFoundobject
▶ findingsSeverityBreakdownobject

▶ findingsTypesBreakdownobject
▶ issuesTypesBreakdownobject
▶ repositoryIdstring

ID of the scanned repository

▶ integrationIdstring
▶ providerstring
▶ scanIdstring

Scan ID

▶ scanHealthstring (Enum)

The health of the scan. Valid values include:

- `ERROR`: Indicates an error with the scan
- `PARTIALLY_COMPLETED`: Indicates that the scan executed partially with some scan modules succeeded and others failing
- `IN_PROGRESS`: The scan is in progress
- `COMPLETED`: Indicates that the scan is complete

▶ scanDatestring

Timestamp of the last scan execution

▶ branchNamestring

The branch analyzed during the scan

▶ organizationNamestring

The organization owning the repository

▶ repoNamestring

Name of the scanned repository

]
RESPONSE

```
[ { "issuesFound": {}, "findingsSeverityBreakdown": {}, "findingsTypesBreakdown": {}, "issuesTypesBreakdown": {},
"repositoryId": "example", "integrationId": "example", "provider": "example", "scanId": "example", "scanHealth":
"COMPLETED", "scanDate": "example", "branchName": "example", "organizationName": "example", "repoName": "example" } ]
```

2.4.8.3 | Get AppSec Pull Request scans

get /public_api/appsec/v1/scans/pr

Pull Request (PR) scans are initiated by events triggered by version control systems such as GitHub, GitLab, Bitbucket and Azure Repos, or via webhooks. These scans are run on default or non-default branches containing open PRs or Merge Requests (MR) from your integrated repositories.

Get the details of PR scans.

How to access Pull Request scans in the UI: Under **Modules** select **Application Security Pull Request Scans** (under **Scans**).

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ organizationName String
Example: `organizationName_example`
▼ repositories array[String]
▼ branchName String
Example: `branchName_example`

▼ prId String
Example: `prId_example`
▼ prTitle String
Example: `prTitle_example`
▼ prStatus ScanStatus
▼ scanHealth ScanHealthEnum
▼ days Double
double
Example: `1.2`
Default: `7`
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=organizationName_example&repositories=&branchName=branchName_example&prId=prId_example&prTitle=prTitle_example
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/pr?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&branchName=SOME_STRING_VALUE&prId=SOME_STRING_VALUE&prTitle=SO
var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
[
▶ issuesFoundobject
▶ findingsSeverityBreakdownobject
▶ findingsTypesBreakdownobject
▶ issuesTypesBreakdownobject
▶ pullRequestTitlestring
▶ integrationIdstring
▶ repositoryIdstring

ID of the scanned repository

▶ scanIdstring
▶ providerstring
▶ userEmailstring
▶ blockingPolicyNamestring
▶ blockingPolicyIdstring
▶ scanHealthstring (Enum)

The health of the scan. Valid values include:

- `ERROR`: Indicates an error with the scan
- `PARTIALLY_COMPLETED`: Indicates that the scan executed partially with some scan modules succeeded and others failing
- `IN_PROGRESS`: The scan is in progress
- `COMPLETED`: Indicates that the scan is complete

▶ scanDatestring

The timestamp of the last scan execution

▶ commitIdstring

The commit included in the PR

▶ pullRequestStatusstring (Enum)

Status of the PR scan. Valid values include:

- `PASSED`
- `PASSED_WITH_ISSUES`
- `BLOCKED`
- `IN_PROGRESS`
- `ERROR`
- `FAILED`

▶ pullRequestIdstring

The ID of the PR

▶ branchNamestring

Name of the branch analyzed during the scan

▶ organizationNamestring

Specifies the organization owning the repository

▶ repoNamestring
]
RESPONSE

```
[ { "issuesFound": {}, "findingsSeverityBreakdown": {}, "findingsTypesBreakdown": {}, "issuesTypesBreakdown": {},
"pullRequestTitle": "example", "integrationId": "example", "repositoryId": "example", "scanId": "example", "provider":
"example", "userEmail": "example", "blockingPolicyName": "example", "blockingPolicyId": "example", "scanHealth":
"COMPLETED", "scanDate": "example", "commitId": "example", "pullRequestStatus": "ERROR", "pullRequestId": "example",
"branchName": "example", "organizationName": "example", "repoName": "example" } ]
```

2.4.8.4 | Get AppSec CI scans

get /public_api/appsec/v1/scans/ci

CI scans detect exposed secrets, misconfigurations in your infrastructure-as-code (IaC) files, vulnerabilities in your software composition analysis (SCA) packages, and license non-compliance in your CI pipelines.

Get the details of CI scans.

How to access CI scans in the UI: Under Modules select Application Security > CI Scans (under Scans).

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ organizationName String
Example: `organizationName_example`
▼ repositories array[String]
▼ ciStatus ScanStatus
▼ scanHealth ScanHealthEnum
▼ days Double
double
Example: `1.2`
Default: `7`
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=organizationName_example&repositories=&ciStatus=&scanHealth=&days=1.2&offset=1.2&limit=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
```

```
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/ci?
organizationName=SOME_STRING_VALUE&repositories=SOME_ARRAY_VALUE&ciStatus=SOME_STRING_VALUE&scanHealth=SOME_STRING_VALUE&days=S
var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body

application/json

[

- ▶ issuesFoundobject
- ▶ findingsSeverityBreakdownobject
- ▶ findingsTypesBreakdownobject
- ▶ issuesTypesBreakdownobject
- ▶ repositoryIdstring

ID of the scanned repository

- ▶ integrationIdstring
- ▶ scanIdstring
- ▶ providerstring
- ▶ blockingPolicyNamestring
- ▶ blockingPolicyIdstring
- ▶ ciStatusstring (Enum)

Status of the PR scan. Valid values include:

- `PASSED`
- `PASSED_WITH_ISSUES`
- `BLOCKED`
- `IN_PROGRESS`
- `ERROR`
- `FAILED`

▶ scanHealthstring (Enum)

The health of the scan. Valid values include:

- `ERROR`: Indicates an error with the scan
- `PARTIALLY_COMPLETED`: Indicates that the scan executed partially with some scan modules succeeded and others failing
- `IN_PROGRESS`: The scan is in progress
- `COMPLETED`: Indicates that the scan is complete

▶ scanDatestring

The timestamp of the last scan execution

▶ branchNamestring

The name of the branch analyzed during the scan

▶ organizationNamestring

Name of the organization owning the repository

▶ repoNamestring

Name of the scanned repository

]
RESPONSE


```
[ { "issuesFound": {}, "findingsSeverityBreakdown": {}, "findingsTypesBreakdown": {}, "issuesTypesBreakdown": {},
"repositoryId": "example", "integrationId": "example", "scanId": "example", "provider": "example",
"blockingPolicyName": "example", "blockingPolicyId": "example", "ciStatus": "ERROR", "scanHealth": "COMPLETED",
"scanDate": "example", "branchName": "example", "organizationName": "example", "repoName": "example" } ]
```

2.4.8.5 | List AppSec scan issues

get /public_api/appsec/v1/scans/{scanId}/issues

Get a list of the issues discovered in the scan specified by scan ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ scanId String required
Example: `scanId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ severity SeverityEnum
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/{scanId}/issues?severity=&offset=1.2&limit=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/issues?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body

application/json

[

▶ resolution_commentstringrequired

▶ resolution_reasonstring (Enum)required
▶ resolution_statusstring (Enum)required
▶ assigneestringrequired
▶ branchstringrequired
▶ run_idstringrequired
▶ pull_request_idstringrequired
▶ repo_idstringrequired
▶ createdstringrequired
▶ file_pathstringrequired
▶ asset_namestringrequired
▶ detection_methodstring (Enum)required
▶ alert_namestringrequired
▶ severitystring (Enum)required
▶ scan_idstringrequired
▶ issue_idstringrequired
]
RESPONSE

```
[ { "resolution_comment": "example", "resolution_reason": "Resolved - Known Issue", "resolution_status": "New",
"assignee": "example", "branch": "example", "run_id": "example", "pull_request_id": "example", "repo_id": "example",
"created": "example", "file_path": "example", "asset_name": "example", "detection_method": "Secrets Security",
"alert_name": "example", "severity": "Critical", "scan_id": "example", "issue_id": "example" } ]
```

2.4.8.6 | List AppSec scan findings

get /public_api/appsec/v1/scans/{scanId}/findings

Get a list of the findings discovered in the scan specified by scan ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ scanId String required
Example: `scanId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ severity SeverityEnum
▼ offset Double
double
Example: `1.2`
Default: `0`
▼ limit Double
double
Example: `1.2`
Default: `100`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scans/{scanId}/findings?severity=&offset=1.2&limit=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scans/%7BscanId%7D/findings?
severity=SOME_STRING_VALUE&offset=SOME_NUMBER_VALUE&limit=SOME_NUMBER_VALUE"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body

application/json

[

- ▶ scan_sourcestring (Enum)required
- ▶ git_userstringrequired
- ▶ first_hash_timestringrequired
- ▶ first_hashstringrequired
- ▶ platform_idstringrequired
- ▶ branchstringrequired
- ▶ detection_methodstring (Enum)required
- ▶ file_pathstringrequired
- ▶ descriptionstringrequired
- ▶ last_observedstringrequired
- ▶ first_observedstringrequired
- ▶ suppression_typestring (Enum)required
- ▶ data_sourcestring (Enum)required

▶ namestringrequired
▶ categorystringrequired
▶ asset_idstringrequired
▶ asset_namestringrequired
▶ severitystring (Enum)required
▶ scan_idstringrequired
▶ issue_namestringrequired
]
RESPONSE

```
[ { "scan_source": "pr", "git_user": "example", "first_hash_time": "example", "first_hash": "example", "platform_id":
"example", "branch": "example", "detection_method": "Secrets Security", "file_path": "example", "description":
"example", "last_observed": "example", "first_observed": "example", "suppression_type": "Inline", "data_source":
"GitHub", "name": "example", "category": "example", "asset_id": "example", "asset_name": "example", "severity":
"Critical", "scan_id": "example", "issue_name": "example" } ]
```

2.4.8.7 | Rerun a repository scan

post /public_api/appsec/v1/scan/repository/{repositoryId}

Create a repository scan by specifying the branch name.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ repositoryId String required
Example: `repositoryId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ scanFullGitHistory Boolean
Example: `true`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/scan/repository/{repositoryId}?scanFullGitHistory=true'
-d '{ "branchName" : "branchName" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"branchName\":\"string\"}" headers
= { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE", payload, headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"branchName\":\"string\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "branchName": "string" }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE");
xhr.setRequestHeader("Authorization",
```

```
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"branchName\":\"string\"}")
.asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["branchName": "string"] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?
scanFullGitHistory=SOME_BOOLEAN_VALUE")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"branchName\":\"string\"}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?scanFullGitHistory=SOME_BOOLEAN_VALUE");
struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"branchName\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/scan/repository/%7BrepositoryId%7D?
scanFullGitHistory=SOME_BOOLEAN_VALUE"); var request = new RestRequest(Method.POST);
request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"branchName\":\"string\"}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

required

application/json

▼ branchNamestring

REQUEST

```
{ "branchName": "example" }
```

Responses

Ok

Body

application/json

Any of ScanRepositorySuccessResponse

▶ metadataobject

▶ err_msgstringrequired

▶ metadataobjectrequired

RESPONSE

```
{ "metadata": {}, "err_msg": "example" }
```

2.4.9 | SBOM management

APIs for managing SBOMs

2.4.9.1 | Get an SBOM for the specified repository

get /public_api/appsec/v1/sbom/repository/{repoId}

Get an SBOM (Software Bill of Materials) report for the specified repository.

Only the following combinations are supported:

`format`: `cyclonedx` `fileType`: `json` or `xml` `version:` 1.4or1.5or1.6`

`format`: `spdx` `fileType`: `json` or `txt` `version:` 2.3`

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ repoId String required
Example: `repoId_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ branchName String required

Branch name for which you want to export the SBOM.

Example: `branchName_example`
▼ fileType String required

Define the file type you want to export. For cyclonedx, either json or xml. For spdx, either json or txt.

Allowed values: json xml txt
Example: `fileType_example`
Default: `xml`
▼ version String required

For cyclonedx, version can be 1.4, 1.5, or 1.6. For spdx, version is 2.3.

Allowed values: 1.4 1.5 1.6 2.3
Example: `version_example`
Default: `1.6`
▼ format String required

Define the SBOM format.

Allowed values: cyclonedx spdx
Example: `format_example`
Default: `cyclonedx`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/sbom/repository/{repoId}?
branchName=branchName_example&fileType=fileType_example&version=version_example&format=format_example'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
```

```
Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/sbom/repository/%7BrepoId%7D?
branchName=SOME_STRING_VALUE&fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE"); var
request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ stringbyte
RESPONSE
`"Ym9uam91cg=="`

2.4.9.2 | Get all SBOMs for the specified organization

get /public_api/appsec/v1/sbom/organization/{orgName}

Get SBOM (Software Bill of Materials) reports for all repositories in the specified organization.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ orgName String required
Example: `orgName_example`

Request headers

▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

Query parameters

▼ fileType String required

Define the file type you want to export. For cyclonedx, either json or xml. For spdx, either json or txt.

Allowed values: json xml txt
Example: `fileType_example`
Default: `xml`

▼ version String required

For cyclonedx, version can be 1.4, 1.5, or 1.6. For spdx, version is 2.3.

Allowed values: 1.4 1.5 1.6 2.3
Example: `version_example`
Default: `1.6`

▼ format String required

Define the SBOM format.

Allowed values: cyclonedx spdx
Example: `format_example`
Default: `cyclonedx`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/sbom/organization/{orgName}?
fileType=fileType_example&version=version_example&format=format_example'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
```

```
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/sbom/organization/%7BorgName%7D?
fileType=SOME_STRING_VALUE&version=SOME_STRING_VALUE&format=SOME_STRING_VALUE"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ stringbyte
RESPONSE
`"Ym9uam91cg=="`

2.4.10 | Remediations

APIs for managing Remediation

2.4.10.1 | Get Fix Suggestion

get /public_api/appsec/v1/issues/fix/{issueId}/fix_suggestion

Retrieves a comprehensive fix suggestion for a specified application security issue. Use optional query parameters to include data such as the original code block, remediation instructions, or the suggested code fix.

> Required license:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ issueId String required

The unique identifier for the specific application security issue.

Example: `1234567`
Query parameters
▼ showCodeBlock Boolean

Specifies whether to include the original code block in the response.

Example: `true`
Default: `true`
▼ showRemediationInstruction Boolean

Specifies whether to include manual remediation instructions in the response.

Example: `true`
Default: `false`

▼ showSuggestedCodeBlock Boolean

Specifies whether to include the automated code fix in the response.

Example: `true`
Default: `true`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/appsec/v1/issues/fix/{issueId}/fix_suggestion?
showCodeBlock=true&showRemediationInstruction=true&showSuggestedCodeBlock=true'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") conn.request("GET",
"/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE")
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/issues/fix/1234567/fix_suggestion?
showCodeBlock=SOME_BOOLEAN_VALUE&showRemediationInstruction=SOME_BOOLEAN_VALUE&showSuggestedCodeBlock=SOME_BOOLEAN_VALUE");
var request = new RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```
Responses

Fix Suggestion Response

Body
application/json
▼ issueIdstringrequired

Unique identifier for the issue.

▼ issueNamestringrequired

Name of the security issue.

▼ existingCodeBlockstring

Original vulnerable code.

▼ remediationInstructionstring

Manual remediation instructions.
▼ suggestedCodeBlockstring

Automated fix suggestions.
RESPONSE

```
{ "issueId": "example", "issueName": "example", "existingCodeBlock": "example", "remediationInstruction": "example",
"suggestedCodeBlock": "example" }
```

2.4.10.2 | Trigger Fix Pull Request

post /public_api/appsec/v1/issues/fix/trigger_fix_pull_request

Create automated pull requests to fix multiple security issues in a single bulk operation.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request'
-d '{ "fixBranchName" : "fixBranchName", "issueIds" : [ "1234567", "9876543" ], "title" : "title" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":[\"1234567\",\"9876543\"]}" headers = { 'content-
type': "application/json" } conn.request("POST", "/public_api/appsec/v1/issues/fix/trigger_fix_pull_request", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["content-
type"] = 'application/json' request.body = "{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":
[\"1234567\",\"9876543\"]}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "fixBranchName": "string", "title": "string", "issueIds": [ "1234567", "9876543" ] });
const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () {
if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request") .header("content-type", "application/json")
.body("{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":[\"1234567\",\"9876543\"]}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = [ "fixBranchName": "string",
"title": "string", "issueIds": ["1234567", "9876543"] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":[\"1234567\",\"9876543\"]}", CURLOPT_HTTPHEADER => [
"content-type: application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":
[\"1234567\",\"9876543\"]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/issues/fix/trigger_fix_pull_request"); var
request = new RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"fixBranchName\":\"string\",\"title\":\"string\",\"issueIds\":
[\"1234567\",\"9876543\"]}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```
Body parameters

required
application/json
▼ fixBranchNamestring

The branch name for the fix pull request. If not specified, a custom branch will be used.

▼ titlestring

The title for the fix pull request. If not specified, a default message will be used.

▼ issueIdsarray[string]required

A list of unique identifiers for the issues to be fixed. Maximum 10 IDs per request.

Example:`["1234567","9876543"]`
REQUEST
```
{ "fixBranchName": "example", "title": "example", "issueIds": [ "1234567", "9876543" ] }
```
Responses

Ok

Body
application/json
▼ messagestringrequired

Error message if the process fails.

▼ triggeredPrsarrayrequired

Status of each issue.

[
▶ issueIdstringrequired

A unique identifier for issue.

▶ statusstring (Enum)required

PR status. Possible values: -`triggered`: If the PR is in triggered state. -`automated_fix_not_available`: If the PR is in automated_fix_not_available state.

]
▼ statusstring

Overall process status.

▼ remediationIdstring

Unique identifier to track the remediation process

▼ errorstring

Error details if the process fails.

RESPONSE
```
{ "message": "example", "triggeredPrs": [ { "issueId": "example", "status": "triggered" } ], "status": "example",
"remediationId": "example", "error": "example" }
```

2.4.10.3 | Get Fix Status

get /public_api/appsec/v1/issues/fix/{remediationId}

Retrieves the fix status of remediation processes using the remediation ID.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security add-on.

Path parameters
▼ remediationId String required

Remediation Id

Example: `remediationId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
```

```
'https://api-yourfqdn/public_api/appsec/v1/issues/fix/{remediationId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") conn.request("GET",
"/public_api/appsec/v1/issues/fix/%7BremediationId%7D") res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response = http.request(request)
puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error
#:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/issues/fix/%7BremediationId%7D"); var request =
new RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
▼ isProcessDonebooleanrequired

Indicates whether all remediation processes are complete.

▼ resultsarrayrequired

Remediation results grouped by repository.

[
▶ prUrlstring

URL of the created pull request.

▶ errorMessagestring

Error details if the process failed.

▶ remediationRepositoryIdstringrequired

Internal repository identifier.

▶ failureIssueIdsarray[string]required
▶ successfulIssueIdsarray[string]required
]

RESPONSE

```
{ "isProcessDone": false, "results": [ { "prUrl": "example", "errorMessage": "example", "remediationRepositoryId":
"example", "failureIssueIds": [ "example" ], "successfulIssueIds": [ "example" ] } ] }
```

2.4.11 | Criteria

APIs for managing Criteria

2.4.11.1 | Get all criteria

get /public_api/appsec/v1/application/criteria/all

Retrieves a paginated list of all criteria.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Query parameters
▼ page Double

Current page number in the paginated response.

double
Example: `1.2`
▼ pageSize Double

Total number of items in the current page.

double
Example: `1.2`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-yourfqdn/public_api/appsec/v1/application/criteria/all?page=1.2&pageSize=1.2'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") conn.request("GET",
"/public_api/appsec/v1/application/criteria/all?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE") res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/criteria/all?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/all?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/appsec/v1/application/criteria/all?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/all?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/all?page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/criteria/all?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/criteria/all?
page=SOME_NUMBER_VALUE&pageSize=SOME_NUMBER_VALUE"); var request = new RestRequest(Method.GET); IRestResponse response
= client.Execute(request);
```

Responses

Ok

Body
application/json
▼ itemsarrayrequired
[
Any of CriteriaDTOCode
▶ idstringrequired

Unique Id of the criteria.

▶ namestringrequired

Unique name of the criteria.

▶ descriptionstring

Criteria description.

▶ creationMethodstring (Enum)required

Creation method for the criteria. Possible values: -`manual`: For the criteria created manually. -`automatic`: Criteria that are automatically created.

▶ createdBystringrequired

Owner of the criteria.

▶ createdAtstringrequireddate-time

Timestamp when the criteria was created.

▶ lastUpdatedstringdate-time

Timestamp when the criteria was updated.

▶ deletedAtstringdate-time

Timestamp when the criteria was deleted.

▶ metadataobject

Additional metadata for the criteria.

▶ typestring (Enum)required

Criteria Type.

▶ configobject
▶ idstringrequired

Unique Id of the criteria.

▶ namestringrequired

Unique name of the criteria.

▶ descriptionstring

Criteria description.

▶ creationMethodstring (Enum)required

Creation method for the criteria. Possible values: -`manual`: For the criteria created manually. -`automatic`: Criteria that are automatically created.

▶ createdBystringrequired

Owner of the criteria.

▶ createdAtstringrequireddate-time

Timestamp when the criteria was created.

▶ lastUpdatedstringdate-time

Timestamp when the criteria was updated.

▶ deletedAtstringdate-time

Timestamp when the criteria was deleted.

▶ metadataobject

Additional metadata for the criteria.

▶ typestring (Enum)required

Criteria Type. Allowed values - `cloud`.

▶ configobject
]
▼ currentPagenumberrequireddouble

Current page number in the paginated response.
▼ totalPagesnumberdouble

Total number of pages for the paginated response.

▼ pageSizenumberrequireddouble

Number of entries in each page.

▼ totalItemsnumberrequireddouble

Total number of items in the response.
RESPONSE

```
{ "items": [ { "id": "example", "name": "example", "description": "example", "creationMethod": "manual", "createdBy":
"example", "createdAt": "2020-01-01T12:00:00Z", "lastUpdated": "2020-01-01T12:00:00Z", "deletedAt": "2020-01-
01T12:00:00Z", "metadata": { "applicationCount": 0.1, "assetCount": 0.1, "refreshStatus": "in_progress",
"deletedFromUai": false }, "type": "cloud", "config": { "unifyWithinProvider": false, "unifyAcrossProviders": false,
"criteriaDefinitions": [ { "type": "tags", "provider": "GCP", "tagKeys": [ "example" ] } ], "criteriaPrettyName":
"example", "criteriaPrettyNameTags": [ {} ], "applicationMetaData": { "applicationNameSourceTags": "example",
"businessCriticalitySourceTags": "example", "businessOwnerSourceTags": [ "example" ], "businessUnitSourceTags":
"example" } } } ], "currentPage": 0.1, "totalPages": 0.1, "pageSize": 0.1, "totalItems": 0.1 }
```

2.4.11.2 | Get a Criteria by ID

get /public_api/appsec/v1/application/criteria/{criteriaId}

Retrieves detailed information for a specific criteria using its unique Id.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Path parameters
▼ criteriaId String required

Unique identifier for the criteria

Example: `criteriaId_example`
Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/criteria/{criteriaId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
```

```
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); var
request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Ok

Body
application/json
Any of CriteriaDTOCode

▶ idstringrequired

Unique Id of the criteria.

▶ namestringrequired

Unique name of the criteria.

▶ descriptionstring

Criteria description.

▶ creationMethodstring (Enum)required

Creation method for the criteria. Possible values: -`manual`: For the criteria created manually. -`automatic`: Criteria that are automatically created.

▶ createdBystringrequired

Owner of the criteria.

▶ createdAtstringrequireddate-time

Timestamp when the criteria was created.

▶ lastUpdatedstringdate-time

Timestamp when the criteria was updated.

▶ deletedAtstringdate-time

Timestamp when the criteria was deleted.

▶ metadataobject

Additional metadata for the criteria.
▶ typestring (Enum)required

Criteria Type.

▶ configobject
▶ idstringrequired

Unique Id of the criteria.

▶ namestringrequired

Unique name of the criteria.

▶ descriptionstring

Criteria description.

▶ creationMethodstring (Enum)required

Creation method for the criteria. Possible values: -`manual`: For the criteria created manually. -`automatic`: Criteria that are automatically created.

▶ createdBystringrequired

Owner of the criteria.

▶ createdAtstringrequireddate-time

Timestamp when the criteria was created.

▶ lastUpdatedstringdate-time

Timestamp when the criteria was updated.

▶ deletedAtstringdate-time

Timestamp when the criteria was deleted.

▶ metadataobject

Additional metadata for the criteria.

▶ typestring (Enum)required

Criteria Type. Allowed values - `cloud`.

▶ configobject
RESPONSE


```
{ "id": "example", "name": "example", "description": "example", "creationMethod": "manual", "createdBy": "example",
"createdAt": "2020-01-01T12:00:00Z", "lastUpdated": "2020-01-01T12:00:00Z", "deletedAt": "2020-01-01T12:00:00Z",
"metadata": { "applicationCount": 0.1, "assetCount": 0.1, "refreshStatus": "in_progress", "deletedFromUai": false },
"type": "cloud", "config": { "unifyWithinProvider": false, "unifyAcrossProviders": false, "criteriaDefinitions": [ {
"type": "tags", "provider": "GCP", "tagKeys": [ "example" ] } ], "criteriaPrettyName": "example",
"criteriaPrettyNameTags": [ {} ], "applicationMetaData": { "applicationNameSourceTags": "example",
"businessCriticalitySourceTags": "example", "businessOwnerSourceTags": [ "example" ], "businessUnitSourceTags":
"example" } } }
```

2.4.11.3 | Delete a Criteria

delete /public_api/appsec/v1/application/criteria/{criteriaId}

Deletes a specific criteria identified by its unique Id.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Path parameters
▼ criteriaId String required

Unique identifier for the criteria

Example: `criteriaId_example`
Request headers
▼ Authorization String required

{api_key}
Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/criteria/{criteriaId}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("DELETE", "/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/criteria/%7BcriteriaId%7D"); var
request = new RestRequest(Method.DELETE); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```
Responses

No content

2.4.11.4 | Create a Criteria

post /public_api/appsec/v1/application/criteria

Creates a Criteria based on the provided details.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security with Application Security Add-on.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/appsec/v1/application/criteria'
-d '{ "name" : "name", "description" : "description", "config" : { "criteriaPrettyName" : "criteriaPrettyName",
"applicationMetaData" : { "exposedToInternetOverride" : true }, "unifyAcrossProviders" : true, "unifyWithinProvider" :
true, "criteriaDefinitions" : [ { "tagKeys" : [ "tagKeys", "tagKeys" ] }, { "tagKeys" : [ "tagKeys", "tagKeys" ] } ],
"criteriaPrettyNameTags" : [ "criteriaPrettyNameTags", "criteriaPrettyNameTags" ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/appsec/v1/application/criteria", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/appsec/v1/application/criteria") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "string", "description": "string", "type": "cloud", "config": {
"unifyWithinProvider": true, "unifyAcrossProviders": true, "criteriaDefinitions": [ { "type": "tags", "provider":
"GITLAB", "tagKeys": [ "string" ] } ], "criteriaPrettyName": "string", "criteriaPrettyNameTags": [ "string" ],
"applicationMetaData": { "businessOwner": "none", "businessCriticality": "Critical", "exposedToInternetOverride": true
} } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/appsec/v1/application/criteria"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/appsec/v1/application/criteria")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "name": "string", "description":
"string", "type": "cloud", "config": [ "unifyWithinProvider": true, "unifyAcrossProviders": true,
"criteriaDefinitions": [ [ "type": "tags", "provider": "GITLAB", "tagKeys": ["string"] ] ], "criteriaPrettyName":
"string", "criteriaPrettyNameTags": ["string"], "applicationMetaData": [ "businessOwner": "none",
"businessCriticality": "Critical", "exposedToInternetOverride": true ] ] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/appsec/v1/application/criteria")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/appsec/v1/application/criteria", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/appsec/v1/application/criteria"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}"); CURLcode ret
= curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/appsec/v1/application/criteria"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"name\":\"string\",\"description\":\"string\",\"type\":\"cloud\",\"config\":
{\"unifyWithinProvider\":true,\"unifyAcrossProviders\":true,\"criteriaDefinitions\":
[{\"type\":\"tags\",\"provider\":\"GITLAB\",\"tagKeys\":
[\"string\"]}],\"criteriaPrettyName\":\"string\",\"criteriaPrettyNameTags\":[\"string\"],\"applicationMetaData\":
{\"businessOwner\":\"none\",\"businessCriticality\":\"Critical\",\"exposedToInternetOverride\":true}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Creates a new criteria object.

▼ namestringrequired

Unique name for the criteria.

▼ descriptionstring

Optional description for the criteria.

▼ typestring (Enum)required

Criteria Type. Allowed values - `cloud`.

Allowed values:"cloud"
▼ configobjectrequired
Any of CodeCriteriaConfig
▶ unifyWithinProviderboolean

Repositories with the same name at the selected group-by level (org, project, or repository) are consolidated into a single application within the selected provider.

▶ unifyAcrossProvidersboolean

If multiple applications share the same name at the chosen group-by level (org, project, or repository), they are merged across providers to form a single unified application.

▶ criteriaDefinitionsarrayrequired
▶ criteriaPrettyNamestring

A human-readable name for the criteria.

▶ criteriaPrettyNameTagsarray[string]

Tags associated with the criteria name.

▶ applicationMetaDataobject
▶ unifyWithinProviderboolean

Repositories with the same name at the selected group-by level (org, project, or repository) are consolidated into a single application within the selected provider.

▶ unifyAcrossProvidersboolean

If multiple applications share the same name at the chosen group-by level (org, project, or repository), they are merged across providers to form a single unified application.

▶ criteriaDefinitionsarrayrequired
▶ criteriaPrettyNamestring

A human-readable name for the criteria.

▶ criteriaPrettyNameTagsarray

Tags associated with the criteria name.

▶ applicationMetaDataobjectrequired
REQUEST

```
{ "name": "example", "description": "example", "type": "cloud", "config": { "unifyWithinProvider": false, "unifyAcrossProviders": false, "criteriaDefinitions": [ { "type": "tags", "provider": "GCP", "tagKeys": [ "example" ] } ], "criteriaPrettyName": "example", "criteriaPrettyNameTags": [ {} ], "applicationMetaData": { "applicationNameSourceTags": "example", "businessCriticalitySourceTags": "example", "businessOwnerSourceTags": [ "example" ], "businessUnitSourceTags": "example" } } }
```

Responses

Ok

Body
application/json
▼ idstringrequired

Unique Id of the criteria.

▼ namestringrequired

Unique name of the criteria.

RESPONSE

```
{ "id": "example", "name": "example" }
```

2.5 | Get Asset Compliance Results API

2.5.1 | Preface

REST API for retrieving compliance results for an asset.

Required licenses: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Version: 1.0.0

2.5.1.1 | Servers

https://api-{fqdn}

2.5.1.2 | Authentication methods

▼ XDRAuth
Api Key "x-xdr-auth-id"

XDR API Key ID for authentication

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.

▼ XDRAuthToken
Api Key "Authorization"

XDR API Key for authentication

Authorized requests to the API should use: **Authorization** inside **a header** with the access token.

2.5.1.2.1 | Default authentication

Please note that this documentation assumes a minimum level of authentication is required, unless explicitly stated otherwise.
It is essential to ensure that any of the following authentication mechanisms are in place to access the API endpoints:

- XDRAuth=[], XDRAuthToken

2.5.2 | Control Findings

Operations for retrieving compliance control findings and assessment results

2.5.2.1 | Get asset compliance results

post /public_api/v1/compliance/get_asset

Retrieve compliance standard and control results for a specific asset ID, with optional filtering, sorting and pagination.

Required params:

- `asset_id` (string) - The asset identifier
- `last_evaluation_time` (integer) - Unix timestamp in milliseconds for the evaluation time

Filtering Support:

- **String fields** (`standard`, `category`, `control`, `source`): `eq`, `neq`, `contains`, `not_contains`
- **Status fields** (`status`, `severity`): `eq`, `neq`
- Status valid values: [`FAILED`, `PASSED`, `NOT_ASSESSED`]
- Severity valid values: [`SEV_010_INFO`, `SEV_020_LOW`, `SEV_030_MEDIUM`, `SEV_040_HIGH`, `SEV_050_CRITICAL`]

Sorting Support:

- Available fields: `standard`, `category`, `control`, `severity`, `status`
- Sort orders: `asc`, `desc`
- Default: `standard` in ascending order

Pagination: (max number of elements is 100)

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
```

```
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/public_api/v1/compliance/get_asset'
-d '{ "request_data" : { "search_from" : 0, "asset_id" :
"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da", "last_evaluation_time" : 1763669115000, "filters"
: [ { "field" : "severity", "value" : "SEV_030_MEDIUM", "operator" : "eq" }, { "field" : "severity", "value" :
"SEV_030_MEDIUM", "operator" : "eq" } ], "sort" : "", "search_to" : 60 } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" headers = { 'x-xdr-
auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"%7Bfqdn%7D/public_api/v1/compliance/get_asset", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "asset_id":
"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da", "last_evaluation_time": 1763669115000, "filters":
[], "sort": { "field": "standard", "keyword": "asc" }, "search_from": 0, "search_to": 100 } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "asset_id": "eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da",
"last_evaluation_time": 1763669115000, "filters": [], "sort": [ "field": "standard", "keyword": "asc" ],
"search_from": 0, "search_to": 100 ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}", CURLOPT_HTTPHEADER =>
[ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/compliance/get_asset"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"asset_id\":\"eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da\",\"last_evaluation_time\":1763669115000,\"fil
[],\"sort\":{\"field\":\"standard\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required
application/json

Request payload for retrieving asset compliance data. Supports filtering, sorting, and pagination.

▼ request_dataobject
▶ asset_idstringrequired

Asset identifier for which to retrieve control findings

▶ last_evaluation_timeintegerrequiredint64

Unix timestamp in milliseconds for the evaluation time

▶ filtersarray

Array of filter objects for filtering control findings

▶ sortobject

Sort configuration (defaults to standard asc)

▶ search_frominteger

Starting index for pagination

▶ search_tointeger

Ending index for pagination

REQUEST

```
{ "request_data": { "asset_id": "eea3102e81bc8cf10b43168a7a1ff27cb539a7325428f3cd956240472335c6da",
"last_evaluation_time": 1763669115000, "filters": [], "sort": {}, "search_from": 0, "search_to": 100 } }
```

Responses

Successfully retrieved control findings

Body
application/json

Response containing asset compliance data including compliance status, findings, and associated standards.

▼ replyobject
▶ total_countintegerrequired

Total number of control findings available

▶ result_countintegerrequired

Number of control findings returned after filtering and pagination

▶ filter_countintegerrequired

Number of control findings matching the applied filters

▶ assetsarrayrequired

Array of control findings for the asset

RESPONSE

```
{ "reply": { "total_count": 5, "result_count": 5, "filter_count": 5, "assets": [ { "STANDARD": "Secure Controls
Framework (SCF) v2024.2", "STANDARD_REVISION": "-3633352044114537559", "CATEGORY": "Continuous Monitoring",
"CONTROL_REVISION": "5207648284675893530", "CONTROL": "MON-05.1:Real-Time Alerts of Event Logging Failure",
"SEVERITY": "SEV_030_MEDIUM", "RULE_IDS": [ "ab0317ac-661a-4a7d-a28a-53f4fdf6d290" ], "LAST_EVALUATION_TIME":
1762718526, "STATUS": "FAILED", "SOURCE": "Finding" } ] } }
```


Bad request - invalid parameters or request format

Body
application/json

Standard error response returned when the API request fails.

▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE missing_asset_id


```
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: asset_id", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: last_evaluation_time", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: standard, category, control, severity, status, source", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid severity value. Allowed values: SEV_010_INFO, SEV_020_LOW, SEV_030_MEDIUM, SEV_040_HIGH, SEV_050_CRITICAL", "err_extra": {} } }
```


Authentication required

Body
application/json

Standard error response returned when the API request fails.

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }
```


Access denied - insufficient permissions

Body
application/json

Standard error response returned when the API request fails.

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access control findings", "err_extra": {} } }
```


Internal server error

Body
application/json

Standard error response returned when the API request fails.

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details
RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve control findings", "err_extra": {} } }
```

2.6 | Cortex Cloud Logging and Collection Service Management APIs

2.6.1 | Preface

The Cloud Logging and Collection Service (CLCS) Management APIs allow you to programmatically manage Next-Generation Firewalls (NGFWs) connected to your CLCS environment.

CLCS enables NGFWs to forward logs directly to Cortex XDR for analysis and threat detection. These APIs provide the ability to list all connected devices and disconnect one or more devices in bulk, replacing the slow, manual UI workflow that only supports one-at-a-time removal.

Required licenses: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

RBAC permissions:

- List connected devices: Data Collection > Data Sources > View
- Disconnect devices: Data Collection > Data Sources > Edit

Version: 1.0.0

2.6.1.1 | Servers

https://api-yourfqdn

Your Cortex Cloud tenant API endpoint. Replace `yourfqdn` with your tenant's fully qualified domain name.

2.6.2 | CLCS Management

Endpoints for managing Next-Generation Firewalls (NGFWs) connected to the Cloud Logging and Collection Service (CLCS). Use these APIs to list connected devices and disconnect devices in bulk.

2.6.2.1 | List connected NGFW devices

get /public_api/v1/clcs/get_connected_devices

Returns a list of all Next-Generation Firewalls (NGFWs) currently connected to the Cloud Logging and Collection Service (CLCS) for the authenticated tenant.

Each device in the response includes its serial number (`device_id`), the CSP account ID it belongs to, and the region it is deployed in.

Required license: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Required permission: Data Collection > Data Sources > View

Request headers
▼ Authorization String required

Your Cortex Cloud API key.

Example: `{api_key}`
▼ x-xdr-auth-id String required

Your Cortex Cloud API key ID.

Example: `{api_key_id}`
▼ x-xdr-nonce String

A unique nonce value used for request authentication.

Example: `0123456789abcdef`
▼ x-xdr-timestamp String

The Unix timestamp in milliseconds at the time the request is sent.

Example: `1714118400000`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authorization: {api_key}' -H 'x-xdr-auth-id: {api_key_id}' -H 'x-xdr-nonce: 0123456789abcdef' -H 'x-xdr-timestamp:
1714118400000'
```

```
'https://api-yourfqdn/public_api/v1/clcs/get_connected_devices'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization': "{api_key}", 'x-
xdr-auth-id': "{api_key_id}", 'x-xdr-nonce': "0123456789abcdef", 'x-xdr-timestamp': "1714118400000" }
conn.request("GET", "/public_api/v1/clcs/get_connected_devices", headers=headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/clcs/get_connected_devices") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] = '{api_key}'
request["x-xdr-auth-id"] = '{api_key_id}' request["x-xdr-nonce"] = '0123456789abcdef' request["x-xdr-timestamp"] =
'1714118400000' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/clcs/get_connected_devices"); xhr.setRequestHeader("Authorization", "{api_key}");
xhr.setRequestHeader("x-xdr-auth-id", "{api_key_id}"); xhr.setRequestHeader("x-xdr-nonce", "0123456789abcdef");
xhr.setRequestHeader("x-xdr-timestamp", "1714118400000"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/clcs/get_connected_devices")
.header("Authorization", "{api_key}") .header("x-xdr-auth-id", "{api_key_id}") .header("x-xdr-nonce",
"0123456789abcdef") .header("x-xdr-timestamp", "1714118400000") .asString();
import Foundation let headers = [ "Authorization": "{api_key}", "x-xdr-auth-id": "{api_key_id}", "x-xdr-nonce":
"0123456789abcdef", "x-xdr-timestamp": "1714118400000" ] let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/clcs/get_connected_devices")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/clcs/get_connected_devices", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization: {api_key}", "x-xdr-auth-id: {api_key_id}", "x-xdr-nonce:
0123456789abcdef", "x-xdr-timestamp: 1714118400000" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/clcs/get_connected_devices"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: {api_key}"); headers = curl_slist_append(headers, "x-xdr-auth-id:
{api_key_id}"); headers = curl_slist_append(headers, "x-xdr-nonce: 0123456789abcdef"); headers =
curl_slist_append(headers, "x-xdr-timestamp: 1714118400000"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/clcs/get_connected_devices"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization", "{api_key}"); request.AddHeader("x-xdr-auth-id", "
{api_key_id}"); request.AddHeader("x-xdr-nonce", "0123456789abcdef"); request.AddHeader("x-xdr-timestamp",
"1714118400000"); IRestResponse response = client.Execute(request);
```

Responses

A list of NGFW devices currently connected to CLCS.

Body
application/json

The response envelope for the get connected devices operation.

▼ replyobject

The response payload containing the list of connected devices.

▶ devicesarrayrequired

A list of NGFW devices currently connected to CLCS. Returns an empty array if no devices are connected.

RESPONSE success

```
{ "reply": { "devices": [ { "device_id": "01234567890", "csp_account_id": 123456, "region": "us" }, { "device_id":
"01234567891", "csp_account_id": 123456, "region": "eu" } ] } }
{ "reply": { "devices": [] } }
```

Unauthorized. The API key or key ID is missing or invalid.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE

{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }

Forbidden. The API key does not have the required permissions to list connected devices. Ensure the key has Data Collection > Data Sources > View permission.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE

{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }

Internal server error. An unexpected error occurred on the server.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE

{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }

2.6.2.2 | Disconnect NGFW devices from CLCS

post /public_api/v1/clcs/disconnect_devices

Disconnects one or more Next-Generation Firewalls (NGFWs) from the Cloud Logging and Collection Service (CLCS). This operation removes the specified devices from CLCS so they no longer forward logs to Cortex XDR.

The request must specify the target devices by their serial numbers (`device_ids`), along with the CSP account ID and region that the devices belong to. Up to 1000 device IDs can be submitted in a single request.

If a device ID in the request does not exist or is not connected, it is silently ignored. The response returns only the IDs of devices that were successfully disconnected.

Required license: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Required permission: Data Collection > Data Sources > Edit

Validation rules:

- `device_ids`: Must contain 1â€ 1000 unique alphanumeric strings, each 1â€ 50 characters long.
- `csp_account_id`: Must be a positive integer.
- `region`: Must be a non-empty string (not whitespace-only, not a number).

Request headers

▼ Authorization String required

Your Cortex Cloud API key.

Example: `{api_key}`

▼ x-xdr-auth-id String required

Your Cortex Cloud API key ID.

Example: `{api_key_id}`

▼ x-xdr-nonce String

A unique nonce value used for request authentication.

Example: `0123456789abcdef`

▼ x-xdr-timestamp String

The Unix timestamp in milliseconds at the time the request is sent.

Example: `1714118400000`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: {api_key}' -H 'x-xdr-auth-id: {api_key_id}' -H 'x-xdr-nonce: 0123456789abcdef' -H 'x-xdr-timestamp:
1714118400000'
'https://api-yourfqdn/public_api/v1/clcs/disconnect_devices'
-d '{ "request_data" : { "device_ids" : [ "01234567890", "01234567891" ], "csp_account_id" : 123456, "region" : "us" }
}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"device_ids\":
[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}" headers = { 'Authorization': "
{api_key}", 'x-xdr-auth-id': "{api_key_id}", 'x-xdr-nonce': "0123456789abcdef", 'x-xdr-timestamp': "1714118400000",
'content-type': "application/json" } conn.request("POST", "/public_api/v1/clcs/disconnect_devices", payload, headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/clcs/disconnect_devices") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] = '{api_key}'
request["x-xdr-auth-id"] = '{api_key_id}' request["x-xdr-nonce"] = '0123456789abcdef' request["x-xdr-timestamp"] =
'1714118400000' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"device_ids\":
[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "device_ids": [ "01234567890", "01234567891" ], "csp_account_id":
123456, "region": "us" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/clcs/disconnect_devices");
xhr.setRequestHeader("Authorization", "{api_key}"); xhr.setRequestHeader("x-xdr-auth-id", "{api_key_id}");
xhr.setRequestHeader("x-xdr-nonce", "0123456789abcdef"); xhr.setRequestHeader("x-xdr-timestamp", "1714118400000");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/clcs/disconnect_devices")
.header("Authorization", "{api_key}") .header("x-xdr-auth-id", "{api_key_id}") .header("x-xdr-nonce",
"0123456789abcdef") .header("x-xdr-timestamp", "1714118400000") .header("content-type", "application/json") .body("
{\"request_data\":{\"device_ids\":[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}")
.asString();
```

```
import Foundation let headers = [ "Authorization": "{api_key}", "x-xdr-auth-id": "{api_key_id}", "x-xdr-nonce": "0123456789abcdef", "x-xdr-timestamp": "1714118400000", "content-type": "application/json" ] let parameters = ["request_data": [ "device_ids": ["01234567890", "01234567891"], "csp_account_id": 123456, "region": "us" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/clcs/disconnect_devices")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/clcs/disconnect_devices", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"device_ids\":[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}", CURLOPT_HTTPHEADER => [ "Authorization: {api_key}", "content-type: application/json", "x-xdr-auth-id: {api_key_id}", "x-xdr-nonce: 0123456789abcdef", "x-xdr-timestamp: 1714118400000" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/v1/clcs/disconnect_devices"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization: {api_key}"); headers = curl_slist_append(headers, "x-xdr-auth-id: {api_key_id}"); headers = curl_slist_append(headers, "x-xdr-nonce: 0123456789abcdef"); headers = curl_slist_append(headers, "x-xdr-timestamp: 1714118400000"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"device_ids\":[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/clcs/disconnect_devices"); var request = new RestRequest(Method.POST); request.AddHeader("Authorization", "{api_key}"); request.AddHeader("x-xdr-auth-id", "{api_key_id}"); request.AddHeader("x-xdr-nonce", "0123456789abcdef"); request.AddHeader("x-xdr-timestamp", "1714118400000"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"device_ids\":[\"01234567890\",\"01234567891\"],\"csp_account_id\":123456,\"region\":\"us\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

The request body for disconnecting NGFW devices from CLCS.

▼ request_dataobject

The parameters specifying which devices to disconnect.

▶ device_idsarray[string]required

A list of NGFW device serial numbers to disconnect. Must contain 1â€ 1000 unique alphanumeric strings, each between 1 and 50 characters long.

▶ csp_account_idintegerrequired

The CSP (Cloud Service Provider) account ID that the devices belong to. Must be a positive integer.

▶ regionstringrequired

The cloud region where the devices are deployed. Must be a non-empty string (not whitespace-only, not a numeric value).

REQUEST disconnect-two-devices

```
{ "request_data": { "device_ids": [ "01234567890", "01234567891" ], "csp_account_id": 123456, "region": "us" } }
{ "request_data": { "device_ids": [ "033333333330123" ], "csp_account_id": 789012, "region": "eu" } }
```

Responses

The operation completed. The response contains the IDs of devices that were successfully disconnected. Device IDs that were not found are silently omitted from the response.

Body
application/json

The response envelope for the disconnect devices operation.

▼ replyobject

The response payload containing the IDs of successfully disconnected devices.

▶ device_idsarray[string]required

The serial numbers of devices that were successfully disconnected. Device IDs from the request that were not found are silently omitted.

RESPONSE success


```
{ "reply": { "device_ids": [ "01234567890", "01234567891" ] } }
{ "reply": { "device_ids": [] } }
```


Note: This response describes the intended validation error envelope. The backend currently raises a generic `500 Internal Server Error` for these validation failures pending a fix to wrap Pydantic validation errors in the documented envelope. Treat the structure below as the contract clients should code against.

Bad request. The request body failed validation. Common causes include duplicate device IDs, an invalid or zero-value `csp_account_id`, or an empty `region`.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE duplicate-ids


```
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "The csp_account_id 0 is invalid. Try again using a number greater than zero." } }
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "The region is empty. Try again by providing a valid region." } }
```


Unauthorized. The API key or key ID provided for this request is missing or invalid.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE


```
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }
```


Forbidden. The API key does not have the required permissions to disconnect devices. Ensure the key has Data Collection > Data Sources > Edit permission.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.
▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }

Internal server error. An unexpected error occurred while processing the disconnect request.

Body
application/json

A standard error response envelope returned when a request fails.

▼ replyobject

The error payload containing the status code, message, and additional detail.

▶ err_codeintegerrequired

The HTTP status code of the error.

▶ err_msgstringrequired

A short description of the error.

▶ err_extrastring

Additional detail about the error, including remediation guidance where applicable.

RESPONSE
{ "reply": { "err_code": 400, "err_msg": "Bad Request", "err_extra": "Duplicate device IDs found: 01234567890" } }

2.7 | Cloud Onboarding APIs

2.7.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Public APIs for cloud onboarding and instance management.

The following API categories are included:

- Cloud instance management: These APIs enable you to create a cloud instance in *pending* state and provide a link to download the authentication template to be executed in your CSP. You can get details on the cloud instances currently in Cortex Cloud and you can enable, disable, or delete them. You can also edit the cloud instance configuration.
- Cloud account management: The cloud account APIs allow you to manage accounts within a specific cloud instance. You can have multiple cloud accounts within one cloud instance. Use these APIs to get the cloud accounts in the specified cloud instance and to enable or disable cloud accounts.
- Outpost management: Use these APIs to create or edit templates for onboarding outposts.
- General: These APIs are for general management.

Required license: Cortex Cloud Posture Management or Cortex Cloud Runtime Security.

Version: Cortex Cloud

2.7.1.1 | Servers

https://api-yourfqdn

2.7.1.2 | Authentication methods

▼ Authorization
Api Key "x-api-key"

Authorized requests to the API should use: x-api-key inside a header with the access token.

▼ x-xdr-auth-id
Api Key "x-api-key-id"

Authorized requests to the API should use: **x-api-key-id** inside **a header** with the access token.

2.7.2 | Cloud instance management

APIs for managing cloud instances

2.7.2.1 | Create a cloud onboarding integration template

post /public_api/v1/cloud_onboarding/create_instance_template

Create a template to facilitate the seamless setup of CSP data in Cortex. Define the scope and specify the scan mode. For full control of the setup, you can use the advanced settings. Based on the onboarding settings, Cortex generates an authentication template to establish trust to the CSP and grant permissions to Cortex. Cortex Cloud creates an instance in *pending* state. The API returns a link to download the template from the Cortex tenant.

Note: If the template execution in the CSP fails, there is currently no manual execution of the template by API. You must perform manual execution in the UI.

For scope modifications, the parameters are CSP-specific. For AWS, use `accounts`, for GCP, use `projects`, and for Azure, use `subscriptions`.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/create_instance_template'
-d '{ "request_data" : { "scope" : "ORGANIZATION", "scan_mode" : "MANAGED", "cloud_provider" : "AWS", "instance_name"
: "My AWS Instance", "custom_resources_tags" : [ { "key" : "environment", "value" : "production" } ],
"collection_configuration" : { "audit_logs" : { "enabled" : true } }, "scope_modifications" : { "accounts" : {
"enabled" : true, "type" : "INCLUDE", "account_ids" : [ "123456789012" ] }, "regions" : { "enabled" : true, "type" :
"INCLUDE", "regions" : [ "us-east-1", "us-west-2" ] } }, "additional_capabilities" : { "xsiam_analytics" : true,
"data_security_posture_management" : true, "registry_scanning" : true, "registry_scanning_options" : { "type" : "ECR"
}, "serverless_scanning" : true, "agentless_disk_scanning" : true } } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/create_instance_template", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_instance_template") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
```

```
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": { "scope": "ORGANIZATION", "scan_mode": "MANAGED", "cloud_provider":
"AWS", "instance_name": "My AWS Instance", "custom_resources_tags": [ { "key": "environment", "value": "production" }
], "collection_configuration": { "audit_logs": { "enabled": true } }, "scope_modifications": { "accounts": {
"enabled": true, "type": "INCLUDE", "account_ids": [ "123456789012" ] }, "regions": { "enabled": true, "type":
"INCLUDE", "regions": [ "us-east-1", "us-west-2" ] } }, "additional_capabilities": { "xsiam_analytics": true,
"data_security_posture_management": true, "registry_scanning": true, "registry_scanning_options": { "type": "ECR" },
"serverless_scanning": true, "agentless_disk_scanning": true } } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_instance_template"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_instance_template") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "scope":
"ORGANIZATION", "scan_mode": "MANAGED", "cloud_provider": "AWS", "instance_name": "My AWS Instance",
"custom_resources_tags": [ [ "key": "environment", "value": "production" ] ], "collection_configuration":
["audit_logs": ["enabled": true]], "scope_modifications": [ "accounts": [ "enabled": true, "type": "INCLUDE",
"account_ids": ["123456789012"] ], "regions": [ "enabled": true, "type": "INCLUDE", "regions": ["us-east-1", "us-west-
2"] ] ], "additional_capabilities": [ "xsiam_analytics": true, "data_security_posture_management": true,
"registry_scanning": true, "registry_scanning_options": ["type": "ECR"], "serverless_scanning": true,
"agentless_disk_scanning": true ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_instance_template")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_instance_template", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/create_instance_template"); struct curl_slist *headers = NULL;
```

```
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/create_instance_template"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"scope\":\"ORGANIZATION\",\"scan_mode\":\"MANAGED\",\"cloud_provider\":\"AWS\",\"instance_name\":\"My AWS
Instance\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"production\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"scope_modifications\":{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":
[\"123456789012\"]},\"regions\":{\"enabled\":true,\"type\":\"INCLUDE\",\"regions\":[\"us-east-1\",\"us-west-
2\"]}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true}}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ scopestring (Enum)required

Define the scope for this cloud instance. Valid values include:

- `ORGANIZATION`: Use this to indicate an AWS organization, GCP organization, or Azure tenant.
- `ACCOUNT_GROUP`: Use this to indicate an AWS account group, GCP folder, or Azure management group.
- `ACCOUNT`: Use this to indicate an AWS account, GCP project, or Azure subscription.

▶ scan_modestring (Enum)required

Define the scan mode. Valid values include:

- `MANAGED`: (Recommended) Security scanning is performed in the Cortex cloud environment.
- `OUTPOST`: Security scanning is performed on infrastructure deployed to a cloud account owned by you.

**Note: ** Scanning with an outpost may require additional CSP permissions and may incur additional CSP costs.

▶ scan_env_idstring

When the scan mode is `OUTPOST`, you must include the `scan_env_id` field with the outpost ID as the value. To obtain the outpost ID, call `/public_api/v1/cloud_onboarding/get_outposts`. The value of `outpost_id` in the response is the outpost ID.

▶ account_detailsobject

`account_details` is required for onboarding Azure and is not used for onboarding AWS or GCP.

▶ instance_namestringrequired

▶ cloud_providerstring (Enum)required

The cloud service provider. Valid values include:

- `AWS`
- `AZURE`
- `GCP`
- `OCI`
- `ALIBABA_CLOUD`

▶ custom_resources_tagsarrayrequired

▶ collection_configurationobjectrequired

▶ scope_modificationsobjectrequired
▶ additional_capabilitiesobject

Define which security capabilities you want to benefit from.

Note: Adding security capability typically requires additional cloud provider permissions. For detailed information on the permissions required, see Cloud service provider permissions.

▶ cloud_partitionobject (Enum)

Whether the CSP environment is `COMMERCIAL` or `GOV`:

- `COMMERCIAL`: (Default) Standard cloud deployment typically used for private and public sector organizations that do not require isolated government-specific infrastructure.
- `GOV`: Government cloud environments for compatibility with FedRAMP-certified tenants.

▶ gcp_workspaceobject

GCP Workspace configuration (GCP only).

REQUEST AWS, Managed scan, region excluded, audit logs enabled with custom collection

```
{ "request_data": { "scope": "ACCOUNT", "scan_mode": "MANAGED", "instance_name": "AWS 1 Instance",
"scope_modifications": { "regions": { "enabled": true, "type": "EXCLUDE", "regions": [ "us-east-1" ] } },
"additional_capabilities": { "xsiam_analytics": false, "data_security_posture_management": true, "registry_scanning":
false, "serverless_scanning": true, "agentless_disk_scanning": true }, "custom_resources_tags": [ { "key":
"managed_by", "value": "paloaltonetworks" } ], "collection_configuration": { "audit_logs": { "enabled": true,
"collection_method": "AUTOMATED" } }, "cloud_provider": "AWS", "cloud_partition": "COMMERCIAL" } }
{ "request_data": { "scope": "ACCOUNT", "instance_name": "test-oci-instance-01", "scan_mode": "OUTPOST",
"scan_env_id": "acafb912391c44f59a01b6512317abf9", "cloud_provider": "OCI", "scope_modifications": { "regions": {
"enabled": true, "type": "INCLUDE", "regions": [ "us-phoenix-1", "us-ashburn-1" ] } }, "additional_capabilities": {
"xsiam_analytics": false, "data_security_posture_management": true, "registry_scanning": false, "serverless_scanning":
false, "agentless_disk_scanning": true }, "custom_resources_tags": [ { "key": "managed_by", "value":
"paloaltonetworks" } ], "collection_configuration": { "audit_logs": { "enabled": true, "collection_method": "CUSTOM",
"custom_collectors": [ { "region": "us-phoenix-1", "bucket_name": "prod-audit-logs-bucket", "compartment_ocid":
"ocid1.compartment.oc1..xxxxxxxxxxxxxx" }, { "region": "us-ashburn-1", "bucket_name": "dr-audit-logs-bucket",
"compartment_ocid": "ocid1.compartment.oc1..yyyyyyyyyyyyyy" } ] } } } }
```

Responses

Successful Response

Body
application/json
▼ replyobject

The main payload of the response, containing instance information data. It includes a link to download the template file from your tenant. If you use automated upload (only for AWS), the link will take you directly to AWS CloudFormation to create the stack. Otherwise, download the template and upload it in your CSP and follow the instructions to manually upload the template:

- AWS
- GCP
- Azure ARM
- Azure CLI

RESPONSE

```
{ "reply": { "automated": { "link": "string", "tracking_guid": "string" }, "manual": { "TF/ARM": "string" } } }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.7.2.2 | Get cloud instance details

post /public_api/v1/cloud_onboarding/get_instance_details

Get the configuration details of the specified cloud instance.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instance_details'
-d '{ "request_data" : { "id" : "instance-1" } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"id\":\"instance-
1\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/get_instance_details", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instance_details") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"instance-1\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "instance-1" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instance_details"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instance_details") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"instance-1\"}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["id": "instance-
1"]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instance_details")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instance_details", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"instance-1\"}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instance_details"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"instance-1\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instance_details"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"id\":\"instance-1\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

The ID of the cloud instance of which you want to get the details.

REQUEST

```
{ "request_data": { "id": "instance-1" } }
```

Responses

Successful Response

Body

application/json

▼ replyobject

▶ idstring

▶ collectorstring

▶ connector_namestring

▶ scopestring

▶ tagsarray

▶ StatusUIinteger

▶ scanobject

▶ is_pending_changesboolean

▶ accountsobject

▶ security_capabilitiesarray

▶ upgrade_availableboolean

▶ cloud_partitionstring

RESPONSE

Example 1


```
{ "reply": { "id": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx", "collector": "AWS", "connector_name": "AWS-Sample", "scope":
"ACCOUNT", "tags": [ { "key": "managed_by", "value": "paloaltonetworks" } ], "StatusUI": 0, "scan": { "StatusUI": 0,
```

"outpost_id": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx", "scan_method": "OUTPOST" }, "is_pending_changes": false, "accounts": { "0": 1, "1": 0, "2": 0, "3": 0 }, "security_capabilities": [{ "name": "PERMISSIONS", "description": "Permissions", "StatusUI": 0 }, { "name": "DISCOVERY", "description": "Discovery Engine", "StatusUI": 0 }, { "name": "ADS", "description": "Agentless Disk Scanning", "StatusUI": 0 }, { "name": "DSPM", "description": "Data Security Scanning", "StatusUI": 2 }, { "name": "AUDIT_LOGS", "description": "Audit Logs", "StatusUI": 0 }, { "name": "REGISTRY", "description": "Registry Scanning", "StatusUI": 0 }, { "name": "SERVERLESS", "description": "Serverless Scanning", "StatusUI": 0 }, { "name": "IDENTITY_SECURITY", "description": "Identity Security", "StatusUI": 0 }, { "name": "AUTOMATION", "description": "Automation", "StatusUI": 2 }], "upgrade_available": true, "cloud_partition": "GOV" } }

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.7.2.3 | Get all or filtered cloud instances

post /public_api/v1/cloud_onboarding/get_instances

Get the configuration details of all or filtered cloud instances. This does not include instances in *pending* state.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
```

```
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instances'
-d '{ "request_data" : { "filter_data" : { "sort" : [ { "FIELD" : "STATUS", "ORDER" : "DESC" } ], "paging" : { "from"
: 0, "to" : 50 }, "filter" : { "AND" : [ { "SEARCH_FIELD" : "CLOUD_PROVIDER", "SEARCH_TYPE" : "EQ", "SEARCH_VALUE" :
"AWS" } ] } } } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter_data\":
{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/get_instances", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instances") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":
{\"AND\":[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filter_data": { "sort": [ { "FIELD": "STATUS", "ORDER": "DESC" } ],
"paging": { "from": 0, "to": 50 }, "filter": { "AND": [ { "SEARCH_FIELD": "CLOUD_PROVIDER", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "AWS" } ] } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instances"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instances")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":
{\"AND\":[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["filter_data": [
"sort": [ [ "FIELD": "STATUS", "ORDER": "DESC" ] ], "paging": [ "from": 0, "to": 50 ], "filter": ["AND": [ [
"SEARCH_FIELD": "CLOUD_PROVIDER", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "AWS" ] ] ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instances")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_instances", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filter_data\":{\"sort\":
[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instances"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":
```

```
{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_instances"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"filter_data\":{\"sort\":
[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"CLOUD_PROVIDER\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"AWS\"}]}}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject

Valid values for the sort field `FIELD` the filter field `SEARCH_FIELD` include:

- `STATUS`
- `PROVIDER`
- `INSTANCE_NAME`
- `SCOPE`
- `SCAN_MODE`
- `CREATION_TIME`
- `OUTPOST_ID`
- `AUTHENTICATION_METHOD`
- `ID`

▶ filter_dataobject
REQUEST

```
{ "request_data": { "filter_data": { "sort": [ { "FIELD": "STATUS", "ORDER": "DESC" } ], "paging": { "from": 0, "to":
50 }, "filter": { "AND": [ { "SEARCH_FIELD": "CLOUD_PROVIDER", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "AWS" } ] } } } }
```

Responses

Successful Response

Body
application/json
▼ replyobject
▶ DATAarray
▶ FILTER_COUNTinteger
▶ TOTAL_COUNTinteger
RESPONSE

```
{ "reply": { "DATA": [ { "instance_id": "716e6a20f1ca41efb966bd9fa486fb60", "cloud_provider": "AWS", "instance_name":
"aws-expanse-afr-sbx", "account_name": "", "accounts": 1, "scope": "ACCOUNT", "scan_mode": "MANAGED",
"cloud_partition": "COMMERCIAL", "creation_time": 1768333922750, "custom_resources_tags": "[{\"key\": \"managed_by\",
\"value\": \"paloaltonetworks\"}]", "provisioning_method": "CF", "additional_capabilities": "{\"automation\": true,
\"xsiam_analytics\": true, \"registry_scanning\": true}", "update_status": "UPDATE_AVAILABLE", "is_pending_changes":
0, "status": "DISABLED", "outpost_id": "6e1e2eb8fce34c6e889538ea177644f7" } ], "FILTER_COUNT": 1, "TOTAL_COUNT": 1 } }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.7.2.4 | Edit a cloud instance

post /public_api/v1/cloud_onboarding/edit_instance

Edit the configuration settings of the specified cloud instance. After editing, there is a notice in the UI that there are pending changes. The changes are applied after you execute the template in the CSP after editing.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_instance'
-d '{ "request_data" : { "id" : "instance-1", "scan_env_id" : "env-1", "instance_name" : "Updated AWS Instance",
"cloud_provider" : "AWS", "custom_resources_tags" : [ { "key" : "environment", "value" : "staging" } ],
"collection_configuration" : { "audit_logs" : { "enabled" : true } }, "additional_capabilities" : { "xsiam_analytics"
: true, "data_security_posture_management" : true, "registry_scanning" : true, "registry_scanning_options" : { "type"
: "ECR" }, "serverless_scanning" : true, "agentless_disk_scanning" : true }, "scope_modifications" : { "accounts" : {
"enabled" : true, "type" : "INCLUDE", "account_ids" : [ "123456789012", "210987654321" ] }, "regions" : { "enabled" :
true, "type" : "EXCLUDE", "regions" : [ "us-east-1" ] } } } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"id\":\"instance-
1\",\"scan_env_id\":\"env-1\",\"instance_name\":\"Updated AWS
Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/edit_instance", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_instance") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
```

```
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"instance-1\",\"scan_env_id\":\"env-1\",\"instance_name\":\"Updated AWS
Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "id": "instance-1", "scan_env_id": "env-1", "instance_name": "Updated
AWS Instance", "cloud_provider": "AWS", "custom_resources_tags": [ { "key": "environment", "value": "staging" } ],
"collection_configuration": { "audit_logs": { "enabled": true } }, "additional_capabilities": { "xsiam_analytics":
true, "data_security_posture_management": true, "registry_scanning": true, "registry_scanning_options": { "type":
"ECR" }, "serverless_scanning": true, "agentless_disk_scanning": true }, "scope_modifications": { "accounts": {
"enabled": true, "type": "INCLUDE", "account_ids": [ "123456789012", "210987654321" ] }, "regions": { "enabled": true,
"type": "EXCLUDE", "regions": [ "us-east-1" ] } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_instance"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_instance")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"instance-1\",\"scan_env_id\":\"env-1\",\"instance_name\":\"Updated AWS
Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "id": "instance-
1", "scan_env_id": "env-1", "instance_name": "Updated AWS Instance", "cloud_provider": "AWS", "custom_resources_tags":
[ [ "key": "environment", "value": "staging" ] ], "collection_configuration": ["audit_logs": ["enabled": true]],
"additional_capabilities": [ "xsiam_analytics": true, "data_security_posture_management": true, "registry_scanning":
true, "registry_scanning_options": ["type": "ECR"], "serverless_scanning": true, "agentless_disk_scanning": true ],
"scope_modifications": [ "accounts": [ "enabled": true, "type": "INCLUDE", "account_ids": ["123456789012",
"210987654321"] ], "regions": [ "enabled": true, "type": "EXCLUDE", "regions": ["us-east-1"] ] ] ]] as [String : Any]
let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_instance")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_instance", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"instance-1\",\"scan_env_id\":\"env-
1\",\"instance_name\":\"Updated AWS Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_instance"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"instance-1\",\"scan_env_id\":\"env-1\",\"instance_name\":\"Updated AWS
Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_instance"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"id\":\"instance-1\",\"scan_env_id\":\"env-
1\",\"instance_name\":\"Updated AWS Instance\",\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"environment\",\"value\":\"staging\"}],\"collection_configuration\":{\"audit_logs\":
{\"enabled\":true}},\"additional_capabilities\":
{\"xsiam_analytics\":true,\"data_security_posture_management\":true,\"registry_scanning\":true,\"registry_scanning_options\":
{\"type\":\"ECR\"},\"serverless_scanning\":true,\"agentless_disk_scanning\":true},\"scope_modifications\":
{\"accounts\":{\"enabled\":true,\"type\":\"INCLUDE\",\"account_ids\":[\"123456789012\",\"210987654321\"]},\"regions\":
{\"enabled\":true,\"type\":\"EXCLUDE\",\"regions\":[\"us-east-1\"]}}}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters
required
application/json

▼ request_dataobject

▶ idstring

Cloud instance ID.

▶ scan_env_idstring

When the scan mode is `OUTPOST`, you must include the `scan_env_id` field with the outpost ID as the value. To obtain the outpost ID, call `/public_api/v1/cloud_onboarding/get_outposts`. The value of `outpost_id` in the response is the outpost ID.

▶ instance_namestring

Cloud instance name.

▶ additional_capabilitiesobject

Define which security capabilities you want to benefit from.

Note: Adding security capability typically requires additional cloud provider permissions. For detailed information on the permissions required, see Cloud service provider permissions.

▶ cloud_providerstring (Enum)

The cloud service provider. Valid values include:

- `AWS`
- `AZURE`
- `GCP`
- `OCI`
- `ALIBABA_CLOUD`

▶ cloud_partitionobject (Enum)

Whether the CSP environment is `COMMERCIAL` or `GOV`:

- `COMMERCIAL`: (Default) Standard cloud deployment typically used for private and public sector organizations that do not require isolated government-specific infrastructure.
- `GOV`: Government cloud environments for compatibility with FedRAMP-certified tenants. Note: You must use the same value that was used when the cloud instance was created.

▶ custom_resources_tagsarray

▶ collection_configurationobject



▶ scope_modificationsobject
▶ gcp_workspaceobject

GCP Workspace configuration (GCP only).

REQUEST
AWS GOV

```
{ "request_data": { "scope_modifications": { "accounts": { "enabled": true, "type": "EXCLUDE", "account_ids": [
"sample-account-1" ] }, "regions": { "enabled": false, "type": null, "regions": null } }, "additional_capabilities": {
"xsiam_analytics": true, "data_security_posture_management": true, "registry_scanning": true, "serverless_scanning":
true, "agentless_disk_scanning": true, "registry_scanning_options": { "type": "ALL" } }, "custom_resources_tags": [ {
"key": "managed_by", "value": "paloaltonetworks" } ], "collection_configuration": { "audit_logs": { "enabled": true,
"collection_method": "AUTOMATED", "data_events": true } }, "scan_env_id": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx",
"cloud_provider": "AWS", "cloud_partition": "GOV" } }
```

Responses

Successful Response

Body
application/json
▼ replyobject
▶ automatedobject
▶ manualobject
RESPONSE

```
{ "reply": { "automated": { "link": "example", "tracking_guid": "example" }, "manual": { "TF/ARM": "example" } } }
```


Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.2.5 | Enable or disable cloud instances

post /public_api/v1/cloud_onboarding/enable_disable_instance

Enable or disable the cloud instances specified by their instance IDs. To obtain the instance IDs, use `/public_api/v1/cloud_onboarding/get_instances/`.

Required license: Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance'
-d '{ "request_data" : { "ids" : [ "e22b3a29260c404183d1a0ea6cbd4418", "d32d3b19730d414387d2a3ea7eac4218" ], "enable"
: true } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"ids\":
[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/enable_disable_instance", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"ids\":[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "ids": [ "e22b3a29260c404183d1a0ea6cbd4418",
"d32d3b19730d414387d2a3ea7eac4218" ], "enable": true } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":{\"ids\":
[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "ids":
["e22b3a29260c404183d1a0ea6cbd4418", "d32d3b19730d414387d2a3ea7eac4218"], "enable": true ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"ids\":
[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}", CURLOPT_HTTPHEADER =>
[ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

```
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"ids\":
[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_instance"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"ids\":
[\"e22b3a29260c404183d1a0ea6cbd4418\",\"d32d3b19730d414387d2a3ea7eac4218\"],\"enable\":true}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idsarray[string]

List of cloud instance IDs to enable/disable/

▶ enableboolean

Whether to enable the cloud instances (`true`) or disable (`false`).

REQUEST

```
{ "request_data": { "ids": [ "e22b3a29260c404183d1a0ea6cbd4418", "d32d3b19730d414387d2a3ea7eac4218" ], "enable": true
} }
```

Responses

Successful Response

Body
application/json
▼ replyobject

The main payload of the response, containing operation-specific data.

RESPONSE

```
{ "reply": {} }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.2.6 | Delete the specified cloud instances

post /public_api/v1/cloud_onboarding/delete_instance

Delete the specified cloud instances.

Required license: Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example:

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/delete_instance'
-d '{ "request_data" : { "ids" : [ "instance-1", "instance-2" ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"ids\":
[\"instance-1\",\"instance-2\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/delete_instance", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/delete_instance") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"ids\":[\"instance-1\",\"instance-2\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "ids": [ "instance-1", "instance-2" ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/delete_instance"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/delete_instance")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":{\"ids\":
[\"instance-1\",\"instance-2\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["ids": ["instance-
1", "instance-2"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: [])
let request = NSMutableURLRequest(url: NSURL(string: "https://api-
```

```
yourfqdn/public_api/v1/cloud_onboarding/delete_instance")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/delete_instance", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"ids\":[\"instance-1\",\"instance-2\"]}}", CURLOPT_HTTPHEADER =>
[ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/delete_instance"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"ids\":[\"instance-1\",\"instance-2\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/delete_instance"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"ids\":[\"instance-1\",\"instance-2\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idsarray[string]

List of cloud instance IDs to delete.

REQUEST
```
{ "request_data": { "ids": [ "instance-1", "instance-2" ] } }
```
Responses

Successful Response

Body
application/json
▼ replyobject

The main payload of the response, containing operation-specific data.

RESPONSE
```
{ "reply": {} }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body

application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.2.7 | Get identifier roles for cloud instance

post /public_api/v1/cloud_onboarding/get_identifiers

List all of the identifiers roles for the cloud instance. In the UI, these details are listed under **Authorization details** of the cloud instance.

Required license: In Cortex XSIAM Premium, Cortex XSIAM Enterprise, or Cortex XSIAM NG SIEM, requires the Cortex Cloud Posture Management add-on. In Cortex XSIAM Enterprise Plus, requires the Data Collection add-on.

CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_identifiers'
-d '{ "instance_id" : "instance_id", "cloud_provider" : "GCP" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}" headers = { 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/cloud_onboarding/get_identifiers", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_identifiers") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["content-type"] =
'application/json' request.body = "{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "instance_id": "string", "cloud_provider": "GCP" }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_identifiers"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_identifiers")
.header("content-type", "application/json") .body("{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}")
.asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = [ "instance_id": "string",
"cloud_provider": "GCP" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_identifiers")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_identifiers", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}", CURLOPT_HTTPHEADER => [
"content-type: application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_identifiers"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}"); CURLcode ret =
curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_identifiers"); var request = new RestRequest(Method.POST); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"instance_id\":\"string\",\"cloud_provider\":\"GCP\"}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ instance_idstring

The cloud instance ID for which you want to list the authorization details.

▼ cloud_providerstring (Enum)

The cloud service provider for which you want to list the authorization details.

Allowed values:"GCP"
REQUEST

```
{ "instance_id": "example", "cloud_provider": "GCP" }
```

Responses

Successful Response

Body
application/json
▼ replyobject
▶ cortex_discovery_rolestring

The Cortex discovery role identifier

▶ cortex_scan_platform_rolestring

The Cortex scan platform role identifier

▶ cortex_log_collection_rolestring

The Cortex log collection role identifier

▶ cortex_outpost_rolestring

The Cortex outpost role identifier

RESPONSE

```
{ "reply": { "cortex_discovery_role": "example", "cortex_scan_platform_role": "example", "cortex_log_collection_role": "example", "cortex_outpost_role": "example" } }
```

Bad Request

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.3 | Cloud account management

APIs for managing cloud accounts per instance

2.7.3.1 | Get accounts in the specified cloud instances

post /public_api/v1/cloud_onboarding/get_accounts

List accounts and their details for the specified cloud instance.

Required license: Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example:

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_accounts'
-d '{ "request_data" : { "instance_id" : "instance_id", "filter_data" : { "sort" : [ { "FIELD" : "STATUS", "ORDER" :
"DESC" } ], "paging" : { "from" : 0, "to" : 50 }, "filter" : { "AND" : [ { "SEARCH_FIELD" : "STATUS", "SEARCH_TYPE" :
"EQ", "SEARCH_VALUE" : "ACTIVE" } ] } } } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"instance_id\":\"string\",\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":
{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/get_accounts", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_accounts") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"instance_id\":\"string\",\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":
{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "instance_id": "string", "filter_data": { "sort": [ { "FIELD":
"STATUS", "ORDER": "DESC" } ], "paging": { "from": 0, "to": 50 }, "filter": { "AND": [ { "SEARCH_FIELD": "STATUS",
"SEARCH_TYPE": "EQ", "SEARCH_VALUE": "ACTIVE" } ] } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_accounts"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_accounts")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"instance_id\":\"string\",\"filter_data\":{\"sort\":[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":
{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "instance_id":
"string", "filter_data": [ "sort": [ [ "FIELD": "STATUS", "ORDER": "DESC" ] ], "paging": [ "from": 0, "to": 50 ],
"filter": ["AND": [ [ "SEARCH_FIELD": "STATUS", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "ACTIVE" ] ]] ] ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/cloud_onboarding/get_accounts")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_accounts", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"instance_id\":\"string\",\"filter_data\":{\"sort\":
[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_accounts"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"instance_id\":\"string\",\"filter_data\":{\"sort\":
[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_accounts"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"instance_id\":\"string\",\"filter_data\":{\"sort\":
[{\"FIELD\":\"STATUS\",\"ORDER\":\"DESC\"}],\"paging\":{\"from\":0,\"to\":50},\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"STATUS\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"ACTIVE\"}]}}}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

Valid values for the filter field `SEARCH_FIELD` include:

- `STATUS`
- `ACCOUNT_NAME`
- `CLOUD_ACCOUNT_ID`
- `ENVIRONMENT`
- `TYPE`
- `CREATED_AT`

▶ instance_idstring

▶ filter_dataobject

REQUEST

```
{ "request_data": { "instance_id": "example", "filter_data": { "sort": [ { "FIELD": "STATUS", "ORDER": "DESC" } ],
"paging": { "from": 0, "to": 50 }, "filter": { "AND": [ { "SEARCH_FIELD": "STATUS", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "ACTIVE" } ] } } } }
```

Responses

Successful Response

Body
application/json
▼ replyobject
▶ DATAarray
▶ FILTER_COUNTinteger
▶ TOTAL_COUNTinteger
RESPONSE

```
{ "reply": { "DATA": [ { "account_name": "546064730288", "cloud_account_id": "546064730288", "account_type":
"ORGANIZATION", "status": "ENABLED", "environment": "NONE", "created_at": 1775686847489 } ], "FILTER_COUNT": 1,
"TOTAL_COUNT": 1 } }
```


Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.3.2 | Enable or disable cloud accounts

post /public_api/v1/cloud_onboarding/enable_disable_account

Enable or disable the specified cloud accounts within a specific cloud instance.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account'
-d '{ "request_data" : { "ids" : [ "account-1", "account-2" ], "instance_id" : "instance-1", "enable" : true } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"ids\":
[\"account-1\",\"account-2\"],\"instance_id\":\"instance-1\",\"enable\":true}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/enable_disable_account", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"ids\":[\"account-1\",\"account-2\"],\"instance_id\":\"instance-1\",\"enable\":true}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "ids": [ "account-1", "account-2" ], "instance_id": "instance-1",
"enable": true } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":{\"ids\":
[\"account-1\",\"account-2\"],\"instance_id\":\"instance-1\",\"enable\":true}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "ids": ["account-
1", "account-2"], "instance_id": "instance-1", "enable": true ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"ids\":[\"account-1\",\"account-
2\"],\"instance_id\":\"instance-1\",\"enable\":true}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"ids\":[\"account-1\",\"account-2\"],\"instance_id\":\"instance-1\",\"enable\":true}}"); CURLcode
ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/enable_disable_account"); var request
= new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"ids\":[\"account-1\",\"account-
```

```
2\"],\"instance_id\":\"instance-1\",\"enable\":true}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idsarray[string]

List of account IDs to enable or disable.

▶ instance_idstring

The cloud instance ID where the cloud accounts should be disabled.

▶ enableboolean

Whether to enable (`true`) or disable (`false`) to specified accounts.

REQUEST

```
{ "request_data": { "ids": [ "account-1", "account-2" ], "instance_id": "instance-1", "enable": true } }
```

Responses

Successful Response

Body
application/json
▼ replyobject
RESPONSE

```
{ "reply": {} }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.4 | Outpost management

APIs for managing outposts

2.7.4.1 | Create an outpost template

post /public_api/v1/cloud_onboarding/create_outpost_template

Create a template to onboard an outpost. Define the custom resource tags you want associated with the outpost and Cortex generates an authentication template to establish trust to the CSP and grant permissions to Cortex.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template'
-d '{ "request_data" : { "cloud_provider" : "AWS", "custom_resources_tags" : [ { "key" : "purpose", "value" :
"outpost" } ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/create_outpost_template", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "cloud_provider": "AWS", "custom_resources_tags": [ { "key":
"purpose", "value": "outpost" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "cloud_provider":
"AWS", "custom_resources_tags": [ [ "key": "purpose", "value": "outpost" ] ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/create_outpost_template"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"cloud_provider\":\"AWS\",\"custom_resources_tags\":
[{\"key\":\"purpose\",\"value\":\"outpost\"}]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ cloud_providerstring (Enum)

The cloud service provider. Valid values include:

- `AWS`
- `AZURE`
- `GCP`
- `OCI`

▶ cloud_partitionobject (Enum)

Whether the CSP environment is `COMMERCIAL` or `GOV`:

- `COMMERCIAL`: (Default) Standard cloud deployment typically used for private and public sector organizations that do not require isolated government-specific infrastructure.
- `GOV`: Government cloud environments for compatibility with FedRAMP-certified tenants.

▶ custom_resources_tagsarray
REQUEST

```
{ "request_data": { "cloud_provider": "AWS", "custom_resources_tags": [ { "key": "purpose", "value": "outpost" } ] } }
```

Responses

Successful Response

Body
application/json
▼ replyobject

The main payload of the response, containing a link to download the outpost template

RESPONSE

```
{ "reply": { "automated": {}, "manual": { "TF": "https://qa2-test-9999219916297-cloud-onboarding-
templates.storage.googleapis.com/outposts/aws/tf-12711a531d51412d930a647ed2fdacdf-1743447640.tar.gz?
Expires=1744052440&GoogleAccessId=api-pod%40qa2-test-9999219916297.iam.gserviceaccount.com&Signature=&response-
content-disposition=attachment%3Bfilename%3Doutposts_aws_tf-12711a531d51412d930a647ed2fdacdf-1743447640.tar.gz" } } }
```

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code
▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.7.4.2 | Edit an outpost

post /public_api/v1/cloud_onboarding/edit_outpost

Edit the custom resource tags of the specified outpost. The template must be applied in the CSP after editing.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_outpost'
-d '{ "request_data" : { "id" : "id", "custom_resources_tags" : [ { "value" : "value", "key" : "key" }, { "value" :
"value", "key" : "key" } ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\",\"custom_resources_tags\":[{\"key\":\"string\",\"value\":\"string\"}]}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/edit_outpost", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_outpost") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
```

```
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\",\"custom_resources_tags\":[{\"key\":\"string\",\"value\":\"string\"}]}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string", "custom_resources_tags": [ { "key": "string", "value":
"string" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_outpost"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_outpost")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\",\"custom_resources_tags\":[{\"key\":\"string\",\"value\":\"string\"}]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "id": "string",
"custom_resources_tags": [ [ "key": "string", "value": "string" ] ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_outpost")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/edit_outpost", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\",\"custom_resources_tags\":
[{\"key\":\"string\",\"value\":\"string\"}]}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_outpost"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\",\"custom_resources_tags\":[{\"key\":\"string\",\"value\":\"string\"}]}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/edit_outpost"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\",\"custom_resources_tags\":
[{\"key\":\"string\",\"value\":\"string\"}]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstring

▶ custom_resources_tagsarray

REQUEST

```
{ "request_data": { "id": "example", "custom_resources_tags": [ { "key": "example", "value": "example" } ] } }
```

Responses

Successful Response

Body

application/json

▼ replyobject

▶ automatedobject

▶ manualobject

RESPONSE
{ "reply": { "automated": { "link": "example", "tracking_guid": "example" }, "manual": { "TF/ARM": "example" } } }

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.7.4.3 | Get all or filtered outposts

post /public_api/v1/cloud_onboarding/get_outposts

Get a list of all or filtered outposts.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_outposts'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filter_data\":
{\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
```

```
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/get_outposts", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_outposts") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"filter_data\":{\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filter_data": { "sort": [ { "FIELD": "string", "ORDER": "string" } ],
"filter": { "OR": [ { "SEARCH_FIELD": "string", "SEARCH_TYPE": "string", "SEARCH_VALUE": "string" } ] }, "paging": {
"from": 0, "to": 0 } } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_outposts"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_outposts")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"filter_data\":{\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["filter_data": [
"sort": [ [ "FIELD": "string", "ORDER": "string" ] ], "filter": ["OR": [ [ "SEARCH_FIELD": "string", "SEARCH_TYPE":
"string", "SEARCH_VALUE": "string" ] ]], "paging": [ "from": 0, "to": 0 ] ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_outposts")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_outposts", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filter_data\":{\"sort\":
[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_outposts"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filter_data\":{\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_outposts"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"filter_data\":{\"sort\":
```

[{\"FIELD\":\"string\",\"ORDER\":\"string\"}],\"filter\":{\"OR\":
[{\"SEARCH_FIELD\":\"string\",\"SEARCH_TYPE\":\"string\",\"SEARCH_VALUE\":\"string\"}]},\"paging\":
{\"from\":0,\"to\":0}}}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
Body parameters
application/json
▼ request_dataobject
▶ filter_dataobject
REQUEST
Example 1
{ "request_data": { "filter_data": { "sort": [{ "FIELD": "CREATED_AT", "ORDER": "ASC" }], "filter": { "OR": [{
"SEARCH_FIELD": "CLOUD_PROVIDER", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "AWS" }, { "SEARCH_FIELD":
"CLOUD_PROVIDER", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "GCP" }] }, "paging": { "from": 0, "to": 20 } } } }
Responses

OK

Body
application/json
▼ replyobject
▶ DATAarray
▶ FILTER_COUNTinteger
▶ TOTAL_COUNTinteger
RESPONSE
Example 1
{ "reply": { "DATA": [{ "cloud_provider": "AWS", "outpost_id": "094935393dcf46128e5a2138a51bd54a", "created_at":
"1748309918599", "type": "MANAGED" }], "FILTER_COUNT": 1, "TOTAL_COUNT": 1 } }

2.7.5 | General

APIs for general tasks

2.7.5.1 | Get available regions for a CSP

post /public_api/v1/cloud_onboarding/list_regions

Get a list of all available regions for the specified cloud service provider.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/list_regions'
-d '{ "request_data" : { "cloud_provider" : "AWS" } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"cloud_provider\":\"AWS\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/list_regions", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/list_regions") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =

```
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"cloud_provider\":\"AWS\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "cloud_provider": "AWS" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/list_regions"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cloud_onboarding/list_regions")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"cloud_provider\":\"AWS\"}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["cloud_provider":
"AWS"]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/cloud_onboarding/list_regions")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/list_regions", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"cloud_provider\":\"AWS\"}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/list_regions"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"cloud_provider\":\"AWS\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/list_regions"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"cloud_provider\":\"AWS\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ cloud_providerstring (Enum)

The cloud service provider for which you want to list the regions.

▶ cloud_partitionobject (Enum)

Whether the CSP environment is `COMMERCIAL` or `GOV`:

- `COMMERCIAL`: (Default) Standard cloud deployment typically used for private and public sector organizations that do not require isolated government-specific infrastructure.
- `GOV`: Government cloud environments for compatibility with FedRAMP-certified tenants.

REQUEST

```
{ "request_data": { "cloud_provider": "AWS" } }
```

Responses

Successful Response

Body

application/json
▼ replyarray
[
▶ namestring

Name of the CSP region.

▶ valuestring
▶ typestring
]
RESPONSE
{ "reply": [{ "name": "example", "value": "example", "type": "example" }] }

Invalid Client Request Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.7.5.2 | Get approved Azure tenants

post /public_api/v1/cloud_onboarding/get_azure_approved_tenants

In order to onboard an Azure tenant to Cortex, Cortex must first be added as an enterprise-approved application on the tenant. Get a list of all the Azure tenants that are already enterprise-approved.

Required license: Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"cloud_partition\":\"COMMERCIAL\"}"
headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cloud_onboarding/get_azure_approved_tenants", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"cloud_partition\":\"COMMERCIAL\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "cloud_partition": "COMMERCIAL" }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"cloud_partition\":\"COMMERCIAL\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["cloud_partition": "COMMERCIAL"] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"cloud_partition\":\"COMMERCIAL\"}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"cloud_partition\":\"COMMERCIAL\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cloud_onboarding/get_azure_approved_tenants"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"cloud_partition\":\"COMMERCIAL\"}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ cloud_partitionobject (Enum)

Whether the CSP environment is `COMMERCIAL` or `GOV`:

- `COMMERCIAL`: (Default) Standard cloud deployment typically used for private and public sector organizations that do not require isolated government-specific infrastructure.
- `GOV`: Government cloud environments for compatibility with FedRAMP-certified tenants.

Allowed values:"COMMERCIAL""GOV"
REQUEST
```
{ "cloud_partition": "COMMERCIAL" }
```
Responses

Successful Response

Body
application/json
▼ replyobject

The main payload of the response, containing the Azure tenant ID and whether the tenant is approved.

RESPONSE
```
{ "reply": { "tenants": [ { "tenant_id": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx", "is_still_approved": true } ] } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.8 | Cloud Infrastructure Entitlement Management APIs

2.8.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instancehttps://cortex-panw.stoplight.io/docs/cortex-cloud/iul4tcqnj800b-cloud-infrastructure-entitlement-management-ap-is).

API for searching and retrieving access information within the Cloud Infrastructure Entitlement Management(CIEM) module.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: Cortex Cloud

2.8.1.1 | Servers

https://api-yourfqdn

2.8.2 | CIEM access

Search CIEM access

2.8.2.1 | Search CIEM Access

post /public_api/v1/ciem/access/search

Retrieves a list of access entries based on specified filters, sorting, and pagination.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ x-xdr-auth-id String required

{api_key_id}

Example: `xXdrAuthId_example`

▼ Authorization String required

{api_key}

Example: `authorization_example`

▼ Content-Type String required

Specifies the request body format.

Example: `contentType_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: xXdrAuthId_example' -H 'Authorization: authorization_example' -H 'Content-Type:
contentType_example'
'https://api-yourfqdn/public_api/v1/ciem/access/search'
-d '{ "filter" : { "AND" : [ { "search_field" : "dest_cloud_resource_id", "search_type" : "EQ", "search_value" : "abc"
} ] }, "sort" : [ { "field" : "dest_cloud_resource_id", "order" : "DESC" } ], "metadata" : { "next_page_token" :
"some_base64_string" } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}" headers = { 'x-xdr-auth-id': "SOME_STRING_VALUE", 'Authorization':
"SOME_STRING_VALUE", 'Content-Type': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/ciem/access/search", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/ciem/access/search")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["Authorization"] = 'SOME_STRING_VALUE'
request["Content-Type"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": { "AND": [ { "search_field": "dest_cloud_resource_id", "search_type": "EQ",
"search_value": "abc" } ] }, "sort": [ { "field": "dest_cloud_resource_id", "order": "DESC" } ], "metadata": {
"next_page_token": "some_base64_string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/ciem/access/search");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("Authorization",
"SOME_STRING_VALUE"); xhr.setRequestHeader("Content-Type", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/ciem/access/search") .header("x-xdr-
auth-id", "SOME_STRING_VALUE") .header("Authorization", "SOME_STRING_VALUE") .header("Content-Type",
"SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "SOME_STRING_VALUE", "Authorization": "SOME_STRING_VALUE",
"Content-Type": "SOME_STRING_VALUE", "content-type": "application/json" ] let parameters = [ "filter": ["AND": [ [
"search_field": "dest_cloud_resource_id", "search_type": "EQ", "search_value": "abc" ] ]], "sort": [ [ "field":
"dest_cloud_resource_id", "order": "DESC" ] ], "metadata": ["next_page_token": "some_base64_string"] ] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/ciem/access/search")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/ciem/access/search", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS
=> 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
```

```
CURLOPT_POSTFIELDS => "{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}", CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "Content-
Type: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/ciem/access/search"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "Authorization:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "Content-Type: SOME_STRING_VALUE"); headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/ciem/access/search"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); request.AddHeader("Authorization",
"SOME_STRING_VALUE"); request.AddHeader("Content-Type", "SOME_STRING_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("SOME_STRING_VALUE", "{\"filter\":{\"AND\":
[{\"search_field\":\"dest_cloud_resource_id\",\"search_type\":\"EQ\",\"search_value\":\"abc\"}]},\"sort\":
[{\"field\":\"dest_cloud_resource_id\",\"order\":\"DESC\"}],\"metadata\":
{\"next_page_token\":\"some_base64_string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

required

application/json

▼ filterobject

Optional filters to apply to the search results.

▶ ANDarray

A list of filter conditions. Currently only supports AND logic.

▼ sortarray

Optional sorting criteria for the search results.

[

▶ fieldstring (Enum)required

The field to sort by.

▶ orderstring (Enum)required

The sort order.

]

▼ metadataobject

Optional metadata for pagination.

▶ next_page_tokenstring

A token provided by a previous response to fetch the next page of results.

REQUEST

default

```
{ "filter": { "AND": [ { "search_field": "dest_cloud_resource_id", "search_type": "EQ", "search_value": "abc" } ] },
"sort": [ { "field": "dest_cloud_resource_id", "order": "DESC" } ], "metadata": { "next_page_token":
"some_base64_string" } }
```

Responses

Successful response with CIEM access data.

Body

application/json

▼ dataarray

An array of access entries.

[

▶ access_levelsarray[string]

Access levels granted

▶ account_access_transformedstring

Transformed account access details

▶ dest_cloud_account_idstring

Destination account ID

▶ dest_cloud_account_namestring

Name of the destination cloud account

▶ dest_cloud_regionstring

Destination region

▶ dest_cloud_resource_idstring

Destination resource ID

▶ dest_cloud_resource_namestring

Name of the destination resource

▶ dest_cloud_resource_typestring

Type of the destination resource

▶ dest_cloud_resource_uaistring

Destination resource UAI

▶ dest_cloud_service_namestring

Name of the destination cloud service

▶ dest_categorystring (Enum)

Category of the destination entity. Valid values include:

- `Human`: All cloud, identity provider (IdP), and platform users.
- `Non-human`: Machine identities that can assume permissions and perform cloud Identity and Access Management (IAM) actions such as VMs and functions.
- `Cloud Service Account`: A category unifying AWS roles, Microsoft Azure service accounts and managed identities, and GCP service accounts.
- `IAM Group`: IAM group, which is a collection of IAM users.
- `IAM Policy`: Permission documents, such as AWS policies, Azure roles, and GCP roles.

▶ destination_access_labelsarray[string]

Labels describing access to data

▶ excessive_policies_countinteger

Number of excessive policies

▶ grantedby_cloud_entity_idstring

Granted by cloud entity ID

▶ grantedby_cloud_entity_namestring

Name of the cloud entity that granted access

▶ grantedby_cloud_entity_typestring

Type of the cloud entity that granted access

▶ grantedby_cloud_entity_uaistring

Granted by cloud entity UAI

▶ granter_categorystring

Category of the granter entity

▶ is_last_access_supportedboolean

Indicates if last access is supported

▶ last_usedstringdate-time

Timestamp of when access was last used

▶ permission_scopestring

Scope of the permission

▶ source_cloud_account_idstring

Source account ID

▶ source_cloud_account_is_vendorboolean

Indicates if the source account is a known vendor

▶ source_cloud_account_namestring

Name of the source cloud account

▶ source_cloud_regionstring

Source region

▶ source_cloud_resource_idstring

Source resource ID

▶ source_cloud_resource_namestring

Name of the source resource

▶ source_cloud_resource_typestring

Type of the source resource

▶ source_cloud_resource_uaistring

Source resource UAI

▶ source_cloud_service_namestring

Name of the source cloud service

▶ source_categorystring (Enum)

Category of the source entity. Valid values include:

- `Human`: All cloud, identity provider (IdP), and platform users.
- `Non-human`: Machine identities that can assume permissions and perform cloud Identity and Access Management (IAM) actions such as VMs and functions.
- `Cloud Service Account`: A category unifying AWS roles, Microsoft Azure service accounts and managed identities, and GCP service accounts.
- `IAM Group`: IAM group, which is a collection of IAM users.
- `IAM Policy`: Permission documents, such as AWS policies, Azure roles, and GCP roles.

▶ source_vendor_namestring

Name of the source vendor

▶ unused_actions_countinteger

Number of unused actions

]

▼ metadataobject

Metadata for pagination.

▶ next_page_tokenstring

A token to retrieve the next page of results, if available.

▼ filter_countintegerint32

The number of results after applying filters.

▼ total_countintegerint32

The total number of available results, ignoring pagination.

RESPONSE

{ "data": [{ "access_levels": ["Read", "Write"], "account_access_transformed": "admin_access", "dest_cloud_account_name": "prod-account", "dest_cloud_resource_name": "S3 Bucket", "dest_cloud_resource_type": "AWS::S3::Bucket", "dest_cloud_service_name": "Amazon S3", "dest_category": "Cloud Service Account", "destination_access_labels": [], "excessive_policies_count": 5, "grantedby_cloud_entity_name": "AdminRole", "grantedby_cloud_entity_type": "IAM Role", "granter_category": "IAM Group", "last_used": "2023-01-15T10:30:00Z", "permission_scope": "Global", "source_cloud_account_name": "dev-account", "source_cloud_account_is_vendor": false, "source_cloud_resource_name": "EC2 Instance", "source_cloud_resource_type": "AWS::EC2::Instance", "source_cloud_service_name": "Amazon EC2", "source_category": "Human", "source_vendor_name": "AWS", "unused_actions_count": 10 }], "metadata": { "next_page_token": "another_base64_string" }, "filter_count": 100, "total_count": 500 }

Bad Request. Invalid JSON.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1

{ "reply": { "err_code": 400, "err_msg": "Invalid Request Body", "err_extra": { "err_msg": "The request body contains invalid JSON or malformed parameters for CIEM Access Search." } } }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1

{ "reply": { "err_code": 401, "err_msg": "Authentication Failed", "err_extra": { "err_msg": "Invalid API key or key ID provided. Please check your authentication credentials." } } }

Unauthorized access. User does not have the required license type to run this API.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1

{ "reply": { "err_code": 402, "err_msg": "License Required", "err_extra": { "err_msg": "Your account does not have the necessary license to access the CIEM Access Search API." } } }

Forbidden access. The provided API Key does not have the required RBAC permissions to run this API.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extraobject
RESPONSE
Example 1

{ "reply": { "err_code": 403, "err_msg": "Forbidden Access", "err_extra": { "err_msg": "The provided API key lacks the required RBAC permissions for the CIEM Access Search operation." } } }

Internal server error. A unified status for API communication type errors.

Body
application/json
▼ replyobject
▶ err_codeinteger
▶ err_msgstring

▶ err_extraobject
RESPONSE
Example 1

```
{ "reply": { "err_code": 500, "err_msg": "An error occurred while processing CIEM Access Search query", "err_extra": {
"err_msg": "Internal server issue encountered during CIEM Access Search." } } }
```

2.9 | Compliance Controls API

2.9.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

API for managing compliance controls, rules and retrieving compliance results.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: Cortex Cloud

2.9.1.1 | Servers

https://api-yourfqdn

2.9.1.2 | Authentication methods

▼ XDRAuth
Api Key "x-xdr-auth-id"

API Key ID for authentication

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.

▼ XDRAuthToken
Api Key "Authorization"

API Key for authentication

Authorized requests to the API should use: **Authorization** inside **a header** with the access token.

2.9.1.2.1 | Default authentication

Please note that this documentation assumes a minimum level of authentication is required, unless explicitly stated otherwise.
It is essential to ensure that any of the following authentication mechanisms are in place to access the API endpoints:

- XDRAuth=[], XDRAuthToken

2.9.2 | Assessment profiles

Operations for managing assessment profiles

2.9.2.1 | Get assessment profiles

post /public_api/v1/compliance/get_assessment_profiles

An assessment profile uses a standard to run scans on an asset group to check whether the assets adhere to the standard.

Retrieve compliance assessment profiles with optional filtering, sorting and pagination.

- The response is concatenated using AND condition (OR is not supported)
- The maximum result set size is >100
- Offset is the zero-based number of assessment profiles from the start of the result set

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_assessment_profiles'
-d '{ "request_data" : { "pagination" : { "search_from" : 0, "search_to" : 1 }, "filters" : [ { "field" : "field",
"value" : "AssessmentProfileFilter_value", "operator" : "operator" }, { "field" : "field", "value" :
"AssessmentProfileFilter_value", "operator" : "operator" } ], "sort" : { "field" : "creation_time", "keyword" : "asc"
} } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}" headers = { 'x-xdr-
auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_assessment_profiles", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profiles") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "string", "operator": "string", "value":
"string" } ], "sort": { "field": "name", "keyword": "asc" }, "pagination": { "search_from": 0, "search_to": 100 } }
}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function ()
{ if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profiles"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_assessment_profiles")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"filters\":[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "filters": [ [ "field": "string", "operator": "string", "value": "string" ] ], "sort":
[ "field": "name", "keyword": "asc" ], "pagination": [ "search_from": 0, "search_to": 100 ] ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/get_assessment_profiles")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profiles", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}", CURLOPT_HTTPHEADER
=> [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_assessment_profiles"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filters\":[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_assessment_profiles"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"string\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobjectrequired
▶ filtersarray
▶ sortobject
▶ paginationobject
REQUEST
Example 1

```
{ "request_data": { "search_from": 0, "search_to": 50, "sort": { "field": "report_type", "keyword": "desc" },
"filters": [ { "field": "creation_time", "operator": "gte", "value": 0 }, { "field": "name", "operator": "eq",
"value": "John" } ] } }
```

Responses

Successfully retrieved assessment profiles

Body
application/json
▼ replyobject
▶ total_countinteger

Total number of records

▶ result_countinteger

Number of records matching the filter + paging

▶ assessment_profilesarray
RESPONSE

```
{ "reply": { "total_count": 925, "result_count": 1, "assessment_profiles": [ { "ID":
"472141782aff4a2f999c5e3c35745b3a", "NAME": "Assessment example", "STANDARD_ID": "2nnd684-4z14-5cs82-c1a0-
7c322b671844", "STANDARD_NAME": "CIS Amazon Linux 2 Benchmark v1.0.0", "ASSET_GROUP_ID": 1, "ASSET_GROUP_NAME": "asset
group name", "DESCRIPTION": "assessment description", "REPORT_FREQUENCY": null, "REPORT_TARGETS": [], "REPORT_TYPE":
"NONE", "ENABLED": true, "INSERT_TS": 1748259453615, "MODIFY_TS": 1748259453615, "CREATED_BY": "Generic Name",
"MODIFIED_BY": "Generic Name" } ] } }
```


Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Authentication required

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }
```

Access denied - insufficient permissions

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.2.2 | Get assessment profile by ID

post /public_api/v1/compliance/get_assessment_profile

An assessment profile uses a standard to run scans on an asset group to check whether the assets adhere to the standard.

Get details of the assessment profile specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_assessment_profile'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/get_assessment_profile", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profile") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profile"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_assessment_profile")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_assessment_profile")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_assessment_profile", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_assessment_profile"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_assessment_profile"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

Assessment profile ID

REQUEST

```
{ "request_data": { "id": "eee175cb00ef4da4a0e3091b1ee77368" } }
```

Responses

Successfully retrieved assessment profile

Body

application/json

▼ idstring

Assessment profile ID

▼ namestring

Assessment profile name

▼ descriptionstring

Description of the assessment profile

▼ enabledboolean

Whether the assessment profile is enabled

▼ standard_idstring

Standard ID

▼ standard_namestring

Standard name

▼ asset_group_idinteger

Asset Group ID

▼ asset_group_namestring

Asset Group name

▼ report_typestring

Report type

▼ report_targetsarray[string]
▼ evaluation_frequencystring
▼ creation_timestringdate-time

Assessment profile creation time

▼ modification_timestringdate-time

Assessment profile modification time

▼ created_bystring

Assessment profile creator

▼ modified_bystring

Assessment profile modified by

RESPONSE


```
{ "id": "example", "name": "example", "description": "example", "enabled": false, "standard_id": "example",
"standard_name": "example", "asset_group_id": 0, "asset_group_name": "example", "report_type": "example",
"report_targets": [ "email string" ], "evaluation_frequency": "example", "creation_time": "2020-01-01T12:00:00Z",
"modification_time": "2020-01-01T12:00:00Z", "created_by": "example", "modified_by": "example" }
```


Bad request - invalid input parameters

Body

application/json

▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field


```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Authentication required

Body

application/json

▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }

Access denied - insufficient permissions

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.2.3 | Add assessment profile

post /public_api/v1/compliance/add_assessment_profile

Create a custom compliance assessment profile that is tailored to your own business needs and organizational policies.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/add_assessment_profile'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/add_assessment_profile", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/add_assessment_profile") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "profile_name": "string", "asset_group_id": "string", "standard_id":
"string", "description": "string", "report_targets": [ "user@example.com" ], "report_type": "ALL",
"evaluation_frequency": "0 12 * * *" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/add_assessment_profile"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/add_assessment_profile")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "profile_name": "string", "asset_group_id": "string", "standard_id": "string",
"description": "string", "report_targets": ["user@example.com"], "report_type": "ALL", "evaluation_frequency": "0 12 *
* *" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/add_assessment_profile")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/add_assessment_profile", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/add_assessment_profile"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/add_assessment_profile"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
```

```
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"profile_name\":\"string\",\"asset_group_id\":\"string\",\"standard_id\":\"string\",\"description\":\"string\",\"report_targe
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * * *\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ profile_namestringrequired

Name of the assessment profile

▶ asset_group_idstringrequired

Asset Group ID

▶ standard_idstringrequired

Standard ID

▶ descriptionstring

Description of the assessment profile

▶ report_targetsarray[string]

Assessment profile targets

▶ report_typestring (Enum)

Assessment profile report type. Valid values include:

- `ALL`
- `PDF`
- `CSV`
- `NONE`

▶ evaluation_frequencystringcron

Assessment report evaluation frequency

REQUEST

```
{ "request_data": { "profile_name": "profile example", "description": "profile description example",
"evaluation_frequency": "0 12 * * *", "asset_group_id": "3", "report_type": "ALL", "standard_id": "532ac684-451c-
5c789-b1a8-7c325b678843", "report_targets": [ "user@company.com" ] } }
```

Responses

Successfully created assessment profile

Body
application/json
▼ successboolean

Whether the assessment profile creation succeeded

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Authentication required

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }

Access denied - insufficient permissions

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }

Conflict - duplicate resource

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": {} } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.2.4 | Edit assessment profile

post /public_api/v1/compliance/edit_assessment_profile

Edit an existing compliance custom assessment profile.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/edit_assessment_profile'
-d '{ "request_data" : { "standard_id" : "standard_id", "profile_name" : "profile_name", "asset_group_id" : 0,
"evaluation_frequency" : "0 12 * * *", "description" : "description", "report_targets" : [ "report_targets",
"report_targets" ], "id" : "id", "report_type" : "ALL", "enabled" : "yes" } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"\":{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-
type': "application/json" } conn.request("POST", "/public_api/v1/compliance/edit_assessment_profile", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/edit_assessment_profile") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"\":{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "": { "request_data": { "id": "string", "enabled": "yes", "profile_name": "string",
"description": "string", "report_targets": [ "user@example.com" ], "report_type": "ALL", "evaluation_frequency": "0 12
* * *", "asset_group_id": 0, "standard_id": "string" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/edit_assessment_profile"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/edit_assessment_profile")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"\":
{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["": ["request_data": [ "id": "string", "enabled": "yes", "profile_name": "string", "description":
"string", "report_targets": ["user@example.com"], "report_type": "ALL", "evaluation_frequency": "0 12 * * *",
"asset_group_id": 0, "standard_id": "string" ]]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/edit_assessment_profile")! as URL, cachePolicy:
```

```
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/edit_assessment_profile", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"\":{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-
xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/edit_assessment_profile"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"\":{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/edit_assessment_profile"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"\":{\"request_data\":
{\"id\":\"string\",\"enabled\":\"yes\",\"profile_name\":\"string\",\"description\":\"string\",\"report_targets\":
[\"user@example.com\"],\"report_type\":\"ALL\",\"evaluation_frequency\":\"0 12 * *
*\",\"asset_group_id\":0,\"standard_id\":\"string\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

required

application/json

▼ object

▶ request_dataobject

REQUEST

Example 1

```
{ "request_data": { "id": "48e2f6a9fdc049479e9c6a8eda0bd163", "control_name": "Control 1" } }
```

Responses

Successfully updated assessment profile

Body

application/json

▼ successboolean

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
```

{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Authentication required

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }

Access denied - insufficient permissions

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Conflict - duplicate resource

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 0, "err_msg": "example", "err_extra": {} } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.2.5 | Delete assessment profile

post /public_api/v1/compliance/delete_assessment_profile

Delete an assessment profile specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/delete_assessment_profile'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/delete_assessment_profile", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/delete_assessment_profile") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/delete_assessment_profile"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/compliance/delete_assessment_profile") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"request_data\":{\"id\":\"string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/delete_assessment_profile")! as URL, cachePolicy:
```

```
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/delete_assessment_profile", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/delete_assessment_profile"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/delete_assessment_profile"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

Assessment profile ID

REQUEST

```
{ "request_data": { "id": "f9f764717b284e9483f9c1210ed3149d" } }
```

Responses

Successfully deleted assessment profile

Body

application/json

▼ successboolean

Whether the assessment profile deletion succeeded

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```

Authentication required

Body

application/json

▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }

Access denied - insufficient permissions

Body
application/json
▼ replyobject
▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.3 | Assessment results

Operations for managing assessment results

2.9.3.1 | Get assessment profile results

post /public_api/v1/compliance/get_assessment_results

Retrieve assessment profile results with optional filtering based on the last successful evaluation.

Filtering Support:

- Field (`labels`): `contains`, `not_contains`

Note: This API does not support sorting or pagination. Sorting will not take effect even if it is specified in the payload. The results will not return the results based on sorting'

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_assessment_results'
-d '{ "request_data" : { "filters" : [ { "field" : "labels", "operator" : "contains", "value" : "aws" } ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_assessment_results", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_assessment_results") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "labels", "operator": "contains", "value":
"aws" } ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange",
function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-yourfqdn/public_api/v1/compliance/get_assessment_results"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_assessment_results")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"filters\":[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["filters": [ [ "field": "labels", "operator": "contains", "value": "aws" ] ]]] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/get_assessment_results")! as
URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_assessment_results", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_assessment_results"); struct curl_slist *headers = NULL; headers =
```

```
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filters\":[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}"); CURLcode ret
= curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_assessment_results"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"labels\",\"operator\":\"contains\",\"value\":\"aws\"}]}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobjectrequired

▶ filtersarray

Array of filter objects

REQUEST

Example 1

```
{ "request_data": { "filters": [ { "field": "labels", "operator": "contains", "value": "aws" } ] } }
```

Responses

Successfully retrieved assessment profile results

Body

application/json

▼ replyobject

▶ total_countinteger

Total number of assessment results available

▶ result_countinteger

Number of assessment results matching the applied filters

▶ standard_filter_countinteger

Count from standard filter processing

▶ standard_total_countinteger

Total count from standard processing

▶ dataarray

Array of assessment profile results

RESPONSE

```
{ "reply": { "total_count": 150, "result_count": 25, "standard_filter_count": 25, "standard_total_count": 150, "data":
[ { "TYPE": "standard", "SCORE": null, "ASSET_GROUP_NAME": null, "ASSET_GROUP_ID": null, "ADDITIONAL_DATA": null,
"LAST_EVALUATION_TIME": 1751533328000, "STANDARD_NAME": "CIS Amazon Elastic Kubernetes Service (EKS) Benchmark v1.4",
"PROFILES_COUNT": 3, "STANDARD_ID": 9101546381587280000, "LABELS": [ "eks" ], "PATH": [ "CIS Amazon Elastic Kubernetes
Service (EKS) Benchmark v1.4" ], "FAILED_CONTROLS_SEVERITY": [ { "value": "CRITICAL", "count": 0, "pretty_name":
"Critical" }, { "value": "HIGH", "count": 0, "pretty_name": "High" }, { "value": "MEDIUM", "count": 1, "pretty_name":
"Medium" }, { "value": "LOW", "count": 2, "pretty_name": "Low" }, { "value": "INFORMATIONAL", "count": 0,
"pretty_name": "Informational" } ], "CONTROLS_STATUS": [ { "value": "PASSED", "count": 0, "pretty_name": "Passed" }, {
"value": "NOT_ASSESSED", "count": 153, "pretty_name": "Not Assessed" }, { "value": "FAILED", "count": 0,
"pretty_name": "Failed" } ], "ASSESSMENT_PROFILE_REVISION": null } ] } }
```

Bad request - invalid input parameters

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field


```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }
```


Authentication required

Body

application/json

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }
```


Access denied - insufficient permissions

Body

application/json

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }
```


Internal server error

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.4 | Controls

Operations for managing compliance controls

2.9.4.1 | Get compliance controls

post /public_api/v1/compliance/get_controls

Compliance controls are measures related to the standard that ensure compliance and mitigate risks. Controls are built from one or more rules, the specific checks that run on an asset. Controls can be grouped into categories, for example RBAC and Pod security.

Retrieve compliance control details with optional filtering, sorting and pagination.

- The response is concatenated using AND condition (OR is not supported)
- The maximum result set size is >100
- Offset is the zero-based number of assessment profiles from the start of the result set

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_controls'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_controls", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_controls") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "eq", "value": "string" }
], "sort": { "field": "name", "keyword": "asc" }, "search_from": 0, "search_to": 100 } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_controls"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_controls") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "filters": [ [ "field": "name", "operator": "eq", "value": "string" ] ], "sort": [
"field": "name", "keyword": "asc" ], "search_from": 0, "search_to": 100 ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_controls")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_controls", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
```

```
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}", CURLOPT_HTTPHEADER => [ "content-
type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_controls"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_controls"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject
▶ filtersarray
▶ sortobject
▶ search_frominteger

Integer representing the starting offset within the query result set from which you want compliance controls returned. Compliance controls are returned as a zero-based list. Any compliance control indexed less than this value is not returned in the final result set and defaults to zero.

▶ search_tointeger

Integer representing the end offset within the result set after which you do not want compliance controls returned. Compliance controls in the compliance control list that are indexed higher than this value are not returned in the final results set. Defaults to >100, which returns all compliance controls to the end of the list.

REQUEST basic_filter

```
{ "request_data": { "filters": [ { "field": "name", "operator": "contains", "value": "Access Enforcement" } ] } }
{ "request_data": { "filters": [ { "field": "is_custom", "operator": "in", "value": [ "yes" ] } ] } }
{ "request_data": { "filters": [ { "field": "creation_time", "operator": "gte", "value": 1640995200000 }, { "field":
"creation_time", "operator": "lte", "value": 1672531200000 } ] } }
```

Responses

Successfully retrieved controls

Body
application/json
▼ replyobject
▶ total_countinteger

Total number of controls

▶ result_countinteger

Number of controls matching filters + paging

▶ controlsarray

RESPONSE

```
{ "reply": { "total_count": 0, "result_count": 0, "controls": [ { "id": "example", "name": "example", "description":
"example", "category": "example", "subcategory": "example", "creation_time": 0, "modification_time": 0, "created_by":
"example", "modified_by": "example", "is_custom": false } ] } }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```

Internal server error

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.4.2 | Get compliance control by ID

post /public_api/v1/compliance/get_control

Get details of the compliance control specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/get_control", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/compliance/get_control");
xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_control") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\"}}") .asString();
```

```
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_control")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_control"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_control"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

Compliance control ID

REQUEST

Example 1

```
{ "request_data": { "id": "ede175cb30ef4dd4a0e3031b1ee77868" } }
```

Responses

Successfully retrieved control

Body

application/json

▼ controlobject

▶ CATEGORYstring

▶ CATEGORY_DESCRIPTIONstring

▶ SUBCATEGORYstring

▶ SUBCATEGORY_DESCRIPTIONstring

▶ CONTROL_IDstring

▶ STANDARDSarray[string]

▶ CONTROL_NAMEstring

▶ SEVERITYstring

▶ SUPPORTEDboolean

▶ INSERTION_TIMEinteger

▶ MODIFICATION_TIMEinteger

▶ MODIFIED_BYnull

▶ CREATED_BYstring

▶ DESCRIPTIONstring

▶ MITIGATIONnull

▶ ADDITIONAL_DATAarray

▶ COMPLIANCE_RULESarray

▶ RULESinteger

▶ REVISIONstring

▶ IMPACTnull

▶ AUTOMATION_STATUSstring

▶ AUDIT_PROCEDUREnull

▶ ENABLEDboolean

▶ IS_CUSTOMboolean

▶ STATUSstring

RESPONSE

{ "control": { "CATEGORY": "example", "CATEGORY_DESCRIPTION": "example", "SUBCATEGORY": "example", "SUBCATEGORY_DESCRIPTION": "example", "CONTROL_ID": "example", "STANDARDS": ["example"], "CONTROL_NAME": "example", "SEVERITY": "example", "SUPPORTED": false, "INSERTION_TIME": 0, "MODIFICATION_TIME": 0, "MODIFIED_BY": null, "CREATED_BY": "example", "DESCRIPTION": "example", "MITIGATION": null, "ADDITIONAL_DATA": [{}], "COMPLIANCE_RULES": [{}], "RULES": 0, "REVISION": "example", "IMPACT": null, "AUTOMATION_STATUS": "example", "AUDIT_PROCEDURE": null, "ENABLED": false, "IS_CUSTOM": false, "STATUS": "example" } }

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.4.3 | Add new control

post /public_api/v1/compliance/add_control

Create a custom compliance control.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/add_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}" headers
= { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/add_control", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/add_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}" response
= http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_name": "string", "description": "string", "category":
"string", "subcategory": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/compliance/add_control");
xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/add_control") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "control_name": "string", "description": "string", "category": "string",
"subcategory": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/add_control")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/add_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/add_control"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}");
CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/add_control"); var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\": {\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ control_namestringrequired

Name of the compliance control

▶ descriptionstring

Description of the compliance control

▶ categorystringrequired

Compliance control category

▶ subcategorystring

Compliance control subcategory

REQUEST
Example 1

```
{ "request_data": { "control_name": "control name", "category": "Network Configuration", "subcategory": "4.2" } }
```

Responses

Control added successfully

Body
application/json
▼ successboolean

Whether the compliance control creation was successful

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.4.4.4 | Edit existing control

post /public_api/v1/compliance/edit_control

Edit an existing compliance custom compliance control.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/edit_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/edit_control", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/edit_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string", "control_name": "string", "description": "string",
"category": "string", "subcategory": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/compliance/edit_control");
xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/edit_control") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "id": "string", "control_name": "string", "description": "string", "category":
"string", "subcategory": "string" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/edit_control")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/edit_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
```

```
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/edit_control"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/edit_control"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"id\":\"string\",\"control_name\":\"string\",\"description\":\"string\",\"category\":\"string\",\"subcategory\":\"string\"}}"
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idstringrequired

Compliance control ID

▶ control_namestring

Name of the compliance control

▶ descriptionstring

Description of the compliance control

▶ categorystring

Compliance control category

▶ subcategorystring

Compliance control subcategory

REQUEST
Example 1

```
{ "request_data": { "id": "48e2f6a9fcc049579e9c6b8eda0bd123", "control_name": "Great new name" } }
```

Responses

Control updated successfully

Body
application/json
▼ successboolean

Whether the custom compliance control was edited successfully

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
```

{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.4.5 | Delete control

post /public_api/v1/compliance/delete_control

Delete a compliance control specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/delete_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\": {\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/delete_control", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/delete_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/delete_control"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/delete_control")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\"}}") .asString();
```

```
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/delete_control")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/delete_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/delete_control"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/delete_control"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idstringrequired

Compliance control ID

REQUEST
Example 1

```
{ "request_data": { "id": "f9f744717b284e9383f9c1210ad3143d" } }
```

Responses

Control deleted successfully

Body
application/json
▼ successboolean

Whether the compliance control was successfully deleted

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```

Resource not found

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id":
"eee175cb00ef4da4a0e3091b1ee77368" } } }
```

Internal server error

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.4.6 | Get control by revision

post /public_api/v1/compliance/get_control_by_revision

Get details of the compliance control specified by its revision ID, including inactive controls.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
```

```
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_control_by_revision'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_revision\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/v1/compliance/get_control_by_revision", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_control_by_revision") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_revision\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_revision": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_control_by_revision"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_control_by_revision")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"control_revision\":\"string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["control_revision": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_control_by_revision")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_control_by_revision", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"control_revision\":\"string\"}}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_control_by_revision"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"control_revision\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_control_by_revision"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"control_revision\":\"string\"}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ control_revisionstringrequired

Control revision ID

REQUEST

Example 1

```
{ "request_data": { "control_revision": "4983640851729713422" } }
```

Responses

Successfully retrieved control

Body

application/json

▼ replyobject

▶ controlobject

RESPONSE

```
{ "reply": { "control": { "id": "example", "name": "example", "description": "example", "category": "example",
"subcategory": "example", "creation_time": 0, "modification_time": 0, "created_by": "example", "modified_by":
"example", "is_custom": false } } }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id":
"eee175cb00ef4da4a0e3091b1ee77368" } } }
```


Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.5 | Rules

Operations for managing compliance rules

2.9.5.1 | Add compliance rules to a compliance control

post /public_api/v1/compliance/add_rules_to_control

Add compliance rules to the specific compliance control.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/add_rules_to_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_id\":\"string\",\"rules\":
[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/add_rules_to_control", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/add_rules_to_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_id\":\"string\",\"rules\":
[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_id": "string", "rules": [ { "name": "string", "description":
"string", "type": "Identity", "logical_id": "string", "severity": "low", "scannable_assets": [ "KUBERNETES_NODE" ],
"remediation_steps": "string", "generate_findings": true, "generate_issues": true, "generate_scan_logs": true } ] }
}); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function ()
{ if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/add_rules_to_control"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/add_rules_to_control")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"control_id\":\"string\",\"rules\":
[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "control_id": "string", "rules": [ [ "name": "string", "description": "string",
"type": "Identity", "logical_id": "string", "severity": "low", "scannable_assets": ["KUBERNETES_NODE"],
"remediation_steps": "string", "generate_findings": true, "generate_issues": true, "generate_scan_logs": true ] ] ]]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/add_rules_to_control")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/add_rules_to_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"control_id\":\"string\",\"rules\":
[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/add_rules_to_control"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"control_id\":\"string\",\"rules\":
```

[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/add_rules_to_control"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"control_id\":\"string\",\"rules\":
[{\"name\":\"string\",\"description\":\"string\",\"type\":\"Identity\",\"logical_id\":\"string\",\"severity\":\"low\",\"scannab
[\"KUBERNETES_NODE\"],\"remediation_steps\":\"string\",\"generate_findings\":true,\"generate_issues\":true,\"generate_scan_logs
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
Body parameters
required
application/json
▼ request_dataobject
▶ control_idstringrequired

Compliance control ID

▶ rulesarrayrequired
REQUEST
Example 1
{ "request_data": { "control_id": "0b0b5354d06d43ffc3d7465858378135", "rules": [{ "name": "Rule 1", "description":
"Description 1", "type": "Identity", "logical_id": "2b16a9f3-260x2-4xsf0cc-a9091", "severity": "high",
"scannable_assets": ["KUBERNETES_NODE"], "remediation_steps": "Run the following command...", "generate_findings":
true, "generate_issues": true, "generate_scan_logs": true }, { "name": "Rule 2", "description": "Description 2",
"type": "Identity", "logical_id": "2b16a9f3-cc2x602-4vvxXccXfn0c1", "scannable_assets": ["KUBERNETES_NODE"],
"generate_findings": false, "generate_issues": true, "generate_scan_logs": true }] } }
Responses

Rules added successfully

Body
application/json
▼ successboolean

Whether the rules were added successfully

RESPONSE
{ "success": false }

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.5.2 | Delete rules from control

post /public_api/v1/compliance/delete_rules_from_control

Remove specific rules from the specified compliance control.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/delete_rules_from_control'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_id\":\"string\",\"rules_ids\":[\"string\"]}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-
type': "application/json" } conn.request("POST", "/public_api/v1/compliance/delete_rules_from_control", payload,
headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/delete_rules_from_control") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_id\":\"string\",\"rules_ids\":[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_id": "string", "rules_ids": [ "string" ] } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/delete_rules_from_control"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/compliance/delete_rules_from_control") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"request_data\":{\"control_id\":\"string\",\"rules_ids\":
[\"string\"]}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "control_id": "string", "rules_ids": ["string"] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/delete_rules_from_control")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/delete_rules_from_control", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"control_id\":\"string\",\"rules_ids\":[\"string\"]}}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/delete_rules_from_control"); struct curl_slist *headers = NULL; headers
```

```
= curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"control_id\":\"string\",\"rules_ids\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/delete_rules_from_control"); var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":{\"control_id\":\"string\",\"rules_ids\":[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ control_idstringrequired

Compliance control ID

▶ rules_idsarray[string]required

List of rule IDs to delete

REQUEST
Example 1

```
{ "request_data": { "control_id": "48e2f6a9cdc049479e3c6a8eda3bd161", "rules_ids": [ "2b26a9f3-ca2x602-4vvxXccXf3c1" ] } }
```

Responses

Rules deleted successfully

Body
application/json
▼ successboolean

Whether the rules were successfully deleted from the compliance control

RESPONSE

```
{ "success": false }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.6 | Categories

Operations for retrieving categories and subcategories

2.9.6.1 | Get categories and subcategories

post /public_api/v1/compliance/get_control_categories_and_subcategories

Retrieve available compliance control categories and subcategories.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{}}" headers = {
'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_control_categories_and_subcategories", payload, headers) res = conn.getresponse() data
= res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-
auth-id"] = 'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": {} }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories") .header("x-xdr-auth-id",
"REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": []] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
```

```
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"request_data\":{}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_control_categories_and_subcategories");
var request = new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
REQUEST
Example 1

```
{ "request_data": {} }
```

Responses

Successfully retrieved categories and subcategories

Body
application/json
▼ replyobject
▶ dataobject
RESPONSE

```
{ "reply": { "data": { "categories": [ "example" ], "subcategories": [ "example" ] } } }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.7 | Results

Operations for retrieving compliance results and findings

2.9.7.1 | Get control failed results

post /public_api/v1/compliance/get_control_failed_results

Get the failed findings and issues for a specific compliance control.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_control_failed_results'
-d ''
```

```
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}" headers = {
'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_control_failed_results", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_control_failed_results") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_revision": "string", "assessment_profile_revision": "string",
"last_evaluation_time": 0 } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_control_failed_results"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/compliance/get_control_failed_results") .header("x-xdr-auth-id", "REPLACE_KEY_VALUE")
.header("content-type", "application/json") .body("{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "control_revision": "string", "assessment_profile_revision": "string",
"last_evaluation_time": 0 ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/get_control_failed_results")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_control_failed_results", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_control_failed_results"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}"); CURLcode
ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_control_failed_results"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ control_revisionstringrequired

Compliance control revision ID

▶ assessment_profile_revisionstringrequired

Assessment profile revision ID

▶ last_evaluation_timeintegerrequiredint64

Last evaluation timestamp (epoch time in milliseconds)

REQUEST



{ "request_data": { "control_revision": "example", "assessment_profile_revision": "example", "last_evaluation_time": 0 } }

Responses

Successfully retrieved failed results

Body
application/json
▼ replyobject
▶ dataobject
RESPONSE
Example 1
{ "reply": { "data": { "findings": { "ids": ["45667890n85678908765456789bkk"], "value": 1 }, "issues": [{ "name": "SEV_020_LOW", "pretty_name": "Low", "value": 0, "ids": [] }, { "name": "SEV_030_MEDIUM", "pretty_name": "Medium", "value": 0, "ids": [] }, { "name": "SEV_040_HIGH", "pretty_name": "High", "value": 1, "ids": ["4537893ijnmskiu2y6t5rxt7y789ok"] }, { "name": "SEV_050_CRITICAL", "pretty_name": "Critical", "value": 0, "ids": [] }] } } }

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.7.2 | Get rule failed results

post /public_api/v1/compliance/get_rule_failed_results

Get the failed findings and issues for a specific rule.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_rule_failed_results'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_rule_failed_results", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_rule_failed_results") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "control_revision": "string", "assessment_profile_revision": "string",
"last_evaluation_time": 0, "rule_id": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_rule_failed_results"); xhr.setRequestHeader("x-xdr-auth-id",
"REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_rule_failed_results")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "control_revision": "string", "assessment_profile_revision": "string",
"last_evaluation_time": 0, "rule_id": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_rule_failed_results")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_rule_failed_results", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_rule_failed_results"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_rule_failed_results"); var request =
new RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-
type", "application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"control_revision\":\"string\",\"assessment_profile_revision\":\"string\",\"last_evaluation_time\":0,\"rule_id\":\"string\"}}
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject
▶ control_revisionstringrequired

Compliance control revision ID

▶ assessment_profile_revisionstringrequired

Assessment profile revision ID

▶ last_evaluation_timeintegerrequiredint64

Last evaluation timestamp (epoch time in milliseconds)

▶ rule_idstringrequired

Rule ID

REQUEST

```
{ "request_data": { "control_revision": "example", "assessment_profile_revision": "example", "last_evaluation_time": 0, "rule_id": "example" } }
```

Responses

Successfully retrieved rule failed results

Body
application/json
▼ replyobject
▶ dataobject

RESPONSE

Example 1

```
{ "reply": { "data": { "findings": { "ids": [ "45667890n85678908765456789bkk" ], "value": 1 }, "issues": [ { "name": "SEV_020_LOW", "pretty_name": "Low", "value": 0, "ids": [] }, { "name": "SEV_030_MEDIUM", "pretty_name": "Medium", "value": 0, "ids": [] }, { "name": "SEV_040_HIGH", "pretty_name": "High", "value": 1, "ids": [ "4567893ijnmskiu7y6t5rxt6y789ok" ] }, { "name": "SEV_050_CRITICAL", "pretty_name": "Critical", "value": 0, "ids": [] } ] } } }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details
RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.8 | Reports

Operations for managing reports

2.9.8.1 | Get compliance reports

post /public_api/v1/compliance/get_reports

Retrieve archived compliance assessment reports with optional filtering, sorting and pagination.

- The response is concatenated using AND condition (OR is not supported)
- The maximum result set size is >100
- Offset is the zero-based number of assessment profiles from the start of the result set

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_reports'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_reports", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_reports") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "standard_name", "operator": "eq", "value":
"string" } ], "sort": { "field": "standard_name", "keyword": "asc" }, "search_from": 0, "search_to": 1 } }); const xhr
= new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_reports"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_reports") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "filters": [ [ "field": "standard_name", "operator": "eq", "value": "string" ] ],
"sort": [ "field": "standard_name", "keyword": "asc" ], "search_from": 0, "search_to": 1 ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/get_reports")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_reports", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_reports"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filters\":[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_reports"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"standard_name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"standard_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":1}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobjectrequired

▶ filtersarray

Optional filters to apply to the reports

▶ sortobject

Sorting configuration

▶ search_frominteger

Starting index for pagination

▶ search_tointeger

Ending index for pagination

REQUEST basic_request

```
{ "request_data": { "search_from": 0, "search_to": 1, "filters": [ { "field": "standard_name", "operator": "neq",
"value": "PCI DSS v4.0.1" } ] } }
{ "request_data": { "search_from": 0, "search_to": 25, "filters": [ { "field": "score", "operator": "gte", "value": 80
} ], "sort": { "field": "score", "keyword": "desc" } } }
{ "request_data": { "search_from": 0, "search_to": 50, "filters": [ { "field": "standard_name", "operator": "eq",
"value": "SOC2" }, { "field": "evaluation_time", "operator": "gte", "value": 1640995200000 } ], "sort": { "field":
"evaluation_time", "keyword": "desc" } } }
```

Responses

Successfully retrieved compliance reports

Body

application/json

▼ replyobject

▶ total_countinteger

Total number of reports in the archive

▶ result_countinteger

Number of reports returned in this response (filter + paging)

▶ filter_countinteger

Number of reports matching the filter criteria

▶ reportsarray

List of compliance reports

RESPONSE

{ "reply": { "total_count": 0, "result_count": 0, "filter_count": 0, "reports": [{ "report_id": 2, "standard_name": "Secure Controls Framework (SCF) v2022.2.1", "assessment_profile": "test-p1", "asset_group": "Asset group for AWS, Azure & GCP", "score": 63, "controls_status": [{ "count": 11, "value": "PASSED", "pretty_name": "Passed" }, { "count": 1027, "value": "NOT_ASSESSED", "pretty_name": "Not assessed" }, { "count": 19, "value": "FAILED", "pretty_name": "Failed" }], "failed_controls_severity": [{ "count": 1, "value": "CRITICAL", "pretty_name": "Critical" }, { "count": 11, "value": "HIGH", "pretty_name": "High" }, { "count": 5, "value": "MEDIUM", "pretty_name": "Medium" }, { "count": 2, "value": "LOW", "pretty_name": "Low" }, { "count": 0, "value": "INFORMATIONAL", "pretty_name": "Informational" }], "evaluation_time": 1759305778000, "assessment_profile_id": "ddc31d5742ba4480b6d1c940c51651c2", "cvs_file_deleted": false }] } }

Bad request - invalid input parameters for reports

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_score_value
{ "reply": { "err_code": 400, "err_msg": "Invalid score value. Score must be between 0 and 100", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'contains' for field 'score'. Allowed operators: gte, lte, eq, neq", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid sort field. Allowed fields: standard_name, assessment_profile_name, asset_group_name, score, evaluation_time", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field 'invalid_field'. Allowed fields: standard_name, assessment_profile_name, asset_group_name, score, evaluation_time", "err_extra": {} } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.9 | Standards

Operations for managing standards

2.9.9.1 | Get compliance standards

post /public_api/v1/compliance/get_standards

Retrieve compliance standards with optional filtering, sorting and pagination.

- The response is concatenated using AND condition (OR is not supported)
- The maximum result set size is >100
- Offset is the zero-based number of assessment profiles from the start of the result set

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_standards'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}" headers = { 'x-xdr-
auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/get_standards", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_standards") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "name", "operator": "eq", "value": "string" }
], "sort": { "field": "name", "keyword": "asc" }, "pagination": { "search_from": 0, "search_to": 100 } } }); const xhr
= new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_standards"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_standards")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "filters": [ [ "field": "name", "operator": "eq", "value": "string" ] ], "sort": [
"field": "name", "keyword": "asc" ], "pagination": [ "search_from": 0, "search_to": 100 ] ]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/v1/compliance/get_standards")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_standards", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}", CURLOPT_HTTPHEADER
=> [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_standards"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"filters\":[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_standards"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"name\",\"operator\":\"eq\",\"value\":\"string\"}],\"sort\":
{\"field\":\"name\",\"keyword\":\"asc\"},\"pagination\":{\"search_from\":0,\"search_to\":100}}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject
▶ filtersarray

Array of filter conditions

▶ sortobject
▶ paginationobject
REQUEST basic_request

```
{ "request_data": { "pagination": { "search_from": 0, "search_to": 49 } } }
{ "request_data": { "filters": [ { "field": "is_custom", "operator": "in", "value": [ "yes" ] }, { "field": "labels", "operator": "contains", "value": "aws" } ], "sort": { "field": "insertion_time", "keyword": "desc" }, "pagination": { "search_from": 0, "search_to": 24 } } }
{ "request_data": { "filters": [ { "field": "labels", "operator": "contains", "value": "security" }, { "field": "is_custom", "operator": "in", "value": [ "yes" ] } ] } }
{ "request_data": { "filters": [ { "field": "insertion_time", "operator": "gte", "value": 1640995200000 }, { "field": "insertion_time", "operator": "lte", "value": 1672531200000 } ], "sort": { "field": "insertion_time", "keyword": "desc" } } }
```

Responses

Successfully retrieved standards

Body
application/json
▼ total_countinteger

Total number of standards in the system

▼ result_countinteger

Number of standards matching the filter criteria + paging

▼ standardsarray
[
▶ idstring

Standard ID

▶ namestring

Standard name

▶ descriptionstring

Description of the standard

▶ publisherstring

Standard publisher/organization

▶ labelsarray[string]

List of labels for categorization

▶ insertion_timeintegerint64

Creation timestamp (epoch)

▶ created_bystring

User who created the standard

▶ is_customboolean

Whether this is a custom standard

▶ controls_countinteger

Number of associated controls

▶ controls_idsarray[string]

List of associated control IDs

]

RESPONSE

success_response


```
{ "reply": { "total_count": 17, "result_count": 2, "standards": [ { "id": "394fc8fc210645f6af8bb4267321482a", "name":
"standard name", "description": "convert ...", "version": "", "assessments_profiles_count": 0, "controls_ids": [
"0b0b5304d06d44ffb3d7465855378185", "98497e7bf21f413b9df0d84ccb8857d0" ], "labels": [ "aws", "azure", "gcp" ],
"revision": -6043636965775741000, "publisher": null, "release_date": "2025-06-18", "created_date": "2025-06-18",
"created_by": "Palo Alto Networks", "insert_ts": 1750247438000, "modify_ts": 1750247439000, "is_custom": false }, {
"id": "36ed307155e446938f157e3ed214fd72", "name": "standard name ...", "description": "", "version": "",
"assessments_profiles_count": 0, "controls_ids": [ "0b0b5304d06d44ffb3d7465855378185",
"98497e7bf21f413b9df0d84ccb8857d0" ], "labels": [ "aws" ], "revision": 8279863739578999000, "publisher": null,
"release_date": "2025-05-18", "created_date": "2025-05-18", "created_by": "Palo Alto Networks", "insert_ts":
1750247311000, "modify_ts": 1750247313000, "is_custom": false } ] } }
```


Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field


```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE


```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.9.2 | Get single standard by ID

post /public_api/v1/compliance/get_standard

Retrieve details of the compliance standard specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_standard'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/get_standard", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_standard") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_standard"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_standard") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_standard")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_standard", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_standard"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_standard"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

Compliance standard ID

REQUEST

get_single_standard

```
{ "request_data": { "id": "eee175cb04da4a0e3091b1ee77368" } }
```

Responses

Successfully retrieved standard

Body

application/json

▼ standardobject

▶ idstring

Standard ID

▶ namestring

Standard name

▶ descriptionstring

Description of the standard

▶ publisherstring

Standard publisher/organization

▶ labelsarray[string]

List of labels for categorization

▶ insertion_timeintegerint64

Creation timestamp (epoch)

▶ created_bystring

User who created the standard

▶ is_customboolean

Whether this is a custom standard

▶ controls_countinteger

Number of associated controls

▶ controls_idsarray[string]

List of associated control IDs

RESPONSE

single_standard


```
{ "standard": { "id": "36ed307155e446938f157e3ed214fd72", "name": "standard name ...", "description": "", "version":
"", "assessments_profiles_count": 0, "controls_ids": [ "0b0b5304d06d44ffb3d7465855378185",
"98497e7bf21f413b9df0d84ccb8857d0" ], "labels": [ "aws", "azure", "gcp" ], "revision": 8279863739578999000,
"publisher": null, "release_date": "2025-06-18", "created_date": "2025-06-18", "created_by": "Palo Alto Networks",
"insert_ts": 1750247411000, "modify_ts": 1750247413000, "is_custom": true } }
```


Bad request - invalid input parameters

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field


```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Resource not found

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code
▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }

2.9.9.3 | Add new standard

post /public_api/v1/compliance/add_standard

Create a new compliance standard.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/add_standard'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":[\"string\"]}}"
headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/compliance/add_standard", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/add_standard") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":[\"string\"]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "standard_name": "string", "description": "string", "labels": [
"string" ], "controls_ids": [ "string" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/compliance/add_standard");
```

```
xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/add_standard") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":[\"string\"]}}")
.asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "standard_name": "string", "description": "string", "labels": ["string"],
"controls_ids": ["string"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/add_standard")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/add_standard", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":[\"string\"]}}",
CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/add_standard"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/add_standard"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":[\"string\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ standard_namestringrequired

Name of the compliance standard

▶ descriptionstring

Description of the standard

▶ labelsarray[string]

List of labels for categorization

▶ controls_idsarray[string]

List of control IDs to associate with this standard. Only custom controls can be included.

REQUEST

Add new standard

```
{ "standard_name": "Standard name", "description": "Standard description....", "labels": [ "aws", "azure", "gcp",
"oci" ], "controls_ids": [ "48f2f6a9fde049479e9c8c8eda0be163" ] }
```

Responses

Standard added successfully

Body

application/json

▼ successboolean

Operation success status

RESPONSE

success

```
{ "reply": { "success": true } }
```

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field
```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.9.4 | Edit existing standard

post /public_api/v1/compliance/edit_standard

Edit an existing compliance standard specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/edit_standard'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/edit_standard", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/edit_standard") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string", "standard_name": "string", "description": "string",
"labels": [ "string" ], "controls_ids": [ "string" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/compliance/edit_standard");
xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/edit_standard")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "id": "string", "standard_name": "string", "description": "string", "labels":
["string"], "controls_ids": ["string"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/compliance/edit_standard")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/edit_standard", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/edit_standard"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"controls_ids\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/edit_standard"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"id\":\"string\",\"standard_name\":\"string\",\"description\":\"string\",\"labels\":[\"string\"],\"controls_ids\":
[\"string\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ idstringrequired

Compliance standard ID

▶ standard_namestring

Name of the standard

▶ descriptionstring

Description of the standard

▶ labelsarray[string]

List of labels for categorization

▶ controls_idsarray[string]

List of control IDs to associate with this standard. Only custom controls can be included.

REQUEST

edit_existing_standard

{ "request_data": { "id": "48e2f6a9fdc049479e9c6a8eda0bd163", "standard_name": "test new name" } }

Responses

Standard updated successfully

Body
application/json
▼ successboolean

Operation success status

RESPONSE
success
{ "reply": { "success": true } }

Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory, is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq, contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {} } }

Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id": "eee175cb00ef4da4a0e3091b1ee77368" } } }

Internal server error

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details
RESPONSE
```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.9.5 | Delete standard

post /public_api/v1/compliance/delete_standard

Delete a the compliance standard specified by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/delete_standard'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"id\":\"string\"}}" headers = { 'x-xdr-auth-id': "REPLACE_KEY_VALUE", 'content-type': "application/json" }
conn.request("POST", "/public_api/v1/compliance/delete_standard", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/delete_standard") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"id\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "id": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/delete_standard"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/delete_standard")
.header("x-xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"id\":\"string\"}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["id": "string"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/delete_standard")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/delete_standard", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"id\":\"string\"}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/delete_standard"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"id\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/delete_standard"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"id\":\"string\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ idstringrequired

Compliance standard ID

REQUEST
delete_standard

```
{ "request_data": { "id": "f9f764717b284e9483f9c1210ed3149d" } }
```

Responses

Standard deleted successfully

Body
application/json
▼ successboolean

Operation success status

RESPONSE
success

```
{ "reply": { "success": true } }
```


Bad request - invalid input parameters

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Resource not found

Body
application/json
▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 404, "err_msg": "Control not found", "err_extra": { "control_id":
"eee175cb00ef4da4a0e3091b1ee77368" } } }
```


Internal server error

Body
application/json

▼ replyobject
▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.9.10 | Compliance Assets

Operations for retrieving compliance assets

2.9.10.1 | Get compliance assets

post /public_api/v1/compliance/get_assets

Retrieve compliance assets with required assessment profile revision and last evaluation time, with optional filtering, sorting and pagination.

Filtering Support:

- String fields (`asset_name`, `rule_name`, `control`): `eq`, `neq`, `contains`, `not_contains`
- Status fields (`asset_type`, `status`, `severity`, `rule_type`): `eq`, `neq`
- Status valid values: [`FAILED`, `PASSED`, `NOT_ASSESSED`]
- Severity valid values: [`low`, `medium`, `high`, `critical`]

Sorting Support:

- Available fields: `asset_name`, `asset_type`, `status`, `rule_name`, `control`, `severity`
- Sort orders: `asc`, `desc`
- Default: `asset_name` in ascending order

Pagination: (max number of elements is 100)

Authentication: XDRAuthToken Api Key "Authorization"

Authentication: XDRAuth Api Key "x-xdr-auth-id"
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H "Authorization: [[apiKey]]" \
-H "x-xdr-auth-id: [[apiKey]]" \
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/v1/compliance/get_assets'
-d '{ "request_data" : { "search_from" : 0, "assessment_profile_revision" : "343554605578776831",
"last_evaluation_time" : 1758816221000, "filters" : [ { "field" : "SEVERITY", "value" : "high", "operator" : "eq" }, {
"field" : "SEVERITY", "value" : "high", "operator" : "eq" } ], "sort" : { "field" : "asset_name", "keyword" : "asc" },
"search_to" : 1 } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" headers = { 'x-xdr-auth-id':
"REPLACE_KEY_VALUE", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/compliance/get_assets",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/compliance/get_assets") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["x-xdr-auth-id"] =
'REPLACE_KEY_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
```

```
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}" response = http.request(request)
puts response.read_body
const data = JSON.stringify({ "request_data": { "assessment_profile_revision": "343554605578776831",
"last_evaluation_time": 1758816221000, "filters": [ { "field": "severity", "operator": "eq", "value": "low" } ],
"sort": { "field": "asset_name", "keyword": "asc" }, "search_from": 0, "search_to": 100 } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/compliance/get_assets"); xhr.setRequestHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/compliance/get_assets") .header("x-
xdr-auth-id", "REPLACE_KEY_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "REPLACE_KEY_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "assessment_profile_revision": "343554605578776831", "last_evaluation_time":
1758816221000, "filters": [ [ "field": "severity", "operator": "eq", "value": "low" ] ], "sort": [ "field":
"asset_name", "keyword": "asc" ], "search_from": 0, "search_to": 100 ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/compliance/get_assets")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/compliance/get_assets", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}", CURLOPT_HTTPHEADER => [
"content-type: application/json", "x-xdr-auth-id: REPLACE_KEY_VALUE" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/compliance/get_assets"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: REPLACE_KEY_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/compliance/get_assets"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "REPLACE_KEY_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"assessment_profile_revision\":\"343554605578776831\",\"last_evaluation_time\":1758816221000,\"filters\":
[{\"field\":\"severity\",\"operator\":\"eq\",\"value\":\"low\"}],\"sort\":
{\"field\":\"asset_name\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":100}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ assessment_profile_revisionstringrequired

Assessment profile revision identifier

▶ last_evaluation_timeintegerrequiredint64

Last evaluation timestamp in epoch format

▶ filtersarray

Array of filter objects for filtering assets

▶ sortobject

▶ search_frominteger

Starting index for pagination

▶ search_tointeger

Ending index for pagination

REQUEST


```
{ "request_data": { "assessment_profile_revision": "343554605578776831", "last_evaluation_time": 1758816221000,
"filters": [ { "field": "SEVERITY", "operator": "eq", "value": "high" } ], "sort": { "field": "asset_name", "keyword":
"asc" }, "search_from": 0, "search_to": 0 } }
```


Responses

Successfully retrieved compliance assets

Body

application/json

▼ replyobject

▶ total_countinteger

Total number of assets available

▶ result_countinteger

Number of assets matching the applied filters + paging

▶ filter_countinteger

Number of assets matching the applied filters

▶ assetsarray

Array of compliance assets

RESPONSE


```
{ "reply": { "total_count": 134, "result_count": 29, "filter_count": 29, "assets": [ { "ASSET_ID":
"a4d9b7b4e7c88cecaf24a063d86cb0069ed659f8bc66c4c1572c90e716291e3d", "ASSET_NAME": "mock-gcloud-storage-buckets-list-
3d0a69ff21184406aa1cbd07b29f6f1f", "ASSET_TYPE": "GOOGLE_CLOUD_STORAGE_BUCKET", "STATUS": "PASSED", "RULE_NAME":
"Sensitive public object in private storage", "CONTROL": "Safeguard 3.2 : Establish and Maintain a Data Inventory",
"RULE_REVISION_ID": "DSPM_1006", "CONTROL_REVISION_ID": -7177800670050593000, "SOURCE": "No Finding or Issue",
"SEVERITY": "high", "RULE_TYPE": "Data", "PROVIDER": "GCP", "REGION": "us", "REALM": "gcp-c0844a50-dd0f-47ec-9d14-
c7af5f5325aa", "TAGS": { "Name": "mock-gcloud-storage-buckets-list-3d0a69ff21184406aa1cbd07b29f6f1f" },
"ORGANIZATION": null, "ASSET_STRONG_ID": "mock-gcloud-storage-buckets-list-3d0a69ff21184406aa1cbd07b29f6f1f" } ] } }
```


Bad request - invalid input parameters

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE invalid_field


```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter field. Allowed fields: name, category, subcategory,
is_custom, creation_time, created_by, modified_by, modification_time, id, description", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid operator 'range' for field 'name'. Allowed operators: eq, neq,
contains, not_contains", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Missing required parameter: control_name", "err_extra": {} } }
{ "reply": { "err_code": 400, "err_msg": "Invalid value for is_custom field. Allowed values: yes, no", "err_extra": {}
} }
```


Authentication required

Body

application/json

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Authentication credentials were not provided or are invalid", "err_extra": {} } }
```

Access denied - insufficient permissions

Body

application/json

▼ replyobject

▶ err_codeintegerrequired

Error code

▶ err_msgstringrequired

Error message describing what went wrong

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "You do not have permission to access assessment results", "err_extra": {} } }
```

Internal server error

Body

application/json

▼ replyobject

▶ err_codeinteger

Error code

▶ err_msgstring

Error message

▶ err_extraobject

Additional error details

RESPONSE

```
{ "reply": { "err_code": 500, "err_msg": "Failed to retrieve controls", "err_extra": {} } }
```

2.10 | Policies

2.10.1 | Preface

Manage security policies that define which rules apply to which assets. Policies control how security findings are evaluated across your cloud environment.

Required license: This feature is included with Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Version: Cortex Cloud

2.10.2 | Cloud Security Policies

APIs for operations related to cloud security policies

2.10.2.1 | Create Cloud Security Policy

post /public_api/v1/policy

Create a new cloud security policy.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'http://localhost/public_api/v1/policy'
-d '{ "associated_cloud_account_ids" : [ "", "" ], "name" : "", "description" : "", "associated_rule_ids" : [ "", "",
"", "", "" ], "associated_rule_filter" : { "AND" : [ null, null ] }, "associated_asset_group_ids" : [ "", "", "", "",
"" ], "enabled" : "", "labels" : [ "", "" ] }'
import http.client conn = http.client.HTTPSConnection("example.com") payload = "
{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}" headers = { 'content-type': "application/json" }
conn.request("POST", "//public_api/v1/policy", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://example.com//public_api/v1/policy") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["content-type"] = 'application/json' request.body = "
{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "name": "string", "description": "string", "labels": [ "string" ], "rule_matching_type":
"ALL_RULES", "associated_rule_filter": { "AND": [ { "AND": [ {} ] } ] }, "associated_rule_ids": [ "497f6eca-6276-4993-
bfeb-53cbbbba6f08" ], "asset_matching_type": "ALL_ASSETS", "associated_asset_group_ids": [ 0 ],
"associated_cloud_account_ids": [ "string" ], "enabled": true }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://example.com//public_api/v1/policy");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://example.com//public_api/v1/policy") .header("content-type",
"application/json") .body("{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = [ "name": "string",
"description": "string", "labels": ["string"], "rule_matching_type": "ALL_RULES", "associated_rule_filter": ["AND":
[["AND": [[]]]]], "associated_rule_ids": ["497f6eca-6276-4993-bfeb-53cbbbba6f08"], "asset_matching_type":
"ALL_ASSETS", "associated_asset_group_ids": [0], "associated_cloud_account_ids": ["string"], "enabled": true ] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://example.com//public_api/v1/policy")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://example.com//public_api/v1/policy",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}", CURLOPT_HTTPHEADER => [ "content-type:
application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://example.com//public_api/v1/policy"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers,
"content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd,
CURLOPT_POSTFIELDS, "{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}"); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://example.com//public_api/v1/policy"); var request = new RestRequest(Method.POST);
request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "
{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"ALL_RULES\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ALL_ASSETS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);
```

Body parameters
required
application/json

▼ namestringrequired

Name of the policy

▼ descriptionstringrequired

Description of the policy

▼ labelsobject

Labels associated with the policy

Any of a
Array
▼ rule_matching_typestring (Enum)required
Allowed values:"ALL_RULES""RULES""RULE_FILTER"
▼ associated_rule_filterobject

Rule filter for the policy, required if rule_matching_type is RULE_FILTER

Any of a
▶ ANDarrayrequired
▶ ORarrayrequired
▼ associated_rule_idsobject

List of rule IDs, required if rule_matching_type is RULES

Any of a
Array
▼ asset_matching_typestring (Enum)required
Allowed values:"ALL_ASSETS""ASSET_GROUPS""CLOUD_ACCOUNTS"
▼ associated_asset_group_idsobject

List of asset group IDs, required if asset_matching_type is ASSET_GROUPS

Any of a
Array
▼ associated_cloud_account_idsobject

List of cloud account IDs associated with the policy

Any of a
Array
▼ enabledboolean

Whether the policy is enabled or not

Default:`true`
REQUEST createPolicyWithRuleFilter

```
{ "name": "API Request with rule_matching_type RULE_FILTER", "description": "API Request with rule_matching_type
RULE_FILTER", "labels": [ "vm_automation" ], "rule_matching_type": "RULE_FILTER", "associated_rule_filter": { "AND": [
{ "OR": [ { "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "low" }, { "SEARCH_FIELD": "severity",
"SEARCH_TYPE": "EQ", "SEARCH_VALUE": "medium" } ] }, { "OR": [ { "SEARCH_FIELD": "cloudType", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "aws" }, { "SEARCH_FIELD": "cloudType", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "azure" } ] }, {
"SEARCH_FIELD": "labels", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": "test" }, { "SEARCH_FIELD":
"complianceStandards", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": "Australian Energy Sector Cyber Security
Framework (AESCSF)" } ] }, "asset_matching_type": "ALL_ASSETS", "enabled": true }
{ "name": "IBM-alert-rule-with-custom-and-default-policy-prisma_cloud_copy", "description": "", "labels": [
"prisma_cloud_alert_rule_copy" ], "rule_matching_type": "RULES", "associated_rule_ids": [ "67b8ea9e-1409-4c5a-9c56-
1289b48acc1b", "20c1f067-447f-4d1a-af21-bc404ae66b94", "5a4fcc81-5481-4d37-b96b-eb87333d3b32", "f2d2945d-a509-44d8-
abbc-12566ae7962d" ], "asset_matching_type": "ALL_ASSETS", "enabled": true }
```

{ "name": "test-all-policies-prisma_cloud_copy", "description": "Test policy rule filter with asset groups", "labels": ["prisma_cloud_alert_rule_copy"], "rule_matching_type": "ALL_RULES", "asset_matching_type": "ASSET_GROUPS", "associated_asset_group_ids": [52] }
{ "name": "Automation policy rule filter with all assets", "description": "Test policy rule filter with all assets", "labels": ["vm_automation"], "rule_matching_type": "RULES", "associated_rule_ids": ["f1dd78f2-7667-4b69-8a3e-af257e5d4cf6"], "asset_matching_type": "CLOUD_ACCOUNTS", "associated_cloud_account_ids": ["2866778037"] }

Responses

Policy created successfully

Body
application/json
▼ idstringrequireduuid
▼ namestringrequired
▼ descriptionobject
Any of a
▶ string
▼ labelsobject
Any of a
Array
▼ rule_matching_typestring (Enum)required
Allowed values:"RULE_FILTER""RULES""ALL_RULES"
▼ associated_rule_filterobject

present if Rule Matching Type is `RULE_FILTER`

Any of a
▶ ANDarrayrequired
▶ ORarrayrequired
▼ associated_rule_idsobject

present if Rule Matching Type is `RULES`

Any of a
Array
▼ asset_matching_typestring (Enum)required
Allowed values:"ASSET_GROUPS""ALL_ASSETS""CLOUD_ACCOUNTS"
▼ associated_asset_group_idsobject

present if Asset Matching Type is `ASSET_GROUPS`

Any of a
Array
▼ associated_cloud_account_idsobject

present if Asset Matching Type is `CLOUD_ACCOUNTS`

Any of a
Array
▼ enabledbooleanrequired
▼ modestring (Enum)required
Allowed values:"DEFAULT""CUSTOM"
▼ creation_timeintegerrequired

in Unix epoch milliseconds

▼ created_bystringrequired
▼ modification_timeintegerrequired

in Unix epoch milliseconds

▼ modified_bystringrequired
RESPONSE API response with rule_matching_type RULE_FILTER

{ "id": "5988e7f2-ed6a-40cf-98b4-a05175f0db53", "name": "Automation policy rule filter with all assets", "description": "Test policy rule filter with all assets", "labels": ["vm_automation"], "rule_matching_type": "RULE_FILTER", "associated_rule_filter": { "AND": [{ "OR": [{ "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "low" }, { "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "medium" }] }, { "OR": [{ "SEARCH_FIELD": "cloudType", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "aws" }, { "SEARCH_FIELD": "cloudType", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "azure" }] }, { "SEARCH_FIELD": "labels", "SEARCH_TYPE": "ARRAY_CONTAINS", "SEARCH_VALUE": "test" }] }, "asset_matching_type": "ALL_ASSETS", "enabled": true, "mode": "CUSTOM", "creation_time": 1678886400000, "created_by": "mock_user", "modification_time": 1678886400000, "modified_by": "mock_user" }

{ "id": "b98a6839-6215-42c8-bd1e-65b49d93e224", "name": "IBM-alert-rule-with-custom-and-default-policy-prisma_cloud_copy", "description": "", "labels": ["prisma_cloud_alert_rule_copy"], "rule_matching_type": "RULES", "associated_rule_ids": ["67b8ea9e-1409-4c5a-9c56-1289b48acc1b", "20c1f067-447f-4d1a-af21-bc404ae66b94", "5a4fcc81-5481-4d37-b96b-eb87333d3b32", "f2d2945d-a509-44d8-abbc-12566ae7962d"], "asset_matching_type": "ALL_ASSETS", "enabled": true, "mode": "CUSTOM", "creation_time": 1678886400000, "created_by": "mock_user", "modification_time": 1678886400000, "modified_by": "mock_user" }
{ "id": "569ce82b-f3b2-42d9-a6e8-1bc6339893d1", "name": "test-all-policies-prisma_cloud_copy", "description": "Test policy rule filter with asset groups", "labels": ["prisma_cloud_alert_rule_copy"], "rule_matching_type": "ALL_RULES", "asset_matching_type": "ASSET_GROUPS", "associated_asset_group_ids": [52], "mode": "CUSTOM", "creation_time": 1678886400000, "created_by": "mock_user", "modification_time": 1678886400000, "modified_by": "mock_user" }
{ "id": "002a7844-fe11-43af-876a-f9ad91b79f23", "name": "Automation policy rule filter with all assets", "description": "Test policy rule filter with all assets", "labels": ["vm_automation"], "rule_matching_type": "RULES", "associated_rule_ids": ["f1dd78f2-7667-4b69-8a3e-af257e5d4cf6"], "asset_matching_type": "CLOUD_ACCOUNTS", "associated_cloud_account_ids": ["286677803794946164413015306518444191290"], "enabled": true, "mode": "CUSTOM", "creation_time": 1678886400000, "created_by": "mock_user", "modification_time": 1678886400000, "modified_by": "mock_user" }

Unprocessable Content

Too Many Requests

Bad Request

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE Invalid parameters Examples
{ "err_msg": "The request contains invalid parameters", "metadata": { "err_extra": [{ "field": "rule_matching_type", "message": "Input should be 'ALL_RULES', 'RULES' or 'RULE_FILTER'" }, { "field": "associated_rule_filter", "message": "Value error, Invalid filter format: missing SEARCH_FIELD, SEARCH_TYPE, SEARCH_VALUE or logical operator (AND/OR)" }, { "field": "asset_matching_type", "message": "Input should be 'ALL_ASSETS', 'ASSET_GROUPS' or 'CLOUD_ACCOUNTS'" }] } }
{ "err_msg": "The request contains invalid parameters", "metadata": { "err_extra": [{ "field": "asset_matching_type", "message": "Field required" }, { "field": "body", "message": "Value error, associated_asset_group_ids is required when asset_matching_type is ASSET_GROUPS" }, { "field": "body", "message": "Value error, associated_rule_filter is required when rule_matching_type is RULE_FILTER" }] } }

Unauthorized

Forbidden

Not Found

Conflict

Internal Server Error

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.10.2.2 | List Cloud Security Policies

post /public_api/v1/policy/search

Get all cloud security policies.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'http://localhost/public_api/v1/policy/search'
-d '{ "filter" : { "AND" : [ null, null ] }, "search_from" : "", "sort" : [ { "FIELD" : "" }, { "FIELD" : "" } ],
"search_to" : "" }'
import http.client conn = http.client.HTTPSConnection("example.com") payload = "{\"filter\":{\"AND\":[{\"AND\":
[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}" headers = { 'content-
type': "application/json" } conn.request("POST", "//public_api/v1/policy/search", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://example.com//public_api/v1/policy/search") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["content-type"] = 'application/json' request.body = "{\"filter\":{\"AND\":[{\"AND\":
[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": { "AND": [ { "AND": [ {} ] } ] }, "search_from": 0, "search_to": 50, "sort": [
{ "FIELD": "string", "ORDER": "ASC" } ] }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://example.com//public_api/v1/policy/search");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://example.com//public_api/v1/policy/search") .header("content-
type", "application/json") .body("{\"filter\":{\"AND\":[{\"AND\":[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":
[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = [ "filter": ["AND": [["AND":
[[]]]]], "search_from": 0, "search_to": 50, "sort": [ [ "FIELD": "string", "ORDER": "ASC" ] ] ] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://example.com//public_api/v1/policy/search")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://example.com//public_api/v1/policy/search", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"filter\":{\"AND\":[{\"AND\":[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":
[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}", CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://example.com//public_api/v1/policy/search"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"filter\":{\"AND\":[{\"AND\":
[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://example.com//public_api/v1/policy/search"); var request = new
RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"filter\":{\"AND\":[{\"AND\":
[{}]}]},\"search_from\":0,\"search_to\":50,\"sort\":[{\"FIELD\":\"string\",\"ORDER\":\"ASC\"}]}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ filterobject

Filter for policies

Any of a

▶ ANDarrayrequired

▶ ORarrayrequired

▼ search_frominteger

Start index for pagination

▼ search_tointeger

End index for pagination

Default:50
▼ sortarray
[
▶ FIELDstringrequired
▶ ORDERstring (Enum)required
]
REQUEST
listPoliciesExample
{ "filter": { "AND": [{ "SEARCH_FIELD": "id", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "b2b1279e-8760-44a8-8dca-bcc4508f8ce7" }, { "SEARCH_FIELD": "name", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "Cloud Posture Security" }] }, "search_from": 0, "search_to": 50, "sort": [{ "FIELD": "name", "ORDER": "ASC" }] }
Responses

Successful Response

Body
application/json
▼ dataarray
[
▶ idstringrequireduuid
▶ namestringrequired
▶ descriptionobject
▶ labelsobject
▶ rule_matching_typestring (Enum)required
▶ associated_rule_filterobject

present if Rule Matching Type is RULE_FILTER

▶ associated_rule_idsobject

present if Rule Matching Type is RULES

▶ asset_matching_typestring (Enum)required
▶ associated_asset_group_idsobject

present if Asset Matching Type is ASSET_GROUPS

▶ associated_cloud_account_idsobject

present if Asset Matching Type is CLOUD_ACCOUNTS

▶ enabledbooleanrequired
▶ modestring (Enum)required
▶ creation_timeintegerrequired

in Unix epoch milliseconds

▶ created_bystringrequired
▶ modification_timeintegerrequired

in Unix epoch milliseconds

▶ modified_bystringrequired
]
▼ metadataobject
Any of a
▶ total_countintegerrequired
▶ filter_countintegerrequired
RESPONSE
API response with List of Policies
{ "data": [{ "id": "b2b1279e-8760-44a8-8dca-bcc4508f8ce7", "name": "Default Cloud Posture Security Policy", "description": "Comprehensive default security policy that identifies risks across you entire cloud security estate. It leverages best practices to scan and detect attack paths, misconfigurations, vulnerabilities, identity risks, data risks, network exposures, and other security gaps across your cloud infrastructure and applications, enabling proactive management and mitigation of cloud security risks.", "labels": ["prisma_cloud"], "rule_matching_type": "RULE_FILTER", "associated_rule_filter": { "OR": [{ "AND": [{ "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "critical" }] }, { "AND": [{ "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "high" }] }] }, "asset_matching_type": "ALL_ASSETS", "enabled": true, "mode": "DEFAULT", "creation_time": 1732557301240, "created_by": "Palo Alto Networks", "modification_time": 1732557301240, "modified_by": "Palo Alto Networks" }], "metadata": { "total_count": 5, "filter_count": 1 } }

Unprocessable Content

Too Many Requests

Bad Request

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
The request contains invalid parameters
{ "err_msg": "The request contains invalid parameters", "metadata": { "err_extra": [{ "field": "SEARCH_TYPE", "message": "SEARCH_TYPE 'EBQ' is not supported. Allowed values: EQ, CONTAINS, NCONTAINS, NEQ" }] } }

Unauthorized

Forbidden

Not Found

Internal Server Error

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.10.2.3 | Get Cloud Security Policy

get /public_api/v1/policy/{policy_id}

Get a cloud security policy by ID.

Path parameters
▼ policy_id UUID required
Example: 38400000-8cf0-11bd-b23e-10b96e4ef00d
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'http://localhost/public_api/v1/policy/{policy_id}'
import http.client conn = http.client.HTTPSConnection("example.com") conn.request("GET",
"//public_api/v1/policy/%7Bpolicy_id%7D") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response = http.request(request)
puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://example.com//public_api/v1/policy/%7Bpolicy_id%7D");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
```

```
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error
#:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successful Response

Body
application/json
▼ idstringrequireduuid
▼ namestringrequired
▼ descriptionobject
Any of a
▶ string
▼ labelsobject
Any of a
Array
▼ rule_matching_typestring (Enum)required
Allowed values:"RULE_FILTER""RULES""ALL_RULES"
▼ associated_rule_filterobject

present if Rule Matching Type is `RULE_FILTER`

Any of a
▶ ANDarrayrequired
▶ ORarrayrequired
▼ associated_rule_idsobject

present if Rule Matching Type is `RULES`

Any of a
Array
▼ asset_matching_typestring (Enum)required
Allowed values:"ASSET_GROUPS""ALL_ASSETS""CLOUD_ACCOUNTS"
▼ associated_asset_group_idsobject

present if Asset Matching Type is `ASSET_GROUPS`

Any of a
Array
▼ associated_cloud_account_idsobject

present if Asset Matching Type is `CLOUD_ACCOUNTS`

Any of a
Array
▼ enabledbooleanrequired
▼ modestring (Enum)required
Allowed values:"DEFAULT""CUSTOM"
▼ creation_timeintegerrequired

in Unix epoch milliseconds

▼ created_bystringrequired
▼ modification_timeintegerrequired

in Unix epoch milliseconds

▼ modified_bystringrequired
RESPONSE
API response with rule_matching_type RULE_FILTER


```
{ "id": "b2b1279e-8760-44a8-8dca-bcc4508f8ce7", "name": "Default Cloud Posture Security Policy", "description":
"Comprehensive default security policy that identifies risks across you entire cloud security estate. It leverages
best practices to scan and detect attack paths, misconfigurations, vulnerabilities, identity risks, data risks,
network exposures, and other security gaps across your cloud infrastructure and applications, enabling proactive
management and mitigation of cloud security risks.", "labels": [ "prisma_cloud" ], "rule_matching_type":
"RULE_FILTER", "associated_rule_filter": { "OR": [ { "AND": [ { "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ",
"SEARCH_VALUE": "critical" } ] }, { "AND": [ { "SEARCH_FIELD": "severity", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "high"
```

}] }] }, "asset_matching_type": "ALL_ASSETS", "enabled": true, "mode": "DEFAULT", "creation_time": 1732557301240, "created_by": "Palo Alto Networks", "modification_time": 1732557301240, "modified_by": "Palo Alto Networks" }

Unprocessable Content

Too Many Requests

Unauthorized

Forbidden

Not Found

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Policy not found with id
{ "err_msg": "Policy not found", "metadata": { "err_extra": [{ "field": "id", "message": "No policy found with the specified ID" }] } }

Internal Server Error

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.10.2.4 | Update Cloud Security Policy

patch /public_api/v1/policy/{policy_id}

Modify an existing cloud security policy by ID.

Path parameters
▼ policy_id UUID required
Example: 38400000-8cf0-11bd-b23e-10b96e4ef00d
CLIENT REQUEST Bash+curl
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'http://localhost/public_api/v1/policy/{policy_id}'
-d '{ "associated_cloud_account_ids" : ["", ""], "name" : "", "description" : "", "associated_rule_ids" : ["", "", "", "", ""], "associated_rule_filter" : { "AND" : [null, null] }, "associated_asset_group_ids" : ["", "", "", "", ""], "enabled" : "", "labels" : ["", ""] }'
import http.client conn = http.client.HTTPSConnection("example.com") payload = "
{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}" headers = { 'content-type': "application/json" }
conn.request("PATCH", "//public_api/v1/policy/%7Bpolicy_id%7D", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Patch.new(url) request["content-type"] =
'application/json' request.body = "{\"name\":\"string\",\"description\":\"string\",\"labels\":

[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "name": "string", "description": "string", "labels": ["string"], "rule_matching_type":
"RULE_FILTER", "associated_rule_filter": { "AND": [{ "AND": [{}] }] }, "associated_rule_ids": ["497f6eca-6276-
4993-bfeb-53cbbbba6f08"], "asset_matching_type": "ASSET_GROUPS", "associated_asset_group_ids": [0],
"associated_cloud_account_ids": ["string"], "enabled": true }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("PATCH",
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D")
.header("content-type", "application/json") .body("{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["name": "string",
"description": "string", "labels": ["string"], "rule_matching_type": "RULE_FILTER", "associated_rule_filter": ["AND":
[["AND": [[]]]]], "associated_rule_ids": ["497f6eca-6276-4993-bfeb-53cbbbba6f08"], "asset_matching_type":
"ASSET_GROUPS", "associated_asset_group_ids": [0], "associated_cloud_account_ids": ["string"], "enabled": true] as
[String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://example.com//public_api/v1/policy/%7Bpolicy_id%7D")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PATCH" request.allHTTPHeaderFields
= headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL =>
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PATCH", CURLOPT_POSTFIELDS => "{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}", CURLOPT_HTTPHEADER => ["content-type:
application/json"],]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); var request = new
RestRequest(Method.PATCH); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"name\":\"string\",\"description\":\"string\",\"labels\":
[\"string\"],\"rule_matching_type\":\"RULE_FILTER\",\"associated_rule_filter\":{\"AND\":[{\"AND\":
[{}]}]},\"associated_rule_ids\":[\"497f6eca-6276-4993-bfeb-
53cbbbba6f08\"],\"asset_matching_type\":\"ASSET_GROUPS\",\"associated_asset_group_ids\":
[0],\"associated_cloud_account_ids\":[\"string\"],\"enabled\":true}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);

Body parameters

required

application/json

▼ nameobject

Any of a

▶ string

▼ descriptionobject

Any of a

▶ string

▼ labelsobject

Any of a

Array
▼ rule_matching_typeobject

method of selecting the applicable rules for this policy

Any of a
▶ string (Enum)

method of selecting the applicable rules for this policy

▼ associated_rule_filterobject

required if Rule Matching Type is `RULE_FILTER`

Any of a
▶ ANDarrayrequired
▶ ORarrayrequired
▼ associated_rule_idsobject

required if Rule Matching Type is `RULES`

Any of a
Array
▼ asset_matching_typeobject

method of selecting the assets in scope for this policy

Any of a
▶ string (Enum)

method of selecting the assets in scope for this policy

▼ associated_asset_group_idsobject

required if Asset Matching Type is `ASSET_GROUPS`

Any of a
Array
▼ associated_cloud_account_idsobject

required if Asset Matching Type is `CLOUD_ACCOUNTS`

Any of a
Array
▼ enabledobject
Any of a
▶ boolean
REQUEST
update Policy Example Request Payload

```
{ "name": "API Request with rule_matching_type RULES", "description": "API Request with rule_matching_type RULES",
"labels": [ "prisma_cloud" ], "rule_matching_type": "RULES", "associated_rule_ids": [ "60cf2495-32a5-401f-ba56-
6bbbf80fe1e2", "3c16e31e-1421-4a25-854e-e5870093c99f" ], "asset_matching_type": "CLOUD_ACCOUNTS",
"associated_cloud_account_ids": [ "hvenkatesan-2", "883588134481" ], "enabled": false }
```

Responses

Successful Response

Body
application/json
▼ idstringrequireduuid
▼ namestringrequired
▼ descriptionobject
Any of a
▶ string
▼ labelsobject
Any of a
Array
▼ rule_matching_typestring (Enum)required
Allowed values:"RULE_FILTER""RULES""ALL_RULES"
▼ associated_rule_filterobject

present if Rule Matching Type is `RULE_FILTER`

Any of a

▶ ANDarrayrequired
▶ ORarrayrequired
▼ associated_rule_idsobject

present if Rule Matching Type is `RULES`

Any of a
Array
▼ asset_matching_typestring (Enum)required
Allowed values:"ASSET_GROUPS""ALL_ASSETS""CLOUD_ACCOUNTS"
▼ associated_asset_group_idsobject

present if Asset Matching Type is `ASSET_GROUPS`

Any of a
Array
▼ associated_cloud_account_idsobject

present if Asset Matching Type is `CLOUD_ACCOUNTS`

Any of a
Array
▼ enabledbooleanrequired
▼ modestring (Enum)required
Allowed values:"DEFAULT""CUSTOM"
▼ creation_timeintegerrequired

in Unix epoch milliseconds

▼ created_bystringrequired
▼ modification_timeintegerrequired

in Unix epoch milliseconds

▼ modified_bystringrequired
RESPONSE
API response with rule_matching_type RULES


```
{ "id": "b2b1279e-8760-44a8-8dca-bcc4508f8ce6", "name": "API Request with rule_matching_type RULES", "description":
"API Request with rule_matching_type RULES", "labels": [ "prisma_cloud" ], "rule_matching_type": "RULES",
"associated_rule_ids": [ "60cf2495-32a5-401f-ba56-6bbbf80fe1e2", "3c16e31e-1421-4a25-854e-e5870093c99f" ],
"asset_matching_type": "CLOUD_ACCOUNTS", "associated_cloud_account_ids": [ "hvenkatesan-2", "883588134481" ],
"enabled": false, "mode": "DEFAULT", "creation_time": 1732557301240, "created_by": "Palo Alto Networks",
"modification_time": 1732557301240, "modified_by": "Palo Alto Networks" }
```


Unprocessable Content

Too Many Requests

Unauthorized

Forbidden

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE The request contains invalid or missing parameters


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Cannot modify 'name' for system default policy. Only 'labels' can be updated." }, { "field":
"description", "message": "Cannot modify 'description' for system default policy. Only 'labels' can be updated." }, {
"field": "rule_matching_type", "message": "Cannot modify 'rule_matching_type' for system default policy. Only 'labels'
can be updated." } ] } }
{ "err_msg": "Cannot update system default policy", "metadata": { "err_extra": [ { "field": "system_default",
"message": "System default policy are managed by the platform and cannot be modified" } ] } }
```


Not Found

Body
application/json
▼ err_msgstringrequired
▼ metadataobject

Any of a
▶ err_extraobject
RESPONSE
Policy not found with id
{ "err_msg": "Policy not found", "metadata": { "err_extra": [{ "field": "id", "message": "No policy found with the specified ID" }] } }

Conflict

Internal Server Error

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.10.2.5 | Delete Cloud Security Policy

delete /public_api/v1/policy/{policy_id}

Delete an existing cloud security policy by ID.

Path parameters
▼ policy_id UUID required
Example: 38400000-8cf0-11bd-b23e-10b96e4ef00d
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Accept: application/json'
'http://localhost/public_api/v1/policy/{policy_id}'
```
```
import http.client conn = http.client.HTTPSConnection("example.com") conn.request("DELETE",
"//public_api/v1/policy/%7Bpolicy_id%7D") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```
```
require 'uri' require 'net/http' require 'openssl' url =
URI("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) response =
http.request(request) puts response.read_body
```
```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://example.com//public_api/v1/policy/%7Bpolicy_id%7D");
xhr.send(data);
```
```
HttpResponse<String> response = Unirest.delete("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D")
.asString();
```
```
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "DELETE" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
```
```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://example.com//public_api/v1/policy/%7Bpolicy_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "DELETE", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL
Error #:" . $err; } else { echo $response; }
```
```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); CURLcode ret = curl_easy_perform(hnd);
```
```
var client = new RestClient("https://example.com//public_api/v1/policy/%7Bpolicy_id%7D"); var request = new
RestRequest(Method.DELETE); IRestResponse response = client.Execute(request);
```
Responses

Successful Response

Unprocessable Content

Too Many Requests

Bad Request

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Invalid Parameters
{ "err_msg": "The request contains invalid parameters", "metadata": { "err_extra": [{ "field": "policy_id", "message": "Invalid policy ID format" }] } }

Unauthorized

Forbidden

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Cannot delete system default policy
{ "err_msg": "Cannot delete system default policy", "metadata": { "err_extra": [{ "field": "system_default", "message": "System default policy are managed by the platform and cannot be deleted" }] } }

Not Found

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Policy not found with id
{ "err_msg": "Policy not found", "metadata": { "err_extra": [{ "field": "id", "message": "No policy found with the specified ID" }] } }

Internal Server Error

Body
application/json
▼ err_msgstringrequired
▼ metadataobject
Any of a
▶ err_extraobject
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.11 | Cloud Workload Protection APIs

2.11.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Cloud Workload Policies and Rules ensure security compliance, prevent misconfigurations, and mitigate risks across cloud environments. Cloud Workload Policies leverage actionable findings or enforce preventive measures at defined stages of the Software Development Life Cycle (SDLC).

Registry Connectors are used to connect to third-party registries. You can use the Registry Onboarding APIs to onboard third-party registry connectors (such as Docker Hub, GitLab, Harbor, JFrog, and OpenShift) and managing their instances.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management
Version: Cortex Cloud

2.11.1.1 | Servers

https://api-yourfqdn

2.11.1.2 | Authentication methods

▼ Authorization
Api Key "x-api-key"

Authorized requests to the API should use: **x-api-key** inside **a header** with the access token.

▼ x-xdr-auth-id
Api Key "x-api-key-id"

Authorized requests to the API should use: **x-api-key-id** inside **a header** with the access token.

2.11.2 | Policies

APIs for managing Cloud Workload Policies

2.11.2.1 | Get CWP Policies (v2)

get /public_api/v2/cwp/policies

Fetches a list of all CWP policy instances. You can filter the results by policy type (e.g., COMPLIANCE, MALWARE, SECRET, TRUSTED_IMAGES). By default, all policy types are returned. Use the disableVerbose flag to optimize performance by skipping asset group data updates.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ types array[PolicyType]

The policies type

▼ disableVerbose Boolean

Flag to bypass calling platform for asset groups data when fetching policies. Note that this means asset groups will not be updated upon fetching policies.

Example: `true`
Default: `false`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v2/cwp/policies?types=&disableVerbose=true'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v2/cwp/policies?types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v2/cwp/policies?types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v2/cwp/policies?
types=SOME_ARRAY_VALUE&disableVerbose=SOME_BOOLEAN_VALUE"); var request = new RestRequest(Method.GET);
request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Success

Body
application/json; charset=UTF-8

The response you get when calling the `get policies V2` path

[
- ▶ idstringrequired
- ▶ revisionintegerrequired
- ▶ createdAtstringrequireddate-time
- ▶ modifiedAtstringrequireddate-time
- ▶ typestring (Enum)required

One of the supported policy types

- ▶ createdBystringrequired
- ▶ disabledbooleanrequired
- ▶ namestringrequired
- ▶ descriptionstringrequired
- ▶ evaluationModesarray[string]required
- ▶ evaluationStagestring (Enum)required

One of the supported evaluation stages

- ▶ policyRulesarrayrequired

Array of policy_rule objects related to the policy
▶ conditionstringrequiredbyte
▶ exceptionstringrequiredbyte
▶ assetScopestringrequiredbyte
▶ assetGroupsIDsarray[integer]required
▶ assetGroupsarray[string]required
▶ actionstring (Enum)required

One of the supported policy actions

▶ severitystring (Enum)required

One of the supported policy severities

▶ remediationGuidancestringrequired
▶ missingInformationActionstring (Enum)

One of the supported policy actions

▶ usingSystemAssetGroupsbooleanrequired
▶ unifiedPolicyIdstring
▶ gracePeriodstringrequired

Grace period duration string in days

]
RESPONSE
`[application/json; charset=UTF-8 content]`

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

2.11.2.2 | Add CWP Policies (v2)

post /public_api/v2/cwp/policies

Creates new CWP policy. This version supports advanced configuration including policyRules, gracePeriod, and usingSystemAssetGroups.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json; charset=UTF-8'
-H 'Content-Type: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v2/cwp/policies'
-d '{ "type" : "COMPLIANCE", "disabled" : false, "name" : "some policy", "description" : "some policy description",
"evaluationModes" : [ "PERIODIC" ], "evaluationStage" : "CI", "gracePeriod" : "", "policyRules" : [ { "rule_id" : "3",
"severity" : "CRITICAL", "action" : "ISSUE", "user_remediation_guidance" : "2" }, { "rule_id" : "4", "severity" :
"HIGH", "action" : "PREVENT", "user_remediation_guidance" : "1" } ], "condition" : "Y29uZGl0aW9u", "exception" :
"ZXhjZXB0aW9u", "assetScope" : "YXNzZXRY29wZQ==", "assetGroupsIDs" : [ 1, 2 ], "assetGroups" : [ "group1", "group2"
], "action" : "ISSUE", "severity" : "CRITICAL", "remediationGuidance" : "some remediation guidance", "createdBy" :
"user", "missingInformationAction" : "ISSUE", "usingSystemAssetGroups" : false }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("POST", "/public_api/v2/cwp/policies", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v2/cwp/policies") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v2/cwp/policies");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v2/cwp/policies")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v2/cwp/policies")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v2/cwp/policies", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v2/cwp/policies"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-yourfqdn/public_api/v2/cwp/policies"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json; charset=UTF-8

The schema of a created policy

▼ typestring (Enum)required

One of the supported policy types

Example:`"MALWARE"`
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ disabledbooleanrequired
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]required
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:`"CI"`
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ policyRulesarrayrequired

Array of policy_rule objects related to the policy

[
▶ rule_idstringrequired
▶ severitystring (Enum)required

One of the supported policy severities

▶ actionstring (Enum)required

One of the supported policy actions

▶ user_remediation_guidancestringrequired
]
▼ conditionstringrequiredbyte
▼ exceptionstringrequiredbyte
▼ assetScopestringrequiredbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]required
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities

Example:`"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ remediationGuidancestringrequired
▼ createdBystringrequired
▼ missingInformationActionstring (Enum)

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ usingSystemAssetGroupsbooleanrequired
▼ unifiedPolicyIdstring
▼ gracePeriodstringrequired

Grace period duration string in days

REQUEST
`[application/json; charset=UTF-8 content]`

Responses

Success

Body
application/json; charset=UTF-8
▼ idstring
RESPONSE
`[application/json; charset=UTF-8 content]`

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Forbidden error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

2.11.2.3 | Get a CWP Policy by ID (v2)

get /public_api/v2/cwp/policies/{id}

Fetches the detailed configuration of a single CWP policy identified by its unique ID. This includes associated rules, evaluation stages, and asset scope. Use disableVerbose to exclude platform-specific asset group metadata.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management.

Path parameters
▼ id String required
Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ disableVerbose Boolean

Flag to bypass calling platform for asset groups data when fetching policies. Note that this means asset groups will not be updated upon fetching policies.

Example: `true`
Default: `false`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v2/cwp/policies/{id}?disableVerbose=true'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v2/cwp/policies/%7Bid%7D?
disableVerbose=SOME_BOOLEAN_VALUE", headers=headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?disableVerbose=SOME_BOOLEAN_VALUE") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?
disableVerbose=SOME_BOOLEAN_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?
disableVerbose=SOME_BOOLEAN_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?disableVerbose=SOME_BOOLEAN_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?disableVerbose=SOME_BOOLEAN_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?disableVerbose=SOME_BOOLEAN_VALUE"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "Authorization:
```

```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D?
disableVerbose=SOME_BOOLEAN_VALUE"); var request = new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Success

Body
application/json; charset=UTF-8

The schema of a returned policy

▼ idstringrequired
▼ revisionintegerrequired
▼ createdAtstringrequireddate-time
▼ modifiedAtstringrequireddate-time
▼ typestring (Enum)required

One of the supported policy types

Example:`"MALWARE"`
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ createdBystringrequired
▼ disabledbooleanrequired
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]required
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:`"CI"`
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ policyRulesarrayrequired

Array of policy_rule objects related to the policy

[
▶ idstringrequired
▶ rule_idstringrequired
▶ policy_idstringrequired
▶ severitystring (Enum)required

One of the supported policy severities

▶ actionstring (Enum)required

One of the supported policy actions

▶ policy_revisionintegerrequired
▶ rule_namestringrequired
▶ remediation_guidancestringrequired
▶ user_remediation_guidancestringrequired

Additional remediation guidance that can be added to the ruleâ€™s predefined guidance.

]
▼ conditionstringrequiredbyte
▼ exceptionstringrequiredbyte
▼ assetScopestringrequiredbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]required
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities
Example: `"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ remediationGuidancestringrequired
▼ missingInformationActionstring (Enum)

One of the supported policy actions

Example: `"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ usingSystemAssetGroupsbooleanrequired
▼ unifiedPolicyIdstring
▼ gracePeriodstringrequired

Grace period duration string in days
RESPONSE
`[application/json; charset=UTF-8 content]`

Policy ID not found

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

2.11.2.4 | Update a CWP Policy by ID (v2)

put /public_api/v2/cwp/policies/{id}

Updates the configuration of an existing CWP policy. The policy ID is mandatory. Note: The policy revision will be automatically incremented upon a successful update. Fields not provided in the request body will be reset to their default values.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required

The policy ID to delete

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json; charset=UTF-8'
-H 'Content-Type: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v2/cwp/policies/{id}'
-d '{ "id" : "policyID", "type" : "COMPLIANCE", "disabled" : false, "name" : "some policy", "description" : "some
policy description", "evaluationModes" : [ "PERIODIC" ], "gracePeriod" : "", "evaluationStage" : "CI", "policyRules" :
[ { "rule_id" : "3", "severity" : "CRITICAL", "action" : "ISSUE", "user_remediation_guidance" : "1" }, { "rule_id" :
"4", "severity" : "HIGH", "action" : "PREVENT", "user_remediation_guidance" : "1" } ], "condition" :
"U29tZUJhc2U2NERfdGE=", "exception" : "U29tZUJhc2U2NERfdGE=", "assetScope" : "U29tZUJhc2U2NEFhdGE=", "assetGroupsIDs"
: [ 1, 2 ], "assetGroups" : [ "group1", "group2" ], "action" : "ISSUE", "severity" : "CRITICAL", "remediationGuidance"
: "some remediation guidance", "createdBy" : "user", "missingInformationAction" : "ISSUE", "usingSystemAssetGroups" :
false }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("PUT", "/public_api/v2/cwp/policies/%7Bid%7D", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "PUT" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v2/cwp/policies/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PUT", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v2/cwp/policies/%7Bid%7D"); var request = new
RestRequest(Method.PUT); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json; charset=UTF-8

The schema of a created policy

▼ idstringrequired
▼ typestring (Enum)required

One of the supported policy types

Example:`"MALWARE"`
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ disabledbooleanrequired
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]required
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:`"CI"`
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ policyRulesarrayrequired

Array of policy_rule objects related to the policy

[
▶ rule_idstringrequired
▶ severitystring (Enum)required

One of the supported policy severities

▶ actionstring (Enum)required

One of the supported policy actions

▶ user_remediation_guidancestringrequired
]
▼ conditionstringrequiredbyte
▼ exceptionstringrequiredbyte
▼ assetScopestringrequiredbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]required
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities

Example:`"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ remediationGuidancestringrequired
▼ createdBystring
▼ missingInformationActionstring (Enum)

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ usingSystemAssetGroupsbooleanrequired
▼ unifiedPolicyIdstring
▼ gracePeriodstringrequired

Grace period duration string in days

REQUEST
`[application/json; charset=UTF-8 content]`
Responses

Success

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Forbidden error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Policy ID not found

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
`[application/json; charset=UTF-8 content]`

2.11.2.5 | Get CWP Policies (v1)

get /public_api/v1/cwp/policies

Cloud Workload Policies help you prevent and manage security violations in your cloud runtime instances. They enable you to apply detection logic to specific asset groups at the desired SDLC stage, and define what action needs to be taken if the conditions are met.

Get all CWP policies of the given type. Default behavior is all.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ types array[PolicyType]

The policy type

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json,application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/policies?types='
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v1/cwp/policies?types=SOME_ARRAY_VALUE", headers=headers)
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/cwp/policies?
types=SOME_ARRAY_VALUE") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/cwp/policies?
types=SOME_ARRAY_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/cwp/policies?types=SOME_ARRAY_VALUE")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/policies?types=SOME_ARRAY_VALUE")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/cwp/policies?
types=SOME_ARRAY_VALUE", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/policies?types=SOME_ARRAY_VALUE"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/policies?types=SOME_ARRAY_VALUE"); var request =
new RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Success

Body
application/json

The response you get when calling the `get policies` path

[
▶ idstring
▶ revisioninteger
▶ createdAtstringdate-time
▶ modifiedAtstringdate-time
▶ typestring (Enum)required

One of the supported policy types

▶ createdBystring
▶ disabledboolean
▶ namestringrequired
▶ descriptionstringrequired
▶ evaluationModesarray[string]
▶ evaluationStagestring (Enum)required

One of the supported evaluation stages

▶ rulesIdsarray[string]required

The UUIDs of the rules that define the condition The `rulesIds` field is only required for non-compliance policies.

▶ conditionstringrequiredbyte

The `condition` field is only required for non-compliance policies.

▶ exceptionstringbyte
▶ assetScopestringbyte
▶ assetGroupsIDsarray[integer]required
▶ assetGroupsarray[string]
▶ actionstring (Enum)required

One of the supported policy actions

▶ severitystring (Enum)required

One of the supported policy severities

▶ missingInformationActionstring (Enum)required

One of the supported policy actions

▶ remediationGuidancestring
]
RESPONSE


```
[ { "id": "1", "revision": 3, "createdAt": "2024-07-28T18:50:55Z", "modifiedAt": "2024-07-28T18:50:55Z", "type":
"COMPLIANCE", "createdBy": "admin", "disabled": false, "name": "some policy", "description": "some policy
description", "evaluationModes": [ "PERIODIC" ], "evaluationStage": "CI", "rulesIds": [ "1", "2" ], "condition":
"U29tZUJhc2U2NEGhdGE=", "exception": "U29tZUJhc2U2NEhhdGE=", "assetScope": "U29tZUJhc2U2NE2hdGE=", "assetGroupsIDs": [
1, 2 ], "assetGroups": [ "group1", "group2" ], "action": "ISSUE", "severity": "CRITICAL", "missingInformationAction":
"ISSUE", "remediationGuidance": "some remediation guidance" } ]
```


Client error

Body

application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
```
{ "err_msg": "Bad Request", "metadata": { "code": "BAD_REQUEST" } }
```

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
```
[application/json; charset=UTF-8 content]
```

2.11.2.6 | Add CWP Policies (v1)

post /public_api/v1/cwp/policies

Add CWP policy instances.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json; charset=UTF-8'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/policies'
-d '{ "id" : "1", "revision" : 3, "createdAt" : "2024-07-28T18:50:44Z", "modifiedAt" : "2024-07-28T18:50:55Z", "type"
: "COMPLIANCE", "createdBy" : "admin", "disabled" : false, "name" : "some policy", "description" : "some policy
description", "evaluationModes" : [ "PERIODIC" ], "evaluationStage" : "CI", "rulesIds" : [ ], "condition" :
"U29tZUJhc1U2NERhdGE=", "exception" : "U29tZUJhc5U2NERhdGE=", "assetScope" : "U29tZUJh72U2NERhdGE=", "assetGroupsIDs"
: [ 1, 2 ], "assetGroups" : [ "group1", "group2" ], "action" : "ISSUE", "severity" : "CRITICAL",
"missingInformationAction" : "ISSUE", "remediationGuidance" : "some remediation guidance" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-28T18:50:44Z\",\"modifiedAt\":\"2024-07-
```

```
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/cwp/policies",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/cwp/policies") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-28T18:50:44Z\",\"modifiedAt\":\"2024-07-
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "id": "1", "revision": 3, "createdAt": "2024-07-28T18:50:44Z", "modifiedAt": "2024-07-
28T18:50:55Z", "type": "COMPLIANCE", "createdBy": "admin", "disabled": false, "name": "some policy", "description":
"some policy description", "evaluationModes": [ "PERIODIC" ], "evaluationStage": "CI", "rulesIds": [], "condition":
"U29tZUJhc1U2NERhdGE=", "exception": "U29tZUJhc5U2NERhdGE=", "assetScope": "U29tZUJh72U2NERhdGE=", "assetGroupsIDs": [
1, 2 ], "assetGroups": [ "group1", "group2" ], "action": "ISSUE", "severity": "CRITICAL", "missingInformationAction":
"ISSUE", "remediationGuidance": "some remediation guidance" }); const xhr = new XMLHttpRequest(); xhr.withCredentials
= true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/cwp/policies");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cwp/policies")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-28T18:50:44Z\",\"modifiedAt\":\"2024-07-
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "id": "1", "revision": 3,
"createdAt": "2024-07-28T18:50:44Z", "modifiedAt": "2024-07-28T18:50:55Z", "type": "COMPLIANCE", "createdBy": "admin",
"disabled": false, "name": "some policy", "description": "some policy description", "evaluationModes": ["PERIODIC"],
"evaluationStage": "CI", "rulesIds": [], "condition": "U29tZUJhc1U2NERhdGE=", "exception": "U29tZUJhc5U2NERhdGE=",
"assetScope": "U29tZUJh72U2NERhdGE=", "assetGroupsIDs": [1, 2], "assetGroups": ["group1", "group2"], "action":
"ISSUE", "severity": "CRITICAL", "missingInformationAction": "ISSUE", "remediationGuidance": "some remediation
guidance" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/cwp/policies")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/policies", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-28T18:50:44Z\",\"modifiedAt\":\"2024-07-
```

```
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/policies"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-28T18:50:44Z\",\"modifiedAt\":\"2024-07-
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/policies"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"id\":\"1\",\"revision\":3,\"createdAt\":\"2024-07-
28T18:50:44Z\",\"modifiedAt\":\"2024-07-
28T18:50:55Z\",\"type\":\"COMPLIANCE\",\"createdBy\":\"admin\",\"disabled\":false,\"name\":\"some
policy\",\"description\":\"some policy description\",\"evaluationModes\":
[\"PERIODIC\"],\"evaluationStage\":\"CI\",\"rulesIds\":
[],\"condition\":\"U29tZUJhc1U2NERhdGE=\",\"exception\":\"U29tZUJhc5U2NERhdGE=\",\"assetScope\":\"U29tZUJh72U2NERhdGE=\",\"asse
[1,2],\"assetGroups\":
[\"group1\",\"group2\"],\"action\":\"ISSUE\",\"severity\":\"CRITICAL\",\"missingInformationAction\":\"ISSUE\",\"remediationGuid
remediation guidance\"}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```


Body parameters
required
application/json

The schema of a policy

▼ idstring
▼ revisioninteger
▼ createdAtstringdate-time
▼ modifiedAtstringdate-time
▼ typestring (Enum)required

One of the supported policy types

Example:"`MALWARE`"
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ createdBystring
▼ disabledboolean
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:"`CI`"
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ rulesIdsarray[string]required

The UUIDs of the rules that define the condition The `rulesIds` field is only required for non-compliance policies.

▼ conditionstringrequiredbyte

The `condition` field is only required for non-compliance policies.
▼ exceptionstringbyte
▼ assetScopestringbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities

Example:`"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ missingInformationActionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ remediationGuidancestring
REQUEST

```
{ "id": "1", "revision": 3, "createdAt": "2024-07-28T18:50:44Z", "modifiedAt": "2024-07-28T18:50:55Z", "type": "COMPLIANCE", "createdBy": "admin", "disabled": false, "name": "some policy", "description": "some policy description", "evaluationModes": [ "PERIODIC" ], "evaluationStage": "CI", "rulesIds": [], "condition": "U29tZUJhc1U2NERhdGE=", "exception": "U29tZUJhc5U2NERhdGE=", "assetScope": "U29tZUJh72U2NERhdGE=", "assetGroupsIDs": [ 1, 2 ], "assetGroups": [ "group1", "group2" ], "action": "ISSUE", "severity": "CRITICAL", "missingInformationAction": "ISSUE", "remediationGuidance": "some remediation guidance" }
```

Responses

Success

Body
application/json; charset=UTF-8
▼ idstring
RESPONSE

```
[application/json; charset=UTF-8 content]
```

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default

```
[application/json; charset=UTF-8 content]
```

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported
RESPONSE
default
[application/json; charset=UTF-8 content]

2.11.2.7 | Get a CWP Policy by ID (v1)

get /public_api/v1/cwp/policies/{id}

Get a CWP policy by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required
Example: id_example
Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json,application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/policies/{id}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v1/cwp/policies/%7Bid%7D", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

```
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Success

Body
application/json

The schema of a policy

▼ idstring
▼ revisioninteger
▼ createdAtstringdate-time
▼ modifiedAtstringdate-time
▼ typestring (Enum)required

One of the supported policy types

Example:`"MALWARE"`
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ createdBystring
▼ disabledboolean
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:`"CI"`
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ rulesIdsarray[string]required

The UUIDs of the rules that define the condition The `rulesIds` field is only required for non-compliance policies.

▼ conditionstringrequiredbyte

The `condition` field is only required for non-compliance policies.

▼ exceptionstringbyte
▼ assetScopestringbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities

Example:`"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ missingInformationActionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ remediationGuidancestring

RESPONSE


```
{ "id": "1", "revision": 3, "createdAt": "2024-07-28T18:50:44Z", "modifiedAt": "2024-07-28T18:50:55Z", "type":
"COMPLIANCE", "createdBy": "admin", "disabled": false, "name": "some policy", "description": "some policy
description", "evaluationModes": [ "PERIODIC" ], "evaluationStage": "CI", "rulesIds": [], "condition":
"U29tZUJhc1U2NERhdGE=", "exception": "U29tZUJhc5U2NERhdGE=", "assetScope": "U29tZUJh72U2NERhdGE=", "assetGroupsIDs": [
1, 2 ], "assetGroups": [ "group1", "group2" ], "action": "ISSUE", "severity": "CRITICAL", "missingInformationAction":
"ISSUE", "remediationGuidance": "some remediation guidance" }
```


Policy ID not found

Body
application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default


```
{ "err_msg": "Policy ID not found", "metadata": { "code": "NOT_FOUND" } }
```


Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default


```
[application/json; charset=UTF-8 content]
```

2.11.2.8 | Delete a CWP Policy by ID (v1)

delete /public_api/v1/cwp/policies/{id}

Delete a CWP policy by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required

The policy ID to delete

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

Query parameters

▼ closeIssues Boolean

If set, will trigger issue closing of issues opened by the deleted policy

Example: `true`

CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/policies/{id}?closeIssues=true'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("DELETE", "/public_api/v1/cwp/policies/%7Bid%7D?
closeIssues=SOME_BOOLEAN_VALUE", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-
8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?closeIssues=SOME_BOOLEAN_VALUE") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?
closeIssues=SOME_BOOLEAN_VALUE"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?
closeIssues=SOME_BOOLEAN_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?closeIssues=SOME_BOOLEAN_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers
let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: {
(data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?closeIssues=SOME_BOOLEAN_VALUE", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?closeIssues=SOME_BOOLEAN_VALUE"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D?
closeIssues=SOME_BOOLEAN_VALUE"); var request = new RestRequest(Method.DELETE); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Success

Client error

Body

application/json; charset=UTF-8

▼ err_msgstringrequired

The error message
▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

Policy ID not found

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

2.11.2.9 | Update a CWP Policy by ID (v1)

put /public_api/v1/cwp/policies/{id}

Update a CWP policy by its ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id String required

The policy ID to delete

Example: `id_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}
Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'PUT'
-H 'Accept: application/json; charset=UTF-8'
-H 'Content-Type: application/json; charset=UTF-8'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/policies/{id}'
-d '{ "id" : "1", "revision" : 3, "createdAt" : "2024-07-28T18:50:44Z", "modifiedAt" : "2024-07-28T18:50:55Z", "type"
: "COMPLIANCE", "createdBy" : "admin", "disabled" : false, "name" : "some policy", "description" : "some policy
description", "evaluationModes" : [ "PERIODIC" ], "evaluationStage" : "CI", "rulesIds" : [ ], "condition" :
"U29tZUJhc1U2NERhdGE=", "exception" : "U29tZUJhc5U2NERhdGE=", "assetScope" : "U29tZUJh72U2NERhdGE=", "assetGroupsIDs"
: [ 1, 2 ], "assetGroups" : [ "group1", "group2" ], "action" : "ISSUE", "severity" : "CRITICAL",
"missingInformationAction" : "ISSUE", "remediationGuidance" : "some remediation guidance" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("PUT", "/public_api/v1/cwp/policies/%7Bid%7D", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "PUT" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/policies/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PUT", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/policies/%7Bid%7D"); var request = new
RestRequest(Method.PUT); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json; charset=UTF-8

The schema of a policy

▼ idstring

▼ revisioninteger
▼ createdAtstringdate-time
▼ modifiedAtstringdate-time
▼ typestring (Enum)required

One of the supported policy types

Example:`"MALWARE"`
Allowed values:"COMPLIANCE""MALWARE""SECRET""TRUSTED_IMAGES"
▼ createdBystring
▼ disabledboolean
▼ namestringrequired
▼ descriptionstringrequired
▼ evaluationModesarray[string]
▼ evaluationStagestring (Enum)required

One of the supported evaluation stages

Example:`"CI"`
Allowed values:"CI""RUNTIME""DEPLOY"null
▼ rulesIdsarray[string]required

The UUIDs of the rules that define the condition The `rulesIds` field is only required for non-compliance policies.

▼ conditionstringrequiredbyte

The `condition` field is only required for non-compliance policies.

▼ exceptionstringbyte
▼ assetScopestringbyte
▼ assetGroupsIDsarray[integer]required
▼ assetGroupsarray[string]
▼ actionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ severitystring (Enum)required

One of the supported policy severities

Example:`"CRITICAL"`
Allowed values:"LOW""MEDIUM""HIGH""CRITICAL"null
▼ missingInformationActionstring (Enum)required

One of the supported policy actions

Example:`"ISSUE"`
Allowed values:"ISSUE""PREVENT"null
▼ remediationGuidancestring
REQUEST
`[application/json; charset=UTF-8 content]`
Responses

Success

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

Policy ID not found

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
default
`[application/json; charset=UTF-8 content]`

2.11.3 | SBOM

APIs for managing SBOMs

2.11.3.1 | Get the SBOM of the specified asset

get /public_api/v1/assets/{assetID}/sbom

Get an SBOM (Software Bill of Materials) report for the specified asset. You can specify the format and version of the SBOM, as well as which attribute you would like included.

Required license: Cortex Cloud Runtime Security. In Cortex Cloud Posture Management, requires the Cortex Cloud Runtime Security add-on.

Path parameters
▼ assetID String required

ID of the asset of which you want to export the SBOM

Example: `assetID_example`
Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
Query parameters
▼ format String

The format in which the SBOM is to be exported.

Allowed values: XML JSON
Example: `format_example`
▼ output_format String

The version of the SBOM format to be used.

Allowed values: CycloneDX 1.4 SPDX
Example: `outputFormat_example`
▼ attributes String

The list of attributes to be included in the SBOM. If not specified, all fields are included except **`Type`** and **`Name`**, which are always included.

Allowed values: PURL Author Version License Source Package Binaries
Example: `attributes_example`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/xml,application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/assets/{assetID}/sbom?
format=format_example&output_format=outputFormat_example&attributes=attributes_example'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE", CURLOPT_RETURNTRANSFER =>
true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION =>
CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE"); struct curl_slist *headers =
NULL; headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

```
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/assets/%7BassetID%7D/sbom?
format=SOME_STRING_VALUE&output_format=SOME_STRING_VALUE&attributes=SOME_STRING_VALUE"); var request = new
RestRequest(Method.GET); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

OK. The request was successful, and the SBOM data is returned in the specified format.

Body
application/xml
▼ stringbinary
RESPONSE
```
<root>[binary file]</root>
```

Bad Request. The request was malformed, missing the required parameters, or the Asset ID provided does not support SBOM Export.

Body
application/json
▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "example", "err_extra": "example" }
```

The API key provided is invalid or missing.

Body
application/json
▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "example", "err_extra": "example" }
```

Forbidden. The API key does not have the necessary permissions to access the requested resource.

Body
application/json
▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

▼ err_extrastring

Additional information describing the error.

RESPONSE
```
{ "err_code": "example", "err_msg": "example", "err_extra": "example" }
```

The specified asset was not found.

Body

application/json
▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "example", "err_extra": "example" }

An error occurred on the server while processing the request.

Body
application/json
▼ err_codestring

HTTP response code.

▼ err_msgstring

Error message.

▼ err_extrastring

Additional information describing the error.

RESPONSE
{ "err_code": "example", "err_msg": "example", "err_extra": "example" }

2.11.4 | Registry Onboarding

APIs for managing Registry Onboarding

2.11.4.1 | Create a registry connector

post /public_api/v1/cwp/registry_onboarding/instances

Creates a new registry connector for based on the provided details.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
curl -X 'POST'
-H 'Accept: application/json,application/json; charset=UTF-8'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances'
-d '{ "ca_certificate" : "ca_certificate", "tenant_id" : "tenant_id", "allow_static_ips" : true, "repository" :
"repository", "enabled" : true, "password" : "password", "filter_type" : "", "initial_scan_configuration" : { "mode" :
"TAGS_MODIFIED_DAYS", "numDays" : 7 }, "outpost_id" : "outpost_id", "ip_identifier" : "ip_identifier", "broker_id" :
"broker_id", "asset_scope_filters" : { "AND" : [null, null] }, "url" : "url", "insecure_pull" : true, "connector_id"
: "connector_id", "name" : "name", "broker_type" : "", "auth_token" : "auth_token", "region" : "region",

```
"vendor_specific_configuration" : { "group_ids" : "group_ids", "api_domain_name" : "api_domain_name", "project_ids" :
"project_ids" }, "username" : "username" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/cwp/registry_onboarding/instances", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "connector_id": "string", "vendor": "DOCKER", "name": "string", "enabled": true, "url":
"string", "username": "string", "password": "string", "auth_token": "string", "scanning_mode": "CLOUD",
"cloud_provider": "AWS", "outpost_id": "string", "region": "string", "insecure_pull": true, "ca_certificate":
"string", "repository": "string", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 },
"allow_static_ips": true, "ip_identifier": "string", "asset_scope_filters": { "AND": [ { "AND": [ null ] } ] },
"registry_type": "CLOUD_HOSTED", "tenant_id": "string", "broker_type": "BROKER_VM", "broker_id": "string",
"filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "string", "project_ids": "string",
"api_domain_name": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "connector_id": "string", "vendor":
"DOCKER", "name": "string", "enabled": true, "url": "string", "username": "string", "password": "string",
"auth_token": "string", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "string", "region": "string",
"insecure_pull": true, "ca_certificate": "string", "repository": "string", "initial_scan_configuration": [ "mode":
"TAGS_MODIFIED_DAYS", "numDays": 7 ], "allow_static_ips": true, "ip_identifier": "string", "asset_scope_filters":
["AND": [["AND": []]]], "registry_type": "CLOUD_HOSTED", "tenant_id": "string", "broker_type": "BROKER_VM",
"broker_id": "string", "filter_type": "INCLUDE", "vendor_specific_configuration": [ "group_ids": "string",
"project_ids": "string", "api_domain_name": "string" ] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
```

```
=> "POST", CURLOPT_POSTFIELDS => "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ connector_idstring

The connector ID.

▼ vendorstring (Enum)required

Name of the registry vendor.

Allowed values:"DOCKER""JFROG""SONATYPE""DOCKER_HUB""HARBOR""GITLAB_CONTAINER_REGISTRY""OPENSHIFT"

▼ namestringrequired

Name of the registry connector.

▼ enabledboolean

Indicates whether the connector is enabled.

Default:`true`

▼ urlstringrequired

The URL of the registry.

▼ usernamestringrequired

The username for authentication.

▼ passwordstringrequired

The password for authentication.

▼ auth_tokenstringrequired

Token to authenticate the request.

▼ scanning_modestring (Enum)required

The scanning mode used by the connector
Allowed values:"CLOUD""OUTPOST""BROKER""NOT_APPLICABLE""KAPI"
▼ cloud_providerstring (Enum)

Specifies the cloud provider for the Cortex environment to use for registry scanning.

Allowed values:"AWS""GCP""AZURE"
▼ outpost_idstring

The outpost ID.

▼ regionstringrequired

Specifies the region to use for registry scanning. As a best practice, choose the region closest to your registry deployment to achieve the best scanning throughput and potentially reduce cloud costs.

▼ insecure_pullbooleanrequired

When set to `true`, allows image pulls from insecure registries.

▼ ca_certificatestring

Optional. The CA certificate used for authentication.

▼ repositorystring

Optional. The repository used for image discovery.

▼ initial_scan_configurationobjectrequired
▶ modestring (Enum)

Specifies the initial scan configuration mode.

- `ALL` â€ Scans all container images, including every tag, in all discovered repositories.
- `LATEST_TAG` â€ Scans only images tagged as `latest` in all discovered repositories.
- `TAGS_MODIFIED_DAYS` â€ Scans images in each repository modified within the last *X* days, where *X* is set via an argument. You can select a range of up to 90 days for the scan.

▶ numDaysinteger

Number of days for the scan mode `lastNDays`

▼ allow_static_ipsboolean

Optional. Indicates whether static IP addresses are allowed.

▼ ip_identifierstring

Optional. The identifier associated with the IP address.

▼ asset_scope_filtersobject

Defines the type of assets to be filtered (the scope). You can combine multiple conditions to create complex rules for when the asset filter should be applied.

One of ConnectorNode
One of AndConnectorNode
▶ ANDarray
▶ ORarray
▶ SEARCH_FIELDstring

Defines the Field to be searched.

▶ SEARCH_TYPEstring

Defines the comparison operator to use for this filter.

▶ SEARCH_VALUEstring

Defines the value to be searched.

▼ registry_typestring (Enum)

The type of registry.

Allowed values:"CLOUD_HOSTED""SELF_HOSTED"
▼ tenant_idstring

The tenant ID

▼ broker_typeobject
▶ string (Enum)

Indicates the Broker VM type used by the Outpost.

▼ broker_idstring

The broker ID.

▼ filter_typeobject

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

Default: `"INCLUDE"`
▶ string (Enum)

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

▼ vendor_specific_configurationobject

Vendor specific configuration options for scanning.

One of GitlabSpecificConfig
▶ group_idsstring

Optional. The group IDs to scan.

▶ project_idsstring

Optional. The project IDs to scan.

▶ api_domain_namestring

Optional. The API domain name to use for the scan.

▶ repositorystring

Optional. The Docker Hub repository to scan.

▶ cluster_idstring

The unique identifier of the OpenShift cluster.

▶ cluster_namestring

The name of the OpenShift cluster.

▶ cluster_asset_idstring

The asset ID associated with the cluster.

▶ cluster_asset_type_idstring

The asset type ID of the cluster.

▶ cluster_realmstring

The realm or environment in which the cluster resides.

REQUEST ConnectorNode

```
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "AND": [ { "AND": [ {} ] } ] }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "SEARCH_FIELD": "Registry", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "library/ubuntu" }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
```

Responses

Connector details have been stored successfully.

Body
application/json
▼ connector_idstringrequired
RESPONSE
```
{ "connector_id": "example" }
```

Client error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
```
[application/json; charset=UTF-8 content]
```

Service had unexpected internal error

Body
application/json; charset=UTF-8
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
```
[application/json; charset=UTF-8 content]
```

2.11.4.2 | Get a registry connector

get /public_api/v1/cwp/registry_onboarding/instances/{connectorID}

Retrieves a registry connector details using its unique ID.

> **Required license**:
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security.

Path parameters
▼ connectorID String required

The unique identifier for the connector.

Example: `connectorID_example`
Request headers
▼ Authentication String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/{connectorID}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authentication':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241" } conn.request("GET", "/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url)
request["Authentication"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); xhr.setRequestHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") .header("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authentication":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D");
var request = new RestRequest(Method.GET); request.AddHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Connector details retrieved successfully.

Body
application/json
▼ connector_idstring

The connector ID.

▼ vendorstring (Enum)

Name of the registry vendor.

Allowed values:"DOCKER""JFROG""SONATYPE""DOCKER_HUB""HARBOR""GITLAB_CONTAINER_REGISTRY""OPENSHIFT"
▼ namestring

The name of the registry connector.

▼ enabledboolean

Indicates whether the connector is enabled.

Default:`true`
▼ urlstring

The URL of the registry.

▼ usernamestring

The username for authentication.

▼ passwordstring

The password for authentication.

▼ auth_tokenstring

Authentication token used to authorize requests to the API.

▼ scanning_modestring (Enum)

The scanning mode used by the connector

Allowed values:"CLOUD""OUTPOST""BROKER""NOT_APPLICABLE""KAPI"
▼ cloud_providerstring (Enum)

Specifies the cloud provider for the Cortex environment to use for registry scanning.

Allowed values:"AWS""GCP""AZURE"
▼ outpost_idstring

The outpost ID.

▼ regionstring

The region of the connector.

▼ insecure_pullboolean

When set to `true`, allows image pulls from insecure registries.

▼ ca_certificatestring

Optional. The CA certificate used for authentication.

▼ repositorystring

Optional. The repository used for image discovery.

▼ initial_scan_configurationobject
▶ modestring (Enum)

Specifies the initial scan configuration mode.

- `ALL` â€ Scans all container images, including every tag, in all discovered repositories.
- `LATEST_TAG` â€ Scans only images tagged as `latest` in all discovered repositories.
- `TAGS_MODIFIED_DAYS` â€ Scans images in each repository modified within the last *X* days, where *X* is set via an argument. You can select a range of up to 90 days for the scan.

▶ numDaysinteger

Number of days for the scan mode `lastNDays`

▼ allow_static_ipsboolean

Optional. Indicates whether static IP addresses are allowed.

▼ ip_identifierstring

Optional. The identifier associated with the IP address.

▼ asset_scope_filtersobject

Defines the type of assets to be filtered (the scope). You can combine multiple conditions to create complex rules for when the asset filter should be applied.

One of ConnectorNode
One of AndConnectorNode
▶ ANDarray

▶ ORarray
▶ SEARCH_FIELDstring

Defines the Field to be searched.

▶ SEARCH_TYPEstring

Defines the comparison operator to use for this filter.

▶ SEARCH_VALUEstring

Defines the value to be searched.

▼ registry_typestring (Enum)

The type of registry.

Allowed values:"CLOUD_HOSTED""SELF_HOSTED"
▼ tenant_idstring

The tenant ID

▼ broker_typeobject
▶ string (Enum)

Indicates the Broker VM type used by the Outpost.

▼ broker_idstring

The broker ID.

▼ filter_typeobject

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

Default:`"INCLUDE"`
▶ string (Enum)

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

▼ vendor_specific_configurationobject

Vendor specific configuration options for scanning.

One of GitlabSpecificConfig
▶ group_idsstring

Optional. The group IDs to scan.

▶ project_idsstring

Optional. The project IDs to scan.

▶ api_domain_namestring

Optional. The API domain name to use for the scan.

▶ repositorystring

Optional. The Docker Hub repository to scan.

▶ cluster_idstring

The unique identifier of the OpenShift cluster.

▶ cluster_namestring

The name of the OpenShift cluster.

▶ cluster_asset_idstring

The asset ID associated with the cluster.

▶ cluster_asset_type_idstring

The asset type ID of the cluster.

▶ cluster_realmstring

The realm or environment in which the cluster resides.

RESPONSE ConnectorNode


```
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "AND": [ { "AND": [ {} ] } ] }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "SEARCH_FIELD": "Registry", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "library/ubuntu" }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
```


Connector not found.

Body
application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE


```
{ "err_msg": "Policy ID not found", "metadata": { "code": "NOT_FOUND" } }
```


Service had unexpected internal error.

Body
application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE


```
{ "err_msg": "Policy ID not found", "metadata": { "code": "NOT_FOUND" } }
```

2.11.4.3 | Update a registry connector

put /public_api/v1/cwp/registry_onboarding/instances/{connectorID}

Updates the attributes of an existing registry connector identified by its unique ID.

> **Required license:**
>
> Cortex Cloud Posture Management or Cortex Cloud Runtime Security.

Path parameters
▼ connectorID String required

The unique identifier for the connector.

Example: `connectorID_example`
Request headers
▼ Authentication String required

{api_key}
Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'PUT'
-H 'Accept: application/json,application/json; charset=UTF-8'
-H 'Content-Type: application/json'
-H 'Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/{connectorID}'
-d '{ "ca_certificate" : "ca_certificate", "tenant_id" : "tenant_id", "allow_static_ips" : true, "repository" :
"repository", "enabled" : true, "password" : "password", "filter_type" : "", "initial_scan_configuration" : { "mode" :
"TAGS_MODIFIED_DAYS", "numDays" : 7 }, "outpost_id" : "outpost_id", "ip_identifier" : "ip_identifier", "broker_id" :
"broker_id", "asset_scope_filters" : { "AND" : [ null, null ] }, "url" : "url", "insecure_pull" : true, "connector_id"
: "connector_id", "name" : "name", "broker_type" : "", "auth_token" : "auth_token", "region" : "region",
"vendor_specific_configuration" : { "group_ids" : "group_ids", "api_domain_name" : "api_domain_name", "project_ids" :
"project_ids" }, "username" : "username" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}" headers = { 'Authentication':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("PUT",
"/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D", payload, headers) res = conn.getresponse() data
= res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url)
request["Authentication"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "connector_id": "string", "vendor": "DOCKER", "name": "string", "enabled": true, "url":
"string", "username": "string", "password": "string", "auth_token": "string", "scanning_mode": "CLOUD",
"cloud_provider": "AWS", "outpost_id": "string", "region": "string", "insecure_pull": true, "ca_certificate":
"string", "repository": "string", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 },
"allow_static_ips": true, "ip_identifier": "string", "asset_scope_filters": { "AND": [ { "AND": [ null ] } ] },
"registry_type": "CLOUD_HOSTED", "tenant_id": "string", "broker_type": "BROKER_VM", "broker_id": "string",
"filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "string", "project_ids": "string",
"api_domain_name": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); xhr.setRequestHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") .header("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
```

```
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}") .asString();
import Foundation let headers = [ "Authentication":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "connector_id": "string", "vendor":
"DOCKER", "name": "string", "enabled": true, "url": "string", "username": "string", "password": "string",
"auth_token": "string", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "string", "region": "string",
"insecure_pull": true, "ca_certificate": "string", "repository": "string", "initial_scan_configuration": [ "mode":
"TAGS_MODIFIED_DAYS", "numDays": 7 ], "allow_static_ips": true, "ip_identifier": "string", "asset_scope_filters":
["AND": [["AND": []]]], "registry_type": "CLOUD_HOSTED", "tenant_id": "string", "broker_type": "BROKER_VM",
"broker_id": "string", "filter_type": "INCLUDE", "vendor_specific_configuration": [ "group_ids": "string",
"project_ids": "string", "api_domain_name": "string" ] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D");
var request = new RestRequest(Method.PUT); request.AddHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"connector_id\":\"string\",\"vendor\":\"DOCKER\",\"name\":\"string\",\"enabled\":true,\"url\":\"string\",\"username\":\"strin
{\"mode\":\"TAGS_MODIFIED_DAYS\",\"numDays\":7},\"allow_static_ips\":true,\"ip_identifier\":\"string\",\"asset_scope_filters\":
{\"AND\":[{\"AND\":
[null]}]},\"registry_type\":\"CLOUD_HOSTED\",\"tenant_id\":\"string\",\"broker_type\":\"BROKER_VM\",\"broker_id\":\"string\",\"
{\"group_ids\":\"string\",\"project_ids\":\"string\",\"api_domain_name\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ connector_idstring

The connector ID.

▼ vendorstring (Enum)required

Name of the registry vendor.

Allowed values:"DOCKER""JFROG""SONATYPE""DOCKER_HUB""HARBOR""GITLAB_CONTAINER_REGISTRY""OPENSHIFT"

▼ namestringrequired

Name of the registry connector.

▼ enabledboolean

Indicates whether the connector is enabled.

Default:`true`

▼ urlstringrequired

The URL of the registry.

▼ usernamestringrequired

The username for authentication.

▼ passwordstringrequired

The password for authentication.

▼ auth_tokenstringrequired

Token to authenticate the request.

▼ scanning_modestring (Enum)required

The scanning mode used by the connector

Allowed values:"CLOUD""OUTPOST""BROKER""NOT_APPLICABLE""KAPI"

▼ cloud_providerstring (Enum)

Specifies the cloud provider for the Cortex environment to use for registry scanning.

Allowed values:"AWS""GCP""AZURE"

▼ outpost_idstring

The outpost ID.

▼ regionstringrequired

Specifies the region to use for registry scanning. As a best practice, choose the region closest to your registry deployment to achieve the best scanning throughput and potentially reduce cloud costs.

▼ insecure_pullbooleanrequired

When set to `true`, allows image pulls from insecure registries.

▼ ca_certificatestring

Optional. The CA certificate used for authentication.

▼ repositorystring

Optional. The repository used for image discovery.

▼ initial_scan_configurationobjectrequired

▶ modestring (Enum)

Specifies the initial scan configuration mode.

- `ALL` â€ Scans all container images, including every tag, in all discovered repositories.
- `LATEST_TAG` â€ Scans only images tagged as `latest` in all discovered repositories.
- `TAGS_MODIFIED_DAYS` â€ Scans images in each repository modified within the last *X* days, where *X* is set via an argument. You can select a range of up to 90 days for the scan.

▶ numDaysinteger

Number of days for the scan mode `lastNDays`

▼ allow_static_ipsboolean

Optional. Indicates whether static IP addresses are allowed.

▼ ip_identifierstring

Optional. The identifier associated with the IP address.

▼ asset_scope_filtersobject

Defines the type of assets to be filtered (the scope). You can combine multiple conditions to create complex rules for when the asset filter should be applied.

One of ConnectorNode

One of AndConnectorNode

▶ ANDarray

▶ ORarray

▶ SEARCH_FIELDstring

Defines the Field to be searched.

▶ SEARCH_TYPEstring

Defines the comparison operator to use for this filter.

▶ SEARCH_VALUEstring

Defines the value to be searched.

▼ registry_typestring (Enum)

The type of registry.

Allowed values:"CLOUD_HOSTED""SELF_HOSTED"

▼ tenant_idstring

The tenant ID

▼ broker_typeobject

▶ string (Enum)

Indicates the Broker VM type used by the Outpost.

▼ broker_idstring

The broker ID.

▼ filter_typeobject

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

Default:`"INCLUDE"`

▶ string (Enum)

Controls whether `asset_scope_filters` act as an inclusion or exclusion filter.

▼ vendor_specific_configurationobject

Vendor specific configuration options for scanning.

One of GitlabSpecificConfig

▶ group_idsstring

Optional. The group IDs to scan.

▶ project_idsstring

Optional. The project IDs to scan.

▶ api_domain_namestring

Optional. The API domain name to use for the scan.

▶ repositorystring

Optional. The Docker Hub repository to scan.

▶ cluster_idstring

The unique identifier of the OpenShift cluster.

▶ cluster_namestring

The name of the OpenShift cluster.

▶ cluster_asset_idstring

The asset ID associated with the cluster.

▶ cluster_asset_type_idstring

The asset type ID of the cluster.

▶ cluster_realmstring

The realm or environment in which the cluster resides.

REQUEST ConnectorNode


```
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "AND": [ { "AND": [ {} ] } ] }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
{ "connector_id": "example", "vendor": "DOCKER", "name": "example", "enabled": false, "url": "example", "username": "example", "password": "example", "auth_token": "example", "scanning_mode": "CLOUD", "cloud_provider": "AWS", "outpost_id": "example", "region": "example", "insecure_pull": false, "ca_certificate": "example", "repository": "example", "initial_scan_configuration": { "mode": "TAGS_MODIFIED_DAYS", "numDays": 7 }, "allow_static_ips": false, "ip_identifier": "example", "asset_scope_filters": { "SEARCH_FIELD": "Registry", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "library/ubuntu" }, "registry_type": "CLOUD_HOSTED", "tenant_id": "example", "broker_type": "BROKER_VM", "broker_id": "example", "filter_type": "INCLUDE", "vendor_specific_configuration": { "group_ids": "example", "project_ids": "example", "api_domain_name": "example" } }
```


Responses

Connector details have been updated successfully.

Body

application/json

▼ connector_idstringrequired

RESPONSE


```
{ "connector_id": "example" }
```


Client error

Body

application/json; charset=UTF-8

▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE


```
[application/json; charset=UTF-8 content]
```


Connector ID not found

Body

application/json; charset=UTF-8

▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE


```
[application/json; charset=UTF-8 content]
```


Service had unexpected internal error

Body

application/json; charset=UTF-8

▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError
▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE
[application/json; charset=UTF-8 content]

2.11.4.4 | Delete a registry connector

delete /public_api/v1/cwp/registry_onboarding/instances/{connectorID}

Deletes a specific registry connector identified by its unique ID.

Required license:

Cortex Cloud Posture Management or Cortex Cloud Runtime Security.

Path parameters
▼ connectorID String required

The unique identifier for the connector.

Example: connectorID_example
Request headers
▼ Authentication String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/{connectorID}'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'Authentication':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241" } conn.request("DELETE", "/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url)
request["Authentication"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); xhr.setRequestHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D") .header("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .asString();
import Foundation let headers = [ "Authentication":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers
let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: {
```

```
(data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) {
echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "Authentication:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/cwp/registry_onboarding/instances/%7BconnectorID%7D");
var request = new RestRequest(Method.DELETE); request.AddHeader("Authentication",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); IRestResponse response = client.Execute(request);
```

Responses

Connector deleted successfully.

Connector not found.

Body
application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE

```
{ "err_msg": "Policy ID not found", "metadata": { "code": "NOT_FOUND" } }
```

Service had unexpected internal error.

Body
application/json
▼ err_msgstringrequired

The error message

▼ metadataobject

Details for the PublicAPIError

▶ codestring (Enum)required

A short, programmatically safe string indicating the error code reported

RESPONSE

```
{ "err_msg": "Policy ID not found", "metadata": { "code": "NOT_FOUND" } }
```

2.12 | Disable Injection and Prevention Rules Public API

2.12.1 | Preface

The Disable Injection and Prevention Rules API lets you add and manage rules in Cortex XDR that define process-level exceptions, bypassing prevention modules and injection. These rules can be applied only to endpoints running Cortex XDR agent version 7.9 or later.

This API allows you to:

- Fetch existing Disable Injection and Prevention rules with filtering and pagination.
- Add new Disable Injection and Prevention rules to generate a temporary exception to bypass a process from prevention modules and injections.
- Disable existing rules by their IDs.

You can export the OpenAPI specs in the Cortex Stoplight instance

Required license: Cortex Cloud Posture Management or Cortex Cloud Runtime Security
Version: Cortex Cloud

2.12.1.1 | Servers

https://api-yourfqdn

2.12.2 | Default

2.12.2.1 | Get Disable Injection and Prevention rules

post /public_api/v1/disable_injection_prevention_rules/fetch

Retrieves a paginated list of Disable Injection and Prevention rules based on optional filters and sorting criteria.

This endpoint allows you to:

- Retrieve all rules or filter by specific criteria
- Sort results by any field in ascending or descending order
- Paginate through large result sets
- Get total count and filtered count of rules

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_injection_prevention_rules/fetch", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "search_from": 0, "search_to": 1, "sort": { "field": "rule_id",
"keyword": "desc" }, "filters": [ { "field": "status", "operator": "eq", "value": "active" } ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch"); xhr.setRequestHeader("Authorization",
```

"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"search_from\":0,\"search_to\":1,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}") .asString();
import Foundation let headers = ["Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json"] let parameters = ["request_data": ["search_from": 0,
"search_to": 1, "sort": ["field": "rule_id", "keyword": "desc"], "filters": [["field": "status", "operator": "eq",
"value": "active"]]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}", CURLOPT_HTTPHEADER => ["Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241"],]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/fetch"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"search_from\":0,\"search_to\":1,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"desc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":\"active\"}]}}", ParameterType.RequestBody); IRestResponse
response = client.Execute(request);

Body parameters

required

application/json

▼ request_dataobjectrequired

Request body containing pagination, sorting, and filtering parameters.

▶ search_frominteger

Starting index for pagination (zero-based). Defines the offset from which to begin returning results.

▶ search_tointeger

Ending index for pagination (exclusive). Defines the maximum number of results to return (search_to - search_from).

▶ sortobject

Defines sorting criteria for query results.

▶ filtersarray

REQUEST Example 1

{ "request_data": { "search_from": 0, "search_to": 1, "sort": { "field": "rule_id", "keyword": "desc" }, "filters": [
{ "field": "status", "operator": "eq", "value": "active" }] } }

{ "request_data": { "search_from": 0, "search_to": 10, "filters": [{ "field": "rule_name", "operator": "eq", "value": "Protect Critical app" }, { "field": "status", "operator": "eq", "value": "active" }] } }

Responses

Successful response

Body
application/json
▼ replyobject

Container object for the response data and metadata

▶ dataarray
▶ filter_countinteger

The number of rules returned in the current response after applying filters.

▶ total_countinteger

The total number of rules available that match the filter criteria, regardless of pagination.

RESPONSE Example 1

{ "reply": { "data": [{ "rule_id": "24bd70bab9d94905aa18773de2555969", "rule_name": "Protect Critical App", "description": "Disable injection prevention for critical business application", "platform": "windows", "status": "active", "expiration_time": 1770445053461, "process_name": "criticalApp.exe", "path": "string", "created_by": "John Doe", "creation_time": 1770358653000, "is_global": false, "profile_ids": [96] }], "filter_count": 1, "total_count": 6 } }
{ "reply": { "data": [{ "rule_id": "24bd70bab9d94905aa18773de2555969", "rule_name": "Protect Critical App", "description": "Disable injection prevention for critical business application", "platform": "windows", "status": "active", "expiration_time": 1770445053461, "process_name": "criticalApp.exe", "path": "string", "created_by": "Public API - 241", "creation_time": 1770358653000, "is_global": true, "profile_ids": null }], "filter_count": 1, "total_count": 6 } }

Bad Request

Body
application/json
▼ replyobject
▶ err_codeinteger

Numeric error code returned by the API.

▶ err_msgstring

Human-readable summary of the error.

▶ err_extrastring

Detailed description of the error, including the cause and how to resolve it when applicable.

RESPONSE Example 1

{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "search_from: Input should be greater than or equal to 0" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "search_from: Input should be greater than or equal to 0" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "Unknown field 'scope'" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "Unsupported operator 'lte' for field rule_id" } }

2.12.2.2 | Add Disable Injection and Prevention rule

post /public_api/v1/disable_injection_prevention_rules/add

Creates a new Disable Injection and Prevention rule to allow specific processes to bypass injection prevention.

This endpoint allows you to:

- Define a new rule with a unique name and description
- Specify the target platform (Windows, Linux, or macOS)
- Set the process name and path to be protected
- Configure expiration time
- Apply the rule globally or to specific profiles

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/add'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"rule_name\":\"Global Windows Exception\",\"description\":\"Allow injection for trusted Windows application across
all endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}"
headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_injection_prevention_rules/add", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/add") http = Net::HTTP.new(url.host, url.port) http.use_ssl
= true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"rule_name\":\"Global Windows Exception\",\"description\":\"Allow injection for trusted Windows application across
all endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "rule_name": "Global Windows Exception", "description": "Allow
injection for trusted Windows application across all endpoints", "platform": "windows", "process_name":
"trustedapp.exe", "path": "C:\\Program Files\\TrustedApp\\trustedapp.exe", "hours_to_expiration": 24, "profile_ids": [
96 ], "scope": "global" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/add"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/add") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"rule_name\":\"Global Windows Exception\",\"description\":\"Allow injection for trusted Windows application across
all endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}")
.asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "rule_name": "Global
Windows Exception", "description": "Allow injection for trusted Windows application across all endpoints", "platform":
"windows", "process_name": "trustedapp.exe", "path": "C:\Program Files\TrustedApp\trustedapp.exe",
"hours_to_expiration": 24, "profile_ids": [96], "scope": "global" ]] as [String : Any] let postData =
```

```
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/add")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/add", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"rule_name\":\"Global Windows
Exception\",\"description\":\"Allow injection for trusted Windows application across all
endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/add"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"rule_name\":\"Global Windows Exception\",\"description\":\"Allow injection for trusted Windows
application across all
endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/add"); var request
= new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"rule_name\":\"Global Windows
Exception\",\"description\":\"Allow injection for trusted Windows application across all
endpoints\",\"platform\":\"windows\",\"process_name\":\"trustedapp.exe\",\"path\":\"C:\\\\Program
Files\\\\TrustedApp\\\\trustedapp.exe\",\"hours_to_expiration\":24,\"profile_ids\":[96],\"scope\":\"global\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

Request schema for creating a new Disable Injection and Prevention rule. All required fields must be provided to successfully create a rule.

▶ rule_namestringrequired

Unique name for the new rule. Must be between 1-100 characters and should be descriptive of the rule's purpose.

▶ descriptionstringrequired

Description explaining the purpose and context of this rule. Maximum 500 characters.

▶ platformstring (Enum)required

Target operating system to which the rule applies.

▶ process_namestringrequired

Name of the process executable to protect. Must match the exact process name (1-100 characters).

▶ pathstringrequired

Full file system path to the process executable. Must be a valid path for the specified platform (1-1000 characters).

▶ hours_to_expirationinteger (Enum)required

Number of hours until the rule expires. After expiration, the rule will no longer be applied. For example, 24 hours.

▶ profile_idsarray[integer]

Array of profile IDs to which this rule should apply. Required when `scope` is `profile`. Must be `null` or omitted when scope is `global`.

▶ scopestring (Enum)required

Defines the application scope of the rule.

- `global`: Rule applies to all endpoints all matching endpoints (by platform and agent version >= 7.9)
- `profile`: Rule applies only to endpoints in the specified `profile_ids`

REQUEST Profile rule for Windows

```
{ "request_data": { "rule_name": "Global Windows Exception", "description": "Allow injection for trusted Windows application across all endpoints", "platform": "windows", "process_name": "trustedapp.exe", "path": "C:\\Program Files\\TrustedApp\\trustedapp.exe", "hours_to_expiration": 24, "profile_ids": [ 96 ], "scope": "profile" } }
{ "request_data": { "rule_name": "Global Windows Exception", "description": "Allow injection for trusted Windows application across all endpoints", "platform": "windows", "process_name": "trustedapp.exe", "path": "C:\\Program Files\\TrustedApp\\trustedapp.exe", "hours_to_expiration": 24, "profile_ids": [], "scope": "global" } }
{ "request_data": { "rule_name": "Development Server Exception", "description": "Temporary exception for development servers", "platform": "linux", "process_name": "node", "path": "/usr/bin/node", "hours_to_expiration": 24, "scope": "profile", "profile_ids": [ 201, 202 ] } }
{ "request_data": { "rule_name": "macOS Design Tool", "description": "Exception for design application on macOS", "platform": "macos", "process_name": "DesignApp", "path": "/Applications/DesignApp.app/Contents/MacOS/DesignApp", "hours_to_expiration": 48, "scope": "global", "profile_ids": null } }
```

Responses

OK

Body
application/json
▼ replystring

Returns the Disable Injection and Prevention Rule ID.

Example: `"e35dcf2150b74d19ba354fbe871f978d"`
RESPONSE
Example 1

```
{ "reply": "e35dcf2150b74d19ba354fbe871f978d" }
```

Bad Request

Body
application/json
▼ replyobject
▶ err_codeinteger

Numeric error code returned by the API.

▶ err_msgstring

Human-readable summary of the error.

▶ err_extrastring

Detailed description of the error, including the cause and how to resolve it when applicable.

RESPONSE Example 1

```
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "hours_to_expiration: Value error, Invalid value '12'. Allowed values: {24, 48}" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "The following profile ID(s) have a wrong type: [96]. The allowed types are: ['Exceptions']" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "Value error, profile_ids are required when scope is 'profile'" } }
{ "reply": { "err_code": 400, "err_msg": "Got an invalid input while processing XDR public API", "err_extra": "Value error, profile_ids can only be set when scope is 'profile'" } }
```

2.12.2.3 | Disable Disable Injection and Prevention Rules

post /public_api/v1/disable_injection_prevention_rules/disable

Disables one or more existing Disable Injection and Prevention rules by their IDs.

This endpoint allows you to:

- Disable multiple rules in a single request
- Immediately stop rules from being applied

Request headers

▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/disable'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"rule_ids\":
[\"24bd70bab9d94905aa18773de2555969\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_injection_prevention_rules/disable", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/disable") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"rule_ids\":[\"24bd70bab9d94905aa18773de2555969\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "rule_ids": [ "24bd70bab9d94905aa18773de2555969" ] } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/disable"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/disable") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":{\"rule_ids\":
[\"24bd70bab9d94905aa18773de2555969\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["rule_ids":
["24bd70bab9d94905aa18773de2555969"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/disable")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_injection_prevention_rules/disable", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING
=> "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"rule_ids\":
[\"24bd70bab9d94905aa18773de2555969\"]}}", CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/disable"); struct curl_slist *headers = NULL;
```

```
headers = curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"rule_ids\":[\"24bd70bab9d94905aa18773de2555969\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_injection_prevention_rules/disable"); var
request = new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"rule_ids\":[\"24bd70bab9d94905aa18773de2555969\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject

Request schema for disabling one or more existing Disable Injection Prevention rules. Requires at least one valid rule ID.

▶ rule_idsarray[string]required

Array of rule IDs to disable. Must contain at least one valid rule ID.

REQUEST

```
{ "request_data": { "rule_ids": [ "24bd70bab9d94905aa18773de2555969" ] } }
```

Responses

OK

Body
application/json
▼ replystring

Describes the success message.

Example:`"The selected rules were disabled"`
RESPONSE

```
{ "reply": "The selected rules were disabled" }
```

Not Found

Body
application/json
▼ replyobject
▶ err_codeinteger

Numeric error code returned by the API.

▶ err_msgstring

Human-readable summary of the error.

▶ err_extrastring

Detailed description of the error, including the cause and how to resolve it when applicable.

RESPONSE
Example 1

```
{ "reply": { "err_code": 404, "err_msg": "Requested resource not found while processing XDR public API", "err_extra":
"Could not find Disable Injection and Prevention Rule(s) with the following ID(s): ['9133403bfc764080ad8909a6e05b67']"
} }
```

2.13 | Disable Prevention Rule Public APIs

2.13.1 | Preface

The Disable Prevention Rule API lets you manage Disable Prevention rules in Cortex Cloud. These rules allow you to define specific exceptions to prevention actions enforced on endpoints.

You can apply Disable Prevention rules only to endpoints running Cortex XDR agent version 7.9 or later.

Using this API, you can:

- Retrieve existing Disable Prevention rules with support for filtering and pagination.
- Retrieve the list of available modules for a specified platform.
- Create new Disable Prevention rules to configure granular exceptions to endpoint prevention actions.
- Update existing Disable Prevention rules.
- Delete Disable Prevention rules by their IDs.

You can export the OpenAPI specs in the Cortex Stoplight instance.

Required license: Cortex Cloud Posture Management or Cortex Cloud Runtime Security
Version: Cortex Cloud

2.13.1.1 | Servers

https://api-yourfqdn

2.13.2 | Default

2.13.2.1 | Get Disable Prevention Rules

post /public_api/v1/disable_prevention/fetch

Returns a list of Disable Prevention rules based on filters, sorting, and pagination.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_prevention/fetch'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_prevention/fetch", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_prevention/fetch") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "search_from": 0, "search_to": 100, "sort": { "field": "rule_id",
"keyword": "asc" }, "filters": [ { "field": "status", "operator": "eq", "value": {} } ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_prevention/fetch"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/disable_prevention/fetch")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"search_from\":0,\"search_to\":100,\"sort\":{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":
[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "search_from": 0,
"search_to": 100, "sort": [ "field": "rule_id", "keyword": "asc" ], "filters": [ [ "field": "status", "operator":
"eq", "value": [] ] ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/disable_prevention/fetch")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_prevention/fetch", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_prevention/fetch"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}");
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_prevention/fetch"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"search_from\":0,\"search_to\":100,\"sort\":
{\"field\":\"rule_id\",\"keyword\":\"asc\"},\"filters\":[{\"field\":\"status\",\"operator\":\"eq\",\"value\":{}}]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobjectrequired

▶ search_frominteger

Zero-based index of the first Disable Prevention rule to return. Used for pagination.

▶ search_tointeger

Index number of Disable Prevention rules to return starting from `search_from`.

▶ sortobject

▶ filtersarray

REQUEST Example 1

```
{ "request_data": { "search_from": 0, "search_to": 100, "sort": { "field": "rule_id", "keyword": "asc" }, "filters": [
{ "field": "rule_id", "operator": "eq", "value": "1bce99ee792e4f0682d7c9bde0aaf44e" } ] } }
{ "request_data": { "search_from": 0, "search_to": 3, "sort": { "field": "modification_time", "keyword": "desc" },
"filters": [ { "field": "status", "operator": "eq", "value": "enabled" }, { "field": "modification_time", "operator":
"gte", "value": 1762870187000 } ] } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ dataarray

▶ filter_countinteger

The number of rules returned in the current response after applying filters.

▶ total_countinteger

The total number of rules available that match the filter criteria, regardless of pagination.

RESPONSE

Example 1


```
{ "reply": { "data": [ { "rule_id": "1bce99ee792e4f0682d7c9bde0aaf44e", "rule_name": "DPR", "description": "Prevention
rules using API", "platform": "linux", "conditions": { "hash":
"3b7d28f7a6c1e9b0f4a5c2d9e8f1a0b6c7d4e5f8091a2b3c4d5e6f7a8b9c0d1 ", "path": "/*", "signer": "trusted company.inc",
"command": "command line argument", "sign_thumbprint": "certificate thumbprint" }, "module_ids": [ 56 ],
"profile_ids": [ 96 ], "scope": "profile", "status": "enabled", "created_by": "Jane Doe", "user_email":
"jane.doe@example.com", "modification_time": 1764475578200, "associated_targets": [ "endpoint != AFDSFDS" ] } ],
"filter_count": 1, "total_count": 4 } }
```

2.13.2.2 | Get Disable Prevention Modules

post /public_api/v1/disable_prevention/get_modules

Returns a list of available modules for a specific platform.

Request headers

▼ Authorization String required

{api_key}

Example:


```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```


▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl


```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_prevention/get_modules'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"platform\":\"string\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_prevention/get_modules", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_prevention/get_modules") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"platform\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "platform": "string" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_prevention/get_modules"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/disable_prevention/get_modules")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"platform\":\"string\"}}") .asString();
```

```
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["platform":
"string"]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/disable_prevention/get_modules")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST"
request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask
= session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_prevention/get_modules", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"platform\":\"string\"}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_prevention/get_modules"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"platform\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_prevention/get_modules"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"platform\":\"string\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobject

▶ platformstringrequired

Indicates the operating system to which the rule applies. For example, `windows`, `linux`, or `macos`.

REQUEST Example 1

```
{ "request_data": { "platform": "windows" } }
{ "request_data": { "platform": "macos" } }
```

Responses

OK

Body

application/json

▼ replyarray

[

▶ module_idinteger

Module ID associated with the rule.

▶ namestring

Name of the security module.

▶ descriptionstring

Description of the disable prevention rule.

▶ profile_typestring

Type of security profile.

▶ conditions_definitionobject

A combination of parameters configured during rule creation.

▶ additionalPropertiesboolean

▶ minPropertiesinteger
]
RESPONSE
Example 1

```
{ "reply": [ { "module_id": 1, "name": "DLL Security", "description": "Memory Corruption Exploit", "profile_type":
"Exploit", "conditions_definition": { "properties": { "hash": { "type": "string", "description": "Hash" }, "path": {
"type": "string", "description": "Files / Folders", "minLength": 1 }, "command": { "type": "string", "description":
"Command Line", "minLength": 1 }, "signer": { "type": "string", "description": "Signer Name", "minLength": 1 },
"sign_thumbprint": { "type": "string", "description": "Certificate Thumbprint", "minLength": 1 } } },
"additionalProperties": false, "minProperties": 1 } ] }
```

2.13.2.3 | Add Disable Prevention Rule

post /public_api/v1/disable_prevention/add

Creates a new Disable Prevention rule.

Request headers
▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_prevention/add'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_prevention/add", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_prevention/add") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "rule_name": "string", "description": "string", "platform": "string",
"module_ids": [ 0 ], "conditions": { "hash": "string", "path": "string", "signer": "string", "command": "string",
"sign_thumbprint": "string" }, "profile_ids": [ 0 ], "status": "string", "scope": "string" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_prevention/add"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/disable_prevention/add")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
```

{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}") .asString();
import Foundation let headers = ["Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json"] let parameters = ["request_data": ["rule_name":
"string", "description": "string", "platform": "string", "module_ids": [0], "conditions": ["hash": "string", "path":
"string", "signer": "string", "command": "string", "sign_thumbprint": "string"], "profile_ids": [0], "status":
"string", "scope": "string"]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/disable_prevention/add")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_prevention/add", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}", CURLOPT_HTTPHEADER => ["Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241"],]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_prevention/add"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":
[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_prevention/add"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);

Body parameters

required

application/json

▼ request_dataobject

▶ rule_namestringrequired

Name of the disable prevention rule.

▶ descriptionstringrequired

Description explaining the purpose and behavior of the rule.

▶ platformstringrequired

Indicates the operating system to which the rule applies. For example, `windows`, `linux`, or `macos`

▶ module_idsarray[integer]required

A list of module ids associated with the rule.

▶ conditionsobjectrequired

A combination of parameters configured during rule creation.

▶ profile_idsarray[integer]

A list of profile ids to which the rule is applied.

▶ statusstringrequired

Status of the rule (for example, `enabled` or `disabled`).

▶ scopestringrequired

Specifies the scope of the rule, such as `global` (All endpoints) or `profile` (Exception profiles).

REQUEST

Example 1


```
{ "request_data": { "rule_name": "My MacOS Rule", "description": "Data prevention rule for MacOS", "platform":
"macos", "module_ids": [ 38 ], "conditions": { "hash":
"2cf24dba5fb0a30e26e83b2ac5b9e29e1b161e5c1fa7425e73043362938b9824", "path": "/usr/", "signer": "Trusted Company Inc.",
"command": "command line argument" }, "profile_ids": [ 96 ], "status": "enabled", "scope": "profile" } }
```


Responses

OK

Body

application/json

▼ replystring

Returns the Disable Prevention Rule ID.

Example:`"330fc8dec96a4810af886af328e73264"`

RESPONSE

Example 1


```
{ "reply": "330fc8dec96a4810af886af328e73264" }
```

2.13.2.4 | Edit Disable Prevention Rule

post /public_api/v1/disable_prevention/edit

Updates an existing Disable Prevention rule.

Request headers

▼ Authorization String required

{api_key}

Example:

`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl


```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_prevention/edit'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}" headers = {
'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_prevention/edit", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_prevention/edit") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "rule_name": "string", "description": "string", "platform": "string",
"module_ids": [ 0 ], "conditions": { "hash": "string", "path": "string", "signer": "string", "command": "string",
"sign_thumbprint": "string" }, "profile_ids": [ 0 ], "status": "string", "scope": "string", "rule_id":
"5bfb2a15ca2a4525a4e69f11792dfe61" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/disable_prevention/edit");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/disable_prevention/edit")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": [ "rule_name":
"string", "description": "string", "platform": "string", "module_ids": [0], "conditions": [ "hash": "string", "path":
"string", "signer": "string", "command": "string", "sign_thumbprint": "string" ], "profile_ids": [0], "status":
"string", "scope": "string", "rule_id": "5bfb2a15ca2a4525a4e69f11792dfe61" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/v1/disable_prevention/edit")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_prevention/edit", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}", CURLOPT_HTTPHEADER
=> [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_prevention/edit"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":
[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_prevention/edit"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"rule_name\":\"string\",\"description\":\"string\",\"platform\":\"string\",\"module_ids\":[0],\"conditions\":
{\"hash\":\"string\",\"path\":\"string\",\"signer\":\"string\",\"command\":\"string\",\"sign_thumbprint\":\"string\"},\"profile
[0],\"status\":\"string\",\"scope\":\"string\",\"rule_id\":\"5bfb2a15ca2a4525a4e69f11792dfe61\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobjectrequired
▶ rule_namestring

Name of the disable prevention rule.

▶ descriptionstring

Description explaining the purpose and behavior of the rule.

▶ platformstring

Indicates the operating system to which the rule applies. For example, `windows`, `linux`, or `macos`

▶ module_idsarray[integer]

A list of module ids associated with the rule.

▶ conditionsobject

A combination of parameters configured during rule creation.

▶ profile_idsarray[integer]

A list of profile ids to which the rule is applied.

▶ statusstring

Status of the rule (for example, `enabled` or `disabled`).

▶ scopestring

Specifies the scope of the rule, such as `global` (All endpoints) or `profile` (Exception profiles).

▶ rule_idstringrequired

The unique identifier of the Disable Prevention rule.

REQUEST
Example 1
```
{ "request_data": { "rule_name": "My MacOS Rule", "description": "Data prevention rule for MacOS", "platform": "macos", "module_ids": [ 38 ], "conditions": { "hash": "2cf24dba5fb0a30e26e83b2ac5b9e29e1b161e5c1fa7425e73043362938b9824", "path": "/usr/", "signer": "Trusted Company Inc.", "command": "command line argument" }, "profile_ids": [ 96 ], "status": "enabled", "scope": "profile", "rule_id": "5bfb2a15ca2a4525a4e69f11792dfe61" } }
```
Responses

OK

Body
application/json
▼ replystring

Returns the Disable Prevention Rule ID.

Example:`"330fc8dec96a4810af886af328e73264"`
RESPONSE
Example 1
```
{ "reply": "330fc8dec96a4810af886af328e73264" }
```

2.13.2.5 | Delete Disable Prevention Rules

post /public_api/v1/disable_prevention/delete

Deletes one or more Disable Prevention rules based on the provided rule ID.

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`

▼ x-xdr-auth-id String required

{api_key_id}

Example: 241

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/disable_prevention/delete'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"rule_ids\":
[\"00e2308ad4a54fca8b478766ee9de57e\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/disable_prevention/delete", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/disable_prevention/delete") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"rule_ids\":[\"00e2308ad4a54fca8b478766ee9de57e\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "rule_ids": [ "00e2308ad4a54fca8b478766ee9de57e" ] } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/disable_prevention/delete"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/disable_prevention/delete")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":{\"rule_ids\":
[\"00e2308ad4a54fca8b478766ee9de57e\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["rule_ids":
["00e2308ad4a54fca8b478766ee9de57e"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/disable_prevention/delete")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/disable_prevention/delete", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"rule_ids\":[\"00e2308ad4a54fca8b478766ee9de57e\"]}}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/disable_prevention/delete"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"rule_ids\":[\"00e2308ad4a54fca8b478766ee9de57e\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/disable_prevention/delete"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
```

```
request.AddParameter("application/json", "{\"request_data\":{\"rule_ids\":[\"00e2308ad4a54fca8b478766ee9de57e\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ rule_idsarray[string]required

The unique identifier of the Disable Prevention rule.

REQUEST
Example 1
```
{ "request_data": { "rule_ids": [ "00e2308ad4a54fca8b478766ee9de57e" ] } }
```
Responses

OK

Body
application/json
▼ replystring

Describes the result of the API operation.

Example:`"1 rule was deleted."`
RESPONSE
```
{ "reply": "1 rule was deleted." }
```

2.14 | Data Security Posture Management APIs

2.14.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

The Cortex Cloud Data Security solution is an agentless multi-cloud data security platform that discovers, classifies, protects, and governs sensitive data.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: Cortex Cloud

2.14.1.1 | Servers

https://api-yourfqdn

2.14.2 | Inventory

Inventory Management

2.14.2.1 | Get data pattern inventory

post /public_api/v1/data-security/data-patterns

Get all data patterns found in the environment, including high-level aggregations for each of them.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: */*'
-H 'Content-Type: application/json'
```

```
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/data-security/data-patterns'
-d '{ "filter" : "{}", "next_page_token" : "next_page_token", "sort" : [ "sort", "sort" ] }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/data-
security/data-patterns", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/data-security/data-
patterns") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE
request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"filter\":
{},\"sort\":[],\"next_page_token\":\"string\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": {}, "sort": [], "next_page_token": "string" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/data-security/data-patterns"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/data-security/data-patterns")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "filter": [], "sort": [],
"next_page_token": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/data-
security/data-patterns")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod =
"POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/data-
security/data-patterns", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/data-security/data-patterns"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/data-security/data-patterns"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ filterobject

▼ sortarray

▼ next_page_tokenstring

REQUEST

```
{ "filter": {}, "sort": null, "next_page_token": "example" }
```
Responses

OK

Body
/
▼ dataarrayrequired
▼ metadataobjectrequired
▶ total_countintegerint32
▶ filter_countintegerint32
▶ next_page_tokenstring
RESPONSE
```
[*/* content]
```

Bad Request

Body
/
▼ err_msgstringrequired
▼ err_extraarrayrequired
RESPONSE
Example#1
```
[*/* content]
```

Internal Server Error

Body
/
▼ err_msgstringrequired
▼ err_extraarrayrequired
RESPONSE
Example#1
```
[*/* content]
```

2.14.2.2 | Get field inventory details

post /public_api/v1/data-security/objects/fields

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
```
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: */*'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/data-security/objects/fields'
-d '{ "filter" : "{}", "next_page_token" : "next_page_token", "sort" : [ "sort", "sort" ] }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/data-
security/objects/fields", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/data-
security/objects/fields") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
```

```
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"filter\":
{},\"sort\":[],\"next_page_token\":\"string\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": {}, "sort": [], "next_page_token": "string" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/data-security/objects/fields"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/data-security/objects/fields")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "filter": [], "sort": [],
"next_page_token": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/data-
security/objects/fields")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod =
"POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/data-
security/objects/fields", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/data-security/objects/fields"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/data-security/objects/fields"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ filterobject

▼ sortarray

▼ next_page_tokenstring

REQUEST

```
{ "filter": {}, "sort": null, "next_page_token": "example" }
```

Responses

OK

Body

/

▼ dataarrayrequired

▼ metadataobjectrequired

▶ total_countintegerint32

▶ filter_countintegerint32

▶ next_page_tokenstring

RESPONSE

```
[*/* content]
```

Bad Request

Body
/
▼ err_msgstringrequired
▼ err_extraarrayrequired
RESPONSE
Example#1
```
[*/* content]
```

Internal Server Error

Body
/
▼ err_msgstringrequired
▼ err_extraarrayrequired
RESPONSE
Example#1
```
[*/* content]
```

2.14.2.3 | Get file inventory details

post /public_api/v1/data-security/objects/files

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: */*'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
' -H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/data-security/objects/files'
-d '{ "filter" : "{}", "next_page_token" : "next_page_token", "sort" : [ "sort", "sort" ] }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", 'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST", "/public_api/v1/data-
security/objects/files", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/v1/data-
security/objects/files") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
' request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"filter\":
{},\"sort\":[],\"next_page_token\":\"string\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": {}, "sort": [], "next_page_token": "string" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/data-security/objects/files"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/data-security/objects/files")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
") .header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"filter\":{},\"sort\":
[],\"next_page_token\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
", "x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "filter": [], "sort": [],
"next_page_token": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/data-
security/objects/files")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod =
"POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/v1/data-
security/objects/files", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST",
CURLOPT_POSTFIELDS => "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
", "content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/data-security/objects/files"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"); headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/data-security/objects/files"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"); request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"filter\":{},\"sort\":[],\"next_page_token\":\"string\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ filterobject

▼ sortarray

▼ next_page_tokenstring

REQUEST

```
{ "filter": {}, "sort": null, "next_page_token": "example" }
```

Responses

OK

Body

/

▼ dataarrayrequired

▼ metadataobjectrequired

▶ total_countintegerint32

▶ filter_countintegerint32

▶ next_page_tokenstring

RESPONSE

```
[*/* content]
```

Bad Request

Body

/

▼ err_msgstringrequired

▼ err_extraarrayrequired

RESPONSE

Example#1

```
[*/* content]
```

Internal Server Error

Body

/

▼ err_msgstringrequired
▼ err_extraarrayrequired
RESPONSE
Example#1
```
[*/* content]
```

2.15 | Detection Rules Management API

2.15.1 | Preface

API for managing detection rules including CRUD operations for security policies, compliance metadata, and rule configurations.

Version: 1.0.0

2.15.1.1 | Servers

https://api-{fqdn}

2.15.1.2 | Authentication methods

▼ X_CALLER_ID
Api Key "x-xdr-auth-id"

API key authentication using x-xdr-auth-id header

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.

2.15.2 | Detection Rules

Manage detection rules for cloud security posture. Detection rules define XQL queries that identify misconfigurations, compliance violations, and security risks across cloud resources.

2.15.2.1 | Create Detection Rule

post /public_api/v1/rule

Creates a new detection rule with the specified configuration including name, severity, query, and compliance metadata. The rule will be validated and persisted if all required fields are provided correctly.

Request headers
▼ x-xdr-auth-id String required

api_key_id authentication identifier

Example: `123`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: 123'
'https://api-cortex.paloaltonetworks.com/public_api/v1/rule'
-d '{ "severity" : "severity", "metadata" : "", "query" : "", "name" : "name", "description" : "description",
"compliance_metadata" : [ { "control_id" : "control_id" }, { "control_id" : "control_id" }, { "control_id" :
"control_id" }, { "control_id" : "control_id" }, { "control_id" : "control_id" } ], "type" : "type", "class" :
"class", "asset_types" : [ "asset_types" ], "enabled" : true, "labels" : [ "labels", "labels", "labels", "labels",
"labels" ] }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"name\":\"GCP BigQuery Table not encrypted
with CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}" headers = { 'x-xdr-auth-id': "123", 'content-type':
```

```
"application/json" } conn.request("POST", "%7Bfqdn%7D/public_api/v1/rule", payload, headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/v1/rule") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["x-xdr-auth-id"] = '123' request["content-type"] = 'application/json' request.body =
"{\"name\":\"GCP BigQuery Table not encrypted with CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "GCP BigQuery Table not encrypted with CMEK", "description": "This policy
identifies GCP BigQuery tables...", "class": "config", "type": "DETECTION", "asset_types": [ "gcp-bigquery-dataset" ],
"severity": "high", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"GCP\" and
asset_type = \"GCP::BigQuery::Table\" | filter json_extract(config, \"$.encryptionConfiguration.kmsKeyName\") = null |
fields asset_id, asset_name, cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "To configure
CMEK for BigQuery Table, follow the steps..." } }, "compliance_metadata": [ { "control_id": "CIS-AWS-2.1.5" }, {
"control_id": "NIST-AC-3" } ], "labels": [ "Custom Rule", "Security" ], "enabled": true }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/v1/rule"); xhr.setRequestHeader("x-xdr-auth-id", "123");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/v1/rule") .header("x-xdr-auth-id",
"123") .header("content-type", "application/json") .body("{\"name\":\"GCP BigQuery Table not encrypted with
CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "123", "content-type": "application/json" ] let parameters = [
"name": "GCP BigQuery Table not encrypted with CMEK", "description": "This policy identifies GCP BigQuery tables...",
"class": "config", "type": "DETECTION", "asset_types": ["gcp-bigquery-dataset"], "severity": "high", "query": ["xql":
"dataset = cloud_resource_inventory | filter cloud_provider = \"GCP\" and asset_type = \"GCP::BigQuery::Table\" |
filter json_extract(config, \"$.encryptionConfiguration.kmsKeyName\") = null | fields asset_id, asset_name,
cloud_account_id, region"], "metadata": ["issue": ["recommendation": "To configure CMEK for BigQuery Table, follow the
steps..."]], "compliance_metadata": [["control_id": "CIS-AWS-2.1.5"], ["control_id": "NIST-AC-3"]], "labels": ["Custom
Rule", "Security"], "enabled": true ] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/v1/rule")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/public_api/v1/rule",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"name\":\"GCP
BigQuery Table not encrypted with CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-
auth-id: 123" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL
Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/v1/rule"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers,
"x-xdr-auth-id: 123"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"name\":\"GCP BigQuery Table not encrypted
```

```
with CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/rule"); var request = new RestRequest(Method.POST);
request.AddHeader("x-xdr-auth-id", "123"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"name\":\"GCP BigQuery Table not encrypted with
CMEK\",\"description\":\"This policy identifies GCP BigQuery
tables...\",\"class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"gcp-bigquery-
dataset\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"GCP\\\" and asset_type = \\\"GCP::BigQuery::Table\\\" | filter json_extract(config,
\\\"$.encryptionConfiguration.kmsKeyName\\\") = null | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To configure CMEK for BigQuery Table, follow the
steps...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Custom Rule\",\"Security\"],\"enabled\":true}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json

Request body for creating a detection rule

▼ namestringrequired

Unique rule name

▼ descriptionstring

Detailed rule description

▼ classstring

Rule class - Must be 'config' (CSPM)

▼ typestring

Rule type - Must be 'DETECTION' (can be inferred if not provided)

▼ asset_typesarray[string]required

Array with single asset type identifier (exactly one required)

▼ severitystringrequired

Rule severity (low, medium, high, critical, informational)

▼ queryobjectrequired

Query object containing XQL

▶ xqlstringrequired

Valid XQL query string

▼ metadataobject

Metadata containing issue information

▶ issueobject

Issue information

▼ compliance_metadataarray

List of compliance metadata with control IDs

[
▶ control_idstringrequired

Compliance control identifier

]



▼ labelsarray[string]

Custom labels (max 50, each max 100 chars)

▼ enabledboolean

Rule enabled status (default: true)
REQUEST
Create config rule

```
{ "name": "AWS S3 Bucket with Public Access", "description": "Identifies S3 buckets that allow public access", "rule_class": "config", "asset_types": [ "aws-s3-bucket" ], "severity": "high", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name, cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "Remove public access from the S3 bucket by updating the bucket ACL..." } }, "compliance_metadata": [ { "control_id": "CIS-AWS-2.1.5" } ], "labels": [ "S3", "Public Access" ], "enabled": true }
```

Responses

Rule successfully created

Body
application/json

Response for rule operations

▼ idstring

Unique rule identifier

▼ namestring

Rule name

▼ descriptionstring

Rule description

▼ rule_classstring

Rule class

▼ typestring

Rule type

▼ providersarray[string]

Cloud providers (derived from asset_types)

▼ asset_typesarray[string]

Array of asset type identifiers

▼ severitystring

Rule severity

▼ queryobject

Query object

▶ xqlstring

XQL query string

▼ metadataobject

Metadata containing issue information

▶ issueobject

Issue information

▼ compliance_metadataarray

Array of compliance metadata objects with full standard and control information

[
▶ standard_namestring

Full name of the compliance standard

▶ control_idstring

Compliance control identifier

▶ control_namestring

Full name of the compliance control

]

▼ labelsarray[string]

Custom labels

▼ enabledboolean

Rule enabled status

▼ system_defaultboolean

System default rule indicator

▼ created_bystring

Creator identifier

▼ created_onintegerint64

Creation timestamp (epoch milliseconds)

▼ last_modified_bystring

Last modifier

▼ last_modified_onintegerint64

Last modification timestamp (epoch milliseconds)

▼ deletedboolean

Deletion status

▼ deleted_atintegerint64

Deletion timestamp (epoch milliseconds)

▼ deleted_bystring

User who deleted the rule

RESPONSE

Successful rule creation


```
{ "id": "c053f2b7-a106-4550-9f9e-6272e5a45a04", "name": "GCP BigQuery Table not encrypted with CMEK", "description":
"This policy identifies GCP BigQuery tables that are not encrypted with Customer Managed Encryption Keys (CMEK)",
"rule_class": "config", "type": "DETECTION", "providers": [ "gcp" ], "asset_types": [ "gcp-bigquery-dataset" ],
"severity": "high", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"GCP\" and
asset_type = \"GCP::BigQuery::Table\" | filter json_extract(config, \"$.encryptionConfiguration.kmsKeyName\") = null |
fields asset_id, asset_name, cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "To configure a
Customer-managed encryption key (CMEK) for BigQuery Table, follow the steps..." } }, "compliance_metadata": [ {
"standard_name": "Health Insurance Portability and Accountability Act", "control_id": "164.312(a)(2)(iv)",
"control_name": "Encryption and Decryption" }, { "standard_name": "Payment Card Industry Data Security Standard",
"control_id": "3.5.1", "control_name": "Protect encryption keys" } ], "labels": [ "Custom Rule", "Encryption" ],
"enabled": true, "system_default": false, "created_by": "user@example.com", "created_on": 1733452350456,
"last_modified_by": "user@example.com", "last_modified_on": 1733452350456 }
```


Bad Request - Invalid parameters

Body

application/json

▼ err_msgstring

▼ metadataobject

▶ err_extraarray

RESPONSE Missing required fields


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field cannot be empty" }, { "field": "rule_class", "message": "rule_class cannot be empty" }, { "field":
"asset_types", "message": "Field required - Only single asset type must be provided" }, { "field": "severity",
```

"message": "Invalid severity value. Must be one of: low, medium, high, critical, informational" }, { "field": "query.xql", "message": "Field required - XQL query must be provided" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "query.xql", "message": "Invalid XQL query syntax: Expected 'config from' or 'event from' at the beginning of the query" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "rule_class", "message": "Invalid rule_class. Must be 'configuration'" }, { "field": "type", "message": "Invalid type. Must be DETECTION" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "asset_types", "message": "Field required - Only single asset type must be provided" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "asset_types", "message": "Invalid asset type 'invalid-asset'. Must be a valid asset type identifier" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "labels", "message": "Max number of labels allowed: 50" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "compliance_metadata[].control_id", "message": "Control ID does not exist" }] } }
{ "err_msg": "Invalid request body: Failed to parse JSON", "metadata": { "err_extra": [{ "message": "Request body must be valid JSON" }] } }

Unauthorized

Forbidden

Conflict - Rule with same name already exists

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Duplicate rule name
{ "err_msg": "A detection rule with the same name already exists", "metadata": { "err_extra": [{ "field": "name", "message": "Rule name must be unique" }] } }

Too Many Requests

Internal Server Error

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Internal Server Error
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [{ "message": "Internal Server Error" }] } }

Bad Gateway

Service Unavailable

2.15.2.2 | Get Detection Rules

post /public_api/v1/rule/search

Searches for detection rules based on filter criteria with support for pagination and sorting. Returns a list of rules matching the specified filters.

Request headers
▼ x-xdr-auth-id String required

api_key_id authentication identifier

Example: 123
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: 123'
'https://api-cortex.paloaltonetworks.com/public_api/v1/rule/search'
```

```
-d '{ "filter" : "", "search_from" : 0, "sort" : [ { "ORDER" : "ORDER", "FIELD" : "FIELD" }, { "ORDER" : "ORDER",
"FIELD" : "FIELD" } ], "search_to" : 6 }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-63a31769a786\"}],\"OR\":
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}"
headers = { 'x-xdr-auth-id': "123", 'content-type': "application/json" } conn.request("POST",
"%7Bfqdn%7D/public_api/v1/rule/search", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/v1/rule/search") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["x-xdr-auth-id"] = '123' request["content-type"] = 'application/json' request.body =
"{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-
63a31769a786\"}],\"OR\":
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "filter": { "AND": [ { "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE":
"4f900112-eb70-490e-a867-63a31769a786" } ], "OR": [ { "SEARCH_FIELD": "name", "SEARCH_TYPE": "CONTAINS",
"SEARCH_VALUE": "cloud" } ], "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "4f900112-eb70-490e-a867-
63a31769a786" }, "search_from": 0, "search_to": 100, "sort": [ { "FIELD": "name", "ORDER": "ASC" } ] }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/v1/rule/search"); xhr.setRequestHeader("x-xdr-auth-id", "123");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/v1/rule/search") .header("x-xdr-auth-
id", "123") .header("content-type", "application/json") .body("{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-63a31769a786\"}],\"OR\":
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":
[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "123", "content-type": "application/json" ] let parameters = [
"filter": [ "AND": [ [ "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "4f900112-eb70-490e-a867-
63a31769a786" ] ], "OR": [ [ "SEARCH_FIELD": "name", "SEARCH_TYPE": "CONTAINS", "SEARCH_VALUE": "cloud" ] ],
"SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "4f900112-eb70-490e-a867-63a31769a786" ], "search_from": 0,
"search_to": 100, "sort": [ [ "FIELD": "name", "ORDER": "ASC" ] ] ] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/v1/rule/search")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval:
10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/v1/rule/search", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-63a31769a786\"}],\"OR\":
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":
[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id:
123" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error
#:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/v1/rule/search"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "x-xdr-auth-id: 123"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"filter\":{\"AND\":[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-
63a31769a786\"}],\"OR\":
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":
[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/rule/search"); var request = new
RestRequest(Method.POST); request.AddHeader("x-xdr-auth-id", "123"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"filter\":{\"AND\":
[{\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\"EQ\",\"SEARCH_VALUE\":\"4f900112-eb70-490e-a867-63a31769a786\"}],\"OR\":
```

```
[{\"SEARCH_FIELD\":\"name\",\"SEARCH_TYPE\":\"CONTAINS\",\"SEARCH_VALUE\":\"cloud\"}],\"SEARCH_FIELD\":\"id\",\"SEARCH_TYPE\":\
eb70-490e-a867-63a31769a786\"},\"search_from\":0,\"search_to\":100,\"sort\":
[{\"FIELD\":\"name\",\"ORDER\":\"ASC\"}]}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json

Request body for querying detection rules

▼ filterobject

Filter criteria for searching rules

▶ ANDarray

Array of filter criteria to be combined with AND logic

▶ ORarray

Array of filter criteria to be combined with OR logic

▶ SEARCH_FIELDstring

Field name to search on

▶ SEARCH_TYPEstring

Search operation type (EQ, NEQ, CONTAINS, NCONTAINS)

▶ SEARCH_VALUEstring

Value to search for

▼ search_fromintegerint32

Starting index for pagination

▼ search_tointegerint32

Ending index for pagination

▼ sortarray

Sort criteria

[
▶ FIELDstringrequired

Field name to sort by

▶ ORDERstring

Sort order (ASC or DESC)

]
REQUEST
Get rules by Ids

```
{ "filter": { "OR": [ { "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "4f900112-eb70-490e-a867-
63a31769a786" }, { "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "1236bf26-18d5-4393-885d-e828115f5836"
}, { "SEARCH_FIELD": "id", "SEARCH_TYPE": "EQ", "SEARCH_VALUE": "e928a48c-c734-4d89-895f-24220616c2ef" } ] },
"search_from": 0, "search_to": 50, "sort": [ { "FIELD": "name", "ORDER": "ASC" } ] }
```

Responses

OK

Body
application/json

Response containing a list of detection rules with metadata

▼ dataarrayrequired

List of detection rules matching the filter criteria

[
▶ asset_typesarray[string]

Array of asset type identifiers

▶ classstringrequired

Rule class

▶ compliance_metadataarray

Array of compliance metadata objects with full standard and control information

▶ compliance_standardsarray[string]

List of compliance standards associated with the rule

▶ created_bystringrequired

User who created the rule

▶ created_onintegerrequiredint64

Timestamp when the rule was created (milliseconds since epoch)

▶ descriptionstringrequired

Detailed description of the rule

▶ enabledbooleanrequired

Whether the rule is enabled

▶ idstringrequired

Unique identifier of the rule

▶ labelsarray[string]

Custom labels associated with the rule

▶ last_modified_bystringrequired

User who last modified the rule

▶ last_modified_onintegerrequiredint64

Timestamp when the rule was last modified (milliseconds since epoch)

▶ modulestringrequired

Module the rule belongs to

▶ namestringrequired

Name of the rule

▶ providerstringrequired

Cloud provider

▶ severitystring (Enum)required

Severity level of the rule

▶ system_defaultbooleanrequired

Whether this is a system default rule

▶ typestring (Enum)required

Type of the rule

]

▼ metadataobjectrequired

Metadata about the response including counts

▶ filter_countintegerrequiredint64

Number of rules matching the filter criteria

▶ total_countintegerrequiredint64

Total number of rules available

RESPONSE

Successful response with detection rules


```
{ "data": [ { "id": "19403de7-0b16-476f-97c1-2e15ffcb9ab4", "name": "Authorization bypass risk due to a publicly exposed Azure Virtual Machine with an unauthorized Docker API access vulnerability (Docker, CVE-2024-41110)", "description": "Publicly exposed Azure Virtual Machines with unauthorized Docker API access (CVE-2024-41110) pose a significant authorization bypass risk, enabling attackers to execute arbitrary commands and escalate privileges.", "class": "config", "module": "CSPM", "asset_types": [ "azure-vm" ], "severity": "critical", "enabled": true, "system_default": true, "provider": "azure", "type": "config", "compliance_metadata": [ { 'standard_name': "CIS Microsoft Azure Foundations Benchmark", "control_id": "7.1", "control_name": "Ensure that 'OS and Data' disks are encrypted with CMK" } ], "labels": [ "Cloud Security" ], "created_by": "John Doe", "created_on": 1756934040224, "last_modified_by": "Cortex System Admin", "last_modified_on": 1756934040224 } ], "metadata": { "filter_count": 1213, "total_count": 1213 } }
```


Bad Request

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE

Invalid request parameters


```
{ "err_msg": "The request contains invalid parameters", "metadata": { "err_extra": [ { "field": "SEARCH_TYPE", "message": "SEARCH_TYPE 'EBQ' is not supported. Allowed values: EQ, CONTAINS, NCONTAINS, NEQ" } ] } }
```


Unauthorized

Forbidden

Not Found

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE

Data not found


```
{ "err_msg": "Data not found", "metadata": { "err_extra": [ { "message": "Data is not found for the filter criteria" } ] } }
```


Too many requests

Internal Server Error

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE

Internal Server Error


```
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [ { "message": "Internal Server Error" } ] } }
```


Bad Gateway

Service Unavailable

2.15.2.3 | Get Rule By Id

get /public_api/v1/rule/{id}

Retrieves a specific detection rule by its unique identifier. Returns the complete rule configuration including query, compliance metadata, and labels.

Path parameters
▼ id String required

Unique identifier of the detection rule to retrieve

Example: `a1b2c3d4-e5f6-7890-abcd-ef1234567890`
Request headers

▼ x-xdr-auth-id String required

api_key_id authentication identifier

Example: `123`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
-H 'x-xdr-auth-id: 123'
'https://api-cortex.paloaltonetworks.com/public_api/v1/rule/{id}'
```

```
import http.client conn = http.client.HTTPSConnection("api-") headers = { 'x-xdr-auth-id': "123" } conn.request("GET", "%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["x-xdr-auth-id"] = '123' response = http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); xhr.setRequestHeader("x-xdr-auth-id", "123"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890") .header("x-xdr-auth-id", "123") .asString();
```

```
import Foundation let headers = ["x-xdr-auth-id": "123"] let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: 123" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: 123"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); var request = new RestRequest(Method.GET); request.AddHeader("x-xdr-auth-id", "123"); IRestResponse response = client.Execute(request);
```

Responses

Rule successfully retrieved

Body
application/json

Response for rule operations

▼ idstring

Unique rule identifier

▼ namestring

Rule name

▼ descriptionstring

Rule description

▼ rule_classstring

Rule class

▼ typestring

Rule type

▼ providersarray[string]

Cloud providers (derived from asset_types)

▼ asset_typesarray[string]

Array of asset type identifiers

▼ severitystring

Rule severity

▼ queryobject

Query object

▶ xqlstring

XQL query string

▼ metadataobject

Metadata containing issue information

▶ issueobject

Issue information

▼ compliance_metadataarray

Array of compliance metadata objects with full standard and control information

[
▶ standard_namestring

Full name of the compliance standard

▶ control_idstring

Compliance control identifier

▶ control_namestring

Full name of the compliance control

]
▼ labelsarray[string]

Custom labels

▼ enabledboolean

Rule enabled status

▼ system_defaultboolean

System default rule indicator

▼ created_bystring

Creator identifier

▼ created_onintegerint64

Creation timestamp (epoch milliseconds)

▼ last_modified_bystring

Last modifier

▼ last_modified_onintegerint64

Last modification timestamp (epoch milliseconds)

▼ deletedboolean

Deletion status

▼ deleted_atintegerint64

Deletion timestamp (epoch milliseconds)

▼ deleted_bystring

User who deleted the rule

RESPONSE

Successful rule retrieval


```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "name": "AWS S3 Bucket with Public Access", "description": "Identifies S3 buckets that allow public access", "rule_class": "config", "type": "DETECTION", "providers": [ "aws" ], "asset_types": [ "aws-s3-bucket" ], "severity": "high", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name, cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "Remove public access from the S3 bucket by updating the bucket ACL..." } }, "compliance_metadata": [ { "standard_name": "CIS Amazon Web Services Foundations Benchmark", "control_id": "2.1.5", "control_name": "Ensure S3 buckets are configured with Block public access" } ], "labels": [ "S3", "Public Access" ], "enabled": true, "system_default": false, "created_by": "user@example.com", "created_on": 1733452350456, "last_modified_by": "user@example.com", "last_modified_on": 1733452350456 }
```


Bad Request - Invalid ID format

Body

application/json

▼ err_msgstring

▼ metadataobject

▶ err_extraarray

RESPONSE

Invalid ID format


```
{ "err_msg": "Invalid rule ID format", "metadata": { "err_extra": [ { "field": "rule_id", "message": "Expected UUID (e.g., a1b2c3d4-e5f6-7890-abcd-ef1234567890)" } ] } }
```


Unauthorized

Forbidden

Not Found - Rule does not exist

Body

application/json

▼ err_msgstring

▼ metadataobject

▶ err_extraarray

RESPONSE

Rule not found


```
{ "err_msg": "Detection rule not found", "metadata": { "err_extra": [ { "field": "id", "message": "No rule found with the specified ID" } ] } }
```


Too Many Requests

Internal Server Error

Body

application/json

▼ err_msgstring

▼ metadataobject

▶ err_extraarray

RESPONSE

Internal Server Error


```
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [ { "message": "Internal Server Error" } ] } }
```


Bad Gateway

Service Unavailable

2.15.2.4 | Update Detection Rule

patch /public_api/v1/rule/{id}

Updates an existing detection rule with the provided fields. Only the fields included in the request body will be updated. The rule_class field is required for validation.

Path parameters

▼ id String required

Unique identifier of the detection rule to update

Example: `a1b2c3d4-e5f6-7890-abcd-ef1234567890`

Request headers

▼ x-xdr-auth-id String required

api_key_id authentication identifier

Example: `123`

CLIENT REQUEST Bash+curl

```
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: 123'
'https://api-cortex.paloaltonetworks.com/public_api/v1/rule/{id}'
-d '{ "severity" : "severity", "metadata" : "", "rule_class" : "rule_class", "query" : "", "name" : "name",
"description" : "description", "compliance_metadata" : [ { "control_id" : "control_id" }, { "control_id" :
"control_id" }, { "control_id" : "control_id" }, { "control_id" : "control_id" }, { "control_id" : "control_id" } ],
"type" : "type", "asset_types" : [ "asset_types" ], "enabled" : true, "labels" : [ "labels", "labels", "labels",
"labels", "labels" ] }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"name\":\"Updated AWS S3 Bucket
Rule\",\"description\":\"Updated description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":
[\"aws-s3-bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter
cloud_provider = \\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config,
\\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":
[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Updated\",\"Security\"],\"enabled\":true}" headers = { 'x-xdr-auth-id': "123", 'content-type': "application/json" }
conn.request("PATCH", "%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-
e5f6-7890-abcd-ef1234567890") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Patch.new(url) request["x-xdr-auth-id"] = '123' request["content-type"]
= 'application/json' request.body = "{\"name\":\"Updated AWS S3 Bucket Rule\",\"description\":\"Updated
description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"aws-s3-
bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config,
\\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":
[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Updated\",\"Security\"],\"enabled\":true}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "name": "Updated AWS S3 Bucket Rule", "description": "Updated description...",
"rule_class": "config", "type": "DETECTION", "asset_types": [ "aws-s3-bucket" ], "severity": "high", "query": { "xql":
"dataset = cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter
json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name,
cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "To fix this issue..." } },
"compliance_metadata": [ { "control_id": "CIS-AWS-2.1.5" }, { "control_id": "NIST-AC-3" } ], "labels": [ "Updated",
"Security" ], "enabled": true }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PATCH", "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-
7890-abcd-ef1234567890"); xhr.setRequestHeader("x-xdr-auth-id", "123"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-
ef1234567890") .header("x-xdr-auth-id", "123") .header("content-type", "application/json") .body("{\"name\":\"Updated
AWS S3 Bucket Rule\",\"description\":\"Updated
description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"aws-s3-
bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider =
\\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config,
\\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id,
region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":
[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":
[\"Updated\",\"Security\"],\"enabled\":true}") .asString();
import Foundation let headers = [ "x-xdr-auth-id": "123", "content-type": "application/json" ] let parameters = [
"name": "Updated AWS S3 Bucket Rule", "description": "Updated description...", "rule_class": "config", "type":
"DETECTION", "asset_types": ["aws-s3-bucket"], "severity": "high", "query": ["xql": "dataset =
cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter
json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name,
cloud_account_id, region"], "metadata": ["issue": ["recommendation": "To fix this issue..."]], "compliance_metadata":
[["control_id": "CIS-AWS-2.1.5"], ["control_id": "NIST-AC-3"]], "labels": ["Updated", "Security"], "enabled": true ]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
```

```
NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PATCH" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "PATCH", CURLOPT_POSTFIELDS => "{\"name\":\"Updated AWS S3 Bucket Rule\",\"description\":\"Updated description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"aws-s3-bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider = \\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config, \\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id, region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":[\"Updated\",\"Security\"],\"enabled\":true}", CURLOPT_HTTPHEADER => [ "content-type: application/json", "x-xdr-auth-id: 123" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: 123"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"name\":\"Updated AWS S3 Bucket Rule\",\"description\":\"Updated description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"aws-s3-bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider = \\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config, \\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id, region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":[\"Updated\",\"Security\"],\"enabled\":true}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); var request = new RestRequest(Method.PATCH); request.AddHeader("x-xdr-auth-id", "123"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json", "{\"name\":\"Updated AWS S3 Bucket Rule\",\"description\":\"Updated description...\",\"rule_class\":\"config\",\"type\":\"DETECTION\",\"asset_types\":[\"aws-s3-bucket\"],\"severity\":\"high\",\"query\":{\"xql\":\"dataset = cloud_resource_inventory | filter cloud_provider = \\\"AWS\\\" and asset_type = \\\"AWS::S3::Bucket\\\" | filter json_extract(config, \\\"$.acl.grants[*].grantee.uri\\\") contains \\\"AllUsers\\\" | fields asset_id, asset_name, cloud_account_id, region\"},\"metadata\":{\"issue\":{\"recommendation\":\"To fix this issue...\"}},\"compliance_metadata\":[{\"control_id\":\"CIS-AWS-2.1.5\"},{\"control_id\":\"NIST-AC-3\"}],\"labels\":[\"Updated\",\"Security\"],\"enabled\":true}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request body for updating a detection rule

▼ namestring

Rule name (must be unique if changed)

▼ descriptionstring

Rule description

▼ rule_classstringrequired

Rule class - Must be 'config' (CSPM)

▼ typestring

Rule type - Must be 'DETECTION'

▼ asset_typesarray[string]

Array with single asset type identifier (exactly one if provided)

▼ severitystring

Rule severity (low, medium, high, critical, informational)

▼ queryobject

Query object containing XQL (only editable for custom config rules with XQL)

▶ xqlstring

XQL query string (only editable for custom config rules with XQL)

▼ metadataobject

Metadata containing issue information

▶ issueobject

Issue information

▼ compliance_metadataarray

List of compliance metadata with control IDs

[
▶ control_idstring

Compliance control identifier

]
▼ labelsarray[string]

Custom labels (max 50, each max 100 chars)

▼ enabledboolean

Rule enabled status
REQUEST
Update rule with all editable fields

```
{ "name": "Updated AWS S3 Bucket Policy", "description": "Updated description for S3 bucket policy", "rule_class": "config", "type": "DETECTION", "asset_types": [ "aws-s3-bucket" ], "severity": "critical", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name, cloud_account_id, region, config" }, "metadata": { "issue": { "recommendation": "Updated remediation steps:\n1. Login to AWS Console\n2. Navigate to S3\n3. Select the bucket\n4. Go to Permissions tab\n5. Edit Block Public Access settings\n6. Enable all Block Public Access options" } }, "compliance_metadata": [ { "control_id": "CIS-AWS-2.1.5" }, { "control_id": "NIST-AC-3" } ], "labels": [ "Updated", "S3", "Critical" ], "enabled": true }
```

Responses

Rule successfully updated

Body
application/json

Response for rule operations

▼ idstring

Unique rule identifier

▼ namestring

Rule name

▼ descriptionstring

Rule description

▼ rule_classstring

Rule class

▼ typestring

Rule type

▼ providersarray[string]

Cloud providers (derived from asset_types)

▼ asset_typesarray[string]

Array of asset type identifiers

▼ severitystring

Rule severity

▼ queryobject

Query object

▶ xqlstring

XQL query string

▼ metadataobject

Metadata containing issue information

▶ issueobject

Issue information

▼ compliance_metadataarray

Array of compliance metadata objects with full standard and control information

[
▶ standard_namestring

Full name of the compliance standard

▶ control_idstring

Compliance control identifier

▶ control_namestring

Full name of the compliance control

]
▼ labelsarray[string]

Custom labels

▼ enabledboolean

Rule enabled status

▼ system_defaultboolean

System default rule indicator

▼ created_bystring

Creator identifier

▼ created_onintegerint64

Creation timestamp (epoch milliseconds)

▼ last_modified_bystring

Last modifier

▼ last_modified_onintegerint64

Last modification timestamp (epoch milliseconds)

▼ deletedboolean

Deletion status

▼ deleted_atintegerint64

Deletion timestamp (epoch milliseconds)

▼ deleted_bystring

User who deleted the rule
RESPONSE
Successful rule update

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "name": "Updated AWS S3 Bucket Policy", "description": "Updated
description for S3 bucket policy", "rule_class": "config", "type": "DETECTION", "providers": [ "aws" ], "asset_types":
```

["aws-s3-bucket"], "severity": "critical", "query": { "xql": "dataset = cloud_resource_inventory | filter cloud_provider = \"AWS\" and asset_type = \"AWS::S3::Bucket\" | filter json_extract(config, \"$.acl.grants[*].grantee.uri\") contains \"AllUsers\" | fields asset_id, asset_name, cloud_account_id, region" }, "metadata": { "issue": { "recommendation": "Updated remediation steps..." } }, "compliance_metadata": [{ "standard_name": "CIS Amazon Web Services Foundations Benchmark", "control_id": "2.1.5", "control_name": "Ensure S3 buckets are configured with Block public access" }], "labels": ["Updated", "S3", "Critical"], "enabled": true, "system_default": false, "created_by": "user@example.com", "created_on": 1733452350456, "last_modified_by": "admin@example.com", "last_modified_on": 1733552350456 }

Bad Request - Invalid parameters

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE Invalid severity

{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "severity", "message": "Invalid severity value. Must be one of: low, medium, high, critical, informational" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "query.xql", "message": "Invalid XQL query syntax: Expected 'config from' or 'event from' at the beginning of the query" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "asset_types", "message": "Only single asset type must be provided" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "asset_types", "message": "Invalid asset type 'invalid-asset'. Must be a valid asset type identifier" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "labels", "message": "Max number of labels allowed: 50" }] } }
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "compliance_metadata[].control_id", "message": "Control ID does not exist" }] } }
{ "err_msg": "Invalid request body: Failed to parse JSON", "metadata": { "err_extra": [{ "message": "Request body must be valid JSON" }] } }

Unauthorized

Forbidden

Not Found - Rule does not exist

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Rule not found

{ "err_msg": "Detection rule not found", "metadata": { "err_extra": [{ "field": "id", "message": "No rule found with the specified ID" }] } }

Conflict - Name already exists

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Duplicate rule name

{ "err_msg": "A detection rule with the same name already exists", "metadata": { "err_extra": [{ "field": "name", "message": "Rule name must be unique" }] } }

Too Many Requests

Internal Server Error

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray

RESPONSE

Internal Server Error

```
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [ { "message": "Internal Server Error" } ] } }
```

Bad Gateway

Service Unavailable

2.15.2.5 | Delete Detection Rule

delete /public_api/v1/rule/{id}

Permanently deletes a detection rule by its unique identifier. This action cannot be undone. Only custom rules can be deleted; system default rules cannot be removed.

Path parameters

▼ id String required

Unique identifier of the detection rule to delete

Example: `a1b2c3d4-e5f6-7890-abcd-ef1234567890`

Request headers

▼ x-xdr-auth-id String required

api_key_id authentication identifier

Example: `123`

CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'x-xdr-auth-id: 123'
'https://api-cortex.paloaltonetworks.com/public_api/v1/rule/{id}'
```

```
import http.client conn = http.client.HTTPSConnection("api-") headers = { 'x-xdr-auth-id': "123" }
conn.request("DELETE", "%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", headers=headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-
e5f6-7890-abcd-ef1234567890") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) request["x-xdr-auth-id"] = '123' response =
http.request(request) puts response.read_body
```

```
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-
7890-abcd-ef1234567890"); xhr.setRequestHeader("x-xdr-auth-id", "123"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.delete("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-
ef1234567890") .header("x-xdr-auth-id", "123") .asString();
```

```
import Foundation let headers = ["x-xdr-auth-id": "123"] let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE" request.allHTTPHeaderFields = headers
let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: {
(data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "DELETE", CURLOPT_HTTPHEADER => [ "x-xdr-auth-id: 123" ], ]); $response = curl_exec($curl);
$err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); struct curl_slist
*headers = NULL; headers = curl_slist_append(headers, "x-xdr-auth-id: 123"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); CURLcode ret = curl_easy_perform(hnd);
```

```
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/v1/rule/a1b2c3d4-e5f6-7890-abcd-ef1234567890"); var
request = new RestRequest(Method.DELETE); request.AddHeader("x-xdr-auth-id", "123"); IRestResponse response =
client.Execute(request);
```

Responses

Rule successfully deleted (no content)

Bad Request - Invalid ID format

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Invalid ID format

```
{ "err_msg": "Invalid rule ID format", "metadata": { "err_extra": [ { "field": "rule_id", "message": "Expected UUID (e.g., a1b2c3d4-e5f6-7890-abcd-ef1234567890)" } ] } }
```

Unauthorized

Forbidden

Not Found - Rule does not exist

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Rule not found

```
{ "err_msg": "Detection rule not found", "metadata": { "err_extra": [ { "field": "id", "message": "No rule found with the specified ID" } ] } }
```

Too Many Requests

Internal Server Error

Body
application/json
▼ err_msgstring
▼ metadataobject
▶ err_extraarray
RESPONSE
Internal Server Error

```
{ "err_msg": "Internal Server Error", "metadata": { "err_extra": [ { "message": "Internal Server Error" } ] } }
```

Bad Gateway

Service Unavailable

2.16 | Cortex Cloud External Application Management API

2.16.1 | Preface

This OpenAPI Specification provides documentation about External Applications Public APIs for Cortex Cloud. With these endpoints, you can create, read, update, and delete external applications including webhook, Splunk, AWS SQS, AWS S3, and Syslog integrations. These APIs are intended to be accessed via API keys. Therefore, the key must have the RBAC permission `alert_notifications` for list & read operations and permission `alert_notifications_action` for create, edit, enable/disable, & delete operations.

Version: Cortex Cloud

2.16.1.1 | Servers

https://api-{fqdn}

2.16.1.2 | Authentication methods

▼ bearerAuth
HTTP - bearer scheme

JWT token for authentication

Authorized requests to the API should use a **header** with the access token "TOKEN": `Authorization: Bearer TOKEN`, The Bearer token is typically represented in the following format: `JWT`

2.16.2 | External Applications

Operations for managing external applications including creating, editing, deleting, and listing external applications.

2.16.2.1 | Create a new application

post /platform/integration/v1/external-application

Allows the user to create a new external application integration and specify its attributes. To see the possible `application_type` values, please check the relevant enum in the `ExternalApplication` schema for additional information. The `connection_config` attribute is where a user would define AWS SQS, AWS S3, Splunk, Syslog, and webhook configurations; the required formats for these fields are documented in the respective schemas that are linked to the base `ConnectionConfig` schema. Please ensure that you have setup the proper egress configurations on the Cortex Gateway; this API verifies the new connection against the egress configurations specified for the given tenant. If assistance is required, please utilize the cue on the UI menu for creating a new external application configuration.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/integration/v1/external-application'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"name\":\"Test External
Application 01\",\"description\":\"test description for the given external
application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-
45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}" headers = { 'content-type': "application/json" }
conn.request("POST", "%7Bfqdn%7D/platform/integration/v1/external-application", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["content-
type"] = 'application/json' request.body = "{\"request_data\":{\"name\":\"Test External Application
01\",\"description\":\"test description for the given external
application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-
45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "name": "Test External Application 01", "description": "test
description for the given external application", "application_type": "webhook", "connection_config": { "url":
"https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST", "headers": {} } } }); const xhr =
new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application")
.header("content-type", "application/json") .body("{\"request_data\":{\"name\":\"Test External Application
01\",\"description\":\"test description for the given external
application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-
45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "name": "Test
External Application 01", "description": "test description for the given external application", "application_type":
"webhook", "connection_config": [ "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method":
"POST", "headers": [] ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"name\":\"Test External Application
01\",\"description\":\"test description for the given external
application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-
45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
```

```
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/integration/v1/external-application"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"name\":\"Test External Application 01\",\"description\":\"test description for the given external application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application"); var request = new RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"name\":\"Test External Application 01\",\"description\":\"test description for the given external application\",\"application_type\":\"webhook\",\"connection_config\":{\"url\":\"https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96\",\"http_method\":\"POST\",\"headers\":{}}}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
application/json
▼ request_dataobject
▶ namestringrequired

Name of the application.

▶ descriptionstring

Description of the application.

▶ application_typestring (Enum)required

The type of application instance.

▶ connection_configobjectrequired

Connection configuration based on application_type.

▼ application_idobject

Omitted on insert

▼ created_atobject

Omitted on insert

▼ last_modified_byobject

Must be supplied on insert, but not readOnly.

▼ modified_atobject

Omitted on insert

REQUEST

```
{ "request_data": { "name": "Test External Application 01", "description": "test description for the given external application", "application_type": "webhook", "connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" } } }
```

Responses

Application successfully created.

Body
application/json

Enumerates the various attributes of an external application response object

▼ dataobject
▶ application_idintegerint64

Unique identifier

▶ namestring

Name of the application.

▶ descriptionstring

Description of the application.

▶ statusstring (Enum)

Current status of the application.

▶ created_atintegerint64

Timestamp when the application was created.

▶ last_modified_bystring

Identifier of the user who created the app.

▶ last_errorstring

Description summarizing that last known error for the given external application.

▶ last_error_atintegerint64

Timestamp of the last error.

▶ modified_atintegerint64

Timestamp of the last modification.

▶ application_typestring (Enum)

The type of application instance.

▶ connection_configobject

Connection configuration based on application_type.

RESPONSE


```
{ "data": { "application_id": "e94fbc98-3053-6506-876b-f809f344f118", "name": "Test External Application 01",
"description": "test description for the given external application", "status": "connected", "created_at": 1753918286,
"last_modified_by": "john.doe@example.com", "modified_at": 1753918286, "application_type": "webhook",
"connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" },
"last_error": null, "last_error_at": null } }
```


Body

application/json

▼ dataobject

▶ err_msgstring

Error message describing the issue

▶ metadataobject

RESPONSE


```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Test
Connection failed: message={\\\"response_code\\\":404,\\\"message\\\":{\\\"message\\\":\\\"Token \\\\\\\"57f8759b-
9c58-4443-b922-a706\\\\\\\" not found\\\",\\\"id\\\":\\\"\\\"}}", "err_code": 400 } } }
```


Body

application/json

▼ replyobject

▶ err_msgstring

▶ err_extrastring

▶ err_codeinteger

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body

application/json

▼ replyobject

▶ err_msgstring

▶ err_extrastring

▶ err_codeinteger

RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.16.2.2 | List all applications

get /platform/integration/v1/external-application

Retrieves a list of external applications (AWS SQS, AWS S3, Syslog, Splunk, and webhook) and their attributes. The meaning behind all attributes in this response could be found in the `ExternalApplication` schema. Please note that the field `connection_config` is retrieved with masked attributes for security purposes; examples are provided in the sample response shown for this endpoint. Please note that the `last_modified_by`, `last_error`, and `last_error_at` attributes are not populated for Syslog integrations.

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/integration/v1/external-application'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/integration/v1/external-application") res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response =
http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

A list of applications.

Body
application/json
▼ dataarray
[
▶ application_idintegerint64

Unique identifier

▶ namestring

Name of the application.

▶ descriptionstring

Description of the application.

▶ statusstring (Enum)

Current status of the application.

▶ created_atintegerint64

Timestamp when the application was created.

▶ last_modified_bystring

Identifier of the user who created the app.

▶ last_errorstring

Description summarizing that last known error for the given external application.

▶ last_error_atintegerint64

Timestamp of the last error.

▶ modified_atintegerint64

Timestamp of the last modification.

▶ application_typestring (Enum)

The type of application instance.

▶ connection_configobject

Connection configuration based on application_type.

]
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE

```
{ "data": [ { "application_id": 1, "name": "Test External Application 01", "description": "test description for the given external application", "status": "connected", "created_at": 1753918286, "last_modified_by": "john.doe@example.com", "modified_at": 1753918286, "application_type": "webhook", "connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" }, "last_error": null, "last_error_at": null }, { "application_id": 2, "name": "Test External Application 02", "status": "connected", "created_at": 1753918288, "last_modified_by": "john.doe@example.com", "modified_at": 1753918288, "application_type": "splunk", "connection_config": { "hec_endpoint": "https://splunk-hec-****.company.com:8088/services/collector/event", "auth_token": "123-****-****-****-abcd456" }, "last_error": null, "last_error_at": null } ] }
```


Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }
```

2.16.2.3 | Update an existing application (full replacement)

put /platform/integration/v1/external-application/{application_id}

Allows the user to edit an external application and specify its new attributes. To see the possible `application_type` values, please check the relevant enum in the `ExternalApplication` schema for additional information. The `connection_config` attribute is where a user would define AWS SQS, AWS S3, Splunk, Syslog, and webhook configurations; the required formats for these fields are documented in the respective schemas that are linked to the base `ConnectionConfig` schema. Please ensure that you have setup the proper egress configurations on the Cortex Gateway; this API verifies the new connection against the egress configurations specified for the given tenant. If assistance is required, please utilize the cue on the UI menu for creating a new external application configuration.

Path parameters
▼ application_id String required

The unique identifier of the application.

Example: `e94fbc98-3053-6506-876b-f809f344f118`
CLIENT REQUEST Bash+curl
```
curl -X 'PUT'
-H 'Accept: application/json'
```

```
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/integration/v1/external-application/{application_id}'
-d '{ "request_data" : { "application_type" : "syslog", "connection_config" : { "url" :
"https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96" }, "name" : "name", "description" : "description" } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}" headers = { 'content-type': "application/json" }
conn.request("PUT", "%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118") http
= Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Put.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "request_data": { "name": "string", "description": "string", "application_type":
"syslog", "connection_config": { "url": "string", "http_method": "POST", "headers": {} } } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("PUT",
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application/e94fbc98-3053-6506-876b-f809f344f118") .header("content-type", "application/json") .body("
{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "name":
"string", "description": "string", "application_type": "syslog", "connection_config": [ "url": "string",
"http_method": "POST", "headers": [] ] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject:
parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "
{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}", CURLOPT_HTTPHEADER => [ "content-type:
application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-876b-f809f344f118"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "content-type: application/json");
curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/e94fbc98-3053-6506-
876b-f809f344f118"); var request = new RestRequest(Method.PUT); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"name\":\"string\",\"description\":\"string\",\"application_type\":\"syslog\",\"connection_config\":
{\"url\":\"string\",\"http_method\":\"POST\",\"headers\":{}}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

application/json

Enumerates the parameters for an external application request object

▼ request_dataobject

▶ namestringrequired

Name of the application.

▶ descriptionstring

Description of the application.

▶ application_typestring (Enum)required

The type of application instance.

▶ connection_configobjectrequired

Connection configuration based on application_type.

REQUEST

```
{ "request_data": { "name": "Test External Application 03", "description": "test description for the given external application", "application_type": "webhook", "connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" } } }
```

Responses

Application updated successfully.

Body
application/json

Enumerates the various attributes of an external application response object

▼ dataobject
▶ application_idintegerint64

Unique identifier

▶ namestring

Name of the application.

▶ descriptionstring

Description of the application.

▶ statusstring (Enum)

Current status of the application.

▶ created_atintegerint64

Timestamp when the application was created.

▶ last_modified_bystring

Identifier of the user who created the app.

▶ last_errorstring

Description summarizing that last known error for the given external application.

▶ last_error_atintegerint64

Timestamp of the last error.

▶ modified_atintegerint64

Timestamp of the last modification.

▶ application_typestring (Enum)

The type of application instance.

▶ connection_configobject

Connection configuration based on application_type.

RESPONSE

```
{ "data": { "application_id": 2, "name": "Test External Application 03", "description": "test description for the given external application", "status": "connected", "created_at": 1753918287, "last_modified_by": "john.doe@example.com", "modified_at": 1753918288, "application_type": "webhook", "connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" }, "last_error": null, "last_error_at": null } }
```

Body
application/json

▼ dataobject
▶ err_msgstring

Error message describing the issue

▶ metadataobject
RESPONSE
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Application type for a given external application cannot be modified", "err_code": 400 } } }

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key" } }

2.16.2.4 | Delete an application

delete /platform/integration/v1/external-application/{application_type}/id/{application_id}

Allows the user to delete an external application. Deletion is not permitted if the application is associated with an active notification rule.

Path parameters
▼ application_id String required

The unique identifier of the application.

Example: `e94fbc98-3053-6506-876b-f809f344f118`
▼ application_type String required

The application type of the specified application

Example: `syslog`
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/integration/v1/external-
application/{application_type}/id/{application_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("DELETE",
"%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-3053-6506-876b-f809f344f118") res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-3053-6506-876b-
f809f344f118") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE", "https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application/syslog/id/e94fbc98-3053-6506-876b-f809f344f118"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application/syslog/id/e94fbc98-3053-6506-876b-f809f344f118") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-3053-6506-876b-
f809f344f118")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "DELETE" let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
```

```
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-3053-6506-876b-f809f344f118",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "DELETE", ]); $response = curl_exec($curl);
$err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-3053-6506-876b-
f809f344f118"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/syslog/id/e94fbc98-
3053-6506-876b-f809f344f118"); var request = new RestRequest(Method.DELETE); IRestResponse response =
client.Execute(request);
```

Responses

Body
application/json
RESPONSE

```
null
```

Body
application/json
▼ dataobject
▶ err_msgstring

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "External
application not found, id=25", "err_code": 400 } } }
```

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.16.2.5 | Get External Application details by ID

get /platform/integration/v1/external-application/{application_type}/id/{application_id}

Retrieves an external application and returns its attributes. The meaning behind all attributes in this response could be found in the `ExternalApplication` schema.

Path parameters
▼ application_id String required

The unique identifier of the application.

Example: `e94fbc98-3053-6506-876b-f809f344f118`
▼ application_type String required

The application type of the specified application

Example: `webhook`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/integration/v1/external-
application/{application_type}/id/{application_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-3053-6506-876b-f809f344f118") res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-3053-6506-876b-
f809f344f118") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application/webhook/id/e94fbc98-3053-6506-876b-f809f344f118"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/integration/v1/external-
application/webhook/id/e94fbc98-3053-6506-876b-f809f344f118") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-3053-6506-876b-
f809f344f118")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-3053-6506-876b-
f809f344f118", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-3053-6506-876b-
f809f344f118"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/integration/v1/external-application/webhook/id/e94fbc98-
3053-6506-876b-f809f344f118"); var request = new RestRequest(Method.GET); IRestResponse response =
client.Execute(request);
```

Responses

Application details retrieved successfully.

Body
application/json

Enumerates the various attributes of an external application response object

▼ dataobject
▶ application_idintegerint64

Unique identifier

▶ namestring

Name of the application.

▶ descriptionstring

Description of the application.

▶ statusstring (Enum)

Current status of the application.

▶ created_atintegerint64

Timestamp when the application was created.

▶ last_modified_bystring

Identifier of the user who created the app.

▶ last_errorstring

Description summarizing that last known error for the given external application.

▶ last_error_atintegerint64

Timestamp of the last error.

▶ modified_atintegerint64

Timestamp of the last modification.

▶ application_typestring (Enum)

The type of application instance.

▶ connection_configobject

Connection configuration based on application_type.

RESPONSE


```
{ "data": { "application_id": "e94fbc98-3053-6506-876b-f809f344f118", "name": "Test External Application 01",
"description": "test description for the given external application", "status": "connected", "created_at": 1753918286,
"last_modified_by": "john.doe@example.com", "modified_at": 1753918286, "application_type": "webhook",
"connection_config": { "url": "https://webhook.site/305650415-aad3-45ac-9d92-2455105edb96", "http_method": "POST" },
"last_error": null, "last_error_at": null } }
```


Body
application/json
▼ dataobject
▶ err_msgstring

Error message describing the issue

▶ metadataobject

RESPONSE


```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "External
application with id 1bef0d93-e82e-40e5-852b-2ab0a98791b2 not found", "err_code": 400 } } }
```


Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger

RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Body
application/json
▼ replyobject
▶ err_msgstring
▶ err_extrastring
▶ err_codeinteger

RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key" } }
```

2.17 | Managed Services APIs

2.17.1 | Preface

Public endpoints are provided for MTH (Managed Threat Hunting) and MDR (Managed Detection and Response) child tenants to manage reports, comments, and assignment-related operations.

2.17.1.1 | Authentication

All endpoints require API key based authentication using the x-xdr-auth-id and Authorization headers.

2.17.1.2 | Supported Tenants

Access is limited to MTH Child and MDR Child tenants only.

2.17.1.3 | Timestamps

All timestamps must be in milliseconds since the Unix epoch (UTC). **Required licenses:** MDR, MTH, Managed XSIAM Pro, Managed XSIAM Premium.

Version: 1.0.0

2.17.1.3.1 | Servers

https://api-yourfqdn

2.17.1.4 | Authentication methods

▼ Authorization
Api Key "Authorization"

API Key for authentication

Authorized requests to the API should use: **Authorization** inside **a header** with the access token.

▼ x-xdr-auth-id
Api Key "x-xdr-auth-id"

API Key ID for authentication

Authorized requests to the API should use: **x-xdr-auth-id** inside **a header** with the access token.

2.17.2 | Comments

APIs for managing report comments

2.17.2.1 | Add a comment to an MTH/MDR report

post /public_api/v1/mth/child/add_comment

Adds a new comment to an MTH/MDR report from a child tenant.

Notes:

- If the source_id is not found, a generic error response is returned.

Request headers
▼ Authorization String required

{api_key}

Example:
`UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W`
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/add_comment'
-d '{ "attachment_path" : "attachment_path", "comment_text" : "comment_text", "xsoar_source_id" : "xsoar_source_id",
"comment_created_by" : "comment_created_by", "extract_zip_file" : "extract_zip_file" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/add_comment", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
```

```
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/add_comment") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "xsoar_source_id": "string", "comment_text": "string", "comment_created_by": "string",
"attachment_path": "string", "extract_zip_file": "string" }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/v1/mth/child/add_comment");
xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/mth/child/add_comment")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
.asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "xsoar_source_id": "string",
"comment_text": "string", "comment_created_by": "string", "attachment_path": "string", "extract_zip_file": "string" ]
as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/v1/mth/child/add_comment")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/add_comment", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/add_comment"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/add_comment"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"xsoar_source_id\":\"string\",\"comment_text\":\"string\",\"comment_created_by\":\"string\",\"attachment_path\":\"string\",\"
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ xsoar_source_idstringrequired

The unique identifier of the report to comment on

▼ comment_textstringrequired

The text content of the comment

▼ comment_created_bystringrequired

Email or username of the comment author (not validated)

▼ attachment_pathstring

Path to attachment

▼ extract_zip_filestring

Whether to extract zip file

REQUEST

Example 1

```
{ "xsoar_source_id": "777771", "comment_text": "Investigation completed. No malicious activity found.",
"comment_created_by": "analyst@company.com", "attachment_path": "comment/investigation-report-1234567890.pdf",
"extract_zip_file": "false" }
```

Responses

Successful Response

Body

application/json

▼ replyboolean

Indicates if the comment was added successfully

RESPONSE

Example 1

```
{ "reply": true }
```

Bad Request - Invalid parameters or missing required fields

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Unauthorized - Invalid or missing API key

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Forbidden - Tenant not authorized for this endpoint

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message
▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.17.2.2 | Get comments for MTH/MDR reports

post /public_api/v1/mth/child/get_comments

Retrieves comments for a specific report or for all comments within a specified time range.

Validation Rules:

- The request requires either the `xsoar_source_id` parameter or the combination of `start_time` and `end_time` parameters.
- At least one search criteria must be provided

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/get_comments'
-d '{ "start_time" : 0, "xsoar_source_id" : "xsoar_source_id", "end_time" : 6 }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/get_comments", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/get_comments") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
```

```
{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "xsoar_source_id": "string", "start_time": 0, "end_time": 0 }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/mth/child/get_comments"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/mth/child/get_comments")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "xsoar_source_id": "string",
"start_time": 0, "end_time": 0 ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/mth/child/get_comments")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/get_comments", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/get_comments"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/get_comments"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"xsoar_source_id\":\"string\",\"start_time\":0,\"end_time\":0}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

Include either **xsoar_source_id** or the combination of **start_time** and **end_time** in the request.

▼ xsoar_source_idstring

The unique identifier of the report

▼ start_timeintegerint64

Start timestamp in milliseconds (epoch)

▼ end_timeintegerint64

End timestamp in milliseconds (epoch)

REQUEST Get comments by report ID

```
{ "xsoar_source_id": "777772" }
{ "start_time": 1764517583000, "end_time": 1764512583000 }
```

Responses

Successful Response

Body
application/json
▼ replyobject
▶ Additional propertiesobject
RESPONSE
Example 1

```
{ "reply": { "9998546484426": { "status": true, "data": [ { "comment_id": 7, "comment_created_by":
"stam_updated_user", "comment_author_type": 0, "comment_insert_time": 1763468552000, "comment_update_time":
1763468849000, "comment_text": "Update comment stam2025-11-18 14:27:28.123680", "comment_attachments": [],
"xsoar_source_id": "777771", "comment_username": "Managed Threat Hunting" }, { "comment_id": 8, "comment_created_by":
"stam_user", "comment_author_type": 0, "comment_insert_time": 1763468560000, "comment_update_time": null,
"comment_text": "stam comment_2025-11-18 14:22:39.114626", "comment_attachments": [], "xsoar_source_id": "777771",
"comment_username": "Managed Threat Hunting" }, { "comment_id": 21, "comment_created_by": "random_user",
"comment_author_type": 0, "comment_insert_time": 1763468843000, "comment_update_time": null, "comment_text": "stam
comment_2025-11-18 14:27:22.608768", "comment_attachments": [], "xsoar_source_id": "777771", "comment_username":
"analyst@company.com" }, { "comment_id": 34, "comment_created_by": "iavron iavron", "comment_author_type": 1,
"comment_insert_time": 1764235743000, "comment_update_time": null, "comment_text": "Attachment test",
"comment_attachments": [ "https://qa2-test-9998546484426-papi.storage.googleapis.com/comment/Screenshot%202025-11-
27%20at%2010.34.50.png-1764235743000?Expires=1765122615&GoogleAccessId=api-pod%40qa2-test-
9998546484426.iam.gserviceaccount.com&Signature=ku3dHGq8exMve3Hs25iKjDG64ZKqrNPfkCc4G8Njk2hv9aWKnhFqBDC5viMxcZRVMR8EtI7%2BZ7fci
], "xsoar_source_id": "484485", "comment_username": "iavron@paloaltonetworks.com" } ] } } }
```


Bad Request - Invalid parameters or missing required fields

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Unauthorized - Invalid or missing API key

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE

```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Forbidden - Tenant not authorized for this endpoint

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.17.3 | Status

APIs for updating report status

2.17.3.1 | Update report status

post /public_api/v1/mth/child/report/update/status

Updates the status of an MTH/MDR report.

Validation Rules:

- If the specified source_id cannot be found, a generic error response is returned.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/report/update/status'
-d '{ "xsoar_source_id" : "xsoar_source_id", "report_status" : "New" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/report/update/status", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/report/update/status") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
```

```
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "xsoar_source_id": "string", "report_status": "New" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/mth/child/report/update/status"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/mth/child/report/update/status")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "xsoar_source_id": "string",
"report_status": "New" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/mth/child/report/update/status")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/report/update/status", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/report/update/status"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/report/update/status"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"xsoar_source_id\":\"string\",\"report_status\":\"New\"}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Update the report status.

▼ xsoar_source_idstringrequired

The unique identifier of the report

▼ report_statusstring (Enum)required

New status for the report. Must include only one of the supported status values.

Allowed values:"New""In Progress""Pending""Resolved""Closed"
REQUEST
Example 1

```
{ "xsoar_source_id": "777776", "report_status": "In Progress" }
```

Responses

Successful Response

Body
application/json

▼ replyobject

MTH/MDR Report object with uppercase field names (returned by update status endpoint)

▶ XSOAR_SOURCE_IDstring

Unique identifier of the report

▶ NAMEstring

Name/title of the report

▶ DESCRIPTIONstring

Detailed description of the report

▶ CREATED_BYstring

Creator of the report

▶ INSERT_TIMEintegerint64

Creation timestamp in milliseconds (epoch)

▶ UPDATE_TIMEintegerint64

Last update timestamp in milliseconds (epoch)

▶ ATTACHMENTSstring

JSON-formatted string containing attachment information

▶ INCIDENT_IDinteger

Associated incident ID

▶ REPORT_TYPEstring

Type of the report

▶ SEVERITYstring

Severity level of the report

▶ COMMENTSstring

Comments on the report

▶ CLASSIFICATIONstring

Classification of the report (MTH or MDR)

▶ ASSIGNED_USERstring

Email of the assigned user

▶ ASSIGNED_USER_PRETTYstring

Display name of the assigned user

▶ REPORT_STATUSstring

Current status of the report

RESPONSE

Example 1


```
{ "reply": { "XSOAR_SOURCE_ID": "777776", "NAME": "Royi test 2025-11-18 14:27:18.299620", "DESCRIPTION": "Royi",
"CREATED_BY": "Roei", "INSERT_TIME": 1763468832000, "UPDATE_TIME": 1763907713000, "ATTACHMENTS": "
{\"update_report/1763468839243-sample.pdf-d0bc29ba-2b46-46b7-94d6-24826da2c82b\": {\"attachment_name\":
\"sample.pdf\", \"attachment_size\": 55483}}", "INCIDENT_ID": null, "REPORT_TYPE": "Cyber Hygiene Report", "SEVERITY":
"SEV_020_LOW", "COMMENTS": null, "CLASSIFICATION": "MTH", "ASSIGNED_USER": "iavron@paloaltonetworks.com",
"ASSIGNED_USER_PRETTY": "iavron iavron", "REPORT_STATUS": "IN_PROGRESS" } }
```


Bad Request - Invalid parameters or missing required fields

Body
application/json
▼ replyobject
▶ err_codestring

Error code
▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Unauthorized - Invalid or missing API key

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Forbidden - Tenant not authorized for this endpoint

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.17.4 | Assignment

APIs for managing report assignments

2.17.4.1 | Update report assignment

post /public_api/v1/mth/child/report/update/assign

Assigns a user to an MTH/MDR report.

Validation Rules:

- The `user` parameter is validated based on the tenant context; the `username` parameter is not validated
- If the specified source_id is not found, a generic error response is returned.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/report/update/assign'
-d '{ "xsoar_source_id" : "xsoar_source_id", "user" : "user", "username" : "username" }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "
{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/report/update/assign", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/report/update/assign") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "
{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}" response = http.request(request) puts
response.read_body
const data = JSON.stringify({ "xsoar_source_id": "string", "user": "string", "username": "string" }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/mth/child/report/update/assign"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/mth/child/report/update/assign")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("
{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = [ "xsoar_source_id": "string", "user":
"string", "username": "string" ] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters,
options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/mth/child/report/update/assign")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/report/update/assign", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
```

```
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}",
CURLOPT_HTTPHEADER => [ "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/report/update/assign"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/report/update/assign"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "
{\"xsoar_source_id\":\"string\",\"user\":\"string\",\"username\":\"string\"}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```

Body parameters

required

application/json

▼ xsoar_source_idstringrequired

The unique identifier of the report.

▼ userstring

User identifier (email). This parameter is not validated.

▼ usernamestring

Display name of the user.

REQUEST

Example 1

```
{ "xsoar_source_id": "777774", "user": "analyst@company.com", "username": "Motti Analysto" }
```

Responses

Successful Response

Body

application/json

▼ replyobject

▶ successboolean

Indicates if the assignment was successful

▶ xsoar_source_idstring

The source ID of the report

▶ assigned_userstring

Email of the assigned user

RESPONSE

Example 1

```
{ "reply": { "success": true, "xsoar_source_id": "777774", "assigned_user": "analyst@company.com" } }
```

Bad Request - Invalid parameters or missing required fields

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Unauthorized - Invalid or missing API key

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Forbidden - Tenant not authorized for this endpoint

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.17.5 | Reports

APIs for retrieving MTH/MDR reports

2.17.5.1 | Get reports by source ID

post /public_api/v1/mth/child/get_reports_by_source_id

Retrieves detailed information for one or more MTH/MDR reports based on the provided source_id values. At least one source_id must be specified.

Request headers

▼ Authorization String required

{api_key}

Example:

UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W

▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_source_id'
-d '{ "request_data" : { "xsoar_source_ids" : [ "xsoar_source_ids", "xsoar_source_ids" ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":
{\"xsoar_source_ids\":[\"string\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/get_reports_by_source_id", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_source_id") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"xsoar_source_ids\":[\"string\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "xsoar_source_ids": [ "string" ] } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_source_id"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_source_id")
.header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"xsoar_source_ids\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["xsoar_source_ids":
["string"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_source_id")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_source_id", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"xsoar_source_ids\":[\"string\"]}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_source_id"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
```

```
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"xsoar_source_ids\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_source_id"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"xsoar_source_ids\":[\"string\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Retrieves source_id for one or more MTH/MDR reports.

▼ request_dataobject
▶ xsoar_source_idsarray[string]required

List of source IDs to retrieve

REQUEST
Example 1

```
{ "request_data": { "xsoar_source_ids": [ "777774", "777771", "777772" ] } }
```

Responses

Successful Response

Body
application/json
▼ replyarray
[
▶ xsoar_source_idstring

Unique identifier of the report

▶ report_typestring

Type of the report

▶ insert_timeintegerint64

Creation timestamp in milliseconds (epoch)

▶ namestring

Name/title of the report

▶ descriptionstring

Detailed description of the report

▶ incident_idinteger

Associated incident ID

▶ update_timeintegerint64

Last update timestamp in milliseconds (epoch)

▶ created_bystring

Creator of the report

▶ severitystring

Severity level of the report

▶ attachmentsstring

JSON-formatted string containing attachment information

▶ classificationstring

Classification of the report (MTH or MDR)

▶ assigned_userstring

Email of the assigned user

▶ report_statusstring

Current status of the report

▶ assigned_user_prettystring

Display name of the assigned user

]

RESPONSE

Example 1


```
{ "reply": [ { "xsoar_source_id": "777771", "report_type": "Threat Report Update", "insert_time": 1763468832000,
"name": "Updated Report 5", "description": "Updated description", "incident_id": 1, "update_time": 1765983782000,
"created_by": "iavron@paloaltonetworks.com", "severity": "SEV_040_HIGH", "attachments": "
{\"update_report/1764864986901--f2ada4b9-d7f2-43cb-978c-91cc2eb4c97d\": {\"attachment_name\": \"\",
\"attachment_size\": 0}}", "classification": "MTH", "assigned_user": "iavron@paloaltonetworks.com", "report_status":
"ON_HOLD", "assigned_user_pretty": "iavron iavron" }, { "xsoar_source_id": "777772", "report_type": "Monthly Status
Report", "insert_time": 1763468615000, "name": "Royi test 2025-11-18 14:23:40.937528", "description": "Royi",
"incident_id": null, "update_time": 1763468623000, "created_by": "Roei", "severity": "SEV_020_LOW", "attachments": "
{\"update_report/1763468621971-sample.pdf-9b2feb72-0835-4ccf-b49c-e192550bf85f\": {\"attachment_name\":
\"sample.pdf\", \"attachment_size\": 55483}}", "classification": "MTH", "assigned_user": null, "report_status": "New",
"assigned_user_pretty": null }, { "xsoar_source_id": "777774", "report_type": "Threat Report Update", "insert_time":
1763468487000, "name": "Updated Report", "description": "Updated description", "incident_id": null, "update_time":
1766061370000, "created_by": "Test user", "severity": "SEV_040_HIGH", "attachments": "{\"update_report/1764861767462-
-89d3d06a-39c6-4959-aba6-229b786985c2\": {\"attachment_name\": \"\", \"attachment_size\": 0}}", "classification":
"MTH", "assigned_user": "tzohar@paloaltonetworks.com", "report_status": "IN_PROGRESS", "assigned_user_pretty": "Timor
zohar" } ] }
```


Bad Request - Invalid parameters or missing required fields

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE


```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Unauthorized - Invalid or missing API key

Body

application/json

▼ replyobject

▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE


```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Forbidden - Tenant not authorized for this endpoint

Body

application/json

▼ replyobject

▶ err_codestring

Error code
▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.17.5.2 | Get reports by incident ID

post /public_api/v1/mth/child/get_reports_by_incident_id

Retrieves detailed information for one or more MTH/MDR reports based on the provided incident_id values. At least one incident_id must be specified.

Request headers
▼ Authorization String required

{api_key}

Example:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
▼ x-xdr-auth-id String required

{api_key_id}

Example: `241`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
-H 'x-xdr-auth-id: 241'
'https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id'
-d '{ "request_data" : { "incident_ids" : [ "incident_ids", "incident_ids" ] } }'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"incident_ids\":
[\"string\"]}}" headers = { 'Authorization':
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
'x-xdr-auth-id': "241", 'content-type': "application/json" } conn.request("POST",
"/public_api/v1/mth/child/get_reports_by_incident_id", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id") http = Net::HTTP.new(url.host, url.port) http.use_ssl =
true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request["x-xdr-auth-id"] = '241' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"incident_ids\":[\"string\"]}}" response = http.request(request) puts response.read_body
```

```
const data = JSON.stringify({ "request_data": { "incident_ids": [ "string" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id"); xhr.setRequestHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
xhr.setRequestHeader("x-xdr-auth-id", "241"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id") .header("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
.header("x-xdr-auth-id", "241") .header("content-type", "application/json") .body("{\"request_data\":
{\"incident_ids\":[\"string\"]}}") .asString();
import Foundation let headers = [ "Authorization":
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
"x-xdr-auth-id": "241", "content-type": "application/json" ] let parameters = ["request_data": ["incident_ids":
["string"]]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let
request = NSMutableURLRequest(url: NSURL(string: "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"incident_ids\":[\"string\"]}}", CURLOPT_HTTPHEADER => [
"Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
"content-type: application/json", "x-xdr-auth-id: 241" ], ]); $response = curl_exec($curl); $err = curl_error($curl);
curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "Authorization:
UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9W
headers = curl_slist_append(headers, "x-xdr-auth-id: 241"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"incident_ids\":[\"string\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/v1/mth/child/get_reports_by_incident_id"); var request =
new RestRequest(Method.POST); request.AddHeader("Authorization",
"UCoWpG4rkNzgCp2dsh8m02iVpZsskwKHz7N1tErPcUV3Wmf59Gc9kytmgOv0pDWoem3PBlORyRIPiir4OcYdWUOWAM3JyTgoCxQf4nQoTlKmFRKz9Bj5vIjluw66p9
request.AddHeader("x-xdr-auth-id", "241"); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"incident_ids\":[\"string\"]}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Retrieves incident_id for one or more MTH/MDR reports.

▼ request_dataobject
▶ incident_idsarray[string]required

List of incident IDs to retrieve

REQUEST
Example 1

```
{ "request_data": { "incident_ids": [ "777773", "15" ] } }
```

Responses

Successful Response

Body
application/json
▼ replyarray
[
▶ xsoar_source_idstring

Unique identifier of the report

▶ report_typestring

Type of the report

▶ insert_timeintegerint64

Creation timestamp in milliseconds (epoch)

▶ namestring

Name/title of the report

▶ descriptionstring

Detailed description of the report

▶ incident_idinteger

Associated incident ID

▶ update_timeintegerint64

Last update timestamp in milliseconds (epoch)

▶ created_bystring

Creator of the report

▶ severitystring

Severity level of the report

▶ attachmentsstring

JSON-formatted string containing attachment information

▶ classificationstring

Classification of the report (MTH or MDR)

▶ assigned_userstring

Email of the assigned user

▶ report_statusstring

Current status of the report

▶ assigned_user_prettystring

Display name of the assigned user

]
RESPONSE
Example 1


```
{ "reply": [ { "xsoar_source_id": "777773", "report_type": "Threat Report Update1", "insert_time": 1763468832000,
"name": "Updated Report 5", "description": "Updated description", "incident_id": 777773, "update_time": 1765983782000,
"created_by": "iavron@paloaltonetworks.com", "severity": "SEV_040_HIGH", "attachments": "
{\"update_report/1764864986901--f2ada4b9-d7f2-43cb-978c-91cc2eb4c97d\": {\"attachment_name\": \"\",
\"attachment_size\": 0}}", "classification": "MTH", "assigned_user": "iavron@paloaltonetworks.com", "report_status":
"ON_HOLD", "assigned_user_pretty": "iavron iavron" }, { "xsoar_source_id": "15", "report_type": "Threat Report
Update2", "insert_time": 1763468832002, "name": "Updated Report 6", "description": "Updated description",
"incident_id": 15, "update_time": 1765983782003, "created_by": "iavron1@paloaltonetworks.com", "severity":
"SEV_040_HIGH", "attachments": "{\"update_report/1764864986901--f2ada4b9-d7f2-43cb-978c-91cc2eb4c97e\":
{\"attachment_name\": \"\", \"attachment_size\": 0}}", "classification": "MTH", "assigned_user":
"iavron@paloaltonetworks.com", "report_status": "ON_HOLD", "assigned_user_pretty": "iavron1 iavron1" } ] }
```


Bad Request - Invalid parameters or missing required fields

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message
▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Unauthorized - Invalid or missing API key

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Forbidden - Tenant not authorized for this endpoint

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal Server Error

Body
application/json
▼ replyobject
▶ err_codestring

Error code

▶ err_msgstring

Error message

▶ err_extrastring

Extra information about the error

RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.18 | NetScan Public API

2.18.1 | Preface

Public API for network scan configuration and management. Use these endpoints to create scan definitions from templates, launch scan runs, monitor scan status, and control running scans with pause, resume, or abort commands.

Required permission: `network_scanners_action`
Version: 1.0.0

2.18.1.1 | Servers

https://api-{fqdn}

2.18.2 | Vulnerability Network Scan Management

Endpoints for managing network vulnerability scans, including scan definitions, scan runs, and scan control commands.

2.18.2.1 | Launch a scan run

post /public_api/netscan/v1/scan/run

Launch a scan execution using a previously configured scan definition. Optionally override the target IP addresses for this specific run.

Request headers
▼ User-Agent String required
Example: `userAgent_example`
CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/run'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}" headers = { 'User-Agent': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "%7Bfqdn%7D/public_api/netscan/v1/scan/run", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["User-Agent"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "definition_id": 123, "target": "1.2.3.4.0/12" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run"); xhr.setRequestHeader("User-Agent", "SOME_STRING_VALUE");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run") .header("User-
Agent", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}") .asString();
import Foundation let headers = [ "User-Agent": "SOME_STRING_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "definition_id": 123, "target": "1.2.3.4.0/12" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}",
CURLOPT_HTTPHEADER => [ "User-Agent: SOME_STRING_VALUE", "content-type: application/json" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run"); var request = new
RestRequest(Method.POST); request.AddHeader("User-Agent", "SOME_STRING_VALUE"); request.AddHeader("content-type",
```

```
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json
▼ request_dataobject
▶ definition_idintegerrequired

Scan definition ID to execute

▶ targetstring

IP address or IP range. If provided, overrides the targets configured in the scan definition for this run.

REQUEST
```
{ "request_data": { "definition_id": 123, "target": "1.2.3.4.0/12" } }
```
Responses

Scan launched successfully

Body
application/json

Response returned after a scan action (launch, pause, resume, or abort)

▼ DATAstringrequired

Action result message

Example:`"Scan launched successfully with run ID: 789"`
RESPONSE
```
{ "DATA": "Scan launched successfully with run ID: 789" }
```

Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```

User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE

{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Not found

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

2.18.2.2 | Get scan run status

get /public_api/netscan/v1/scan/run

Retrieve the current status of a scan run by its ID. Use the `fields` parameter to specify which fields to return in the response.

Request headers
▼ User-Agent String required
Example: `userAgent_example`
Query parameters
▼ id Long required

Scan run ID to check status for

int64
Example: `789`
▼ fields array[String] required

Fields to include in the response (for example, `status`).

CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/run?id=789&fields='
```

```
import http.client conn = http.client.HTTPSConnection("api-") headers = { 'User-Agent': "SOME_STRING_VALUE" }
conn.request("GET", "%7Bfqdn%7D/public_api/netscan/v1/scan/run?id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE",
headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?
id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["User-Agent"] =
'SOME_STRING_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?
id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE"); xhr.setRequestHeader("User-Agent", "SOME_STRING_VALUE");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?
id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE") .header("User-Agent", "SOME_STRING_VALUE") .asString();
import Foundation let headers = ["User-Agent": "SOME_STRING_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE")!
as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET"
request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "User-Agent:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE");
curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run?
id=SOME_INTEGER_VALUE&fields=SOME_ARRAY_VALUE"); var request = new RestRequest(Method.GET); request.AddHeader("User-
Agent", "SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Scan status retrieved successfully

Body
application/json

Response containing the current status of a scan run

▼ DATAstringrequired

Scan status message

Example:`"Scan is in Running state"`
RESPONSE

```
{ "DATA": "Scan is in Running state" }
```

Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE

```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```

User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Run ID not found

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

2.18.2.3 | Launch a scan run by definition ID

post /public_api/netscan/v1/scan/run/{id}

Launch a scan execution using a scan definition specified by the path parameter. Optionally override the target IP addresses for this run.

Path parameters
▼ id Long required

Scan definition ID
Example: `789`
Request headers
▼ User-Agent String required
Example: `userAgent_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/run/{id}'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}" headers = { 'User-Agent': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D", payload, headers) res
= conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["User-
Agent"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "definition_id": 123, "target": "1.2.3.4.0/12" } }); const xhr = new
XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if
(this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D"); xhr.setRequestHeader("User-Agent",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D")
.header("User-Agent", "SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}") .asString();
import Foundation let headers = [ "User-Agent": "SOME_STRING_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": [ "definition_id": 123, "target": "1.2.3.4.0/12" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}", CURLOPT_HTTPHEADER => [ "User-Agent: SOME_STRING_VALUE",
"content-type: application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D"); var request = new
RestRequest(Method.POST); request.AddHeader("User-Agent", "SOME_STRING_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"definition_id\":123,\"target\":\"1.2.3.4.0/12\"}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```
Body parameters
required
application/json
▼ request_dataobject
▶ definition_idintegerrequired

Scan definition ID to execute

▶ targetstring

IP address or IP range. If provided, overrides the targets configured in the scan definition for this run.

REQUEST
```
{ "request_data": { "definition_id": 123, "target": "1.2.3.4.0/12" } }
```

Responses

Scan launched successfully

Body
application/json

Response returned after a scan action (launch, pause, resume, or abort)

▼ DATAstringrequired

Action result message

Example:`"Scan launched successfully with run ID: 789"`
RESPONSE

```
{ "DATA": "Scan launched successfully with run ID: 789" }
```


Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE

```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```


User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE

```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```


Not found

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details
RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

2.18.2.4 | Get scan run status by ID

get /public_api/netscan/v1/scan/run/{id}

Retrieve the current status of a specific scan run identified by the path parameter. Use the `fields` parameter to specify which fields to return in the response.

Path parameters
▼ id Long required

Scan run ID

Example: `789`
Request headers
▼ User-Agent String required
Example: `userAgent_example`
Query parameters
▼ fields array[String] required

Fields to include in the response (for example, `status`).

CLIENT REQUEST Bash+curl
curl -X 'GET'
-H 'Accept: application/json'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/run/{id}?fields='
import http.client conn = http.client.HTTPSConnection("api-") headers = { 'User-Agent': "SOME_STRING_VALUE" }
conn.request("GET", "%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE", headers=headers) res
= conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) request["User-Agent"] = 'SOME_STRING_VALUE' response = http.request(request) puts
response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET",
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE");
xhr.setRequestHeader("User-Agent", "SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?
fields=SOME_ARRAY_VALUE") .header("User-Agent", "SOME_STRING_VALUE") .asString();
import Foundation let headers = ["User-Agent": "SOME_STRING_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields =

```
headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE", CURLOPT_RETURNTRANSFER =>
true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION =>
CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "User-Agent: SOME_STRING_VALUE" ], ]);
$response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; }
else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?fields=SOME_ARRAY_VALUE"); struct curl_slist *headers
= NULL; headers = curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D?
fields=SOME_ARRAY_VALUE"); var request = new RestRequest(Method.GET); request.AddHeader("User-Agent",
"SOME_STRING_VALUE"); IRestResponse response = client.Execute(request);
```

Responses

Scan status retrieved successfully

Body
application/json

Response containing the current status of a scan run

▼ DATAstringrequired

Scan status message

Example:`"Scan is in Running state"`
RESPONSE
```
{ "DATA": "Scan is in Running state" }
```

Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```

User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE

{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Run ID not found

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

2.18.2.5 | Create a scan definition

post /public_api/netscan/v1/scan/definition

Create a new scan definition with detailed settings and validation options. A scan definition specifies the targets, schedule, credentials, and scan parameters used when launching scan runs.

Request headers
▼ User-Agent String required
Example: `userAgent_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json; charset=UTF-8'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/definition'
-d '{ "plugins_timeout" : 5, "excluded_targets" : [ "" ], "schedule_days" : 127, "schedule_quiet_hours" : [ ],
"network_scanner_ids" : [ "scanner-1", "scanner-2" ], "schedule_cadence" : "DAILY", "description" : "Weekly security
scan for production servers", "disable_wmi_search" : "1", "exclude_printers" : "1", "target_ids" : [ ],
"scanner_plugins_timeout" : 3600, "targets" : [ "192.168.1.0/24", "10.0.0.1-10.0.0.100" ], "enable_report" : true,
"network" : 1, "definition_id" : 123, "schedule_dates" : [ ], "credential_ids" : [ 1 ], "schedule_start_date" :
1765083183326, "timeout_retry" : 5, "max_hosts" : 30, "strict_unauthenticated" : "0", "override_target_exclusions" :
false, "port_list_id" : 5, "auth_port_ssh" : 22, "checks_read_timeout" : 5, "non_simult_ports" :
"139,445,3389,Services/irc", "exclude_fragile_devices" : "1", "vt_config_id" : 4, "disable_cgi_cache" : "1",
```

```
"open_sock_max_attempts" : 5, "max_checks" : 4, "safe_checks" : "1", "schedule_timezone" : "America/Los_Angeles",
"alive_test_methods" : [ "arp", "icmp", "tcp_ack" ], "alive_test_ports" : "21-23,25,53,80,110-
111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080", "schedule_time" : { "hour" : 2, "minute" : 0, "second" : 0
}, "expand_vhosts" : "1", "disable_win_cmd_exec" : "1", "name" : "Weekly Production Scan", "asset_groups" : [ { "name"
: "name", "count" : 6, "id" : 0 }, { "name" : "name", "count" : 6, "id" : 0 } ], "optimize_test" : "1", "scan_ports" :
[ ] }'
import http.client conn = http.client.HTTPSConnection("api-") headers = { 'User-Agent': "SOME_STRING_VALUE" }
conn.request("POST", "%7Bfqdn%7D/public_api/netscan/v1/scan/definition", headers=headers) res = conn.getresponse()
data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["User-
Agent"] = 'SOME_STRING_VALUE' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST",
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition"); xhr.setRequestHeader("User-Agent",
"SOME_STRING_VALUE"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition")
.header("User-Agent", "SOME_STRING_VALUE") .asString();
import Foundation let headers = ["User-Agent": "SOME_STRING_VALUE"] let request = NSMutableURLRequest(url:
NSURL(string: "https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers let
session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data,
response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_HTTPHEADER => [ "User-Agent: SOME_STRING_VALUE" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/definition"); var request = new
RestRequest(Method.POST); request.AddHeader("User-Agent", "SOME_STRING_VALUE"); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json; charset=UTF-8

Complete scan definition including scan settings, targets, schedule, and credentials

▼ port_list_idinteger

Port list ID to use

Example:`5`
▼ scan_portsarray

Custom list of ports to scan (overrides `port_list_id` if provided)

[
]
▼ auth_port_sshinteger

SSH authentication port

Example:`22`
▼ disable_cgi_cachestring (Enum)

Disable CGI cache (`0` = enabled, `1` = disabled)

Example:`"1"`
Allowed values:"0""1"
▼ plugins_timeoutinteger

Plugin timeout in minutes

Example:`5`

▼ checks_read_timeoutinteger

Checks read timeout in minutes

Example:`5`

▼ max_hostsinteger

Maximum number of hosts to scan simultaneously

Example:`30`

▼ max_checksinteger

Maximum number of checks per host

Example:`4`

▼ scanner_plugins_timeoutinteger

Scanner plugins timeout in seconds

Example:`3600`

▼ timeout_retryinteger

Number of timeout retries

Example:`5`

▼ open_sock_max_attemptsinteger

Maximum attempts to open socket

Example:`5`

▼ non_simult_portsstring

Ports that should not be scanned simultaneously (comma-separated)

Example:`"139,445,3389,Services/irc"`

▼ strict_unauthenticatedstring (Enum)

Strict unauthenticated mode (`0` = disabled, `1` = enabled)

Example:`"0"`
Allowed values:"0""1"

▼ optimize_teststring (Enum)

Optimize test execution (`0` = disabled, `1` = enabled)

Example:`"1"`
Allowed values:"0""1"

▼ expand_vhostsstring (Enum)

Expand virtual hosts (`0` = disabled, `1` = enabled)

Example:`"1"`
Allowed values:"0""1"

▼ exclude_fragile_devicesstring (Enum)

Exclude fragile devices (`0` = disabled, `1` = enabled)

Example:`"1"`
Allowed values:"0""1"

▼ exclude_printersstring (Enum)

Exclude printers (`0` = disabled, `1` = enabled)

Example:`"1"`
Allowed values:"0""1"

▼ safe_checksstring (Enum)

Enable safe checks (`0` = disabled, `1` = enabled)

Example:`"1"`
Allowed values:"0""1"

▼ disable_win_cmd_execstring (Enum)

Disable Windows command execution (`0` = disabled, `1` = enabled)

Example:`"1"`

Allowed values:"0""1"

▼ disable_wmi_searchstring (Enum)

Disable WMI search (`0` = disabled, `1` = enabled)

Example:`"1"`

Allowed values:"0""1"

▼ alive_test_methodsarray[string]

Methods to test if hosts are alive

Example:`["arp","icmp","tcp_ack"]`

▼ alive_test_portsstring

Ports to use for alive testing (comma-separated or ranges)

Example:`"21-23,25,53,80,110-111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080"`

▼ definition_idinteger

ID of existing definition (for updates)

Example:`123`

▼ vt_config_idintegerrequired

Vulnerability test configuration template ID

Example:`4`

▼ namestringrequired

Name of the scan definition

Example:`"Weekly Production Scan"`

▼ descriptionstringrequired

Description of the scan definition

Example:`"Weekly security scan for production servers"`

▼ network_scanner_idsarray[string]required

Array of network scanner UUIDs to use for this scan

Example:`["scanner-1","scanner-2"]`

▼ networkintegerrequired

Network ID

Example:`1`

▼ credential_idsarray[integer]required

Array of credential IDs for authenticated scanning

Example:`[1]`

▼ schedule_cadencestring (Enum)required

Schedule cadence frequency

Example:`"DAILY"`

Allowed values:"DAILY""WEEKLY""MONTHLY""ONCE"

▼ schedule_daysintegerrequired

Scheduled days as bitmask (127 = all days)

Example:`127`

▼ schedule_datesarray[integer]required

Array of scheduled dates (for monthly cadence)

▼ schedule_start_dateintegerrequiredint64

Schedule start date as Unix timestamp in milliseconds

Example:`1765083183326`

▼ schedule_timeobject

Time of day specification for scan scheduling

▶ hourintegerrequired

Hour of the day (0-23)
▶ minuteintegerrequired

Minute of the hour (0-59)

▶ secondintegerrequired

Second of the minute (0-59)

▼ schedule_quiet_hoursarrayrequired

Array of quiet hours periods when scanning should not run

[
▶ startobject

Time of day specification for scan scheduling

▶ endobject

Time of day specification for scan scheduling

]
▼ schedule_timezonestringrequired

Timezone for scheduling (IANA timezone format)

Example:`"America/Los_Angeles"`
▼ override_target_exclusionsbooleanrequired

Whether to override global target exclusions

▼ target_idsarray[integer]required

Array of target group IDs

▼ targetsarray[string]required

Array of target hosts or IP ranges (CIDR notation)

Example:`["192.168.1.0/24","10.0.0.1-10.0.0.100"]`
▼ excluded_targetsarray[string]required

Array of excluded targets

Example:`[""]`
▼ enable_reportbooleanrequired

Whether to enable scan reporting

Example:`true`
▼ asset_groupsarray
[
▶ idintegerrequired
▶ namestring
▶ countinteger
]
REQUEST
```
[application/json; charset=UTF-8 content]
```
Responses

New scan definition created successfully.

Body
application/json
▼ definition_idinteger

ID of the created definition

Example:`123`
▼ messagestring

Success message

Example:`"Scan created successfully"`
RESPONSE
```
{ "definition_id": 123, "message": "Scan created successfully" }
```

Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

VT template not found or cannot create a new scan definition

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Failed definition validation during scan definition creation.

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [{ "field": "name", "message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" }] } }

2.18.2.6 | Send a command to a running scan

post /public_api/netscan/v1/scan/run/{id}/command

Send a control command to a running scan execution. Supported commands are `ABORT` (cancel the scan), `PAUSE` (pause the scan), and `RESUME` (resume a paused scan).

Path parameters
▼ id Long required

Unique identifier of the scan run

Example: `789`
Request headers
▼ User-Agent String required
Example: `userAgent_example`
CLIENT REQUEST Bash+curl
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'User-Agent: userAgent_example'
'https://api-cortex.paloaltonetworks.com/public_api/netscan/v1/scan/run/{id}/command'
-d ''
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"type\":\"ABORT\"}}"
headers = { 'User-Agent': "SOME_STRING_VALUE", 'content-type': "application/json" } conn.request("POST",
"%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command", payload, headers) res = conn.getresponse() data =
res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url)
request["User-Agent"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json' request.body = "
{\"request_data\":{\"type\":\"ABORT\"}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "type": "ABORT" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST",

```
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command"); xhr.setRequestHeader("User-Agent",
"SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response =
Unirest.post("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command") .header("User-Agent",
"SOME_STRING_VALUE") .header("content-type", "application/json") .body("{\"request_data\":{\"type\":\"ABORT\"}}")
.asString();
import Foundation let headers = [ "User-Agent": "SOME_STRING_VALUE", "content-type": "application/json" ] let
parameters = ["request_data": ["type": "ABORT"]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"type\":\"ABORT\"}}", CURLOPT_HTTPHEADER
=> [ "User-Agent: SOME_STRING_VALUE", "content-type: application/json" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command"); struct curl_slist *headers = NULL; headers
= curl_slist_append(headers, "User-Agent: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type:
application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "
{\"request_data\":{\"type\":\"ABORT\"}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/public_api/netscan/v1/scan/run/%7Bid%7D/command"); var request =
new RestRequest(Method.POST); request.AddHeader("User-Agent", "SOME_STRING_VALUE"); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":{\"type\":\"ABORT\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

▼ request_dataobject
▶ typestring (Enum)required

Command to perform on the scan run

REQUEST
```
{ "request_data": { "type": "ABORT" } }
```
Responses

Command executed successfully

Body
application/json

Response returned after a scan action (launch, pause, resume, or abort)

▼ DATAstringrequired

Action result message

Example:`"Scan launched successfully with run ID: 789"`
RESPONSE
```
{ "DATA": "Scan launched successfully with run ID: 789" }
```

Bad Request

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```


User not Authorized

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```


Run ID not found or command cannot be performed

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```


Internal Server Error

Body
application/json

Standard error response returned for all error status codes

▼ err_msgstringrequired

Human-readable error message

▼ metadataobject

Additional error context with field-level details

▶ err_extraarray

List of field-level error details

RESPONSE


```
{ "err_msg": "The request contains invalid or missing parameters", "metadata": { "err_extra": [ { "field": "name",
"message": "Field required" }, { "field": "extra_info", "message": "Extra inputs are not permitted" } ] } }
```

2.19 | Cortex Platform IAM APIs



2.19.1 | Preface

Identity and Access Management (IAM) APIs for the Cortex platform. These APIs enable programmatic management of roles, user groups, users, API keys, and scope-based access control (SBAC) configurations. With these endpoints, you can create, read, update, and delete IAM entities, manage permissions and access controls, and configure security scopes for users, groups, and API keys. These APIs are intended to be accessed via API keys. Therefore, the key must have the RBAC permission 'access_management_view' for list & read operations and permission 'access_management_action' for create, edit, & delete operations.

Version: Cortex Cloud

2.19.1.1 | Servers

https://api-{fqdn}

2.19.1.2 | Authentication methods

▼ Authorization
Api Key "x-api-key"

Authorized requests to the API should use: **x-api-key** inside **a header** with the access token.

▼ x-xdr-auth-id
Api Key "x-api-key-id"

Authorized requests to the API should use: **x-api-key-id** inside **a header** with the access token.

2.19.2 | Roles

Operations for managing roles including creation, editing, deletion, and listing roles.

2.19.2.1 | List all roles

get /platform/iam/v1/role

This endpoint retrieves a list of roles and returns their attributes. This API does not list permissions for said roles. To receive that information, please leverage the existing Get Roles API (https://docs-cortex.paloaltonetworks.com/r/Cortex-Cloud-Platform-APIs/Get-Roles). Note: 'role_id' refers to the immutable role ID, while 'pretty_name' refers to the display name.

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/role'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET", "%7Bfqdn%7D/platform/iam/v1/role")
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/role") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/iam/v1/role"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/role") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/role")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "GET" let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/role",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/role"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/role"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved roles

Body
application/json
▼ dataarrayrequired
[
▶ role_idstringrequired

The unique identifier for the role

▶ pretty_namestringrequired

The display name for the role

▶ descriptionstringrequired

A description of the role's purpose and permissions

▶ is_custombooleanrequired

Indicates if the role is a custom role (true) or a predefined system role (false)

▶ created_bystringrequired

The user or system that created the role

▶ created_tsintegerrequired

The timestamp when the role was created

▶ updated_tsintegerrequired

The timestamp when the role was last updated

]
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE

```
{ "data": [ { "role_id": "test_role_01", "pretty_name": "Test Role Pretty Name 01", "description": "Complete description", "is_custom": true, "created_by": "User 01", "created_ts": 1661171650679, "updated_ts": 1661171650679 }, { "role_id": "test_role_02", "pretty_name": "Test Role Pretty Name 02", "description": "Complete description", "is_custom": true, "created_by": "User 02", "created_ts": 1661171650679, "updated_ts": 1661171650679 } ], "metadata": { "total_count": 2 } }
```


Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.2.2 | Create a new role

post /platform/iam/v1/role

To identify all potential permissions that can be entered into the 'component_permissions' field, please utilize the 'GET /platform/iam/v1/role/permission-config' endpoint and utilize the 'view_name' and 'action_name' properties. Note: if you input an 'action' permission, then the relevant 'view' permission will be added

for you. There will also be checks done on sub-permissions, ensuring that the main 'action' permissions are present as well. The available datasets can also be found by utilizing the 'GET /platform/iam/v1/role/permission-config' endpoint. Any dataset related permissions are not permissible in the 'component_permissions' field (an error will be thrown). The 'permissions' field in the entry for 'dataset_permissions' refers to dataset names for said dataset category.It is important to note that the 'access_all' field will only grant the role access to all datasets in said category that the API key has access to.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/role'
-d '{ "request_data" : { "component_permissions" : [ "rules_action", "wf_verdict_change" ], "dataset_permissions" : [
{ "category" : "Lookup", "access_all" : true, "permissions" : [ ] } ], "pretty_name" : "CustomRoleName", "description"
: "A custom role with specific permissions" } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"component_permissions\":
[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}" headers = {
'content-type': "application/json" } conn.request("POST", "%7Bfqdn%7D/platform/iam/v1/role", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/role") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"component_permissions\":[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}" response =
http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "component_permissions": [ "rules_action", "wf_verdict_change" ],
"dataset_permissions": [ { "category": "Lookup", "access_all": true, "permissions": [] } ], "pretty_name":
"CustomRoleName", "description": "A custom role with specific permissions" } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("POST", "https://api-/%7Bfqdn%7D/platform/iam/v1/role");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/platform/iam/v1/role") .header("content-type",
"application/json") .body("{\"request_data\":{\"component_permissions\":
[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [
"component_permissions": ["rules_action", "wf_verdict_change"], "dataset_permissions": [ [ "category": "Lookup",
"access_all": true, "permissions": [] ] ], "pretty_name": "CustomRoleName", "description": "A custom role with
specific permissions" ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
[]) let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/role")! as URL,
cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields =
headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with:
request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else
{ let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/role",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"component_permissions\":[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}",
CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/role"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"component_permissions\":
[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}"); CURLcode ret
= curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/role"); var request = new
RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"component_permissions\":
[\"rules_action\",\"wf_verdict_change\"],\"dataset_permissions\":
[{\"category\":\"Lookup\",\"access_all\":true,\"permissions\":
```

```
[]}],\"pretty_name\":\"CustomRoleName\",\"description\":\"A custom role with specific permissions\"}}",
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request object for creating a new role

▼ request_dataobject

The data required to create a new role

▶ component_permissionsarray[string]required

List of component permissions for the role. Possible values can be found by using the permission configs API and referring to the `rbac_permissions` field.

▶ dataset_permissionsarray

Optional list of dataset permissions. This must be a list of JSONs. The layout for this JSON can be found under the 'DatasetPermission' schema . Note: possible dataset values can be found by using the permission configs API and referring to the `datasetGroups` field.

▶ pretty_namestringrequired

Name of the role

▶ descriptionstring

Optional description of the role

REQUEST

```
{ "request_data": { "component_permissions": [ "rules_action", "wf_verdict_change" ], "dataset_permissions": [ {
"category": "Lookup", "access_all": true, "permissions": [] } ], "pretty_name": "CustomRoleName", "description": "A
custom role with specific permissions" } }
```

Responses

Role created successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the role was created

RESPONSE

```
{ "data": { "message": "role_id test_role01 created successfully." } }
```

Bad request for role create call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject

RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "The role
name CustomRoleName is already utilized by another role.", "err_code": 400 } } }
```

Unauthorized access

Body
application/json

RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger

▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.2.3 | Delete an existing role

delete /platform/iam/v1/role/{role_id}

Delete an existing Role

Path parameters
▼ role_id String required

Full role id of the custom role

Example: `roleId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'DELETE'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/role/{role_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("DELETE",
"%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) response =
http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("DELETE",
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "DELETE" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "DELETE", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL
Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/role/%7Brole_id%7D"); var request = new
RestRequest(Method.DELETE); IRestResponse response = client.Execute(request);
```

Responses

Role deleted successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the role was deleted

RESPONSE

```
{ "data": { "message": "role_id test_role01 deleted successfully." } }
```


Bad request for role delete call

Body
application/json

▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Role name cannot be empty / Role name provided is not valid / Non-custom and account-level roles cannot be deleted / Role name provided is assigned to a user or user group and therefore cannot be deleted.", "err_code": 400 } } }

Unauthorized access

Body
application/json
RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }

Internal server error. A unified status for API communication type errors.

2.19.2.4 | List all permission configs

get /platform/iam/v1/role/permission-config

Returns the current list of permissions available for the specified tenant. Each permission includes:

- name: Display name of the permission as shown in the UI.
- view_name: Permission key for the "View" option, used in role creation APIs.
- action_name: Permission key for the "View/Edit" option, used in role creation APIs.

Intended use: Use this endpoint to identify the correct permission keys corresponding to the display names visible in the UI.
Note - The response mirrors how permissions are organized and displayed in the UI (by category and subcategory).

CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/role/permission-config'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/iam/v1/role/permission-config") res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-
config") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE
request = Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-
config"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-config")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-config")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
```

```
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-config", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-config"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/role/permission-config"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved permission configs

Body
application/json
▼ dataobjectrequired
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE


```
{ "data": { "rbac_permissions": [ { "category_name": "Dashboards & Reports", "sub_categories": [ {
"sub_category_name": null, "permissions": [ { "name": "Dashboards", "view_name": "dashboard_view", "action_name":
"dashboard_action", "sub_permissions": [] }, { "name": "Reports", "view_name": "reports_view", "action_name":
"reports_action", "sub_permissions": [] } ] } ] }, { "category_name": "Investigation & Response", "sub_categories": [
{ "sub_category_name": "Search", "permissions": [ { "name": "Query Center", "view_name": "investigation_query_view",
"action_name": "investigation_query_action", "sub_permissions": [] } ] }, { "sub_category_name": "Response",
"permissions": [ { "name": "Action Center", "view_name": "actions_center", "action_name": "actions_center_action",
"sub_permissions": [ { "action_name": "isolate", "name": "Isolate" }, { "action_name": "quarantine", "name":
"Quarantine" } ] } ] } ] } ], "datasetGroups": [ { "datasets": [ "alerts", "cases", "endpoints", "incidents" ],
"dataset_category": "System" }, { "datasets": [], "dataset_category": "Lookup" } ] } }
```


Unauthorized access

Body
application/json
RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.3 | User Groups

Operations for managing user groups including creation, editing, deletion, and listing user groups.

2.19.3.1 | List all user groups

get /platform/iam/v1/user-group

This endpoint retrieves a list of user groups and returns their attributes. For possible 'group_type' values, please refer to the enum documentation for 'GroupType'. Also, 'nested_groups' refers to the list of direct child groups of the given user group. Similarly, 'idp_groups' refers to the identifiers of associated identity provider groups to the given user group.

CLIENT REQUEST Bash+curl
```
curl -X 'GET'
```

```
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user-group'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET", "%7Bfqdn%7D/platform/iam/v1/user-
group") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group");
xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/user-
group")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session =
URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response,
error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse
print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/user-
group", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/user-group"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved user groups

Body
application/json
▼ dataarrayrequired
[
]
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE

```
{ "data": [ { "group_id": "test_group1", "group_name": "Group2", "description": null, "role_id": "role_name01",
"pretty_role_name": "Role Name 01", "created_by": "user1@test.com", "created_ts": 1661170832341, "updated_ts":
1661171650679, "users": [ "user1@test.com", "user2@test.com", "user3@test.com", "user4@test.com", "user5@test.com" ],
"group_type": "custom", "nested_groups": [ { "group_id": "abc_123", "group_name": "child-group-name1" } ],
"idp_groups": [ "test_idp_group_name" ] } ], "metadata": { "total_count": 1 } }
```

Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key", "metadata": {} } }
```

Internal server error. A unified status for API communication type errors.

2.19.3.2 | Create a new user group

post /platform/iam/v1/user-group

This endpoint creates a new user group with the specified configuration. You can assign a role, add users, configure nested groups, and link identity provider groups. All fields except 'group_name' are optional.

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user-group'
-d '{ "request_data" : { "group_name" : "test_group_name", "role_id" : "role_name_123", "description" : "Test
Description", "users" : [ "user1@test.com" ], "nested_group_ids" : [ "7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123" ],
"idp_groups" : [ "test idp group" ] } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Description\",\"users\":
[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp
group\"]}}" headers = { 'content-type': "application/json" } conn.request("POST", "%7Bfqdn%7D/platform/iam/v1/user-
group", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group")
http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Post.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Description\",\"users\":
[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp
group\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "group_name": "test_group_name", "role_id": "role_name_123",
"description": "Test Description", "users": [ "user1@test.com" ], "nested_group_ids": [ "7f3o5b2c-4d5e-4f6a-8b9c-
1d3o5f4a5b6c_123" ], "idp_groups": [ "test idp group" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group") .header("content-
type", "application/json") .body("{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Description\",\"users\":
[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp
group\"]}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "group_name":
"test_group_name", "role_id": "role_name_123", "description": "Test Description", "users": ["user1@test.com"],
"nested_group_ids": ["7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123"], "idp_groups": ["test idp group"] ]] as [String :
Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request =
NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/user-
group", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "POST", CURLOPT_POSTFIELDS => "
{\"request_data\":{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test
Description\",\"users\":[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-
1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}", CURLOPT_HTTPHEADER => [ "content-type: application/json"
], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/user-group"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Description\",\"users\":
[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp
group\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group"); var request = new
RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Description\",\"users\":
[\"user1@test.com\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp
group\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request object for creating a new user group

▼ request_dataobject

The data required to create a new user group

▶ group_namestringrequired

The unique name for the user group

▶ role_idstring

The unique identifier of the role to assign to this group

▶ descriptionstring

A brief description of the user group's purpose

▶ usersarray[string]

A list of user email addresses to add to the group

▶ nested_group_idsarray[string]

A list of unique identifiers for groups to be nested within this group

▶ idp_groupsarray[string]

A list of identity provider (IdP) group names to associate with this group

REQUEST

```
{ "request_data": { "group_name": "test_group_name", "role_id": "role_name_123", "description": "Test Description", "users": [ "user1@test.com" ], "nested_group_ids": [ "7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123" ], "idp_groups": [ "test idp group" ] } }
```

Responses

User Group created successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the user group was created

RESPONSE

```
{ "data": { "message": "user group with group id 123-456 created successfully" } }
```

Bad request for user group create call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject

RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "This user group name is already being used in the tenant for existing_group_name.", "err_code": 400 } } }
```

Unauthorized access

Body
application/json

RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json

▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }

Internal server error. A unified status for API communication type errors.

2.19.3.3 | Edit an existing user group

patch /platform/iam/v1/user-group/{group_id}

This endpoint allows modification of an existing user group by providing the group_id in the path and the update details in the request body. Only specified fields will be updated. Please note that to remove attributes, you must provide either an empty string or empty list as the value of the respective field in the request body.

Path parameters
▼ group_id String required

Full user group id

Example: 7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123
CLIENT REQUEST Bash+curl

```
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user-group/{group_id}'
-d '{ "request_data" : { "group_name" : "test_group_name", "role_id" : "role_name_123", "description" : "Test Updated Description", "users" : [ "test user" ], "nested_group_ids" : [ "7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123" ], "idp_groups" : [ "test idp group" ] } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\": {\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}" headers = { 'content-type': "application/json" } conn.request("PATCH", "%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Patch.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\": {\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "group_name": "test_group_name", "role_id": "role_name_123", "description": "Test Updated Description", "users": [ "test user" ], "nested_group_ids": [ "7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123" ], "idp_groups": [ "test idp group" ] } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("PATCH", "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123") .header("content-type", "application/json") .body("{\"request_data\": {\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "group_name": "test_group_name", "role_id": "role_name_123", "description": "Test Updated Description", "users": ["test user"], "nested_group_ids": ["7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123"], "idp_groups": ["test idp group"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PATCH" request.allHTTPHeaderFields = headers request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
```

```
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/user-
group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "PATCH", CURLOPT_POSTFIELDS => "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated
Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-
1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}", CURLOPT_HTTPHEADER => [ "content-type: application/json"
], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123"); struct
curl_slist *headers = NULL; headers = curl_slist_append(headers, "content-type: application/json");
curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated
Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-
1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-
1d2e3f4a5b6c_123"); var request = new RestRequest(Method.PATCH); request.AddHeader("content-type",
"application/json"); request.AddParameter("application/json", "{\"request_data\":
{\"group_name\":\"test_group_name\",\"role_id\":\"role_name_123\",\"description\":\"Test Updated
Description\",\"users\":[\"test user\"],\"nested_group_ids\":[\"7f3o5b2c-4d5e-4f6a-8b9c-
1d3o5f4a5b6c_123\"],\"idp_groups\":[\"test idp group\"]}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters
required
application/json

Request object for editing an existing user group

▼ request_dataobjectrequired

The data fields to update for the user group

▶ group_namestring

The new name for the user group

▶ role_idstring

The unique identifier of the new role to assign to this group

▶ descriptionstring

The updated description for the user group

▶ usersarray[string]

The updated list of user email addresses for the group

▶ nested_group_idsarray[string]

The updated list of nested group identifiers

▶ idp_groupsarray[string]

The updated list of associated identity provider (IdP) group names

REQUEST

```
{ "request_data": { "group_name": "test_group_name", "role_id": "role_name_123", "description": "Test Updated
Description", "users": [ "test user" ], "nested_group_ids": [ "7f3o5b2c-4d5e-4f6a-8b9c-1d3o5f4a5b6c_123" ],
"idp_groups": [ "test idp group" ] } }
```

Responses

User Group edited successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the user group was edited

RESPONSE
{ "data": { "message": "user group with group id 123-456 updated successfully" } }

Bad request for user group edit call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "This user group name is already being used in the tenant for existing_group_name", "err_code": 400 } } }

Unauthorized access

Body
application/json
RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }

Internal server error. A unified status for API communication type errors.

2.19.3.4 | Delete an existing user group

delete /platform/iam/v1/user-group/{group_id}

Delete an existing user group. Note: upon deletion of a user group, its nested groups are not deleted; the relationships are simply removed.

Path parameters
▼ group_id String required

Full user group id

Example: 7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user-group/{group_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("DELETE", "%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Delete.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("DELETE", "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123"); xhr.send(data);
HttpResponse<String> response = Unirest.delete("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
```

```
request.httpMethod = "DELETE" let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "DELETE", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "DELETE"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user-group/7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123"); var request = new RestRequest(Method.DELETE); IRestResponse response = client.Execute(request);
```

Responses

User Group deleted successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the user group was deleted

RESPONSE

```
{ "data": { "message": "user group with group id 7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123 deleted successfully" } }
```

Bad request for user group delete call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Could not find group for ['7f8a9b2c-4d5e-4f6a-8b9c-1d2e3f4a5b6c_123'] in tenant: tenant_name", "err_code": 400 } } }
```

Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```

Internal server error. A unified status for API communication type errors.

2.19.4 | Scopes

Operations for managing Scope-Based Access Control (SBAC) configurations for users, groups, and API keys.

2.19.4.1 | Retrieve an existing scope

get /platform/iam/v1/scope/{entity_type}/{entity_id}

This API endpoint allows retrieving the scope details for a specific entity type and entity ID. For possible 'mode' and 'entity_type' values, please refer to the enum documentation for 'ModeType' and 'EntityType'.

Path parameters

▼ entity_type EntityType required

Full name of the entity's type

▼ entity_id String required

Full id of the entity

Example: `entityId_example`

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/scope/{entity_type}/{entity_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D") res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D") http = Net::HTTP.new(url.host,
url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response
= http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET",
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); xhr.send(data);
HttpResponse<String> response =
Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let
dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if
(error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); var
request = new RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved scope

Body

application/json

▼ dataobjectrequired

▼ metadataobject

Metadata for the response

Free-Form object

RESPONSE


```
{ "data": { "assets": { "mode": "scope", "asset_groups": [ { "asset_group_id": 1, "asset_group_name": "Asset Test
Group 1" }, { "asset_group_id": 2, "asset_group_name": "Asset Test Group 2" }, { "asset_group_id": 3,
"asset_group_name": "Asset Test Group 3" } ] }, "datasets_rows": { "default_filter_mode": "no_scope", "filters": [ {
"dataset": "dataset_1", "filter": "_collector_name = filter_collector_1" }, { "dataset": "dataset_2", "filter":
"_collector_name = filter_collector_2" } ] }, "endpoints": { "endpoint_groups": { "mode": "scope", "tags": [ {
"tag_id": "EG:1", "tag_name": "test-eg-1" } ] }, "endpoint_tags": { "mode": "any", "tags": [ { "tag_id": null,
"tag_name": "Any" } ] } }, "cases_issues": { "mode": "scope", "tags": [ { "tag_id": "DOM:4", "tag_name": "Health" }, {
"tag_id": "DOM:3", "tag_name": "IT" } ] } } }
```


Unauthorized access

Body

application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.4.2 | Edit an existing scope

put /platform/iam/v1/scope/{entity_type}/{entity_id}

This API endpoint allows editing the scope details for a specific entity type and entity ID. For possible 'mode' and 'entity_type' values, please refer to the enum documentation for 'ModeType' and 'EntityType'. Please note that the 'datasets_rows' field can only be passed in to the request body if the dataset scope config is enabled.

Path parameters
▼ entity_type EntityType required

Full name of the entity's type

▼ entity_id String required

Full id of the entity

Example: `entityId_example`
CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/scope/{entity_type}/{entity_id}'
-d '{ "request_data" : { "endpoints" : { "endpoint_groups" : { "names" : [ "test-eg-1" ], "mode" : "scope" }, "endpoint_tags" : { "names" : [ ], "mode" : "any" } }, "cases_issues" : { "mode" : "scope", "include_cases_issues_empty_entities" : true, "names" : [ "Health", "IT" ] }, "assets" : { "mode" : "scope", "asset_group_ids" : [ 1, 2, 3 ] }, "datasets_rows" : { "filters" : [ { "dataset" : "test-dataset-1", "filter" : "_collector_name = bu2_collector" }, { "dataset" : "test-dataset-2", "filter" : "_collector_name = bu2_collector" } ], "default_filter_mode" : "no_scope" } } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"endpoints\":{\"endpoint_groups\":{\"names\":[\"test-eg-1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name = bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}" headers = { 'content-type': "application/json" } conn.request("PUT", "%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D", payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["content-type"] = 'application/json' request.body = "{\"request_data\":{\"endpoints\":{\"endpoint_groups\":{\"names\":[\"test-eg-1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name = bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}" response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "endpoints": { "endpoint_groups": { "names": [ "test-eg-1" ], "mode": "scope" }, "endpoint_tags": { "names": [], "mode": "any" } }, "cases_issues": { "mode": "scope", "include_cases_issues_empty_entities": true, "names": [ "Health", "IT" ] }, "assets": { "mode": "scope",
```

```
"asset_group_ids": [ 1, 2, 3 ] }, "datasets_rows": { "filters": [ { "dataset": "test-dataset-1", "filter":
"_collector_name = bu2_collector" }, { "dataset": "test-dataset-2", "filter": "_collector_name = bu2_collector" } ],
"default_filter_mode": "no_scope" } } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT",
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); xhr.setRequestHeader("content-
type", "application/json"); xhr.send(data);
HttpResponse<String> response =
Unirest.put("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D") .header("content-type",
"application/json") .body("{\"request_data\":{\"endpoints\":{\"endpoint_groups\":{\"names\":[\"test-eg-
1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":
{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":
{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-
1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name =
bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "endpoints":
[ "endpoint_groups": [ "names": ["test-eg-1"], "mode": "scope" ], "endpoint_tags": [ "names": [], "mode": "any" ] ],
"cases_issues": [ "mode": "scope", "include_cases_issues_empty_entities": true, "names": ["Health", "IT"] ], "assets":
[ "mode": "scope", "asset_group_ids": [1, 2, 3] ], "datasets_rows": [ "filters": [ [ "dataset": "test-dataset-1",
"filter": "_collector_name = bu2_collector" ], [ "dataset": "test-dataset-2", "filter": "_collector_name =
bu2_collector" ] ], "default_filter_mode": "no_scope" ] ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D", CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PUT", CURLOPT_POSTFIELDS => "{\"request_data\":{\"endpoints\":{\"endpoint_groups\":
{\"names\":[\"test-eg-1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":
{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":
{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-
1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name =
bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}", CURLOPT_HTTPHEADER => [ "content-type: application/json"
], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" .
$err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"endpoints\":{\"endpoint_groups\":{\"names\":
[\"test-eg-1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":
{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":
{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-
1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name =
bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/scope/%7Bentity_type%7D/%7Bentity_id%7D"); var
request = new RestRequest(Method.PUT); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"endpoints\":{\"endpoint_groups\":{\"names\":[\"test-eg-
1\"],\"mode\":\"scope\"},\"endpoint_tags\":{\"names\":[],\"mode\":\"any\"}},\"cases_issues\":
{\"mode\":\"scope\",\"include_cases_issues_empty_entities\":true,\"names\":[\"Health\",\"IT\"]},\"assets\":
{\"mode\":\"scope\",\"asset_group_ids\":[1,2,3]},\"datasets_rows\":{\"filters\":[{\"dataset\":\"test-dataset-
1\",\"filter\":\"_collector_name = bu2_collector\"},{\"dataset\":\"test-dataset-2\",\"filter\":\"_collector_name =
bu2_collector\"}],\"default_filter_mode\":\"no_scope\"}}}", ParameterType.RequestBody); IRestResponse response =
client.Execute(request);
```

Body parameters

required

application/json

▼ request_dataobjectrequired

Scope configuration data to update

▶ assetsobject

Asset scope configuration for request payloads

▶ datasets_rowsobject

Dataset rows scope configuration for filtering data access

▶ endpointsobject

Endpoint scope configuration for request payloads

▶ cases_issuesobject

Cases and issues scope configuration for requests

REQUEST

```
{ "request_data": { "endpoints": { "endpoint_groups": { "names": [ "test-eg-1" ], "mode": "scope" }, "endpoint_tags": { "names": [], "mode": "any" } }, "cases_issues": { "mode": "scope", "include_cases_issues_empty_entities": true, "names": [ "Health", "IT" ] }, "assets": { "mode": "scope", "asset_group_ids": [ 1, 2, 3 ] }, "datasets_rows": { "filters": [ { "dataset": "test-dataset-1", "filter": "_collector_name = bu2_collector" }, { "dataset": "test-dataset-2", "filter": "_collector_name = bu2_collector" } ], "default_filter_mode": "no_scope" } } }
```

Responses

Scope edited successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the scope was edited

RESPONSE

```
{ "data": { "message": "Scope updated for user user@email.com successfully" } }
```


Bad request for scope edit call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "The scope name test_scope_01 does not exist.", "err_code": 400 } } }
```


Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.5 | User

Operations for managing users including listing users and editing user configurations.

2.19.5.1 | List all users

get /platform/iam/v1/user

This endpoint retrieves a list of all users and their respective properties. Note: the 'role_name' field refers to the 'pretty_name' attribute from the Roles APIs and the direct role assigned to the user, not roles inherited through groups.

CLIENT REQUEST Bash+curl

```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET", "%7Bfqdn%7D/platform/iam/v1/user")
res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user") http =
Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request =
Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/iam/v1/user"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/user") .asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/user")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0)
request.httpMethod = "GET" let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/user",
CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err
= curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/user"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved users

Body
application/json
▼ dataarrayrequired
[
]
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE

```
{ "data": [ { "user_email": "user1@test.com", "user_first_name": "<first name>", "user_last_name": "<last name>",
"phone_number": "408-753-4000", "role_name": "Investigator", "status": "Active", "last_logged_in": 1640024700241,
"is_hidden": true, "user_type": "CSP", "groups": [ { "group_id": 123, "group_name": "usergroup1" } ] }, {
"user_email": "user2@test.com", "user_first_name": "<first name>", "user_last_name": "<last name>", "phone_number":
"408-753-4000", "status": "Active", "role_name": "Investigator", "last_logged_in": 1640024700241, "is_hidden": true,
"user_type": "CSP", "groups": [ { "group_id": 123, "group_name": "usergroup2" } ] } ], "metadata": { "total_count": 2
} }
```

Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring

▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }

Internal server error. A unified status for API communication type errors.

2.19.5.2 | Get user

get /platform/iam/v1/user/{user_email}

This endpoint retrieves a user and its respective properties. Note: the 'role_name' field refers to the 'pretty_name' attribute from the Roles APIs, not the unique role identifier.

Path parameters
▼ user_email String required

Full email of the user

Example: `userEmail_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user/{user_email}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET",
"%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response =
http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("GET",
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "GET" let session = URLSession.shared let dataTask =
session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error !=
nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } })
dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "GET", ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```
Responses

Successfully retrieved user

Body
application/json
▼ dataobjectrequired
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE
{ "data": { "user_email": "user@test.com", "user_first_name": "<first name>", "user_last_name": "<last name>", "phone_number": "408-753-4000", "status": "Active", "role_name": "Account Admin", "last_logged_in": 1640024700241,

"is_hidden": true, "user_type": "CSP", "groups": [{ "group_id": "unique_group_id", "group_name": "usergroup" }] } }

Unauthorized access

Body
application/json
RESPONSE
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }

Internal server error. A unified status for API communication type errors.

2.19.5.3 | Edit an existing user

patch /platform/iam/v1/user/{user_email}

This endpoint allows updating various user details. Please note that you must pass an empty string for the 'role_id' field if you are attempting to remove a role from a user. For the 'user_groups' field, please pass an empty list to remove user group associations for the provided user.

Path parameters
▼ user_email String required

Full email of the user

Example: `userEmail_example`
CLIENT REQUEST Bash+curl
```
curl -X 'PATCH'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/user/{user_email}'
-d '{ "request_data" : { "phone_number" : "408-753-4000", "status" : "Active", "role_id" : "role_name_123",
"is_hidden" : true, "user_groups" : [ "user_groups_123" ] } }'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"phone_number\":\"408-
753-4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":
[\"user_groups_123\"]}}" headers = { 'content-type': "application/json" } conn.request("PATCH",
"%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D", payload, headers) res = conn.getresponse() data = res.read()
print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url =
URI("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D") http = Net::HTTP.new(url.host, url.port)
http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Patch.new(url) request["content-
type"] = 'application/json' request.body = "{\"request_data\":{\"phone_number\":\"408-753-
4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":[\"user_groups_123\"]}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "phone_number": "408-753-4000", "status": "Active", "role_id":
"role_name_123", "is_hidden": true, "user_groups": [ "user_groups_123" ] } }); const xhr = new XMLHttpRequest();
xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE)
{ console.log(this.responseText); } }); xhr.open("PATCH",
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); xhr.setRequestHeader("content-type",
"application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.patch("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D")
.header("content-type", "application/json") .body("{\"request_data\":{\"phone_number\":\"408-753-
4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":
[\"user_groups_123\"]}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [
"phone_number": "408-753-4000", "status": "Active", "role_id": "role_name_123", "is_hidden": true, "user_groups":
["user_groups_123"] ]] as [String : Any] let postData = JSONSerialization.data(withJSONObject: parameters, options:
```

```
[]) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "PATCH" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL =>
"https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING =>
"", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => "PATCH", CURLOPT_POSTFIELDS => "{\"request_data\":{\"phone_number\":\"408-753-
4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":
[\"user_groups_123\"]}}", CURLOPT_HTTPHEADER => [ "content-type: application/json" ], ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PATCH"); curl_easy_setopt(hnd,
CURLOPT_URL, "https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); struct curl_slist *headers = NULL;
headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER,
headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"phone_number\":\"408-753-
4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":
[\"user_groups_123\"]}}"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/user/%7Buser_email%7D"); var request = new
RestRequest(Method.PATCH); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"phone_number\":\"408-753-
4000\",\"status\":\"Active\",\"role_id\":\"role_name_123\",\"is_hidden\":true,\"user_groups\":
[\"user_groups_123\"]}}", ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters
required
application/json

Request object for editing an existing user

▼ request_dataobjectrequired

The data fields to update for the user

▶ user_first_namestring

The user's first name

▶ user_last_namestring

The user's last name

▶ role_idstring

The unique identifier of the role to assign to the user. Use an empty string to remove the role.

▶ phone_numberstring

The user's contact phone number

▶ statusstring

The user's account status (e.g., 'Active', 'Disabled')

▶ is_hiddenboolean

Whether the user should be hidden from certain UI views

▶ user_groupsarray[string]

A list of unique identifiers for the groups the user belongs to. Use an empty list to remove all group associations.

REQUEST

```
{ "request_data": { "phone_number": "408-753-4000", "status": "Active", "role_id": "role_name_123", "is_hidden": true,
"user_groups": [ "user_groups_123" ] } }
```

Responses

User edited successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the user was edited
RESPONSE
```
{ "data": { "message": "User updated successfully" } }
```

Bad request for user edit call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE
```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "No update performed. All fields are null or empty.", "err_code": 400 } } }
```

Unauthorized access

Body
application/json
RESPONSE
```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```

Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE
```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```

Internal server error. A unified status for API communication type errors.

2.19.6 | API Keys

Operations for managing API keys including retrieving and editing API key configurations.

2.19.6.1 | Get API Key

get /platform/iam/v1/api-key/{api_key_id}

This endpoint retrieves an API key and its respective properties. Note: the 'roles' field refers to the 'pretty_name' attributes from the Roles APIs, not the unique role identifiers. For possible 'security_level' values, please refer to the enum documentation for 'SecurityLevel'.

Path parameters
▼ api_key_id Integer required

Full API key ID

Example: 56
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/api-key/{api_key_id}'
import http.client conn = http.client.HTTPSConnection("api-") conn.request("GET", "%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D") res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("GET", "https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D"); xhr.send(data);
```

```
HttpResponse<String> response = Unirest.get("https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D")
.asString();
import Foundation let request = NSMutableURLRequest(url: NSURL(string: "https://api-/%7Bfqdn%7D/platform/iam/v1/api-
key/%7Bapi_key_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod =
"GET" let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler:
{ (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/api-
key/%7Bapi_key_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", ]); $response =
curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo
$response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D"); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D"); var request = new
RestRequest(Method.GET); IRestResponse response = client.Execute(request);
```

Responses

Successfully retrieved API key

Body
application/json
▼ dataobjectrequired
▼ metadataobject

Metadata for the response

Free-Form object
RESPONSE


```
{ "data": { "id": 123, "creation_time": 1640024700241, "created_by": "test user", "user_name": "user_name", "roles": [
"role 01" ], "security_level": "standard", "comment": "useful comment", "expiration": 1640024700241 } }
```


Bad request for api key get call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE


```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Api Key
fetch failed: api_key_id does not exist, id=1.", "err_code": 400 } } }
```


Unauthorized access

Body
application/json
RESPONSE


```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE


```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient
permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.19.6.2 | Edit an API key

put /platform/iam/v1/api-key/{api_key_id}

This endpoint allows for the editing of an existing API key. For possible 'security_level' values, please refer to the enum documentation for 'SecurityLevel'.

Path parameters
▼ api_key_id Integer required

Full API key ID

Example: 56
CLIENT REQUEST Bash+curl
```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-cortex.paloaltonetworks.com/platform/iam/v1/api-key/{api_key_id}'
-d '{ "request_data" : { "roles" : [ "role_name_123" ], "security_level" : "standard", "comment" : "useful comment" }
}'
import http.client conn = http.client.HTTPSConnection("api-") payload = "{\"request_data\":{\"roles\":
[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}" headers = { 'content-type':
"application/json" } conn.request("PUT", "%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D", payload, headers) res
= conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-/%7Bfqdn%7D/platform/iam/v1/api-
key/%7Bapi_key_id%7D") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Put.new(url) request["content-type"] = 'application/json' request.body
= "{\"request_data\":{\"roles\":[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}"
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "roles": [ "role_name_123" ], "security_level": "standard", "comment":
"useful comment" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials = true;
xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("PUT", "https://api-/%7Bfqdn%7D/platform/iam/v1/api-
key/%7Bapi_key_id%7D"); xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.put("https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D")
.header("content-type", "application/json") .body("{\"request_data\":{\"roles\":
[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}") .asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": [ "roles":
["role_name_123"], "security_level": "standard", "comment": "useful comment" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "PUT" request.allHTTPHeaderFields = headers request.httpBody = postData as
Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: {
(data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as?
HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-/%7Bfqdn%7D/platform/iam/v1/api-
key/%7Bapi_key_id%7D", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "PUT",
CURLOPT_POSTFIELDS => "{\"request_data\":{\"roles\":
[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}", CURLOPT_HTTPHEADER => [
"content-type: application/json" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if
($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "PUT"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"roles\":
[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}"); CURLcode ret =
curl_easy_perform(hnd);
var client = new RestClient("https://api-/%7Bfqdn%7D/platform/iam/v1/api-key/%7Bapi_key_id%7D"); var request = new
RestRequest(Method.PUT); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"roles\":
[\"role_name_123\"],\"security_level\":\"standard\",\"comment\":\"useful comment\"}}", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
```
Body parameters
required
application/json

Request object for editing an existing API key

▼ request_dataobject

The data fields to update for the API key

▶ rolesarray[string]required

A list of unique role identifiers to assign to the API key

▶ security_levelstring (Enum)required

The security level for the API key (e.g., 'standard', 'advanced')

▶ commentstring

An optional comment or description for the API key

REQUEST

```
{ "request_data": { "roles": [ "role_name_123" ], "security_level": "standard", "comment": "useful comment" } }
```

Responses

API key edited successfully

Body
application/json
▼ dataobject
▶ messagestringrequired

Success message indicating the API key was edited

RESPONSE

```
{ "data": { "message": "API key updated successfully" } }
```


Bad request for api key edit call

Body
application/json
▼ dataobject
▶ err_msgstringrequired

Error message describing the issue

▶ metadataobject
RESPONSE

```
{ "data": { "err_msg": "The request contains invalid or missing parameters.", "metadata": { "err_extra": "Invalid api_key_id", "err_code": 400 } } }
```


Unauthorized access

Body
application/json
RESPONSE

```
{ "reply": { "err_code": 401, "err_msg": "Public API request unauthorized", "err_extra": null } }
```


Unauthorized access due to lack of sufficient permissions

Body
application/json
▼ replyobject
▶ err_msgstringrequired
▶ err_extrastring
▶ err_codeinteger
▶ metadataobjectrequired
RESPONSE

```
{ "reply": { "err_code": 403, "err_msg": "Forbidden. Access was denied to this resource.", "err_extra": "Insufficient permissions for api key", "metadata": {} } }
```


Internal server error. A unified status for API communication type errors.

2.20 | Vulnerability Intelligence public APIs

2.20.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Vulnerability Intelligence is a real-time feed that contains vulnerability data and threat intelligence from a variety of certified upstream sources. This feed continuously pulls data from known vulnerability databases, official vendor feeds and commercial providers to provide the most accurate vulnerability detection results.

In addition to the information collected from official feeds, Vulnerability Intelligence is enriched with data curated by a dedicated research team. Our security researchers monitor cloud and open-source projects to identify security issues through automated and manual means. As a result, we can detect new vulnerabilities that were only recently disclosed, and even vulnerabilities that were quietly patched.

Use these public APIs to obtain details on vulnerabilities and affected software.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management
Version: Cortex Cloud

2.20.1.1 | Servers

https://api-yourfqdn

2.20.1.2 | Authentication methods

▼ Authorization
Api Key "x-api-key"

Authorized requests to the API should use: **x-api-key** inside **a header** with the access token.

▼ x-xdr-auth-id
Api Key "x-api-key-id"

Authorized requests to the API should use: **x-api-key-id** inside **a header** with the access token.

2.20.2 | Vulnerabilities

APIs for managing vulnerabilities

2.20.2.1 | Get list of vulnerabilities

post /public_api/uvem/v1/get_vulnerabilities

Get a list of vulnerabilities that match the filter fields. The list includes key information about each vulnerability.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
headers = { 'content-type': "application/json" } conn.request("POST", "/public_api/uvem/v1/get_vulnerabilities",
payload, headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/uvem/v1/get_vulnerabilities") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["content-type"] =
'application/json' request.body = "{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "attack_vector", "operator": "string",
"value": "string" } ], "sort": { "field": "string", "keyword": "asc" }, "search_from": 0, "search_to": 500,
"use_page_token": true, "next_page_token": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities");
xhr.setRequestHeader("content-type", "application/json"); xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities")
.header("content-type", "application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
```

{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
.asString();
import Foundation let headers = ["content-type": "application/json"] let parameters = ["request_data": ["filters": [
["field": "attack_vector", "operator": "string", "value": "string"]], "sort": ["field": "string", "keyword": "asc"
], "search_from": 0, "search_to": 500, "use_page_token": true, "next_page_token": "string"]] as [String : Any] let
postData = JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url:
NSURL(string: "https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities")! as URL, cachePolicy:
.useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers
request.httpBody = postData as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as
URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let
httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [CURLOPT_URL => "https://api-
yourfqdn/public_api/uvem/v1/get_vulnerabilities", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
CURLOPT_HTTPHEADER => ["content-type: application/json"],]); $response = curl_exec($curl); $err =
curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers);
curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/uvem/v1/get_vulnerabilities"); var request = new
RestRequest(Method.POST); request.AddHeader("content-type", "application/json");
request.AddParameter("application/json", "{\"request_data\":{\"filters\":
[{\"field\":\"attack_vector\",\"operator\":\"string\",\"value\":\"string\"}],\"sort\":
{\"field\":\"string\",\"keyword\":\"asc\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\"st
ParameterType.RequestBody); IRestResponse response = client.Execute(request);

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

An array of filter fields

▶ sortobject

▶ search_frominteger

An integer representing the start offset index of results Default value - 0

▶ search_tointeger

An integer representing the start offset index of results. Use this field to specify the number of results on a page when using page token pagination. Default value - 500

▶ use_page_tokenboolean

Use `"use_page_token":true` in the initial request to paginate the response data.

▶ next_page_tokenstring

If `"use_page_token":true` was included in the initial request, the response for that request will include a page token. Use `"next_page_token":"string"` to pass that page token into the next request to paginate the next set of data.

REQUEST

```
{ "request_data": { "filters": [ { "field": "attack_vector", "operator": "example", "value": "example" } ], "sort": {
"field": "example", "keyword": "asc" }, "search_from": 0, "search_to": 0, "use_page_token": false, "next_page_token":
"example" } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ result_countinteger

▶ total_countinteger

▶ vulnerabilitiesarray
▶ next_page_tokenstring
RESPONSE
{ "reply": { "result_count": 0, "total_count": 0, "vulnerabilities": [{ "vulnerability_id": "example", "epss_score": 0, "cvss_score": 0, "cvss_severity": "example", "package_names": ["example"], "vendors": ["example"], "distribution_and_releases": ["example"], "cisa_kev": {}, "cvss_severity_source": "example", "cvss_score_source": "example", "first_published": 0, "last_modified": 0, "reported_exploited_by": [{}], "attack_vector": "example", "cvss_version": "example" }], "next_page_token": "example" } }

Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json
▼ replyobject
▶ err_codestring
▶ err_msgstring
▶ err_extrastring
RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

Internal server error. A unified status for API communication type errors.

Body
application/json
▼ replyobject
▶ err_codestring
▶ err_msgstring
▶ err_extrastring
RESPONSE
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }

2.20.2.2 | Get vulnerability details

get /public_api/uvem/v1/vulnerabilities

Get detailed information about a specific vulnerability.

For example, the following request retrieves detailed information about CVE-2021-28799: https://api-{{fqdn}}/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2021-28799

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ authorization String required

api-key

Example: `{{api-key}}`
▼ x-xdr-auth-id String required

api-key-id

Example: `{{api_key_id}}`
Query parameters
▼ vulnerabilityId String required

Vulnerability ID

Example: `CVE-2023-1234`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'authorization: {{api-key}}' -H 'x-xdr-auth-id: {{api_key_id}}'
'https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234'
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") headers = { 'authorization': "{{api-key}}", 'x-xdr-auth-id': "{{api_key_id}}" } conn.request("GET", "/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234", headers=headers) res = conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true http.verify_mode =
```

```
OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Get.new(url) request["authorization"] = '{{api-key}}' request["x-xdr-auth-id"] = '{{api_key_id}}' response = http.request(request) puts response.read_body
const data = null; const xhr = new XMLHttpRequest(); xhr.withCredentials = true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) { console.log(this.responseText); } }); xhr.open("GET", "https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234"); xhr.setRequestHeader("authorization", "{{api-key}}"); xhr.setRequestHeader("x-xdr-auth-id", "{{api_key_id}}"); xhr.send(data);
HttpResponse<String> response = Unirest.get("https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234") .header("authorization", "{{api-key}}") .header("x-xdr-auth-id", "{{api_key_id}}") .asString();
import Foundation let headers = [ "authorization": "{{api-key}}", "x-xdr-auth-id": "{{api_key_id}}" ] let request = NSMutableURLRequest(url: NSURL(string: "https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234")! as URL, cachePolicy: .useProtocolCachePolicy, timeoutInterval: 10.0) request.httpMethod = "GET" request.allHTTPHeaderFields = headers let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest, completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse = response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "", CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST => "GET", CURLOPT_HTTPHEADER => [ "authorization: {{api-key}}", "x-xdr-auth-id: {{api_key_id}}" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo "cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "GET"); curl_easy_setopt(hnd, CURLOPT_URL, "https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234"); struct curl_slist *headers = NULL; headers = curl_slist_append(headers, "authorization: {{api-key}}"); headers = curl_slist_append(headers, "x-xdr-auth-id: {{api_key_id}}"); curl_easy_setopt(hnd, CURLOPT_HTTPHEADER, headers); CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/uvem/v1/vulnerabilities?vulnerabilityId=CVE-2023-1234"); var request = new RestRequest(Method.GET); request.AddHeader("authorization", "{{api-key}}"); request.AddHeader("x-xdr-auth-id", "{{api_key_id}}"); IRestResponse response = client.Execute(request);
```

Responses

OK

Body

application/json

▼ cvssobject
▶ baseScoreMetricsobject
▶ scorenumber
▶ scoreSourcestring
▶ severitystring
▶ severitySourcestring
▶ vectorStringstring
▶ versionstring
▼ descriptionstring
▼ epss_scorenumber
▼ exploitDetailsobject
▶ commercialExploitFoundboolean
▶ exploitMaturitystring
▶ firstReportedThreatActorinteger
▶ mostRecentReportedThreatActorinteger
▶ publicExploitFoundboolean
▶ reportedExploitedboolean
▶ reportedExploitedByBotnetsboolean
▶ reportedExploitedByRansomwareboolean
▶ reportedExploitedByThreatActorsboolean
▶ weaponizedExploitFoundboolean
▼ fixVersionsstring
▼ isKevboolean
▼ temporalCvssobject
▶ confidencestring
▶ scorenumber
▶ vectorStringstring
▶ versionstring
▼ vulnerabilityIDstring

RESPONSE


```
{ "cvss": { "baseScoreMetrics": { "attackComplexity": "example", "attackVector": "example", "availabilityImpact": "example", "confidentialityImpact": "example", "integrityImpact": "example", "privilegesRequired": "example", "scope": "example", "userInteraction": "example" }, "score": 0.1, "scoreSource": "example", "severity": "example",
```

"severitySource": "example", "vectorString": "example", "version": "example" }, "description": "example", "epss_score": 0.1, "exploitDetails": { "commercialExploitFound": false, "exploitMaturity": "example", "firstReportedThreatActor": 0, "mostRecentReportedThreatActor": 0, "publicExploitFound": false, "reportedExploited": false, "reportedExploitedByBotnets": false, "reportedExploitedByRansomware": false, "reportedExploitedByThreatActors": false, "weaponizedExploitFound": false }, "fixVersions": "example", "isKev": false, "temporalCvss": { "confidence": "example", "score": 0.1, "vectorString": "example", "version": "example" }, "vulnerabilityID": "example" }

2.20.3 | Affected software

APIs for managing affected software

2.20.3.1 | Get affected software

post /public_api/uvem/v1/get_affected_software

Get a filtered list of the software affected by one or more vulnerabilities.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ Authorization String required

{api-key}

Example: `authorization_example`
▼ x-xdr-auth-id String required

{api-key-id}

Example: `xXdrAuthId_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'Authorization: authorization_example' -H 'x-xdr-auth-id: xXdrAuthId_example'
'https://api-yourfqdn/public_api/uvem/v1/get_affected_software'
-d ''
import http.client conn = http.client.HTTPSConnection("api-yourfqdn") payload = "{\"request_data\":{\"filters\":
[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
headers = { 'Authorization': "SOME_STRING_VALUE", 'x-xdr-auth-id': "SOME_STRING_VALUE", 'content-type':
"application/json" } conn.request("POST", "/public_api/uvem/v1/get_affected_software", payload, headers) res =
conn.getresponse() data = res.read() print(data.decode("utf-8"))
require 'uri' require 'net/http' require 'openssl' url = URI("https://api-
yourfqdn/public_api/uvem/v1/get_affected_software") http = Net::HTTP.new(url.host, url.port) http.use_ssl = true
http.verify_mode = OpenSSL::SSL::VERIFY_NONE request = Net::HTTP::Post.new(url) request["Authorization"] =
'SOME_STRING_VALUE' request["x-xdr-auth-id"] = 'SOME_STRING_VALUE' request["content-type"] = 'application/json'
request.body = "{\"request_data\":{\"filters\":[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":
[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
response = http.request(request) puts response.read_body
const data = JSON.stringify({ "request_data": { "filters": [ { "field": "affected_cpu_archs", "operator": "contains",
"value": [ "string" ] } ], "sort": { "field": "string", "keyword": "string" }, "search_from": 0, "search_to": 500,
"use_page_token": true, "next_page_token": "string" } }); const xhr = new XMLHttpRequest(); xhr.withCredentials =
true; xhr.addEventListener("readystatechange", function () { if (this.readyState === this.DONE) {
console.log(this.responseText); } }); xhr.open("POST", "https://api-
yourfqdn/public_api/uvem/v1/get_affected_software"); xhr.setRequestHeader("Authorization", "SOME_STRING_VALUE");
xhr.setRequestHeader("x-xdr-auth-id", "SOME_STRING_VALUE"); xhr.setRequestHeader("content-type", "application/json");
xhr.send(data);
HttpResponse<String> response = Unirest.post("https://api-yourfqdn/public_api/uvem/v1/get_affected_software")
.header("Authorization", "SOME_STRING_VALUE") .header("x-xdr-auth-id", "SOME_STRING_VALUE") .header("content-type",
"application/json") .body("{\"request_data\":{\"filters\":
[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
.asString();
import Foundation let headers = [ "Authorization": "SOME_STRING_VALUE", "x-xdr-auth-id": "SOME_STRING_VALUE",
"content-type": "application/json" ] let parameters = ["request_data": [ "filters": [ [ "field": "affected_cpu_archs",
```

```
"operator": "contains", "value": ["string"] ] ], "sort": [ "field": "string", "keyword": "string" ], "search_from": 0,
"search_to": 500, "use_page_token": true, "next_page_token": "string" ]] as [String : Any] let postData =
JSONSerialization.data(withJSONObject: parameters, options: []) let request = NSMutableURLRequest(url: NSURL(string:
"https://api-yourfqdn/public_api/uvem/v1/get_affected_software")! as URL, cachePolicy: .useProtocolCachePolicy,
timeoutInterval: 10.0) request.httpMethod = "POST" request.allHTTPHeaderFields = headers request.httpBody = postData
as Data let session = URLSession.shared let dataTask = session.dataTask(with: request as URLRequest,
completionHandler: { (data, response, error) -> Void in if (error != nil) { print(error) } else { let httpResponse =
response as? HTTPURLResponse print(httpResponse) } }) dataTask.resume()
<?php $curl = curl_init(); curl_setopt_array($curl, [ CURLOPT_URL => "https://api-
yourfqdn/public_api/uvem/v1/get_affected_software", CURLOPT_RETURNTRANSFER => true, CURLOPT_ENCODING => "",
CURLOPT_MAXREDIRS => 10, CURLOPT_TIMEOUT => 30, CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1, CURLOPT_CUSTOMREQUEST
=> "POST", CURLOPT_POSTFIELDS => "{\"request_data\":{\"filters\":
[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
CURLOPT_HTTPHEADER => [ "Authorization: SOME_STRING_VALUE", "content-type: application/json", "x-xdr-auth-id:
SOME_STRING_VALUE" ], ]); $response = curl_exec($curl); $err = curl_error($curl); curl_close($curl); if ($err) { echo
"cURL Error #:" . $err; } else { echo $response; }
CURL *hnd = curl_easy_init(); curl_easy_setopt(hnd, CURLOPT_CUSTOMREQUEST, "POST"); curl_easy_setopt(hnd, CURLOPT_URL,
"https://api-yourfqdn/public_api/uvem/v1/get_affected_software"); struct curl_slist *headers = NULL; headers =
curl_slist_append(headers, "Authorization: SOME_STRING_VALUE"); headers = curl_slist_append(headers, "x-xdr-auth-id:
SOME_STRING_VALUE"); headers = curl_slist_append(headers, "content-type: application/json"); curl_easy_setopt(hnd,
CURLOPT_HTTPHEADER, headers); curl_easy_setopt(hnd, CURLOPT_POSTFIELDS, "{\"request_data\":{\"filters\":
[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
CURLcode ret = curl_easy_perform(hnd);
var client = new RestClient("https://api-yourfqdn/public_api/uvem/v1/get_affected_software"); var request = new
RestRequest(Method.POST); request.AddHeader("Authorization", "SOME_STRING_VALUE"); request.AddHeader("x-xdr-auth-id",
"SOME_STRING_VALUE"); request.AddHeader("content-type", "application/json"); request.AddParameter("application/json",
"{\"request_data\":{\"filters\":[{\"field\":\"affected_cpu_archs\",\"operator\":\"contains\",\"value\":
[\"string\"]}],\"sort\":
{\"field\":\"string\",\"keyword\":\"string\"},\"search_from\":0,\"search_to\":500,\"use_page_token\":true,\"next_page_token\":\
ParameterType.RequestBody); IRestResponse response = client.Execute(request);
```

Body parameters

application/json

▼ request_dataobjectrequired

▶ filtersarray

▶ sortobject

▶ search_frominteger

An integer representing the start offset index of results Default value - 0

▶ search_tointeger

An integer representing the start offset index of results. Use this field to specify the number of results on a page when using page token pagination. Default value - 500

▶ use_page_tokenboolean

Use `"use_page_token":true` in the initial request to paginate the response data.

▶ next_page_tokenstring

If `"use_page_token":true` was included in the initial request, the response for that request will include a page token. Use `"next_page_token":"string"` to pass that page token into the next request to paginate the next set of data.

REQUEST

```
{ "request_data": { "filters": [ { "field": "affected_cpu_archs", "operator": "contains", "value": 0.1 } ], "sort": {
"field": "example", "keyword": "example" }, "search_from": 0, "search_to": 0, "use_page_token": false,
"next_page_token": "example" } }
```

Responses

OK

Body

application/json

▼ replyobject

▶ result_countinteger

▶ total_countinteger

▶ vulnerabilitiesarray

▶ next_page_tokenstring

RESPONSE


```
{ "reply": { "result_count": 0, "total_count": 0, "vulnerabilities": [ { "vulnerability_id": "example", "cvss_score": 0.1, "cvss_severity": "example", "package_name": "example", "distro": "example", "release": "example", "affected_cpu_archs": [ {} ], "last_modified": 0, "affected_versions": [ "example" ] } ], "next_page_token": "example" } }
```


Unauthorized access. An issue occurred during authentication. This can indicate an incorrect key, id, or other invalid authentication parameters.

Body
application/json
▼ replyobject
▶ err_codestring
▶ err_msgstring
▶ err_extrastring
RESPONSE


```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```


Internal server error. A unified status for API communication type errors.

Body
application/json
▼ replyobject
▶ err_codestring
▶ err_msgstring
▶ err_extrastring
RESPONSE


```
{ "reply": { "err_code": "example", "err_msg": "example", "err_extra": "example" } }
```

2.21 | Vulnerability Management APIs

2.21.1 | Preface

You can export the OpenAPI specs in the Cortex Stoplight instance.

Managing vulnerabilities effectively is crucial to proactively maintaining the security, integrity, and availability of IT infrastructure. Cortex Cloud provides a comprehensive vulnerability management platform, helping you identify, assess, prioritize, and remediate security vulnerabilities across your entire IT infrastructure including endpoints, code, and cloud.

This API covers two capability areas:

- Vulnerability Management Policies â€ create, read, update, and delete vulnerability management policies; trigger on-demand scans.
- Vulnerability Findings â€ query per-asset CVE finding records (paginated or by ID) and perform bulk snapshot exports via XQL.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Version: Cortex Cloud

2.21.1.1 | Servers

https://{fqdn}

Tenant-specific API base URL

2.21.1.2 | Default authentication

Please note that this documentation assumes a minimum level of authentication is required, unless explicitly stated otherwise.
It is essential to ensure that any of the following authentication mechanisms are in place to access the API endpoints:

- ApiKeyAuth=[], ApiKeyNonce

2.21.2 | Vulnerability Management

Public APIs for vulnerability policy management

2.21.2.1 | Get Policies List

post /public_api/uvm_public/v1/list_policies

Retrieve a paginated list of vulnerability management policies with optional filtering and sorting capabilities. This endpoint allows you to search through policies based on various criteria such as name, status, priority, and other attributes.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management
Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/uvm_public/v1/list_policies'
-d '{ "filter_data" : { "filter" : { "AND" : [ { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD",
"SEARCH_VALUE" : "Search_Value_1" }, { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE"
: "Search_Value_1" } ] }, "paging" : "", "sort" : [ { "ORDER" : "ASC", "FIELD" : "FIELD" }, { "ORDER" : "ASC", "FIELD"
: "FIELD" } ], "locked" : { "AND" : [ { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE"
: "Search_Value_1" }, { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE" :
"Search_Value_1" } ] } } }'
```
Body parameters
required
application/json
▼ filter_dataobjectrequired
▶ filterobject
▶ sortarray
▶ pagingobject
▶ lockedobject

Filter passed in from the application that is not intended to be modified by the user. Be aware that this field is not guaranteed to not be modified by the user.

REQUEST a
```
{ "filter_data": { "filter": { "AND": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }
], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "sort": [ { "FIELD":
"example", "ORDER": "ASC" } ], "paging": { "from": 0, "to": 0 }, "locked": { "AND": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] } } }
{ "filter_data": { "filter": { "AND": [ { "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }
] }, "sort": [ { "FIELD": "example", "ORDER": "ASC" } ], "paging": { "from": 0, "to": 0 }, "locked": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } } }
{ "filter_data": { "filter": { "AND": [ { "AND": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }
] }, "sort": [ { "FIELD": "example", "ORDER": "ASC" } ], "paging": { "from": 0, "to": 0 }, "locked": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } } }
{ "filter_data": { "filter": { "AND": [ {} ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] }, "sort": [ { "FIELD": "example", "ORDER": "ASC" } ], "paging": { "from": 0, "to": 0 },
"locked": { "AND": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } } }
```
Responses

Successful Response

Body
application/json
▼ DATAarrayrequired
[
]
▼ FILTER_COUNTintegerrequired
▼ TOTAL_COUNTintegerrequired
RESPONSE
```
{ "DATA": [ {} ], "FILTER_COUNT": 0, "TOTAL_COUNT": 0 }
```

Validation Error

Body
application/json
▼ detailarray

[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE

```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.2.2 | Create Policy Public

post /public_api/uvm_public/v1/create_policy

Create a new vulnerability management policy for issue creation, kubernetes runtime protection, or prevention actions.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/uvm_public/v1/create_policy'
-d '{ "match_criteria" : { "AND" : [ { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE"
: "Search_Value_1" }, { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE" :
"Search_Value_1" } ] }, "severity" : "", "asset_group_scope" : [ 6, 6 ], "policy_type" : "", "exclusion_criteria" : {
}, "name" : "name", "issue_type" : "issue_type", "description" : "description", "action" : [ { "action_type" :
"BLOCK_BUILD", "take_action" : true, "category" : "BLOCK" }, { "action_type" : "BLOCK_BUILD", "take_action" : true,
"category" : "BLOCK" } ], "priority" : 0, "status" : "" }'
```
Body parameters
required
application/json
▼ namestringrequired
▼ descriptionstring
▼ priorityintegerrequired
▼ statusobject
Default:`"DISABLED"`
▶ string (Enum)
▼ match_criteriaobjectrequired
Any of AND-Input
▶ ANDarrayrequired
▶ ORarrayrequired
▼ exclusion_criteriaobject
Any of EMPTY
▶ ANDarrayrequired
▶ ORarrayrequired
▼ actionarrayrequired
[
Any of BlockBuild
▶ action_typestring
▶ take_actionboolean
▶ categorystring
▶ action_typestring
▶ take_actionboolean
▶ categorystring
▶ action_typestring
▶ namestring
▶ take_actionboolean
▶ categorystring
]
▼ action_categorystring (Enum)required
Allowed values:"BLOCK""CREATE_ISSUE"
▼ issue_typestring
▼ severityobject

▶ string (Enum)
▼ asset_group_scopearray[integer]required
▼ policy_typeobject
Default: `"STANDARD_POLICY"`
▶ string (Enum)
REQUEST a

```
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": { "AND": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] }, "action": [ { "action_type": "example", "take_action": false, "category": "example",
"name": "example" } ], "action_category": "BLOCK", "issue_type": "example", "severity": "CRITICAL",
"asset_group_scope": [ 0 ], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {
"OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } ], "OR": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "action": [ { "action_type": "example", "take_action": false,
"category": "example", "name": "example" } ], "action_category": "BLOCK", "issue_type": "example", "severity":
"CRITICAL", "asset_group_scope": [ 0 ], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {
"AND": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } ], "OR": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "action": [ { "action_type": "example", "take_action": false,
"category": "example", "name": "example" } ], "action_category": "BLOCK", "issue_type": "example", "severity":
"CRITICAL", "asset_group_scope": [ 0 ], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {} ],
"OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": {
"AND": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD":
"example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "action": [ { "action_type": "example",
"take_action": false, "category": "example", "name": "example" } ], "action_category": "BLOCK", "issue_type":
"example", "severity": "CRITICAL", "asset_group_scope": [ 0 ], "policy_type": "GLOBAL_EXCLUSION" }
```

Responses

Successful Response

Body
application/json
▼ idstringrequireduuid
RESPONSE

```
{ "id": "uuid string" }
```


Validation Error

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE

```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.2.3 | Update Policy

put /public_api/uvm_public/v1/update_policy/{id}

Update an existing vulnerability management policy by providing its unique identifier.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id UUID required
Example: `38400000-8cf0-11bd-b23e-10b96e4ef00d`

Request headers

▼ x-xdr-auth-id required

▼ Authorization String required

Example: `authorization_example`

CLIENT REQUEST Bash+curl

```
curl -X 'PUT'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/uvm_public/v1/update_policy/{id}'
-d '{ "match_criteria" : { "AND" : [ { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE"
: "Search_Value_1" }, { "SEARCH_TYPE" : "SEARCH_TYPE", "SEARCH_FIELD" : "SEARCH_FIELD", "SEARCH_VALUE" :
"Search_Value_1" } ] }, "severity" : "", "asset_group_scope" : [ 6, 6 ], "policy_type" : "", "exclusion_criteria" : {
}, "name" : "name", "issue_type" : "issue_type", "description" : "description", "action" : [ { "action_type" :
"BLOCK_BUILD", "take_action" : true, "category" : "BLOCK" }, { "action_type" : "BLOCK_BUILD", "take_action" : true,
"category" : "BLOCK" } ], "priority" : 0, "status" : "" }'
```

Body parameters

required

application/json

▼ namestringrequired

▼ descriptionstring

▼ priorityintegerrequired

▼ statusobject

Default:`"DISABLED"`

▶ string (Enum)

▼ match_criteriaobjectrequired

Any of AND-Input

▶ ANDarrayrequired

▶ ORarrayrequired

▼ exclusion_criteriaobject

Any of EMPTY

▶ ANDarrayrequired

▶ ORarrayrequired

▼ actionarrayrequired

[

Any of BlockBuild

▶ action_typestring

▶ take_actionboolean

▶ categorystring

▶ action_typestring

▶ take_actionboolean

▶ categorystring

▶ action_typestring

▶ namestring

▶ take_actionboolean

▶ categorystring

]

▼ action_categorystring (Enum)required

Allowed values:"BLOCK""CREATE_ISSUE"

▼ issue_typestring

▼ severityobject

▶ string (Enum)

▼ asset_group_scopearray[integer]required

▼ policy_typeobject

Default:`"STANDARD_POLICY"`

▶ string (Enum)

REQUEST a

```
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": { "AND": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] }, "action": [ { "action_type": "example", "take_action": false, "category": "example",
"name": "example" } ], "action_category": "BLOCK", "issue_type": "example", "severity": "CRITICAL",
"asset_group_scope": [ 0 ], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [ {
"OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } ], "OR": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "exclusion_criteria": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
```

"SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }, "action": [{ "action_type": "example", "take_action": false, "category": "example", "name": "example" }], "action_category": "BLOCK", "issue_type": "example", "severity": "CRITICAL", "asset_group_scope": [0], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [{ "AND": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }], "OR": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }, "exclusion_criteria": { "AND": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }], "OR": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }, "action": [{ "action_type": "example", "take_action": false, "category": "example", "name": "example" }], "action_category": "BLOCK", "issue_type": "example", "severity": "CRITICAL", "asset_group_scope": [0], "policy_type": "GLOBAL_EXCLUSION" }
{ "name": "example", "description": "example", "priority": 0, "status": "ENABLED", "match_criteria": { "AND": [{}], "OR": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }, "exclusion_criteria": { "AND": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }], "OR": [{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false }] }, "action": [{ "action_type": "example", "take_action": false, "category": "example", "name": "example" }], "action_category": "BLOCK", "issue_type": "example", "severity": "CRITICAL", "asset_group_scope": [0], "policy_type": "GLOBAL_EXCLUSION" }

Responses

Successful Response

Body
application/json
▼ idstringrequireduuid
RESPONSE
{ "id": "uuid string" }

Validation Error

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE
{ "detail": [{ "loc": [0], "msg": "example", "type": "example" }] }

2.21.2.4 | Get Policy By ID

get /public_api/uvm_public/v1/get_policy/{id}

Retrieve a specific vulnerability management policy by its unique identifier.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id UUID required
Example: `38400000-8cf0-11bd-b23e-10b96e4ef00d`
Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`
CLIENT REQUEST Bash+curl
curl -X 'GET'
-H 'Accept: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/uvm_public/v1/get_policy/{id}'

Responses

Successful Response

Body
application/json
▼ PRIORITYintegerrequired
▼ IDstringrequireduuid
▼ NAMEstringrequired
▼ STATUSstringrequired

▼ MATCH_CRITERIAobjectrequired
Any of EMPTY
▶ ANDarrayrequired
▶ ORarrayrequired
▼ EXCLUSIONSobjectrequired
Any of EMPTY
▶ ANDarrayrequired
▶ ORarrayrequired
▼ SEVERITYobject
▶ string (Enum)
▼ OPEN_ISSUESintegerrequired
▼ ESTIMATED_MATCH_COUNTintegerrequired
▼ DESCRIPTIONstringrequired
▼ MODIFIED_BYstringrequired
▼ MODIFIED_TIMESTAMPstringrequireddate-time
▼ ACTIONarrayrequired
[
Any of BlockBuild
▶ action_typestring
▶ take_actionboolean
▶ categorystring
▶ action_typestring
▶ take_actionboolean
▶ categorystring
▶ action_typestring
▶ namestring
▶ take_actionboolean
▶ categorystring
]
▼ ACTION_CATEGORYstring (Enum)required
Allowed values:"BLOCK""CREATE_ISSUE"
▼ ASSET_GROUP_SCOPEarray[integer]
▼ POLICY_TYPEobject
Default:"STANDARD_POLICY"
▶ string (Enum)
RESPONSE a


```
{ "PRIORITY": 0, "ID": "uuid string", "NAME": "example", "STATUS": "example", "MATCH_CRITERIA": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "EXCLUSIONS": { "AND": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example",
"SEARCH_VALUE": false } ] }, "SEVERITY": "CRITICAL", "OPEN_ISSUES": 0, "ESTIMATED_MATCH_COUNT": 0, "DESCRIPTION":
"example", "MODIFIED_BY": "example", "MODIFIED_TIMESTAMP": "2020-01-01T12:00:00Z", "ACTION": [ { "action_type":
"example", "take_action": false, "category": "example", "name": "example" } ], "ACTION_CATEGORY": "BLOCK",
"ASSET_GROUP_SCOPE": [ 0 ], "POLICY_TYPE": "GLOBAL_EXCLUSION" }
{ "PRIORITY": 0, "ID": "uuid string", "NAME": "example", "STATUS": "example", "MATCH_CRITERIA": { "AND": [ { "OR": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } ], "OR": [ { "SEARCH_FIELD":
"example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "EXCLUSIONS": { "AND": [ { "SEARCH_FIELD":
"example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE":
"example", "SEARCH_VALUE": false } ] }, "SEVERITY": "CRITICAL", "OPEN_ISSUES": 0, "ESTIMATED_MATCH_COUNT": 0,
"DESCRIPTION": "example", "MODIFIED_BY": "example", "MODIFIED_TIMESTAMP": "2020-01-01T12:00:00Z", "ACTION": [ {
"action_type": "example", "take_action": false, "category": "example", "name": "example" } ], "ACTION_CATEGORY":
"BLOCK", "ASSET_GROUP_SCOPE": [ 0 ], "POLICY_TYPE": "GLOBAL_EXCLUSION" }
{ "PRIORITY": 0, "ID": "uuid string", "NAME": "example", "STATUS": "example", "MATCH_CRITERIA": { "AND": [ { "AND": [
{ "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] } ], "OR": [ { "SEARCH_FIELD":
"example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "EXCLUSIONS": { "AND": [ { "SEARCH_FIELD":
"example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example", "SEARCH_TYPE":
"example", "SEARCH_VALUE": false } ] }, "SEVERITY": "CRITICAL", "OPEN_ISSUES": 0, "ESTIMATED_MATCH_COUNT": 0,
"DESCRIPTION": "example", "MODIFIED_BY": "example", "MODIFIED_TIMESTAMP": "2020-01-01T12:00:00Z", "ACTION": [ {
"action_type": "example", "take_action": false, "category": "example", "name": "example" } ], "ACTION_CATEGORY":
"BLOCK", "ASSET_GROUP_SCOPE": [ 0 ], "POLICY_TYPE": "GLOBAL_EXCLUSION" }
{ "PRIORITY": 0, "ID": "uuid string", "NAME": "example", "STATUS": "example", "MATCH_CRITERIA": { "AND": [ {} ], "OR":
[ { "SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "EXCLUSIONS": { "AND": [ {
"SEARCH_FIELD": "example", "SEARCH_TYPE": "example", "SEARCH_VALUE": false } ], "OR": [ { "SEARCH_FIELD": "example",
"SEARCH_TYPE": "example", "SEARCH_VALUE": false } ] }, "SEVERITY": "CRITICAL", "OPEN_ISSUES": 0,
"ESTIMATED_MATCH_COUNT": 0, "DESCRIPTION": "example", "MODIFIED_BY": "example", "MODIFIED_TIMESTAMP": "2020-01-
01T12:00:00Z", "ACTION": [ { "action_type": "example", "take_action": false, "category": "example", "name": "example"
} ], "ACTION_CATEGORY": "BLOCK", "ASSET_GROUP_SCOPE": [ 0 ], "POLICY_TYPE": "GLOBAL_EXCLUSION" }
```

Validation Error

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE
```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.2.5 | Delete Policy

delete /public_api/uvm_public/v1/delete_policy/{id}

Delete an existing vulnerability management policy using a policy ID.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ id UUID required
Example: `38400000-8cf0-11bd-b23e-10b96e4ef00d`
Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`
CLIENT REQUEST Bash+curl
```
curl -X 'DELETE'
-H 'Accept: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/uvm_public/v1/delete_policy/{id}'
```
Responses

Successful Response

Body
application/json
▼ boolean
RESPONSE
```
false
```

Validation Error

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE
```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.2.6 | Trigger Scan for an AssetId

post /public_api/vulnerability-management/v1/scan

Trigger On demand Scan based on AssetId on one of CORTEX_NETWORK_SCANNER, CORTEX_XDR_AGENT, CORTEX_XDR_AGENTLESS scanners.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`

CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/vulnerability-management/v1/scan'
-d '{ "scanner_type" : "", "scan_target" : "CONTAINER", "cve_id" : "cve_id", "asset_id" : "asset_id" }'
```
Body parameters
required
application/json

Request model for triggering a vulnerability scan

▼ asset_idstringrequired

The unique identifier of the asset to scan

▼ scanner_typeobjectrequired

The type of scanner to use for the scan

▶ string (Enum)

Type of vulnerability scanner

▼ cve_idstring

CVE identifier (e.g., 'CVE-2024-1234'). Required when scanner_type is CORTEX_NETWORK_SCANNER, optional for other scanner types.

▼ scan_targetstring (Enum)

Scan Target (e.g., 'CONTAINER' or 'HOST' or 'IMAGE'). Required when scanner_type is CORTEX_XDR_AGENT and its Linux endpoint, optional for other scanner types.

Allowed values:"CONTAINER""HOST""IMAGE"
REQUEST
```
{ "asset_id": "example", "scanner_type": "CORTEX_NETWORK_SCANNER", "cve_id": "example", "scan_target": "CONTAINER" }
```
Responses

Successful Response

Body
application/json

Response model for scan trigger operation

▼ messagestringrequired
▼ scan_idinteger
RESPONSE
```
{ "message": "example", "scan_id": 0 }
```

Validation Error

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE
```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.3 | Bring Your Own Scanner

Import vulnerability findings from external scanners into Cortex vulnerability management. Use these endpoints to submit asset and CVE data from third-party scanners and to poll the status of async import jobs.

2.21.3.1 | Submit assets and vulnerabilities from an external scanner

post /public_api/vulnerability-management/v1/external-scans/assets

Imports asset and vulnerability data from a third-party scanner into Cortex vulnerability management.

Each request must include at least one asset. Each asset can carry multiple CVE findings. The platform validates all input on receipt â€ if validation fails, a `422 Unprocessable Entity` response is returned with field-level error details.

Successful requests are processed asynchronously. The response includes a `job_id` that can be polled using the Get BYOS import job status endpoint, plus counts of accepted assets and vulnerabilities.

RBAC permission required: `manage_vulnerabilities_action`

Required licenses: Exposure Management; and either Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Request headers

▼ x-xdr-auth-id required

▼ Authorization String required

Example: `authorization_example`

CLIENT REQUEST Bash+curl

```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/vulnerability-management/v1/external-scans/assets'
-d '{ "product" : "product", "assets" : [ { "product" : "product", "origin_asset_id" : "origin_asset_id", "last_seen"
: 1, "fqdn" : [ "fqdn", "fqdn" ], "version" : "version", "origin_tags" : [ "env:perf-test", "batch:stress" ], "ipv4" :
[ "ipv4", "ipv4" ], "asset_name" : "asset_name", "ipv6" : [ "ipv6", "ipv6" ], "mac_address" : "mac_address", "vendor"
: "vendor", "vulnerabilities" : [ { "protocol" : "TCP", "vulnerability_id" : "vulnerability_id", "last_seen" : 0,
"evidence" : "evidence", "port" : 39500, "cve_id" : [ "cve_id", "cve_id" ], "raw_output" : "raw_output", "confidence"
: "Potential", "description" : "description", "scan_name" : "scan_name" }, { "protocol" : "TCP", "vulnerability_id" :
"vulnerability_id", "last_seen" : 0, "evidence" : "evidence", "port" : 39500, "cve_id" : [ "cve_id", "cve_id" ],
"raw_output" : "raw_output", "confidence" : "Potential", "description" : "description", "scan_name" : "scan_name" } ],
"os_name" : "os_name" }, { "product" : "product", "origin_asset_id" : "origin_asset_id", "last_seen" : 1, "fqdn" : [
"fqdn", "fqdn" ], "version" : "version", "origin_tags" : [ "env:perf-test", "batch:stress" ], "ipv4" : [ "ipv4",
"ipv4" ], "asset_name" : "asset_name", "ipv6" : [ "ipv6", "ipv6" ], "mac_address" : "mac_address", "vendor" :
"vendor", "vulnerabilities" : [ { "protocol" : "TCP", "vulnerability_id" : "vulnerability_id", "last_seen" : 0,
"evidence" : "evidence", "port" : 39500, "cve_id" : [ "cve_id", "cve_id" ], "raw_output" : "raw_output", "confidence"
: "Potential", "description" : "description", "scan_name" : "scan_name" }, { "protocol" : "TCP", "vulnerability_id" :
"vulnerability_id", "last_seen" : 0, "evidence" : "evidence", "port" : 39500, "cve_id" : [ "cve_id", "cve_id" ],
"raw_output" : "raw_output", "confidence" : "Potential", "description" : "description", "scan_name" : "scan_name" } ],
"os_name" : "os_name" } ], "vendor" : "vendor", "version" : "version" }'
```

Body parameters

required

application/json

Request body for importing vulnerable assets from an external scanner.

▼ vendorstringrequired

Vulnerability scanner vendor. Examples: `TENABLE`, `QUALYS`, `RAPID7_VM`, `RAPID7_CLOUD`.

▼ productstringrequired

Product name associated with the vulnerabilities.

▼ versionstring

Product version, used for `(vendor, product, version)` CVE mapping.

▼ assetsarrayrequired

List of assets with their vulnerability findings. Must contain at least one asset.

[

▶ ipv4array[string]

IPv4 addresses used to identify this asset in the source system.

▶ vulnerabilitiesarrayrequired

All vulnerabilities related to this asset.

▶ origin_asset_idstring

Unique ID generated by the source system. Used as a uniqueness constraint for future matching.

▶ asset_namestring

Friendly name of the asset. If omitted, the platform may auto-generate a name from the FQDN, IPv4, or IPv6 address.

▶ ipv6array[string]

IPv6 addresses used to identify this asset in the source system.

▶ fqdnarray[string]

FQDNs used to identify this asset in the source system.

▶ mac_addressstring

MAC address assigned to the asset in the source system.

▶ origin_tagsarray[string]

Tags from the origin system. Stored in the platform tags field to allow ingesting additional asset context. Parsed as key/value pairs separated by colons.

▶ last_seenintegerrequired

Timestamp in milliseconds. Must be within the last 30 days from the current time. Older or future timestamps are rejected with HTTP 422.

▶ os_namestring

Operating system name of the asset.

▶ productstring

Product name installed on the asset.

▶ vendorstring

Vendor of the product installed on the asset.

▶ versionstring

Version of the product installed on the asset.

]

REQUEST


```
{ "vendor": "example", "product": "example", "version": "example", "assets": [ { "ipv4": [ "ipv4 string" ],
"vulnerabilities": [ { "vulnerability_id": "example", "last_seen": 0, "port": 0, "protocol": "TCP", "raw_output":
"example", "confidence": "Potential", "description": "example", "evidence": "example", "scan_name": "example",
"cve_id": [ "example" ] } ], "origin_asset_id": "example", "asset_name": "example", "ipv6": [ "ipv6 string" ], "fqdn":
[ "example" ], "mac_address": "example", "origin_tags": [ "env:perf-test", "batch:stress" ], "last_seen": 0,
"os_name": "example", "product": "example", "vendor": "example", "version": "example" } ] }
```


Responses

Assets accepted for asynchronous processing. The response includes import counts and the `job_id` for status polling.

Body

application/json

Response for a successful vulnerable asset import. Returns counts and the async job identifier needed to poll for completion.

▼ assets_countintegerrequired

Total number of assets accepted in the import request.

Example:`2`

▼ vulnerabilities_countintegerrequired

Total number of vulnerabilities accepted across all assets in the import request.

Example:`4`

▼ job_idstringrequireduuid

Unique identifier for the async import job. Use this value with the Get BYOS Import Job Status endpoint to poll for completion.

Example:`"a2b1aba2-37fe-4fb4-ba6d-829e8cf5d653"`

▼ job_statusobjectrequired

Initial status of the import job. Will be `INITIATED` immediately after a successful POST.

▶ string (Enum)

Possible status values for a BYOS import job.

RESPONSE

{ "assets_count": 2, "vulnerabilities_count": 4, "job_id": "a2b1aba2-37fe-4fb4-ba6d-829e8cf5d653", "job_status": "INITIATED" }

Validation Error â€ one or more request fields failed schema validation. Check the `detail` array for field-level error messages.

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE
{ "detail": [{ "loc": [0], "msg": "example", "type": "example" }] }

2.21.3.2 | Poll the status of a BYOS import job

get /public_api/vulnerability-management/v1/external-scans/assets/jobs/{job_id}

Returns the current status of an asynchronous BYOS import job.

After submitting assets via the Submit assets and vulnerabilities from an external scanner endpoint, use the returned `job_id` to poll this endpoint until the job reaches a terminal state (`COMPLETED`, `FAILED`, or `COMPLETED_WITH_ERRORS`).

Possible `job_status` values:

- `INITIATED` â€ job received, not yet queued
- `PROCESSING` â€ job is actively being processed
- `COMPLETED` â€ all assets imported successfully
- `COMPLETED_WITH_ERRORS` â€ import finished but some assets failed; check `error_log`
- `FAILED` â€ job failed entirely; check `error_log` for details

Response codes:

- `200` â€ Job status retrieved successfully. The HTTP status reflects only the poll request itself; the *job's* outcome is in `job_status` (including the terminal `FAILED` and `COMPLETED_WITH_ERRORS` states).
- `404` â€ `job_id` was not found.

`422 Unprocessable Entity` is only returned by the upstream Submit assets and vulnerabilities from an external scanner endpoint when the request payload fails schema validation. A `422` therefore means the job was never created; a `FAILED` `job_status` returned in a `200` response means the job ran but could not complete â€ see `error_log` for details.

RBAC permission required: `manage_vulnerabilities_action`

Required licenses: Exposure Management; and either Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ job_id String required

The unique identifier of the BYOS import job, returned by the Submit assets and vulnerabilities from an external scanner endpoint.

Example: `jobId_example`
Request headers
▼ x-xdr-auth-id required
▼ Authorization String required
Example: `authorization_example`
CLIENT REQUEST Bash+curl
```
curl -X 'GET'
-H 'Accept: application/json'
-H 'x-xdr-auth-id: ' -H 'Authorization: authorization_example'
'https://api-yourfqdn/public_api/vulnerability-management/v1/external-scans/assets/jobs/{job_id}'
```
Responses

Job status retrieved successfully.

Body
application/json

Status and metadata for a BYOS import job.

▼ job_idstringrequired

Unique job ID. Use this value with the Get BYOS Import Job Status endpoint to poll for completion.

▼ created_timestampstringrequireddate-time

ISO 8601 timestamp of when the job was received.

▼ job_statusobjectrequired

Current status of the import job.

▶ string (Enum)

Possible status values for a BYOS import job.

▼ last_updatedstringdate-time

ISO 8601 timestamp of when the job was last updated.

▼ error_logstring or null

Error details if the job failed or completed with errors. May be `null` when there is no error.
RESPONSE

```
{ "job_id": "example", "created_timestamp": "2020-01-01T12:00:00Z", "job_status": "INITIATED", "last_updated": "2020-01-01T12:00:00Z", "error_log": null }
```


Job not found â€ the specified `job_id` does not exist.

Body
application/json
▼ detailstring
Example:`"Job with id 'a2b1aba2-37fe-4fb4-ba6d-829e8cf5d653' not found"`
RESPONSE

```
{ "detail": "Job with id 'a2b1aba2-37fe-4fb4-ba6d-829e8cf5d653' not found" }
```


Validation Error â€ the `job_id` path parameter failed schema validation.

Body
application/json
▼ detailarray
[
▶ locarrayrequired
▶ msgstringrequired
▶ typestringrequired
]
RESPONSE

```
{ "detail": [ { "loc": [ 0 ], "msg": "example", "type": "example" } ] }
```

2.21.4 | Vulnerability Findings

vulnerability finding records (paginated or by ID)

2.21.4.1 | List vulnerability findings (paginated)

post /vulnerability-management/v1/vulnerability-finding/search/

Returns paginated vulnerability findings â€ one record per CVE/asset pair. Use `next_page_token` from the response to fetch subsequent pages.

Rate limit: 10 per 24 hours period

Filterable fields: `ASSET_NAME`, `ASSET_GROUP_IDS`, `ASSET_CATEGORY`, `CVE_ID`, `CVSS_SEVERITY`, `PLATFORM_ID`, `FIX_AVAILABLE`, `PACKAGE_IN_USE`, `HAS_KEV`, `EXPLOIT_LEVEL`, `EPSS_SCORE`, `INTERNET_EXPOSED`, `FIRST_OBSERVED`, `LAST_OBSERVED`.

Sortable fields: `EPSS_SCORE`, `CVSS_SCORE`, `CORTEX_VULNERABILITY_RISK_SCORE`.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/vulnerability-management/v1/vulnerability-finding/search/'
```

```
-d '{ "filter" : "", "next_page_token" : "eyJsYXN0X2VsZW1lbnQiOiAxMjM0fQ==", "sort" : [ { "field" : "CVSS_SCORE",
"keyword" : "DESC" }, { "field" : "CVSS_SCORE", "keyword" : "DESC" } ] }'
```

Body parameters
required
application/json

Request body for paginated vulnerability findings search.

▼ filterobject

Optional filter block. Filterable fields: `ASSET_NAME`, `ASSET_GROUP_IDS`, `ASSET_CATEGORY`, `CVE_ID`, `CVSS_SEVERITY`, `PLATFORM_ID`, `FIX_AVAILABLE`, `PACKAGE_IN_USE`, `HAS_KEV`, `EXPLOIT_LEVEL`, `EPSS_SCORE`, `INTERNET_EXPOSED`, `FIRST_OBSERVED`, `LAST_OBSERVED`.

▶ ANDarray
▶ ORarray
▼ sortarray

Optional sort criteria. Sortable fields: `EPSS_SCORE`, `CVSS_SCORE`, `CORTEX_VULNERABILITY_RISK_SCORE`.

[
▶ fieldstringrequired

Field to sort by. Allowed values: `EPSS_SCORE`, `CVSS_SCORE`, `CORTEX_VULNERABILITY_RISK_SCORE`.

▶ keywordstring (Enum)required
]
▼ next_page_tokenstring

Opaque token returned by a previous response to fetch the next page. Omit on the first request.

Example:`"eyJsYXN0X2VsZW1lbnQiOiAxMjM0fQ=="`
REQUEST first_page
```
{ "filter": { "AND": [ { "field": "CVSS_SEVERITY", "operator": "EQ", "value": "CRITICAL" }, { "field":
"INTERNET_EXPOSED", "operator": "EQ", "value": true } ] }, "sort": [ { "field": "EPSS_SCORE", "keyword": "desc" } ] }
{ "filter": { "AND": [ { "field": "CVSS_SEVERITY", "operator": "EQ", "value": "CRITICAL" } ] }, "next_page_token":
"eyJsYXN0X2VsZW1lbnQiOiAxMjM0fQ==" }
```

Responses

Successful response with vulnerability findings.

Body
application/json

Paginated response containing vulnerability findings.

▼ replyobject
▶ dataarray
▶ filter_countinteger

Total number of findings matching the applied filter.

▶ total_countinteger

Total number of findings across all filters.

▶ next_page_tokenstring

Present only when additional pages exist. Pass this value as `next_page_token` in the next request.

RESPONSE with_next_page

```
{ "reply": { "data": [ { "cortex_vulnerability_risk_score": null, "asset_name": "SNMP Server at 89.170.90.209:161",
"cve_id": "CVE-2025-20169", "cve_description": "A vulnerability in the SNMP subsystem of Cisco IOS Software and Cisco
IOS XE Software could allow an authenticated, remote attacker to cause a DoS condition on an affected
device.\r\n\r\nThis vulnerability is due to improper error handling when parsing SNMP requests. An attacker could
exploit this vulnerability by sending a crafted SNMP request to an affected device. A successful exploit could allow
the attacker to cause the device to reload unexpectedly, resulting in a DoS condition. \r\nThis vulnerability affects
SNMP versions 1, 2c, and 3. To exploit this vulnerability through SNMP v2c or earlier, the attacker must know a valid
read-write or read-only SNMP community string for the affected system. To exploit this vulnerability through SNMP v3,
the attacker must have valid SNMP user credentials for the affected system.", "epss_score": 0.00368, "cvss_score":
7.7, "cvss_severity": "HIGH", "fix_versions": [], "fix_date": null, "published_date": 1738713600000,
"cve_risk_factors": [ "Attack vector: network", "High severity", "Attack complexity: low", "DoS - High" ],
"affected_software": null, "has_kev": null, "exploitable": false, "exploit_level": "NONE", "asset_type": "SERVICE",
"asset_category": "Service", "has_issue": false, "ipv4_addresses": [ "89.170.90.209" ], "ipv6_addresses": [],
"operating_system": null, "os_family": null, "location": null, "internet_exposed": true, "provider": "ON_PREM",
```

"finding_sources": ["CORTEX_ATTACK_SURFACE_MANAGEMENT"], "first_observed": 1764890719158, "last_observed": 1764715866000, "source_tags": ["asm.attribution.organization_names:[Parameter FAKE_2332423424]"], "layer_id": null, "image": null, "origin_package_name": null, "package_file_creation_time": null, "package_licenses": [], "package_version": null, "package_purl": null, "package_type": null, "cve_publish_date": 1738713600000, "platform_id": "c273519c3b61adfb7dc46547fbcbfa32", "asset_id": "fef704015fd52a8495025f830b7483988d170f93b5807617761e4af827275a83", "fix_available": false, "package_in_use": null, "file_path": null, "package_symbols": [], "package_author": null, "application_version": null, "asset_type_class": "External Surface", "type_id": "140000000", "derived_from_base_image": null, "is_derived": false, "image_name": null, "asset_group_ids": [], "volume_asset_id": null, "is_root": null, "volume_path": null, "partition_id": null, "partition_id_type": null, "disk_name": null, "remediation": null, "issue_id": null }], "filter_count": 342, "total_count": 10500, "next_page_token": "eyJsYXN0X2VsZW1lbnQiOiA1Njc4fQ==" } }
{ "reply": { "data": [{ "cortex_vulnerability_risk_score": null, "asset_name": "SNMP Server at 89.170.90.209:161", "cve_id": "CVE-2025-20169", "cve_description": "A vulnerability in the SNMP subsystem of Cisco IOS Software and Cisco IOS XE Software could allow an authenticated, remote attacker to cause a DoS condition on an affected device.\r\n\r\nThis vulnerability is due to improper error handling when parsing SNMP requests. An attacker could exploit this vulnerability by sending a crafted SNMP request to an affected device. A successful exploit could allow the attacker to cause the device to reload unexpectedly, resulting in a DoS condition. \r\nThis vulnerability affects SNMP versions 1, 2c, and 3. To exploit this vulnerability through SNMP v2c or earlier, the attacker must know a valid read-write or read-only SNMP community string for the affected system. To exploit this vulnerability through SNMP v3, the attacker must have valid SNMP user credentials for the affected system.", "epss_score": 0.00368, "cvss_score": 7.7, "cvss_severity": "HIGH", "fix_versions": [], "fix_date": null, "published_date": 1738713600000, "cve_risk_factors": ["Attack vector: network", "High severity", "Attack complexity: low", "DoS - High"], "affected_software": null, "has_kev": null, "exploitable": false, "exploit_level": "NONE", "asset_type": "SERVICE", "asset_category": "Service", "has_issue": false, "ipv4_addresses": ["89.170.90.209"], "ipv6_addresses": [], "operating_system": null, "os_family": null, "location": null, "internet_exposed": true, "provider": "ON_PREM", "finding_sources": ["CORTEX_ATTACK_SURFACE_MANAGEMENT"], "first_observed": 1764890719158, "last_observed": 1764715866000, "source_tags": ["asm.attribution.organization_names:[Parameter FAKE_2332423424]"], "layer_id": null, "image": null, "origin_package_name": null, "package_file_creation_time": null, "package_licenses": [], "package_version": null, "package_purl": null, "package_type": null, "cve_publish_date": 1738713600000, "platform_id": "c273519c3b61adfb7dc46547fbcbfa32", "asset_id": "fef704015fd52a8495025f830b7483988d170f93b5807617761e4af827275a83", "fix_available": false, "package_in_use": null, "file_path": null, "package_symbols": [], "package_author": null, "application_version": null, "asset_type_class": "External Surface", "type_id": "140000000", "derived_from_base_image": null, "is_derived": false, "image_name": null, "asset_group_ids": [], "volume_asset_id": null, "is_root": null, "volume_path": null, "partition_id": null, "partition_id_type": null, "disk_name": null, "remediation": null, "issue_id": null }], "filter_count": 342, "total_count": 10500 } }

Invalid filter parameters or expired page token.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
RESPONSE expired_token
{ "reply": { "err_code": 400, "err_msg": "Token Expired" } }
{ "reply": { "err_code": 400, "err_msg": "Invalid filter parameters" } }

Rate limit exceeded.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
RESPONSE
{ "reply": { "err_code": 400, "err_msg": "Invalid filter parameters", "err_extra": "Field 'unknown_field' is not allowed" } }

2.21.4.2 | Get a single vulnerability finding by platform ID

post /vulnerability-management/v1/vulnerability-finding/{platform_id}

Returns the vulnerability finding record for the given `platform_id`. Returns HTTP 404 when no matching finding exists.

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

Path parameters
▼ platform_id String required

Unique platform identifier for a vulnerability finding.

Example: `abc123def456`
CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/vulnerability-management/v1/vulnerability-finding/{platform_id}'
-d ''
```
Body parameters
Object
application/json

Empty body â€ no request parameters required.

REQUEST
```
{}
```
Responses

Vulnerability finding record.

Body
application/json

Response containing a single vulnerability finding by platform ID.

▼ replyobject
▶ dataarray
RESPONSE
found

```
{ "reply": { "data": [ { "cortex_vulnerability_risk_score": null, "asset_name": "SNMP Server at 89.170.90.209:161",
"cve_id": "CVE-2025-20169", "cve_description": "A vulnerability in the SNMP subsystem of Cisco IOS Software and Cisco
IOS XE Software could allow an authenticated, remote attacker to cause a DoS condition on an affected
device.\r\n\r\nThis vulnerability is due to improper error handling when parsing SNMP requests. An attacker could
exploit this vulnerability by sending a crafted SNMP request to an affected device. A successful exploit could allow
the attacker to cause the device to reload unexpectedly, resulting in a DoS condition. \r\nThis vulnerability affects
SNMP versions 1, 2c, and 3. To exploit this vulnerability through SNMP v2c or earlier, the attacker must know a valid
read-write or read-only SNMP community string for the affected system. To exploit this vulnerability through SNMP v3,
the attacker must have valid SNMP user credentials for the affected system.", "epss_score": 0.00368, "cvss_score":
7.7, "cvss_severity": "HIGH", "fix_versions": [], "fix_date": null, "published_date": 1738713600000,
"cve_risk_factors": [ "Attack vector: network", "High severity", "Attack complexity: low", "DoS - High" ],
"affected_software": null, "has_kev": null, "exploitable": false, "exploit_level": "NONE", "asset_type": "SERVICE",
"asset_category": "Service", "has_issue": false, "ipv4_addresses": [ "89.170.90.209" ], "ipv6_addresses": [],
"operating_system": null, "os_family": null, "location": null, "internet_exposed": true, "provider": "ON_PREM",
"finding_sources": [ "CORTEX_ATTACK_SURFACE_MANAGEMENT" ], "first_observed": 1764890719158, "last_observed":
1764715866000, "source_tags": [ "asm.attribution.organization_names:[Parameter FAKE_2332423424]" ], "layer_id": null,
"image": null, "origin_package_name": null, "package_file_creation_time": null, "package_licenses": [],
"package_version": null, "package_purl": null, "package_type": null, "cve_publish_date": 1738713600000, "platform_id":
"c273519c3b61adfb7dc46547fbcbfa32", "asset_id": "fef704015fd52a8495025f830b7483988d170f93b5807617761e4af827275a83",
"fix_available": false, "package_in_use": null, "file_path": null, "package_symbols": [], "package_author": null,
"application_version": null, "asset_type_class": "External Surface", "type_id": "140000000",
"derived_from_base_image": null, "is_derived": false, "image_name": null, "asset_group_ids": [], "volume_asset_id":
null, "is_root": null, "volume_path": null, "partition_id": null, "partition_id_type": null, "disk_name": null,
"remediation": null, "issue_id": null } ] } }
```


Missing or invalid platform_id.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
RESPONSE
missing_id
```
{ "reply": { "err_code": 400, "err_msg": "platform_id is missing" } }
```

No finding found for the given platform_id.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring
RESPONSE
not_found
```
{ "reply": { "err_code": 404, "err_msg": "No data found" } }
```

2.21.5 | Snapshot

2.21.5.1 | Bulk export vulnerability findings snapshot

post /vulnerability-management/v1/vulnerability-finding/snapshot/

Executes an XQL query against the `uvm_findings` dataset and returns results as a newline-delimited JSON (NDJSON) stream for large result sets.

Rate limit: 10 requests per 24-hour window per tenant

Response variants:

- Stream (`application/x-ndjson`) â€ large result sets; each line is a `VulnerabilityFinding` JSON object
- Inline (`application/json`) â€ small result sets returned directly

Required license: Cortex Cloud Runtime Security or Cortex Cloud Posture Management

CLIENT REQUEST Bash+curl
```
curl -X 'POST'
-H 'Accept: application/x-ndjson,application/json'
-H 'Content-Type: application/json'
'https://api-yourfqdn/vulnerability-management/v1/vulnerability-finding/snapshot/'
-d '{ "timeframe" : "", "limit" : 10000 }'
```
Body parameters
application/json

Top-level request envelope.

▼ contextobject

Tenant context.

▶ lcaas_idintegerint64

Tenant LCaaS identifier.

▼ request_dataobject

Request parameters for the vulnerability findings snapshot export.

▶ limitinteger

Maximum number of rows to return. Omit for the full dataset.

▶ timeframeobject

Optional XQL timeframe using an absolute range (`from` + `to`). When omitted the server's default lookback window is used.

REQUEST default_full_snapshot
```
{ "request_data": { "timeframe": { "from": 15989076874, "to": 1771482089874 } } }
```

```
{ "request_data": { "limit": 5000 } }
{ "request_data": { "timeframe": { "from": 15989076787, "to": 1771482089874 }, "limit": 10000 } }
```

Responses

Newline-delimited JSON stream response. Body is a newline-delimited stream of `VulnerabilityFinding` JSON objects.

Body
application/x-ndjson

Newline-delimited JSON stream. Each line is a self-contained `VulnerabilityFinding` JSON object.

▼ stringbinary

Newline-delimited JSON stream. Each line is a self-contained `VulnerabilityFinding` JSON object.

RESPONSE
ndjson_stream

```
"{\"platform_id\":\"abc123\",\"asset_name\":\"prod-web-01\",\"cve_id\":\"CVE-2024-
12345\",\"cvss_severity\":\"CRITICAL\",\"epss_score\":0.87,\"first_observed\":1700000000000,\"last_observed\":1710000000000}\n{
server-02\",\"cve_id\":\"CVE-2023-
99999\",\"cvss_severity\":\"HIGH\",\"epss_score\":0.12,\"first_observed\":1705000000000,\"last_observed\":1710000000000}"
```

Invalid request parameters, or the feature is disabled.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring

RESPONSE feature_disabled

```
{ "error": { "message": "Invalid Request" } }
{ "error": { "message": "Invalid request parameters" } }
```

Request timed out waiting for response.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring

RESPONSE
timeout

```
{ "error": { "message": "Timed out waiting for results. Please try again later." } }
```

Rate limit exceeded. Maximum 10 snapshot requests per 24-hour window per tenant.

Body
application/json

Standard error response for vulnerability findings endpoints.

▼ replyobject
▶ err_codeinteger
▶ err_msgstring
▶ err_extrastring

RESPONSE

```
{ "reply": { "err_code": 400, "err_msg": "Invalid filter parameters", "err_extra": "Field 'unknown_field' is not
allowed" } }
```