Cortex AgentIX Documentation - Summary
1. Learn about Cortex AgentIX
1.1 Get Started with Cortex AgentIX
1.2 Understand Cortex AgentIX Scenes
1.3 Agentic AI in Cortex AgentIX
1.3.1 Manage Cortex AgentIX agents
1.3.2 Cortex AgentIX use cases
1.3.3 Agentic Assistant security
1.4 Key components and concepts
1.5. Data retention policy
1.6. Supported cultures
1.7. Supported web browsers
2. Onboard Cortex AgentIX
2.1 Plan and prepare your deployment
2.2. Onboarding checklist
2.3. Activate Cortex AgentIX
2.3.1 Cortex AgentIX supported regions
2.3.2 Enable access to Palo Alto Networks resources
2.4. Install and configure content
2.5.1 Pre-deployment checklist
2.5.2. Set up users and roles
2.5.3. Configure system settings
If the Password Protection (for downracked files) setting under Settings -> Configuration -> General -> Server Settings is enabled, enter the password. Instead, it is stored in the Fa
Settings -> Configuration -> General -> Server Settings
2.5.4 Configure security settings
2.5.5. Set up an engine
Settings -> Configurations -> Data Broker -> Engines -> Create New Engine
2.5. Pre-deployment steps
2.6.1 Forward logs and data from Cortex AgentIX to external services
2.6.2 Data and log notification formats
2.6.2.1 Configure external applications for forwarding
2.6.2.2 Integrate notification forwarding
2.6.2.3 Monitor administrative activity
2.6.2.4 Issue notification format
2.6.2.5 Management Audit log notification format
2.6. Log forwarding
2.7. Plan and prepare your deployment
2.8. Pre-deployment checklist
2.9. Configure Cortex AgentIX
2.9.1 Manage tenancies
2.9.2. Add a new data source or instance
2.9.3. Configure integration permissions
Settings -> Configurations -> Data Collection -> Integration Permissions
2.9.4 Configure Marketplace
2.9.4.1 Cortex Marketplace
Settings -> Configurations -> Marketplace or in Cortex Deploy Docs Marketplace
2.9.4.2 Content packs
2.9.4.3 Content Pack Support Types
2.9.4.4 Cortex AgentIX content
2.9.4.5 Manage content packs
2.9.4.6 Marketplace FAQs
2.9.4.7 Content changes when upgrading Cortex AgentIX content
2.9.4.8 Content pack contributions
2.9.5.1 Manage API keys
2.9.5.2 Integration use cases
2.9.5.3. Add an integration instance
2.9.5.4 Fetch issues from an integration instance
2.9.5.4.1 Map fields to issue types
Settings -> Configurations -> Object Setup -> Issues -> Classification & Mapping
2.9.5.4.2 Classify events using a classifier for issue types
2.9.5.5. Forward Requests to Long-Running Integrations
2.9.5.6a Manage credentials
Settings -> Configurations -> Integrations -> Credentials -> New Credential
2.9.6. Troubleshoot integrations
2.9.7. Measuring data freshness
2.9.8. Overview of data ingestion metrics
2.9.9 Verify collector connectivity
2.9.10 Creating correlation rules to monitor data ingestion health
3.1. Agentic Assistant components and concepts
3.1.1 Manage actions
3.1.2 Register actions
3.1.3 Manage agents
3.1.4 Build agents
3.1.5 Expand agent capabilities with MCP integrations
3.1.6. Agentic Assistant role-based access control
3.2. Configure the Cortex Agentic Assistant
3.2.1 Agents Hub
3.2.1.1 Create a new agent
3.2.1.2 Manage agents
3.2.1.3 Build agents
3.2.1.4. Expand agent capabilities with MCP integrations
3.3. Cortex MCP server
3.3.1 Install the Cortex MCP server
3.3.2 Configure the MCP client
3.3.3 Use the Cortex MCP server
3.3.4 Create custom Cortex MCP server tools
Settings -> Developer -> Edit Config
3.4. Users and Roles Management
3.4.1 Users and roles in Cortex AgentIX
3.4.2. Role management
3.4.2.1 Role-based permissions in Cortex AgentIX
3.4.2.2 Manage roles in the Cortex AgentIX tenant
In the Cortex AgentIX tenant, you can set permission levels for each role by going to Settings -> Configurations -> Access Management -> Roles and then editing or creating a new role.
3.4.3 User group management
By default, Enable Scope-Based Access Control is disabled in Settings -> Configurations -> General -> Server Settings, and granular scoping is not enforced.
3.4.4 User management
3.4.4.1 Manage users in the Cortex AgentIX tenant
3.4.4.2. Manage user scope
3.4.5 Manage access to objects
3.4.5.1 Manage access to custom dashboards
3.4.5.2. Manage access to saved queries
3.4.6 Authentication users through the Customer Support Portal
3.4.6.2. Authentication users using SSO
3.4.6. Set up an authentication
3.4.6.1. Set up Okta as the Identity Provider using SAML 2.0
3.4.6.4. Set up Azure AD as the Identity Provider using SAML 2.0
Configure tenant level settings: An administrator must first establish the sharing framework under Settings -> Configurations -> Access Management -> Objects.
3.5. Engines
3.5.1. What is an engine?
3.5.2.Engine requirements
3.5.3. Install an engine
3.5.3.1. Docker
3.5.3.1.1 Install Docker
3.5.3.1.2 Docker image security
3.5.3.1.3 Docker FAQs
3.5.3.1.4. Troubleshoot Docker issues
3.5.3.1.5. Configure Docker just rate limit
3.5.3.1.6. Change the Docker installation folder
3.5.3.2 Docker hardening guide
3.5.3.3 Change the container storage directory
3.5.3.4 Install Podman
3.5.3.5. Migrate From Docker to Podman
3.5.3.6. Troubleshoot Podman
3.5.4. Manage engines
You can manage your engines and load-balancing groups by in Settings -> Configurations -> Engines.
3.5.5. Upgrade an engine
3.5.6. Remove an engine
3.5.7 Configure the engine to use a web proxy
3.5.7.1 Configure the engine to call the server through a reverse proxy
3.5.7.2 Use NGINX as a reverse proxy
3.5.7.3 Configure an engine to use custom certificates
3.5.8 Use an engine in an integration
3.5.9 Run a script using an engine
Investigation & Response -> Automation -> Scripts
3.5.10. Troubleshoot engines
When troubleshooting engines, access the logs from Settings -> Configurations -> Engines and select the engine for which you want to download the logs.
3.5.11. Troubleshoot integrations using engines
3.6. Cases and Issues configuration
3.6.1. Case and Issue lifecycle
3.6.2. Customize your cases
3.6.2.1 External integrations
3.6.2.2. Create a case domain
3.6.2.2.1 Create Domains
You can see all domains under Configurations -> Object Setup -> Cases -> Domains
Settings -> Configurations -> Object Setup -> Cases -> Domains
Settings -> Configurations -> Access Management -> User Groups
Settings -> Configurations -> Access Management -> Users.
To enable/ or to the domain for an API key, go to Settings -> Configurations -> Integrations -> API Keys.
3.6.2.3 Create a starting configuration
3.6.2.4 Create custom case statuses and resolution reasons
Configurations -> Object Setup -> Cases -> Properties.
3.6.3. Customize issue fields and layouts
3.6.3.1 Issue fields
3.6.3.1.1 Issue field types
Settings -> Configurations -> Object Setup -> Issues -> Fields -> New Field
3.6.3.1.2 Create custom issue fields
3.6.3.1.2.1 Create a grid field for an issue
3.6.3.1.2.2 Issue field triggered scripts
Settings -> Configurations -> General -> Server Settings -> Issues and Enable Time Field.
3.6.3.1.2.3 Configure issue time fields
3.6.3.1.2.4. Configure a playbook to run timers
3.6.3.1.2.5 Automatic changes to issue fields using playbooks
3.6.3.1.2.6 Use issue timer field commands manually in the CLI
3.6.3.1.3. Issue field types
3.6.3.2 Issue layouts
3.6.3.2.1 Create custom issue layouts
3.6.3.2.2. Add a custom widget to an issue layout
Investigation & Response -> Automation -> Scripts and upload the following script: scriptlet_widget_create.py, scriptlet_widget_update.py, scriptlet_widget_delete.py, scriptlet_widget_get.py, scriptlet_widget_list.py, scriptlet_widget_test.py, scriptlet_widget_help.py, scriptlet_widget_validate.py, scriptlet_widget_clone.py, scriptlet_widget_export.py, scriptlet_widget_import.py, scriptlet_widget_bulk_export.py, scriptlet_widget_bulk_import.py, scriptlet_widget_bulk_clone.py, scriptlet_widget_bulk_delete.py, scriptlet_widget_bulk_enable.py, scriptlet_widget_bulk_disable.py, scriptlet_widget_bulk_validate.py, scriptlet_widget_help.py, scriptlet_widget_list.py, scriptlet_widget_test.py, scriptlet_widget