Cortex AgentiX Documentation - Summary

- 1. Learn about Cortex AgentiX
  - 1.1. Get Started with Cortex AgentiX
  - 1.2. Understand Cortex AgentiX licenses
  - 1.3. Agentic AI in Cortex AgentiX
    - 1.3.1. Manage Cortex AgentiX agents
    - 1.3.2. Cortex AgentiX use cases
    - 1.3.3. Agentic Assistant security
  - 1.4. Key components and concepts
  - 1.5. Data retention policy
  - 1.6. Supported ciphers
  - 1.7. Supported web browsers
- 2. Onboard Cortex AgentiX
  - 2.1. Plan and prepare your deployment
  - 2.2. Onboarding checklist
  - 2.3. Activate Cortex AgentiX
    - 2.3.1. Cortex AgentiX supported regions
    - 2.3.2. Enable access to Palo Alto Networks resources
  - 2.4. Install and configure content
  - 2.5. Post-deployment steps
    - 2.5.1. Post-deployment checklist
    - 2.5.2. Set up users and roles
    - 2.5.3. Configure server settings
      - If the Password Protection (for downloaded files) setting under Settings → Configuration → General → Server Settings is enabled, enter the password 'suspicious' to download the file
      - Settings → Configurations → General → Server Settings
    - 2.5.4. Configure security settings
    - 2.5.5. Set up an engine
      - Settings → Configurations → Data Broker → Engines → Create New Engine
    - 2.5.6. Log forwarding
      - 2.5.6.1. Forward logs and data from Cortex AgentiX to external services
        - 2.5.6.1.1. Configure external applications for forwarding
          - 2.5.6.1.1.1. Integrate a syslog receiver
          - 2.5.6.1.1.2. Integrate Slack for outbound notifications
        - 2.5.6.1.2. Configure notification forwarding
        - 2.5.6.1.3. Monitor administrative activity
      - 2.5.6.2. Data and log notification formats
        - 2.5.6.2.1. Issue notification format
        - 2.5.6.2.2. Management Audit log notification format
- 3. Cortex AgentiX configuration
  - 3.1. Configure Cortex AgentiX
  - 3.2. Content configuration
    - 3.2.1. Configure content using Data Sources
      - 3.2.1.1. Manage instances
      - 3.2.1.2. Add a new data source or instance
      - 3.2.1.3. Configure integration permissions
        - Settings → Configurations → Data Collection → Integration Permissions
    - 3.2.2. Marketplace
      - 3.2.2.1. Cortex Marketplace
        - Settings → Configurations → Marketplace) or at Cortex Developer Docs Marketplace
      - 3.2.2.2. Content packs
      - 3.2.2.3. Content Pack Support Types
      - 3.2.2.4. Cortex AgentiX content
      - 3.2.2.5. Manage content packs
      - 3.2.2.6. Marketplace FAQs
      - 3.2.2.7. Content changes when upgrading Cortex AgentiX versions
      - 3.2.2.8. Content pack contributions
    - 3.2.3. Integrations
      - Settings → Configurations → Marketplace
      - 3.2.3.1. Manage API keys
      - 3.2.3.2. Integration use cases
      - 3.2.3.3. Add an integration instance
      - 3.2.3.4. Fetch issues from an integration instance
        - 3.2.3.4.1. Map fields to issue types
          - Settings → Configurations → Object Setup → Issues → Classification & Mapping
        - 3.2.3.4.2. Classify events using a classifier for issue types
      - 3.2.3.5. Forward Requests to Long-Running Integrations
      - 3.2.3.6. Manage credentials
        - Settings → Configurations → Integrations → Credentials → New Credential
    - 3.2.4. Troubleshoot integrations
    - 3.2.5. Measuring data freshness
    - 3.2.6. Overview of data ingestion metrics
    - 3.2.7. Verify collector connectivity
    - 3.2.8. Creating correlation rules to monitor data ingestion health
  - 3.3. Configure the Cortex Agentic Assistant
    - 3.3.1. Agentic Assistant components and concepts
    - 3.3.2. Agents Hub
      - 3.3.2.1. Manage actions
      - 3.3.2.2. Register actions
      - 3.3.2.3. Manage agents
      - 3.3.2.4. Build agents
      - 3.3.2.5. Expand agent capabilities with MCP integrations
    - 3.3.3. Agentic Assistant role-based access control
  - 3.4. Cortex MCP server
    - 3.4.1. Cortex MCP server overview
      - 3.4.1.1. Install the Cortex MCP server
      - 3.4.1.2. Configure the MCP client
        - Settings → Developer → Edit Config
      - 3.4.1.3. Use the Cortex MCP server
      - 3.4.1.4. Create custom Cortex MCP server tools
  - 3.5. Users and roles management
    - 3.5.1. Users and roles in Cortex AgentiX
    - 3.5.2. Roles management
      - 3.5.2.1. Role-based permissions in Cortex AgentiX
        - In the Cortex AgentiX tenant, you can set permission levels for each role by going to Settings → Configurations → Access Management → Roles and then editing or creating a new role
      - 3.5.2.2. Manage roles in the Cortex AgentiX tenant
    - 3.5.3. User group management
      - By default, Enable Scope Based Access Control is disabled in Settings → Configurations → General → Server Settings, and granular scoping is not enforced
    - 3.5.4. User management
      - 3.5.4.1. Manage users in the Cortex AgentiX tenant
      - 3.5.4.2. Manage user scope
    - 3.5.5. Manage access to objects
    - 3.5.6. Set up authentication
      - 3.5.6.1. Authenticate users through the Customer Support Portal
      - 3.5.6.2. Authenticate users using SSO
      - 3.5.6.3. Set up Okta as the Identity Provider Using SAML 2.0
      - 3.5.6.4. Set up Azure AD as the Identity Provider Using SAML 2.0
  - 3.6. Engines
    - 3.6.1. What is an engine?
    - 3.6.2. Engine requirements
    - 3.6.3. Install an engine
      - 3.6.3.1. Docker
        - 3.6.3.1.1. Install Docker
          - 3.6.3.1.1.1. Install Docker distribution for Red Hat on an engine server
          - 3.6.3.1.1.2. Docker image security
          - 3.6.3.1.1.3. Docker FAQs
          - 3.6.3.1.1.4. Troubleshoot Docker issues
          - 3.6.3.1.1.5. Configure Docker pull rate limit
          - 3.6.3.1.1.6. Change the Docker installation folder
        - 3.6.3.1.2. Docker hardening guide
      - 3.6.3.2. Podman
        - 3.6.3.2.1. Change the container storage directory
        - 3.6.3.2.2. Install Podman
        - 3.6.3.2.3. Migrate From Docker to Podman
        - 3.6.3.2.4. Troubleshoot Podman
    - 3.6.4. Manage engines
      - You can manage your engines and load-balancing groups by going to Settings → Configurations → Engines
    - 3.6.5. Upgrade an engine
    - 3.6.6. Remove an engine
    - 3.6.7. Configure engines
      - 3.6.7.1. Configure the engine to use a web proxy
      - 3.6.7.2. Configure the engine to call the server without using a proxy
        - 3.6.7.2.1. Use NGINX as a reverse proxy
      - 3.6.7.3. Configure an engine to use custom certificates
    - 3.6.8. Use an engine in an integration
    - 3.6.9. Run a script using an engine
      - Investigation & Response → Automation → Scripts
    - 3.6.10. Troubleshoot engines
      - When troubleshooting engines, access the logs from Settings → Configurations → Engines and select the engine from which you want to download the logs
    - 3.6.11. Troubleshoot integrations running on engines
  - 3.7. Cases and issues configuration
    - 3.7.1. Case and issue lifecycle
    - 3.7.2. Customize your cases
      - 3.7.2.1. External integrations
      - 3.7.2.2. Create a case domain
        - You can see all domains under Configurations → Object Setup → Cases → Domains
        - Settings → Configurations → Object Setup → Cases → Domains
        - Settings → Configurations → Access Management → User Groups
        - Settings → Configurations → Access Management → Users
        - To enable access to the domain for an API key, got to Settings → Configurations → Integrations → API Keys
      - 3.7.2.3. Create a starring configuration
      - 3.7.2.4. Create custom case statuses and resolution reasons
        - Configurations → Object Setup → Cases → Properties
    - 3.7.3. Customize issue fields and layouts
      - 3.7.3.1. Issue fields
        - 3.7.3.1.1. Issue field types
        - 3.7.3.1.2. Create custom issue fields
          - Settings → Configurations → Object Setup → Issues → Fields → New Field
          - 3.7.3.1.2.1. Create a grid field for an issue
          - 3.7.3.1.2.2. Issue field triggered scripts
          - 3.7.3.1.2.3. Issue timer fields
            - Settings → Configurations → General → Server Settings → Issues and Enable Timer Field
            - 3.7.3.1.2.3.1. Configure issue timer fields
            - 3.7.3.1.2.3.2. Configure a playbook to run timers
            - 3.7.3.1.2.3.3. Automate changes to issue fields using timer scripts
            - 3.7.3.1.2.3.4. Use issue timer field commands manually in the CLI
      - 3.7.3.2. Issue layouts
        - 3.7.3.2.1. Create custom issue layouts
        - 3.7.3.2.2. Add a custom widget to an issue layout
          - Investigation & Response → Automation → Scripts and upload the following script: Expand script commonfields: id: ee3b9604-324b-4ab5-8164-15ddf6e428ab version: 49 name: IndicatorWidgetBar script: |- # Constants HIGH = 3 SUSPICIOUS = 2 LOW = 1 NONE = 0 indicators = [] scores = {HIGH: 0, SUSPICIOUS: 0, LOW: 0, NONE: 0} incident_id = demisto
          - Investigation & Response → Automation → Scripts and upload the following script
          - Settings → Configurations → Object Setup → Issues → Layouts
        - 3.7.3.2.3. Create rules for issue layouts
          - Settings → Configurations → Object Setup → Issues → Layout Rules → New Rule
    - 3.7.4. Customize case fields and layouts
      - 3.7.4.1. Case fields
        - 3.7.4.1.1. Case field types
        - 3.7.4.1.2. Create custom case fields
          - Settings → Configurations → Object Setup → Cases → Fields → New Field
          - 3.7.4.1.2.1. Create a grid field for a case
          - 3.7.4.1.2.2. Update case fields
        - 3.7.4.1.3. Create case timers and SLAs
          - Settings → Configurations → Object Setup → Cases and open the Fields tab
        - 3.7.4.1.4. Update case timer and SLA fields
      - 3.7.4.2. Case layouts
        - 3.7.4.2.1. Create custom case layouts
        - 3.7.4.2.2. Create rules for case layouts
          - Settings → Configurations → Object Setup → Cases → Layout Rules → New Rule
    - 3.7.5. Issue syncing
      - You can find a sync profile ID under Settings → Configurations → Object Setup → Issues → Sync Profiles
      - 3.7.5.1. Create a sync profile
    - 3.7.6. What's a correlation rule?
      - After you configure your correlation rules, you can manage them in Threat Management → Detection Rules → Correlations, and view and analyze the generated issues in Cases and the Issues Table
      - 3.7.6.1. Correlation rule details
        - If you are assigned a role that enables Investigation → Rules privileges, you can manage all user-defined Correlation Rules from Threat Management → Detection Rules → Correlations
      - 3.7.6.2. Create a correlation rule
        - You can create a new correlation rule from either the Threat Management → Detection Rules → Correlation Rules page or when building a query in XQL Search
      - 3.7.6.3. Manage correlation rules
    - 3.7.7. Manage external dynamic lists
      - If creating a custom role, select View/Edit for EDL (Roles → New Roles → INVESTIGATION & RESPONSE → Response → EDL
  - 3.8. Automations
    - 3.8.1. Automation in Cortex AgentiX
    - 3.8.2. Quick Actions
    - 3.8.3. Automation Exclusion Center
      - 3.8.3.1. Manage automation exclusion policies
    - 3.8.4. Playbooks
      - 3.8.4.1. Playbooks overview
      - 3.8.4.2. Playbook development checklist
      - 3.8.4.3. Plan your playbook
      - 3.8.4.4. Manage playbooks
      - 3.8.4.5. Build your playbook
        - 3.8.4.5.1. Task 1. Choose from existing playbooks or create your own
          - the Investigation & Response → Automation → Playbooks page to find an existing playbook, customize it, or create a playbook
        - 3.8.4.5.2. Task 2. Configure playbook settings
        - 3.8.4.5.3. Task 3. Add objects from the Task Library
          - 3.8.4.5.3.1. Add Quick Actions, commands, and scripts
          - 3.8.4.5.3.2. Add sub-playbooks
          - 3.8.4.5.3.3. Add AI prompt tasks
          - 3.8.4.5.3.4. Add manual tasks and blank tasks
            - 3.8.4.5.3.4.1. Create a standard task
            - 3.8.4.5.3.4.2. Create a conditional task
            - 3.8.4.5.3.4.3. Create a communication task
          - 3.8.4.5.3.5. Create a section header
          - 3.8.4.5.3.6. Configure script error handling in a playbook
        - 3.8.4.5.4. Task 4. Add custom playbook features
        - 3.8.4.5.5. Task 5. Test and debug the playbook
        - 3.8.4.5.6. Task 6. Manage playbook content
      - 3.8.4.6. Customize your playbook
        - 3.8.4.6.1. Configure a sub-playbook loop
        - 3.8.4.6.2. Filter and transform data
          - Investigation & Response → Automation → Scripts → New Script
          - 3.8.4.6.2.1. Filter considerations, categories, and built-in filters
          - 3.8.4.6.2.2. Transformer considerations, categories, and built-in transformers
        - 3.8.4.6.3. Extract indicators
        - 3.8.4.6.4. Extend context
        - 3.8.4.6.5. Update issue fields with playbook tasks
        - 3.8.4.6.6. Playbook polling
      - 3.8.4.7. Test your playbook
        - 3.8.4.7.1. Troubleshoot playbook performance
      - 3.8.4.8. Manage playbook content
        - Investigation & Response → Automations → Playbooks
      - 3.8.4.9. Best practices
    - 3.8.5. Create an automation rule
    - 3.8.6. AI Prompts
      - On the AI Prompts page (Investigation → Response → Automation → AI Prompts), you can view, edit, and manually create prompts
      - 3.8.6.1. AI prompts role-based access control
      - 3.8.6.2. Use existing prompts
        - Investigation & Response → Automation → AI Prompts and in the Prompts Library search for the prompt you want to use
      - 3.8.6.3. Create a prompt
        - Investigation & Response → Automation → AI Prompts and click + New Prompt
    - 3.8.7. Scripts
      - On the Scripts page (Investigation → Response → Automation → Scripts), you can view, edit, and create scripts in JavaScript, Python, or PowerShell
      - 3.8.7.1. Use existing scripts
        - Investigation & Response → Automation → Scripts and in the Scripts Library search for the script you want to use
      - 3.8.7.2. Create a script
      - 3.8.7.3. Use the Automation Engineer agent to accelerate script development and deployment
      - 3.8.7.4. Change the Docker image in an integration or script
    - 3.8.8. Context data
      - 3.8.8.1. Issue context data
      - 3.8.8.2. Case context data
      - 3.8.8.3. Search context data
      - 3.8.8.4. Add context data to an issue
      - 3.8.8.5. Add context data to a case
      - 3.8.8.6. Delete context data from a case
      - 3.8.8.7. Use context data in a playbook
  - 3.9. Jobs
    - 3.9.1. Manage jobs
    - 3.9.2. Create a time triggered job
    - 3.9.3. Create a job triggered by a delta in a feed
      - Investigation & Response → Automation → Jobs → New Job
  - 3.10. Lists
    - 3.10.1. Create a list
    - 3.10.2. List commands
    - 3.10.3. Use cases: JSON lists
      - Settings → Configurations → Object Setup → Lists → Add a List
      - Investigation & Response → Automation → Playbooks → New Playbook
    - 3.10.4. Transform a list into an array
      - Investigation & Response → Automation → Playbooks and create or edit a playbook
  - 3.11. Data management
    - 3.11.1. Dataset management
      - 3.11.1.1. What are datasets?
      - 3.11.1.2. Lookup datasets
        - 3.11.1.2.1. Import a lookup dataset
        - 3.11.1.2.2. Download JSON file of lookup dataset
          - Open the Settings → Configurations → Data Management → Dataset Management page
        - 3.11.1.2.3. Set time to live for lookup datasets
      - 3.11.1.3. Monitor datasets and dataset views activity
    - 3.11.2. What are Data Model Rules?
      - 3.11.2.1. Data Model Rules editor views
      - 3.11.2.2. Data Model Rules file structure and syntax
      - 3.11.2.3. MODEL
        - The Settings → Configurations → XQL Configuration → Case Sensitivity (case_sensitive) setting can overwrite this case_sensitive configuration for all fields in the application except for BIOCs, which will remain case insensitive no matter what this setting is set to
      - 3.11.2.4. RULE
      - 3.11.2.5. Field structure
      - 3.11.2.6. How to map authentication story events?
      - 3.11.2.7. Create Data Model Rules
        - In Cortex AgentiX, select Settings → Configurations → Data Management → Data Model Rules
      - 3.11.2.8. Troubleshooting Data Model Rules
      - 3.11.2.9. Using data enrichment
      - 3.11.2.10. Data Model Rules notifications
      - 3.11.2.11. Monitor Data Model Rules activity
    - 3.11.3. Manage Event Forwarding
      - Under Settings → Configurations → Data Management → Event Forwarding, activate one or more of the following: Enable GB Event Forwarding
      - Under Settings → Configurations → Data Management → Event Forwarding, activate one or more of the following
  - 3.12. Dashboards and Reports
    - 3.12.1. About dashboards
      - 3.12.1.1. Command Center dashboards
        - 3.12.1.1.1. AgentiX Command Center
      - 3.12.1.2. Predefined dashboards
    - 3.12.2. Reports
      - 3.12.2.1. Report templates
      - 3.12.2.2. Run or schedule reports
        - Under Settings → Configurations → General → Notifications, click + Add Forwarding Configuration
    - 3.12.3. Build custom dashboards and reports
      - 3.12.3.1. Build a custom dashboard
      - 3.12.3.2. Manage your Widget Library
    - 3.12.4. Fine-tune dashboards and reports
      - 3.12.4.1. Create a custom widget using a script
        - 3.12.4.1.1. Script-based widget examples
      - 3.12.4.2. Create a text widget
      - 3.12.4.3. Create custom XQL widgets
        - 3.12.4.3.1. Configure filters and inputs for custom XQL widgets
      - 3.12.4.4. Configure dashboard drilldowns
        - 3.12.4.4.1. Variables in drilldowns
- 4. Investigation and Response
  - 4.1. Overview of cases
    - 4.1.1. What are cases?
    - 4.1.2. Resolving cases with AI
    - 4.1.3. Case lifecycle
    - 4.1.4. Case thresholds
    - 4.1.5. Case scope and impact
    - 4.1.6. Case and issue domains
  - 4.2. Case concepts
    - 4.2.1. Issues
    - 4.2.2. Case grouping
    - 4.2.3. Case scoring
    - 4.2.4. Case starring
      - You can manage all starring configurations under Case & Issues → Case Configuration → Starred Issues
    - 4.2.5. SLAs and tracking
  - 4.3. Analyze and resolve cases
    - 4.3.1. Review all cases
    - 4.3.2. Start case analysis
      - 4.3.2.1. Agentic Assistant- Case Investigation agent
    - 4.3.3. Establish case context
      - 4.3.3.1. AI-generated case summaries
        - Configurations → General → Server Settings → AI Configuration and enable the following settings
      - 4.3.3.2. Assess case severity and score
      - 4.3.3.3. Update case attributes
    - 4.3.4. Analyze case details
      - 4.3.4.1. Grouping graph
      - 4.3.4.2. Evidence
      - 4.3.4.3. Issue feed
      - 4.3.4.4. Associated assets and artifacts
      - 4.3.4.5. MITRE ATT&CK tactics and techniques
      - 4.3.4.6. Detailed View
    - 4.3.5. Resolve the case
      - 4.3.5.1. Resolution Center
      - 4.3.5.2. Collaborative notes and comments
      - 4.3.5.3. Resolve a case
      - 4.3.5.4. Resolution reasons for cases and issues
    - 4.3.6. Use Cortex Agentic Assistant chat in an investigation
      - Settings → Configurations → General → Server
    - 4.3.7. Create a case
      - To create a case manually, you must have View/Edit permission for Cases and Issues selected under Settings → Configurations → Access Management → Roles → Components → Cases & Issues
  - 4.4. Investigate issues
    - 4.4.1. Overview of the Issues page
    - 4.4.2. Issue card
    - 4.4.3. Link or unlink issues from a case
    - 4.4.4. Run an automation on an issue
    - 4.4.5. Use the War Room in an investigation
      - Investigation & Response → Automation → Playground
    - 4.4.6. Use the Work Plan in an investigation
    - 4.4.7. Manage synced tickets in issues
    - 4.4.8. Issue investigation actions
      - 4.4.8.1. Copy issues
      - 4.4.8.2. Investigate contributing events
      - 4.4.8.3. Export issue details to a file
      - 4.4.8.4. Exclude an issue
      - 4.4.8.5. Query case and issue data
      - 4.4.8.6. Run indicator extraction in the CLI
      - 4.4.8.7. Update issue fields
      - 4.4.8.8. Use issue timer field commands manually in the CLI
      - 4.4.8.9. Close an issue
  - 4.5. Investigate artifacts and assets
    - 4.5.1. Investigate an IP address
    - 4.5.2. Investigate a file and process hash
      - Settings → Configurations → Integrations → Threat Intelligence
- 5. Threat Intel Management
  - 5.1. Get started with Threat Intel Management
    - 5.1.1. What is Threat Intel Management?
    - 5.1.2. Threat Intel Management use cases
    - 5.1.3. Roles and responsibilities in Threat Intel Management
    - 5.1.4. Indicator concepts
    - 5.1.5. Indicator lifecycle
  - 5.2. Indicator configuration
    - 5.2.1. Customize indicator fields and types
      - 5.2.1.1. Create an indicator type
        - Settings → Configurations → Object Setup → Indicators → Types
        - 5.2.1.1.1. Indicator type profile
        - 5.2.1.1.2. File indicators
        - 5.2.1.1.3. Formatting scripts
        - 5.2.1.1.4. Enhancement scripts
        - 5.2.1.1.5. Reputation scripts
        - 5.2.1.1.6. Reputation commands
        - 5.2.1.1.7. Map custom indicator fields
      - 5.2.1.2. Create an indicator field
        - Settings → Configurations → Object Setup → Indicators → Fields → New Field
        - 5.2.1.2.1. Indicator field structure
        - 5.2.1.2.2. Indicator field trigger scripts
    - 5.2.2. Indicator classification and mapping
    - 5.2.3. Indicator extraction
      - 5.2.3.1. Set the indicator extraction mode for a playbook task
      - 5.2.3.2. Disable indicator extraction for scripts or integrations
    - 5.2.4. Configure indicator expiration
    - 5.2.5. Configure Threat Intelligence feed integrations
    - 5.2.6. Exclude indicators from enrichment
    - 5.2.7. Generate issues from indicator rules
      - Indicators should be present in the Threat Intelligence database (Threat Management → Threat Intelligence → Indicators) before creating detection rules
    - 5.2.8. Export indicators
  - 5.3. Indicator management
  - 5.4. Indicator investigation
    - 5.4.1. Indicator verdict
    - 5.4.2. Extract and enrich an indicator
    - 5.4.3. Expire an indicator
    - 5.4.4. Manage indicator relationships
    - 5.4.5. Delete and exclude indicators
- 6. Cortex AgentiX XQL
  - 6.1. Get started with XQL
    - 6.1.1. XQL language features
      - You submit XQL queries to Cortex AgentiX using the Investigation & Response → Search → Query Builder user interface
    - 6.1.2. XQL Language Structure
      - 6.1.2.1. Adding comments in queries
    - 6.1.3. Supported operators
    - 6.1.4. Datasets and presets
    - 6.1.5. About examples
      - Investigation & Response → Search → Query Builder → XQL → Query Library
    - 6.1.6. JSON functions
    - 6.1.7. How to filter for empty values in the results table
    - 6.1.8. Understanding string manipulation in XQL
  - 6.2. Build XQL queries
    - 6.2.1. About the Query Builder
    - 6.2.2. How to build XQL queries
      - 6.2.2.1. Get started with XQL queries
      - 6.2.2.2. Useful XQL user interface features
      - 6.2.2.3. XQL Query best practices
      - 6.2.2.4. Expected results when querying fields
      - 6.2.2.5. Create XQL query
      - 6.2.2.6. Review XQL query results
      - 6.2.2.7. Translate to XQL
      - 6.2.2.8. Graph query results
    - 6.2.3. Query Builder templates
      - 6.2.3.1. Get started with Query Builder templates
      - 6.2.3.2. Considerations for using Query Builder templates
      - 6.2.3.3. Create a query from a template
      - 6.2.3.4. Run a free text query
      - 6.2.3.5. Query Builder template examples
        - Investigation & Response → Search → Query Builder
    - 6.2.4. Overview of the Query Center
      - 6.2.4.1. Edit and run queries in Query Center
        - Investigation & Response → Search → Query Center → Query History
        - 6.2.4.1.1. Query Center reference information
    - 6.2.5. Manage scheduled queries
      - Investigation & Response → Search → Scheduled Queries
      - 6.2.5.1. Scheduled Queries reference information
    - 6.2.6. Manage your personal query library
      - From the Query Builder Select Investigation & Response → Search → Query Builder → XQL
      - Investigation & Response → Search → Query Builder → XQL
      - Investigation & Response → Search → Query Center
    - 6.2.7. Legacy Query Builder
      - 6.2.7.1. Create authentication query
      - 6.2.7.2. Create event log query
      - 6.2.7.3. Create file query
      - 6.2.7.4. Create image load query
      - 6.2.7.5. Create network connections query
      - 6.2.7.6. Create network query
      - 6.2.7.7. Create process query
      - 6.2.7.8. Create registry query
      - 6.2.7.9. Query across all entities
  - 6.3. Stages
  - 6.4. Functions
- 7. Troubleshoot
  - 7.1. About health issues
    - 7.1.1. Monitor data ingestion health
    - 7.1.2. Monitor correlation rules
    - 7.1.3. Investigate and resolve health issues
  - 7.2. Log forwarding
    - 7.2.1. Forward logs and data from Cortex AgentiX to external services
      - 7.2.1.1. Configure external applications for forwarding
        - 7.2.1.1.1. Integrate a syslog receiver
        - 7.2.1.1.2. Integrate Slack for outbound notifications
      - 7.2.1.2. Configure notification forwarding
      - 7.2.1.3. Monitor administrative activity
    - 7.2.2. Data and log notification formats
      - 7.2.2.1. Issue notification format
      - 7.2.2.2. Management Audit log notification format
  - 7.3. In-product support case creation
- 8. Reference
  - 8.1. Cortex AgentiX API
    - Settings → Configurations → Integrations → API Keys
  - 8.2. XDM fields for mapping authentication events
  - 8.3. Fair Usage policy for Cortex AgentiX