Cortex XSIAM

Documentation -

Detailed

1. Learn about Cortex XSIAM 

1.1. Get started with Cortex XSIAM  1.1.1. Cortex XSIAM architecture  📝

🟢note

If you plan to stream data from a Strata
Logging Service instance, it must reside in the
same region as your Cortex XSIAM tenant.

1.2. Agentic AI in Cortex XSIAM  1.2.1. Cortex Agentic Assistant 

📝

🟢note

By default, you have access to the Cortex
Assistant, which includes a natural language
interface for entity investigation and provides a
list of recommended responses such as running
a playbook, performing a scan, or collecting
support files.
If you enable the Cortex Agentic Assistant, it
replaces the Cortex Assistant interface entirely.
For more...

💡

🔵tip

The system Help Center Agent provides fast
access to documentation. You can ask natural
language questions, such as "How do I create a
dashboard?" or "Where can I review my data
retention policies?" and the agent retrieves
concise, relevant information from the official
documentation site.

🧭

➡️n…

Settings → Configurations → General → Server
Settings → Agentic Assistant

1.2.1.1. Agentic Assistant use cases 

1.2.1.2. Compare Agentic Assistant with Cortex
Assistant 

1.2.1.3. Agentic Assistant security 

1.3. Cortex XSIAM product licenses 

📝

🟢note

You can upgrade your license by purchasing
add-ons or moving to a different XSIAM license.

📝

🟢note

Full code security scanning requires a separate
add-on.

📝

🟢note

Existing users who have a Cortex XSIAM
Enterprise Plus license retain all Cortex XSIAM
Enterprise features, with cloud agent features.
You can deploy agents for runtime detection on
cloud sources, such as Kubernetes nodes,
OpenShift clusters, or cloud VMs, whether in
the cloud or on-premises. If you want the full
cloud posture security bundle (Cloud...

1.3.1. Data retention 

📝

🟢note

Case data is retained according to the Last
Updated date.
Issue data is retained according to the
Observation Time. Data collected within these
dates is kept and displayed for 186 days. To
ensure the accuracy of issues, Cortex XSIAM
provides a grace period of up to 31 days for
issues displayed in the Issues View, Issues table,
and Cases View.

📝

🟢note

Requires the Forensics add-on.

1.3.2. Data storage lifecycle 

💡

🔵tip

If you want your cold storage data to align with
the hot storage data, you must ensure to
purchase your cold storage license at the same
time as your regular Cortex XSIAM license.

💡

🔵tip

You can view details about your Cortex XSIAM
licenses by selecting Settings → Cortex XSIAM
License.

1.3.3. License allocation 

📝

🟢note

For Cortex XSIAM Enterprise Plus licenses, if an
endpoint requires a Cortex XDR per Endpoint
license, and you've exceeded the number of
available Cortex XDR per Endpoint licenses,
one of your surplus Cloud per Host licenses is
automatically consumed as a Cortex XDR per
Endpoint license for the endpoint. After utilizing
all available XDR per Endpoint...

📝

🟢note

It can take up to an hour for Cortex XSIAM to
display revived assets.

1.3.4. License expiration 

1.3.5. Upgrade your tenant 

1.4. In-product support case creation 

📝

🟢note

When opening a support case through the
Customer Support Portal, you need to manually
select Cortex XSIAM as the product. While
there may be discrepancies between the
categories in this wizard and the Customer
Support Portal process, that's because this
wizard is designed specifically to focus on
options relevant to Cortex XSIAM.

📝

🟢note

Selecting an endpoint from the endpoint table
and retrieving TSF requires full Retrieve
Endpoint Data permissions under Endpoint
Administration.

📝

🟢note

Console recordings cannot exceed 10 minutes.
The current recording time is displayed at the
top of the window.

1.5. Supported web browsers 

1.6. Use the interface 

📝

🟢note

Each SAML login session is valid for 8 hours.
Some menu items only appear if you have the
relevant license.

📝

🟢note

CMD fields have a 128-character limit. Shorten
longer query strings to 127 characters and add
an asterisk (*).

📝

🟢note

Deleting a shared view removes it for all users.

1.7. Manage API keys 

📝

🟢note

Visibility of Security domain Issues that refer to
assets with agents is controlled by the
Endpoints scoping configuration.

📝

🟢note

When defining a filter for row-level scoping on
raw datasets, queries based on the Cortex Data
Model (XDM) are not supported. XDM queries
return specific rows only when All rows are
accessible is selected and no filter is defined in
the Datasets Rows scoping area. Otherwise, no
rows are returned.

👀

🟠i…

Before configuring, ensure that you review
Understand scoping in the Manage user scope
section.

👀

🟠i…

For optimal performance, we recommend using
a single field in the filter definition and simple
comparison operators.

👀

🟠i…

By default, Enable Scope Based Access
Control is disabled in Settings →
Configurations → General → Server Settings,
and granular scoping is not enforced. Before
enabling SBAC, we recommend that an
administrator or a user with Access
Management permissions first ensures that the
users, user groups, and API Keys defined in
Cortex XSIAM are granted...

👀

🟠i…

You will not be able to view the API key again
after you complete this step. Ensure that you
copy the API key before closing the notification.

2. Onboard Cortex XSIAM 

2.1. Plan and prepare 

📝

🟢note

This topic does not include any specific Cloud
Security requirements. If you have a Cortex
XSIAM Premium license or another XSIAM
license with Cloud Posture Security/Runtime
addons, you should also plan and prepare
Cloud Posture Security and Runtime during or
after completing this stage. For more
information about Cloud Security onboarding,
see Ingest...

📝

🟢note

The XDR agent is included with the Cortex
XSIAM Premium and Enterprise licenses and any
other XSIAM license with the Enterprise
Runtime Security (XDR) add-on.

2.1.1. Plan your agent deployment 

2.2. Deployment steps 

2.2.1. Cortex XSIAM onboarding checklist 

📝

🟢note

This checklist does not include any specific
Cloud Security requirements. If you have a
Cortex XSIAM Premium license or another
XSIAM license with Cloud Posture
Security/Runtime, you should also onboard
Cloud Posture Security and Runtime during or
after completing this stage. For more
information about Cloud Security onboarding,
see Ingest cloud assets.

📝

🟢note

You need EDR or network logs from at least 30
endpoints over a minimum of 2 weeks, or Cloud
audit logs over a minimum of 2 weeks.

📝

🟢note

The Cloud Identity Engine must be set up.

2.2.2. Activate Cortex XSIAM 

☑️

🟣pr…

The Cortex XSIAM activation email.
A Customer Support Portal (CSP) account.
You need to set up your CSP account. For more
information, see How to Create Your CSP User
Account.
When you create a CSP account, you can set
up two-factor authentication (2FA) to log into
the CSP by using an Email, Okta Verify, or
Google Authenticator (non-FedRAMP
accounts)....

📝

🟢note

When you activate, a production tenant is first
activated. After activation, you can set up a
development tenant (subject to your license).

📝

🟢note

Activation can take about an hour and does not
require you to remain on the activation page.
Cortex XSIAM sends a notification to your
email when the process is complete.

📝

🟢note

If you want to change your tenant's name, the
subdomain, or activate a development tenant
(subject to license), on the right-hand side, click
the ellipsis.
You can only change the subdomain once, and
it cannot be undone.
After deleting the subdomain, you can reuse it
after 7 days.

2.2.2.1. Bring your own keys 

☑️

🟣pr…

Access to BYOK (Bring Your Own Keys)
functionality is restricted to tenants that were
initially activated with BYOK.

☑️

🟣pr…

To disable your encryption keys and deactivate
a tenant, you must have an Account Admin role.

📝

🟢note

The new keys you import will serve as primary
encryption keys for newly generated data.

📝

🟢note

At any stage, you can select Continue Later to
pause the process. To resume the process, in
the Cortex gateway, select Continue Setup next
to the tenant, and follow the wizard
instructions from the point you left off, as
detailed below. If you don't use either of your
wrapping keys within three days, they expire
and you'll have to restart the process.

📝

🟢note

BYOK requires a 32-byte, symmetric,
unencoded key in binary format.

⚠️

🟡c…

Disabling all encryption keys and deactivating
the tenant renders the tenant inaccessible and
non-operational.
Disabling the keys affects the communication
with the agents, may prevent the agents from
receiving updates to policies, configurations,
and crucial information, and may result in loss
of data.
To secure your tenant data and to prevent...

2.2.2.2. Cortex XSIAM supported regions 

2.2.2.3. Enable access to required PANW
resources



📝

🟢note

<tenant-name> refers to the selected
subdomain of your Cortex XSIAM tenant, and
<region> is the region in which your tenant is
deployed. For more information, see Cortex
XSIAM supported regions.

📝

🟢note

Refer to Regional Docker registry mapping for
your specific tenant location and
corresponding Docker registry URL.

🧭

➡️n…

SSL decryption: If you use SSL decryption and
experience difficulty connecting the Cortex
XDR agent to the server, we recommend that
you add the FQDNs required for access to your
SSL Decryption Exclusion list in Device →
Certificate Management → SSL Decryption
Exclusion

2.2.3. Set up users and roles 

📝

🟢note

Some features are license-dependent.
Accordingly, users may not see a specific
feature if the feature is not supported by the
license type or if they do not have access
based on their assigned role or scope.

📝

🟢note

The user who activated the Cortex product is
assigned the Account Admin role. You cannot
create additional Account Admin roles in the
Cortex XSIAM tenant. If you do not want the
user to have Account Admin permission, you
must remove the Account Admin role in Cortex
Gateway.

2.2.3.1. User group management 

📝

🟢note

You can create user groups in the tenant or
Cortex Gateway. User groups created in Cortex
Gateway cannot be mapped to SAML groups.
Only user groups created in the tenant support
SAML group mapping and scoring. We
recommend creating user groups in the Cortex
tenant because:
User groups are available for all tenants, and
you may want different user...

📝

🟢note

If users have been created in the CSP, but you
want them to access the tenant through SSO
only, skip this field and add only SAML group
mapping after SSO is set up, otherwise, users
can access the tenant through both the CSP
and SSO.
If you have not yet created any users, skip this
field and add them later. See Set up
authentication .

📝

🟢note

When using Azure AD for SSO, the SAML group
mapping needs to be provided using the group
object ID (GUID) and not the group name.

👀

🟠i…

By default, Enable Scope Based Access
Control is disabled in Settings →
Configurations → General → Server Settings,
and granular scoping is not enforced. Before
enabling SBAC, we recommend that an
administrator or a user with Access
Management permissions first ensures that the
users, user groups, and API Keys defined in
Cortex XSIAM are granted...

2.2.3.2. Assign user roles and groups 

📝

🟢note

If an existing user in the Cortex Gateway no
longer has a role or a user group assigned, the
user is revoked. Any roles, user groups, or
egress configurations created by that user are
shown as created by Revoked user instead of
the user's email address.

📝

🟢note

Visibility of Security domain Issues that refer to
assets with agents is controlled by the
Endpoints scoping configuration.

📝

🟢note

When defining a filter for row-level scoping on
raw datasets, queries based on the Cortex Data
Model (XDM) are not supported. XDM queries
return specific rows only when All rows are
accessible is selected and no filter is defined in
the Datasets Rows scoping area. Otherwise, no
rows are returned.

👀

🟠i…

Setting Cortex Query Language (XQL) dataset
access permissions for a user role can only be
performed from Cortex XSIAM Access
Management. For more information, see
Manage user roles.

👀

🟠i…

Before configuring, ensure that you review
Understand scoping in the Manage user scope
section.

👀

🟠i…

For optimal performance, we recommend using
a single field in the filter definition and simple
comparison operators.

👀

🟠i…

By default, Enable Scope Based Access
Control is disabled in Settings →
Configurations → General → Server Settings,
and granular scoping is not enforced. Before
enabling SBAC, we recommend that an
administrator or a user with Access
Management permissions first ensures that the
users, user groups, and API Keys defined in
Cortex XSIAM are granted...

💡

🔵tip

To apply the same settings to multiple users,
select them, and then right-click and select Edit
Users Permissions.

2.2.4. Set up authentication 

💡

🔵tip

You should have at least one user in the
Customer Support Portal for backup, in case of
any authentication issues with your IdP provider.

2.2.4.1. Authenticate users through the
Customer Support Portal 

📝

🟢note

You must be assigned the Super User role in the
Customer Support Portal to add users in the
Customer Support Portal.
The first Super User who logs into Cortex
Gateway is automatically assigned the Account
Admin role and has access to the tenant. The
user who activates the Cortex XSIAM tenant
will also be assigned the Account Admin role (if
there is no...

📝

🟢note

After users are added to the Customer Support
Portal and they accept the invitation, you can
manage them in Cortex Gateway or the Cortex
XSIAM tenant.

2.2.4.2. Authenticate users using SSO 

📝

🟢note

To set up SSO authentication in the tenant, you
must be assigned an Instance Administrator or
Account Admin role.
SAML 2.0 users must log in to Cortex XSIAM
using the FQDN (full URL) of the tenant. To
allow login directly from the IdP to , you must
set the relay state on the IdP to the FQDN of
the tenant.
If you have multiple tenants, you must set up...

📝

🟢note

The first SSO cannot be deleted, it can only be
deactivated by toggling SSO Enabled to off.
The Domain parameter is predefined for the
first SSO.
If you add additional SSO providers, you must
provide the email Domain in the SSO Integration
settings for all providers except the first.
Cortex XSIAM uses this domain to determine to
which identity provider...

📝

🟢note

Cortex XSIAM requires the IdP to send the
group membership as part of the SAML token.
Some IdPs send values in a format that include
a comma, which is not compatible with Cortex
XSIAM. In that case, you must configure your
IdP to send a single value without a comma for
each group membership. For example, if your
IdP sends the Group DN (a...

2.2.4.3. Set up Okta as the Identity Provider
Using SAML 2.0 

📝

🟢note

When using SAML 2.0, users are required to
authenticate by logging in directly at the tenant
URL. They cannot log in via Cortex Gateway.

🧭

➡️n…

Settings → Configurations → Access
Management → Authentication Settings

Settings → Configurations → Access
Management → User Groups

2.2.4.4. Set up Azure AD as the Identity Provider
Using SAML 2.0 

📝

🟢note

The default attributes shown on the main single
sign-on page in Azure AD are not the values
you need. You must click Edit next to Attributes
and Claims to view and copy the actual values.

📝

🟢note

The attribute claim name must exactly match
the value sent by your IdP. In some cases, this
may be the full attribute name/namespace,
depending on the configuration of our IdP

📝

🟢note

When using SAML 2.0, users are required to
authenticate by logging in directly at the tenant
URL. They cannot log in via Cortex Gateway.

👀

🟠i…

When copying the Single Sign-On URL value,
remove idp/saml and leave the trailing /.
For example, if the Single Sign-On URL is
https://clientname.panproduct.region.paloaltone
tworks.com/idp/saml, just copy
https://clientname.panproduct.region.paloaltone
tworks.com/.

2.2.5. Configure content 

2.2.6. Set up Cloud Identity Engine 

📝

🟢note

The Activate risk signal sharing to CIE checkbox
is available only after the second step is
completed.

🧭

➡️n…

Settings → Configuration → Integrations →
Cloud Identity Engine

2.2.7. Install Cortex XDR agents 

2.2.7.1. Create an agent installation package 

📝

🟢note

The profile will be applied if the security policy
cannot be retrieved in real-time.

📝

🟢note

The Cortex serverless library must be imported
after other libraries to activate the hooks that
enable auditing.

2.2.7.2. Deploy agent installation packages 

2.2.7.3. Endpoint data collection 

📝

🟢note

For specific files only and only if the file was
written.

👀

🟠i…

Registry key is collected as a real key name, and
not as a symbolic link.
Instead of
HKEY_LOCAL_MACHINE\System\CurrentControl
Set, which is a symbolic link,
KEY_LOCAL_MACHINE\System\ControlSet001
will be collected.
Instead of HKEY_CURRENT_USER, HKEY_USERS\
<SID> will be collected, where SID is a SID of
the current user.

2.2.7.4. Configure global agent settings 

📝

🟢note

Disabling this capability takes immediate effect
on new hashes, fresh agent installations, and
existing security policies. It could take up to a
week to take effect on existing agents in your
environment pending agent caching.

📝

🟢note

If you have any Cortex XSIAM filters, starring
policies, exclusion policies, scoring rules, log
forwarding queries, or automation rules
configured for XSOAR/3rd party SIEM, we
advise you to update those to support the
changes before activating the feature. For
example, change the query to include the
previous description that is still available in the...

2.2.7.5. Define endpoint groups 

📝

🟢note

Configuration based on user granular policy is
optimized for VDI and session-persistent
environments; it is not recommended for
decentralized or traditional endpoint
architectures.

📝

🟢note

Disconnecting Cloud Identity Engine in your
Cortex XSIAM deployment can affect existing
endpoint groups and policy rules based on
Active Directory properties.

2.2.7.6. Manage endpoint profiles 

2.2.7.7. Guidelines for keeping Cortex XDR
agents and content updated 

📝

🟢note

The Cortex XDR agent keeps the name of the
original installation package after every
upgrade.

📝

🟢note

Custom dashboards that include upgrade
status widgets, and the All Endpoints page
display upgrade status.
During the upgrade process, the endpoint
operating system might request a reboot.
However, you do not have to perform the
reboot for the Cortex XDR agent upgrade
process to complete it successfully.
After you upgrade on an endpoint with Cortex...

📝

🟢note

These profiles can be configured on one or
more endpoints, static/dynamic groups, tags, IP
ranges, endpoint names, or other parameters
that allow the creation of logical endpoint
groups. See how to define endpoint group.

📝

🟢note

These profiles can be configured on one or
more endpoints, static/dynamic groups, tags, IP
ranges, endpoint names, or other parameters
that allow the creation of logical endpoint
groups.

👀

🟠i…

When planning Cortex XDR agent upgrades
and content updates, consult with the
appropriate stakeholders and teams and follow
the change management strategy in your
organization.

⚠️

🟡c…

Before enabling Auto-Update for Cortex XDR
agents, make sure to consult with all relevant
stakeholders in your organization.

2.2.8. Cortex XSIAM - Analytics 

☑️

🟣pr…

Before Cortex XSIAM - Analytics can start to
analyze your endpoint data, perform the
following steps:
Configure Cortex XSIAM network parameters
to monitor your internal networks.
Enable the Analytics Engine.
Make sure Cloud Identity Engine is set up.
Enable Identity Analytics.

2.2.8.1. Configure Cortex XSIAM network
parameters



📝

🟢note

You can add a range that is fully contained in
an existing range, however, you cannot add a
new range that partially intersects with another
range.

🧭

➡️n…

Inventory → Assets → Network Configuration
→ Internal Domain Suffixes

2.2.8.2. Enable the Analytics Engine and Identity
Analytics 

☑️

🟣pr…

Analytics Engine
To create a baseline for enabling analytics,
Cortex XSIAM requires a minimum of one of the
following data sets:
EDR or Network logs from at least 30 endpoints
over a minimum of 2 weeks
Cloud audit logs over a minimum of 5 days
Identity Analytics
Cortex XSIAM - Analytics must be activated.
Cloud Identity Engine must be set up. For more...

🧭

➡️n…

Settings → Configurations → Cortex XSIAM -
Analytics

2.3. Post-deployment 

2.3.1. Post-deployment checklist 

📝

🟢note

This checklist includes post-deployment for the
Cortex XSIAM environment, but does not
include any specific Cloud Security
requirements. See the relevant Cloud Security
sections for specific post-deployment steps.

📝

🟢note

If you set up Cloud Identity Engine, you can
also leverage your Active Directory user, group,
and computer details in endpoint groups.

📝

🟢note

You can also use the Broker VM for high
availability.

2.3.2. Perform health checks 

2.3.2.1. Monitor agent operational status in
Cortex XSIAM 

📝

🟢note

Any of the listed items could lead to a partially
protected state. Refer to the Cortex XSIAM
management console for specific reasons for
the state.

⚠️

🟡c…

Status can have the following implications on
the endpoint:
*(Status): The exploit protection module is not
running.
**(Status):
XDR data collection is not running
Behavioral threat protection is not running
Anti-malware flow is asynchronous
Local privilege escalation protection is
asynchronous
**(Status):
XDR data collection is not...

2.3.3. Cortex Marketplace 

🧭

➡️n…

Settings → Configurations → Marketplace) or
at Cortex Developer Docs Marketplace

2.3.3.1. Content packs  📝

🟢note

Cortex XSIAM includes a built-in default mail
sender. You also have the option of installing a
different mail sender content pack, such as
Microsoft Exchange Online.

2.3.3.2. Install content packs 

📝

🟢note

Currently, not all content packs are supported
in the Data Sources & Integrations page. For
example, content packs with several
integrations are not yet supported.

📝

🟢note

Content packs are also automatically installed
when you adopt playbooks and configure tasks.

🧭

➡️n…

Settings → Configurations → Marketplace →
Browse and locate the content pack you want
to install

2.3.4. Manage user roles and access
management 

☑️

🟣pr…

Managing users, roles, scopes, user groups,
authentication settings in Cortex XSIAM Access
Management requires View/Edit RBAC
permissions for Access Management (under
Configurations). Account Admin and Instance
Administrator roles are granted this permission
by default. For more information, see
Predefined user roles in Set up users and roles.

📝

🟢note

For more information on assigning user roles
when generating an API key, see Manage API
keys.

📝

🟢note

Some features are license-dependent.
Accordingly, users may not see a specific
feature if the feature is not supported by the
license type or if they do not have access
based on their assigned role or scope.

📝

🟢note

For features where scoping is not applicable,
Role-Based Access Control (RBAC) is used and
can be configured when managing user roles.
For more information, see Manage user roles.

2.3.4.1. Manage user roles 

☑️

🟣pr…

Managing user roles in Cortex XSIAM Access
Management requires View/Edit RBAC
permissions for Access Management (under
Configurations). Account Admin and Instance
Administrator roles are granted this permission
by default. For more information, see
Predefined user roles in Set up users and roles.

🧭

➡️n…

Settings → Configurations → Access
Management → Roles

2.3.4.2. Manage user access 

☑️

🟣pr…

Managing users, roles, scopes, user groups,
authentication settings in Cortex XSIAM Access
Management requires View/Edit RBAC
permissions for Access Management (under
Configurations). Account Admin and Instance
Administrator roles are granted this permission
by default. For more information, see
Predefined user roles in Set up users and roles.

📝

🟢note

You can only reduce the permissions of an
Account Admin user via Cortex Gateway.

📝

🟢note

User permissions for components and datasets
are based on the access permissions set in the
user role. For more information on editing these
user role permissions, see Manage user roles.

📝

🟢note

Visibility of Security domain Issues that refer to
assets with agents is controlled by the
Endpoints scoping configuration.

📝

🟢note

When defining a filter for row-level scoping on
raw datasets, queries based on the Cortex Data
Model (XDM) are not supported. XDM queries
return specific rows only when All rows are
accessible is selected and no filter is defined in
the Datasets Rows scoping area. Otherwise, no
rows are returned.

👀

🟠i…

Before configuring, ensure that you review
Understand scoping in the Manage user scope
section.

👀

🟠i…

For optimal performance, we recommend using
a single field in the filter definition and simple
comparison operators.

👀

🟠i…

By default, Enable Scope Based Access
Control is disabled in Settings →
Configurations → General → Server Settings,
and granular scoping is not enforced. Before
enabling SBAC, we recommend that an
administrator or a user with Access
Management permissions first ensures that the
users, user groups, and API Keys defined in
Cortex XSIAM are granted...

💡

🔵tip

To apply the same settings to multiple users,
select them, and then right-click and select Edit
User Permissions.

💡

🔵tip

To apply the same settings to multiple users,
select them, and then right-click and select Edit
User Permissions.

💡

🔵tip

To apply the same settings to multiple users,
select them, and then right-click and select Edit
User Permissions.

🧭

➡️n…

Settings → Configurations → Access
Management → Users

2.3.4.2.1. User access reference information 

2.3.4.3. Manage user scope 

☑️

🟣pr…

Configuring user scopes in Cortex XSIAM
Access Management requires View/Edit RBAC
permissions for Access Management (under
Configurations). Account Admin and Instance
Administrator roles are granted this permission
by default. For more information, see
Predefined user roles in Set up users and roles.
By default, Enable Scope Based Access
Control is...

📝

🟢note

This configuration can impact the visibility of
the related Security domain in the Cases and
Issues scope area, but with not affect asset
visibility.

📝

🟢note

Whenever a user's SBAC permissions are
changed, Cortex XSIAM logs this event in the
audit logs (Settings → Management Audit
Logs). These monitored activity events are
found on the Management Audit Logs table by
filtering the Type column by Permissions and
Subtype column by Scope Edit.

📝

🟢note

XQL-based dashboard widgets may require a
few hours to initially reflect changes to the list
or definitions of asset groups used for scoping.
To view the most current data immediately,
refresh the dashboard or its XQL widgets.

📝

🟢note

For Cases and Issues domains, a workaround is
to create a Dataset View for each required
combination of domains, and allow the relevant
entity access only to this Dataset View, not to
the underlying cases and issues datasets.

📝

🟢note

This feature is included with a Cortex XSIAM
Premium, Enterprise, and NG-SIEM licenses.

📝

🟢note

Make sure to assign the required default
granular scoping for users. This depends on the
structure and divisions within your organization
and the particular purpose of each
organizational unit to which scoped users
belong.

📝

🟢note

Visibility of Security domain Issues that refer to
assets with agents is controlled by the
Endpoints scoping configuration.

📝

🟢note

When defining a filter for row-level scoping on
raw datasets, queries based on the Cortex Data
Model (XDM) are not supported. XDM queries
return specific rows only when All rows are
accessible is selected and no filter is defined in
the Datasets Rows scoping area. Otherwise, no
rows are returned.

👀

🟠i…

Some areas and features in Cortex XSIAM do
not respect SBAC. In these cases, use RBAC
permissions to restrict access.

👀

🟠i…

Action Required: Recent security enhancements
enforce stricter default permissions for cases
and issues that lack specific asset or endpoint
references. This notice explains how to include
access to these items if your users' visibility has
been impacted.

👀

🟠i…

Before configuring, ensure that you review the
Understand scoping section.

👀

🟠i…

For optimal performance, we recommend using
a single field in the filter definition and simple
comparison operators.

2.3.4.4. Manage access to objects  2.3.4.4.1. Manage access to custom dashboards 

☑️

🟣pr…

Configure tenant-level settings: An
administrator must first establish the sharing
framework under Settings → Configurations →
Access Management → Objects.
The configuration of these settings defines the
authorized sharing workflows for custom
dashboards:
Enable "Owners can Share objects they
created": Grants owners the ability to share...

📝

🟢note

If you're designated as an Editor, you can
always duplicate the widget and make your
changes on the copy.

📝

🟢note

Only Account Administrators and Instance
Administrators have the authority to change the
owner of an object.

2.3.5. Dashboards and reports 

2.3.6. Configure server settings 

📝

🟢note

Keyboard shortcuts, timezone, and timestamp
format are not set universally and only apply to
the user who sets them.

📝

🟢note

The Cortex Agentic Assistant and AI case
summarization are currently available for users
in limited regions. For more information, see
Cortex Agentic Assistant.

📝

🟢note

If the Password Protection (for downloaded
files) setting under Settings → Configuration →
General → Server Settings is enabled, enter the
password 'suspicious' to download the file.

📝

🟢note

Requires the TIM add-on.
By default, system-wide automatic indicator
extraction and enrichment is disabled. However,
if you migrated from Cortex XSIAM 2.x to
Cortex XSIAM 3.x, system-wide automatic
indicator extraction and enrichment is enabled.

📝

🟢note

Requires an MSSP License and RBAC
permissions to Cases & Issues and Investigation
& Response → Automation.
This setting is available for the parent tenant
only.

🧭

➡️n…

Settings → Configurations → General → Server
Settings

2.3.7. Configure security settings  🧭

➡️n…

Settings → Configurations → General →
Security Settings

2.3.8. Data and log forwarding 

2.3.8.1. Forward logs and data from Cortex
XSIAM to external services 

🔒

🟣c…

Requires an XDR Agent.

2.3.8.1.1. Configure external applications for
forwarding 

📝

🟢note

No prior configuration is required to send data
or logs to an email distribution list.
Only cases and issues can be forwarded to
Slack, Amazon S3, Amazon SQS, Splunk, and
Webhook.
To forward data to Amazon SQS, the following
permissions are required:
sqs:GetQueueAttributes, sqs:ListQueues,
sqs:SendMessage, sqs:SendMessageBatch,
tag:GetResources, and...

📝

🟢note

Only a user with Account Admin or Instance
Admin permissions can configure egress. For
more information, see Egress
configurations.Egress configurations

📝

🟢note

For Amazon SQS or Amazon S3, you need to
provide the queue/bucket name. For Webhook
or Splunk, you need to provide the domain,
including any subdomain. Note that the path
does not include HTTP or HTTPS.

📝

🟢note

You can also configure external applications
when you create a new forwarding
configuration. After defining the configuration
and setting the scope, you can Add Application
and follow the instructions below for any of
these destinations.

📝

🟢note

If egress has not been configured in the Cortex
Gateway, verification will fail and a message
will display that the endpoint does not match
any approved routes.

📝

🟢note

If egress has not been configured in the Cortex
Gateway, verification will fail and a message
will display that no approved routes were found.

📝

🟢note

If egress has not been configured in the Cortex
Gateway, verification will fail and a message
will display that the endpoint does not match
any approved routes.

📝

🟢note

If egress has not been configured in the Cortex
Gateway, verification will fail and a message
will display that the endpoint does not match
any approved routes.

2.3.8.1.1.1. Integrate a syslog receiver  📝

🟢note

Up to TLS 1.3 is supported.
Verify the self-signed CA includes your public
key.

2.3.8.1.1.2. Integrate Slack for outbound
notifications  📝
🟢note

You are directed to the Slack browser to install
Cortex XSIAM. You can only use this link to
install Cortex XSIAM on Slack. Attempting to
install from Slack Marketplace will redirect you
to Cortex XSIAM documentation.

2.3.8.1.2. Configure notification forwarding 

☑️

🟣pr…

Before you can select an external service for
notification forwarding, you must integrate the
external service with Cortex XSIAM. For more
information, see Configure external
applications for forwarding. No prior
configuration is required to send data to an
email distribution list.

📝

🟢note

Forwarding destinations: Only issues and cases
can be forwarded to Slack, Splunk, Amazon
SQS, Amazon S3, or Webhook.
Notification forwarding by domain: To
configure notification forwarding for issues by
domain, select Issues and filter the Issues table
by Issue Domain.
Alert vs. issue format:By default, new
configurations use the issue format, but you...

📝

🟢note

Not all data and log types can be sent to all
external services. For more information, see
Forward logs and data from Cortex XSIAM to
external services.Forward logs and data from
Cortex XSIAM to external services

📝

🟢note

The Grouping Timeframe defines the time
frame, in minutes, of how often Cortex XSIAM
sends notifications. Every 20 issues or 20 events
aggregated within this time frame are sent
together in one notification, sorted according
to severity. To send a notification when one
issue or event is generated, set the time frame
to 0.

2.3.8.1.3. Monitor administrative activity 

2.3.8.2. Data and log notification formats 

📝

🟢note

Issues can be forwarded to email, syslog
servers, and Slack in the alert format, if you
prefer. The alert format can be selected when
you configure your forwarding notification.

2.3.8.2.1. Management audit log messages 

2.3.8.2.2. Issue notification format 

2.3.8.2.3. Agent Audit log notification format 

2.3.8.2.4. Management Audit log notification
format 

2.3.8.2.5. Log format for IOC and BIOC issues 

2.3.8.2.6. Analytics log format 

3. Configure Cortex XSIAM 

3.1. Data management 

3.1.1. Configure Cortex Data Lake tier 

🔒

🟣c…

The Cortex Data Lake tier is only available with
an active Cortex XSIAM NG SIEM, Cortex
XSIAM Enterprise, or Cortex XSIAM Premium
license.

☑️

🟣pr…

The Cortex Data Lake tier require View/Edit
RBAC permissions for Data Management (under
Configurations → Data Management), the same
permissions used for Dataset Management,
ingestion rules, parsing rules, data model rules,
and event forwarding.

📝

🟢note

Currently, specific data sources receive these
capabilities temporarily; yet, be aware that
these will be completely removed from the
Cortex Data Lake tier in a future update.

3.1.2. Broker VM 

3.1.2.1. What is the Broker VM?  📝

🟢note

The Broker VM is a closed, hardened appliance.
To maintain its security integrity and
performance standards, third-party agents
cannot be installed on the Broker VM.

3.1.2.2. Set up and configure Broker VM 

📝

🟢note

The Broker VM comes with a 512 GB disk.
Therefore, deploy the Broker VM with thin
provisioning, meaning the hard disk can grow up
to 512 GB but will do so only if needed.

📝

🟢note

When DHCP is not enabled in your network and
there isn't an IP address for your Broker VM,
configure the Broker VM with a static IP using
the serial console menu.

📝

🟢note

When configuring a Local Agent Settings
applet with installer and content caching, you
need to configure an SSL certificate for the
Broker VM as explained in the task below. For
more information on specific requirements for
the Local Agent Settings applet, see Activate
Local Agent Settings.
Keep in mind that several Broker VM applets,
such as the...

📝

🟢note

When a Broker VM is disconnected for more
than 30 days, it will have to go through a re-
registration process.

📝

🟢note

When DHCP is not enabled in your network and
there isn't an IP address for your Broker VM,
configure the Broker VM with a static IP using
the serial console menu.

📝

🟢note

You can configure another Broker VM as a
proxy server for this Broker VM by selecting the
HTTP type. When selecting HTTP to route
Broker VM communication, you need to add the
IP Address and Port number (set when
activating the Agent Proxy) for another Broker
VM registered in your tenant. This designates
the other Broker VM as a proxy for this Broker
VM.

📝

🟢note

The Palo Alto Networks Broker VM supports
only strong cipher SHA256-based certificates.
MD5/SHA1-based certificates are not
supported.

📝

🟢note

If adding a CA certificate to the Broker VM is
not possible, ensure that you've added the
Broker Service FQDNs to the SSL Decryption
Exclusion list on your firewalls. See Enable
Access to Cortex XDR.
If you need to enable legacy SSL renegotiation,
use the Broker VM Serial console.

📝

🟢note

If you need to enable legacy SSL renegotiation,
use the Broker VM Serial console.

👀

🟠i…

There can be instances in which the Broker VM
requires up to 50% of the incoming bandwidth
as outgoing. Such instances can be, network
instability between the Broker VM and Cortex
XSIAM, or data that is being collected, but not
well compressed.

👀

🟠i…

The internal network for the Broker VM must be
unique and reserved. Other devices should not
use the same IP as the Broker VM internal
network as it can lead to communication issues
with the Broker VM.

👀

🟠i…

If you use SSL decryption in your firewalls and
proxies, see the Understanding CA certificate
functionality in Broker VM deployments section
below. In addition, verify that the proxies used
support HTTP/2, gRPC-specific headers, and
HTTP/2 trailers, and the inspection policies
support gRPC traffic. Any devices that you use
with this configuration...

👀

🟠i…

When configuring more than one network
interface, ensure that only one Default
Gateway is defined. The rest must be set to
0.0.0.0, which configures them as undefined. In
addition, we recommend assigning each
network interface to a different subnet, as
oppose to configuring two interfaces on the
same subnet which can potentially cause
unexpected...

👀

🟠i…

Internal IP must be:
Formatted as prefix/mask, for example
192.0.2.1/24.
Must be within /8 to /24 range.
Cannot be configured to end with a zero.
For Broker VM version 9.0 and earlier, Cortex
XSIAM will only accept 172.17.0.0/16.

👀

🟠i…

We strongly recommend disabling SSH
connectivity when it's not being used.
Therefore, activate SSH connectivity when it's
needed and disable it right afterwards.
When generating a new SSH key ensure to avoid
embedding the domain-style username, by not
using any backslashes (\) in the comment field,
to ensure the SSH key passes validation.

3.1.2.2.1. Broker VM image installations 

3.1.2.2.1.1. Set up Broker VM on Alibaba Cloud 

☑️

🟣pr…

Download a Cortex XSIAM Broker VM QCOW2
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.

📝

🟢note

For Linux and Windows uploads, you can use
Alibaba Cloud's graphical management tool
called ossbrowser.

📝

🟢note

The Object Storage Service must be created in
the same Region as the image of the virtual
machine.

🧭

➡️n…

Hamburger menu → Elastic Compute Service
→ Instances & Images → Instances

3.1.2.2.1.2. Set up Broker VM on Amazon Web
Services 

☑️

🟣pr…

Download a Cortex XSIAM Broker VM VMDK
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.
You need to set up an AWS VM Import role
(vmimport) before you continue with the steps
to convert the image as it is required for the
import-snapshot CLI command. You can use a
different role, if the...

📝

🟢note

Assigning security groups can take up to 15
minutes.

👀

🟠i…

A t3.xlarge (16 GB RAM) is the lowest machine
type that can be used as an instance type to
meet the mandatory 4 vCPU requirement.

🧭

➡️n…

Log in to the AWS IAM Console, and in the
navigation pane, select Access Management →
Users → Add Users

In the Cortex XSIAM Web Console , select
Settings → Configurations → Data Broker →
Broker VMs → Add Broker → VMDK

Services → Storage → S3 → Buckets

Services → EC2 → IMAGES → AMIs and locate
your AMI image using the task ID

Obtain a registration token from the Cortex
XSIAM Web Console by selecting Settings →
Configurations → Data Broker → Broker VMs →
Add Broker → Generate Token

3.1.2.2.1.3. Set up Broker VM on Google Cloud
Platform (GCP) 

☑️

🟣pr…

Download a Cortex XSIAM Broker VM VMDK
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.
To complete the set up, you must have G Cloud
installed and have an authenticated user
account.

☑️

🟣pr…

Before importing a GCP image using the gcloud
CLI, ensure that you update the Google Cloud
components to version 371.0.0 and above using
the following command:

📝

🟢note

The import tool uses Cloud Build API, which
must be enabled in your project. For the import
to work, Cloud Build service account must have
compute.admin and iam.serviceAccountUser
roles. When using the Google Cloud console to
import the image, you will be prompted to add
these permissions automatically.

3.1.2.2.1.4. Set up Broker VM on KVM using
Ubuntu  ☑️

🟣pr…

Download a Cortex XSIAM Broker VM QCOW2
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.

3.1.2.2.1.5. Set up Broker VM on Microsoft Azure 

☑️

🟣pr…

Download a Cortex XSIAM Broker VM VHD
(Azure) image. For more information, see the
virtual machine compatibility requirements in
Set up and configure Broker VM.

📝

🟢note

Extraction can take up to a few hours.

📝

🟢note

Upload can take up to a few hours.

📝

🟢note

For more information, see the Azure
Documentation.

📝

🟢note

Creating the VM can take up to 15 minutes. The
Broker VM Web UI is not accessible during this
time.

📝

🟢note

For more information on creating a rule in an
Azure VM, see Create a Security Rule in the
Azure Documentation.

3.1.2.2.1.6. Set up Broker VM on Microsoft Hyper-
V  ☑️

🟣pr…

Download a Cortex XSIAM Broker VM VHD
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.

3.1.2.2.1.7. Set up Broker VM on Nutanix
Hypervisor 

☑️

🟣pr…

Download a Cortex XSIAM Broker VM QCOW2
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.

📝

🟢note

Saving the image to Nutanix hypervisor can
take time as it's a large file. We recommend
verifying periodically that the connection is
alive for the upload process to finish
successfully.

📝

🟢note

Creating the VM can take up to 15 minutes. The
Broker VM Web user interface is not accessible
during this time.

3.1.2.2.1.8. Set up Broker VM on VMware ESXi
using vSphere Client  ☑️
🟣pr…

Ensure you have a virtualization platform
installed that is compatible with an OVA image,
and have an authenticated user account.
Download a Cortex XSIAM Broker VM OVA
image. For more information, see the virtual
machine compatibility requirements in Set up
and configure Broker VM.

3.1.2.2.2. Broker VM data collector applets 

3.1.2.3. Manage Broker VM 

📝

🟢note

For more information on troubleshooting errors
and warnings for these broker applets, see
Troubleshoot Broker VM applet errors.

📝

🟢note

Certain fields are also exposed in the Clusters
tab, when a Broker VM node is added to a High
Availability (HA) cluster, and each cluster node
is expanded to view the Broker VM nodes table.
An asterisk (*) is beside every field that is also
included in the Broker VM nodes table for each
HA cluster.

🧭

➡️n…

Settings → Configurations → Data Broker →
Broker VMs

3.1.2.3.1. Edit Broker VM Configuration 

📝

🟢note

For all Broker VM nodes added to a HA cluster,
you can also Configure the Broker VM nodes
from the Clusters tab.

📝

🟢note

Internal IP must be:
Formatted as prefix/mask, for example
192.0.2.1/24.
Must be within /8 to /24 range.
Cannot be configured to end with a zero.
For Broker VM version 9.0 and lower, Cortex
XSIAM accepts only 172.17.0.0/16.

📝

🟢note

Make sure you save the password before
closing the window. The only way to re-
generate a password is to disable ssh and re-
enable.

3.1.2.3.2. Increase Broker VM storage allocated
for data caching 

📝

🟢note

Follow your hypervisor documentation to
understand how to add a persistent disk
storage to your VM.

📝

🟢note

If your disk is not listed and you didn't
shutdown your Broker VM in your hypervisor
before manually adding a disk to the VM, you'll
need to reboot the Broker VM before the disk
details are detected by the Broker VM. This can
be performed either in the hypervisor or
directly in the Broker VMs page.

⛔

🔴w…

This operation is irreversible, and will make the
disk become an integral part of the broker,
where disconnecting the disk will result in
errors and data loss.

3.1.2.3.3. Monitor Broker VM using Prometheus 

📝

🟢note

For all Broker VM nodes added to a HA cluster,
you can also Configure the Broker VM nodes
from the Clusters tab.

📝

🟢note

For more information on Docker, see the Docker
website.

3.1.2.3.4. Collect Broker VM Logs  📝

🟢note

The Download Logs (<TIMESTAMP>) is only
displayed when you've downloaded your logs
previously using Generate New Logs.

3.1.2.3.5. Upgrade Broker VM  👀

🟠i…

After a Broker VM upgrade, your broker may
require a reboot to finish installing important
updates. A notification about this will be sent
to your Cortex XSIAM console Notification
Center.

3.1.2.3.6. Import Broker VM Configuration 

👀

🟠i…

This option can only be used on Broker VMs
with version 20.0 and later, and is only suitable
for importing a configuration of brokers in the
same version, or from a broker in an older
version to a broker in a newer version.

👀

🟠i…

If your source Broker VM configuration includes
a WEC applet, you'll need to ensure that you
update the DNS record of this Broker VM's
FQDN to point to the target Broker VM IP
address.

3.1.2.3.7. Open Live Terminal  📝

🟢note

You can either restart_routes or reboot the
Broker VM for the changes in the
/etc/network/routes file to take affect.

3.1.2.3.8. Add Broker VM to cluster 

3.1.2.3.9. Switchover Primary Node in Cluster 

3.1.2.3.10. Remove from Cluster  📝

🟢note

If you've enabled a Load Balancer Health-
Check on the cluster, you need to exclude this
Broker VM from your Load Balancer settings.

3.1.2.4. Manage Broker VM data collector
applets  📝
🟢note

For more information on the Broker VM applet
connectivity status, see Manage Broker VM.

3.1.2.5. Broker VM High Availability Cluster 

📝

🟢note

For Load Balancing, you must install a Load
Balancer in your network, which will distribute
the incoming data between the nodes.

📝

🟢note

The following applets aren't supported when
configuring Broker VMs in HA clusters: Cortex
Network Scanner, DSPM Fileshare, Registry
Scanner, and Transporter.

3.1.2.5.1. Configure High Availability Cluster 

☑️

🟣pr…

Be sure you do the following task before
creating a cluster from an existing Broker VM:
If the Broker VM is explicitly specified in some
Agent Settings profile, which means Cortex
XSIAM agents retrieve release upgrades and
content updates from this Broker VM, you must
change the Broker VM's current designated
role. To do this, you need to modify the...

📝

🟢note

The Broker VM Load Balancer Health Check
requires HTTP/1.1 or higher. Legacy HTTP/1.0 is
no longer supported. Ensure your external load
balancer is configured to use HTTP/1.1 or above
when performing health checks.

👀

🟠i…

You can only create a new cluster from an
existing Broker VM, when the Broker VM version
is 19.0 and later, and the STATUS is Connected.
The Create a Cluster from this Broker option is
only listed if the Broker VM is not already
added to a cluster.

👀

🟠i…

When the Protocol is set to HTTPS, you may
need to perform a few follow-up steps to
establish a validated secure SSL connection
with the Broker VM.
If you're using your own Certificate Authority
(CA) to sign the certificates, you'll need to
place the CA in the client, such as the Load
Balancer, and upload the certificates to the
Broker VM.
If you're...

3.1.2.5.2. Manage Broker VM clusters 

🧭

➡️n…

After you've configured a cluster, you can
manage all your Broker VM clusters from the
Clusters tab on the Broker VMs page (Settings
→ Configurations → Data Broker → Broker VMs
→ Clusters

3.1.2.5.2.1. View cluster details 

📝

🟢note

For more information on troubleshooting errors
and warnings for these applets, see
Troubleshoot Broker VM applet errors.

🧭

➡️n…

The Clusters tab of the Broker VMs page
(Settings → Configurations → Data Broker →
Broker VMs) enables you

3.1.2.5.2.2. Edit cluster  🧭

➡️n…

Settings → Configurations → Data Broker →
Broker VMs, and select the Clusters tab

3.1.2.5.2.3. Add applet to cluster 

📝

🟢note

With Cortex XDR Prevent, it's only relevant to
configure a HA cluster with a Local Agent
Settings applet as this is the only applet
supported for this product license. The other
applets are collector applets, which are only
available in Cortex XDR Pro or Cortex XSIAM.

📝

🟢note

For more information on troubleshooting errors
and warnings for these applets, see
Troubleshoot Broker VM applet errors.

3.1.2.5.2.4. Add Broker VM to cluster 

3.1.2.5.2.5. Remove cluster 

3.1.2.6. Broker VM notifications  📝

🟢note

For more information on upgrading to a new
Broker VM image, see Migrating to a New
Broker VM Image.

3.1.2.7. Monitor Broker VM activity  📝

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

3.1.2.8. Troubleshoot Broker VM applet errors  📝

🟢note

For more information on creating correlation
rules to trigger collection health issues, see
How can I set up correlation rules to trigger
collection health issues?.

3.1.3. Dataset management 

🔒

🟣c…

Managing Roles requires an Account Admin or
Instance Administrator role. For more
information, see Predefined user roles.

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

📝

🟢note

Cold storage, in addition to a cold storage
license, requires compute units (CU) to run cold
storage queries. For more information on CU,
see Manage compute units.
For information on the CU add-on license, see
Understand the Cortex XSIAM license
planUnderstand the Cortex XSIAM license plan.

📝

🟢note

Only datasets that are already handled as part
of the GB license are supported for this license.
In addition, the retention configuration is only
available in Cortex XSIAM, as opposed to the
public APIs.

📝

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.
Datasets include dataset permission
enforcements in the Cortex Query
Language(XQL), Query Center, and XQL
Widgets. For example, to view or access any of
the endpoints and host_inventory datasets, you
need role-based access control (RBAC)...

📝

🟢note

You'll only be able to save the dataset view if
the query contains no errors; otherwise, the
Save button is disabled.

📝

🟢note

For more information on user roles, see Manage
user roles.

👀

🟠i…

Cortex XSIAM enforces retention on all log-
type datasets excluding Host Inventory,
Vulnerability Assessment, Metrics, and Users.

👀

🟠i…

This column is updated once a day. Therefore,
if the dataset was created or updated by the
target or lookup flows, it's possible that the
Last Updated value is a day behind when the
queries or reports were run as it was before this
column was updated.

3.1.3.1. What are datasets? 

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

📝

🟢note

For more information on tasks specific to
lookup datasets, see Lookup datasets.

📝

🟢note

Schema changes to datasets may not be
reflected in the autocomplete suggestions and
definitions as you type in real time the XQL
query and can appear with a slight delay.

👀

🟠i…

By default, forensic datasets are not included
in XQL query results, unless the dataset query
is explicitly defined to use a forensic dataset.

3.1.3.2. Lookup datasets 

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

📝

🟢note

A lookup dataset can only be deleted if there
are no other dependencies. For example, if a
Correlation Rule is based on a lookup dataset,
you wouldn't be able to delete the lookup
dataset until you removed the dataset from the
XQL query of the Correlation Rule.

👀

🟠i…

When you create or add data to a lookup
dataset using the target stage, the _time field
won't be included by default unless you
explicitly add it with the fields stage.

3.1.3.2.1. Import a lookup dataset 

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

☑️

🟣pr…

When uploading a CSV, TSV, or JSON file,
ensure that the file meets the following
requirements:
The maximum size for the total data to be
imported into a lookup dataset is 30 MB from
the Dataset Management page. Otherwise, the
limit is 50 MB using Cortex Query Language
(XQL) or APIs.
Field names can contain characters from
different languages, special...

👀

🟠i…

The name of a dataset created from a TSV file
must always include the extension. For example,
if the original file name is mrkdptusrsnov23.tsv,
you can save the dataset with the name
marketing_dept_users_Nov_2023.tsv.

3.1.3.2.2. Download JSON file of lookup dataset 

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

🧭

➡️n…

Open the Settings → Configurations → Data
Management → Dataset Management page

3.1.3.2.3. Set time to live for lookup datasets  ☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

3.1.3.3. Monitor datasets and dataset views

activity 

☑️

🟣pr…

Dataset Management requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Event Forwarding.

📝

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

3.1.4. Archived data 

3.1.4.1. Import historical data into cold storage 

🔒

🟣c…

Importing historical data into cold storage
requires a Period-Based Retention - Cold
Storage add-on license.

☑️

🟣pr…

Importing historical data into cold storage
requires a View/Edit RBAC permission for Data
Management (under Configurations).

3.1.4.2. Building XQL archived data queries  ☑️

🟣pr…

Archived cold storage, in addition to a Period-
Based Retention - Cold Storage add-on license,
requires compute units (CU) to run archived
cold storage queries. Cortex XSIAM provides a
free daily quota of compute units (CU)
allocated according to your license size.
Queries run without enough quota will fail. To
expand your investigation capabilities,...

3.1.4.3. Success and failure code responses to
your HTTP POST requests 

3.1.5. Parsing Rules 

3.1.5.1. What are Parsing Rules?  ☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

3.1.5.2. Parsing Rules editor views  ☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

3.1.5.3. Parsing Rules file structure and syntax 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

For more information on the XQL syntax, see
Cortex XQL Language Reference.

📝

🟢note

An inner type of join stage is only supported in
CONST, INGEST, and RULE sections and is not
supported in a COLLECT section.
You cannot call a RULE section that exists in
Default Rules from the User Defined Rules
section.

📝

🟢note

The regexcapture function is only supported in
Parsing Rules and cannot be used in any other
XQL query.

📝

🟢note

Every statement in the Parsing Rules file must
end with a semicolon (;).

3.1.5.3.1. INGEST 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

You can't add tags to parsing rules using the
Next-Generation Firewall (NGFW) datasets that
are in the format panw_ngfw_<text>_raw, and
the Observability dataset called
panw_observability_raw.

3.1.5.3.2. COLLECT 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

The CSV Collector applet is not affected by
the COLLECT rules applied to a Broker VM.

📝

🟢note

The CSV Collector applet is not affected by
the COLLECT rules applied to a Broker VM.

💡

🔵tip

To reduce the amount of data transmitted to
Cortex XSIAM from the broker, use filters to
drop logs. Yet, be aware that once the logs are
modified using alter or fields stages, the Broker
VM will convert the original log into a JSON
format, which could increase the data size
being sent from the broker to Cortex XSIAM.

3.1.5.3.3. CONST 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

The dollar sign ($) must be adjacent to the
[CONST] name, without any whitespace in
between.

👀

🟠i…

Only quoted or integer terminal values are
considered valid for CONST sections.

3.1.5.3.4. RULE 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

For more information on the XQL syntax, see
Get started with XQL.

📝

🟢note

You can also add tags using only the INGEST
section. For more information, see INGEST.

3.1.5.3.5. EXTEND 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

For more information on the XQL syntax, see
Get started with XQL.

3.1.5.4. Create Parsing Rules 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

You need Cortex XSIAM administrator or
Instance Administrator permissions to access
the Simulate view and perform these tests.

👀

🟠i…

When creating Parsing Rules, the _time field is a
mandatory field. If the field is null or invalid, the
_insert_time field is used instead. This field can
be automatically parsed depending on the type
of data being ingested. For example, for CEF or
LEEF logs, the parser first tries to ingest
timestamps from these fields in the following
order: rt,...

3.1.5.5. Troubleshooting Parsing rules errors 

☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

📝

🟢note

Some errors can only be found after the
applicable logs are collected in Cortex XSIAM.

3.1.5.6. Parsing Rules Raw Dataset  ☑️

🟣pr…

Parsing Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Data Model Rules, and Event
Forwarding.

3.1.6. Data Model Rules 

🔒

🟣c…

Only a user with Cortex Account Administrator
or Instance Administrator permissions can
access Data Model Rules.

3.1.6.1. What are Data Model Rules?  ☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

3.1.6.2. Data Model Rules editor views  ☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

3.1.6.3. Data Model Rules file structure and

syntax 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

📝

🟢note

For more information on XQL syntax, see the
XQL Language Reference Guide.

📝

🟢note

You cannot call a RULE section that exists in
Default Rules from the User Defined Rules
section.

3.1.6.3.1. MODEL 

📝

🟢note

The Settings → Configurations → XQL
Configuration → Case Sensitivity
(case_sensitive) setting can overwrite this
case_sensitive configuration for all fields in the
application except for BIOCs, which will remain
case insensitive no matter what this setting is
set to. For more information on this setting, see
XQL Configuration.Set up your...

📝

🟢note

We recommend that you do not configure the
same data source in both Marketplace and
using a Cortex XSIAM data collector. Yet, if you
do, the following will happen:External data
ingestion
For network data, all relevant logs from the
different data sources are stitched to the same
network story.
For authentication data, all relevant logs from
the...

3.1.6.3.2. RULE  📝

🟢note

For more information on the XQL syntax, see
the XQL Language Reference Guide.

3.1.6.3.3. Field structure 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

📝

🟢note

For more information on these data model
fields, see Cortex XSIAM Data Model Schema.

3.1.6.4. How to map authentication story events? 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

☑️

🟣pr…

Familiarize yourself with the Cortex Data model
(XDM) schema for field definitions and naming
conventions, see Cortex XSIAM Data Model
Schema.

👀

🟠i…

This Feature focuses on authentication events
related to SSO (Single Sign-On) and SaaS
(Software-as-a-Service) application
authentications. It does not cover internal
authentication mechanisms such as Kerberos,
NTLM, or traditional domain logon events
generated by on-premise infrastructure.

👀

🟠i…

To maximize the variety of issues that are
retrieved based on the XDM authentication
stories, we recommend that the following
additional fields are populated:
xdm.target.resource_name, xdm.logon.type,
xdm.source.user_agent, and
xdm.source.host.device_category. Should you
decide to change the default XDM mappings,
ensure that both the mandatory and...

3.1.6.5. Create Data Model Rules 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

🧭

➡️n…

In Cortex XSIAM, select Settings →
Configurations → Data Management → Data
Model Rules

3.1.6.6. Troubleshooting Data Model Rules 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

📝

🟢note

Since this dataset also contains Parsing Rules
errors, some of the fields are irrelevant for Data
Model Rules and aren't included in the table.

💡

🔵tip

To ensure you and your colleagues stay
informed about Data Model Rules activity, you
can also Configure notification forwarding to
forward your Data Model Rules audit logs to an
email distribution list or Syslog server. For more
information about the Data Model Rules audit
logs, see Monitor Data Model Rules activity.

3.1.6.7. Using data enrichment 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

📝

🟢note

For a complete list of auto-enriched fields, see
the Cortex Data Model Schema Guide.

👀

🟠i…

When manually mapping ASN fields that are
enriched, such as xdm.source.asn.as_number,
with other ISP and domain fields that are not
enriched, such as xdm.source.asn.isp and
xdm.source.asn.domain, it's possible to receive
incorrect XDM query results due to the
misalignment between the overridden
enrichement and system enrichment fields.

3.1.6.8. Data Model Rules notifications  ☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

3.1.6.9. Monitor Data Model Rules activity 

☑️

🟣pr…

Data Model Rules requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Dataset
Management, Parsing Rules, and Event
Forwarding.

📝

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

3.1.7. Manage Event Forwarding 

☑️

🟣pr…

Event Forwarding requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Dataset
Management.

📝

🟢note

After exporting logs, you can download them
from GCP for up to 14 days. The Pub/Sub
subscription messages are available for 7 days.

📝

🟢note

Requires the Endpoints Event Forwarding add-
on.

📝

🟢note

Requires the GB Event Forwarding add-on

👀

🟠i…

Since data is aggregated and compressed, it
may take up to two hours until the data is
available in the forwarding bucket.

🧭

➡️n…

Under Settings → Configurations → Data
Management → Event Forwarding, activate one
or more of the following: Enable GB Event
Forwarding Enable Endpoints Event Forwarding

Under Settings → Configurations → Data
Management → Event Forwarding, activate one
or more of the following

3.1.7.1. Endpoints Event Forwarding -
included/excluded fields by event type  ☑️
🟣pr…

Event Forwarding requires View/Edit RBAC
permissions for Data Management (under
Configurations → Data Management), which
are the same permissions required for Parsing
Rules, Data Model Rules, and Dataset
Management.

3.1.8. Manage compute units 

📝

🟢note

For more information, see Import historical data
into cold storage.

📝

🟢note

The CU consumption of cold storage queries is
based on the number of days in the query time
frame. For example, when querying 1 hour of a
specific day, the CU of querying this entire day
is consumed. When querying 1 hour that
extends past 2 days, such as from 23�50 to
00�50 of the following day, the CU of querying
these two days is consumed.

3.1.8.1. Compute units usage 

📝

🟢note

To enable the add-on, select Settings →
Configurations → Cortex XSIAM License →
Addons tile, and select the Compute Unit tile
and Enable.

🧭

➡️n…

Settings → Configurations → Data
Management → Compute Unit Usage

3.2. Cortex XSIAM Data Sources 

3.2.1. What are Cortex XSIAM data sources? 

📝

🟢note

Some content packs provide parsing rules and
data model rules for data sources ingested
using a Syslog Collector applet of the Broker
VM or for standard data sources, and won't be
listed in the Data Sources & Integrations page.

👀

🟠i…

We are actively working to evolve the UI to
create a single, unified point of configuration
for all data ingestion and integration points.
This documentation is structured to help you
navigate the current segmented process until
that UI update is available.

3.2.2. Complete data source catalog 

3.2.3. Vendor-specific data sources 

👀

🟠i…

In some cases, the same vendor is available
through one or more of these options: standard
data source, CSP onboarding data source, or
content pack integration. Check the available
descriptions for each data source in both the
user interface and documentation to decide
which option is more suitable for your needs.

3.2.3.1. Amazon CloudWatch  3.2.3.1.1. Ingest logs from Amazon CloudWatch 

3.2.3.2. Amazon S3 

3.2.3.2.1. Ingest audit logs from AWS Cloud Trail 

📝

🟢note

For more information on configuring data
collection from Amazon S3 using AWS
CloudTrail, see the AWS CloudTrail
Documentation.

📝

🟢note

For more information on creating an AWS
CloudTrail trail, see Create a trail.
If you already have an Amazon S3 bucket
configured with AWS CloudTrail audit logs,
skip this step and go to Configure an Amazon
Simple Queue Service (SQS).

📝

🟢note

It is your organization's responsibility to define
a retention policy for your Amazon S3 bucket
by creating a Lifecycle rule in the Management
tab. We recommend setting the retention policy
to at least 7 days to ensure that the data is
retrieved under all circumstances.

📝

🟢note

The CloudWatch Logs - optional settings are
not supported and should be left disabled.

📝

🟢note

Ensure that you create your Amazon S3 bucket
and Amazon SQS queue in the same region.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

📝

🟢note

If your receive an error when trying to save your
changes, you should ensure that the
permissions are set up correctly.

📝

🟢note

It your organization's responsibility to ensure
that the user who performs this task of creating
the access key is designated with the relevant
permissions. Otherwise, this can cause the
process to fail with errors.
Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information, see Managing access
keys for IAM users.

📝

🟢note

Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

3.2.3.2.2. Ingest network flow logs from Amazon
S3 

📝

🟢note

For more information on configuring data
collection from Amazon S3, see the Amazon S3
Documentation.

📝

🟢note

For the Amazon S3 bucket created using
CloudFormation, it is the customer's
responsibility to define a retention policy by
creating a Lifecycle rule in the Management
tab. We recommend setting the retention policy
to at least 7 days to ensure that the data is
retrieved under all circumstances.

📝

🟢note

To create a new VPC, click Launch VPC Wizard.
For more information, see AWS VPC Flow Logs.

📝

🟢note

It is the responsibility of the customer's
organization to ensure that the user who
performs this task of creating the access key is
designated with the relevant permissions.
Otherwise, this can cause the process to fail
with errors.
Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information, see Managing access
keys for IAM users.

📝

🟢note

Skip this step if you are using an Access Key to
provide access to Cortex XSIAM.

3.2.3.2.3. Ingest generic logs from Amazon S3 

📝

🟢note

For more information on configuring data
collection from Amazon S3, see the Amazon S3
Documentation.

📝

🟢note

You need to set up an Amazon S3 data
collector to receive generic logs when
collecting logs from BeyondTrust Privilege
Management Cloud. For more information, see
Ingest logs from BeyondTrust Privilege
Management Cloud.

📝

🟢note

If you want to ingest raw EDR events from
SentinelOne DeepVisibility, use the SentinelOne
DeepVisibility log collector. For more
information, see Ingest raw EDR events from
SentinelOne DeepVisibility.

📝

🟢note

It is the customer's responsibility to define a
retention policy for your Amazon S3 bucket by
creating a Lifecycle rule in the Management
tab. We recommend setting the retention policy
to at least 7 days to ensure that the data is
retrieved under all circumstances.

📝

🟢note

Ensure that you create your Amazon S3 bucket
and Amazon SQS queue in the same region.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

📝

🟢note

If your receive an error when trying to save your
changes, you should ensure that the
permissions are set up correctly.

📝

🟢note

It is the responsibility of your organization to
ensure that the user who performs this task of
creating the access key is assigned the relevant
permissions. Otherwise, this can cause the
process to fail with errors.
Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information, see Managing access
keys for IAM users.

📝

🟢note

Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

📝

🟢note

-The Vendor and Product defaults to Auto-
Detect when the Log Format is set to CEF or
LEEF.
-For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor...

3.2.3.2.4. Ingest network Route 53 logs from
Amazon S3 

📝

🟢note

For more information on configuring data
collection from Amazon S3 for Route 53 DNS
logs, see the AWS Documentation.

📝

🟢note

For more information on creating a Stack, see
Creating a stack on the AWS CloudFormation
console.

📝

🟢note

For the Amazon S3 bucket created using
CloudFormation, it is the customer's
responsibility to define a retention policy by
creating a Lifecycle rule in the Management
tab. We recommend setting the retention policy
to at least 7 days to ensure that the data is
retrieved under all circumstances.

📝

🟢note

It is the responsibility of the customer's
organization to ensure that the user who
performs this task of creating the access key is
designated with the relevant permissions.
Otherwise, this can cause the process to fail
with errors.
Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

For more information, see Managing access
keys for IAM users.

📝

🟢note

Skip this step if you are using an Access Key to
provide access to Cortex XSIAM.

3.2.3.2.5. Create an assumed role 

☑️

🟣pr…

You need ensure you have an Amazon S3
bucket and Amazon Simple Queue Service
(SQS) already configured as it's needed to
configure an IAM policy. The S3 bucket and
SQS required depends on how you plan to
configure your Amazon S3 data source:
When using a CloudFormation script provided
by Cortex XSIAM to configure Amazon S3 with
SQS notifications, you'll...

📝

🟢note

You can retrieve your bucket's ARN by opening
the Amazon S3 Console in a browser window. In
the Buckets section, select the bucket, click
Copy ARN, and paste the ARN in the field.
You can retrieve the SQS queue ARN by
opening another instance of the AWS
Management Console in a browser window, and
opening the Amazon SQS Console, and
selecting the...

📝

🟢note

For more information, see the AWS instructions.

3.2.3.2.6. Configure data collection from
Amazon S3 manually 

📝

🟢note

If you already have an Amazon S3 bucket
configured with VPC flow logs that you want
to use for this configuration, you do not need
to perform the prerequisite steps detailed in
the first two bullets.

📝

🟢note

It is your responsibility to define a retention
policy for your Amazon S3 bucket by creating a
Lifecycle rule in the Management tab. We
recommend setting the retention policy to at
least 7 days to ensure that the data is retrieved
under all circumstances.

📝

🟢note

For resources such as Amazon S3, SQS, VPC
flow logs, and event notifications, you may use
the default configurations; yet, these settings
remain fully customizable to meet your specific
environment requirements.

📝

🟢note

If you already have an Amazon S3 bucket
configured with VPC flow logs, skip this step
and go to Configure an Amazon Simple Queue
Service (SQS).

📝

🟢note

Ensure that you create your Amazon S3 bucket
and Amazon SQS queue in the same region.

📝

🟢note

It is the responsibility of the customer's
organization to ensure that the user who
performs this task of creating the access key is
designated with the relevant permissions.
Otherwise, this can cause the process to fail
with errors.
Skip this step if you are using an Assumed Role
for Cortex XSIAM.

📝

🟢note

Skip this step if you are using an Assumed Role
for Cortex XSIAM.

3.2.3.3. Amazon Web Services 

3.2.3.4. API Security  3.2.3.4.1. Ingest data for API security 

3.2.3.4.1.1. Ingest AWS API Gateway 

📝

🟢note

You must generate a new key if you did not save.

📝

🟢note

If no logs are showing, send some API requests
on Postman or CURL.

👀

🟠i…

Leave '–'filter-pattern empty as displayed
above.

3.2.3.4.1.2. Ingest Azure APIM 

🔒

🟣c…

Requires the Data Collection add-on.

📝

🟢note

Microsoft Azure APIM service must be running
before starting to configure the integration.

📝

🟢note

From the URL, save the UUID and the resource
group -

/resource/subscriptions/<UUID>/resourceGroup
s/<ResourceGroup>.
The UUID is the Azure account/subscription ID
and the resource group, which is the group
where the APIM Service is defined.

📝

🟢note

Use the search to navigate to the specific
section.

📝

🟢note

131072 bytes = 128 KB. This value determines
the size (in bytes) of request and response
bodies to send to Cortex. Any bytes beyond this
limit are truncated.

📝

🟢note

If any other inbound policies should be added,
they must be added after these elements.

👀

🟠i…

If you want to add additional data to the
<outbound>, add it at the start of the
<outbound> code.

3.2.3.4.1.3. Ingest Apigee Proxy 

🔒

🟣c…

Requires the Data Collection add-on.

📝

🟢note

The steps include the prerequisites that run the
automated script that deploys files and
configurations to Apigee. For manual
configuration, refer to the section Manual
deployment.

📝

🟢note

If you have an existing hookand would like to
integrate with the shared flow, run the
deploy.sh script, and select n' and exit at the
prompt to create a new hook. Refer to the
section Connect to existing hook.

📝

🟢note

Start with the hook in pre-proxy.

📝

🟢note

Archive deployments are currently in preview
and are subject to change.

👀

🟠i…

This should only be done when there are
already existing hooks, and API security shared
flows can't be hooked as a standalone. Run the
deployment script, but skip step 9 by passing n.
This step publishes API security shared flows to
the desired Apigee environment without setting
them to flow hooks.

3.2.3.4.1.4. Ingest Kong 

🔒

🟣c…

Requires the Data Collection add-on.

📝

🟢note

Contact support to obtain the custom plugin
file.

📝

🟢note

The queue parameters can be updated to
change when the plugin mirrors data to Cortex.

📝

🟢note

Use commas to separate tags.

👀

🟠i…

The size of the buffer must be equal or larger
than the max body size setting in the plugin
configuration, on every data plane node.

3.2.3.4.1.5. Ingest-F5 

🔒

🟣c…

Requires the Data Collection add-on.

📝

🟢note

Extract the files from the F5 plugin to a folder
before selecting to upload to F5.

📝

🟢note

The provider for "context_provider" should
always be uppercase.
Supported providers: AWS, GCP, Azure, On-
prem.

📝

🟢note

Select panw_apisec_set_ssl_data only if your
client SSL profile is enabled.

3.2.3.5. Azure Event Hub 

3.2.3.5.1. Ingest logs from Microsoft Azure Event
Hub 

☑️

🟣pr…

Ensure that you do the following tasks before
you begin configuring data collection from
Azure Event Hub.
Before you set up an Azure Event Hub,
calculate the quantity of data that you expect
to send to Cortex XSIAM, taking into account
potential data spikes and potential increases in
data ingestion, because partitions cannot be
modified after creation....

📝

🟢note

For more information on Azure Event Hub audit
logs, see Overview of Azure platform logs.

📝

🟢note

These logs are from the management plane.

📝

🟢note

Even though you can collect Azure AD Activity
logs and Azure Sign-in logs using the Azure
Event Hub data collector, we recommend using
the Microsoft Office 365 data collector,
because it is easier to configure. In addition,
ensure that you do not configure both
collectors to collect the same types of logs,
because if you do so, you will be creating...

📝

🟢note

These logs are from the data plane.

📝

🟢note

If you want to ingest raw Microsoft Defender
for Endpoint events, use the Microsoft
Defender log collector. For more information,
see Ingest raw EDR events from Microsoft
Defender for Endpoint.

📝

🟢note

For every resource that you want to confiure,
you'll have to repeat this step, or use Azure
policy for a general configuration.

📝

🟢note

There are additional log categories displayed.
We recommend selecting all the available
options.

📝

🟢note

When you Normalize and enrich audit logs, the
log format is automatically configured. As a
result, the Log Format option is removed and is
no longer available to configure (default).

📝

🟢note

For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor and
Product fields in the Azure Event Hub data
collector settings. Yet, when the values are...

📝

🟢note

When you Normalize and enrich audit logs, the
Vendor and Product fields are automatically
configured, so these fields are removed as
available options (default).

⛔

🔴w…

Misconfiguration of Event Hub resources could
cause ingestion delays.
In an existing Event Hub integration, do not
change the mapping to a different Event Hub.
Do not use the same Event Hub for more than
two purposes.

3.2.3.6. Azure Network Watcher 

3.2.3.6.1. Ingest network flow logs from
Microsoft Azure Network Watcher 

☑️

🟣pr…

For NSG:
Ensure that your NSG flow logs in Azure
Network Watcher conform to the requirements
as outlined in Microsoft documentation. For
more information, see Introduction to flow
logging for network security groups.
Enable NSG flow logs in the Microsoft Azure
Portal.
For NSG:
Ensure that your NSG flow logs in Azure
Network Watcher conform to the...

📝

🟢note

In addition to your storage account, the
template automatically creates another
storage account that is required by the
function app for internal use only. The internal
storage account name is prefixed with cortex
and is followed by a unique suffix based on the
resource group, storage account, and container
names.

3.2.3.7. BeyondTrust Privilege Management
Cloud 

3.2.3.7.1. Ingest logs from BeyondTrust Privilege
Management Cloud  📝
🟢note

For a Log Format set to Beyondtrust Cloud
ECS, the following fields are automatically set
and not configurable.
Vendor: Beyondtrust
Product: Privilege Management
Compression: Uncompressed

3.2.3.8. Box  3.2.3.8.1. Ingest logs and data from Box 

☑️

🟣pr…

Set up an Enterprise Box plan.
Important
To collect Box Shield Alerts, you must purchase
Box Shield and it must be enabled on Box
enterprise.
Set up an Enterprise Box plan.
Create a valid Box account that is assigned to a
role with sufficient permissions for the data you
want to collect. For example, create an account
assigned to an Admin role to...

📝

🟢note

The Fetch Intervals are non-configurable.

📝

🟢note

Collecting Box Shield Alerts requires
implementing Box Shield,

📝

🟢note

There is a current bug with the Groups API from
Box. If you don't configure the Box app with the
proper permissions for managing groups data,
the Groups API from Box won't return an error
message to Cortex XSIAM indicating that the
API failed to receive the data, and the Groups
data will not be collected.

📝

🟢note

For any future change that you make to your
Box app, ensure that you send the changes for
approval to the administrator, who will need to
approve them as explained above.

📝

🟢note

Inventory data snapshots are collected every 10
minutes.

3.2.3.9. Check Point FW1/VPN1 

3.2.3.10. Cisco ASA firewalls and AnyConnect 

3.2.3.11. Corelight Zeek 

3.2.3.12. Cribl  3.2.3.12.1. Ingest data from Cribl 

☑️

🟣pr…

Ensure that you have the credentials and IDs for
each data source, such as Tenant ID, App ID and
Client secret.

☑️

🟣pr…

Ensure that you have the copies of the Cortex
XSIAM authorization token and API URL
obtained in Task 2.

📝

🟢note

We do not support email data collection via
Cribl.

📝

🟢note

Only one Cribl data collector instance can be
configured in Cortex XSIAM.

📝

🟢note

When the logs are in CEF format, Cortex XSIAM
reads events row by row to look for the Vendor
and Product configured in the logs. When the
values are populated in the event log row,
Cortex XSIAM uses these values even if you
specified a value in the Vendor and Product
fields in the Cribl collector settings. However,
when the values are blank in the...

👀

🟠i…

Raw data must be collected by Cribl and
streamed as-is from the passed through source,
because any changes made by Cribl might
affect the way that Cortex XSIAM handles the
data.

3.2.3.12.1.1. Data source UUIDs  📝

🟢note

Do not use this generic UUID when your data
source is listed in this table.

3.2.3.13. CrowdStrike APIs 

3.2.3.13.1. Ingest alerts and metadata from
CrowdStrike APIs 

📝

🟢note

To enable some of the APIs, you may need to
reach out to CrowdStrike support.

📝

🟢note

For more information on configuring data
collection from CrowdStrike APIs, see the
CrowdStrike Documentation.

📝

🟢note

Ensure that you save the SECRET value
because this is the only time that it is displayed.

3.2.3.14. CrowdStrike Falcon Data Replicator 

3.2.3.14.1. Ingest raw EDR events from
CrowdStrike Falcon Data Replicator 

☑️

🟣pr…

Ensure that your organization has a license for
the CrowdStrike Falcon Data Replicator (FDR).
Ensure that CrowdStrike FDR is enabled.
CrowdStrike FDR can only be enabled by
CrowdStrike Support. If CrowdStrike FDR is not
enabled, submit a support ticket through the
CrowdStrike support portal.
Follow these steps to check if CrowdStrike FDR
is...

📝

🟢note

CrowdStrike can provide multiple streams. It
can only be read once per stream.
For more information on configuring data
collection from CrowdStrike via Falcon Data
Replicator, see CrowdStrike documentation.

📝

🟢note

Ensure that you copy the Secret, and store it in
a safe place. You will not be able to retrieve it
later. If you need a new secret, you must reset
the feed credentials.

📝

🟢note

CrowdStrike Falcon Data Replicator only
supports one FDR credential configuration.

📝

🟢note

Ensure that you save the SECRET value,
because this is the only time that it is displayed.
You can go back to this page later to copy the
other credentials, but you will not have access
to the secret again.

3.2.3.15. Databricks  3.2.3.15.1. How to onboard Databricks 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you turn on this feature, both the cloud and
region will be used for scanning, possibly
incurring cost and requiring adherence to
certain compliance policies.

3.2.3.16. Dropbox  3.2.3.16.1. Ingest logs and data from Dropbox 

☑️

🟣pr…

Set up an Advanced Dropbox plan.
Create a Dropbox Business admin account with
Security admin permissions, which is required to
authorize Cortex XSIAM to access the Dropbox
Business account and generate the OAuth 2.0
access token.

📝

🟢note

The Fetch Interval is non-configurable.

📝

🟢note

When the App Key field is empty, the here link
in the tooltip is disabled. When an incorrect
App Key is entered, clicking the link results in a
404 error.

📝

🟢note

Whenever you change the permissions of the
Dropbox app, we recommend that you
generate a new Access Code for the Dropbox
data collector instance so that the permissions
match the updates.

📝

🟢note

Event data is collected every 60 seconds with a
10 minute lag time.

📝

🟢note

Inventory data snapshots are collected every 10
minutes.

3.2.3.17. Elasticsearch Filebeat 

📝

🟢note

You can configure collecting container logs
from Google Kubernetes Engine using
Elasticsearch Filebeat with a Custom - Filebeat
based Collector or with a content pack
Integration. For more information, see Google
Kubernetes Engine.

3.2.3.17.1. Ingest logs from Elasticsearch Filebeat 

3.2.3.18. Forcepoint DLP 

3.2.3.19. Fortinet Fortigate 

3.2.3.20. Google Cloud Platform 

3.2.3.20.1. Ingest logs and data from a GCP
Pub/Sub 

📝

🟢note

When collecting flow logs, we recommend that
you include GKE annotations in your logs, which
enable you to view the names of the containers
that communicated with each other. GKE
annotations are only included in logs if
appended manually using the custom metadata
configuration in GCP. For more information, see
VPC Flow Logs Overview. In addition, to...

📝

🟢note

For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor and
Product fields in the GCP data collector
settings. Yet, when the values are blank in the...

📝

🟢note

For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor and
Product fields in the GCP data collector
settings. Yet, when the values are blank in the...

3.2.3.21. Google Workspace 

3.2.3.21.1. Ingest logs and data from Google
Workspace



📝

🟢note

For all types of data collected via the Admin
Reports API, except alerts and emails, the log
events are collected with a preset lag time as
reported by Google Workspace. For more
information on these lag times for the different
types of data, see Google Workspace Data
retention and lag times.

📝

🟢note

Spam emails from the compliance email
account, and from all other monitored email
accounts, are not collected.
Any draft emails written in the compliance
email account are collected by the Google
Workspace data collector, and are then
deleted even if the email was never sent.

📝

🟢note

For more information on the entire process, see
Perform Google Workspace Domain-Wide
Delegation of Authority.

📝

🟢note

You don't need to add permissions to the GCP
Project-org service account.

📝

🟢note

When collecting Google Workspace alerts with
other types of data, except emails, you need to
configure a service account in Google with the
applicable permissions to collect events from
the Google Reports API and alerts from the
Alert Center API. If you prefer to use different
service accounts to collect events and alerts
separately, you'll need to...

📝

🟢note

For more information on the Admin Reports API
scopes, see OAuth 2.0 Scopes for Google APIs.

📝

🟢note

For more information on the Gmail API scopes,
see OAuth 2.0 Scopes for Google APIs.

📝

🟢note

For more information about the events
collected from the various Google Reports, see
Google Workspace Reports API Documentation.

3.2.3.22. Google Kubernetes Engine 

📝

🟢note

It's also possible to use a Custom - Filebeat
based Collector to ingest logs related to file
activity on your endpoints and servers without
using the Cortex XDR agent. For more
information, see Elasticsearch Filebeat.

3.2.3.22.1. Ingest logs from Google Kubernetes
Engine  📝
🟢note

Cortex XSIAM supports logs in single line
format or multiline format. For more
information on handling messages that span
multiple lines of text in Elasticsearch Filebeat,
see Manage Multiline Messages.

3.2.3.23. HTTP log collector 

3.2.3.23.1. Set up an HTTP log collector to
receive logs 

📝

🟢note

-The Vendor and Product defaults to Auto-
Detect when the Log Format is set to CEF or
LEEF.
-For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor...

📝

🟢note

Each record cannot exceed 5 MB in size.

3.2.3.24. Kubernetes 

3.2.3.24.1. Onboard the Kubernetes Connector 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Runtime Security add-on.

📝

🟢note

This option is not supported for Fargate.

📝

🟢note

Enabling Realtime Protection installs the agent
on your Kubernetes clusters as a DaemonSet.

📝

🟢note

For Fargate, you must provide the cluster
resource identifier.
The format of the identifier is arn:aws:eks:
<region>:<account-id>:cluster/<cluster-name>.

📝

🟢note

Basic authentication is only supported in
Posture Management. If deploying Realtime
Protection, select None .

📝

🟢note

If you install the latest version but select the N-
1 strategy, this policy will take effect starting
from the next upgrade cycle (it will not
immediately downgrade your current
installation).

3.2.3.24.2. What's new in Kubernetes Connector? 

3.2.3.24.3. Supported Kubernetes distributions  📝

🟢note

In Google Container-Optimized OS release 100
and earlier, where the FANOTIFY EXEC flag is
not supported, the Kernel configuration may be
partial for the user mode agent to properly
function. In such cases, the agent will fallback
to asynchronous mode.
In RHCOS version 4.12 and earlier, the Kernel
configuration may be partial for the user mode
agent to...

3.2.3.25. Microsoft Azure 

3.2.3.26. Microsoft Defender for Endpoint Events 

3.2.3.26.1. Ingest raw EDR events from Microsoft
Defender for Endpoint 

☑️

🟣pr…

Ensure that you do the following tasks before
you begin configuring data collection.
Create an Azure Event Hub. For more
information, see Quickstart: Create an event
hub using Azure portal.
Create a resource group (optional if you
already have a resource group configured).
Create an Event Hubs namespace.
Create an event hub within the namespace....

📝

🟢note

The generic Cortex XSIAM Azure Event Hub
collector does not offer full functionality for
EDR data (such as stitching), and is therefore
not suitable for EDR data ingestion.

📝

🟢note

If you select all event types and leave Event-
Hub name empty, an event hub will be created
for each category in the selected namespace. If
you are not using a Dedicated Event Hubs
ClusterEvent Hub, namespaces have a limit of
10 Event Hubs.

3.2.3.27. Microsoft Office 365  3.2.3.27.1. Ingest logs from Microsoft Office 365 

📝

🟢note

Ingesting Microsoft Entra ID (formerly known as
Azure AD) authentication and audit events from
Microsoft Graph API requires a Microsoft Azure
Premium 1 or Premium 2 license. Alternatively, if
the directory type is Azure AD B2C, the sign-in
reports are accessible through the API without
any additional license requirement.
To ingest email logs and data...

📝

🟢note

When auditing is turned off from the default
setting, you need to first turn on auditing for
your organization to collect Microsoft Office
365 audit events from the Management Activity
API. Log duplication of up to 5% in Microsoft
products is considered normal. In some cases,
such as login to a portal using MFA, two log
entries are recorded by design.

📝

🟢note

To address Azure reporting latency, there is a
10-minute latency period for Cortex XSIAM to
receive Azure AD logs.

📝

🟢note

You can also implement the corresponding
Cortex Data Model (XDM) mappings for these
Microsoft Graph Security API v2 alerts using
Cortex Marketplace via the Microsoft Graph
Security content pack.

📝

🟢note

For more information, see the Office 365
Management Activity API schema.

📝

🟢note

In FedRAMP environments, Azure sign-in logs
are not supported, due to vendor technical
constraints.

📝

🟢note

Use this option when you don't want to grant
permissions for Azure AD Authentication and
Azure AD Audit.

3.2.3.28. Microsoft Office 365 (email) 

3.2.3.28.1. Ingest logs and data from Microsoft
365 

🔒

🟣c…

Email content visibility and licensing: Email
subjects and bodies are stored in an encrypted
format to ensure data privacy. To view this
content or generate alerts for it, an Email
Security module license is required.
Without the license: Sensitive email content
(subject, body, and attachments) remains
encrypted and is not accessible for viewing or...

☑️

🟣pr…

A user account with the Microsoft Azure
Account Administrator role is required to set up
a new Microsoft 365 email collector.
The following Microsoft Graph API permissions
are required:
Mailbox access (read-write)
Read and write mail in all mailboxes
Read contacts in all mailboxes
Read all user mailbox settings
User information, groups,...

📝

🟢note

For other logs from Microsoft Office 365, use
the Office 365 data collector. For more
information, see Ingest logs from Microsoft
Office 365.

3.2.3.29. Microsoft 365 (Posture)  3.2.3.29.1. How to onboard Microsoft 365 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

You have generated a Globally Unique Identifier
(GUID), also known as a Universally Unique
Identifier (UUID). You will need this ID for the
tenant you want to use for the Microsoft 365
instance.
In order to use Microsoft 365, you must be
registered with Microsoft Azure.

3.2.3.30. Okta  3.2.3.30.1. Ingest logs and data from Okta  ☑️

🟣pr…

Administrator privileges: Your Okta user must
have a role capable of creating API tokens,
such as Read-only Administrator, Super
Administrator, or Organization Administrator.
For more information, see the Okta
Administrators Documentation.

3.2.3.31. OneLogin  3.2.3.31.1. Ingest logs and data from OneLogin 

📝

🟢note

Event data is collected every 30 seconds.

📝

🟢note

Inventory data snapshots are collected every 10
minutes.

3.2.3.32. Oracle Cloud Infrastructure 

3.2.3.33. PingFederate 

3.2.3.34. PingOne 

3.2.3.34.1. Ingest authentication logs and data
from PingOne  🧭
➡️n…

Reporting → Subscriptions → Add Subscription

3.2.3.35. Proofpoint Targeted Attack Protection 

3.2.3.35.1. Ingest logs from Proofpoint Targeted
Attack Protection 

3.2.3.36. Salesforce.com 

3.2.3.36.1. Ingest logs and data from
Salesforce.com



☑️

🟣pr…

Cortex XSIAM:
To manage collection integration in Cortex
XSIAM, ensure that you have the privilege to
View/Edit Log Collections (for example,
Instance Administrator).
Cortex XSIAM:
To manage collection integration in Cortex
XSIAM, ensure that you have the privilege to
View/Edit Log Collections (for example,
Instance...

📝

🟢note

For more detailed reference information, see
Configure a Connected App for the OAuth 2.0
Client Credentials Flow.
Unlike other data collector setups, in this case,
the setup includes obtaining an OAuth 2.0 code
from Salesforce.com, and this code is only valid
for 15 minutes. Therefore, make sure that you
enable the data collector within 15 minutes of...

📝

🟢note

When these options are cleared, only these
data types will be omitted from collection. All
other data will be collected as usual.

3.2.3.37. SentinelOne DeepVisibility 

3.2.3.37.1. Ingest raw EDR events from
SentinelOne DeepVisibility 

☑️

🟣pr…

The SentinelOne DeepVisibility logs that will be
collected by your dedicated Amazon S3 bucket
must adhere to the following guidelines:
Each log file must use the 1 log per line format
as multi-line format is not supported.
The log format must be compressed as gzip or
uncompressed.
For best performance, we recommend limiting
each file size to up...

📝

🟢note

It is your responsibility to define a retention
policy for your Amazon S3 bucket by creating a
Lifecycle rule on the Management tab. We
recommend setting the retention policy to at
least 7 days to ensure that the data is retrieved
under all circumstances.

📝

🟢note

Ensure that you create your Amazon S3 bucket
and Amazon SQS queue in the same region.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

📝

🟢note

If you receive an error when trying to save your
changes, check that the permissions are set up
correctly, and fix them if necessary.

📝

🟢note

It is the responsibility of your organization to
ensure that the user who creates the access key
is assigned the relevant permissions. Otherwise,
this can cause the process to fail with errors.

📝

🟢note

For more information, see Managing access
keys for IAM users.

📝

🟢note

For more information on granting permissions
to publish messages to an SQS queue, see
Granting permissions to publish event
notification messages to a destination.

3.2.3.38. ServiceNow CMDB  3.2.3.38.1. Ingest data from ServiceNow CMDB 

3.2.3.39. Windows DHCP via Elasticsearch

Filebeat 

3.2.3.39.1. Ingest logs from Windows DHCP using
Elasticsearch Filebeat 

📝

🟢note

To avoid formatting issues in filebeat.yml, we
recommend that you edit the text file inside the
user interface, instead of copying it and editing
it elsewhere. Validate the syntax of the YML file
before you finish creating the profile.

📝

🟢note

For more information on configuring the
filebeat.yml file, see the Elastic Filebeat
Documentation.

📝

🟢note

To avoid formatting issues in your filebeat.yml,
we recommend that you use the download
example file to make your customizations. Do
not copy and paste the code syntax examples
provided later in this procedure into your file.

📝

🟢note

The tokenizer definition is dependent on the
Windows server version that you are using as
the log format differs.
-For platforms earlier than Windows Server
2008, use "%{id},%{date},%{time},%
{description},%{ipAddress},%{hostName},%
{macAddress}"
-For Windows Server 2008 and 2008 R2, use "%
{id},%{date},%{time},%{description},%
{ipAddress},%{hostName},%{mac...

3.2.3.40. Workday  3.2.3.40.1. Ingest report data from Workday 

☑️

🟣pr…

Create an Integration System User that is
designated to access the custom report from
Workday for data collection in Cortex XSIAM.
Create an Integration System Security Group
for the Integration System User created in Step
1 for accessing the report. When setting this
group ensure to define the following:
Type of Tenanted Security Group: Select...

📝

🟢note

Any user with permissions to view issues and
cases can view the Workday data.

📝

🟢note

For more information on completing any of the
prerequisite steps, see the Workday
documentation.

📝

🟢note

The Business Object changes depending on the
Data Source selected.

📝

🟢note

Cortex XSIAM uses a structured schema when
integrating Workday data. To get the best
Analytics results, specify all the fields marked
with an asterisk from the recommended schema.
workday_user_id*
full_name*
workday_manager_user_id*
manager*
worker_type*
position_title*
department*
private_email_address*
business_email_address*
employment_start_date*
em...

3.2.3.41. Snowflake  3.2.3.41.1. How to onboard Snowflake 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

In order to use Snowflake, you must be
registered with one of these cloud providers:
Amazon AWS, Microsoft Azure, or Google
Cloud Platform (GCP).
Ensure you have the necessary account
permissions to onboard. It is recommended to
use Account Admin as the role for the
onboarding.

📝

🟢note

The account identifier can be found using the
user information at the bottom left. Hover over
the account you wish to onboard and select
the copy option at the top right. The account
identifier is usually of the format:
(organization).[account]

3.2.3.42. Zscaler Internet Access 

3.2.3.43. Zscaler Private Access 

3.2.4. Cloud service provider (CSP) onboarding 

3.2.4.1. Ingest cloud assets  📝

🟢note

The cloud accounts being onboarded must be
owned by the customer performing the
onboarding process.

3.2.4.2. Onboard Amazon Web Services 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Runtime Security or Cloud Posture Security
add-ons.
For Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses, see Onboard Amazon Web Services
with basic configuration.

☑️

🟣pr…

Ensure you have access to AWS Management
Console.
Ensure you have the Required AWS permissions.

📝

🟢note

Scanning with an outpost may require
additional CSP permissions and may incur
additional CSP costs.

📝

🟢note

When onboarding an AWS organization or
organizational unit (OU), Cortex XSIAM creates
IAM resources in every account within that
organization or OU. This occurs even if you
choose to exclude specific accounts from
being scanned. While excluded accounts will
not be scanned and will not appear in the asset
inventory, the IAM resources may still be...

3.2.4.2.1. Onboard Amazon Web Services with

basic configuration 

🔒

🟣c…

Onboarding Amazon Web Services (AWS) using
the basic configuration is included with Cortex
XSIAM NG SIEM, Cortex XSIAM Enterprise, and
Cortex XSIAM Enterprise+ licenses. For
onboarding AWS with a Cortex XSIAM Premium
license, see Onboard Amazon Web Services.

☑️

🟣pr…

Ensure you have access to AWS Management
Console.
Ensure you have the Required AWS permissions.

📝

🟢note

When onboarding an AWS organization or
organizational unit (OU), Cortex XSIAM creates
IAM resources in every account within that
organization or OU. This occurs even if you
choose to exclude specific accounts from
being scanned. While excluded accounts will
not be scanned and will not appear in the asset
inventory, the IAM resources may still be...

3.2.4.2.2. Manually upload template to AWS 

☑️

🟣pr…

Before you begin, ensure you have:
An AWS account
Access to AWS Management Console
Permission to create a stack and its resources in
AWS CloudFormation

📝

🟢note

You must ensure that the KMS key region and
the SNS topic region are the exact same as the
AWS region where you are deploying the
CloudFormation stack.

3.2.4.2.3. Configure AWS integration instances
and monitor integration instance health 

📝

🟢note

If you have not yet onboarded your cloud
integration, see Ingest cloud assets.

📝

🟢note

Currently, automation permission errors or
missing automation permissions do not affect
the Automation health status. You can view any
permission errors or missing permissions in the
the Permissions health status.

3.2.4.3. Onboard Google Cloud Platform 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Runtime Security or Cloud Posture Security
add-ons.
For Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses, see Onboard Google Cloud Platform
with basic configuration.

☑️

🟣pr…

Ensure you have cccess to Google Cloud
Console.
Ensure you have an admin user with the
required admin GCP permissions.
Ensure you have the following APIs in the GCP
project you are onboarding:
Cloud Resource Manager API
Identity and Access Management (IAM) API
Cloud Pub/Sub API (if audit logs are enabled)
If you plan on enabling Automation as...

📝

🟢note

Scanning with an outpost may require
additional CSP permissions and may incur
additional CSP costs.

📝

🟢note

If you want to connect to your GCP Workspace,
you must first complete onboarding with the
option disabled. Once the GCP cloud instance
is created, perform the steps detailed in
Connect Google Workspace with your GCP
cloud instance.

3.2.4.3.1. Onboard Google Cloud Platform with
basic configuration 

🔒

🟣c…

Onboarding Google Cloud Platform (GCP)
using the basic configuration is included with
Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses. For onboarding GCP with a Cortex
XSIAM Premium license, see Onboard Google
Cloud Platform.

☑️

🟣pr…

Ensure you have cccess to Google Cloud
Console.
Ensure you have an admin user with the
required admin GCP permissions.
Ensure you have the following APIs in the GCP
project you are onboarding:
Cloud Resource Manager API
Identity and Access Management (IAM) API
Cloud Pub/Sub API (if audit logs are enabled)
If you plan on enabling Automation as...

3.2.4.3.2. Manually upload template to GCP 

☑️

🟣pr…

Before you begin, ensure you have:
A GCP account.
Permission to create the required resources in
Google Cloud Deployment Manager.
Installed Terraform on your local machine. You
can download Terraform from the official
Terraform website and follow the installation
instructions for your operating system.
Installed the GCP gcloud CLI tool.
Reviewed the...

📝

🟢note

The directory you create must be a
subdirectory of the home directory.

👀

🟠i…

You must not delete or move the Terraform files
from this folder. It will prevent you from being
able to edit your cloud instance in the future.

3.2.4.3.3. Connect Google Workspace with your
GCP cloud instance 

☑️

🟣pr…

Ensure you have the Super Admin role in
Google Workspace.

☑️

🟣pr…

Ensure you have the organization ID of the
Google Workspace you want to connect:
Log in to your Google Admin Console. and
navigate to Account → Account settings →
Profile. Next to Customer ID is your
organization ID.
Ensure you have the organization ID of the
Google Workspace you want to connect:
Log in to your Google Admin Console. and
navigate...

3.2.4.3.4. Configure GCP integration instances
and monitor integration instance health 

📝

🟢note

If you have not yet onboarded your cloud
integration, see Ingest cloud assets.

📝

🟢note

Currently, automation permission errors or
missing automation permissions do not affect
the Automation health status. You can view any
permission errors or missing permissions in the
the Permissions health status.

3.2.4.3.5. Monitor GCP resources inside service
perimeters

 📝

🟢note

Each GCP cloud instance is assigned a scope
within GCP. If the scope, whether it be
organization, folder, or project, includes any
projects with a service perimeter, this
procedure must be performed for that cloud
instance to authorize Cortex XSIAM to scan the
resources in the perimeter.

3.2.4.4. Onboard Microsoft Azure 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Runtime Security or Cloud Posture Security
add-ons.
For Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses, see Onboard Microsoft Azure with
basic configuration.

☑️

🟣pr…

Ensure you have a Microsoft Azure subscription.
Ensure you have the admin permissions required
to onboard Microsoft Azure or the built-in
Security Administrator role.
Obtain the tenant ID and subscription ID. You
can view these in the Microsoft Azure Portal in
Management groups.

3.2.4.4.1. Onboard Microsoft Azure with basic

configuration 

🔒

🟣c…

Onboarding Microsoft Azure using the basic
configuration is included with Cortex XSIAM
NG SIEM, Cortex XSIAM Enterprise, and Cortex
XSIAM Enterprise+ licenses. For onboarding
Microsoft Azure with a Cortex XSIAM Premium
license, see Onboard Microsoft Azure.

☑️

🟣pr…

Ensure you have a Microsoft Azure subscription.
Ensure you have the admin permissions required
to onboard Microsoft Azure or the built-in
Security Administrator role.
Obtain the tenant ID and subscription ID. You
can view these in the Microsoft Azure Portal in
Management groups.

3.2.4.4.2. Finalize Microsoft Azure onboarding
by executing the authentication template 

☑️

🟣pr…

Before you begin, ensure you have:
An Azure subscription.
A user with the required permissions for the
relevant scope (subscription, management
group, tenant). We recommend you create a
dedicated role.
Tenant ID and subscription ID. You can view
these in Microsoft Azure Portal in Management
groups.

Installed Terraform on your local machine. You
can...

☑️

🟣pr…

Before you begin, ensure you have:
An Azure subscription.
A user with the required permissions for the
relevant scope (subscription, management
group, tenant). We recommend you create a
dedicated role.
Tenant ID and subscription ID. You can view
these in Microsoft Azure Portal in Management
groups.
Installed the Azure CLI tool.
Authorization to create...

☑️

🟣pr…

Before you begin, ensure you have:
An Azure subscription.
A user with the required permissions for the
relevant scope (subscription, management
group, tenant). We recommend you create a
dedicated role.
Tenant ID and subscription ID. You can view
these in Microsoft Azure Portal in Management
groups.
Installed the Azure CLI tool.
Authorization to create...

👀

🟠i…

Do not delete or move the Terraform files from
this folder. It will prevent you from being able
to edit your cloud instance in the future.

3.2.4.4.3. Configure Azure integration instances
and monitor integration instance health 

📝

🟢note

If you have not yet onboarded your cloud
integration, see Ingest cloud assets.

📝

🟢note

Currently, automation permission errors or
missing automation permissions do not affect
the Automation health status. You can view any
permission errors or missing permissions in the
the Permissions health status.

3.2.4.5. Onboard Oracle Cloud Infrastructure 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Runtime Security or Cloud Posture Security
add-ons.
For Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses, see Onboard Oracle Cloud
Infrastructure with basic configuration.

☑️

🟣pr…

Ensure you have access to the Oracle Cloud
Infrastructure console
Permissions for all of the following are required:
Creation of identity groups (for more
information, refer to Managing Groups)
Policies (for more information, refer to How
Policies Work)
Tag namespaces in the root compartment (for
more information, refer to Tags and Tag
Namespace...

3.2.4.5.1. Onboard Oracle Cloud Infrastructure

with basic configuration 

🔒

🟣c…

Onboarding Oracle Cloud Infrastructure (OCI)
using the basic configuration is included with
Cortex XSIAM NG SIEM, Cortex XSIAM
Enterprise, and Cortex XSIAM Enterprise+
licenses. For onboarding OCI with a Cortex
XSIAM Premium license, see Onboard Oracle
Cloud Infrastructure.

☑️

🟣pr…

Ensure you have access to the Oracle Cloud
Infrastructure console
Permissions for all of the following are required:
Creation of identity groups (for more
information, refer to Managing Groups)
Policies (for more information, refer to How
Policies Work)
Tag namespaces in the root compartment (for
more information, refer to Tags and Tag
Namespace...

3.2.4.5.2. Manually upload template to OCI  ☑️

🟣pr…

Before you begin, ensure you have:
An Oracle Cloud Infrastructure account and
the tenancy OCID.
Permission to deploy a custom template and
create its resources in OCI.
Installed Terraform on your local machine. You
can download Terraform from the official
Terraform website and follow the installation
instructions for your operating system.
Installed...

3.2.4.5.3. Configure the OCI connector for log
collection 

3.2.4.6. Manually connect a cloud instance 

3.2.4.7. Edit your onboarded CSP configuration  👀

🟠i…

When using Terraform authentication
templates, you must execute the updated
Terraform template from the same folder where
the original Terraform template was executed.

3.2.4.8. Outposts 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM product that has the
Cloud Runtime Security add-on.

👀

🟠i…

Outpost scan is an alternative to the
recommended standard cloud scan. Cloud scan
is recommended because it is fully managed by
Palo Alto Networks and incurs no compute
costs for your organization. Outpost scan is an
advanced deployment model reserved for
specific data residency or architectural
requirements.

3.2.4.8.1. Outpost fundamentals and planning 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM product that has the
Cloud Runtime Security add-on.

📝

🟢note

Before you create your outpost, verify that
your internet connection is active. An active
internet connection is necessary for the
notification to be sent to Cortex XSIAM to
create the new outpost.

👀

🟠i…

While outposts provide maximum control over
the scanning environment, cloud scan mode is
the recommended default for most
organizations.

🧭

➡️n…

Before onboarding your Cortex XSIAM with the
cloud service provider (CSP) onboarding
wizard, create an outpost by navigating to
Settings → Data Sources & Integrations →
Outposts

Settings → Data Sources & Integrations → Add
New

View and manage existing outposts by
navigating to Settings → Data Sources &
Integrations → Outposts

3.2.4.8.2. Create an outpost 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM product that has the
Cloud Runtime Security add-on.

☑️

🟣pr…

Before you begin, ensure you have:
An AWS account
Permission to create a stack and its resources in
AWS
Installed Terraform on your local machine. You
can download Terraform from the official
Terraform website and follow the installation
instructions for your operating system.
Installed the AWS CLI tool and configured your
profile with the aws...

☑️

🟣pr…

Before you begin, ensure you have:
A GCP account
Permission to create the required resources in
Google Cloud Deployment Manager
Installed Terraform on your local machine. You
can download Terraform from the official
Terraform website and follow the installation
instructions for your operating system.
Installed the GCP gcloud CLI tool

☑️

🟣pr…

Before you begin, ensure you have:
An active Azure subscription.
Installed the Azure CLI tool.
Permission to deploy a custom template and
create its resources in Microsoft Azure
("Owner" or "Contributor" on the designated
outpost subscription scope, and Active
Directory "Cloud Application Administrator" or
"Application Administrator" privileged...

📝

🟢note

Verify that your internet connection is active.
An active internet connection is necessary for
notifications to be sent to Cortex XSIAM for
creating the new outpost. If you are unable to
establish an internet connection, contact
customer support for a manual workaround.

📝

🟢note

When creating an outpost for a specific Azure
subscription, the outpost account must be in
the same Azure organization as the monitored
subscriptions.

👀

🟠i…

While outposts provide maximum control over
the scanning environment, cloud scan mode is
the recommended default for most
organizations. For details, see When to choose
outpost scan.

🧭

➡️n…

Start the outpost creation wizard by navigating
to Settings → Data Sources & Integrations →
Outposts and clicking New Outpost

A new outpost is created in pending status and
can be viewed in the Outpost page at Settings
→ Data Sources & Integrations → Outposts

3.2.4.9. Introduction to Terraform for Cloud

service provider (CSP) onboarding 

👀

🟠i…

Always run these commands in the same folder
where the original .tf files and .terraform folder
live—this is where the state is stored.

👀

🟠i…

This .tfstate state file is critical because it is
needed by the terraform destroy command to
clean up created resources. It is critical that
you never delete this file.

3.2.4.10. Container Registry Scanning 

3.2.4.10.1. Overview of container registry
scanning 

3.2.4.10.1.1. Registry Components 

3.2.4.10.1.2. How Container Registry Scanning
Works



3.2.4.10.2. Configure registry scanning for cloud
accounts  ☑️

🟣pr…

Ensure that you have performed the all steps
till Additional Security Capabilities as listed in
the onboarding wizard for the required CSP:
Onboard Amazon Web ServicesOnboard
Amazon Web Services
Onboard Google Cloud PlatformOnboard
Google Cloud Platform
Onboard Microsoft AzureOnboard Microsoft
Azure
Onboard Oracle Cloud InfrastructureOnboard
Oracle...

3.2.4.10.3. Modify the container registry
scanning scope 

3.2.4.10.4. Scan re-evaluation process 

3.2.4.10.5. Connect Docker Hub registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.

☑️

🟣pr…

Set up and configure Broker VM
Configure High Availability Cluster

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

3.2.4.10.5.1. Manage a Docker Hub connector  📝

🟢note

If you selected Scan with Broker VM mode, you
can't change to a different scan mode (such as
Cloud Discovery or Scan with Outpost) when
you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.10.6. Connect Docker V2 compliant
container registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.
Outposts

☑️

🟣pr…

Ensure one of the following is configured:
Set up and configure Broker VM.
Configure High Availability Cluster.

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

3.2.4.10.6.1. Manage a Docker V2 connector  📝

🟢note

If you selected Scan with Broker VM mode, you
can't change to a different scan mode (such as
Cloud Discovery or Scan with Outpost) when
you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.10.7. Connect GitLab container registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.

☑️

🟣pr…

Set up and configure Broker VM
Configure High Availability Cluster

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

📝

🟢note

When both the group ID and project ID are
provided, the system retrieves container images
from all projects within the specified group as
well as from the specified project.
If neither the group ID nor the project ID is
provided, the system retrieves container images
from all registries (across all groups and
projects) accessible to the authenticated...

3.2.4.10.7.1. Manage a Gitlab Container Registry
connector  📝
🟢note

If you selected Scan with Broker VM mode, you
can't change to a different scan mode (such as
Cloud Discovery or Scan with Outpost) when
you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.10.8. Connect Harbor registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.

☑️

🟣pr…

Ensure one of the following is configured:
Set up and configure Broker VM.
Configure High Availability Cluster.

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

3.2.4.10.8.1. Manage a Harbor connector  📝

🟢note

If you selected Scan with Broker VM mode, you
can't change to a different scan mode (such as
Cloud Discovery or Scan with Outpost) when
you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.10.9. Connect JFrog container registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.

☑️

🟣pr…

Set up and configure Broker VM
Configure High Availability Cluster

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

3.2.4.10.9.1. Manage a JFrog connector  📝

🟢note

If you selected Scan with Broker VM mode, you
can't change to a different scan mode (such as
Cloud Discovery or Scan with Outpost) when
you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.10.10. Connect Sonatype Nexus registry 

☑️

🟣pr…

Ensure an Outpost is connected to your tenant.
Outposts

☑️

🟣pr…

Ensure one of the following is configured:
Set up and configure Broker VM.
Configure High Availability Cluster.

📝

🟢note

If you are using a CA certificate, enter the
server IP address instead of the registry url.

📝

🟢note

If you choose Azure as the Cloud Provider, you
must also select the Tenant Id. The Tenant Id is
required to approve Cortex as an enterprise
application in your Azure tenant.

📝

🟢note

If you choose Azure as the cloud provider, only
Outposts associated with the selected tenant
ID are displayed.

📝

🟢note

If you are using a CA certificate, enter the
server IP address instead of the registry URL.

📝

🟢note

The list of Broker VMs displays only VMs that
support registry scanning.
The list of high-availability Clusters displays
only clusters that contain at least one VM
supporting registry scanning.
The registry scanning status for each VM
appears in brackets if it was previously
activated for that specific VM.

📝

🟢note

If you are using a CA certificate, enter the
server IP address instead of the registry URL.

3.2.4.10.10.1. Manage a Sonatype connector  📝

🟢note

If you had selected Scan with Broker VM mode,
you can't change to a different scan mode
(such as Cloud Discovery or Scan with
Outpost) when you edit the instance.
When editing an instance configured for Scan
with Broker VM, you must re-enter your
authentication credentials, including Username,
Password, and CA certificate.

3.2.4.11. Cloud service provider permissions 

3.2.4.11.1. Amazon Web Services provider
permissions 

3.2.4.11.2. Google Cloud Platform provider
permissions 

3.2.4.11.3. Microsoft Azure provider permissions 

3.2.4.11.4. Oracle Cloud Infrastructure provider
permissions 

3.2.5. Generic on-premise data collectors 

3.2.5.1. Broker VM data collector applets 

3.2.5.1.1. Activate Apache Kafka Collector 

☑️

🟣pr…

Apache Kafka version 2.5.1 and above.
Kafka cluster set up on premises, from which
the data will be ingested.
Privileges to manage Broker Service
configuration, such as Instance Administrator
privileges.
Create a user in the Kafka cluster with the
necessary permissions and the following
authentication details:
Broker Certificate and Private Key for...

📝

🟢note

For CEF and LEEF logs, Cortex XSIAM takes the
vendor and product names from the log itself,
regardless of what you configure on this page.

3.2.5.1.2. Activate Cortex Network Scanner 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with an
active Cortex XSIAM NG SIEM and Cortex
XSIAM Enterprise license that has the Exposure
Management add-on.

☑️

🟣pr…

Review the Cortex Network Scanner
deployment recommendations and complete
any prerequisites.
Set up and configure Broker VM

👀

🟠i…

The Cortex Network Scanner applet is not
supported for FedRAMP customers.
Cortex Network Scanner does not support high
availability (HA) Broker VM configuration.

3.2.5.1.3. Activate CSV Collector 

☑️

🟣pr…

Set up and configure Broker VM.
Ensure that you share the applicable CSV files.
Know the complete file path for the Windows
directory.

📝

🟢note

When you implement a wildcard file search,
ensure that the CSV files share the same
columns and header rows as all other logs that
are collected from the CSV files to create a
single dataset.

📝

🟢note

The CSV Collector checks for new CSV files
every 10 minutes.

3.2.5.1.4. Activate Database Collector 

☑️

🟣pr…

Set up and configure Broker VM

📝

🟢note

The DB Collector does not support passwords
containing semicolons (;).

📝

🟢note

The reference data ingested using the DB
Collector is counted towards license utilization.

👀

🟠i…

When configuring the DB collector to work
with an Oracle database and enabling this
option, ensure the following steps are
completed for a successful connection:
Ensure you have the certificate of the Database
server.

Upload certificate to Broker CA Trust Store
(Conditional):
This step is only required if the Oracle server's
certificate is self-signed...

👀

🟠i…

The Database Collector applet supports a
single row size of up to 65 KB. Ensure your
source data does not exceed this limit per
record to avoid ingestion errors.

3.2.5.1.5. Activate DSPM Fileshare 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with a
Cortex XSIAM NG SIEM and Cortex XSIAM
Enterprise license that has the Cloud Posture
Security or Cloud Runtime Security add-on.

☑️

🟣pr…

Set up and configure Broker VM
Know the complete path to the files and
folders that you want Cortex XSIAM to monitor.
Necessary user permissions to access the
network shares. For the SMB connection type,
you need the user name and password.

📝

🟢note

The applet list displays only the applets for
which you have permissions.

📝

🟢note

By default, all configured connections are
saved.

📝

🟢note

For details regarding the connection fields, see
the table above under File Share Connection.

📝

🟢note

You can add multiple connections under a
single instance of the DSPM Fileshare applet by
returning to the File Share Connection screen
and clicking Add Connection. Each new
connection can be of either the NFS or SMB
connection type.

3.2.5.1.6. Activate Files and Folders Collector 

☑️

🟣pr…

Set up and configure Broker VM.
Know the complete path to the files and
folders that you want Cortex XSIAM to monitor.
Ensure that the user permissions for the
network share include the ability to rename and
delete files in the folder that you want to
configure collection.

📝

🟢note

Cortex XSIAM only supports ingestion of files
encoded in UTF-8 format.

📝

🟢note

When using the Linux file share, including the
Linux share with NFS, a Username and Password
are not required, so these fields are grayed out
in the screen.

📝

🟢note

In Batch mode, the Files and Folders Collector
supports collecting logs from a network share
for a maximum file size of 500 MB.

📝

🟢note

When uploading JSON files, Cortex XSIAM only
parses the first level of nesting and only
supports single line JSON format, such that
every new line means a separate entry.

📝

🟢note

Use this option only in cases where your files
contain some sort of "header" lines, such as a
general description, an introduction, a
disclaimer, or similar, and you want to skip
ingesting them. The Lines to Skip are not part of
the file format. For example, in CSV files, there
is no need to skip lines.

📝

🟢note

When the storing method is Replace, the
maximum size for the total data to be imported
into a lookup dataset is 30 MB each time the
data is fetched.
The inventory data ingested using the Files and
Folders collector is counted towards license
utilization.
When you use a JOINT function with a lookup
table in a query or correlation rule, make sure
you...

📝

🟢note

You can't specify a file name that's the same as
a system file name.
The name of a dataset created from a tsv file
must always include the extension. If the
original file name is mrkdptusrsnov23.tsv, you
can name save the dataset with the name
marketing_dept_users_Nov_2023.tsv.

📝

🟢note

The Vendor and Product defaults to Auto-
Detect when the Log Format is set to CEF or
LEEF.

3.2.5.1.7. Activate FTP Collector 

☑️

🟣pr…

Set up and configure Broker VM.
Ensure that the user permissions for the FTP,
SFTP, or FTPS include the ability to rename and
delete files in the folder that you want to
configure collection.
When setting up an FTPS Collector with a
server using a Self-signed certificate, you must
upload the certificate first to the Broker VM as
a Trusted CA...

📝

🟢note

When configuring an SFTP connection, Cortex
XSIAM expects the private key to be in the RSA
format that is included in the -----BEGIN RSA
PRIVATE KEY----- tag. Cortex XSIAM does not
support providing the private key in the
OpenSSH format from the -----BEGIN
OPENSSH PRIVATE KEY----- tag.
When using ssh-keygen using a Mac, you get
the OpenSSH format by...

📝

🟢note

When uploading JSON files, Cortex XSIAM only
parses the first level of nesting and only
supports single line JSON format, such that
every new line means a separate entry.

📝

🟢note

Use this option only in cases where your files
contain some sort of "header" lines, such as a
general description, an introduction, a
disclaimer, or similar, and you want to skip
ingesting them. The Lines to Skip are not part of
the file format. For example, in CSV files, there
is no need to skip lines.

📝

🟢note

The Vendor and Product defaults to Auto-
Detect when the Log Format is set to CEF or
LEEF.

3.2.5.1.8. Activate Local Agent Settings 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that includes
endpoints or Cortex Cloud Runtime Security.

📝

🟢note

When routing traffic through a Broker VM
proxy that sits behind a firewall, you may
experience intermittent agent disconnections if
the firewall is configured to drop challenge
ACK reset (RST) packets. For environments
using a Palo Alto Networks Next-Generation
Firewall (NGFW), see this Knowledge Base
article for details on managing this behavior
via...

📝

🟢note

This is assuming a standard hardware setup
with 2vCPU 8 GB memory.

📝

🟢note

Broker VMs can act as as a proxy for routing
XDR Collector traffic to the Cortex XSIAM
tenant. The Broker VM does not cache XDR
Collector installers.

📝

🟢note

When you install your XDR agents, you need to
configure the IP address of the Broker VM and
a port number during the installation. You can
use the default 8888 port or set a custom port.
You are not permitted to configure port
numbers between 0-1024 and 63000-65000, or
port numbers 4369, 5671, 5672, 5986, 6379,
8000, 9100, 15672, 25672. Additionally,...

👀

🟠i…

A FQDN must be configured for WEC and
Agent Installer and Content Caching to
function properly.

👀

🟠i…

You can only enable Agent Installer and
Content Caching, when in the Broker VM
Configuration, you've uploaded your signed
SSL Server Certificate and key and set the
FQDN. For more information, see the Agent
Installer and Content Caching requirements
explained above.

3.2.5.1.9. Activate NetFlow Collector 

☑️

🟣pr…

Set up and configure Broker VM

📝

🟢note

Since multiple network devices can send data
to a single NetFlow Collector, we recommend
that you configure a maximum of 50 NetFlow
Collectors per Broker VM applet, with a
maximum aggregated rate of approximately
50K flows per second (FPS) to maintain system
performance.

📝

🟢note

Since Cortex XSIAM reserves some port
numbers, it is best to select a port number that
is not in the range of 0-1024 (except for 514), in
the range of 63000-65000 or has one of the
following values: 4369, 5671, 5672, 5986, 6379,
8000, 8888, 9100, 15672, or 28672.

📝

🟢note

The options available change, according to the
set Source Network value.

3.2.5.1.10. Activate Network Mapper 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that includes
endpoints or Cortex Cloud Runtime Security.

☑️

🟣pr…

After you have configured and registered your
Broker VM, you can choose to activate the
Network Mapper application.

📝

🟢note

Each IP address range can receive multiple scan
requests based on it's availability.

📝

🟢note

IP address ranges are displayed according to
what you defined as your Network Parameters.

3.2.5.1.11. Activate Registry Scanner 

🔒

🟣c…

Requires the Cortex XSIAM Premium license or
any other XSIAM license with the Cloud Posture
Security or the Cloud Runtime Security add-on.

☑️

🟣pr…

To initialize registry scanning on your Broker
VM, you must first add the necessary data
connectors. For details, see:
Connect Docker Hub registry
Connect Docker V2 compliant container
registry
Connect GitLab container registry
Connect Harbor registry
Connect JFrog container registry
Connect Sonatype Nexus registry
To initialize registry...

📝

🟢note

You cannot activate the Registry Scanner
directly on a new or existing Broker VM. You
can only activate or deactivate existing
Registry Scanner applets. To activate or
deactivate existing applets, see Step 4 under
Verify Registry Scanner connection section.

3.2.5.1.12. Syslog Collector applet 

3.2.5.1.12.1. Activate Syslog Collector 

☑️

🟣pr…

Set up and configure Broker VM

📝

🟢note

Once configured, you cannot change the
Port/PROTOCOL. If you don't want to use a
data source, ensure to remove the data source
from the list as explained in Task 5.

📝

🟢note

The Vendor and Product defaults to Auto-
Detect when the Log Format is set to CEF or
LEEF.
For a Log Format set to CEF or LEEF, Cortex
XSIAM reads events row by row to look for the
Vendor and Product configured in the logs.
When the values are populated in the event log
row, Cortex XSIAM uses these values even if
you specified a value in the Vendor and...

📝

🟢note

The server certificate and private key pair is
expected in a PEM format.
Cortex XSIAM will notify you when your
certificates are about to expire.

📝

🟢note

Because some port numbers are reserved by
Cortex XSIAM , you must choose a port number
that is not:
In the range of 0-1024 (except for 514)
In the range of 63000-65000
Values of 4052, 4369, 5671, 5672, 5986, 6379,
8000, 8888, 9100, 15672, or 28672

📝

🟢note

CORELIGHT is not available for a UDP protocol.

3.2.5.1.12.2. Ingest logs from a Syslog receiver 

3.2.5.1.12.3. Check Point FW1/VPN1 

3.2.5.1.12.3.1. Ingest logs from Check Point
firewalls 

3.2.5.1.12.4. Cisco ASA firewalls and AnyConnect 

3.2.5.1.12.4.1. Ingest logs from Cisco ASA
firewalls and AnyConnect 

3.2.5.1.12.5. Corelight Zeek  3.2.5.1.12.5.1. Ingest logs from Corelight Zeek 

3.2.5.1.12.6. Forcepoint DLP  3.2.5.1.12.6.1. Ingest logs from Forcepoint DLP 

3.2.5.1.12.7. Fortinet Fortigate 

3.2.5.1.12.7.1. Ingest logs from Fortinet Fortigate
firewalls 

3.2.5.1.12.8. Next-Generation Firewall 

3.2.5.1.12.8.1. Ingest Next-Generation Firewall
logs using the Syslog collector 

3.2.5.1.12.9. PingFederate 

3.2.5.1.12.9.1. Ingest authentication logs from
PingFederate 

3.2.5.1.12.10. Zscaler Internet Access 

3.2.5.1.12.10.1. Ingest logs from Zscaler Internet
Access



3.2.5.1.12.11. Zscaler Private Access 

3.2.5.1.12.11.1. Ingest logs from Zscaler Private
Access



3.2.5.1.13. Activate Transporter 

🔒

🟣c…

This feature is included with a Cloud Runtime
Security, Cloud Posture Security, or Cortex
XSIAM Premium license.

☑️

🟣pr…

Permissions: To configure and manage
Transporter applet settings, you must have
permissions to manage Broker Service
configurations (such as an Instance
Administrator)
Set up and configure Broker VMSet up and
configure Broker VM
Confirm that your Broker is v 28 or above
Whitelist IP addresses to enable access to
Cortex XSIAM resources. The IP addresses...

⛔

🔴w…

The Transporter applet is not supported for
FedRAMP customers.

3.2.5.1.14. Activate Windows Event Collector 

☑️

🟣pr…

Set up and configure Broker VM
Broker VM version 8.0 and later
You have knowledge of Windows Active
Directory and Domain Controllers.
You must configure different settings related to
the FQDN where the instructions differ
depending on whether you are configuring a
standalone Broker VM or High Availability (HA)
cluster.
Standalone broker
A...

📝

🟢note

You can also activate the Windows Event
Collector on Windows Core. For more
information, see Activate Windows Event
Collector on Windows Core.

📝

🟢note

By default, Cortex XSIAM collects Palo Alto
Networks predefined Security events that are
used by the Cortex XSIAM detectors. Removing
the Security collector interferes with the
Cortex XSIAM detection functionality. Restore
to Default to reinstate the Security event
collection.

📝

🟢note

You must install the WEF certificate on every
Windows Server, whether DC or not, for the
WEFs that are supposed to forward logs to the
Windows Event Collector applet on the Broker
VM.

📝

🟢note

You must install the WEF certificate on every
Windows Server, whether DC or not, for the
WEFs that are supposed to forward logs to the
Windows Event Collector applet on the Broker
VM.

📝

🟢note

This step overrides any local policy settings.

📝

🟢note

You must type out the name, do not select the
name from the browse button.

📝

🟢note

If Windows Firewall is enabled on your event
forwarders, you will have to define an
outbound rule to enable the WEF to reach port
5986 on the WEC.

3.2.5.1.14.1. Activate Windows Event Collector
on Windows Core



☑️

🟣pr…

Set up and configure Broker VM
Broker VM version 8.0 and later
You have knowledge of Windows Active
Directory and Domain Controllers.
You must configure different settings related to
the FQDN where the instructions differ
depending on whether you are configuring a
standalone Broker VM or High Availability (HA)
cluster.
Standalone broker
A...

📝

🟢note

By default, Cortex XSIAM collects Palo Alto
Networks predefined Security events that are
used by the Cortex XSIAM detectors. Removing
the Security collector interferes with the
Cortex XSIAM detection functionality. Restore
to Default to reinstate the Security event
collection.

📝

🟢note

You must install the WEF certificate on every
Windows Server, whether DC or not, for the
WEFs that are supposed to forward logs to the
Windows Event Collector applet on the Broker
VM.

📝

🟢note

This step overrides any local policy settings.

📝

🟢note

You must type out the name, do not select the
name from the browse button.

📝

🟢note

If Windows Firewall is enabled on your event
forwarders, you will have to define an
outbound rule to enable the WEF to reach port
5986 on the WEC.

3.2.5.1.14.2. Renew WEC certificates 

📝

🟢note

You must install the WEF certificate on every
Windows Server, whether DC or not, for the
WEFs that are supposed to forward logs to the
Windows Event Collector applet on the Broker
VM.

📝

🟢note

You can see more than one
ca.wec.paloaltonetworks.com and
forwarder.wec.paloaltonetworks.com file from a
previous installation in the directory, so select
the file with the most extended Expiration Date.
You can verify that you are using the correct
certificate:
To verify the client certificate in the Personal →
Certificates folder is related to the...

📝

🟢note

Only perform this step under the following
conditions:
You have completed the WEF certification
renewal process for ALL clients in your
environment. Otherwise, events from the WEFs
that you did not install the new client
certificate will not be collected by the WEC.
You are approaching the WEC server CA
certificate expiration date, which is 2 years...

📝

🟢note

If this query does not display results with a
timestamp from after the renewal process, it
could indicate that the renewal process is not
complete, so wait a few minutes before running
another query. If you are still having a problem,
contact Technical Support.

👀

🟠i…

After you receive a notification for renewing
your WEC CA certificate, we recommend that
you do not add any new WEF clients until the
WEC certification renewal process is complete.
Events from these WEF clients that are added
afterwards will not be collected by the server
until the WEC certificates are renewed.

3.2.5.2. XDR Collectors 

📝

🟢note

Ingestion of log events larger than 5 MB is not
supported.

3.2.5.2.1. XDR Collector audit logs 

3.2.5.2.2. XDR Collector machine requirements
and supported operating systems 

3.2.5.2.3. Resources required to enable access
to XDR Collectors



📝

🟢note

Some of the IP addresses required for access
are registered in the United States. As a result,
some GeoIP databases do not correctly
pinpoint the location in which IP addresses are
used. All customer data is stored in your
deployment region, regardless of the IP address
registration and restricts data transmission
through any infrastructure to that...

📝

🟢note

Throughout this topic, <xsiam-tenant> refers to
the chosen subdomain of your Cortex XSIAM
tenant and <region> is the region in which your
Strata Logging Service is deployed.

3.2.5.2.4. Manage XDR Collectors 

3.2.5.2.4.1. XDR Collectors installation resource

for Windows and Linux  📝
🟢note

In some circumstances, such as after an XDR
Collectors upgrade, the configured settings in
the XML configuration file can be erased. Yet,
this won't affect the saved settings in the XDR
Collectors database.

3.2.5.2.4.2. Create an XDR Collector installation
package



📝

🟢note

XDR Collectors cannot be moved between
Cortex XSIAM managing servers. In this
situation, you need to uninstall the existing
collector, and then install a new collector using
an installation package from the new managing
server. For more information on uninstalling, see
Uninstall the XDR Collector.

📝

🟢note

Since Cortex XSIAM relies on the installation
package ID to approve XDR Collector
registration during install, it is not
recommended to delete the installation
package for any active on-premise collector
machines. Hiding the installation package will
remove it from the default list of available
installation packages, and can be useful to
eliminate...

3.2.5.2.4.3. Install the XDR Collector installation
package for Windows



3.2.5.2.4.3.1. Install the XDR Collector on

Windows using the MSI 

3.2.5.2.4.3.2. Install the XDR Collector on
Windows using Msiexec



3.2.5.2.4.4. Install the XDR Collector installation

package for Linux 

📝

🟢note

We recommend that you perform a Linux RPM
or Linux DEB installation.

📝

🟢note

If the XDR Collector does not connect to
Cortex XSIAM, verify your Internet connection
on the collector machine. If the XDR Collector
still does not connect, verify the installation
package has not been removed from the Cortex
XSIAM management console.

📝

🟢note

The XDR Collector does not support proxy
communication in environments where proxy
authentication is required.

👀

🟠i…

When performing a XDR Collector installation
or upgrade in Linux using a shell installer, the
/tmp folder cannot be marked as noexec.
Otherwise, the installation or upgrade fails. As a
workaround, before the installation or upgrade,
use the following command:

3.2.5.2.4.5. Configure the XDR Collector
upgrade scheduler  🧭
➡️n…

In Cortex XSIAM, select Settings →
Configurations → XDR Collectors →
Configuration

3.2.5.2.4.6. Set an application proxy for XDR
Collectors

 🧭

➡️n…

In Cortex XSIAM, select Settings →
Configurations → XDR Collectors →
Administration

3.2.5.2.4.7. Set an alias for an XDR Collector

machine  🧭
➡️n…

Settings → Configurations → XDR Collectors
→ Administration

3.2.5.2.4.8. Upgrade XDR Collectors  📝

🟢note

The XDR Collector keeps the name of the
original installation package after every
upgrade.

3.2.5.2.4.9. Uninstall the XDR Collector 

3.2.5.2.5. Define XDR Collector machine groups 

📝

🟢note

XDR Collectors only support IPv4 addresses.

📝

🟢note

Disconnecting Directory Sync in your Cortex
XSIAM deployment can affect existing
collector machine groups and policy rules
based on Active Directory properties.

3.2.5.2.6. About Cortex XDR Collector content

updates 

3.2.5.2.7. XDR Collector profiles 

3.2.5.2.7.1. Add an XDR Collector profile for
Windows



📝

🟢note

Ingestion of log events larger than 5 MB is not
supported.

📝

🟢note

Fileset validation is enforced. You must enable
at least one fileset in the module, because
filesets are disabled by default.
Cortex XSIAM collects all logs in either an
uncompressed JSON or text format.
Compressed files, such as the gzip format, are
not supported.
Cortex XSIAM supports logs in single line
format or multiline format. For more...

3.2.5.2.7.1.1. Ingest logs from Windows DHCP
using Elasticsearch Filebeat 

3.2.5.2.7.1.2. Ingest Windows DNS debug logs
using Elasticsearch Filebeat 

3.2.5.2.7.2. Add an XDR Collector profile for
Linux 

📝

🟢note

Ingestion of log events larger than 5 MB is not
supported.

📝

🟢note

Fileset validation is enforced. You must enable
at least one fileset in the module, because
filesets are disabled by default.
Cortex XSIAM collects all logs in either an
uncompressed JSON or text format.
Compressed files, such as the gzip format, are
not supported.
Cortex XSIAM supports logs in single line
format or multiline format. For more...

3.2.5.2.8. Apply profiles to collection machine
policies  🧭
➡️n…

Settings → Configurations → XDR Collectors
→ Policies → +Add Policy

3.2.5.2.9. XDR Collector datasets 

3.2.5.2.10. Troubleshoot XDR Collectors errors  📝

🟢note

For more information on creating correlation
rules to trigger collection health issues, see
How can I set up correlation rules to trigger
collection health issues?.

3.2.6. Palo Alto Networks integrations 

🔒

🟣c…

Data collection may require an add-on.

📝

🟢note

Roll-back of Strata Logging Service integration
migration is not supported.

3.2.6.1. About Palo Alto Networks integrations 

📝

🟢note

For Palo Alto Networks Integrations there is an
option to turn on or off the collection of URL
and File log types. For more information, see
Collecting URL and File log types.

📝

🟢note

Roll-back of Strata Logging Service integration
migration is not supported.

3.2.6.2. Next-Generation Firewall 

3.2.6.2.1. Ingest data from Next-Generation
Firewall 

☑️

🟣pr…

Ensure that you have completed the following
on the NGFW or Panorama side:
For Panorama only, ensure that the Panorama
Cloud Services plugin is installed.
Enable log forwarding profiles on firewall rules.
On the Cortex XSIAM side, ensure that you have
user role permissions for Data Collection >
Data Sources & Integrations.
Configuration of data...

📝

🟢note

Roll-back of Strata Logging Service integration
migration is not supported.

📝

🟢note

If your firewalls are located in a different
region, or bandwidth issues are encountered
due to large log size, you can ingest NGFW
logs in CEF format, using the Syslog collector.
However, the Syslog solution is not as powerful
nor as comprehensive as this data collector,
and should only be used when this data
collector cannot be used. For more...

📝

🟢note

In the following procedure, general information
is provided for NGFW and Panorama. For
detailed instructions, consult the
documentation for your specific devices and
Panorama version.

📝

🟢note

Cortex XSIAM does not validate your firewall
credentials, you must ensure the certificates or
PSK details have been updated in your firewalls
in order for data to stream.

📝

🟢note

It can take an hour or longer after connecting
the firewall in Cortex XSIAM until you start
seeing notifications that the certificate has
been approved, and that the logging service
license has appeared on the firewall.

📝

🟢note

IOC and BIOC issues are applicable on stitched
data only, and are not available on raw data.

👀

🟠i…

This cross-account support is limited to the
same SFDC hierarchy; it does not extend to
MSSP scenarios where the customer and
provider own separate ends of the solution.

💡

🔵tip

You can see an overview of ingestion status for
all log types, and a breakdown of each log type
and its daily consumption quota on the NGFW
Ingestion Dashboard.

3.2.6.2.2. Ingest Next-Generation Firewall logs
using the Syslog collector 

📝

🟢note

In the following procedure, general information
is provided for NGFW and Panorama. For
detailed instructions, consult the
documentation for your specific devices and
Panorama version, to ensure that you have
configured log forwarding correctly for all the
log types that you would like to forward to
Cortex XSIAM. The following steps only cover...

📝

🟢note

To avoid the possible effects of line formatting,
do not copy/paste the message formats
directly into the PAN-OS web interface. Instead,
paste into a text editor, remove any carriage
return or line feed characters, and then copy
and paste into the web interface.

📝

🟢note

From version 10.0 and later, the log format
documented for log types (Traffic, Threat, and
URL) exceeds the maximum supported 2048
characters in the Custom Log Format tab on
the firewall and Panorama. Select the CEF keys
and values to limit the number of characters to
2048, as per your requirements.

3.2.6.3. Ingest data from Prisma Access 

☑️

🟣pr…

Configuration of data ingestion from multiple
accounts requires Super User permissions in
both Cortex XSIAM tenant and Prisma Access
accounts.

📝

🟢note

Roll-back of Strata Logging Service integration
migration is not supported.

📝

🟢note

Cortex XSIAM does not validate your Prisma
Access account credentials. You must ensure
the account has been deployed in order for
data to stream.

3.2.6.4. Ingest logs from Prisma Access Browser 

3.2.6.5. Ingest detection data from Strata
Logging Service  📝
🟢note

IOC and BIOC issues are applicable on stitched
data only and are not available on raw data.

3.2.6.6. IoT Security 

3.2.6.6.1. Ingest alerts and assets from IoT
Security 

3.2.6.7. Collecting URL and File log types 

3.2.7. Cloud Posture and Runtime Security data
sources



🔒

🟣c…

These data sources are included with a Cortex
XSIAM Premium license. They are also included
with a Cortex XSIAM NG SIEM and Cortex
XSIAM Enterprise license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

3.2.7.1. How to onboard on-premise file shares
to Cortex Cloud Data Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Your data is scanned on the Broker VM itself,
and only the metadata and classification
results are transmitted from the on-premise
environment to Cortex XSIAM.

📝

🟢note

For information about activating the DSPM
Fileshare applet, see Activate DSPM Fileshare.

3.2.7.1.1. Activate DSPM Fileshare 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with a
Cortex XSIAM NG SIEM and Cortex XSIAM
Enterprise license that has the Cloud Posture
Security or Cloud Runtime Security add-on.

☑️

🟣pr…

Set up and configure Broker VM
Know the complete path to the files and
folders that you want Cortex XSIAM to monitor.
Necessary user permissions to access the
network shares. For the SMB connection type,
you need the user name and password.

📝

🟢note

The applet list displays only the applets for
which you have permissions.

📝

🟢note

By default, all configured connections are
saved.

📝

🟢note

For details regarding the connection fields, see
the table above under File Share Connection.

📝

🟢note

You can add multiple connections under a
single instance of the DSPM Fileshare applet by
returning to the File Share Connection screen
and clicking Add Connection. Each new
connection can be of either the NFS or SMB
connection type.

3.2.7.2. How to onboard Databricks 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you turn on this feature, both the cloud and
region will be used for scanning, possibly
incurring cost and requiring adherence to
certain compliance policies.

3.2.7.3. How to onboard Microsoft 365 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

You have generated a Globally Unique Identifier
(GUID), also known as a Universally Unique
Identifier (UUID). You will need this ID for the
tenant you want to use for the Microsoft 365
instance.
In order to use Microsoft 365, you must be
registered with Microsoft Azure.

3.2.7.4. Ingest logs and data from Okta  ☑️

🟣pr…

Administrator privileges: Your Okta user must
have a role capable of creating API tokens,
such as Read-only Administrator, Super
Administrator, or Organization Administrator.
For more information, see the Okta
Administrators Documentation.

3.2.7.5. Activate Registry Scanner 

🔒

🟣c…

Requires the Cortex XSIAM Premium license or
any other XSIAM license with the Cloud Posture
Security or the Cloud Runtime Security add-on.

☑️

🟣pr…

To initialize registry scanning on your Broker
VM, you must first add the necessary data
connectors. For details, see:
Connect Docker Hub registry
Connect Docker V2 compliant container
registry
Connect GitLab container registry
Connect Harbor registry
Connect JFrog container registry
Connect Sonatype Nexus registry
To initialize registry...

📝

🟢note

You cannot activate the Registry Scanner
directly on a new or existing Broker VM. You
can only activate or deactivate existing
Registry Scanner applets. To activate or
deactivate existing applets, see Step 4 under
Verify Registry Scanner connection section.

3.2.7.6. How to onboard Snowflake 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

In order to use Snowflake, you must be
registered with one of these cloud providers:
Amazon AWS, Microsoft Azure, or Google
Cloud Platform (GCP).
Ensure you have the necessary account
permissions to onboard. It is recommended to
use Account Admin as the role for the
onboarding.

📝

🟢note

The account identifier can be found using the
user information at the bottom left. Hover over
the account you wish to onboard and select
the copy option at the top right. The account
identifier is usually of the format:
(organization).[account]

3.2.7.7. Activate Transporter 

🔒

🟣c…

This feature is included with a Cloud Runtime
Security, Cloud Posture Security, or Cortex
XSIAM Premium license.

☑️

🟣pr…

Permissions: To configure and manage
Transporter applet settings, you must have
permissions to manage Broker Service
configurations (such as an Instance
Administrator)
Set up and configure Broker VMSet up and
configure Broker VM
Confirm that your Broker is v 28 or above
Whitelist IP addresses to enable access to
Cortex XSIAM resources. The IP addresses...

⛔

🔴w…

The Transporter applet is not supported for
FedRAMP customers.

🧭

➡️n…

Settings → Configurations → Broker VMs
(under Data Broker

the Brokers tab → locate your Broker VM →
hover and click + Add under the Apps column
→ AppSec Transporter

the Appsec Transporter under the App column
→ Deactivate → Confirm when prompted All
existing connections are deleted but their
configurations are saved in the database

the Appsec Transporter under the App column
→ Deactivate → Confirm when prompted

3.2.8. External alerts using External Issue
Mapping  3.2.8.1. Ingest external alerts 

📝

🟢note

If you send pre-parsed alerts using the Cortex
XSIAM API, additional mapping is not required.

🧭

➡️n…

In Cortex XSIAM, select Settings →
Configurations → Data Collection → External
Issue Mapping

3.2.9. Administration and troubleshooting 

3.2.9.1. Manage instances 

3.2.9.1.1. Add a new data source or instance 

📝

🟢note

If a data source contains multiple integrations,
the integration configured as the default
integration will used by the Data Onboarder.
The default integration of the content pack is
indicated in each content pack's
documentation. The other integrations are
available for configuration in the Data Sources
& Integrations page after installing the content...

📝

🟢note

If you are adding a new instance to an existing
data source, these options are View only.
You can adjust the view-only options on the
relevant page in the system, for example
Correlations, Playbooks, or Scripts.
If you are adding a new instance to an existing
data source, these options are View only.
You can adjust the view-only options on the
relevant...

3.2.9.1.2. How to configure the scanning settings
for supported services 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you do not select a scanning cadence, the
default setting is applied. For more information,
contact your Customer Support team.

3.2.9.1.3. Manage cloud instances 

3.2.9.1.4. Update cloud permissions after Cortex
release updates 

☑️

🟣pr…

Ensure that the user account used to modify
permissions has the necessary privileges within
both the Cortex platform and your cloud
environment, for example, AWS or Azure.
You received a notification regarding a new
version available that requires permission
updates, or viewed a Needs Update status in
the Data Sources & Integrations page.

📝

🟢note

Instances requiring updates will not change
their connection status, for example,
Connected, Warning, Error, Disabled, due to the
pending permission update.

3.2.9.1.5. Pending cloud instances 

3.2.9.1.6. Troubleshoot errors on cloud instances  📝

🟢note

Errors related to collection of audit logs in the
cloud instance are recorded in the
collection_auditing dataset. For more
information, see Audit logs fields and query
examples.

3.2.9.1.7. Manage Kubernetes Connector
instances  📝
🟢note

After uninstalling the Kubernetes connector,
the connector status updates to Not connected
48 hours after the uninstall process is initiated.

3.2.9.2. Integrations 

📝

🟢note

Some integrations can be downloaded directly
without having to initially download a content
pack from Marketplace. For more information,
see Define data sources.Define data sources
In addition to content packs that you install
from Marketplace, related content packs are
automatically downloaded when you adopt
playbooks or edit tasks that require...

📝

🟢note

If the integration was installed from a content
pack, you need to duplicate the integration
before editing.

📝

🟢note

Integration commands are only available when
the integration instance is enabled. Some
commands depend on a successful connection
between Cortex XSIAM and third-party
integrations.

💡

🔵tip

In the Playground, you can clear the context
data, if needed, which deletes everything in the
Playground context data, but does not affect
the actual issue or case. To clear the context,
run !DeleteContext all=yes' from the CLI or
click Clear Context Data while viewing the
context data.

🧭

➡️n…

Settings → Configurations → Marketplace

3.2.9.2.1. Integration use cases 

3.2.9.2.2. Add an integration instance 

3.2.9.2.3. Configure integration permissions 

3.2.9.2.4. Fetch issues from an integration
instance 

📝

🟢note

In some integrations, the Issue Fetch interval is
called Feed Fetch Interval.
If the integration instance does not have the
Issue Fetch Interval field, you need to add this
field by editing the integration settings. If the
integration is from a content pack, you need to
create a copy of the integration. Any future
updates to this integration will not...

📝

🟢note

Some content packs include preconfigured
correlation rules, but you should review them to
see if they suit your use case and duplicate
them if required. Go to Threat Management →
Detection Rules → Correlations, search for the
relevant rule, right-click, and select Preview
Rule. For example, the ServiceNow v2 Alerts
(automatically generated)...

3.2.9.2.4.1. Map fields to issue types 

📝

🟢note

In the Classification & Mapping page, the
mapping does not indicate for which issue
types they are configured. Therefore, when
creating a mapper, it is best practice to add to
the mapper name, the issue types the mapper is
for. For example, Mail Listener - Phishing.

📝

🟢note

When mapping a list, we recommend you map
to a multi select field. Short text fields do not
support lists. If you do need to map a list to a
short text field, add a transformer in the
relevant playbook task, to split the data back
into a list.

🧭

➡️n…

Settings → Configurations → Object Setup →
Issues → Classification & Mapping

3.2.9.2.4.2. Classify events using a classifier for
issue types 

3.2.9.2.5. Troubleshoot Integrations 

3.2.9.2.6. Forward requests to long-running
integrations 

📝

🟢note

This integration replaces the External Dynamic
list integration, which is deprecated. For more
information about how to set up the
integration, see Manage external dynamic lists.

📝

🟢note

When running on the tenant, you can only use
long-running integrations provided by Cortex
XSIAM, you cannot create custom ones.
Custom long-running integrations are
supported only on engines at this time.
Configuring custom certificates or private API
Keys in the long-running integration instance is
supported only on engines, not on the Cortex
XSIAM...

📝

🟢note

For the TAXII Server and TAXII2 Server
integrations, the xdr string is automatically
replaced by crtx. For the Microsoft Teams
integration, you can use the microsoft-teams-
create-messaging-endpoint command to get
the correct messaging endpoint based on the
server URL, the server version, and the instance
configurations. For more information, see...

3.2.9.3. Verify collector connectivity 

📝

🟢note

For more information on troubleshooting data
collector applet errors, see Troubleshoot
Broker VM applet connectivity.

📝

🟢note

If an issue is triggered, the investigation options
in the right-click menu of the Health Issues
pages are context-specific. Make sure that you
specify the relevant issue category.

3.2.9.4. Overview of data ingestion metrics 

☑️

🟣pr…

For Cortex XSIAM to monitor data ingestion
health and create health issues, you must
enable Cortex - Analytics. Go to Configurations
→ Cortex - Analytics. For more information, see
Enable the Analytics Engine and Identity
Analytics.

3.2.9.4.1. Creating correlation rules to monitor
data ingestion health 

3.2.9.4.2. Measuring data freshness  📝

🟢note

The max_delay metric is taken from the
maximum bucket value with a restricted limit;
therefore, metrics show whole numbers.
The median and ninetieth_percentile metrics are
statistical calculations that give an
approximation of the real value; therefore,
metrics show decimal numbers.
Time slots with a zero log count or zero byte
count display records...

3.2.9.5. About health issues 

☑️

🟣pr…

For Cortex XSIAM to monitor data ingestion
health and create health issues, you must
enable the following settings under
Configurations:
Cortex - Analytics: Go to Configurations →
Cortex - Analytics. For more information, see
Enable the Analytics Engine and Identity
Analytics.

📝

🟢note

The Health Issues page displays issues that
were triggered after July 2024. To see health
issues that were triggered before this date,
click Legacy Health Issues.

📝

🟢note

Cortex XSIAM enforces the dedup logic to
health issues. This logic reduces the likelihood
of identical health issues from flooding the
issues dataset.

3.2.9.5.1. Investigate and resolve health issues 

3.2.9.5.2. Monitor data ingestion health 

3.2.9.5.3. Monitor correlation rules  📝

🟢note

In the dataset, the Query start time and Query
end time indicate the timeframe of the data
that was queried. The actual start and end
times of the correlation rule execution are
recorded in the _time field for the Initiated and
Completed entries.

3.3. Marketplace 

3.3.1. Cortex Marketplace 

3.3.2. Content packs  📝

🟢note

Cortex XSIAM includes a built-in default mail
sender. You also have the option of installing a
different mail sender content pack, such as
Microsoft Exchange Online.

3.3.3. Content Pack Support Types  📝

🟢note

Palo Alto Networks is not liable for and does
not warrant or support any content pack
produced by a third-party publisher.
Palo Alto Networks does not support content
packs that do not have official available
documentation.

3.3.4. Cortex XSIAM content 

3.3.5. Manage content packs 

📝

🟢note

Optional content packs that are already
installed are treated like they are required
content packs to preserve content integrity.

📝

🟢note

Cortex XSIAM includes a built-in default mail
sender. You also have the option of installing a
different mail sender content pack, such as
Microsoft Exchange Online.

📝

🟢note

In addition to content packs that you install
from Marketplace, related content packs are
automatically downloaded when you adopt
playbooks or edit tasks that require content
items such as scripts or integrations.

📝

🟢note

Third-party product integrations are developed
and tested against a specific product version.
For products that are on-prem or cloud-based
with specific API versions, the version
developed and tested against will be included
in the integration's documentation. Newer
versions of the product are not always
immediately tested, and it is expected that...

⚠️

🟡c…

If you want to downgrade, any content that
depends on the content pack including any
customizations may be deleted if it does not
exist in the target content pack version.

⚠️

🟡c…

If another content pack is dependent on the
content pack you want to delete, it may break
the other content pack. You can reinstall the
content pack, but you cannot restore detached
and customized content.

💡

🔵tip

You can also find content packs that require
updates by going to Settings → Data Sources &
Integrations and filtering by Pack Version =
Update Available. If you click on an integration
in the filtered list, there is a link to the content
pack in Marketplace for updates.

3.3.6. Marketplace FAQs 

3.3.7. Content changes when upgrading Cortex
XSIAM versions 

3.3.8. Content pack contributions 

3.4. Configure the Cortex Agentic Assistant 

3.4.1. Agentic Assistant components and
concepts  📝
🟢note

Agents are bound by the same rules and robust
permissions as a human user. In addition, you
can mark actions that make real-world changes
in production systems as sensitive, requiring a
quick manual review and confirmation, ensuring
peace of mind before critical system changes
are made.

3.4.2. Agents Hub 

📝

🟢note

To manage agents in the Agents Hub, you must
have the proper permissions. For more
information, see Agentic Assistant role-based
access control.

3.4.2.1. Manage actions 

📝

🟢note

To manage actions in the Agents Hub, you must
have the correct permissions. For more
information, see Agentic Assistant role-based
access control.

💡

🔵tip

System actions may rely on content packs that
need to be installed and configured.

3.4.2.2. Register actions 

📝

🟢note

To register actions, ensure you have the correct
permissions. For more information, see Agentic
Assistant role-based access control.

📝

🟢note

Mandatory arguments cannot be deselected.

👀

🟠i…

A single content item can be registered as
different actions, with each action using
different inputs and outputs from the same
script. Only register the same script, command,
or AI prompt as a new action if it is required for
your use case, as providing an agent with many
actions with overlapping abilities can reduce
the ability of the agent to choose...

3.4.2.3. Manage agents 

📝

🟢note

In some cases, an agent may include actions
with content items that are not relevant for all
licenses. If that occurs, the grey circle appears,
but you are not able to install the related
content.

💡

🔵tip

System agents can include actions that require
additional content packs to be installed and
configured. To view all actions assigned to a
system agent, including actions not available
due to missing content, click on the system
agent in the Agents Hub. There may be actions
assigned to a system agent that are not
relevant to your organization. For...

3.4.2.4. Build agents 

📝

🟢note

To build agents in the Agents Hub, you must
have view/edit permissions. For more
information, see Agentic Assistant role-based
access control.

📝

🟢note

If you clear the checkbox for a role, all actions
associated with that role are also cleared. The
exception is if another role is also selected,
which is associated with the same actions.
If you clear the checkbox for an action, all roles
associated with that action are cleared. For
example, if you select the Investigator role, and
Send Mail and Tavily...

3.4.2.5. Expand agent capabilities with MCP
integrations 

📝

🟢note

For agentic actions to be created from tools on
an MCP server, the tools must have input and
output descriptions on the MCP server. These
descriptions are required for Cortex XSIAM to
understand the tools' capabilities and the
correct use cases.

📝

🟢note

If you are using OAuth-based authentication,
the Test button returns an error containing the
command to run in the playground in order to
test the connection.

📝

🟢note

If an MCP tool is removed from the MCP server,
the action will be unavailable due to missing
content. If the tool is restored on the MCP
server, the action is automatically reenabled.
If you have a development and a production
tenant, you can push actions created from MCP
tools from development to production.

🧭

➡️n…

Settings → Configurations → Data Collection
→ Integration Permissions

3.4.3. Agentic Assistant role-based access
control  📝
🟢note

Agents are limited by the individual permissions
of the user. For example, if users do not have
sufficient permissions to isolate an endpoint,
they cannot use an agent to isolate an endpoint.

3.5. Cortex MCP server  3.5.1. Cortex MCP server overview 

📝

🟢note

This feature is in Beta.

📝

🟢note

The Cortex MCP Server empowers you to
integrate AI into your security workflows using
natural language. When using LLM-based
suggestions, always review and approve actions
suggested by the AI before they're executed.
We recommend deploying the Cortex MCP
server in a secure environment where access is
limited to authorized users.

3.5.1.1. Install the Cortex MCP server 

☑️

🟣pr…

If you are running the Cortex MCP server in a
Poetry virtual environment, you must have
Python 3.13 or higher.
If you plan to run the Cortex MCP server in a
Docker container, you must have Docker
installed.

📝

🟢note

The MCP Server uses public APIs to
communicate and is limited by the license
quotas available in your tenant. This is
particularly relevant when running XQL queries.
For more information on running XQL query
APIs, see Run XQL query APIs.

📝

🟢note

It is critical to avoid assigning excessive
permissions when creating an API key for the
Cortex MCP Server. Since the key has both read
and write capabilities, overly broad permissions
can lead to unintended actions and potentially
compromise your environment. Ensure the key
follows the principle of least privilege and is
granted only the minimum...

📝

🟢note

When using Docker, we recommend using an
.env file to set the Cortex API credentials as
environment variables. While the credentials
can be provided in the MCP client configuration
settings, the .env file provides safer handling of
API credentials and makes your configuration
easily reproducible.

📝

🟢note

By default, stdio (standard input/output) is
used. You can also configure Streamable HTTP,
to send requests directly to the tenant instead
of through the MCP client. Streamable HTTP
can be useful for testing in the browser without
a MCP client and to bypass limits that may be in
place for your MCP client. For Docker, you can
include the Streamable HTTP...

👀

🟠i…

To configure the Cortex MCP Server, you need
the Cortex API URL, Cortex API key, and Cortex
API key ID. You will not be able to view the API
key again after you complete this step. Ensure
that you copy the API key before closing the
notification.

3.5.1.2. Configure the MCP client  🧭

➡️n…

Settings → Developer → Edit Config

3.5.1.3. Use the Cortex MCP server  📝

🟢note

The built-in tools retrieve information, but do
not write to the tenant. You can create your
own tools that include write actions. The
examples below include both.

3.5.1.4. Create custom Cortex MCP server tools  📝

🟢note

Any new or updated components provided by
Cortex are automatically downloaded into the
remote_components folder. During each
update, the folder is fully replaced and all
existing contents are recreated. Do not add
custom tools to this directory, as it is managed
entirely by Cortex and is overwritten at every
update.

3.6. Automations 

3.6.1. Automation in Cortex XSIAM  📝

🟢note

You can build end-to-end automation
workflows from within the playbook editor,
including creating automation rules,
configuring integration instances, and creating
and editing tasks. For more information, see
Playbooks.

3.6.2. Quick Actions 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Quick Actions appear as War Room entries, but
do not appear in the Work Plan.

3.6.3. Automation Exclusion Center 

📝

🟢note

By default, all users have read and edit
permissions to lists. When creating a list of
critical assets, we recommend limiting the read
and edit permissions to specific roles.

3.6.3.1. Manage automation exclusion policies 

📝

🟢note

For the IAM User Hard Remediation and User
Soft Remediation policies, we recommend
including username, email, and ID for each user
you want to exclude. Example: username1,
user@example.com, userID112.

📝

🟢note

You can also right click on a policy from the
main Automation Exclusion Center page to
disable or enable the policy.
If you click on a list name in the Exclude
column, that list opens in the Lists page.

3.6.4. Playbooks 

☑️

🟣pr…

To provide playbook access, first set the Cases
& Issues RBAC permission to View or View/Edit
and then set the Playbooks permission to View
or View/Edit.
To completely restrict playbook access, first
set the Cases & Issues RBAC permission to
None and then set the Playbooks permission to
None.

3.6.4.1. Playbooks overview 

3.6.4.2. Playbook development checklist 

3.6.4.3. Plan your playbook 

3.6.4.4. Manage playbooks  📝

🟢note

The library by default shows only playbooks
that are not adopted. Click the Show Adopted
checkbox to show the adopted playbooks,
indicated by an Adopted mark.
The library shows the most updated playbook
version. Adopting an older version than shown
should be done through Marketplace.
Adopting a playbook does not make it run.
Some content packs include...

3.6.4.5. Build your playbook 

3.6.4.5.1. Task 1. Choose from existing playbooks
or create your own



📝

🟢note

When a task inside of a sub-playbook is not
configured, the alert is propagated to the main
playbook. If multiple sub-playbooks are nested,
and any of the sub-playbooks have non-
configured components, the alert appears in
the main playbook as well as in the sub-
playbooks. Alerts also appear for the individual
non-configured tasks within the...

💡

🔵tip

If there are additional relevant playbooks in
Marketplace that are not in your Org repository,
you can click Explore them now to see them in
the Playbook Catalog and choose to adopt.

💡

🔵tip

To open multiple playbooks at the same time,
edit the first playbook and then click New next
to the playbook name to create a new tab. You
can either create a new playbook, or add an
existing one.
You can view recently modified or deleted
playbooks by clicking version history for all
playbooks .

🧭

➡️n…

the Investigation & Response → Automation →
Playbooks page to find an existing playbook,
customize it, or create a playbook

3.6.4.5.2. Task 2. Configure playbook settings 

📝

🟢note

If the playbook has inputs and outputs, the
Playbook Starts task will show back and forth
arrows. Clicking them opens the Playbook
Settings pane Inputs/Outputs tab.

📝

🟢note

This rule will trigger the playbook to run if no
other Automation Rule triggers the playbook
first. You can view and edit the order the rules
run in the Automation Rules page.

📝

🟢note

If you do not add any fields, the group will be
deleted when you click Save.

3.6.4.5.3. Task 3. Add objects from the Task
Library



3.6.4.5.3.1. Add Quick Actions, commands, and

scripts 

📝

🟢note

If the Quick Action requires an integration
instance and it is not yet configured, you have
the option to create an integration instance
from within the playbook editor.

📝

🟢note

If you want to add a script that is not yet
adopted, Cortex XSIAM automatically installs
the content pack containing the script. If the
script requires an integration instance, you are
prompted to configure one.

📝

🟢note

If you do not have permission to download the
script, contact your administrator for help. You
can also filter by "show only configured" to
show scripts you can use.

📝

🟢note

Commands you run in the War Room can
automatically populate parameters such as
region, account ID, and tags, based on asset
data. Commands can reference UIA attributes
for the relevant asset(s) in the issue context and
use those attributes as input. The issue must
contain the relevant Asset ID.
The syntax to reference attributes in the UAI is...

📝

🟢note

The output value is dynamic and is derived
from the context at the time that the task is
processed. As a result, parallel tasks that are
based on the same output may return
inconsistent results.

💡

🔵tip

If your needs require a custom script, use the
Agentic Assistant with the Automation Engineer
agent to leverage the Cortex AgentiX built-in
LLM to quickly and efficiently generate
functional Python scripts from natural
language prompts. For more information, see
Create a script.

3.6.4.5.3.2. Add sub-playbooks  💡

🔵tip

Balance between the number of iterations and
the interval so you do not overload the server.

3.6.4.5.3.3. Add AI prompt tasks 

📝

🟢note

Selecting Local AI Prompt creates a local
version of the task within your playbook. Any
future updates made to the Prompts Library
will not sync to this specific task.
Choose Local AI Prompt if you need to
customize the logic for a specific workflow and
want to ensure its behavior remains unchanged,
even if the Prompts Library is updated with...

💡

🔵tip

If an AI prompt task returns a 504 Error with the
status DEADLINE_EXCEEDED, it is likely due to
the task requiring more time to process than
the default setting allows. To resolve this, open
the Task Details pane of the AI task and select
the Advanced tab, then increase the Execution
timeout (seconds) based on how complex your
prompt is and how long...

3.6.4.5.3.4. Add manual tasks and blank tasks 

3.6.4.5.3.4.1. Create a standard task 

3.6.4.5.3.4.2. Create a conditional task 

3.6.4.5.3.4.3. Create a communication task 

3.6.4.5.3.5. Create a section header 

3.6.4.5.3.6. Configure script error handling in a
playbook 

📝

🟢note

Use the GetErrorsFromEntry script (part of the
Common Scripts Pack) to check whether the
given entry returns an error and returns an error
message. For example, when using the script in
a playbook, you can fetch the error message
from a given task, such as a runtime error. You
can then add a step in the playbook flow to
send those error messages to the...

📝

🟢note

You can set up script error handling only when
running a script in a Standard task or a
Conditional task. For more information about
error handling settings for these tasks, see
Create a standard task or Create a conditional
task.
Built-in, Manual, and Ask Conditional tasks have
On Error settings for number of retries and
retry interval, but not Error...

3.6.4.5.4. Task 4. Add custom playbook features 

3.6.4.5.5. Task 5. Test and debug the playbook 

3.6.4.5.6. Task 6. Manage playbook content 

3.6.4.6. Customize your playbook 

3.6.4.6.1. Configure a sub-playbook loop 

📝

🟢note

Consider the following when adding a loop:
The maximum number of loops (default is 100).
A high number of loops or a high wait time
combined with a large number of issues may
affect performance.
Periodically check looping conditions to ensure
they are still valid for the data set.
If you want a sub playbook task to loop over an
array passed into its...

💡

🔵tip

Balance between the number of iterations and
the interval so you do not overload the server.

3.6.4.6.2. Filter and transform data 

⚠️

🟡c…

You can change the context data root to filter,
but it is not recommended to select a different
root, as it affects the filter results. The drop-
down list displays the filter root for backward
compatibility.

🧭

➡️n…

Investigation & Response → Automation →
Scripts → New Script

3.6.4.6.2.1. Filter considerations, categories, and
built-in filters



📝

🟢note

Is defined considers false and empty strings
and lists to be defined values. If you don't want
those to be included as defined, use Is not
empty.

📝

🟢note

Not defined considers false and empty strings
and lists to be defined values. If you don't want
those to be included as defined, use Is empty.

3.6.4.6.2.2. Transformer considerations,
categories, and built-in transformers

 📝

🟢note

To make regex case non-sensitive, use the (?i)
prefix (for example (?i)yourRegexText.

3.6.4.6.3. Extend context 

3.6.4.6.4. Extract indicators 

📝

🟢note

This configuration may delay playbook
execution (issue creation).
While indicator creation is asynchronous,
indicator extraction and enrichment are run
synchronously. Data is placed into the issue
context and is available via the context for
subsequent tasks.

📝

🟢note

When using out of band, the extracted
indicators do not appear in the context. If you
want the extracted indicators to appear select
inline.

3.6.4.6.5. Update issue fields with playbook tasks  📝

🟢note

The setIssue script includes all available fields;
use the scroll bar to see all the fields.
The name field has a limit of 600 characters. If
there are more than 600 characters, you can
shorten the name field to under 600 characters
and then include the full information in a long
text field such as the description field.
There are many fields already...

3.6.4.7. Test your playbook 

📝

🟢note

The debugger does not support using
parentIncidentFields.

📝

🟢note

Using an existing issue in the debugger does not
affect the original issue or change the original
context data.

3.6.4.7.1. Troubleshoot playbook performance 

3.6.4.8. Manage playbook content 

📝

🟢note

Opening a playbook does not immediately lock
it. A playbook is considered to be in edit mode
only when a user makes a modification that
causes the Save button to become available.

👀

🟠i…

Manually unlocking a playbook may cause
version conflicts. This turns off concurrent
editing protection, and if the original user is still
editing, their changes might be lost or
overwritten.

🧭

➡️n…

Investigation & Response → Automations →
Playbooks

3.6.4.9. Best practices 

📝

🟢note

If you reattach a detached playbook, any
customizations you have made to the playbook
will be overwritten when the playbook updates
to the current version.

📝

🟢note

Retries are not supported for data collection
tasks that have errors sending emails (indicated
by a server timeout). This is because retries only
work on automation execution failures, not on
email delivery issues.

3.6.5. AI Prompts 

🧭

➡️n…

On the AI Prompts page (Investigation →
Response → Automation → AI Prompts), you
can view, edit, and manually create prompts

3.6.5.1. AI prompts role-based access control 

3.6.5.2. Use existing prompts  🧭

➡️n…

Investigation & Response → Automation → AI
Prompts and in the Prompts Library search for
the prompt you want to use

3.6.5.3. Create a prompt  🧭

➡️n…

Investigation & Response → Automation → AI
Prompts and click + New Prompt

3.6.6. Create an automation rule 

📝

🟢note

You can also define the conditions that trigger
a specific playbook in the playbook editor. For
more information, see Task 2. Configure
playbook settings

📝

🟢note

Quick Actions, by default, run using all
available integration instances that contain the
command. When selecting a Quick Action for
an automation rule, you can instead choose one
specific integration instance to use.

👀

🟠i…

Automation rules apply to Medium and higher
severity issues. They also apply to Low severity
Analytic issues and Low severity ABIOC issues
that are tagged with Identity or Cloud.
Rules are evaluated in order, and only the first
rule that matches the trigger conditions is
executed.

3.6.7. Scripts 

☑️

🟣pr…

To provide scripts access, first set the
Playbooks and Playground RBAC permissions to
View or View/Edit and then set the Scripts
RBAC permission is set to View or View/Edit.
To completely restrict scripts access, first set
Playbooks and Playground RBAC permissions to
None and then set the Scripts permission to
None.

👀

🟠i…

The Automation Engineer agent is available
when the Agentic Assistant feature is enabled,
for users with script editing permissions. For
more information, see Cortex Agentic Assistant
and Agentic Assistant role-based access
control.

🧭

➡️n…

On the Scripts page (Investigation → Response
→ Automation → Scripts), you can view, edit,
and create scripts in JavaScript, Python, or
PowerShell

3.6.7.1. Use existing scripts  🧭

➡️n…

Investigation & Response → Automation →
Scripts and in the Scripts Library search for the
script you want to use

3.6.7.2. Create a script 

📝

🟢note

You can enable/disable a script in the Settings
without having to duplicate the script.
You can view recently modified or deleted
scripts by clicking the version history for all
scripts .

👀

🟠i…

If you choose Python, from the Agentic
Assistant you can use the Automation Engineer
agent.

💡

🔵tip

If there is an error, you can copy the error
message from the test result into the Agentic
Assistant prompt and ask the Automation
Engineer agent to correct the error.

3.6.7.3. Use the Automation Engineer agent to
accelerate script development and deployment 

📝

🟢note

The Automation Engineer agent is available
with the Cortex Agentic Assistant, for users
with script editing permissions. For more
information, see Cortex Agentic Assistant and
Agentic Assistant role-based access control.

📝

🟢note

If you make manual edits in the script and don't
save the changes and you then modify the
script with the Automation Engineer agent, you
are prompted to confirm overwriting the
manual edits.

💡

🔵tip

Use detailed prompts, for example, Get failed
logins from last 24 hours and return as a table.
Clearly define argument names, types, and
default values.
Mention if you expect the output in a specific
format, such as a table, JSON, or plain text.

💡

🔵tip

If there is an error, you can copy the error
message from the test result into the Agentic
Assistant prompt and ask the Automation
Engineer agent to correct the error.

3.6.7.4. Change the Docker image in an
integration or script  📝
🟢note

You can access publicly available Docker
images from the Cortex XSIAM tenant even if
there is no external connection to the Demisto
registry, for example, if due to firewall
constraints, your engine cannot access the
Demisto registry.

3.6.8. Context data 

3.6.8.1. Issue context data 

3.6.8.2. Case context data 

3.6.8.3. Search context data 

3.6.8.4. Add context data to an issue 

3.6.8.5. Add context data to a case  📝

🟢note

If you run the command in the issue War Room,
the data is added to the following places:
The case context data.
The issue context data under the case tab.
If you run the command in the Case War Room,
the data is added to the case context data only.

3.6.8.6. Delete context data from a case 

3.6.8.7. Use context data in a playbook 

📝

🟢note

Generic polling does not work if a playbook's
context data is shared globally. For more
information, see Playbook polling.Playbook
polling

⚠️

🟡c…

Users with Trigger Playbook permissions on a
given issue may still be able to modify the
parent case via commands and scripts, even
without full access to the case.

3.6.9. Lists 

📝

🟢note

The maximum size of a list is 209715 characters.

3.6.9.1. Create a list 

📝

🟢note

If you intend to use the list as part of an
Automation Exclusion Policy, we recommend
choosing specific roles for read and edit
access. For more information on using lists in
exclusion policies, see Manage automation
exclusion policies.

📝

🟢note

If you want to edit a list from a content pack,
you need to duplicate or detach a list.
Detached lists do not receive updated content
in subsequent Cortex XSIAM content releases.
To retain an updated list, reattach it.

3.6.9.2. List commands 

3.6.9.3. Use cases: JSON lists  🧭

➡️n…

Settings → Configurations → Object Setup →
Lists → Add a List

Investigation & Response → Automation →
Playbooks → New Playbook

3.6.9.4. Transform a list into an array  🧭

➡️n…

Investigation & Response → Automation →
Playbooks and create or edit a playbook

3.6.10. Jobs 

3.6.10.1. Manage jobs  📝

🟢note

Only Account Admins and Instance
Administrator roles can create jobs and
view/edit job runs.
If the owner of a job has been removed from
Cortex XSIAM, the job will fail to run. In this
case, you must change the owner to a current
user.

3.6.10.2. Create a time triggered job 

📝

🟢note

To view a human readable description of a cron
schedule for an existing job, click and select
Job Schedule from the available columns.

👀

🟠i…

We recommend to avoid triggering a job while
a previous run of the job is active by
configuring the playbook a job triggers to close
the investigation before running a new instance
of the job.

3.6.10.3. Create a job triggered by a delta in a
feed 

📝

🟢note

A job triggered by a delta in a feed runs only if
there is a change in the feed, and does not run
on a feed's initial fetch. For the initial fetch, you
can run the playbook manually and then set up
an event triggered job for subsequent fetches.
If you want to trigger a job after a feed
completes a fetch operation and the feed does
not change...

🧭

➡️n…

Investigation & Response → Automation →
Jobs → New Job

3.7. Engines 

3.7.1. What is an engine? 

📝

🟢note

You cannot share a multiple-engine installation
with a single-engine installation.

📝

🟢note

When you add an engine to a load-balancing
group, you cannot use that engine separately.
The engine does not appear in the engines
menu when configuring an integration instance,
but you can choose the load-balancing group.

3.7.2. Engine requirements 

📝

🟢note

The Cron package is required to install engines
on a Linux machine.

📝

🟢note

CentOS 8.x reached End of Life (EOL) on
December 31, 2021, and is no longer supported
as an operating system.
CentOS 7.x reached End of Life (EOL) on June
30, 2024, and is no longer supported as an
operating system.

📝

🟢note

If you have configured a range of Approved IP
Ranges under Allowed Sessions on the Security
Settings page, the engine must communicate
through one of the approved IPs.

3.7.3. Install an engine 

📝

🟢note

If you are using DEB, RPM, or Zip installation,
install Docker or Podman.
Natively running Python or PowerShell
integrations/scripts on Windows or Linux is not
supported on Cortex XSIAM engines.

📝

🟢note

When upgrading an engine that was installed
using the Shell installation, you can use the
Upgrade Engine feature in the Engines page. For
Amazon Linux 2 type engines, you need to
upgrade these engine types using a zip-type
engine and not use the Upgrade Engine feature.
If you use the shell installer, Docker/Podman is
automatically installed. We...

📝

🟢note

Use DEB and RPM installation when the shell
installation is not available. You need to
manually install Docker or Podman and any
dependencies.

📝

🟢note

If you receive a permissions denied error, it is
likely that you do not have permission to access
the /tmp directory.
If the installer fails to start due to a permissions
issue, even if running as root, add one of the
following two arguments when running the
installer:
--target <path> - Extracts the installer files
into the specified custom...

👀

🟠i…

For DEB/RPM engines, Python (including 3.x)
and the containerization platform
(Docker/Podman) must be installed and
configured. For Docker or Podman to work
correctly on an engine, IPv4 forwarding must be
enabled.

💡

🔵tip

For Linux systems, we recommend using the
shell installer. If using Amazon Linux 2, use the
zip installer (see step 4).

3.7.3.1. Docker 

📝

🟢note

This section is relevant when installing an engine.

📝

🟢note

Docker images can be downloaded together
with their relevant content packs for offline
installation.

3.7.3.1.1. Install Docker 

📝

🟢note

For Red Hat's Docker distribution, you need
Mirantis Container Runtime (formerly Docker
Engine - Enterprise) to run specific Docker-
dependent integrations and scripts. For more
information, see Install Docker distribution for
Red Hat on an engine server.
To use the Mirantis Container Runtime (formerly
Docker Engine - Enterprise) follow the
deployment...

3.7.3.1.1.1. Install Docker distribution for Red Hat
on an engine server

 📝

🟢note

If running RHEL v8 or higher, the engine installs
Podman packages and configures the operating
system to enable Podman in rootless mode.

3.7.3.1.1.2. Docker image security 

3.7.3.1.1.3. Docker FAQs 

3.7.3.1.1.4. Troubleshoot Docker issues 

3.7.3.1.1.5. Configure Docker pull rate limit 

3.7.3.1.1.6. Change the Docker installation folder 

3.7.3.1.2. Docker hardening guide 

📝

🟢note

The settings below can also be applied to
Podman, with the exception of limiting available
memory, limiting available CPU, and limiting
PIDS.

📝

🟢note

If you do not want to apply Docker memory
limitations, you should explicitly set the
advanced parameter: limit.docker.memory to
false.

💡

🔵tip

We recommend reviewing Docker network
hardening below before changing any
parameters in the configuration file.
To securely run Docker containers, we
recommend using the latest Docker version.

3.7.3.2. Podman 

📝

🟢note

When upgrading an engine, the engine keeps
the previously used container management
type (regardless of distribution version).

3.7.3.2.1. Change the container storage directory 

📝

🟢note

Alternatively, the runroot setting may be set to
some temporary directory that is accessible by
the user demisto. If you choose to set the
runroot, it must be a directory that is mounted
as tmpfs (temporary filesystem), unlike the
graphroot.

⛔

🔴w…

Do not use NAS storage or a temporary (tmpfs)
directory for the graphroot setting. The
graphroot needs to be a local, non-temporary
directory for Podman to work. For more
information, see
https://en.wikipedia.org/wiki/Network-
attached_storage.

💡

🔵tip

We recommend reserving 150 GB for container
storage, either in the /home partition or a
different storage directory that you have set
using the graphroot key.

3.7.3.2.2. Install Podman 

📝

🟢note

This procedure is intended for RHEL 8 or later. It
may not work for other operating system types.
Do not use NAS storage for the $HOME
directory. The directory needs to be a local
directory for Podman to work.

📝

🟢note

If you edit the file with the root user, make sure
to set the demisto user as file owner by running
chown demisto:demisto
/home/demisto/.config/containers/registries.con
f

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl restart d1_<Engine _name>

3.7.3.2.3. Migrate From Docker to Podman 

3.7.3.2.4. Troubleshoot Podman 

📝

🟢note

This step removes all Podman images, including
any custom images you may have created.

📝

🟢note

$(id -u demisto) is used to get the demisto user
ID, which is part of the directory name. For
example, /tmp/podman-run-993
Not all the directories above may be present.

📝

🟢note

When you run podman container cleanup --rm -
a, you might see a message such as running or
paused containers cannot be moved without
force. The message can be safely ignored, as it
only pertains to current running containers,
which are not removed.

📝

🟢note

To change to the demisto OS user, run the
following command:
sudo su - -s /bin/bash demisto

📝

🟢note

You must switch to user demisto before running
the "system migrate" (running it as root will
have no effect).

📝

🟢note

The "system migrate" must be done by the user
demisto.

👀

🟠i…

The runroot must be located under the tmpfs
file system type. This is required to clean
Podman's run state on reboot and for
performance reasons.

⚠️

🟡c…

Unlike the runroot, the graphroot must NOT be
located under the tmpfs file system type. Using
tmpfs for the graphroot might corrupt
container images, causing command executions
to fail. It also degrades performance by forcing
Podman to needlessly re-pull images.

3.7.4. Manage engines  🧭

➡️n…

You can manage your engines and load-
balancing groups by going to Settings →
Configurations → Data Broker → Engines

3.7.5. Upgrade an engine  📝

🟢note

The upgrade.conf file is available on the engine
after it has been upgraded to Cortex XSIAM 3.1.
Any custom variables you add to the file are
applied when you upgrade from Cortex XSIAM
3.1 to Cortex XSIAM 3.2 or later.

3.7.6. Remove an engine 

3.7.7. Configure engines 

📝

🟢note

A day is defined as 24 hours and may not
exactly correspond to calendar days due to
daylight savings, leap seconds, etc.

📝

🟢note

In addition, to support engine upgrades from
the UI, edit the /usr/local/demisto/upgrade.conf
file on the engine to include the SERVER_URLS
setting with the new tenant's address. Include
only the host, without https:// or any additional
path at the end of the host name. For example:
SERVER_URLS="api-
example.us.paloaltonetworks.com"

📝

🟢note

If the engine loses communication for longer
than this time, it will disconnect and you need
to restart the service.

3.7.7.1. Configure the engine to use a web proxy 

📝

🟢note

You need to configure Docker to use a proxy.
When using a BlueCoat proxy, ensure you
encode the values correctly.

📝

🟢note

In an environment with a single engine, go to
/usr/local/demisto/upgrade.conf. In an
environment with multiple engines, go to
/usr/local/demisto/<engine-
name>/upgrade.conf, replacing <engine-name>
with the name of the engine.
Note that the key is in the upgrade.conf file and
must be https_proxy, even if your proxy address
starts with http://.

3.7.7.2. Configure the engine to call the server
without using a proxy

 3.7.7.2.1. Use NGINX as a reverse proxy  📝

🟢note

For multi-tenant deployments, replace location
~ ^/(websocket|d1ws|d2ws) { with location ~
^/(acc_\S+/)?(websocket|d1ws|d2ws)

3.7.7.3. Configure an engine to use custom
certificates 

3.7.8. Use an engine in an integration  📝

🟢note

Long-running integrations should not run on
load-balancing groups.

3.7.9. Run a script using an engine  🧭

➡️n…

Investigation & Response → Automation →
Scripts

3.7.10. Troubleshoot engines 

📝

🟢note

Ensure that pop-ups are not blocked by your
browser.

📝

🟢note

If the installer fails to start due to a permissions
issue, even if running as root, add one of the
following two arguments when running the
installer:
--target <path> - Extracts the installer files
into the specified custom path.
--keep - Extracts the installer files into the
current working directory (without cleaning at
the end).
If using installer...

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl status d1_<Engine _name>

📝

🟢note

Any changes made to variables in the
upgrade_engine.sh file are reset after each
upgrade. We recommend instead using the
upgrade.conf file to set variables.

📝

🟢note

You can ignore the following error: Cannot
create folder '/var/lib/demisto'

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl status d1_<Engine _name>

📝

🟢note

If the installer fails to start due to a permissions
issue, even if running as root, add one of the
following two arguments when running the
installer:
--target <path> - Extracts the installer files
into the specified custom path.
--keep - Extracts the installer files into the
current working directory (without cleaning at
the end).
If using installer...

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl status d1_<Engine _name>

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl status d1_<Engine _name>

🧭

➡️n…

When troubleshooting engines, access the logs
from Settings → Configurations → Engines and
select the engine from which you want to
download the logs

3.7.11. Troubleshoot integrations running on
engines 

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl restart d1_<Engine _name>

📝

🟢note

Docker CE installations typically run Docker,
while Docker EE installations typically run
dockerroot.

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl restart d1_<Engine _name>

📝

🟢note

If the Allow running multiple engines on the
same machine option is selected, run the
command:
sudo systemctl restart d1_<Engine _name>

3.8. Remote repository management 

3.8.1. Cortex XSIAM development tenant  👀

🟠i…

Development tenants are not intended for
performance checks; they cannot access
production data, and they are connected to a
limited number of endpoints. As a result, all
development tenants have fewer resources than
the production tenant, including data ingestion
capacity and performance, and compute
capabilities. In a development tenant, extreme...

3.8.2. Set up a remote repository 

🧭

➡️n…

If the content repository option is disabled for
the production or development tenant (under
Settings → Configurations → General →
Remote Repository Settings, toggle the
Content repository slider to off), the tenant
becomes standalone and does not push or pull
content

If you are changing your remote repository
settings, back up existing content to your local
computer by navigating to Settings →
Configurations → General → Server Settings →
Custom Content and click Export all custom
content

3.8.2.1. Set up a built-in remote repository 

📝

🟢note

Once enabled, development tenants have a red
banner on the top left showing DEV.

📝

🟢note

The first tenant that is enabled pushes its
content to the remote repository first. For
example, these instructions describe enabling
the production tenant first, so the remote
repository will initially contain production
tenant content. You can enable a development
tenant first if you want the remote repository to
initially contain the content from...

🧭

➡️n…

Settings → Configurations → General →
Remote Repository Settings and toggle the
Content repository slider to enable the remote
repository

3.8.2.2. Set up a Private Remote Repository 

📝

🟢note

Once enabled, the development push tenant
has a red banner on the top left showing DEV.

📝

🟢note

For repository vendors that use tokens, enter
the token type in the username field and the
token in the password field. Verify details with
your vendor.
If your private Git remote repository uses
personal access tokens instead of usernames
and passwords, enter the token type in the
username field and the access token in the
password field. For example,...

📝

🟢note

You can't add an engine that has been added to
a Load-Balancing Group.

📝

🟢note

If your private Git remote repository uses
personal access tokens instead of usernames
and passwords, enter the access token in the
password field and leave the username field
blank.
For repository vendors that use tokens, the
token type is entered in the username field and
the token is entered in the password field.
Verify details with your vendor.
If...

📝

🟢note

The first tenant that is enabled pushes its
content to the remote repository first. For
example, these instructions describe enabling
the production tenant first, so the remote
repository will initially contain production
tenant content. You can enable a development
tenant first if you want the remote repository to
initially contain the content from...

📝

🟢note

For repository vendors that use tokens, enter
the token type in the username field and the
token in the password field. Verify details with
your vendor.
If your private Git remote repository uses
personal access tokens instead of usernames
and passwords, enter the token type in the
username field and the access token in the
password field. For example,...

📝

🟢note

You can't add an engine that has been added to
a Load-Balancing Group.

📝

🟢note

If your private Git remote repository uses
personal access tokens instead of usernames
and passwords, enter the access token in the
password field and leave the username field
blank.
For repository vendors that use tokens, the
token type is entered in the username field and
the token is entered in the password field.
Verify details with your vendor.
If...

💡

🔵tip

Due to security concerns, there is a closed
allow list of approved URLs for private
repositories. If you want to use a URL that is
excluded from the allow list, use an engine
(engine groups are not supported).

3.8.3. Push and pull content  🧭

➡️n…

Settings → Configurations → Remote
Repository Content → User-Defined Content

3.8.4. Remote repository troubleshooting 

3.9. Multi-Tenant 

3.9.1. What is Cortex XSIAM multi-tenant? 

📝

🟢note

By default, multi-tenant licenses include one
child tenant.

3.9.1.1. MSSP multi-tenant 

3.9.1.2. Enterprise multi-tenant 

3.9.2. Multi-tenant central licensing management  📝

🟢note

In MSSP or enterprise multi-tenant, the license
specifies the maximum number of child tenants
that can be created. Once this limit is reached,
no additional tenants can be created, even if
there remains allocation for endpoints or GBs.

3.9.3. Onboard Cortex multi-tenant 

3.9.3.1. Onboarding checklist for multi-tenant
central licensing deployments 

3.9.3.1.1. Step 1. Activate Cortex XSIAM (main

account)  ☑️
🟣pr…

Before you begin, make sure you have the
following:
Cortex XSIAM activation email.
Customer Support Portal Super User role is
assigned to your account.
Before activating your Cortex XSIAM tenant,
you need to set up your Customer Support
Portal account. See How to Create Your
Customer Support Portal User Account. When
you create a Customer Support...

3.9.3.1.2. Step 2. Create a child tenant 

📝

🟢note

The main account is labeled in Cortex Gateway,
but child tenants are not labeled.
Cortex enables parent-child pairing between
tenants located in different geographical
regions. To enable this capability, contact your
support team.
To create a child tenant, ensure that you have
Account Admin permissions.

📝

🟢note

After activating a child tenant, you can't
change the child tenant's name.

📝

🟢note

This is a public FQDN, so be careful with
sensitive information such as the company
name.

After activating a child tenant, you can only
change the child tenant subdomain once.

📝

🟢note

Ensure that you meet the minimum
requirements for child tenant allocation.

📝

🟢note

If you reach your limit for child tenants,
depending on your license, you may be able to
create more tenants. You may be charged for
additional tenants. Contact Customer Support
if you are approaching your authorized limit.

3.9.3.2. Onboarding checklist for multi-tenant
customer-owned license deployments 

3.9.3.2.1. Step 1. Activate Cortex Cortex XSIAM

(parent and child tenants)  ☑️
🟣pr…

Before you begin, make sure you have the
following:
Cortex XSIAM activation email.
Customer Support Portal Super User role is
assigned to your account.
Before activating your Cortex XSIAM tenant,
you need to set up your Customer Support
Portal account. See How to Create Your
Customer Support Portal User Account. When
you create a Customer Support...

3.9.3.2.2. Step 2. Define access configurations
and role permissions 

3.9.3.2.3. Step 3. Pair a parent tenant with child
tenant  📝
🟢note

This field is not enabled by default. To enable
this, contact your support team.

3.9.4. Dynamic license allocation 

📝

🟢note

Changing the tenant's allocations might result
in a short downtime of your tenant.

📝

🟢note

After activating a child tenant, you can't
change the child tenant's name.

📝

🟢note

This is a public FQDN, so be careful with
sensitive information such as the company
name.

After activating a child tenant, you can only
change the child tenant subdomain once.

📝

🟢note

Ensure that you meet the minimum
requirements for child tenant allocation.

📝

🟢note

If you reach your limit for child tenants,
depending on your license, you may be able to
create more tenants. You may be charged for
additional tenants. Contact Customer Support
if you are approaching your authorized limit.

📝

🟢note

In a multi-tenant central licensing management
environment, you cannot unpair a child tenant
from the main account. The only way to remove
the connection to the main account is to delete
the tenant.

3.9.5. Child tenant management 

3.9.5.1. Manage a child tenant  📝

🟢note

Once a configuration is created Cortex XSIAM
resets the child tenant data and synchronizes
the security actions configured in the parent
tenant.

3.9.5.2. Track your tenant management 

📝

🟢note

This field is not enabled by default. To enable
this, contact your support team.

🧭

➡️n…

To view child tenant details, in Cortex XSIAM,
select Settings → Configurations → Tenant
Management

3.9.5.3. Investigate child tenant data 

3.9.5.4. Create and allocate configurations  📝

🟢note

You can configure Profiles only as Managed or
Unmanaged. All profiles you create are
automatically cloned to your child tenants.

3.9.5.5. Create a security managed action  📝

🟢note

Profiles you create are automatically cloned to
your child tenants.

3.9.6. About managed threat hunting 

3.9.6.1. Set up Managed Threat Hunting  🧭

➡️n…

Settings → Configurations → Managed Services

3.9.6.2. Investigate Managed Threat Hunting
reports  📝
🟢note

The MTH page is available for users with the
Managed Threat Hunting license and have the
necessary permission to view and triage alerts
and incidents in Cortex XSIAM.

3.10. XQL query management 

☑️

🟣pr…

Setting query limits requires View/Edit
permissions for Configurations → Query
Management.

📝

🟢note

A scheduled query or report is run on behalf of
the user that originally created it, even if it is
edited and run by another user.

📝

🟢note

Queries run by correlation rules are not
restricted by the query limit.
Very short queries do not count towards
concurrent queries.

📝

🟢note

To ensure optimal system performance, all
queries (user-generated and otherwise) adhere
to a default timeout limit of 60 minutes that is
defined by Palo Alto that takes priority over the
administrator defined value. Therefore,
regardless of the value specified in this field,
queries will be stopped after 60 minutes.
You can override the default timeout...

📝

🟢note

Query visibility is subject to Role-Based Access
Control (RBAC); users can't see queries for
datasets they do not have permission to access.

🧭

➡️n…

You can find Query Management options under
Settings → Configurations → General → Query
Management

3.11. Customize cases and issues  3.11.1. Customize cases and issues 

3.11.1.1. External integrations 

3.11.1.2. Set up case scoring 

📝

🟢note

On the first activation, it can take up to 48
hours for SmartScore to calculate and display
the score.
Enabling SmartScore subsequently impacts the
User Score.

📝

🟢note

For scoped users, a small lock icon indicates
that you don't have permissions to edit a rule.

💡

🔵tip

Right-click an issue field to add it as match
criteria.

🧭

➡️n…

Settings → Configurations → Cortex XSIAM-
Analytics and click Enable

Cases & Issues → Case Configuration → Case
Scoring and enable SmartScore

3.11.1.3. Create a starring configuration  💡

🔵tip

Right-click an issue field to add it as match
criteria.

3.11.1.4. Create custom case statuses and
resolution reasons



📝

🟢note

Before you create a custom status, please
review the built-in options. For more
information, see Resolution reasons for cases
and issues.
We recommend using the built-in statuses and
resolution reasons where possible. Custom
statuses and resolution reasons might not be
supported by all content, and status syncing
can take time.
In addition, custom...

📝

🟢note

After creation, custom statuses and resolution
reasons cannot be deleted or modified.

🧭

➡️n…

Configurations → Object Setup → Cases →
Properties

3.11.1.5. Create a sync profile 

📝

🟢note

If an issue is using bi-directional syncing, you
need to provide both an Inbound and an
outbound sync profile.

📝

🟢note

Blank fields are skipped.
You must define exact values.
Custom status values are not currently
supported.
Support is currently limited to a specific set of
fields.

3.11.1.6. Create a case domain 

📝

🟢note

Adding custom domains requires a View/Edit
RBAC permission for Case Properties (under
Object Setup).
Once created, a custom case domain cannot be
deleted or renamed.

⛔

🔴w…

Before you add a custom domain, please review
the built-in options. For more information, see
Case and issue domains.
We recommend using the built-in domains
where possible. Custom domains might not be
supported by all content. In addition, custom
domains affect Cortex XSIAM's ability to learn,
correctly identify, and score future cases.
Smart...

🧭

➡️n…

You can see all domains under Configurations
→ Object Setup → Cases → Domains

Settings → Configurations → Object Setup →
Cases → Domains

To enable access to the domain for an API key,
got to Settings → Configurations →
Integrations → API Keys

3.11.1.7. Customize case fields and layouts 

3.11.1.7.1. Create case timers and SLAs 

☑️

🟣pr…

Before you can create a case SLA, you must
first create a timer field. A timer field can be
associated with a single case SLA.

📝

🟢note

If you edit this filter after creation, the timer
and associated SLA will be removed from any
case that no longer qualifies, even if the timer is
already running.

🧭

➡️n…

Settings → Configurations → Object Setup →
Cases and open the Fields tab

3.11.1.7.1.1. Update case timer and SLA fields 

3.11.1.7.2. Case fields 

⛔

🔴w…

Deleting a case field or uninstalling a content
pack containing a case field may affect
capabilities based on the deleted field, layouts
and case scoring.

3.11.1.7.2.1. Case field types 

📝

🟢note

You cannot set filters, starring rules,
automation rules, layout rules, or issue
exclusions based on the values in custom
timestamp fields.

📝

🟢note

When grid field is shown in the Cases table, if
there are values in the field, they do not display
in the Cases table. Instead, the column shows
Data Available.

📝

🟢note

When an HTML field is shown in the Issues
table, if there is a value in the field, it does not
display in the Cases table. Instead, the column
shows Data Available.

📝

🟢note

When a Markdown field is shown in the Cases
table, if there is a value in the field, it does not
display in the Cases table. Instead, the column
shows Data Available.

📝

🟢note

If you make changes to case fields you can
update the context data by running a playbook,
script, or command. For more information, see
Update case fields.
To update dynamic custom case fields, such as
SLA and Timer fields, see Update case timer
and SLA fields.

3.11.1.7.2.2. Create custom case fields  🧭

➡️n…

Settings → Configurations → Object Setup →
Cases → Fields → New Field

3.11.1.7.2.3. Create a grid field for a case 

3.11.1.7.2.4. Update case fields  📝

🟢note

Ensure that you have the required RBAC
permission to write scripts.

3.11.1.7.3. Case layouts 

3.11.1.7.3.1. Create custom case layouts 

📝

🟢note

The script that runs when an action button is
clicked accepts only mandatory arguments
through the pop up window and does not
provide an option for any non-mandatory
arguments to be filled in when the button is
clicked. We recommend using a wrapper script
to collect and validate arguments in scenarios
where there can be a combination of
mandatory and...

💡

🔵tip

Limit the number of case fields to 50 in each
section. You can create additional sections as
needed.

3.11.1.7.3.2. Create rules for case layouts 

📝

🟢note

Layout rules support SBAC (scoped based
access control). The following parameters are
considered for editing access.
If Scope-Based Access Control (SBAC) is
enabled and Endpoint Scoping Mode is set to
restrictive mode, you can edit a rule if you are
scoped to all tags in the rule.
If Scope-Based Access Control (SBAC) is
enabled and Endpoint Scoping...

🧭

➡️n…

Settings → Configurations → Object Setup →
Cases → Layout Rules → New Rule

3.11.1.8. Customize issue fields and layouts 

3.11.1.8.1. Issue fields 

⛔

🔴w…

Deleting an issue field or uninstalling a content
pack containing an issue field may affect
detection and other capabilities based on the
deleted field. For example, correlation, layouts,
case scoring, starring rules, and playbook
triggers.

3.11.1.8.1.1. Issue field types 

📝

🟢note

You cannot set filters, starring rules,
automation rules, layout rules, or issue
exclusions based on the values in custom
timestamp fields.

📝

🟢note

When grid field is shown in the Issues table, if
there are values in the field, they do not display
in the table. Instead, the column shows Data
Available.

📝

🟢note

When an HTML field is shown in the Issues
table, if there is a value in the field, it does not
display in the Issues table. Instead, the column
shows Data Available.
The following HTML tags are not permitted:
blockquote, del, dd, div, dl, dt, fieldset, form, h1,
h2, h3, h4, h5, h6, hr, iframe, ins, li, math,
noscript, ol, pre, p, script, style, table,...

📝

🟢note

When a Markdown field is shown in the Issues
table, if there is a value in the field, it does not
display in the table. Instead, the column shows
Data Available.

3.11.1.8.1.2. Create custom issue fields  🧭

➡️n…

Settings → Configurations → Object Setup →
Issues → Fields → New Field

3.11.1.8.1.3. Create a grid field for an issue 

3.11.1.8.1.4. Issue timer fields  🧭

➡️n…

Settings → Configurations → General → Server
Settings → Issues and Enable Timer Field

3.11.1.8.1.5. Issue field triggered scripts 

📝

🟢note

Fields that can hold a list, such as multi-select
custom fields, return the delta in an array as a
new argument. For example, if a multi-select
field value has changed from ["a"] to ["a", "b"],
the new argument of the script gets a value of
["b"].

📝

🟢note

Issue field-triggered scripts must have the field-
change-triggered tag to appear in the list.
Issue field trigger scripts are not supported for
all system fields. The following fields are not
supported for issue field trigger scripts and
may result in failing to populate the issue
layout:
Cases: Case ID, Cases IDs
Asset Fields: Asset IDs, Asset Names,...

📝

🟢note

When creating the script, add the field-change-
triggered tag in the script settings.

📝

🟢note

Verify that User can add rows is selected.

⚠️

🟡c…

This feature assumes fair and intended usage
of field-triggered scripts. In cases of excessive
or abusive usage, execution may be restricted
or disabled. If script execution is restricted or
disabled, fields are still updated, but without
the results of the assigned script.

3.11.1.8.1.6. Configure issue timer fields  📝

🟢note

Only scripts to which you have added the SLA
tag appear in the list of scripts you can select.
To add a tag to a script, create a new script or
edit an existing script and enter the tag name in
the script settings.
When you hover over the machine name (below
the Field Name) note the name which is used in
the command line or script.

3.11.1.8.1.7. Configure a playbook to run timers 

📝

🟢note

When a task or section has a timer configured,
it displays the hourglass icon.

📝

🟢note

Timers are not started automatically when a
case is created.

📝

🟢note

If you stop a timer before the issue is closed,
you must reset the timer using the resetTimer
command before you can start the timer again.
When you reset the timer, all fields are cleared.

3.11.1.8.1.8. Automate changes to issue fields
using timer scripts 

3.11.1.8.1.9. Use issue timer field commands

manually in the CLI 

📝

🟢note

When defining the values for the slaField use
the machine name for the field, which is
lowercase and without spaces. You can check
the machine name by editing the issue field.

📝

🟢note

Timer fields are not started automatically when
an issue is created unless run in a playbook.

📝

🟢note

After a timer field is stopped, before you can
start the timer again you must reset the timer
using the resetTimer command.
Timers are automatically stopped when an
issue is closed.

📝

🟢note

When running commands in the CLI, you can
specify the alertID to change the timer for a
different issue.

3.11.1.8.2. Issue layouts 

3.11.1.8.2.1. Create custom issue layouts 

📝

🟢note

The script that runs when an action button is
clicked accepts only mandatory arguments
through the pop up window and does not
provide an option for any non-mandatory
arguments to be filled in when the button is
clicked. We recommend using a wrapper script
to collect and validate arguments in scenarios
where there can be a combination of
mandatory and...

💡

🔵tip

Limit the number of issue fields to 50 in each
section. You can create additional sections as
needed.

3.11.1.8.2.2. Add a custom widget to an issue
layout  🧭
➡️n…

Investigation & Response → Automation →
Scripts and upload the following script: Expand
script commonfields: id: ee3b9604-324b-4ab5-
8164-15ddf6e428ab version: 49 name:
IndicatorWidgetBar script: |- # Constants HIGH
= 3 SUSPICIOUS = 2 LOW = 1 NONE = 0
indicators = [] scores = {HIGH: 0, SUSPICIOUS: 0,
LOW: 0, NONE: 0} incident_id = demisto

Investigation & Response → Automation →
Scripts and upload the following script

Settings → Configurations → Object Setup →
Issues → Layouts

3.11.1.8.2.3. Create rules for issue layouts  🧭

➡️n…

Settings → Configurations → Object Setup →
Issues → Layout Rules → New Rule

3.11.1.9. Run indicator extraction in the CLI  📝

🟢note

Triggering enrichment on a substantial amount
of indicators can take time (since it's activating
all enrichment integrations per indicator) and
can result in performance degradation.

4. Protect your endpoints 

4.1. Endpoint security 

🔒

🟣c…

Requires one of the following licenses
Cortex XSIAM Premium
Cortex XSIAM Enterprise
Any other Cortex XSIAM license with the Cloud
Runtime Security add-on or the Enterprise
Runtime Security add-on

4.1.1. Endpoint protection 

📝 4.1.1.1. Malware protection 

🟢note

From Cortex XDR agent for Android version 9.0
and later, part of this module, which performs
local analysis on the Android device itself, is
deprecated. APK analysis will be handled only
by Wildfire.

4.1.1.2. Exploit protection 

📝 4.1.1.3. File analysis and protection flow 

🟢note

To enhance performance and efficiency, hash
verdict requests from the Cortex XDR agent
will be routed to the WildFire service with the
lowest latency. File uploads for analysis will
strictly adhere to the designated Cortex XSIAM
and WildFire regions, ensuring data remains
within the appropriate geographical boundaries.

4.1.1.4. Endpoint protection capabilities 

4.1.1.5. Endpoint protection modules 

4.1.1.6. Processes protected by exploit security
policy



4.1.1.7. File Integrity Monitoring (FIM) 

🔒

🟣c…

FIM requires the Cortex Cloud Runtime Security
add-on.

📝

🟢note

Google Kubernetes Engine (GKE) is currently
not supported

📝

🟢note

It is recommended to create a policy that
targets only the necessary files and folders.

📝

🟢note

Platform cannot be changed once a rule group
has been created

📝

🟢note

A rule group can contain up to 100 rules.

📝

🟢note

When importing a policy, select whether to
enable the associated policy targets. Rules
within the imported policy are managed as
follows:
New rules are added to the top of the list.
Default rules override the default rule in the
target tenant.
Rules without a defined target are disabled
until the target is specified.

📝

🟢note

It is possible to ingest up to 15,000 events per
day (24 hours) for each host/container.

🧭

➡️n…

Creating, modifying and viewing FIM rule
groups and rules is be done in the Rule Groups
page, located at the Inventory → Endpoints →
File Integrity Monitoring menu

In Inventory → Endpoints → Policy management
→ Extensions → Profiles, select +Add Profile
and then select either Create New or Import
from File

📝 4.1.1.8. WildFire analysis concepts 

🟢note

In cases when the Cortex XSIAM agent gets a
failed status from the WF service due to a
general error or unsupported file type, and the
Local Analysis is set to disabled or not
applicable, Cortex XSIAM will not generate an
alert on the file.

4.1.1.9. Guidelines for keeping Cortex XDR
agents and content updated 

📝

🟢note

The Cortex XDR agent keeps the name of the
original installation package after every
upgrade.

📝

🟢note

Custom dashboards that include upgrade
status widgets, and the All Endpoints page
display upgrade status.
During the upgrade process, the endpoint
operating system might request a reboot.
However, you do not have to perform the
reboot for the Cortex XDR agent upgrade
process to complete it successfully.
After you upgrade on an endpoint with Cortex...

📝

🟢note

These profiles can be configured on one or
more endpoints, static/dynamic groups, tags, IP
ranges, endpoint names, or other parameters
that allow the creation of logical endpoint
groups. See how to define endpoint group.

📝

🟢note

These profiles can be configured on one or
more endpoints, static/dynamic groups, tags, IP
ranges, endpoint names, or other parameters
that allow the creation of logical endpoint
groups.

👀

🟠i…

When planning Cortex XDR agent upgrades
and content updates, consult with the
appropriate stakeholders and teams and follow
the change management strategy in your
organization.

⚠️

🟡c…

Before enabling Auto-Update for Cortex XDR
agents, make sure to consult with all relevant
stakeholders in your organization.

📝 4.1.1.10. About content updates 

🟢note

Cortex XSIAM delivers the content update to
the agent in parts and not as a single file,
allowing the agent to retrieve only the updates
and additions it needs.

4.1.1.11. Endpoint data collection 

📝

🟢note

For specific files only and only if the file was
written.

👀

🟠i…

Registry key is collected as a real key name, and
not as a symbolic link.
Instead of
HKEY_LOCAL_MACHINE\System\CurrentControl
Set, which is a symbolic link,
KEY_LOCAL_MACHINE\System\ControlSet001
will be collected.
Instead of HKEY_CURRENT_USER, HKEY_USERS\
<SID> will be collected, where SID is a SID of
the current user.

4.1.2. Install and manage endpoints 

4.1.2.1. Set up endpoint protection 

4.1.2.1.1. Set up endpoint profiles and exception
rules 

📝

🟢note

Profiles associated with one or more targets
that are beyond the scope of your defined user
permissions are locked, and cannot be edited.

4.1.2.1.1.1. Set up malware prevention profiles 

🔒

🟣c…

Requires the ITDR add-on.

📝

🟢note

In this profile, the Report options configure the
endpoints to report the corresponding
suspicious files, actions, processes, or
behaviors to Cortex XSIAM, without blocking
them. The Disabled options configure the
endpoints to neither analyze nor report the
corresponding malware or behavior.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

As part of the anti-malware security flow, the
Cortex XDR agent leverages the operating
system's capability to identify revoked
certificates for executables, and DLL files that
attempt to run on the endpoint by accessing
the Windows Certificate Revocation List (CRL).
To allow the Cortex XDR agent access the CRL,
you must enable internet access over...

📝

🟢note

The Quarantine Malicious Executables feature
is not available for malware identified on
network drives.

📝

🟢note

The Quarantine Malicious Script Files feature is
not available for malware identified on network
drives.

📝

🟢note

If on-write actions were configured in earlier
versions of Cortex XSIAM, the same
configuration has been preserved and applied
globally for all file types.
On-write file protection may have an impact on
the resources required by the Cortex XDR
agent.

📝

🟢note

On-demand file protection may have an impact
on the resources required by the Cortex XDR
agent.

📝

🟢note

We recommend that you disable scheduled
scanning. VDI machine scans are based on the
golden image and additional files will be
examined upon execution.

📝

🟢note

When periodic scanning is enabled in your
profile, the Cortex XDR agent initiates an initial
scan when it is first installed on the endpoint,
regardless of the periodic scanning scheduling
time.

📝

🟢note

This feature only comes into effect after a
restart.

📝

🟢note

When you are actively evaluating with BAS
tools, it is recommended to enable the BAS
mode setting only for the duration of your
evaluation, and for a limited number of agents.

📝

🟢note

BAS tools mode with content older than version
1850 cannot be configured, the agent will be
treated as Enabled.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

We recommend that you disable scheduled
scanning. VDI machine scans are based on the
golden image and additional files will be
examined upon execution.

📝

🟢note

When periodic scanning is enabled in your
profile, the Cortex XDR agent initiates an initial
scan when it is first installed on the endpoint,
regardless of the periodic scanning scheduling
time.

📝

🟢note

The Quarantine Malicious Mach-O Files feature
is not available for malware identified on
network drives.

📝

🟢note

This module is supported by Cortex XDR agent
8.1.0 and later releases.

📝

🟢note

The Quarantine Malicious Executables feature
is not available for malware identified on
network drives.

📝

🟢note

When you are actively evaluating with BAS
tools, it is recommended to enable the BAS
mode setting only for the duration of your
evaluation, and for a limited number of agents.

📝

🟢note

BAS tools mode with content older than version
1850 cannot be configured, the agent will be
treated as Enabled.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

The Quarantine Malicious ELF Files feature is
not available for malware identified on network
drives.

📝

🟢note

This module is supported by Cortex XDR agent
8.1.0 and later releases.

📝

🟢note

Enabling on-demand scanning will
automatically scan these core system
directories: /etc, /tmp, /home, /usr, /bin, /sbin,
/lib, /var, /opt, /dev, /root, /boot.

📝

🟢note

We recommend that you disable scheduled
scanning. VDI machine scans are based on the
golden image and additional files will be
examined upon execution.

📝

🟢note

When periodic scanning is enabled in your
profile, the Cortex XDR agent initiates an initial
scan when it is first installed on the endpoint,
regardless of the periodic scanning scheduling
time.

📝

🟢note

When you are actively evaluating with BAS
tools, it is recommended to enable the BAS
mode setting only for the duration of your
evaluation, and for a limited number of agents.

📝

🟢note

BAS tools mode with content older than version
1850 cannot be configured, the agent will be
treated as Enabled.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

From Cortex XDR agent for Android version 9.0
and later, part of this module, which performs
local analysis on the Android device itself, is
deprecated. APK analysis will be handled only
by Wildfire.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Blocking functionality is different for each
security module. For SMS/MMS, Cortex XDR
agent will move detected messages containing
such URLs from unknown senders to the Junk
folder.

📝

🟢note

Ensure that the same numbers are not added
multiple times with different leading zeros.

📝

🟢note

To fully enable the Safari browser security
module on the device side, each iOS device
user must enable the Safari Safeguard module
on the device, and grant it permission to work
on all websites. If the iOS device user does not
do this, the endpoint's operation status is
reported as Partially Protected.
The Safari browser security module will only...

📝

🟢note

Cortex XDR agent version 8.4 or higher are
required for this feature.

⛔

🔴w…

For optimal user experience, we recommend
that you set the action mode to either Allow or
Run Local Analysis.

⛔

🔴w…

For optimal user experience, we recommend
that you set the action mode to either Allow or
Run Local Analysis.

⛔

🔴w…

For optimal user experience, we recommend
that you set the action mode to either Allow or
Run Local Analysis.

⛔

🔴w…

For optimal user experience, we recommend
that you set the action mode to either Allow or
Run Local Analysis.

4.1.2.1.1.2. Set up exploit prevention profiles 

📝

🟢note

In this profile, the Report options configure the
endpoints to report the corresponding exploit
attempts to Cortex XSIAM, without blocking
them. The Disabled options configure the
endpoints to neither analyze nor report the
corresponding malware or behavior.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

In exploit prevention profiles, if you change the
action mode for processes, you must restart
the protected processes for the following
security modules to take effect on the process
and its forked processes:
Brute Force Protection
Java Deserialization
SO Hijacking

📝

🟢note

This step provides a temporary workaround for
the following publicly known information-
security vulnerabilities and exposures: CVE-
2021-24074, CVE-2021-24086 and CVE-2021-
24094.

📝

🟢note

If you have Windows endpoints in your network
that are unpatched and exposed to a known
vulnerability, we strongly recommend that you
upgrade to the latest Windows Update that has
a fix for that vulnerability.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

In exploit prevention profiles, if you change the
action mode for processes, you must restart
the protected processes for the following
security modules to take effect on the process
and its forked processes:
Brute Force Protection
Java Deserialization
SO Hijacking

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

In exploit prevention profiles, if you change the
action mode for processes, you must restart
the protected processes for the following
security modules to take effect on the process
and its forked processes:
Brute Force Protection
Java Deserialization
SO Hijacking

⛔

🔴w…

This workaround applies only to the specific
Windows versions listed as exposed to these
CVEs, and requires a Cortex XDR agent release
7.1 or later and content 167-51646 or later. This
workaround is not recommended for non-
persistent, stateless, or linked-clone
environments. In some cases, enabling this
workaround can affect the network
functionality...

4.1.2.1.1.3. Set up agent settings profiles 

🔒

🟣c…

Requires a Cortex XDR Pro per Endpoint
license. When you enable this feature, a Cortex
XDR Pro per Endpoint license is consumed.

🔒

🟣c…

Requires Host Insights add-on.

🔒

🟣c…

Requires Forensics Add-on.

🔒

🟣c…

Requires a Cortex XDR Pro per Endpoint
license. When you enable this feature, a Cortex
XDR Pro per Endpoint license is consumed.

🔒

🟣c…

Requires Host Insights add-on.

🔒

🟣c…

Requires Forensics Add-on.

🔒

🟣c…

Requires a Cortex XDR Pro per Endpoint
license. When you enable this feature, a Cortex
XDR Pro per Endpoint license is consumed.

🔒

🟣c…

Requires Host Insights add-on

☑️

🟣pr…

User Space Agent mode requires Linux kernel
5.0.0 or higher.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Disabling Device Control Violation notifications
is only supported on endpoints running Cortex
XDR agent version 8.6 and above.

📝

🟢note

You can enable the option to maintain a
persistent notification regarding the
disconnection of the endpoint from the
network. The settings Persistent Isolation
Notification and Blocked Connectivity
Notification must be enabled. Until the threat
on the endpoint has been removed, the
endpoint remains disconnected from the
network.

📝

🟢note

In Traps 5.0.6 and later releases, when
protection is enabled, access will be read-only.
In earlier Traps releases, enabling protection
disables all access to services, processes, files,
and registry values.

📝

🟢note

If you choose the Enable option, you must also
enable XDR Agent Tampering Protection in the
malware profile and set it to Block. Ensure that
both profiles are assigned to the same
endpoints.

📝

🟢note

When you enable Cortex XDR agent
registration with the Windows Security Center,
Windows automatically shuts down Microsoft
Defender on Windows-based workstation
endpoints. If you still want to allow Microsoft
Defender to run on a workstation endpoint
where Cortex XSIAM is installed, you must use
the Disable option. However, Palo Alto
Networks does not...

📝

🟢note

To enable access to these options, scroll down
to Network Location Configuration, and set
Action Mode to Enabled.

📝

🟢note

When using Nmap, the Cortex XDR agent
downloads an Nmap driver for the duration of
the scan and removes the driver upon
completion. If an Nmap scan is in process,
Cortex XSIAM identifies the Nmap driver and
places any additional scans in a queue.

📝

🟢note

If you disable content updates for a newly
installed agent, the agent retrieves the content
for the first time from Cortex XSIAM, and then
disables content updates on the endpoint.
When you add a Cortex XDR agent to an
endpoint group with a disabled content auto-
upgrades policy, the policy is applied to the
added agent as well.

📝

🟢note

Automatic upgrades are not supported with
non-persistent VDI and temporary sessions.

📝

🟢note

The delay timer starts from the date of the
target agent version's availability in the tenant.

📝

🟢note

Limitations in the content download process:
When you install the Cortex XDR agent, the
agent retrieves the latest content update
version available. A freshly installed agent can
take between five to ten minutes (depending on
your network and content update settings) to
retrieve the content for the first time. During
this time, your endpoint is not...

📝

🟢note

If the Cortex XDR agent is initially unable to
communicate without the local store,
enforcement is not enabled and the agent will
show as partially protected.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Disabling Device Control Violation notifications
is only supported on endpoints running Cortex
XDR agent version 8.6 and above.

📝

🟢note

You can enable the option to maintain a
persistent notification regarding the
disconnection of the endpoint from the
network. The settings Persistent Isolation
Notification and Blocked Connectivity
Notification must be enabled. Until the threat
on the endpoint has been removed, the
endpoint remains disconnected from the
network.

📝

🟢note

If you choose the Enabled option, you must
also set Anti Tampering Protection in the
malware security profile to Block, and ensure
that both profiles are assigned to the same
endpoints.

📝

🟢note

When protection is enabled, access to services,
processes, files, and registry values will be
read-only.

📝

🟢note

If you disable content updates for a newly
installed agent, the agent retrieves the content
for the first time from Cortex XSIAM, and then
disables content updates on the endpoint.

📝

🟢note

Automatic upgrades are not supported with
non-persistent VDI and temporary sessions.
When a Cortex XDR agent is added to an
endpoint group, it inherits the group's policy,
including the disabled content auto-upgrades
setting.

📝

🟢note

The delay timer starts from the date of the
target agent version's availability in the tenant.

📝

🟢note

Limitations in the content download process:
When you install the Cortex XDR agent, the
agent retrieves the latest content update
version available. A freshly installed agent can
take between five to ten minutes (depending on
your network and content update settings) to
retrieve the content for the first time. During
this time, your endpoint is not...

📝

🟢note

If the Cortex XDR agent is initially unable to
communicate without the local store,
enforcement is not enabled and the agent will
show as partially protected.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

If you disable content updates for a newly
installed agent, the agent retrieves the content
for the first time from Cortex XSIAM, and then
disables content updates on the endpoint.
When you add a Cortex XDR agent to an
endpoint group with a disabled content auto-
upgrades policy, the policy is applied to the
added agent as well.

📝

🟢note

Automatic upgrades are not supported with
non-persistent VDI and temporary sessions.

📝

🟢note

Automatic upgrades are not supported for XDR
agents running on K8s.

📝

🟢note

The delay timer starts from the date of the
target agent version's availability in the tenant.

📝

🟢note

Limitations in the content download process:
When you install the Cortex XDR agent, the
agent retrieves the latest content update
version available. A freshly installed agent can
take between five to ten minutes (depending on
your network and content update settings) to
retrieve the content for the first time. During
this time, your endpoint is not...

📝

🟢note

User Space Agent mode requires Linux kernel
5.0.0 or higher. Endpoints running an older Linux
kernel version with this fallback enabled, will
not start using User Space Agent mode, and
will operate asynchronously.

📝

🟢note

If you disable content updates for a newly
installed agent, the agent retrieves the content
for the first time from Cortex XSIAM, and then
disables content updates on the endpoint.
When you add a Cortex XDR agent to an
endpoint group with a disabled content auto-
upgrades policy, the policy is applied to the
added agent as well.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

⛔

🔴w…

If you disable or delay automatic-content
updates provided by Palo Alto Networks, it may
affect the security level in your organization.

⛔

🔴w…

If you disable or delay automatic-content
updates provided by Palo Alto Networks, it may
affect the security level in your organization.

⛔

🔴w…

If you disable or delay automatic-content
updates provided by Palo Alto Networks, it may
affect the security level in your organization.

⛔

🔴w…

If you disable or delay automatic-content
updates provided by Palo Alto Networks, it may
affect the security level in your organization.

4.1.2.1.1.4. Set up restrictions prevention profiles 

🔒

🟣c…

A Threat Intel Management (TIM) license is
required for this feature.

🔒

🟣c…

A Threat Intel Management (TIM) license is
required for this feature.

🔒

🟣c…

A Threat Intel Management (TIM) license is
required for this feature.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Configure custom BIOC prevention rules here:
Detection & Threat Intel → Detection Rules →
BIOC

📝

🟢note

Configure this as follows:
Prepare this restriction profile first, make a note
of its name for later, and set it to Enabled.
Prepare the prevention Indicator Rule (go to
Detection & Threat Intel → Indicator Rules,
ensuring to select Prevention when creating the
rule), and while preparing it, map it to your
restriction profile.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Configure custom BIOC prevention rules here:
Detection & Threat Intel → Detection Rules →
BIOC

📝

🟢note

Configure this as follows:
Prepare this restriction profile first, make a note
of its name for later, and set it to Enabled.
Prepare the prevention Indicator Rule (go to
Detection & Threat Intel → Indicator Rules,
ensuring to select Prevention when creating the
rule), and while preparing it, map it to your
restriction profile.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Configure custom BIOC prevention rules here:
Detection & Threat Intel → Detection Rules →
BIOC

📝

🟢note

Configure this as follows:
Prepare this restriction profile first, make a note
of its name for later, and set it to Enabled.
Prepare the prevention Indicator Rule (go to
Detection & Threat Intel → Indicator Rules,
ensuring to select Prevention when creating the
rule), and while preparing it, map it to your
restriction profile.

📝

🟢note

New profiles based on imported profiles are
added, and do not replace existing ones.

📝

🟢note

Wildcards are supported.

4.1.2.1.1.5. Set up exception profiles and rules 

4.1.2.1.1.5.1. Exception configuration 

4.1.2.1.1.5.2.1. Add an issue exclusion rule  4.1.2.1.1.5.2. Issue exclusions 

4.1.2.1.1.5.3. Add an IOC or BIOC rule exception 

4.1.2.1.1.5.4. Add a disable prevention rule for
endpoints 

4.1.2.1.1.5.5. Add a disable injection and
prevention rule 

4.1.2.1.1.5.6. Add a support exception rule for
endpoints 

4.1.2.1.1.5.7. Add a legacy exception rule for
endpoints 

4.1.2.1.1.5.7.1. Add a new exceptions security
profile 

4.1.2.1.1.5.7.2. Add a global endpoint policy
exception 

4.1.2.1.2. Define endpoint groups 

📝

🟢note

Configuration based on user granular policy is
optimized for VDI and session-persistent
environments; it is not recommended for
decentralized or traditional endpoint
architectures.

📝

🟢note

Disconnecting Cloud Identity Engine in your
Cortex XSIAM deployment can affect existing
endpoint groups and policy rules based on
Active Directory properties.

4.1.2.1.3. Configure global agent settings 

📝

🟢note

Disabling this capability takes immediate effect
on new hashes, fresh agent installations, and
existing security policies. It could take up to a
week to take effect on existing agents in your
environment pending agent caching.

📝

🟢note

If you have any Cortex XSIAM filters, starring
policies, exclusion policies, scoring rules, log
forwarding queries, or automation rules
configured for XSOAR/3rd party SIEM, we
advise you to update those to support the
changes before activating the feature. For
example, change the query to include the
previous description that is still available in the...

4.1.2.1.4. Apply profiles to endpoints 

📝

🟢note

When importing a policy, select whether to
enable the associated policy targets. Rules
within the imported policy are managed as
follows:
New rules are added to the top of the list.
Default rules override the default rule in the
target tenant.
Rules without a defined target are disabled
until the target is specified.

📝

🟢note

The exported file is encoded in Base64 and
cannot be edited.

4.1.2.1.5. Create an agent installation package 

📝

🟢note

The profile will be applied if the security policy
cannot be retrieved in real-time.

📝

🟢note

The Cortex serverless library must be imported
after other libraries to activate the hooks that
enable auditing.

📝 4.1.2.1.5.1. Manage an agent installation package 

🟢note

Since Cortex XSIAM relies on the installation
package ID to approve agent registration during
the installation, we recommend that you don't
delete the installation package of active
endpoints. If you install the Cortex XDR agent
from a package after you delete it, Cortex
XSIAM denies the registration request leaving
the agent in an unprotected state....

4.1.2.1.6. Harden endpoint security 

⚠️

🟡c…

Hardened endpoint security capabilities are not
supported for Android or iOS endpoints.

🧭

➡️n…

From Inventory → Endpoints → Policy
Management → Extensions → Profiles, you can
create profiles for the following hardened
endpoint security capabilities

To apply the profiles, from Inventory →
Endpoints → Policy Management → Extensions
→ Policy Rules, you can view all the policy
rules per operating system

4.1.2.1.6.1. Device control 

📝

🟢note

Operating systems report on devices in
different ways. Sometimes, the same BLE device
will report different services and interfaces,
depending on the host's operating system. This
may have an effect on the specific BLE services
that are blocked for each operating system.
Depending on your defined user scope
permissions, creating device profiles,...

📝

🟢note

For network printer print jobs, ensure that you
also configure the Agent Settings profile,
Network Location Configuration option. This
setting must be set to Enabled, and configured.
If you do not enable and configure this setting,
all network printer operations will be treated as
internal network print jobs.
For network printer print jobs, ensure that...

📝

🟢note

Currently, the default is set to Use Default
(Allow), however, Palo Alto Networks may
change the default definition at any time.

📝

🟢note

You cannot edit or delete the default profiles
pre-defined in Cortex XSIAM.

📝

🟢note

You cannot edit or delete the predefined
profiles in Cortex XSIAM.

📝

🟢note

When importing a policy, select whether to
enable the associated policy targets. Rules
within the imported policy are managed as
follows:
New rules are added to the top of the list.
Default rules override the default rule in the
target tenant.
Rules without a defined target are disabled
until the target is specified.

📝

🟢note

Permanent exceptions apply across platforms,
allowing the devices on all operating systems.

📝

🟢note

Disabling Device Control Violation notifications
is only supported on endpoints running Cortex
XDR agent version 8.6 and above.

🧭

➡️n…

Endpoints → Policy Management → Settings →
Device Management

4.1.2.1.6.2. Host firewall 

4.1.2.1.6.2.1. Host firewall for Windows 

4.1.2.1.6.2.2. Host firewall for macOS 

4.1.2.1.6.3. Disk encryption 

📝

🟢note

You must select the same encryption method
configured by the Microsoft Windows Group
Policy in your organization for the target
endpoints. Otherwise, if you select a different
encryption method than the one already
applied through the Windows Group Policy,
Cortex XSIAM displays errors.

📝

🟢note

When importing a policy, select whether to
enable the associated policy targets. Rules
within the imported policy are managed as
follows:
New rules are added to the top of the list.
Default rules override the default rule in the
target tenant.
Rules without a defined target are disabled
until the target is specified.

🧭

➡️n…

You can monitor the Encryption Status of an
endpoint in the Inventory → Endpoints → Disk
Encryption Visibility table

4.1.2.1.6.4. Host Inventory 

📝

🟢note

If you have Cloud Posture Security, Cloud
Runtime Security, or Cortex XSIAM Premium
licenses, go to Inventory → Host Insights →
Host Inventory.

📝

🟢note

Cortex XSIAM includes only the first 10,000
results per endpoint.
Cortex XSIAM lists only users that belong to
each group directly, and does not include users
who belong to a group within the main group.
If a local users group includes a domain user
(whose credentials are stored on the Domain
Controller server and not on the endpoint),
Cortex XSIAM...

🧭

➡️n…

Inventory → Endpoints → Host Inventory

4.1.2.1.6.5. Vulnerability Assessment 

☑️

🟣pr…

The following are prerequisites for Cortex
XSIAM to perform a vulnerability assessment.
Requirement
Description
Licenses and Add-ons
Host Insights license.
This feature is included with Cortex XSIAM
Enterprise and with Cortex XSIAM NG SIEM with
a Host Insights license. If you have a Cloud
Posture Security, Cloud Runtime Security, or
Cortex XSIAM...

📝

🟢note

The CVE will be removed/reinstated to all
views, filters, and widgets after the next
vulnerability recalculation.

📝

🟢note

Starting with macOS 10.15, Mac built-in system
applications are not reported by the Cortex
XDR agent and are not part of the Cortex
XSIAM Application Inventory.

💡

🔵tip

You can click each individual CVE to view in-
depth details about it on a panel that appears
on the right.

💡

🔵tip

You can click each individual endpoint to view
in-depth details about it on a panel that
appears on the right.

4.1.2.1.7. Set a Cortex XDR agent Critical
Environment version 

📝

🟢note

To ensure the stability of the line, CE versions
maintenance release cadence is longer than in
the standard line, we recommend that
deployment is adjusted accordingly.

🧭

➡️n…

Settings → Configurations → General → Agent
Configurations

4.1.2.1.8. Set an application proxy for Cortex
XDR agents ⛔ 
🔴w…

If adding a proxy to the allow list be aware of
the following:
This allows any application on the isolated
endpoint to communicate through that proxy,
potentially allowing a threat actor or malware
to bypass the isolation and reach external
resources.

Ensure that no other non-security applications
are utilizing this proxy if you choose to allow it.

4.1.2.2. Manage endpoint protection 

4.1.2.2.1. Move agents between managing servers 

☑️

🟣pr…

Consider the following before making changes:
Endpoint type is not Kubernetes Node.
Installation type is not VDI.
Ensure you have administrator privileges for
Cortex XSIAM in the hub.

📝

🟢note

Cortex XSIAM does not support moving agents
between FedRamp and commercial tenants.

🧭

➡️n…

Inventory → Endpoints → Agent Installations

4.1.2.2.2. Manage endpoint tags 

📝

🟢note

The following explanations use Windows
operating system installation parameters and
Cytool argument examples.

📝

🟢note

Tag names are case sensitive.
In Windows and Mac, a tag name can contain
spaces.

Linux does not support tag names with spaces
as command line arguments to the shell
installer. Instead, tags can be set in the
/etc/panw/cortex.conf configuration file, which
supports all Linux installers.

📝

🟢note

Tag names are case sensitive and can contain
spaces.

📝

🟢note

Tag names are case sensitive and can contain
spaces.

📝

🟢note

When SBAC is enabled, assigning tags may
impact user permissions.

📝

🟢note

If you remove the tag and there are assigned
users or user groups with scope settings, this
can impact user permissions in the system.

💡 4.1.2.2.3. Set an alias for an endpoint 

🔵tip

If you change your mind in the future, you can
select Endpoint Control → Change Endpoint
Alias again, and delete the required aliases.

4.1.2.2.4. Manage endpoint prevention profiles 

📝

🟢note

The filter is stored within the policy definition
and assessed during runtime to extract the
functions that match the filter criteria.

🧭

➡️n…

From Inventory → Endpoints → Policy
Management → Prevention → Profiles, locate
the profile that you want to remove

Inventory → Endpoints → Policy Management
→ Prevention → Profiles

4.1.2.2.5. Upgrade Cortex XDR agents 

📝

🟢note

The Cortex XDR agent keeps the name of the
original installation package after every
upgrade.

📝

🟢note

It is possible to cancel an upgrade if the Status
is Pending. Once the Status is In Progress, the
action is already received by the agent locally
and cannot be canceled from the management
console.
Custom dashboards that include upgrade
status widgets, and the All Endpoints page
display upgrade status.
During the upgrade process, the endpoint
operating...

⛔

🔴w…

You must ensure that the System Extensions
were approved on the endpoint. Otherwise, if
the extensions were not approved, after the
upgrade the extensions remain on the endpoint
without any option to remove them which could
cause the agent to display unexpected
behavior. To check whether the extensions were
approved, you can either verify that the...

👀

🟠i…

The following list includes important points to
take into account when upgrading the Cortex
XDR agent:
Review the recommended guidelines for
keeping Cortex XDR agents and content
updated. Read more here.
You cannot upgrade the Cortex XDR agent on
VDI endpoints or a Golden Image.
You must reinstall (uninstall and install again)
the relevant agent...

4.1.2.2.6. Restart agent 

4.1.2.2.7. Uninstall the Cortex XDR agent 

📝

🟢note

Before upgrading a Cortex XDR agent running
on macOS 10.15.4 or later, you must ensure that
the System Extensions were approved on the
endpoint. Otherwise, if the extensions were not
approved, after the upgrade the extensions
remain on the endpoint without any option to
remove them which could cause the agent to
display unexpected behavior. To check...

💡

🔵tip

If needed, use the filter to filter the list of
endpoints by attribute or group name.

4.1.2.2.8. Clear agent database 

📝

🟢note

Clearing the agent database is supported on all
platforms with Cortex XDR agent version 7.9 or
later, and is available only when using the
debugging mode.

📝

🟢note

You can only right-click to cancel the clear
agent database for actions with a pending
status.

📝 4.1.2.2.9. Delete Cortex XDR agents 

🟢note

To reinstate an endpoint, you have to uninstall
and reinstall the agent.

4.1.2.2.10. Manage agent tokens 

📝

🟢note

Agent tokens are only supported for Windows
and Mac.

📝

🟢note

You can select a one or multiple agents to add
a temporary token.

4.1.2.2.11. Retrieve support file password 

4.1.2.2.12. Send push notifications to iOS 

4.1.2.2.13. Monitor agent operational status 

📝

🟢note

Any of the listed items could lead to a partially
protected state. Refer to the Cortex XSIAM
management console for specific reasons for
the state.

⚠️

🟡c…

Status can have the following implications on
the endpoint:
*(Status): The exploit protection module is not
running.
**(Status):
XDR data collection is not running
Behavioral threat protection is not running
Anti-malware flow is asynchronous
Local privilege escalation protection is
asynchronous
**(Status):
XDR data collection is not...

🧭

➡️n…

You can monitor the Cortex XDR agent
Operational Status in Inventory → Endpoints →
All Endpoints

4.1.2.2.14. Monitor agent activity 

🧭 4.1.2.2.15. Monitor agent upgrade status 

➡️n…

From Inventory → Endpoints → All Endpoints,
you can view the upgrade status of any Cortex
XDR agent that you manage

4.2. Endpoint DLP 

4.2.1. Cortex Data Loss Prevention (DLP) module
overview



☑️

🟣pr…

Endpoint DLP add-on license
Cortex agent 9.1 and above for Windows and
macOS

🧭

➡️n…

Settings → Configuration → Access
Management → Roles

4.2.2. Personas workflow for DLP 

4.2.3. Best Practices 

📝

🟢note

A good example would be to add the
description from the Raised Issue Name of the
specific Data-in-Motion rule.

📝

🟢note

When adding a source, it becomes a mandatory
requirement that must be met for the rule to
trigger. You should only apply this setting if you
want the rule to take action exclusively when
files originate from those specific locations.

🧭

➡️n…

Refer to Modules → Data Security → Data
Security Issues → Threats

Modules → Data Security → Endpoint Data-in-
Motion Rules → Endpoint DLP Settings to
configure the tenant settings for DLP

4.2.4.1. Onboarding checklist for DLP  4.2.4. Configure DLP end-to-end 

4.2.4.1.1. Install DLP browser extension on your
endpoint 

📝

🟢note

The extensions are not enabled for Incognito or
InPrivate modes in Chrome and Edge. It is
recommended to disable these modes in the
organization.

📝

🟢note

It is highly recommended to refer to Install the
Cortex XDR Agent using JAMF for a
comprehensive overview of setting up a JAMF
profile.Install the Cortex XDR Agent Using JAMF

👀

🟠i…

Endpoints should be linked to the domain.

🧭

➡️n…

Modules → Data Security → Endpoint Data-in-
Motion Rules → Endpoint DLP Settings

🧭 4.2.4.1.2. Create endpoint applications 

➡️n…

Modules → Endpoint Data-in-Motion Rules →
Endpoint Applications

📝 4.2.4.1.3. Create endpoint application groups 

🟢note

The catalog contains a list of all supported and
tested applications. If an application you need
is not on the list, contact support for assistance.

4.2.4.1.4. Create data-in-motion rules 

📝

🟢note

Third-party application behaviour:
When a file upload is blocked, the local
application may display its own generic error
message in response to the DLP restriction. In
similar cases, some third-party applications
might still proceed by sending a dummy file or
an error placeholder instead of the actual data.

📝

🟢note

To maximize data security, if you use Microsoft
Purview for extensive manual and automated
file classification tagging and are looking to
integrate those labels directly with the DLP
policies to trigger protective actions based on
a file's sensitivity, refer to How to use
information protection labels in Cortex Cloud
Data Security.

📝

🟢note

Distribution of the Endpoint DLP package is
restricted to agents assigned to the data-in-
motion policy. This ensures that only endpoints
requiring DLP functionality are affected, rather
than all eligible endpoints in the tenant.

4.2.4.1.5. Configure endpoint DLP settings 

📝

🟢note

When a fail-close action occurs, the system
creates a Data movement blocked by Endpoint
DLP fail-close action issue.

📝

🟢note

The agent does not force-install the extension
if it is already managed by the MDM on the
endpoint.
The XDR agent ensures full coverage by force-
installing the extension on both managed and
unmanaged browsers. But if a browser becomes
officially managed by the organization later,
the extension must be redeployed through the
central management console...

📝

🟢note

In the case of MDM, the extension is user-
managed, so Cortex doesn't remove an
installed MDM extension, it only disables
communication with the DLP extension.

📝

🟢note

You can specify the end-user message per rule.

4.2.5. DLP status in all endpoints 

📝

🟢note

It is recommended to work with the latest
security content.

📝

🟢note

Close and reopen your browser to activate the
DLP extension.

4.2.6. Cortex DLP threat detection and issues 

📝

🟢note

Access to this page is restricted to users with
the roles: Data Security Admin, Instance
Administrator, and Account Admin.

📝

🟢note

If the default action configured in Endpoint DLP
Settings is set to Block file movement (fail-
close), an issue is raised where the assigned
severity is set to low, and includes the Name
Data movement blocked by Endpoint DLP
default action

🧭

➡️n…

Data Security → Data Security Issues → Threats

From Data Security → Data Security Issues →
Threats, you can view the DLP issues

5. Detect, investigate, and respond
to threats 

5.1. Monitor dashboards and reports 

5.1.1. About dashboards 

📝

🟢note

Dashboards that are based on custom
infrastructure cannot be exported.
When importing a dashboard that already
exists in the system, the imported dashboard
overwrites the existing dashboard. To avoid
overwriting the existing dashboard, duplicate
and rename the existing dashboard before
importing the new dashboard.

👀

🟠i…

The ability to create, edit, or share custom
dashboards is governed by access
management. If certain options are unavailable,
contact your administrator. For more
information, see Manage access to custom
dashboards.

5.1.1.1. Command Center dashboards 

📝

🟢note

Access to these dashboards requires RBAC
permissions under Dashboards & Reports. The
Dashboards component must be Enabled in
your role and requires View permissions for
Command Center Dashboards. If certain
options are unavailable, contact your
administrator. For more information, Manage
access to custom dashboards.
The dashboards are available in dark...

📝 5.1.1.1.1. Cortex Command Center 

🟢note

Access to this dashboard requires RBAC
permissions under Dashboards & Reports. The
Dashboards component must be Enabled in
your role and requires View permissions for
Command Center Dashboards and Asset
Inventory. If certain options are unavailable,
contact your administrator. For more
information, see Manage access to custom
dashboards.

5.1.1.1.2. XSIAM Command Center 

5.1.1.1.2.1. Cortex Agentic Assistant dashboard 

☑️

🟣pr…

The Cortex Agentic Assistant is only available
after it is enabled, and for tenants in certain
regions. For more information, see Cortex
Agentic Assistant.

📝

🟢note

Access to this dashboard requires RBAC
permissions under Dashboards & Reports. The
Dashboards component must be Enabled in
your role and requires View permissions for
Command Center Dashboards. If certain
options are unavailable, contact your
administrator. For more information, see
Manage access to custom dashboards.

5.1.1.1.2.2. Data Inventory 

5.1.1.1.2.3. Dynamic View 

5.1.1.1.2.4. Cases Overview 

5.1.1.1.3. Cloud Detection and Response (CDR)
Command Center 🔒 
🟣c…

Requires Cortex XSIAM Premium, or any other
XSIAM license with the Cloud Runtime Security
or the Cloud Posture Security add-on.

5.1.1.1.4.1. Cloud Security Operations  5.1.1.1.4. Cloud Security Operations 

🔒

🟣c…

Requires Cortex XSIAM Premium, or any other
XSIAM license with the Cloud Runtime Security
or the Cloud Posture Security add-on.

📝

🟢note

Command Center data may not match the
counts on the Issues page, and you may
observe inconsistencies. This is because
dashboard data is a snapshot of issues
identified, whereas the Issues page provides the
most up-to-date view of risks across your
cloud assets. In addition, the Issues pages do
not support all the currently available filters on
the...

5.1.1.1.4.1.1. Dashboard Widgets 

5.1.1.1.4.1.1.1. Generate Reports 

5.1.1.1.4.1.1.2. Filter Options 

5.1.1.1.5. Cortex Cloud Command Center 

5.1.1.2. Predefined dashboards 

🔒

🟣c…

Requires the Cortex XSIAM Premium license or
any other XSIAM license with the Attack
Surface Management (ASM) add-on.

🔒

🟣c…

This feature is included with a Cloud Runtime
Security, Cloud Posture Security, or Cortex
XSIAM Premium license.

🔒

🟣c…

Requires the ITDR add-on.

📝

🟢note

This feature is included with a Cloud Runtime
Security, Cloud Posture Security, or Cortex
XSIAM Premium license.

📝

🟢note

Requires a Cortex XSIAM Enterprise Plus license.

📝

🟢note

Requires Cortex XSIAM Premium, Enterprise, or
any other XSIAM license that includes the
Enterprise Runtime add-on.

📝

🟢note

Users can access all information on the
dashboard when their user access is scoped to
view All assets or assigned to the Instance
Administrator role. Otherwise, users with
granular scoping set to No assets or Select
asset groups will have limited access to the
dashboard. For more information on Scope-
Based Access Control (SBAC), see Manage
user...

5.1.1.3.1. Report templates  5.1.1.3. Reports 

5.1.2. Build custom dashboards and reports 

📝 5.1.2.1. Build a custom dashboard 

🟢note

For agent-related widgets, you can apply an
endpoint scope to refine the displayed data to
only show results from specific endpoint
groups. Select the menu on the top right corner
of the widget, select Groups, and select one or
more endpoint groups.
For case-related widgets, you can refine the
displayed data to only show results from cases
that match a...

5.1.2.2. Manage your Widget Library 

📝

🟢note

Unlike dashboards, individual widgets cannot
be shared with other users directly from the
Widget Library. Yet, if you add a Restricted
widget to a dashboard and then share that
dashboard, other users who have access to the
dashboard will also be able to see that specific
widget.

📝

🟢note

Any dashboards or reports that include the
widget are affected by the changes.

5.1.3. Fine-tune dashboards and reports 

5.1.3.1. Create a custom widget using a script 

📝

🟢note

If you have added arguments to the script,
these appear when creating a widget.

📝

🟢note

Available options are Pie, Column, Line, and
Single Value.
To display the result of the script as a time
duration, choose the graph type Single Value
and enable Show as Time. You can then select
the Time Unit (millisecond, second, minute, or
hour) and the Display format.

5.1.3.1.1. Script-based widget examples 

📝

🟢note

Add the widget tag in the script settings to
make the script available for use in script-
based widgets. For more information, see
Create a script.

📝

🟢note

If your script returns a time duration, configure
the widget with the graph type Single Value
and enable Show as Time..

📝 5.1.3.2. Create a text widget 

🟢note

From the Dashboard Manager, you can right-
click an existing dashboard and choose Save as
report template. You can also add text-based
widgets directly to new or existing report
templates, as described below.

5.1.3.3. Create custom XQL widgets 

📝

🟢note

Cortex Query Language (XQL) queries
generated from the Widget Library do not
appear in the Query Center. The results are
used only for creating the custom widget.

📝

🟢note

Whenever the time period is changed in the
query window, the config timeframe is
automatically set to the time period defined,
but this won't be visible as part of the query.
Only if you manually type in the config
timeframe will this be seen in the query.
These time picker options are available in XQL
queries when using the Query Builder, XQL
Widgets,...

📝

🟢note

To display the result of as a time duration,
choose the graph type Single Value and enable
Show as Time. You can then select the Time
Unit (millisecond, second, minute, or hour) and
the Display format.

💡

🔵tip

You can create a generic dashboard for
multiple views of the same dataset by using an
asterisk (*) when defining the dataset in the
XQL widget as dataset = <dataset_name>*. The
placement of the asterisk in the dataset name
ensures that any view containing this prefix text
is displayed in the results.
The dataset in a query is defined as:
If there are...

5.1.3.3.1. Configure filters and inputs for custom
XQL widgets 

☑️

🟣pr…

Fixed filters are based on parameters that are
defined in custom XQL widgets. Before you can
configure fixed filters, take the following steps:
Create custom XQL widgets with parameters.
For more information, see Create custom XQL
widgets.
Add the widgets to a custom dashboard. For
more information, see Build a custom
dashboard.

📝

🟢note

This option only appears if the dashboard
contains custom XQL widgets with defined
parameters.

📝

🟢note

You can define up to four parameter filters on a
single dashboard or report.

📝

🟢note

If you specify more than one field, only the first
field value is used.

💡

🔵tip

After the initial setup, when you access your
dashboard the filters and inputs might need
further refinement. You can make changes to
the configured parameters in the XQL widgets,
and update the Filters & Inputs on your
dashboard until you are satisfied with the
results.

5.1.3.4. Configure dashboard drilldowns 

☑️

🟣pr…

To configure drilldowns your dashboard must
contain custom XQL widgets. In addition, if you
want to configure in-dashboard drilldowns your
custom XQL widget must contain one or more
parameters. For more information about
configuring parameters in custom XQL widgets,
see Create custom XQL widgets.

📝

🟢note

If the selected parameter is configured in other
XQL widgets on the dashboard, these widgets
are also affected by the drilldown.

5.1.3.4.1. Variables in drilldowns 

5.1.4. Run or schedule reports 

📝

🟢note

Report templates that are based on custom
infrastructure cannot be exported.
If you import a report template that already
exists in the system, the imported template will
overwrite the existing template. If you do not
want to overwrite the existing template,
duplicate and rename the existing template
before importing the new template.
You can also...

📝

🟢note

The report name and description will be
displayed in the report header and are not
editable during customization.

📝

🟢note

For agent-related widgets, you can apply an
endpoint scope to refine the displayed data to
only show results from specific endpoint
groups.

Select the menu on the top right corner of the
widget, select Groups, and select one or more
endpoint groups.
For agent-related widgets, you can apply an
endpoint scope to refine the displayed data to
only show...

📝

🟢note

To send reports to Slack, Slack must be
configured as an external application in Cortex
XSIAM. For more information, see Integrate
Slack for outbound notifications

🧭

➡️n…

Under Settings → Configurations → General →
Notifications, click + Add Forwarding
Configuration

5.2. Investigation and response 

5.2.1. Overview of cases 

5.2.1.1. What are cases? 

5.2.1.2. Resolving cases with AI 

5.2.1.3. Case lifecycle 

5.2.1.4. Case thresholds 

5.2.1.5. Case scope and impact 

📝 5.2.1.6. Case and issue domains 

🟢note

You can create your own custom domains to
match specific scenarios in your environment.
For more information, see Create a case
domain.Create a case domain

5.2.2. Case concepts 

5.2.2.1. Issues, findings, and events 

5.2.2.1.1. Issues 

5.2.2.1.2. Findings and events 

5.2.2.2. Case grouping 

5.2.2.3. Case scoring 

📝

🟢note

Requires a Cortex XSIAM Premium, Enterprise,
or Enterprise Plus license.

📝

🟢note

SmartScore requires sufficient data to
calculate and display the score. On first
activation, this can take up to 48 hours. If
sufficient data is not available, no score is
assigned.
If no match is found and there is sufficient data
available, Cortex XSIAM assigns a SmartScore.
If Cortex XSIAM doesn't have sufficient data to
assign a score, you can...

🧭 5.2.2.4. Case starring 

➡️n…

You can manage all starring configurations
under Case & Issues → Case Configuration →
Starred Issues

🔒 5.2.2.5. SLAs and tracking 

🟣c…

This feature requires a Cortex XSIAM Premium,
Cortex XSIAM Enterprise, or Cortex XSIAM NG
SIEM license.

📝 5.2.2.6. What is Causality? 

🟢note

There are no CGOs in the Cloud Causality
View, when investigating cloud Cortex XSIAM
alerts and Cloud Audit Logs, or SaaS Causality
View, when investigating SaaS-related alerts for
501 audit events, such as Office 365 audit logs
and normalized logs.

5.2.3. Analyze and resolve cases 

5.2.3.1. Review all cases 

📝

🟢note

The legacy view is also available for users who
prefer this format. From the Actions menu
select Switch to legacy view.

🧭

➡️n…

You can enable this setting from Settings →
Configurations → General → Server Settings →
Unified Case View

5.2.3.2. Start case analysis 

5.2.3.2.1. Agentic Assistant- Case Investigation

agent 

5.2.3.3. Establish case context 

5.2.3.3.1. AI-generated case summaries 

📝

🟢note

The AI-generated title and description is a
calculated value that is regenerated each time
you open a case.

This value is not a saved static description,
therefore it is not reflected in the saved case
names in the list of cases in the Split view , or in
the Case Name and Case Description columns
in the Table view.

🧭

➡️n…

Configurations → General → Server Settings →
AI Configuration and enable the following
settings

5.2.3.3.2. Assess case severity and score 

📝 5.2.3.3.3. Update case attributes 

🟢note

The defined values are shown in the Case Name
and Case Description columns in the Table view,
and saved to the cases dataset. The case title is
also shown the list of cases in the Split view.
These values do not replace the AI-generated
case title and summary. If the Summarize with
AI toggle is enabled, AI-generated case
summaries are automatically...

5.2.3.4. Analyze case details 

📝

🟢note

If you prefer a tabular or legacy layout, switch
the case card to the Detailed view.
This view preserves the legacy tab based
format and custom layouts, ensuring full
backward compatibility. You can switch
between the new case experience and the
legacy view based on personal workflow
preferences. For more information, see Detailed
View.

📝 5.2.3.4.1. Grouping graph 

🟢note

Similar issues are displayed as individual entities
rather than in a parent/child hierarchy.

5.2.3.4.2. Evidence 

5.2.3.4.3. Issue feed 

📝 5.2.3.4.4. Associated assets and artifacts 

🟢note

If you do not have permissions to access an
asset of a case (which is shown as grayed out
and locked), check your scoping permissions in
Manage Users or Manage User Groups.

📝 5.2.3.4.5. MITRE ATT&CK tactics and techniques 

🟢note

This component is available for cases
associated with the Security domain or custom
domains.

5.2.3.4.6. Detailed View 

📝

🟢note

When an issue is resolved, it remains linked to a
case. Once all of the issues in a case are
resolved, the case is automatically closed.

📝

🟢note

Cloud-related issues are displayed in the User
Name grouping.
Prisma Cloud Compute issues are displayed in
the Host Name grouping.

5.2.3.5. Resolve the case 

📝 5.2.3.5.1. Resolution Center 

🟢note

Tasks that are already In Progress but still
require your input will appear in both the
Pending and In Progress tabs.

5.2.3.5.2. Collaborative notes and comments 

📝 5.2.3.5.3. Resolve a case 

🟢note

If a case is resolved with the status Resolved -
Auto Resolved, Cortex XSIAM can reopen the
case for up-to six hours if a new issue is
triggered that matches the case. The six-hour
period is defined by the timestamp of the last
issue that was grouped into the case. After the
six-hour period, any new issues are linked to a
new case for a new...

5.2.3.5.4. Resolution reasons for cases and issues 

📝

🟢note

The displayed resolution reasons are domain-
specific. You can see the resolution reasons
that are defined for a domain under
Configurations → Object Setup → Cases →
Domains.

📝

🟢note

Cases and issues resolved as True Positive and
False Positive help Cortex XSIAM to identify
real threats in your environment by comparing
future cases and associated issues to the
resolved cases. Therefore, the handling and
scoring of future cases is affected by these
resolutions.

📝

🟢note

Cases and issues resolved as True Positive and
False Positive help Cortex XSIAM to identify
real threats in your environment by comparing
future cases and associated issues to the
resolved cases. Therefore, the handling and
scoring of future cases is affected by these
resolutions.

5.2.3.6. Additional case actions 

5.2.3.6.1. Create a case 

📝

🟢note

To create a case manually, you must have
View/Edit permission for Cases and Issues
selected under Settings → Configurations →
Access Management → Roles → Components
→ Cases & Issues.

📝

🟢note

You can assign a case to a single domain only,
and you cannot change the assigned domain.
For more information, see Case and issue
domains.

📝

🟢note

This option is only relevant for certain domains.

📝

🟢note

This option is only relevant for certain domains.

📝

🟢note

You can't attach files to manually created
cases.

💡

🔵tip

The issues that you link to a case can be linked
to multiple cases, and the issue domains do not
need to match the case domain.

5.2.3.6.2. Merge a case 

5.2.3.7. Unified case view 

🔒

🟣c…

Requires an MSSP license.

📝

🟢note

Requires the following RBAC permissions:
Cases & Issues
Investigation & Response → Automation
Requires the following RBAC permissions:
Cases & Issues
Investigation & Response → Automation
This view is available for the parent tenant only.
To take actions on a child tenant from a parent
tenant, you must have the appropriate
permissions for both...

📝

🟢note

Custom case layouts of child tenants are not
visible in the parent tenant.

5.2.4. Investigate issues 

📝 5.2.4.1. Overview of the Issues page 

🟢note

Every 12 hours, the system enforces a cleanup
policy to remove the oldest issues once the
maximum limit is exceeded. The default issue
retention period in Cortex XSIAM is 186 days.

5.2.4.2. Issue card 

🔒

🟣c…

Requires Cortex XSIAM Premium license or any
other XSIAM license with the TIM add-on.

📝

🟢note

This section is context-specific and shows data
according to the issue context.

5.2.4.3. Link or unlink issues from a case 

5.2.4.4. Run an automation on an issue 

📝

🟢note

In addition to automation, some playbooks
contain manual tasks that prompt the analyst
for input. This enables you to enhance an
automation workflow with analyst input.

📝

🟢note

You can also manually select a playbook to run
from the Issue Work Plan tab.

5.2.4.5. Use the War Room in an investigation 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

The case War Room is usually used for
communication capabilities, but unlike the issue
War Room, it does not include playbook
specific entries. The case War Room enables
you to investigate an entire case, not just an
issue.

📝

🟢note

Cortex XSIAM does not index notes and chats.

💡

🔵tip

In the Playground, you can clear the context
data, if needed, which deletes everything in the
Playground context data, but does not affect
the actual issue or case. To clear the context,
run !DeleteContext all=yes' from the CLI or
click Clear Context Data while viewing the
context data.

💡

🔵tip

You can use the up/down arrow buttons in the
CLI to do a reverse history search for previous
commands with the same prefix.

🧭

➡️n…

Investigation & Response → Automation →
Playground

👀 5.2.4.6. Use the Work Plan in an investigation 

🟠i…

A playbook will not continue its execution path
if a prior task has failed; you must resolve the
failed task before subsequent tasks can run.

5.2.4.7. Issue syncing 

☑️

🟣pr…

You must set up an integration before you can
sync issues. For more information, see Set up an
integration for mirroring issues.

☑️

🟣pr…

You must set up an integration before you can
sync issues. For more information, see Set up an
integration for mirroring issues.

☑️

🟣pr…

You must set up an integration before you can
sync issues. For more information, see Set up an
integration for mirroring issues.

📝

🟢note

Multiple tickets can be linked to an issue with
outbound syncing. Issues with inbound syncing
can be linked to a single ticket only.

📝

🟢note

Using issue fields as variables is not currently
supported.

📝

🟢note

You can only define a single inbound profile. If
you change the inbound sync profile the
current profile is overwritten.
You can define multiple outbound profiles; one
issue can update multiple tickets.

📝

🟢note

Using issue fields as variables is not currently
supported.

📝

🟢note

You can only define a single inbound profile. If
you change the inbound sync profile the
current profile is overwritten.
You can define multiple outbound profiles; one
issue can update multiple tickets.

📝

🟢note

The inbound syncing flow runs every two
minutes, and the outbound syncing flow runs
every five minutes.
In a bi-directional set-up, if the same field is
updated in both tickets, the most recently
updated value is used.
In the external ticket, the logged history shows
updates to the ticket. The user name that is
logged with the history reflects the user...

📝

🟢note

After an issue is resolved, ticket syncing
remains active for up-to seven days. Therefore,
you still update, change, or reopen the issue or
external ticket and the tickets will continue to
sync.

📝

🟢note

If you change the selected inbound sync
profile, the original sync profile is immediately
overwritten.

📝

🟢note

You can only define a single inbound profile. If
you change the inbound sync profile the
current profile is overwritten.
You can define multiple outbound profiles; one
issue can update multiple tickets.

⛔

🔴w…

If you leave this field blank, all configured
instances will be used.

⛔

🔴w…

If you leave this field blank, all configured
instances will be used.

💡

🔵tip

You can find a sync profile ID under Settings →
Configurations → Object Setup → Issues →
Sync Profiles. By default the ID field is not
displayed in the table. Click the three dot menu
and add it to the table layout.

5.2.4.8. Cortex Response and Remediation
content pack 

5.2.4.8.1. Investigate an issue using Cortex
Response and Remediation playbooks



5.2.4.8.2. Example use cases 

5.2.4.9. Causality view 

💡

🔵tip

To view statistics for files on VirusTotal, you
can pivot from the Initiator MD5 or SHA256
value of the file on the Files tab.

5.2.4.9.1. Network causality view 

📝

🟢note

The network causality view displays only the
information it collects from the detectors. It is
possible that the CI may not show some of the
firewall or agent processes.

💡

🔵tip

To view statistics for files on VirusTotal, you
can pivot from the Initiator MD5 or SHA256
value of the file on the Files tab.

5.2.4.9.2. Cloud causality view 

5.2.4.9.3. SaaS causality view 

📝 5.2.4.9.4. Timeline 

🟢note

The Timeline view is not available when
investigating cloud Cortex XSIAM issues and
cloud audit logs or SaaS-related issues for 501
audit events, such as Office 365 audit logs and
normalized logs. Only the applicable cloud
causality view and SaaS causality view is
available for this data.

5.2.4.9.5. Causality icons key 

5.2.4.10. Issue investigation actions 

5.2.4.10.1. Copy issues 

5.2.4.10.2. Update issue fields 

📝

🟢note

You must create a custom status before you
can select it.

💡

🔵tip

You can create custom issue statuses and
resolution reasons, and use the setIssueStatus
command to set these custom statuses for
issues.
For example, when a user starts investigating an
issue, the issue status is automatically changed
from New to Under Investigation. In some cases,
it is useful to create an interim status, such as
Triage. After you...

5.2.4.10.3. Query case and issue data 

5.2.4.10.4. Exclude an issue 

5.2.4.10.5. Create a featured field 

📝

🟢note

Featured Active Directory values are displayed
in the User and Host fields accordingly.

🧭

➡️n…

Cases & Issues → Case Configuration →
Featured Fields and select a type of featured
field

5.2.4.10.6. Export issue details to a file 

5.2.4.10.7. Investigate contributing events 

💡 5.2.4.10.8. Retrieve additional issue details 

🔵tip

If you require assistance from Palo Alto
Networks support to investigate the issue, make
sure to provide the downloaded ZIP file.

5.2.4.10.9. View generating BIOC or IOC rule 

🧭 5.2.4.10.10. Create profile exceptions 

➡️n…

Inventory+Endpoints → Policy Management →
Profiles

5.2.4.10.11. Add a file path to a malware profile
allow list 

🔒

🟣c…

Requires Cortex XSIAM Enterprise, Premium, or
any other XSIAM license that includes
endpoints or Cortex Cloud Runtime Security.

🧭

➡️n…

Inventory+Endpoints → Policy Management →
Prevention → Profiles and locate the malware
profile you selected

📝 5.2.4.10.12. Close an issue 

🟢note

When an issue is resolved it remains linked to a
case. Once all of the issues in a case are
resolved, the case is automatically closed.

5.2.5. Review findings 

📝

🟢note

Some finding types require the Cortex XSIAM
Premium license, or any other XSIAM license
with the Cloud Posture Security or Cloud
Runtime Security add-on.

📝 5.2.5.1. Findings card 

🟢note

The information in this card is context specific,
therefore some sections are not available for all
findings.

5.2.6. Investigate artifacts and assets 

📝 5.2.6.1. Investigate an IP address 

🟢note

Requires a license key. Select Settings →
Configurations → Integrations → Threat
Intelligence.

📝 5.2.6.2. Investigate an asset 

🟢note

The Asset view is available for hosts with a
Cortex XDR agent installed.

5.2.6.3. Investigate a host 

🔒

🟣c…

The Host Risk View requires the Identity Threat
Module add-on. Depending on your
permissions, some information may be limited
by your scope.

🔒

🟣c…

The Host Risk view is available with the ITDR
add-on. Depending on your permissions, some
information may be limited by your scope.

📝

🟢note

Cortex XSIAM normalizes and displays case and
issue times in your time zone. If you're in a half-
hour time zone, the activity in the graphs is
displayed in the whole-hour time slot preceding
it. For example, if you're in a UTC +4.5 time
zone, the time displayed for the activity will be
UTC +4.5, however, the visualization will be in
the UTC +4 slot.

💡

🔵tip

You can also see a list of all hosts under
Inventory → Assets → Asset Scores.

📝 5.2.6.4. Investigate a file and process hash 

🟢note

Requires a license key. Go to Settings →
Configurations → Integrations → Threat
Intelligence.

5.2.6.5. Investigate a user 

🔒

🟣c…

If the Identity Threat module is enabled, you
can open the User Risk View. This view displays
insights and profiling information to help you
investigate issues and cases. Viewing anomalies
in the context of baseline behavior facilitates
risk assessment and shortens the time you
require for making verdicts.
If the Identity Threat module is not enabled...

🔒

🟣c…

The User Risk view is available with the ITDR
add-on. Depending on your permissions, some
information may be limited by your scope.

📝

🟢note

Cortex XSIAM normalizes and displays case and
issue times in your time zone. If you're in a half-
hour time zone, the activity in the Issues &
Insights Heatmap is displayed in the whole-hour
time slot preceding it. For example, if you're in a
UTC +4.5 time zone, the time displayed for the
activity will be UTC +4.5, however, the
visualization in the...

💡

🔵tip

You can also see a list of all users under
Inventory → Assets → Asset Scores.

5.2.7. Investigate endpoints 

5.2.7.1. Overview of the Action Center 

📝

🟢note

For actions on endpoints, you need a Cortex
XSIAM Premium, or Enterprise license, or any
other XSIAM license with the Enterprise
Runtime Security or Cloud Runtime Security
add-on.

📝

🟢note

Blocking files on endpoints is enforced by the
endpoint malware profile. To block a hash
value, ensure the hash value is configured in the
Malware security profile.
Select Override Report mode to allow the
agent to block hashes, even if the Malware
Profile is set to Report.

🧭

➡️n…

Investigation & Response → Response → Action
Center

5.2.7.1.1. Initiate and monitor endpoint actions 

5.2.7.1.2. Action Center reference information 

5.2.7.2. Manage endpoints 

📝

🟢note

For the Include endpoints from auto upgrade
action, you cannot enable auto upgrade for
Mobile, VDI, and TS installations.

📝

🟢note

If an endpoint is excluded, the auto upgrade
profile configuration is not available.
If you exclude the endpoint from auto upgrade
while the auto upgrade action is In progress,
the ongoing upgrade will still take place.

📝

🟢note

Content Status is calculated every 30 minutes.
Therefore, there might be a delay of up to 30
minutes in displaying the data.

📝

🟢note

Only supported for Windows and macOS.

📝

🟢note

Changes to the agent status can take up to ten
minutes to display on Cortex XSIAM .

🧭

➡️n…

Inventory → Endpoints → All Endpoints

Settings → Configurations → General → Agent
Configurations → Endpoint Administration
Cleanup

5.2.7.3. Retrieve files from an endpoint 

📝

🟢note

You cannot define a path using environment
variables on Mac and Linux endpoints.

📝

🟢note

If the Password Protection (for downloaded
files) setting under Settings → Configuration →
General → Server Settings is enabled, enter the
password 'suspicious' to download the file.

📝

🟢note

Disabling File Retrieval does not take effect on
file retrieval actions that are in progress.

🧭 5.2.7.4. Retrieve support logs from an endpoint 

➡️n…

Investigation & Response → Response → Action
Center → + New Action

🧭 5.2.7.5. Retrieve support file password 

➡️n…

Retrieve Support File Password from Inventory
→ Endpoints → All Endpoints

🧭 5.2.7.6. Scan an endpoint for malware 

➡️n…

Investigation & Response → Response → Action
Center → New Action

5.2.8. Investigate files 

📝

🟢note

To take actions on endpoints, you need the
Cortex XSIAM Premium, Enterprise, or any other
XSIAM license with the Enterprise Runtime
Security (XDR) add-on.

5.2.8.1. Manage file execution 

📝 5.2.8.2. Manage quarantined files 

🟢note

This will restore all files with the same hash on
all of your endpoints.

📝 5.2.8.3. Review WildFire analysis details 

🟢note

Cortex XSIAM displays the preview of WildFire
reports that were generated within the last
couple of years. To view a report that was
generated more than two years ago, you can
download the report.

5.2.8.4. Import file hash exceptions 

5.2.9. Cortex Assistant 

📝

🟢note

If you are in an eligible region and have enabled
the Cortex Agentic Assistant, the Cortex
Agentic Assistant replaces the Cortex Assistant.
The Cortex Assistant is available if you do not
have access to the Cortex Agentic Assistant
based on the tenant region or you have not
enabled it. For more information, see Cortex
Agentic Assistant.

🧭

➡️n…

To increase usability, you can create a
personalized keyboard shortcut: Settings →
Configurations → Server Settings → Keyboard
Shortcuts and choose the shortcut you want to
use

5.2.9.1. Cortex Assistant layout 

5.2.9.2. Cortex Assistant capabilities 

📝

🟢note

In some cases, if the prompt does not include at
least one recognizable entity such as an IP,
hash, user, asset, domain, case, or XQL query,
no response is returned.

📝

🟢note

When you choose an option from the Respond
column, Cortex Assistant will always prompt
you to approve the action before executing.

5.2.10. Response actions 

⚠️

🟡c…

Response actions are not supported for
Android endpoints.

5.2.10.1. Initiate a Live Terminal session 

📝

🟢note

You can run PowerShell 5.0 or a later release on
Live Terminal of Windows.

📝

🟢note

Network drives are not supported.

📝

🟢note

On Windows endpoints, you cannot run GUI-
based cmd commands like winver or appwiz.cpl.

📝

🟢note

Disabling Live Terminal does not take effect on
sessions that are in progress.

💡

🔵tip

You can fine-tune the Live Terminal session
visibility on the endpoint by adjusting the User
Interface options in your Agent Settings Profile.

5.2.10.2. Isolate an endpoint 

📝

🟢note

IP-based file storage protocol traffic will also
be blocked. This might affect endpoint
functionality if the endpoint uses such mounts.

📝

🟢note

If file system operations become unresponsive
during isolation, such as being unable to list
folder content, unmount the mounted network
shares.

💡

🔵tip

If needed, Filter the list of endpoints.

5.2.10.3. Pause endpoint protection 

📝

🟢note

Pausing your endpoint protection modules
leaves your machines exposed to risks.

🧭

➡️n…

Investigation & Response → Response → Action
Center and locate Action Type Pause Endpoint
Protection or Resume Endpoint Protection

5.2.10.4. Run agent scripts on an endpoint 

☑️

🟣pr…

To run scripts on an endpoint, you must have
the following system requirements:
Endpoints running the Agent v7.1 and later.
Since the agent uses its built-in capabilities and
many available Python modules to execute the
scripts, no additional setup is required on the
endpoint.
Role in the hub with the following permissions
to run and configure...

📝

🟢note

*Since all scripts are running under System
context, you cannot perform any registry
operations on user-specific hives
(HKEY_CURRENT_USER of a specific user).

📝

🟢note

Always use lowercase for variable names.

📝

🟢note

Disabling Script Execution does not take effect
on scripts that are in progress.

5.2.10.5. Remediate changes from malicious
activity 

☑️

🟣pr…

To initiate remediation suggestions, you must
have the following system requirements:
An App Administrator, Privileged Responder, or
Privileged Security Admin role permissions
which include the remediation permissions.
EDR data collection enabled.
Agent version 7.2 or above on Windows
endpoints.

📝

🟢note

Endpoints that are part of the Case view and
do not meet the required criteria are excluded
from the remediation analysis.

5.2.10.6. Search and destroy malicious files 

☑️

🟣pr…

The following are prerequisites to enable
Cortex XSIAM to search and destroy files on
your endpoints:
Supported platforms:
Windows: Cortex XDR agent version 7.2 or a
later. If you plan to enable Search and Destroy
on VDI sessions, you must perform the initial
scan on the Golden Image.
Mac: Cortex XDR agent version 7.3 or a later
release running on...

📝

🟢note

The Cortex XSIAM agent does not include the
following information in the local files inventory:
Information about files that existed on the
endpoint and were deleted before the Cortex
XSIAM agent was installed.
Information about files where the file size
exceeds the maximum file size for hash
calculations that are pre-configured in Cortex
XSIAM .
If...

5.2.10.7. Manage external dynamic lists 

📝

🟢note

Configuring custom certificates or private API
Keys in the EDL integration instance is
supported only on engines, not on the Cortex
XSIAM tenant.
For EDL integrations on the tenant, you must
set a username and password. For long-running
integrations running on an engine, we strongly
recommend setting a username and password,
but it is not required. You...

📝

🟢note

Ensure EDL sizes don't exceed your firewall
model limit.

👀

🟠i…

The EDL URL must always be prefixed by ext-.

💡

🔵tip

You can also use the IP list and URL lists as part
of a URL Filtering policy, or the domain list as
part of a custom Anti-Spyware profile.

🧭

➡️n…

If creating a custom role, select View/Edit for
EDL (Roles → New Roles → INVESTIGATION &
RESPONSE → Response → EDL

🔒 5.2.10.8. Collect a memory image 

🟣c…

This functionality has the following license
requirements:
Forensics add-on license.

5.2.11. Forensics 

🔒

🟣c…

Requires the Forensics add-on

5.2.11.1. Forensic investigations 

5.2.11.1.1. Manage an investigation 

📝 5.2.11.1.1.1. Create a new investigation 

🟢note

To set up user permissions, you must have
Scope-Based Access Control (SBAC) enabled.

5.2.11.1.1.2. Edit an investigation 

📝 5.2.11.1.1.3. Close an investigation 

🟢note

When you close an investigation, Palo Alto
Networks has a grace period of 24 hours before
deleting any collections associated with the
investigation. During this timeframe, you have
the option to cancel the close investigation
action.

📝 5.2.11.1.1.4. User permissions 

🟢note

Even if a user does not have access to view an
investigation via the Forensics Investigations
page, they can still query the results of the
collections using an XQL query.

5.2.11.1.2. Data collection 

5.2.11.1.2.1. Hunting 

5.2.11.1.2.1.1. Create a hunt 

5.2.11.1.2.1.2. Hunt results 

5.2.11.1.2.1.3. Hunt status 

5.2.11.1.2.2. Triage 

5.2.11.1.2.2.1. Create a triage 

5.2.11.1.2.2.2. Upload an offline triage package 

5.2.11.1.2.2.3. Offline triage collection 

5.2.11.1.2.2.4. Triage results 

5.2.11.1.2.2.5. Triage status 

5.2.11.1.2.3. Configure collection 

📝

🟢note

When search fields are specified, the search is
limited based on those filters. If more than one
entry is in a search filter field, the search
returns entries that match any of them. For
example: A File Search with two specified paths
("C:\Test*" and "C:\Windows*") will return
results from both the Test and Windows folders.
If you specify multiple...

📝

🟢note

Data collected during a Triage Collection is
categorized into Artifacts, Volatiles, and File
Collection

📝

🟢note

Supported only for the UFW tool (Firewall
managment tool for some Linux distributions
such as Ubuntu)

5.2.11.1.3. Analysis and documentation 

5.2.11.1.3.1. Review alerts 

5.2.11.1.3.2. Investigation timeline 

5.2.11.1.3.3. Key assets & artifacts 

📝 5.2.11.1.4. Export 

🟢note

You can export a collection more than once.

5.2.12. Notebooks 

📝

🟢note

The Instance Administrator role has these
permissions by default.

📝

🟢note

You can only add one instance of Notebooks.
Notebooks have access to approved sites on
the internet when embedded in Cortex XSIAM.
To delete the Notebook, hover over Notebooks
and select the delete icon.
Installing or uninstalling some plug-ins and
packages requires the Notebooks server to
refresh the web page. For these actions, go to
File → Shut...

👀

🟠i…

You need a daily minimum of 1000 compute
units. After activation, 1,000 units are deducted
daily at 00�00 UTC.
XQL and BQ queries performed in Cortex
XSIAM Notebooks are calculated similarly to
Compute Unit usage of XQL queries originating
from public APIs. You can't create a Jupyter
instance without sufficient Compute Units.
Based on your security...

🧭

➡️n…

Before you begin, ensure that you have the
View/Edit permissions in Settings →
Configurations → Access Management →
Roles → Configurations → Apps

In Cortex XSIAM, select Settings →
Configurations → Integrations → Apps

View/Edit permissions in Settings →
Configurations → Access Management →
Roles → Apps → Jupyter

5.2.12.1. Manage datasets in Notebooks 

📝

🟢note

If a schema is not provided, the function
automatically detects the schema.

📝

🟢note

Using this function, you can only delete
datasets created using the Notebooks APIs.
When you delete a dataset, the rules that use
the dataset return an error.

5.2.12.2. Notebooks scheduler 

5.2.13. Build XQL queries 

📝

🟢note

If you have the Cortex Agentic Assistant, you
can use natural language prompts to create
and run XQL queries within the chat interface.
For more information, see Create and run XQL
queries with Agentic Assistant chat.

5.2.13.1. About the Query Builder 

📝

🟢note

Schema changes to datasets may not be
reflected in the autocomplete suggestions and
definitions as you type in real time the XQL
query, and can appear with a slight delay.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion commands and
definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc key.

💡

🔵tip

If you prefer to use the Query Builder in Legacy
mode, switch the toggle in the header. In
Legacy mode, the Query Builder searches
predefined datasets only. To search the full
XDM Data Model, switch to New mode or
select XQL Search.

5.2.13.2. How to build XQL queries 

📝

🟢note

Users with different dataset permissions can
receive different results for the same XQL query.
An administrator or a user with a predefined
user role can create and view queries built with
an unknown dataset that currently does not
exist in Cortex XSIAM. All other users can only
create and view queries built with an existing
dataset.
When you have more...

📝

🟢note

You can build a query that investigates data in
both a cold dataset and a hot dataset in the
same query. In addition, as the hot storage
dataset format is the default option and
represents the fully searchable storage, this
format is used throughout this guide for
investigation and threat hunting. For more
information on hot and cold storage, see...

👀

🟠i…

Forensic datasets are not inlcuded by default in
XQL query results, unless the dataset query is
explicitly defined to use a forensic dataset.

💡 5.2.13.2.1. Get started with XQL queries 

🔵tip

If you are new to creating queries, you can also
try our simple search templates, which can help
you get started in understanding how queries
work. See Query Builder templates.Query
Builder templates

5.2.13.2.2. Useful XQL user interface features 

📝

🟢note

Schema changes to datasets may not be
reflected in the autocomplete suggestions and
definitions as you type in real time the XQL
query and can appear with a slight delay.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

5.2.13.2.3. XQL Query best practices 

5.2.13.2.4. Expected results when querying fields 

5.2.13.2.5. Create XQL query 

📝

🟢note

Whenever the time period is changed in the
query window, the config timeframe is
automatically set to the time period defined for
the entire query, including queries that are part
of the join stage. Yet, this won't be visible as
part of the query. Only if you manually type in
the config timeframe will this be seen in the
query.

These time picker...

📝

🟢note

While datamodel dataset=* is supported in the
query, we recommend that you specify specific
datasets for quicker and more efficient results.

📝

🟢note

Whenever the time period is changed in the
query window, the config timeframe is
automatically set to the time period defined for
the entire query, including queries that are part
of the join stage. Yet, this won't be visible as
part of the query. Only if you manually type in
the config timeframe will this be seen in the
query.

These time picker...

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

💡

🔵tip

While the query is running, you can navigate
away from the page. A notification is sent when
the query has finished. You can also Cancel the
query or run a new query, where you have the
option to Run only new query (cancel previous)
or Run both queries.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

💡

🔵tip

While the query is running, you can navigate
away from the page. A notification is sent when
the query has finished. You can also Cancel the
query or run a new query, where you have the
option to Run only new query (cancel previous)
or Run both queries.

5.2.13.2.6. Review XQL query results 

📝

🟢note

It's also possible to graph the results displayed.
For more information, see Graph query results.

📝

🟢note

Real time query results are available only in the
Query Builder and in free text query.
Real time results are displayed only for queries
run on hot datasets.
The Sort option is available only after all the
data is retrieved.
When you formulate complex queries, the
results will be displayed when the query has
finished running completely, and not in real...

📝

🟢note

Results are received incrementally for the first
100K records, or up to 100MB worth of records,
whichever comes first. After that, the next
update is when the query has finished running
completely.

📝

🟢note

In order for Cortex XSIAM to provide a
histogram for a field, the field must not contain
an array or a JSON object.

👀 5.2.13.2.7. Translate to XQL 

🟠i…

This feature is still in a Beta state and you will
find that not all Splunk queries can be
converted to XQL. This feature will be improved
upon in the upcoming releases to support
greater Splunk query translations to XQL.

📝 5.2.13.2.8. Graph query results 

🟢note

To display the result of as a time duration,
choose the graph type Single Value and enable
Show as Time. You can then select the Time
Unit (millisecond, second, minute, or hour) and
the Display format.

5.2.13.3. Query Builder templates 

💡

🔵tip

To get started with queries, you can run an
empty template query with no values specified.
The query results will include all of the fields in
the template specific fieldset. Based on the
query results, you can run subsequent queries
to narrow down your search.

5.2.13.3.1. Get started with Query Builder
templates 

5.2.13.3.2. Considerations for using Query
Builder templates 

5.2.13.3.3. Create a query from a template 

📝

🟢note

Field names and aliases are listed without their
prefix, for example
xdm.SOURCE.USER.USERNAME is listed as
SOURCE.USER.USERNAME and XDM_ALIAS.ipv4
is listed as ipv4.
Fields that are already included in the query
template are shown as grayed out.
In the Identity and Network templates,
xdm.event.outcome shows as grayed out. In
these templates, the ACTION...

📝

🟢note

This order might change if you include a
filtering field that is listed in the fieldset. In that
case, the field is taken out of the fieldset and
ordered at the top of the list with the other
filtering fields.

5.2.13.3.4. Run a free text query 

📝

🟢note

Free-text search is also available in XQL
queries. You can use the search stage to query
free-text strings in specific datasets, or all of
the datasets in your tenant.

📝

🟢note

Free text search is limited to the last 90 days of
data. Specifying a time frame outside of this
limitation will cause the query to fail.

🧭 5.2.13.3.5. Query Builder template examples 

➡️n…

Investigation & Response → Search → Query
Builder

5.2.13.4. Overview of the Query Center 

📝

🟢note

Very short queries might not be listed.
You cannot cancel correlation queries.
The default retention period for historic queries
is aligned with issue retention.

5.2.13.4.1. Edit and run queries in Query Center 

📝

🟢note

If query limits are applied to your tenant, the
number of concurrent running queries is limited
per user. If query usage is reaching the defined
limit, a system message warns you that a high
query load is impacting performance. If you
exceed the limit, new queries are blocked until
query usage drops. You can view all active
queries under Query Center...

📝

🟢note

You can cancel your own queries. To cancel
queries run by other users, you must have
View/Edit permissions for Configurations →
Query Management. By default, Instance
administrators have View/Edit permission.

📝

🟢note

Cancelled queries show a Canceled status. You
can see details of all canceled queries in the
Query History tab.
You cannot cancel correlation rule queries.
If you cancel a scheduled query, only the
current query is cancelled. Future recurrences
of the scheduled query are not affected.

📝 5.2.13.4.1.1. Query Center reference information 

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

5.2.13.5. Manage scheduled queries 

🧭

➡️n…

Investigation & Response → Search →
Scheduled Queries

5.2.13.5.1. Scheduled Queries reference

information 📝 
🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

🧭 5.2.13.6. Manage your personal query library 

➡️n…

From the Query Builder Select Investigation &
Response → Search → Query Builder → XQL

Investigation & Response → Search → Query
Builder → XQL

5.2.13.7. Federated Search 

5.2.13.7.1. Federated Search 

📝

🟢note

Federated Search is not enabled by default. To
enable it in your tenant, please contact your
Customer Support Team.

📝

🟢note

Federated search query costs are calculated
according to timeframe, complexity, and any
cross-cloud egress costs that may apply.

📝

🟢note

For optimal results, we recommend the Parquet
format.

📝

🟢note

The list of supported regions may change in the
future.

5.2.13.7.2. Federated Search configuration 

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
An AWS bucket that contains your data sources.
Permissions to modify IAM policies in AWS.

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
A GCS bucket that contains your data sources.
Permissions to modify IAM policies in GCS.

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
An Azure Blob Storage blob with your data
sources.

Permissions to modify IAM policies in Azure
Blob Storage.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema. However, if the
auto-detected schema is incorrect, you can
add, edit or delete fields.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

You can only configure regions that are in the
multi-region of your tenant.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

Copy the Directory (tenant) ID, the Application
(client) ID, and the Object ID. You will use these
in the connection step.

📝

🟢note

You can only configure regions that are in the
multi-region of your tenant.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema. However, you can
add, edit or delete fields.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

When you create, delete, or update an external
dataset, the action is recorded in the
Management Audit Logs under the type
External Datasets.

🧭

➡️n…

Settings → Configurations → Data
Management → Dataset management →
External Datasets and click Add External
Dataset

5.2.13.7.3. Query using Federated Search 

📝

🟢note

The following aren't available in Federated
Search and remain exclusive to fully ingested
data.
Complex, cross-source analytical functions, for
example correlations, widgets, dashboards, and
APIs
search, target and view XQL stages

🧭

➡️n…

Incident Response → Investigation → Query
Builder and select XQL

5.2.13.7.4. Manage external datasets 

📝

🟢note

We highly recommend that you don't change
the auto-detected schema. However, in the Edit
window you can add new fields or delete the
new fields you added in the Edit window. You
can't delete the fields that were configured
during setup.

🧭

➡️n…

Manage external datasets created for
federates searches in Settings →
Configurations → Data Management → Dataset
management → External Datasets

5.2.13.8. Legacy Query Builder 

📝

🟢note

We recommend using the Query Builder in New
mode to take advantage of the Query Builder
templates and the ability to search the full
Cortex Data Model (XDM).
In Legacy mode, the Query Builder searches
predefined datasets only. To search the full
XDM, switch to New mode or select XQL Search.

5.2.13.8.1. Create authentication query 

5.2.13.8.2. Create event log query 

5.2.13.8.3. Create file query 

5.2.13.8.4. Create image load query 

5.2.13.8.5. Create network connections query 

📝 5.2.13.8.6. Create network query 

🟢note

When you run the query, depending on the
outcome of the results, the value specified in
this field might be displayed in the dst_ip field
in the query results. This occurs if an RDP event
is recorded whereby a user connected from the
source IP to the destination IP.

5.2.13.8.7. Create process query 

👀 5.2.13.8.8. Create registry query 

🟠i…

Ensure the KEY NAME is entered as a real
registry key name, and not as a symbolic link.
Otherwise, the query will not retrieve results.
Instead of
HKEY_LOCAL_MACHINE\System\CurrentControl
Set, which is a symbolic link, use
KEY_LOCAL_MACHINE\System\ControlSet001.
Instead of HKEY_CURRENT_USER, use
HKEY_USERS\<SID>, where SID is either a SID of
the current...

5.2.13.8.9. Query across all entities 

5.2.14. Research a known threat 

5.3. Agentic Assistant chat 

📝 5.3.1. Get started with Agentic Assistant chat 

🟢note

The Cortex Agentic Assistant is currently
available in limited regions. For more
information see Cortex Agentic Assistant If your
tenant is not within one of those regions, you
have access to the Cortex Assistant.
To enable the Cortex Agentic Assistant, go to
Settings → Configurations → General → Server
Settings → AI Configuration.

📝 5.3.2. Choose an Agentic Assistant agent 

🟢note

Requires the Exposure Management add-on.

5.3.3. Chat with an Agentic Assistant agent 

📝

🟢note

Case data is only loaded when you send your
first message. Opening the chat interface
without sending a prompt does not provide the
agent with the case context.

📝

🟢note

An agent's proposed plans and results may
contain inaccuracies or errors. Always review
the results carefully to ensure you fully
understand the proposed action before
proceeding.

💡

🔵tip

You can quickly jump to different product
pages within Cortex XSIAM by typing / in the
prompt area. This shortcut is a built-in
navigation feature that is available even if the
Cortex Agentic Assistant is disabled.

5.3.4. Create and run XQL queries with Agentic
Assistant chat 

📝

🟢note

The TextToXQL action is a hidden system action
and does not appear in the Agents Hub.

📝

🟢note

If you are in a non-supported region and ask an
agent to create an XQL query, it may attempt
to generate the query using general logic. We
do not recommend this, as it may result in
inaccurate syntax and unreliable results.

📝

🟢note

Running XQL queries manually through agent
does not consume compute units. This includes
scenarios where you prompt the agent to
create and execute a multi-step plan.

5.3.5. Manage chat history 

5.4.1. Asset management  5.4. Inventory management 

5.4.1.1. All Assets 

📝

🟢note

When working with the Asset Inventory page,
consider the following:
To maintain an accurate and clutter-free asset
inventory, an automated cleanup process
periodically removes outdated assets in the
background.

📝

🟢note

The options available are dependent on your
license.

🧭 5.4.1.1.1. Container Images 

➡️n…

All Assets → Compute → Container Images

5.4.1.1.2. Kubernetes Cluster 

📝

🟢note

The Vulnerabilities tab is only available if the
cluster you wish to analyze has a K8s connector.

🧭

➡️n…

Inventory → All Assets → Compute →
Kubernetes Cluster for a Kubernetes Clusters
assets overview

🧭 5.4.1.1.3. Container Instances 

➡️n…

Asset Inventory → Compute → Container
Instances

5.4.1.1.4. External Surface assets 

🔒

🟣c…

Requires the Attack Surface Management
(ASM) add-on

5.4.1.1.4.1. External Surface attribution evidence 

5.4.1.2.1. Configure your network parameters  5.4.1.2. Network configuration 

📝

🟢note

You can add a range that is fully contained in
an existing range, however, you cannot add a
new range that partially intersects with another
range.

📝

🟢note

Viewing external IP address ranges requires the
Attack Surface Management add-on.

🧭

➡️n…

In Cortex XSIAM , select Assets → Network
Configuration → Internal Domain Suffixes

5.4.1.3. Asset Groups 

📝

🟢note

When you create or edit an Asset Group, the
changes are applied immediately to new assets
and to existing assets that have been updated.
However, it may take a few hours for the
changes to appear on existing assets that have
not been updated.

🧭

➡️n…

Inventory → Assets → Groups → Add Group

5.4.1.4. Asset Roles 

📝

🟢note

Asset Roles are available only if the Identity
Threat Module add-on is enabled.

5.4.1.4.1. Manage Asset Roles for Endpoints 

📝

🟢note

Endpoint Role Management is available only if
the Identity Threat Module add-on is enabled.

📝

🟢note

Deleting a manually added endpoint removes
the endpoint from the Included Endpoints list. If
this endpoint is detected automatically as
having this asset role in the future, it will appear
in the Included Endpoints list.
Excluding a manually added endpoint ensures
that even if in the future the endpoint is
detected as having this asset role, this...

5.4.1.4.2. Manage Asset Roles for Users 

📝

🟢note

User Role Management is available only if the
Identity Threat Module add-on is enabled.

📝

🟢note

Deleting a manually added user removes the
user from the Included Users list. If this user is
detected automatically as having this asset role
in the future, it will appear in the Included Users
list again.
Excluding a manually added user ensures that
even if in the future the user is detected as
having this asset role, this detection is
overridden and...

☑️ 5.4.1.4.2.1. Honey user 

🟣pr…

The honey user role is available only if the
Identity Threat Module add-on is enabled.

5.4.1.5. Manage Asset Scores 

📝

🟢note

The Hosts tab is available if the Identity Threat
Module add-on is enabled.

📝

🟢note

As new alerts are associated with incidents, the
User and Host Scores are recalculated. You can
view the latest User and Host Scores on the
Asset Scores page, or track the Score trend on
the User Risk View and Host Risk View.

📝

🟢note

Some User Associated Insights may not appear
as part of the User Associated Incidents due to
the insight generation mechanism. For example,
when an insight related to one of the assets in
an incident is generated a few days after the
associated incident, the insight may not be
associated with the incident.

5.4.1.6. Vulnerability Assessment 

☑️

🟣pr…

The following are prerequisites for Cortex
XSIAM to perform a vulnerability assessment.
Requirement
Description
Licenses and Add-ons
Host Insights license.
This feature is included with Cortex XSIAM
Enterprise and with Cortex XSIAM NG SIEM with
a Host Insights license. If you have a Cloud
Posture Security, Cloud Runtime Security, or
Cortex XSIAM...

📝

🟢note

The CVE will be removed/reinstated to all
views, filters, and widgets after the next
vulnerability recalculation.

📝

🟢note

Starting with macOS 10.15, Mac built-in system
applications are not reported by the Cortex
XDR agent and are not part of the Cortex
XSIAM Application Inventory.

💡

🔵tip

You can click each individual CVE to view in-
depth details about it on a panel that appears
on the right.

💡

🔵tip

You can click each individual endpoint to view
in-depth details about it on a panel that
appears on the right.

🧭

➡️n…

You can access the Vulnerability Assessment
panel from Inventory+Endpoints → Host
Inventory → Vulnerability Assessment

5.5. Threat management 

5.5.1.1. What are detection rules?  5.5.1. Detection rules 

5.5.1.1.1. What's an IOC? 

📝

🟢note

Cortex XSIAM supports a maximum of
4,000,000 IOCs.

5.5.1.1.1.1. IOC rule details 

📝

🟢note

Field cannot exceed 36 characters.

🧭

➡️n…

In the Threat Management → Detection Rules
→ IOC page, you can view all configured or
uploaded indicators of compromise (IOCs

5.5.1.1.1.2. Create an IOC rule 

📝

🟢note

To ensure your IOC rules generate issues
efficiently and do not overcrowd your Issues
table, Cortex XSIAM automatically does the
following:
Disables any IOC rules that reach 5000 or more
hits over 24 hours.
Creates a rule exception based on the
PROCESS SHA256 field for IOC rules that hit
more than 100 endpoints over 72 hours.
If you have the Threat...

🧭

➡️n…

In Threat Management → Detection Rules →
IOC, select + Add IOC

5.5.1.1.2. What's a BIOC? 

🧭 5.5.1.1.2.1. BIOC rule details 

➡️n…

Manage your behavioral indicator of
compromise (BIOC) rules in Threat
Management → Detection Rules → BIOC

5.5.1.1.2.2. Create a BIOC rule 

🔒

🟣c…

Custom prevention rules are supported on
Cortex XSIAM agent 7.2 and later versions and
enable you to configure and apply user-
defined BIOC rules to Restriction profiles
deployed on your Windows, Mac, and Linux
endpoints.

📝

🟢note

To ensure your BIOC rules generate issues
efficiently and do not overcrowd your Issues
table, Cortex XSIAM automatically does the
following:
Disables BIOC rules that reach 5000 or more
hits over a 24-hour period.
Creates a rule exception based on the
PROCESS SHA256 field for BIOC rules that hit
more than 100 endpoints over a 72 hour period.

📝

🟢note

A cloud_audit_log dataset requires a Cortex
XDR Pro per GB license.
Currently, you cannot create a BIOC rule on
customized datasets and only the filter stage,
alter stage, and functions without any
aggregations are supported for XQL queries
that define a BIOC.
For BIOC rules, the field values in XQL are
evaluated as case insensitive (config...

📝

🟢note

To demonstrate the expected behavior of the
rule before you save it, Cortex XSIAM tests the
BIOC on historical logs. After you save a BIOC
rule, it will operate both on historical logs (up
to 10,000 hits) and on new data received from
your log sensors.

📝

🟢note

To demonstrate the expected behavior of the
rule before you save it, Cortex XSIAM tests the
BIOC on historical logs. After you save a BIOC
rule, it will operate on both historical logs (up
to 10,000 hits) and new data received from your
log sensors.

📝

🟢note

You can only import files that were exported
from Cortex XSIAM. You can not edit an
exported file.

📝

🟢note

You can only add to existing profiles you
created, Cortex XSIAM Default profiles will not
appear as an option.
When you want to add to restrictions profile,
you can only use fields or options that exist in
pre-built process-type BIOCs

📝

🟢note

Auto-disable will turn off both the BIOC rule
detection and the BIOC prevention rule.

5.5.1.1.2.3. Manage Global BIOC Rules 

5.5.1.1.3. What's a correlation rule? 

🧭

➡️n…

After you configure your correlation rules, you
can manage them in Threat Management →
Detection Rules → Correlations, and view and
analyze the generated issues in Cases and the
Issues Table

5.5.1.1.3.1. Correlation rule details 

📝

🟢note

Only an administrator can create and view
queries built with an unknown dataset that
currently does not exist in Cortex XSIAM .

📝

🟢note

For more information on troubleshooting server
errors in scheduled correlation rules,
Troubleshoot server errors in scheduled
correlation rules.

📝

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

📝

🟢note

Only an administrator can create and view
queries built with an unknown dataset that
currently does not exist in Cortex XSIAM.

🧭

➡️n…

If you are assigned a role that enables
Investigation → Rules privileges, you can
manage all user-defined Correlation Rules from
Threat Management → Detection Rules →
Correlations

5.5.1.1.3.2. Create a correlation rule 

☑️

🟣pr…

To enable pivots from issues to a third-party
source system, ensure that you know the
dataset field name that contains the URL of the
source system. Some vendors already provide
this URL as part of their API, and you can find it
in the third-party product dataset. If there is no
URL, you cannot enable this feature.

📝

🟢note

When creating a Real Time Correlation Rule,
you can only generate an issue as the resulting
action for the Correlation Rule. All other
options are disabled.
To ensure your Correlation rules generate
issues efficiently and do not overcrowd your
Issues table, Cortex XSIAM automatically
disables Correlation rules that reach 5000 or
more hits over a...

📝

🟢note

When you open the New Correlation Rule
editor from XQL Search, this XQL Search field is
already populated with the XQL query that you
defined.
An administrator can create and view queries
built with an unknown dataset that currently
does not exist in Cortex XSIAM . All other users
can only create and view queries built with an
existing dataset.

📝

🟢note

The XQL features for call, top, and wildcards in
datasets (dataset in (<dataset prefix>_*)) are
currently not supported in Correlation Rules. If
you add them to the XQL definition, you will not
be able to Create or Save the Correlation Rule.
The XQL features for transaction in datasets
(dataset in (<dataset prefix>_*)) are currently
not supported in...

📝

🟢note

The incident that contains the issues will also
be assigned to the selected domain. For more
information, see Case and issue domains.
If you want to generate a health issue, choose
the Health domain. For more information about
health issues, see About health issues.

📝

🟢note

If a generated issue has severity Medium or
above, a case is automatically opened.
Low severity issues generated by correlation
rules are not grouped into cases.

📝

🟢note

There is no validation or auto complete for
these parameters and the values can be null or
empty. In these scenarios, Cortex XSIAM does
not display the null or empty values, but adds
the text NULL or EMPTY in the descriptions.

📝

🟢note

When more than one XDM field is listed, Cortex
XSIAM looks for the field value according to
the order of the fields listed.

📝

🟢note

When more than one XDM field is listed, Cortex
XSIAM looks for the field value according to
the order of the fields listed.

📝

🟢note

When Use the Cortex XSIAM default incident
enrichment is not selected and you have not
mapped any issue fields, the issue is dispatched
into a new incident.

👀

🟠i…

The maximum size of a lookup dataset is 50 MB.
If the data exceeds this limit, the add to lookup
action fails.

💡

🔵tip

When creating your correlation rule, you can
use predefined values for different fields in the
editor, such as Alert Name, Alert Description,
and Drill-Down Query. For more information,
see Field replacement syntax in correlation
rules.

🧭

➡️n…

You can create a new correlation rule from
either the Threat Management → Detection
Rules → Correlation Rules page or when
building a query in XQL Search

5.5.1.1.3.3. Field replacement syntax in
correlation rules 

📝 5.5.1.1.3.4. Manage correlation rules 

🟢note

Execute Rule is not available for real time
correlation rules.

📝 5.5.1.1.3.5. Monitor correlation rules 

🟢note

In the dataset, the Query start time and Query
end time indicate the time frame of the data
that was queried. The actual start and end
times of the correlation rule execution are
recorded in the _time field for the Initiated and
Completed entries.

5.5.1.1.3.6. Troubleshoot server errors in

scheduled correlation rules 

5.5.1.1.4. Manage IOC and BIOC rules 

📝

🟢note

For Analytics BIOC rules, you can only disable
and enable rules.

📝

🟢note

You cannot delete global BIOCs delivered with
content updates.

📝

🟢note

For BIOC rules that are applied to prevention
profiles:
If you disable a rule only on the agent,
detection on the server works as usual.
If you disable a rule only on the server,
prevention on the agent works as usual.
If you disable a rule only on the agent,
detection on the server works as usual.
If you disable a rule only on the server,
prevention...

📝

🟢note

When a BIOC rule is disabled automatically by
Cortex XSIAM, for example due to the server
anti flooding mechanism, prevention on the
agent works as before.

🧭

➡️n…

Threat Management → Detection Rules → BIOC

5.5.2.1. Analytics overview  5.5.2. Analytics 

5.5.2.1.1. Analytics engine 

5.5.2.1.2. Analytics sensors 

5.5.2.1.3. Coverage of MITRE Attack tactics 

5.5.2.1.4. Review MITRE ATT&CK framework

coverage 📝 
🟢note

When a contributing data source type is active,
it does not imply that all the rules and
detectors associated with the data source type
are active. Rule applicability is dependent on
the data source's context and configuration. To
enable an active status, data source types
require the following setup:
Endpoint: Installed Cortex XDR agent.
Network: A...

📝 5.5.2.1.5. Analytics detection time intervals 

🟢note

When establishing a baseline, detectors
compute limits beyond which network activity
will require an issue. In some cases, detectors
do not compute baseline limits; instead they are
predetermined by Cortex XSIAM engineers. The
engineers determine the values used for
predetermined limits using statistical analysis of
malicious activity recorded...

5.5.2.1.6. Analytics issues and Analytics BIOCs 

5.5.2.1.7. View and manage Analytics rules 

📝

🟢note

The default severity is updated by content
updates. If a content update determines a new
default severity for the rule that's the same as
the value you had previously determined, you
won't have the option to reset to default. For
example, if the default was Informational, and
you changed the severity to Medium, and after
a content update Cortex XSIAM...

📝

🟢note

When you select multiple rows, you can only
enable or disable the selected rules.

⛔

🔴w…

Changing the default severity may result in
issues not being triggered or too many issues
being triggered. Please consider this carefully
before you change the severity recommended
by Cortex XSIAM. Any responsibility for not
getting issues triggered as a result of changing
the severity will be yours.

🧭 5.5.2.1.8. Identity Analytics 

➡️n…

After configuring your Cloud Identity Engine
instance and Cortex XSIAM Analytics, select
Settings () → Configurations → Cortex XSIAM -
Analytics, and in the Featured in Analytics
section, Enable Identity Analytics

5.5.2.1.9. Identity Threat Module (ITDR) 

5.5.2.1.10. AI Detection & Response in Cortex
XSIAM (Beta) 

☑️

🟣pr…

To enable AIDR, you must have one of the
following user roles: Instance Admin or Account
Admin.

🧭

➡️n…

Settings → Configurations → Cortex - Analytics

5.5.2.1.10.1. Data sources and supported services 

5.5.2.1.10.2. AI Detection & Response Dashboard 

5.5.2.1.10.3. Collect prompt logs 

5.5.3. Threat Intel Management 

5.5.3.1. Get started with Threat Intel Management 

📝

🟢note

You must have the Cortex XSIAM Premium
license or any other XSIAM license with the
Threat Intel Management (TIM) add-on to use
this feature.

📝 5.5.3.1.1. What is Threat Intel Management? 

🟢note

You must have the Cortex XSIAM Premium
license or any other XSIAM license with the
Threat Intel Management (TIM) add-on to use
this feature.

5.5.3.1.2. Threat Intel Management use cases 

5.5.3.1.3. Roles and responsibilities in Threat Intel
Management 

📝 5.5.3.1.4. Indicator concepts 

🟢note

You can store up to 100,000,000 indicators.

5.5.3.1.5. Indicator lifecycle 

📝

🟢note

To run enhancement scripts and reputation
commands, you must configure a relevant
enrichment integration, such as VirusTotal,
IPinfo v2, etc.

💡

🔵tip

We recommend defining your policy for
handling expired indicators.

5.5.3.2. Indicator configuration 

5.5.3.2.1. Configure Threat Intelligence feed
integrations 

📝

🟢note

Some third-party services (such as Whois and
VirusTotal) enforce strict rate limits based on
the source IP address. If you encounter quota
management issues, we recommend running
them on an engine. This routes the traffic
through your own private network, ensuring the
external service sees a unique, dedicated IP
address exclusive to your organization.

📝

🟢note

Some feeds only provide information about
new indicators and do not specify when
indicators are removed. Indicators from these
feeds cannot be automatically expired on
removal.
If a feed's expiration method is set to When
removed from the feed, indicators that are
removed from the feed immediately expire.
Note that if the feed is disabled, its...

5.5.3.2.2. Customize indicator fields and types 

5.5.3.2.2.1. Create an indicator type 

📝

🟢note

If you miss mapping any field, you can create
additional new indicator fields and either relate
them to all indicator types, or relate them only
to the new indicator type (recommended).

🧭

➡️n…

Settings → Configurations → Object Setup →
Indicators → Types

5.5.3.2.2.1.1. Indicator type profile 

5.5.3.2.2.1.2. File indicators 

5.5.3.2.2.1.3. Formatting scripts 

5.5.3.2.2.1.4. Enhancement scripts 

5.5.3.2.2.1.5. Reputation scripts 

5.5.3.2.2.1.6. Reputation commands 

5.5.3.2.2.1.7. Map custom indicator fields 

5.5.3.2.2.2. Create an indicator field 

📝

🟢note

Cortex XSIAM IOC fields are based on the STIX
2.1 specifications. For more information, see
Indicator field structure.

📝

🟢note

The following HTML tags are not permitted:
blockquote, del, dd, div, dl, dt, fieldset, form, h1,
h2, h3, h4, h5, h6, hr, iframe, ins, li, math,
noscript, ol, pre, p, script, style, table, ul,
address, article, aside, canvas, details, dialog,
figcaption, figure, footer, header, hgroup, main,
nav, output, progress, section, video.
The following CSS tags...

🧭

➡️n…

Settings → Configurations → Object Setup →
Indicators → Fields → New Field

5.5.3.2.2.2.1. Indicator field structure 

5.5.3.2.2.2.2. Indicator field trigger scripts 

5.5.3.2.3. Indicator classification and mapping 

📝

🟢note

When creating a new indicator type, you
classify and map the indicator fields in the
indicator type settings. For more details, see
Map custom indicator fields.

📝

🟢note

You can optionally skip importing data. Click
the pencil on the right of each indicator type
on the right pane to enter the value manually.

📝

🟢note

In the Classification & Mapping page, the
mapping does not indicate for which indicator
types they are configured. When creating a
mapper, it is best practice to add to the
mapper name and the indicator type the
mapper is for. For example, Mail Listener -
Phishing.
When mapping a list, we recommend you map
to a multi-select field. Short text fields do...

5.5.3.2.4. Indicator extraction 

📝

🟢note

By default, system-wide automatic indicator
extraction and enrichment is disabled. However,
if you migrated from Cortex XSIAM 2.x to
Cortex XSIAM 3.x, system-wide automatic
indicator extraction and enrichment is enabled.
If you have a Threat Intel Management (TIM)
Add-on, you can enable or disable automatic
indicator extraction system-wide. Go to...

📝

🟢note

Reputation commands, such as !ip and !domain,
can only be used after you configure and
enable a reputation integration instance, such
as VirusTotal and Whois.

📝

🟢note

The inline configuration may delay playbook
execution.

📝

🟢note

While indicator creation is asynchronous,
indicator extraction and enrichment are run
synchronously. Data is placed into the issue
context and is available via the context for
subsequent tasks.
All indicators are automatically extracted and
enriched before a playbook is run. For an on-
field change, extraction occurs before the next
playbook tasks run.

📝

🟢note

When using out of band, the extracted
indicators do not appear in the context. If you
want the extracted indicators to appear select
inline.

5.5.3.2.4.1. Set the indicator extraction mode for

a playbook task 

5.5.3.2.4.2. Disable indicator extraction for

scripts or integrations 📝 
🟢note

The TIM add-on is included in the Cortex
XSIAM Premium license.

5.5.3.2.5. Configure Threat Intelligence feed
integrations 

📝

🟢note

Some third-party services (such as Whois and
VirusTotal) enforce strict rate limits based on
the source IP address. If you encounter quota
management issues, we recommend running
them on an engine. This routes the traffic
through your own private network, ensuring the
external service sees a unique, dedicated IP
address exclusive to your organization.

📝

🟢note

Some feeds only provide information about
new indicators and do not specify when
indicators are removed. Indicators from these
feeds cannot be automatically expired on
removal.
If a feed's expiration method is set to When
removed from the feed, indicators that are
removed from the feed immediately expire.
Note that if the feed is disabled, its...

5.5.3.2.6. Exclude indicators from enrichment 

5.5.3.2.7. Generate issues from indicators using
indicator rules for prevention and detection 

📝

🟢note

Indicators should be present in the Threat
Intelligence database (Threat Management →
Threat Intelligence → Indicators) before
creating detection and prevention rules.

📝

🟢note

Although you can create IOC rules for
detection, indicator rules are designed to
leverage threat intelligence indicators like MD5
and SHA256 hashes that are present in your TIM
library. These rules directly integrate with and
rely on the indicators ingested and managed by
TIM. Indicators must be in the TIM database
before creating these rules.
For more...

📝

🟢note

You can't change the Preventable = True,
Status = Active and Type = File filters, which
comply with the requirements of the supported
indicator type for Prevention on the Agent.

📝

🟢note

The Indicator Rule shows the number of issues
generated by the rule, You can view the issues
that were generated using the Indicator rule, by
right-clicking the rule and select View related
issues.

📝

🟢note

You can't change the Detectable = True and
Status = Active filters, which comply with the
requirements of the supported indicator type
for detection.

📝

🟢note

The Issue source is Threat Intelligence.

📝

🟢note

If an indicator matches multiple indicator rules,
the highest severity rule is used. If all have the
same severity, the rules are used by the first
created.

⚠️ 5.5.3.2.8. Export indicators 

🟡c…

You should not run a query on a field that you
might change in the playbook flow. For
example, you shouldn't have a playbook with
query Verdict:Malicious and then change the
indicator verdict as a part of the playbook.

📝 5.5.3.3. Indicator management 

🟢note

If an indicator matches multiple indicator rules,
the highest severity rule is used. If all have the
same severity, the rules are used by the first
created.

5.5.3.4. Indicator investigation 

5.5.3.4.1. Indicator verdict 

5.5.3.4.2. Extract and enrich an indicator 

📝

🟢note

By default, system-wide automatic indicator
extraction and enrichment is disabled. However,
if you migrated from Cortex XSIAM 2.x to
Cortex XSIAM 3.x, system-wide automatic
indicator extraction and enrichment is enabled.
If you have a Threat Intel Management (TIM)
Add-on, you can enable or disable automatic
indicator extraction system-wide. Go to...

📝

🟢note

Triggering enrichment on a substantial number
of indicators can take time (because it's
activating all enrichment integrations per
indicator) and can result in performance
degradation.

📝

🟢note

Reputation commands, such as !ip, !domain can
only be used when you configure and enable a
reputation integration instance, such as
VirusTotal and WHOIS.

📝 5.5.3.4.3. Expire an indicator 

🟢note

You need to run these commands in the Case or
Issue War Room.

📝 5.5.3.4.4. Manage indicator relationships 

🟢note

You can also add an indicator relationship from
the Quick View when selecting an indicator
from an issue.

⚠️ 5.5.3.4.5. Delete and exclude indicators 

🟡c…

Ensure you are using the correct syntax when
defining the values for your exclusion lists.

5.6. Attack Surface Management 

🔒

🟣c…

Included in Cortex XSIAM Premium. For Cortex
XDR 4.x or any other XSIAM license, the ASM
add-on is required.

5.6.1. Get started with Attack Surface

Management 

5.6.1.1.1. Attack Surface Management use cases  5.6.1.1. What is Attack Surface Management? 

5.6.1.2. Network mapping 

5.6.1.3. Scanning 

5.6.1.3.1. Scanning cadences 

5.6.1.3.2. Known Assets Monitoring 

📝 5.6.1.3.3. Scanning ports and protocols 

🟢note

The following lists are not exhaustive. For
current and complete lists, contact your
customer success team.

5.6.1.3.4. Scanning activity 

5.6.1.4. GeoIP data collection 

5.6.1.5. Attack Surface Management FedRAMP
support 

5.6.2. Attack Surface Management detections 

🧭 5.6.2.1. Attack surface rules 

➡️n…

Modules → Attack Surface → Policies →
Attack Surface Rules

5.6.2.2. Attack Surface Testing 

📝

🟢note

Requires the ASM add-on.

5.6.2.2.1. Attack surface tests 

📝

🟢note

Attack surface testing scans are typically not
CFAA compliant, meaning that they may
attempt more extensive fuzzing to confirm or
deny the presence of a CVE. Additionally, some
attack surface tests are more intrusive than
others. Tests are labeled with the level of
intrusiveness, so you can decide whether to run
more intrusive tests.

5.6.2.2.1.1. Attack Surface Testing intrusivity 

🧭 5.6.2.2.2. Set up Attack Surface Testing 

➡️n…

Settings → Configurations → Access
Management → Roles, and select the role

Modules → Attack Surface → Policies →
Attack Surface Tests

Settings → Configurations → Attack Surface →
Attack Surface Testing

5.6.2.2.3. Manage attack surface tests 

5.6.2.2.4. View issues created from Attack

Surface Testing results 🧭 
➡️n…

Modules → Attack Surface → Attack Surface
Issues

5.6.2.2.5. Source IP addresses for Attack

Surface Testing scans 🧭 
➡️n…

Settings → Configurations → Attack Surface →
Attack Surface Testing and refer to the Source
IP Addresses section

📝 5.6.2.3. Externally inferred CVEs 

🟢note

An externally inferred CVE might impact your
service or asset, but additional investigation is
required to confirm that the CVE is actually
present.

📝 5.6.2.4. Digital Risk Protection 

🟢note

Both of these attack surface rules are based on
the attributed domain assets that appear in the
asset inventory. If there are no attributed
domains in your inventory, Cortex XSIAM will
not generate Digital Risk Protection findings
and issues.

5.6.3. Attack surface assets 

🧭

➡️n…

The internet-facing assets that were discovered
in an attack surface management (ASM) scan
and attributed to your organization are
available in the inventory on the Inventory →
Assets → All Assets → External Surface pages

Inventory → Assets → Network Configuration
→ IP Address Ranges → External IP Address
Ranges

5.6.3.1. Upload or remove ASM assets 

📝

🟢note

You must have the Instance Administrator role
to upload or remove assets.

5.6.3.1.1. Upload assets 

📝

🟢note

If an asset upload request has an invalid CSV or
includes one or more invalid assets, the entire
request will fail, and none of the assets will be
uploaded. If this happens, Cortex XSIAM will
display an error message indicating what
caused the error, so you can fix the problem
and resubmit if you choose.

🧭

➡️n…

Settings → Configurations → Asset
Management → Asset Uploads/Removals

📝 5.6.3.1.2. Remove assets 

🟢note

If an asset removal request has an incorrectly
formatted CSV or includes one or more invalid
assets, the entire request will fail, and none of
the assets will be removed. If this happens,
Cortex XSIAM will display an error message
indicating what caused the error, so you can fix
the problem and resubmit if you choose.

5.6.4. Deploy ASM and Exposure Management
enrichment and remediation automation 

📝

🟢note

For details and requirements regarding the
enrichment information that can be collected
and the specific issues that can be remediated
automatically, review the Exposure
Management Content Pack information in
Marketplace.

📝

🟢note

Cortex Exposure Management playbooks only
run on issues that were created after the
automation rules have been configured.

🧭

➡️n…

Settings → Configurations → Marketplace →
Browse and locate the Cortex Exposure
Management content pack

Investigation & Response → Automation →
Automation Rules

🧭 5.6.5. ASM enrichment of cloud assets 

➡️n…

Inventory → Assets → All Assets → External
Surface → Services

5.6.6. Emerging Vulnerabilities 

🔒

🟣c…

Requires the ASM add-on

📝

🟢note

You must have a role with Attack Surface Rules
permission to access the Emerging
Vulnerabilities page. When setting up Roles
Based Access Control (RBAC), you can find
Attack Surface Rules in the Detection & Threat
Intel component.

🧭

➡️n…

Posture Management → Vulnerability
Management → Emerging Vulnerabilities

🧭 5.6.7. Global Lookup 

➡️n…

Modules → Attack Surface → Global Lookup

5.7. Vulnerability management 

5.7.1. Vulnerability management in Cortex XSIAM 

🔒

🟣c…

Requires the Cortex Cloud Posture Security,
Cortex Cloud Runtime Security, Exposure
Management, Cortex XSIAM Premium or ASM
add-on.

📝

🟢note

Cortex XSIAM vulnerability management
provides the ability to identify and assess
runtime vulnerabilities in every asset across
traditional IT and cloud environments. For
vulnerabilities detected in your software
development lifecycle through application
security scans, refer to the Cortex Cloud
Application Security documentation.

📝 5.7.1.1. Cortex XSIAM vulnerability concepts 

🟢note

CVE is an acronym for Common Vulnerabilities
and Exposures, which is a list of publicly
disclosed security threats. We often use the
term "CVE" to refer to a vulnerability that has
been a assigned a CVE ID. Cortex XSIAM
identifies CVEs and non-CVE vulnerabilities.

5.7.1.2. Vulnerability Management dashboard 

🧭 5.7.2. Cortex Vulnerability Risk Score 

➡️n…

Posture Management → Vulnerability
Management → Vulnerability Issues

5.7.3. Vulnerability policies 

🧭 5.7.3.1. Create a vulnerability policy 

➡️n…

Posture Management → Rules & Policies →
Policies → Vulnerability Management

5.7.3.2. Update the Ignored CVEs, Asset Groups,
and Assets policy



🧭 5.7.3.3. Modify a vulnerability policy 

➡️n…

Posture Management → Rules & Policies →
Vulnerability Management

🧭 5.7.3.4. Configure a block grace period 

➡️n…

Posture Management → Rules & Policies →
Vulnerability Management → Vulnerability
Policies - Prevention

5.7.3.5. Enable or disable a vulnerability policy 

5.7.4. Investigate and remediate vulnerabilities 

🧭 5.7.4.1. View all Vulnerabilities 

➡️n…

Posture Management → Vulnerability
Management → Vulnerabilities

5.7.4.2. View vulnerability issues 

🧭 5.7.4.3. View All Vulnerability Findings 

➡️n…

Posture Management → Vulnerability
Management → Vulnerability Issues and click
the All Vulnerability Findings button

🧭 5.7.4.4. View vulnerable assets 

➡️n…

Posture Management → Vulnerability
Management → Vulnerable Assets

🧭 5.7.5. Vulnerability Intelligence 

➡️n…

Posture Management → Vulnerability
Management → Vulnerability Intelligence

5.7.6. Recast CVSS scores and CVSS severities 

5.8. Cloud Security 

🔒 5.8.1.1. What is the Discovery Engine?  5.8.1. Discovery Engine 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM product that has the
Cloud Runtime Security or Cloud Posture
Security add-ons.

5.8.2. Monitor and track compliance adherence 

📝

🟢note

Requires Cortex XSIAM Premium or any other
XSIAM license with the Cloud Runtime Security
or Cloud Posture Security add-on.

5.8.2.1. Cortex compliance flow 

5.8.2.2. Choose compliance standards from the
compliance catalog 

🧭

➡️n…

Cortex provides lists of available standards and
controls in the Standards and Controls
catalogs under Posture Management →
Compliance → Catalogs

5.8.2.2.1.1. Use a built-in or custom standard  5.8.2.2.1. Standards Catalog 

5.8.2.2.2.1. Use a built-in or custom control  5.8.2.2.2. Controls catalog 

5.8.2.2.2.1.1. Add a custom detection rule to a

custom control 

5.8.2.2.2.1.2. Create a new Custom Detection

Rule 

5.8.2.3. Use an assessment profile to run
compliance checks on your assets 🧭 
➡️n…

Under Posture Management → Compliance →
Assessment Profiles, click Create New
Assessment

5.8.2.4. View and manage compliance
assessments and reports 

📝

🟢note

Compliance assessment results may take up to
six hours to be generated.

📝 5.8.2.4.1. Assessments 

🟢note

If there are no rules associated with the control,
the control will be assigned a severity of low.

🧭 5.8.2.4.2. Reports 

➡️n…

The Posture Management → Compliance →
Results → Reports page shows a table listing
compliance assessment report files

5.8.2.5. View the compliance assessment of an
individual asset 

5.8.3. Cloud Security Rules and Policies 

5.8.3.1. Overview 

5.8.3.2. Cloud Security Rules 

5.8.3.3. Cloud Security Policies 

📝

🟢note

If you have the following Scope Based Access
Control (SBAC) settings in place, User Settings
> Cases and Issues Scope > Select domains >
Posture, you may encounter a Case mismatch in
Issues/Cases/Findings counts. This is because
the Case count on the Rules page captures
Cases belonging to the Posture domain.
Whereas Platform pages, capture Issues...

5.8.3.3.1. Issues 

5.8.3.4. Create Rules 

5.8.3.4.1. Create a configuration rule 

5.8.3.4.1.1. Guidelines for creating cloud security
rules 📝 
🟢note

XQL queries are supported for cloud security
configuration rules only. XQL queries are not
yet supported for other types of cloud security
rules.

5.8.3.4.1.2. Cloud security rule status for custom
configuration rules 

5.8.3.4.2. Create a Data Rule 

5.8.3.4.3. Create a Network Exposure Rule 

5.8.3.4.4. Edit a Rule 

5.8.3.5. Create Policies 

📝

🟢note

When creating Policies, note that Rules with the
Informational severity level are excluded.

5.8.3.5.1. Edit a Policy 

5.8.3.5.2. Use an Existing Policy to Create a New
One 

5.8.4. Cortex Cloud Data Classification 

5.8.4.1. What is Cortex Cloud Data

Classification? 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

🧭

➡️n…

To access Data Classification management,
click Settings → Configurations → Data
Classification

5.8.4.2. How to create and validate a custom

data pattern 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Once a custom data pattern is saved, it runs on
all data in the same way as any out-of-the-box
(OOTB) pattern, becoming globally applicable
for all modules using Cortex Cloud Data
Classification.

📝

🟢note

For more information, see How to disable and
enable data patterns in Data Classification.How
to disable and enable data patterns in Data
Classification

5.8.4.2.1. Custom data patterns: Guardrails and
syntax guide 

5.8.4.3. How to disable and enable data patterns
in Data Classification 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Disabling data patterns can cause changes in
your data profile results and stop detection of
these data patterns.

📝

🟢note

For more information about data patterns in
data classification, see What is Cortex Cloud
Data Classification?.

🧭

➡️n…

In the lower left part of the screen, click
Settings → Configurations → Data
Classification → Data Patterns

5.8.4.4. How to create and validate a custom

data profile 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you choose two data locations, only the
filters they have in common will be included in
the possible filter options.

📝

🟢note

For more information, see How to disable and
enable data profiles in Cortex Cloud Data
Classification.

👀

🟠i…

Deleting a data profile deletes all past data
associated with it in all modules using Cortex
Cloud Data Classification after a warning
notification is displayed.

👀

🟠i…

Enabling and disabling a data profile removes
or re-adds the data profile results to the data
objects; that is, files and tables.

5.8.4.5. How to disable and enable data profiles
in Cortex Cloud Data Classification 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Existing results on past scans are updated in
the Asset and Object inventories within two
hours after being disabled or enabled.

📝

🟢note

For more information about data profiles in
Cortex Cloud Data Classification, see What is
Cortex Cloud Data Classification?.What is
Cortex Cloud Data Classification?

🧭

➡️n…

In the lower left part of the screen, click
Settings → Configurations → Data
Classification → Data Profiles

5.8.4.6. How to report a false positive in Cortex
Cloud Data Classification 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Alternatively, in Cortex Command Center, click
Help → Submit a Support Case.

5.8.5. Cortex Cloud Data Security 

🔒 5.8.5.1. What is Cortex Cloud Data Security? 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.5.2. Supported assets in Cortex Cloud Data
Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

CMK (customer-managed key) in SQL Server is
only supported in outpost mode.

📝

🟢note

The list above refers to only data classification;
however, Cortex Cloud Data Security discovers
and monitors all cloud assets and services for
usage and misconfigurations.

📝

🟢note

For information about configuring data
classification asset types, see How to configure
the scanning settings for supported services.

🔒 5.8.5.3. Cortex Cloud Data Security concepts 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

🔒 5.8.5.4. Cortex Cloud Data Security use cases 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.5.5. Data Inventory 

📝

🟢note

To clear the filter in the filter panel, click Delete.

🧭

➡️n…

When you select Inventory → All Assets →
Data → All Data Assets, a list of all data assets
appears

5.8.5.6. How to review errors in Cortex Cloud

Data Security 🔒 
🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.5.7. How to configure the scanning settings
for supported services 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you do not select a scanning cadence, the
default setting is applied. For more information,
contact your Customer Support team.

5.8.5.8. How to perform advanced Data Security
investigations using XQL 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

For more information, see Build XQL
queries.Build XQL queries

5.8.5.9. How to onboard Databricks 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

If you turn on this feature, both the cloud and
region will be used for scanning, possibly
incurring cost and requiring adherence to
certain compliance policies.

5.8.5.10. How to onboard Microsoft 365 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

You have generated a Globally Unique Identifier
(GUID), also known as a Universally Unique
Identifier (UUID). You will need this ID for the
tenant you want to use for the Microsoft 365
instance.
In order to use Microsoft 365, you must be
registered with Microsoft Azure.

5.8.5.11. How to onboard on-premise file shares
to Cortex Cloud Data Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Your data is scanned on the Broker VM itself,
and only the metadata and classification
results are transmitted from the on-premise
environment to Cortex XSIAM.

📝

🟢note

For information about activating the DSPM
Fileshare applet, see Activate DSPM Fileshare.

5.8.5.12. How to onboard Snowflake 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

In order to use Snowflake, you must be
registered with one of these cloud providers:
Amazon AWS, Microsoft Azure, or Google
Cloud Platform (GCP).
Ensure you have the necessary account
permissions to onboard. It is recommended to
use Account Admin as the role for the
onboarding.

📝

🟢note

The account identifier can be found using the
user information at the bottom left. Hover over
the account you wish to onboard and select
the copy option at the top right. The account
identifier is usually of the format:
(organization).[account]

5.8.5.13. How to use information protection
labels in Cortex Cloud Data Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Only If you have connected a Microsoft 365
instance to Cortex Cloud, the information
protection labels appear. See How to onboard
Microsoft 365.

5.8.6. Cortex Cloud Identity Security 

5.8.6.1. What is Cortex Cloud Identity Security? 

5.8.6.2. Review and improve your Identity
Security posture



🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Management or Cloud Runtime
Security add-on.

💡

🔵tip

Reducing the number of nonhuman entities that
are either dormant or have administrative
privileges is the most effective way to improve
your security score.

5.8.6.3. How does Effective Permission

Calculation work? 🔒 
🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.6.4. Cortex Cloud Identity Security
functionality 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

Access to the Weak/Compromised Password
widget and column requires the ITDR add-on.

📝

🟢note

For more information about Effective
Permission Calculation, see How does Effective
Permission Calculation work?.

📝

🟢note

When a policy is analyzed and categorized as
excessive, a relevant finding and highlight is
attached to that policy and the various
identities being granted excessive permissions.

📝

🟢note

Each action must be defined as either being
administrative or not.
The administrative tag is an additional tag for
administrative actions, along with one of the
other access level types. For example, the AWS
action iam:CreateGroup is categorized as
config and has the administrative tag as well.

👀

🟠i…

If you turn off the audit logs, even briefly, this
temporarily impacts the accuracy of the Last
Access data, potentially showing permissions
as unused when actually they were active. Full
accuracy is restored 90 days after you re-
enable the audit logs.

5.8.6.5. Achieve the principle of least privilege
access



🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

In the case of Amazon AWS, Cortex Cloud
Identity Security also uses AWS Identity and
Access Management (IAM) Access Advisor
insights to expand the coverage of supported
actions.

👀

🟠i…

If you turn off the audit logs, even briefly, this
temporarily impacts the accuracy of the Last
Access data, potentially showing permissions
as unused when actually they were active. Full
accuracy is restored 90 days after you re-
enable the audit logs.

5.8.6.6. Explore permissions using the simple and
advanced access tables 🔒 
🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.6.7. Create a custom detection rule in Cortex

Cloud Identity Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

🧭

➡️n…

Posture Management → Rules & Policies →
Rules → Cloud Security

5.8.6.8. Perform advanced Identity Security
investigations using XQL 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

For more information, see Build XQL
queries.Build XQL queries

☑️ 5.8.6.9. Ingest logs and data from Okta 

🟣pr…

Administrator privileges: Your Okta user must
have a role capable of creating API tokens,
such as Read-only Administrator, Super
Administrator, or Organization Administrator.
For more information, see the Okta
Administrators Documentation.

5.8.6.10. Enable inactive human identity logs on
Azure in Cortex Cloud Identity Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

For more information, see Ingest logs from
Microsoft Azure Event Hub.

5.8.6.11. Manage RBAC and SBAC in Cortex
Cloud Identity Security 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

👀

🟠i…

You can use the Cortex Cloud Identity Security
RBAC roles to define access to the various
sections and functionalities of Cortex Cloud
Identity Security, but these roles do not directly
control the specific data a user sees within
those sections. Data visibility is further refined
and limited by scope-based access control
(SBAC) capabilities.

5.8.7. Network exposure detection 

5.8.7.1. What is Cloud Network Analyzer? 

📝 5.8.7.2. Internet exposure detection 

🟢note

Currently, CNA supports only an isolated
architecture with an AWS Gateway Load
Balancer (GWLB) within a single VPC. Other
more centralized topologies including one
security VPC that forwards traffic to other
workload VPCs are currently not supported.

5.8.7.3. Outbound exposure detection 

5.8.7.4. East-west exposure detection 

5.8.7.5. Investigate an internet exposure 

📝

🟢note

The Network tab is currently only available for
virtual machines.

📝

🟢note

The Network tab is only displayed when you
have access to the main asset and associated
ones, such as security groups, VPCs and
subnets. For more information on Scope-Based
Access Control (SBAC) for configuring granular
scoping, see Manage user scope.Manage user
scope

📝

🟢note

The Network tab is currently only available for
virtual machines.

📝

🟢note

The Network tab is only displayed when you
have access to the main asset and associated
ones, such as security groups, VPCs and
subnets. For more information on Scope-Based
Access Control (SBAC) for configuring granular
scoping, see Manage user scope.Manage user
scope

5.8.8. Cortex Cloud AI Security 

🔒 5.8.8.1. What is Cortex Cloud AI Security? 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.8.2. Supported services in Cortex Cloud AI
Security 🔒 
🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

🔒 5.8.8.3. Cortex Cloud AI Security concepts 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

🔒 5.8.8.4. Cortex Cloud AI Security use cases 

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

5.8.8.5. How to perform advanced AI Security
investigations using XQL 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

📝

🟢note

For more information, see Build XQL
queries.Build XQL queries

5.8.9. Serverless function posture security 

5.8.9.1. Onboard cloud providers for serverless
functions 

📝

🟢note

When scanning serverless functions with layers,
those layers need to be from the same cloud
account.

📝

🟢note

Only functions containing zip files are
supported.

👀

🟠i…

Cortex supports Google Cloud Functions: 1st
gen and 2nd gen Cloud Functions API.

5.8.9.2. Serverless function posture policies 

5.8.9.2.1. Manage serverless function policies 

📝

🟢note

You can select multiple types to view all your
serverless function rules across your cloud
providers.

📝

🟢note

Refer to Create serverless function policies for
more information on how to define the steps of
a policy in the wizard.

5.8.9.2.2. Create serverless function policies 

📝

🟢note

You can select multiple options.

📝

🟢note

For more information about rules, refer to
Manage serverless function rules.

5.8.9.3. Serverless function posture rules 

5.8.9.3.1. Manage serverless function rules 

📝

🟢note

You can select multiple types to view all your
serverless function policies across your cloud
providers.

📝

🟢note

Refer to Create serverless function rules for
more information on how to define the steps of
a rule in the wizard.

5.8.9.3.2. Create serverless function rules 

5.8.9.3.3. Create an attack path rule for
serverless functions 🧭 
➡️n…

Under Posture Management, select Rules &
Policies → Cloud Security (under Rules) →
click Create Rule

in as the operator → enter the CVE ID → Search

> or >= as the operator → Severity level (such
as High, Low) → Search

> or >= as the operator → enter a score →
Search

5.8.9.3.4. Create a configuration rule for
serverless functions 

5.8.9.3.5. Create a network exposure rule for
serverless functions 

🧭 5.8.9.4. Serverless function usage 

➡️n…

To access serverless function assets, under
Inventory, select All Assets → Compute →
Serverless Functions

Posture Management → Vulnerability
Management) → Vulnerability Issues

Add Filters → Asset Category → Serverless
Function

Posture Management → Vulnerability
Management) → Vulnerable Assets

Add Filters → Asset Category → Serverless
Functions

5.8.10. Cortex Cloud Application Security 

5.8.10.1. Onboard Data Sources 

5.8.10.1.1. Onboard version control systems 

📝

🟢note

Application Security (which includes IaC and
Secrets scanning), is an add-on to a license
(such as Posture Security) that must be
purchased separately.

📝

🟢note

Disclaimer: When onboarding with third-party
data sources, we outline the required steps for
setup, but we do not monitor these external
resources, and they may change over time.
Always refer to the relevant third-party
documentation for the most current integration
steps.

💡

🔵tip

Navigate to Settings → Data Sources &
Integrations → + Add New → and enter your
VCS data source in the search bar.

5.8.10.1.1.1. AWS CodeCommit 

☑️

🟣pr…

Before you begin, ensure the following:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
AWS user permissions: To onboard
CodeCommit, the user logged into the AWS
Console must have permissions to deploy the
CloudFormation stack and authorize the...

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

💡

🔵tip

The instance ID is identical to the stack ID on
the AWS platform.

🧭

➡️n…

Modules → Application Security → Periodic
scans

5.8.10.1.1.2. Azure DevOps 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
Azure DevOps permissions: Ensure the user
performing the integration holds one of the
following roles in Azure DevOps:
Project Administrator: This permission is
required to subscribe...

📝

🟢note

This forces Azure to bypass browser cookies
and issue a token for the correct directory.

📝

🟢note

PATs are static. To onboard a different tenant,
you must log in to that specific environment to
generate a new token.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

👀

🟠i…

When redirected to the Microsoft login screen,
do not immediately enter your email.

🧭

➡️n…

Settings → Data Sources & Integrations → +
Add New

User Settings → Personal access tokens → +
New Token

5.8.10.1.1.2.1. Azure DevOps onboarding system
architecture



5.8.10.1.1.3. Bitbucket Cloud 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In Bitbucket, grant the user performing the
Cortex application authorization the following
permissions. The level of access required
depends on the modules you intend to use:
For code...

📝

🟢note

Ensure that you receive the Instance
Successfully Created message on this step,
indicating successful instance creation.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.1.4. Bitbucket Data Center 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In Bitbucket, grant the user performing the
Cortex application authorization the following
permissions:
Administrator permissions for projects
Administrator permissions for...

📝

🟢note

By default, the permissions of the access token
are set according to your current access level.
It is essential to define two levels of
permissions, Project and Repository
permissions. The Repository permissions inherit
from Project permissions, requiring Repository
permissions to match or exceed Project
permissions
Providing read and write permissions...

📝

🟢note

For additional security, it is recommended to
set an expiry automatically. The expiry date of
a token cannot be changed after it is created.
You can see the expiry dates for all your tokens
on Profile picture → Manage account →
Personal access tokens.

📝

🟢note

For more information about the Transporter,
including setup instructions, refer to
Transporter over Broker VM.

📝

🟢note

Ensure that you receive the Instance
Successfully Created message on this step,
indicating successful instance creation.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

👀

🟠i…

Always refer to the Bitbucket documentation
for information relating to creating a PAT.

5.8.10.1.1.5. GitHub Cloud 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In GitHub, grant the user performing the Cortex
application authorization the following
permissions:
Organization Owner: Only an Organization
Owner can directly authorize and install...

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

🧭

➡️n…

Verify integration: On Data Sources, select
Code Providers → GitHub SaaS → View more
and confirm that the status of your integrated
GitHub instance is 'Connected

5.8.10.1.1.6. GitHub Enterprise (On-Prem) 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In GitHub, you must have Organization Owner
permissions to install the Cortex application.
Users with only repository-level admin
permissions cannot complete the installation
unless the...

📝

🟢note

The domain is the hostname associated with
your GitHub Enterprise (On-Prem) instance.

📝

🟢note

For more information about the Transporter,
including setup instructions, refer to
Transporter over Broker VM.

📝

🟢note

Ensure that you receive the Instance
Successfully Created message on this step,
indicating successful instance creation.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.1.7. GitLab SaaS 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In Gitlab, the following permissions are required
to integrate the application:
Maintainer (Project-level). Grants sufficient
permissions to configure external integrations,
manage...

📝

🟢note

A repository can only be integrated with a
single instance. The first instance that connects
with the repository will be the one that the
repository is assigned to. This means that if
multiple integrations attempt to connect to the
same repository, only the first integration to
establish the connection will be associated with
that repository.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.1.8. GitLab Self Managed (On-Prem) 

☑️

🟣pr…

Authorize the user integrating Application
Security with your GitLab Self Managed (On-
Prem) instances with the following permissions:
Maintainer permissions. Grants sufficient
permissions to configure external integrations,
manage repository access, and adjust CI/CD
settings
api: Grants full read and write access to the
API, including all groups...

📝

🟢note

The domain is the hostname associated with
your GitLab Self Managed (On-Prem) instance.

📝

🟢note

For more information about the Transporter,
including setup instructions, refer to
Transporter over Broker VM.

📝

🟢note

Ensure that you receive the Instance
Successfully Created message on this step,
indicating successful instance creation.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.2. Onboard CI/CD systems 

5.8.10.1.2.1. CircleCI for CI/CD pipeline scans 

☑️

🟣pr…

Before you begin:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
CircleCI user requirements:
Permissions: To enable Cortex XSIAM visibility
for all CircleCI projects, a version control
system (VCS) user with integration permissions
must be...

📝

🟢note

This integration utilizes a Personal Access
Token (PAT) for authentication
CircleCI onboarding offers both code and
CI/CD scanning. A single integrated instance
supports either code or CI scanning, but not
both. If you require both code and CI scanning
for your CircleCi environment, you must create
two separate integrations, selecting the
appropriate...

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.2.2. Jenkins for CI/CD pipeline scans 

☑️

🟣pr…

Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
In Jenkins:
To install and configure the Cortex plugin in
Jenkins, you must be a Jenkins Administrator
with Overall/Administer permissions
Ensure the build server allows outbound HTTPS
(Port 443...

📝

🟢note

Jenkins onboarding offers both code and CI/CD
scanning. A single integrated instance supports
either code or CI scanning, but not both. If you
require both code and CI scanning for your
Jenkins servers, you must create two separate
integrations, selecting the appropriate scanning
type for each. To onboard Jenkins for code
scans, refer to Jenkins for...

📝

🟢note

The integration is added on the console but
integration is pending, and will only be
completed after completing step 5 below. You
can view the pending integration on the Jenkins
Instances page: Select Data Sources → Jenkins
→ View Details. The type of integration is
Pipeline Risks

📝

🟢note

Always refer to the official Jenkins
documentation when installing plugins on
Jenkins servers.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.3. Integrate CI tools 

🧭

➡️n…

Settings → Data Sources & Integrations →
hover over a CI tool → View Details

Delete an instance: Right-click on an instance
of the CI tool → Delete instance → Delete

5.8.10.1.3.1. AWS CodeBuild 

☑️

🟣pr…

Before you begin:
User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files) and
manage secrets/credentials within the CI
platform to store the Cortex XSIAM API key
securely

📝

🟢note

Do not change the names of the environment
variables provided by Cortex XSIAM. They are
required for proper integration and
functionality.

📝

🟢note

The code is only a reference. Replace the
placeholder values with your build-specific
values.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.3.2. CircleCI for code scans 

☑️

🟣pr…

Before you begin:
User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files) and
manage secrets/credentials within the CI
platform to store the Cortex XSIAM API key
securely

📝

🟢note

CircleCI onboarding offers both code and
CI/CD scanning. A single integrated instance
supports either code or CI scanning, but not
both. If you require both code and CI scanning
for your CircleCi environment, you must create
two separate integrations, selecting the
appropriate scanning type for each. To onboard
CircleCI for CI/CD scans, refer to...

📝

🟢note

Do not change the names of the environment
variables provided by Cortex XSIAM. They are
required for proper integration and
functionality.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

👀

🟠i…

The cortex-secrets naming convention for the
context is mandatory to ensure functionality
and must not be changed.

5.8.10.1.3.3. Connect Cortex CLI 

☑️

🟣pr…

System requirements:
macOS (Intel Core i7, such as Sequoia): To
ensure all functionalities work correctly, you
must install the vectorscan dependency via
Homebrew, using this command: brew install
vectorscan

RHEL 8.10 and Red Hat UBI9. The following
prerequisites must be met:
Install patchelf
Install zstd
Ubuntu 20 requires the prefetch...

📝

🟢note

The Cortex CLI requires an API key with the
Standard security level.

📝

🟢note

On macOS arm 64 architecture you must
unpack the downloaded file to retrieve the
executable.

📝

🟢note

To add an additional CLI instance, navigate to
Settings → Data Sources → select the menu
for your connected CLI instance → + New
Instance, and repeat the onboarding steps.

📝

🟢note

For more information about CLI usage for CWP,
refer to Cortex CLI for Cloud Workload
Protection

For more information about CLI usage for API
Security, refer to Cortex CLI for API Security
For more information about CLI usage for
Application Security, refer to Cortex CLI usage
for Application Security

5.8.10.1.3.4. GitHub Actions 

☑️

🟣pr…

Before you begin:
User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files) and
manage secrets/credentials within the CI
platform to store the Cortex XSIAM API key
securely

📝

🟢note

Do not change the names of the environment
variables provided by Cortex XSIAM. They are
required for proper integration and
functionality.

📝

🟢note

The code is only a reference. Replace the
placeholder values with your build-specific
values.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.3.5. Jenkins for code scans 

☑️

🟣pr…

Grant Administrator permissions to the user
integrating Application Security with Jenkins
Create an egress path to establish the
designated route for outbound data
transmission from Cortex XSIAM to third party
services. For more information about
configuring egress paths, refer to Egress
configurationsEgress configurations

☑️

🟣pr…

For Application Security CI tools, you must
store secrets in Jenkins Credentials for use in
your Jenkins pipelines using either of these
methods:
Plain text storage: Store secrets directly as
plain text in Jenkins Credentials. Access them in
your pipeline using the credentials function,
which retrieves the secret directly as plain text
Credentials...

📝

🟢note

Jenkins onboarding offers both code and CI/CD
scanning. A single integrated instance supports
either code or CI scanning, but not both. If you
require both code and CI scanning for your
Jenkins servers, you must create two separate
integrations, selecting the appropriate scanning
type for each. To onboard Jenkins for CI/CD
scans, refer to Jenkins for...

📝

🟢note

This step is only required for new pipelines
For private repositories, ensure the necessary
credentials are configured in Jenkins Credentials

📝

🟢note

This ensures your build runs within a Docker
environment. If a node without Docker is used,
the build will fail.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.3.6. Terraform Cloud (Run Tasks) 

☑️

🟣pr…

Before you begin:
User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files) and
manage secrets/credentials within the CI
platform to store the Cortex XSIAM API key
securely
Procure a Terraform cloud license that is either
a trial license or a TF Cloud license at the
TEAM &...

📝

🟢note

Skip this step if you plan on using an existing
token.

📝

🟢note

Application Security performs a scan of
Terraform templates on selected workspaces
based on the Run Stage.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.3.7. Terraform Enterprise (Run Tasks) 

☑️

🟣pr…

Before you begin:
Ensure access to a Terraform Enterprise
console to enable you to provide a user or
team token that authorizes Application Security
to access workspaces and helps regulate run
configurations
Terraform Enterprise version compatibility:
Ensure Run Tasks for workspaces on is
compatible with version 1.1.9 and above
Terraform Enterprise...

📝

🟢note

For container image vulnerabilities, Application
Security performs 'Image Referencer' scans
within Terraform Enterprise (Run Tasks), as full
SCA scans are not currently supported.

📝

🟢note

Skip this step if you plan on using an existing
token.

📝

🟢note

Application Security performs a scan of
Terraform templates on selected workspaces
based on the Run Stage.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

☑️ 5.8.10.1.4. CLI pipeline code snippets 

🟣pr…

User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files).

5.8.10.1.5. Onboard private package registries 

5.8.10.1.5.1. JFrog Artifactory 

5.8.10.1.5.2. Onboard JFrog Artifactory 

☑️

🟣pr…

Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
JFrog permissions:
The permissions associated with the user
configured during the onboarding process
determine the scope of scan results. Only
repositories and artifacts the user can access
are...

📝

🟢note

To authorize the scanner to connect through
your firewall, select Enable access by IPs, and
copy the displayed source IPs to your
organization's allowlist.

📝

🟢note

For Maven:

Select Mirror Registry if this repository mirrors
an external repository
Use the Mirror Of value to define the
duplication scope:
* mirrors all requests
Type a request [value]: Mirrors only specific
requests (such as central).
For Maven:

Select Mirror Registry if this repository mirrors
an external repository
Use the Mirror Of...

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.6. Ingest third-party data sources 

📝

🟢note

Only onboarded and scanned repositories can
be mapped.

5.8.10.1.6.1. Semgrep 

☑️

🟣pr…

Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
Ensure that you have a connected version
control system (VCS) and repositories
Semgrep: A valid Semgrep API token
Note
To create a Semgrep API token, in Semgrep,
navigate to Settings → Tokens →...

📝

🟢note

Mapping establishes relationships between
Semgrep projects and Cortex XSIAM code
repositories, simplifying access management
and enabling risk analysis at the repository
level, including displaying findings on the tenant
Only mapped projects are ingested

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

👀

🟠i…

Deletion is irreversible. To restore Semgrep
findings after deletion, reconfigure the
integration and wait for the next polling cycle
to re-ingest findings from Semgrep.

5.8.10.1.6.1.1. Semgrep Software Composition
Analysis (SCA) data ingestion 

5.8.10.1.6.1.2. Semgrep Static Application
Security Testing (SAST) data ingestion 

5.8.10.1.6.2. Snyk 

☑️

🟣pr…

Permissions: The following user permissions are
required:
Cortex XSIAM user permissions: Ensure you
have View/Edit permissions for Data Sources
and Integrations (RBAC: AppSec Admin or
Instance Administrator)
Ensure that you have a connected version
control system (VCS) and repositories
Snyk permissions and requirements:
Permissions: The...

📝

🟢note

Select Test Connection to verify that Cortex
Cloud can connect to your Snyk organization.

📝

🟢note

SCA requires Snyk Open Source or Snyk
Container projects configured in the
organization
SAST requires Snyk Code enabled and projects
configured in the organization

📝

🟢note

Mapping establishes relationships between
Snyk applications and Cortex XSIAM code
repositories, simplifying access management
and enabling risk analysis at the repository
level, including displaying findings on the tenant
Only mapped applications are ingested

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.6.2.1. Snyk Software Composition
Analysis (SCA) ingestion 

5.8.10.1.6.2.2. Snyk Static Application Security
Testing (SAST) Findings 

5.8.10.1.6.3. SonarQube 

☑️

🟣pr…

Permissions: Ensure you have System Admin,
AppSec Admin or GRBAC permissions. For more
information on AppSec Admin permissions,
refer to Code Security user roles and
permissions
Ensure that you have a connected version
control system (VCS) and repositories
Generate and copy a SonarQube API token.
Ensure to assign Web API scope to the API
token. Refer...

📝

🟢note

Mapping establishes relationships between
SonarQube Applications and Application
Security code repositories, simplifying access
management and enabling risk analysis at the
repository level, including displaying findings on
the tenant
Only mapped projects will be ingested

📝

🟢note

Verify that the Connector Created Successfully
message is displayed on the page.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.6.4. Veracode 

☑️

🟣pr…

Permissions: The following user permissions are
required:
Cortex Cloud: Instance Admin, AppSec Admin
or GRBAC permissions. For more information on
AppSec Admin permissions, refer to Code
Security user roles and permissions
Veracode: At minimum, Reviewer permissions
are required
Permissions: The following user permissions are
required:
Cortex...

📝

🟢note

Only mapped applications will be ingested.

📝

🟢note

This is the recommended option to ensure
complete coverage and successful operation
of all features.

📝

🟢note

Mapping establishes relationships between
Veracode projects and Application Security
code repositories, simplifying access
management and enabling risk analysis at the
repository level, including displaying findings on
the tenant
Only mapped projects will be ingested

📝

🟢note

Verify that the Connector Created Successfully
message is displayed on the page.

📝

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.6.5. Generic 3rd Party AppSec Collector 

👀

🟠i…

File uploads are limited to a maximum size of 10
MB.

5.8.10.1.6.5.1. Onboard the 3rd Party AppSec
Collector 

📝 5.8.10.1.7. Manage data source integrations 

🟢note

Requisite RBAC permissions are required for
edit and delete operations.

5.8.10.1.8. Transporter over Broker VM 

☑️

🟣pr…

Ensure you have the necessary permissions and
have already set up your Broker VM
Confirm that your Broker is v 28 or above
Whitelist IP addresses to enable access to
Cortex XSIAM resources. The IP addresses for
the Transporter are in the Broker VM Resources
section of the Enable access to required PANW
resources document
Open port 4052 (inbound), which...

📝

🟢note

The broker enables multiple connections,
allowing a single Transporter applet to connect
to various VCS instances
Multiple Transporter applets cannot be created
on a single Broker VM. Each Broker VM is
limited to a single Transporter applet instance

⛔

🔴w…

The Transporter applet is not supported for
FedRAMP customers.

5.8.10.1.8.1. Set up a Transporter applet on
Broker VM 

☑️

🟣pr…

Permissions: To configure and manage
Transporter applet settings, you must have
permissions to manage Broker Service
configurations (such as an Instance
Administrator)

📝

🟢note

You cannot add a Transporter applet through
Clusters.

🧭

➡️n…

your AppSec Transporter under the App
column → Configure → Add Connection (on
the redirected AppSec Transporter setup page

5.8.10.1.8.2. Set up a Transporter on your VCS 

☑️

🟣pr…

Ensure you have user permissions to onboard
data sources.
Note
The dedicated AppSec Admin role includes the
required permissions.
Ensure you have user permissions to onboard
data sources.
Before you begin you must setup a Transporter
applet on your Broker VM. Refer to Set up a
Transporter applet on Broker VM for more
information

📝

🟢note

GitLab Enterprise webhook internal IP
restriction: GitLab Enterprise's security policies
prevent webhook subscriptions to internal IP
addresses (such as broker addresses). These
subscriptions can only be enabled through
specific instance configuration. For more
information, refer to
https://docs.gitlab.com/security/webhooks/.

🧭

➡️n…

Settings → Data Sources & Integrations → +
Add New → , and search for your VCS on-
premises data source

🧭 5.8.10.2. Application Security dashboard 

➡️n…

Modules → Application Security → AppSec
Dashboard

5.8.10.3. Application Security Posture
Management (ASPM) 

5.8.10.3.1. ASPM use cases 

5.8.10.3.2. ASPM key features 

🧭 5.8.10.3.3. ASPM user roles and permissions 

➡️n…

You can view AppSec Admin permissions in the
tenant by navigating to Settings →
Configurations → Roles → AppSec Admin

5.8.10.3.4. Code to Cloud 

🧭

➡️n…

Full Code to Cloud (C2C) coverage is achieved
when Cortex XSIAM can resolve the following
chain: Repository → Pipeline → Image →
(optional Registry) → Runtime resources
(including VMs, VM images, and IaC-defined
infrastructure

5.8.10.3.4.1. Supported integrations 

🧭 5.8.10.3.4.2. Code to Cloud visibility 

➡️n…

Topology graph: Located in the Business
Applications side card, this tab visualizes the
entire path to production (Code → Build →
Deploy → Run), allowing you

📝 5.8.10.3.4.3. Code to Cloud troubleshooting 

🟢note

Empty state messages and troubleshooting
guidance for missing lineage are only visible to
users with an active license.

📝 5.8.10.3.5.1. ASPM Command Center workflow  5.8.10.3.5. ASPM Command Center 

🟢note

Breakdown by type: Issues are further broken
down by type (such as IAC or Secrets).

5.8.10.3.6. Applications 

5.8.10.3.6.1. Defining Business Applications 

5.8.10.3.6.1.1. Defining business applications by
Criteria 

5.8.10.3.6.1.2. Define applications by VCS criteria 

5.8.10.3.6.1.3. Manage application criteria 

5.8.10.3.6.1.4. Define applications by cloud tag-
based criteria 

5.8.10.3.6.1.5. How to manually build an
application 

5.8.10.3.6.2. Application management and
visibility 🧭 
➡️n…

Inventory → All Assets → Business Applications
(under Application

5.8.10.3.6.3. Business application assets 

5.8.10.3.6.3.1. Business application expanded
asset details 

5.8.10.3.6.3.2. Export business application data 

5.8.10.3.6.4. Scope user access to applications
(Application SBAC) 

🧭

➡️n…

Configure user scopes in Cortex XSIAM by
navigating to Settings → Configurations →
Access Management

5.8.10.3.6.4.1. Enable SBAC in the Cortex XSIAM

tenant 

5.8.10.3.6.4.2. Create an application-based Asset
Group



5.8.10.3.6.4.3. Scope user access to an

application 

5.8.10.3.6.4.4. Create application-scoped policies 

5.8.10.3.7. Repositories as assets 

5.8.10.3.7.1. Explore repository assets 

5.8.10.3.7.2. In-depth repository asset information 

5.8.10.3.7.3. Manage Repository assets 

5.8.10.3.7.4. Export Software Bill of Materials
(SBOM) 

5.8.10.3.7.5. Manage issues detected in
repositories 📝 
🟢note

You can also find the repository issues in the
general issue inventory table, and in the
dedicated inventory of issues for each scanner
type (see step 4 above for details).

🧭 5.8.10.3.8.1. Coverage in the user interface  5.8.10.3.8. Coverage 

➡️n…

Modules, → Application Security → AppSec
Coverage

5.8.10.3.9.1. Urgency metrics  5.8.10.3.9. Urgency 

5.8.10.3.10. Backlog baseline 

5.8.10.3.10.1. Backlog use cases 

5.8.10.3.10.2. Issue/Finding classification by
scanner



📝

🟢note

In some cases/vendors, this is not accurate as
findings are deleted every time new findings are
uploaded. In such cases, the feature may not be
accurate or supported
For SAST, the vendor does not support policy in
pull requests

📝

🟢note

Scanner updates and new detections: When a
security scanner is updated to support new
languages, detection rules, or capabilities, any
issues discovered by these new features for
existing code are classified as part of the
backlog.

5.8.10.3.10.3. Using Backlog 

5.8.10.3.11. Service Lead Agreements (SLA) 

5.8.10.3.11.1. Configure and monitor Application
Security SLAs 🧭 
➡️n…

Settings → Configurations → Application
Configuration (under Application Security

5.8.10.3.12. Compliance for Application Security 

5.8.10.3.12.1. Infrastructure-as-Code (IaC)

compliance 

5.8.10.3.12.2. Manage IaC compliance 

☑️

🟣pr…

Add these properties to the IaC Rules table
through the Table Settings Menu, as they are
not exposed by default.

🧭

➡️n…

Modules → Application Security → AppSec
Polices → Add Policy

5.8.10.3.12.3. CI/CD Compliance 

🧭

➡️n…

To access Compliance, select Posture
Management → Compliance → Reports or
Assessment

5.8.10.3.12.3.1. Create CI/CD compliance reports 

5.8.10.3.13. Application Security Policies 

5.8.10.3.13.1. User roles and permissions 

📝 5.8.10.3.13.2. Policies inventory 

🟢note

To view all out-of-the-box (OOTB) policies,
filter by Policy Owner = System.

5.8.10.3.13.3. AI-recommended guardrails 

5.8.10.3.13.3.1. Manage AI-recommended
guardrails 

5.8.10.3.13.4. Create Application Security policies 

📝

🟢note

When an issue is created, only the first policy ID
that triggered the issue is associated with it.

5.8.10.3.13.4.1. Create code security policies 

5.8.10.3.13.4.1.1. Application Security code policy
Condition attributes 

5.8.10.3.13.4.2. Create IaC Drift Detection policies 

5.8.10.3.13.4.3. Manage Application Security
policies 

5.8.10.3.14. Application Security Rules 

📝

🟢note

Out-of-the-box rules cannot be modified
directly. However, you can create a custom rule
by cloning the existing one. This allows you to
make changes to the original rule according to
your requirements. Refer to Manage Application
Security custom rules for more information.

5.8.10.3.14.1. Roles and permissions 

🧭 5.8.10.3.14.2. Rules inventory 

➡️n…

To filter rules relating to Secrets, select filter
icon → Scanner (from the Select field) →
Secrets (from the Value field

5.8.10.3.14.3. Create custom Application
Security rules 

📝

🟢note

See Configure YAML file properties below for
more details.

📝

🟢note

Scanning/testing behavior is not supported.

5.8.10.3.14.4. Manage Application Security
custom rules 

5.8.10.3.14.5. Configure YAML file properties 

5.8.10.3.15. Manage code weaknesses 

📝

🟢note

You can customize policies to define which
findings are categorized as issues.

🧭

➡️n…

Dedicated issues view: To access SAST code
violation issues, under Modules, select
Application Security → Issues → Code
Weaknesses

Issues → AppSec Issues (under All Issues) →
SAST Scanner (as the Detection Method value

5.8.10.3.15.1. Code weaknesses issue inventory 

5.8.10.3.15.2. Detailed code weakness issue

information 📝 
🟢note

Different issue types include different
properties; therefore, not all properties are
available for every issue.

📝 5.8.10.3.15.3. Code weakness findings 

🟢note

Findings on the Cortex platform are not
intended for direct action; but rather represent
data collected by the platform. They must be
promoted to issues to enable mitigation efforts
to secure your codebase.

5.8.10.4. CI/CD Security 

5.8.10.4.1. CI/CD Security user roles and
permissions 

5.8.10.4.2. CI/CD Assets 

5.8.10.4.2.1. CI/CD Instances as assets 

5.8.10.4.2.1.1. Explore CI/CD Instance assets 

5.8.10.4.2.1.2. In-depth CI/CD pipeline instance
asset information 

5.8.10.4.2.1.3. Manage CI/CD pipeline instances 

5.8.10.4.2.2. CI/CD Pipelines as assets 

5.8.10.4.2.2.1. Explore CI/CD Pipeline assets 

5.8.10.4.2.2.2. In-depth CI/CD pipeline asset
information 

5.8.10.4.2.2.3. Manage CI/CD pipeline assets 

5.8.10.4.2.3. Version Control System (VCS)
Organizations as assets 

5.8.10.4.2.3.1. Explore VCS Organization assets 

5.8.10.4.2.3.2. In-depth VCS Organization asset
information 

5.8.10.4.2.3.3. Manage VCS organization assets 

5.8.10.4.2.4. VCS Collaborators-as-assets 

5.8.10.4.2.4.1. In-depth Collaborator asset
information 

5.8.10.4.2.4.2. Manage Collaborator assets 

5.8.10.4.3. Supply Chain Inventories 

📝

🟢note

Although attributes are identical across
inventories, their values for the same tool can
differ, most commonly in Risk Factors and Type.
This is because the inventory reflects your live
environment, which may include different
versions or configurations than the catalog—for
example, a package may not have been
upgraded or may be deployed differently.

🧭

➡️n…

In the inventory table, right-click on a tool →
Change Status → select a status

5.8.10.4.3.1. Supply Chain Tools 

5.8.10.4.3.1.1. Supply Chain Tools 

5.8.10.4.3.1.2. Expanded Supply Chain tool
information 

🧭 5.8.10.4.3.2. Supply Chain Catalog 

➡️n…

To access the Supply Chain Catalog, select
Modules → Application Security → Supply
Chain Catalog (under 3rd party tools

5.8.10.4.4. CI/CD Risks 

📝

🟢note

Application Security CI/CD pipeline scans
create a comprehensive inventory of all CI/CD
pipelines in your environment. For more
information refer to CI/CD Pipelines as assets.

🧭 5.8.10.4.4.1. CI/CD pipeline issues 

➡️n…

To access CI/CD pipeline risks issues, under
Modules, select Application Security → Issues
→ CI/CD Risks

5.8.10.4.4.2. Expanded CI/CD risks issue
information 📝 
🟢note

Different issue types include different
properties; therefore, not all properties are
available for every issue.

5.8.10.4.4.3. VCS and CI/CD pipeline risk findings 

5.8.10.4.5. CI/CD Rules 

📝

🟢note

Out-of-the-box rules cannot be modified
Custom CI/CD rules are not supported

5.8.10.4.5.1. CI/CD rules roles and permissions 

5.8.10.4.5.2. CI/CD rules inventory 

5.8.10.4.6. CI/CD Policies 

💡

🔵tip

For Cortex XSIAM Code policies, refer to
Application Security Policies.

5.8.10.4.6.1. CI/CD policies user roles and
permissions 

📝 5.8.10.4.6.2. CI/CD policies inventory 

🟢note

To view all out-of-the-box (OOTB) policies,
filter by Policy Owner = System.

5.8.10.4.6.3. Create custom CI/CD policies 

📝

🟢note

PR Scan and CI Scan triggers are automatically
disabled and unchecked. They can only be
enabled if other scan types (that is non-CI/CD
risk scans such as Secrets) are also selected,
and will only run on non-CI/CD risks types of
scans

📝

🟢note

You can combine multiple conditions to create
complex rules for when the policy should apply.
Create conditions that apply to a CI/CD policy
which detects high severity CI/CD risks on
GitHub: Select Add Filter → Finding Type →
CI/CD Risks → AND → Provider → [VCS/CI/CD
system] → AND → Severity: → High.

📝

🟢note

SBAC scope limitations do not apply to
Matching Criteria
For CI/CD policies, you can filter Matching
Criteria by VCS Organization Name, CI/CD
Pipeline [Name/ID], CI/CD Instance [Name/ID] or
Collaborator [Name/Email/MFA Enabled/Last
Observed]

5.8.10.4.6.4. Manage CI/CD policies 

📝

🟢note

You cannot edit out-of-the-box (OOTB)
policies.

📝

🟢note

The duplicated policy will include the word
"clone" in its name and must be renamed.

5.8.10.5. Code Security 

5.8.10.5.1. Code Security user roles and
permissions 

5.8.10.5.2. Code Security assets 

5.8.10.5.3. Software packages as assets 

5.8.10.5.3.1. Explore software package assets 

5.8.10.5.3.2. In-depth software package asset
information 

5.8.10.5.4. Infrastructure-as-Code (IaC)
resources as assets 

🧭 5.8.10.5.4.1. Explore IaC assets 

➡️n…

To access IaC assets, under Inventory, select All
Assets → Code → IaC Resources

5.8.10.5.4.2. In-depth IaC resource asset
information 

5.8.10.5.5. Code Security scanners 

5.8.10.5.6. Secrets scanners 

🧭 5.8.10.5.6.1. Secrets issues 

➡️n…

Under Modules, select Application Security →
Issues → Secrets

Inventory → All Assets → Code: On the Secrets
tab under Repositories

Inventory → All Assets → Code

Inventory → All Assets → Application → select
an option from the Application menu → select
an item from the inventory → Secrets

5.8.10.5.6.2. Secrets issues inventory 

📝 5.8.10.5.6.3. Detailed Secrets issue information 

🟢note

Different issue types include different
properties; therefore, not all properties are
available for every issue.

5.8.10.5.6.4. Secrets findings 

📝

🟢note

Findings are informational and, as such, are not
directly mitigable. Remediation is performed on
issues derived from findings.

🧭

➡️n…

The Application Security Secrets Findings table
is a pre-filtered view of the comprehensive
Findings inventory (located at Cases & Issues →
Issues → Findings Table tab

To access Secrets findings, select Application
Security → Issues → Secrets → click the
Findings tab

5.8.10.5.6.5. Manage Secrets issues 

5.8.10.5.7. Infrastructure as Code (IaC)

misconfiguration scanner 

5.8.10.5.7.1. Supported frameworks and languages 

5.8.10.5.7.2. IaC misconfiguration issues 

💡

🔵tip

You can also view IaC misconfiguration issues in
dedicated tabs under other sections when
available:
In code Asset inventories, navigate to Inventory
→ All Assets → Code:
On the Configuration tab under Repository
assets. Refer to In-depth repository asset
information for more information
Under the All Code asset inventory: Select an
asset from...

🧭

➡️n…

To access IaC misconfiguration issues, under
Modules, select Application Security → Issues
→ IaC misconfiguration

5.8.10.5.7.3. IaC misconfiguration issues inventory 

5.8.10.5.7.4. Detailed IaC misconfiguration issue
information 📝 
🟢note

Different issue types include different
properties; therefore, not all properties are
available for every issue.

5.8.10.5.7.5. IaC misconfiguration findings 

📝

🟢note

Findings are informational and, as such, are not
directly mitigable. Remediation is performed on
issues derived from findings.

🧭

➡️n…

To access IaC misconfiguration findings, under
Modules, select Application Security → Issues
→ IaC Misconfigurations → click the Findings
tab

5.8.10.5.7.6. Manage IaC misconfiguration issues 

5.8.10.5.8. IaC Drift Detection scans 

🧭 5.8.10.5.8.1. IaC Drift Detection issues 

➡️n…

Modules → Application Security → IaC Drifts

5.8.10.5.8.2. IaC Drift Detection issue inventory 

5.8.10.5.8.3. Detailed IaC drift detection issue

information 

🧭 5.8.10.5.8.4. IaC Drift Detection findings 

➡️n…

Modules → Application Security → IaC Drifts
(under Issues) → click the Findings tab

5.8.10.5.9. Software Composition Analysis (SCA)
scanners



5.8.10.5.9.1. Supported Software Composition
Analysis (SCA) frameworks and languages 

5.8.10.5.9.2. Software Composition Analysis
(SCA) vulnerability issues 

💡

🔵tip

In Asset inventories, navigate to Inventory → All
Assets → Code:
On the Vulnerabilities tab under Repositories.
Refer to In-depth repository asset information
for more information
Under the All Code inventory: Select an asset
from the table → Vulnerabilities
In Asset inventories, navigate to Inventory → All
Assets → Code:
On the...

🧭

➡️n…

To access CVE vulnerability issues, under
Modules, select Application Security → Issues
→ Vulnerabilities

5.8.10.5.9.2.1. Vulnerability issues inventory 

5.8.10.5.9.2.2. Detailed vulnerability issue
information 

5.8.10.5.9.2.3. CVE vulnerabilities findings 

5.8.10.5.9.2.4. Manage SCA CVE vulnerability
issues 

5.8.10.5.9.3. License miscompliance issues 

💡

🔵tip

You can also view license miscompliance issues
in dedicated tabs under other sections when
available:
In Application asset inventories: navigate to
Inventory → All Assets → Application → select
an option from the Application menu → select
an item from the inventory → Package Integrity
In Asset inventories, navigate to Inventory → All...

🧭

➡️n…

To access license miscompliance issues, under
Modules, select Application Security → Issues
→ Licenses

5.8.10.5.9.3.1. License miscompliance issues
inventory 

5.8.10.5.9.3.2. Expanded License miscompliance
issues information 

5.8.10.5.9.3.3. License miscompliance findings 

5.8.10.5.9.3.4. Open-source software license
categories 

5.8.10.5.9.3.5. Manage license miscompliance
issues 

5.8.10.5.9.4. Package Integrity 

5.8.10.5.9.4.1. Package Integrity inventory 

5.8.10.5.9.4.2. Expanded Package Integrity issues
inventory information 

5.8.10.5.9.4.3. Package Integrity findings 

5.8.10.5.9.4.4. Manage Package Integrity issues 

5.8.10.5.10. Application Security scans
management 

📝 5.8.10.5.10.1. Overview 

🟢note

While scans provide a comprehensive inventory
of all issues detected during a scan, dedicated
inventories are also maintained for specific
scan types for more granular management. For
more information, refer to Infrastructure as
Code (IaC) misconfiguration scanner, Secrets
scanners and Software Composition Analysis
(SCA) scanners.

📝 5.8.10.5.10.2. Branch periodic scans 

🟢note

The inventory table displays scan issues for
visibility only; remediation is not available here.
To resolve issues, navigate to the dedicated
issue type inventory, where you can manage
and remediate them.

📝 5.8.10.5.10.3. Pull Request scans 

🟢note

The inventory table displays scan issues for
visibility only; remediation is not available here.
To resolve issues, navigate to the dedicated
issue type inventory, where you can manage
and remediate them.

📝 5.8.10.5.10.4. CI scans 

🟢note

The inventory table displays scan issues for
visibility only; remediation is not available in
scan management. To resolve issues, navigate
to the dedicated issue type inventory, where
you can manage and remediate them.

5.8.10.5.10.5. Manage repository scan
configurations 

5.8.10.5.10.6. Monitor data source instances

health 

5.8.10.5.11. Application Security CLI 

☑️

🟣pr…

These requirements apply specifically to the
Application Security CLI.
For the Cortex CLI binary:
Ensure you have Node.js v22 installed on your
host machine before running any scans with the
Cortex CLI. This is crucial to prevent runtime
errors, as the CLI depends on Node.js for
executing JavaScript analysis
Note
To check your version of...

📝

🟢note

For detailed information about the Cortex
XSIAM CLI, refer to Cortex CLI.

5.8.10.5.11.1. Connect Cortex CLI 

☑️

🟣pr…

System requirements:
macOS (Intel Core i7, such as Sequoia): To
ensure all functionalities work correctly, you
must install the vectorscan dependency via
Homebrew, using this command: brew install
vectorscan

RHEL 8.10 and Red Hat UBI9. The following
prerequisites must be met:
Install patchelf
Install zstd
Ubuntu 20 requires the prefetch...

📝

🟢note

The Cortex CLI requires an API key with the
Standard security level.

📝

🟢note

On macOS arm 64 architecture you must
unpack the downloaded file to retrieve the
executable.

📝

🟢note

To add an additional CLI instance, navigate to
Settings → Data Sources → select the menu
for your connected CLI instance → + New
Instance, and repeat the onboarding steps.

📝

🟢note

For more information about CLI usage for CWP,
refer to Cortex CLI for Cloud Workload
Protection

For more information about CLI usage for API
Security, refer to Cortex CLI for API Security
For more information about CLI usage for
Application Security, refer to Cortex CLI usage
for Application Security

5.8.10.5.11.2. Self-service API keys for CLI scans 

5.8.10.5.11.3. Cortex CLI usage for Application
Security 

☑️ 5.8.10.5.11.4. CLI pipeline code snippets 

🟣pr…

User permissions: Ensure the user performing
the integration has permissions to edit pipeline
configurations (such as YAML files).

5.8.10.5.11.5. Cortex CLI Application Security
command line reference



📝

🟢note

The repo-id flag must not end with .config, .log
or .ini. -config is acceptable.
--repo-id foo.config will be blocked
--repo-id foo-config will pass

👀

🟠i…

The Cortex CLI Application Security only
supports single occurrences of each flag. If the
same flag is passed multiple times, only the last
provided value will be used. For example, in the
following command, only TF CloudFormation
will be the scanned framework.
./cortexcli --api-base-url <YOUR_API_URL> --
api-key <YOUR_API_KEY> --auth-id
<YOUR_AUTH_ID>...

5.8.10.5.11.6. Cortex CLI common command line

reference guide 📝 
🟢note

For soft fails, a failed check matches the
defined severity threshold. If multiple soft fail
severities are specified, the highest severity acts
as the threshold for determining a soft fail.
However, a successful scan will always return
an exit code of 0, even if block-level findings
(which might trigger soft fails based on
severity) are present.

5.8.10.5.11.7. Git Hooks 

5.8.10.5.11.7.1.1. Pre-commit hook usage  5.8.10.5.11.7.1. Cortex CLI pre-commit hooks 

5.8.10.5.11.7.2.1. Pre-receive hook usage  5.8.10.5.11.7.2. Cortex CLI pre-receive hooks 

5.8.10.5.12. IDE 

📝

🟢note

Not all remediation options are available for all
findings or all type of scan category.

5.8.10.5.12.1. System requirements 

5.8.10.5.12.2. Visual Studio (VS) Code and VS

Code compatible IDEs 

☑️

🟣pr…

Before you begin (These prerequisites apply to
both VS Code and VS Code compatibles):
Permissions: CLI Read only permissions. Refer to
Cortex CLI for more information about
permissions
Environment setup
macOS and Windows: Install Python 3.9.x to
3.12.x
Install Node.js version 22 and above for SCA
scans (such as vulnerabilities scans)
Environment...

☑️

🟣pr…

You must insert your API key and API ID values
into the Settings before providing the tenant
URL.

📝

🟢note

Enforcement rules and CA certificates are not
applicable to the open-source project.

👀

🟠i…

When generating an API key, ensure you select
the Standard security level. IDE and CLI scans
will fail if the security level of the API key is set
to Advanced.

💡

🔵tip

You can access Extensions using the keyboard
shortcuts Ctrl+Shift+X (Windows) or
Cmd+Shift+X (macOS).

🧭

➡️n…

Settings → Configurations → API Keys (under
Integration) → click Copy API URL

Install through VS Code IDE Access the Activity
bar → Extensions → Cortex Cloud → Install

Access the Activity bar → Extensions → Cortex
Cloud → Install

5.8.10.5.12.2.1. How to use the Cortex Cloud

extension in VS Code 

5.8.10.5.12.3. JetBrains 

☑️

🟣pr…

Permissions: CLI Read only permissions. Refer to
Cortex CLI for more information about
permissions
Environment setup
macOS and Windows: Install Python 3.9.x to
3.12.x
Install Node.js version 22 and above for SCA
scans (such as vulnerabilities scans)
Environment setup
macOS and Windows: Install Python 3.9.x to
3.12.x
Install Node.js version 22 and...

☑️

🟣pr…

You must insert your API key and API ID values
into the Settings before providing the tenant
URL.

📝

🟢note

The Cortex AppSec code security plugin
supports all JetBrains products.

👀

🟠i…

When generating an API key, ensure you select
the Standard security level. IDE and CLI scans
will fail if the security level of the API key is set
to Advanced.

🧭

➡️n…

Settings → Plugins → select the Marketplace
tab → search for Prisma Cloud → Install → OK

Settings → Tools → Cortex Cloud

5.8.10.5.12.3.1. How to use the JetBrains Cortex

XSIAM extension 

📝 5.8.10.5.13. Developer Suppressions 

🟢note

The check IDs and rule names are placeholders
for illustration purposes and do not correspond
to actual checks.

5.8.10.6. API documentation 

5.8.11. Cloud Workload Policies and Rules 

☑️

🟣pr…

Users need View/Edit RBAC permissions (under
Policies → Compute Policies) or the Instance
Administrator role to view, edit, and modify
Cloud Workload Policies policies.

👀

🟠i…

Users with SBAC granular scoping (in addition
to the RBAC permissions required for Cloud
Workload Policies) can only view Cloud
Workload Policies, when their access is scoped
to any of the available options: All assets, No
assets, or Select asset groups. For more
information on granular scoping, see Manage
user scope. When no SBAC restriction is...

5.8.11.1. How policies and rules work together 

5.8.11.2. Cloud Workload Policies 

📝

🟢note

Issues are automatically resolved when the
finding is no longer applicable to the asset or
when the affected asset is removed from the
inventory.
For more details on Prevent and create issues,
see Cloud Workload Preventive Action.

5.8.11.2.1. Types of Cloud Workload Policies 

5.8.11.2.1.1. Trusted image cloud workload
policies 

📝

🟢note

Registry scanning is for finding problems that
are objectively issues regardless of context,
organization, or scope. Trust, however, is
subjective. Depending on the scope and other
factors, an issue may or may not be
problematic, and can change over time
depending on the context.

📝

🟢note

Trusted image policies do not override other
policies and their rules, such as malware
policies, misconfiguration policies, and secrets
policies.

⚠️

🟡c…

The default behavior for the prevent action
when trust criteria are unavailable is Create an
Issue. Be aware that changing this default will
mean an incomplete deployment file can block
a workload.

5.8.11.2.2. Cloud Workload Policies page 

📝

🟢note

Keep the following caveats in my mind when
working with Policies:
Instance Administrators are able to view all
facets of policies without restrictions, even if
Scope Based Access Control (SBAC) roles are
in effect. Learn more about SBAC.Manage user
scope

If you've been assigned a custom role with
View/Edit permissions limited by SBAC, you may
not be...

5.8.11.2.2.1.1. Show or hide the widget panel  5.8.11.2.2.1. Widgets panel 

5.8.11.2.2.2. Change the layout of the policies
table 

5.8.11.2.2.3. Policy Details Panel 

5.8.11.2.3. Enable or disable a Cloud Workload

Policy 🧭 
➡️n…

Posture Management → Rules & Policies →
Policies → Cloud Workload

5.8.11.2.4. Create a Cloud Workload Policy 

📝

🟢note

The Evaluation stage for Misconfiguration
policies is supported only in the Runtime SDLC
stage and is enforceable through the
Kubernetes Admission Controller for clusters
on-boarded using the Posture Management
(KSPM) Connector.

📝

🟢note

Use Create a new Custom Detection Rule to
define and add new custom rules as required.

📝

🟢note

Each rule may support different actions. While
some include both Create an Issue and Prevent
and Create an Issue, others provide only the
Create an Issue option.

📝

🟢note

All non-relevant (non-compute) assets are
automatically excluded from the included asset
list.

📝

🟢note

Currently, dynamic asset groups for Kubernetes
Prevent Policies support only the following
attributes:
Kubernetes Resource Cluster: The cloud
identifier for the cluster.
Kubernetes Resource Namespace: The
namespace where the resource is located.
Kubernetes Resource Labels: The labels
assigned to the resource.
Kubernetes Resource Category: The category...

📝

🟢note

See Cloud Workload Preventive Action, to learn
more about the Prevent action behavior and
prerequisites.
If the Prevent and create an issue action is
selected, the preventive actions in the CI
pipeline will trigger a Fail Pipeline by returning
an exit code of 2 in the CI tool.

📝

🟢note

Choosing this option results in the automatic
selection of all other asset scopes in the list.

📝

🟢note

See Cloud Workload Preventive Action, to learn
more about the Prevent action behavior and
prerequisites.

📝

🟢note

See Cloud Workload Preventive Action, to learn
more about the Prevent action behavior and
prerequisites.

📝

🟢note

Choosing this option results in the automatic
selection of all other asset scopes in the list.

📝

🟢note

See Cloud Workload Preventive Action, to learn
more about the Prevent action behavior and
prerequisites.

5.8.11.2.5. Use an existing policy to create a new
Cloud Workload policy



5.8.11.2.6. Edit a Cloud Workload Policy 

5.8.11.2.7. Delete a Cloud Workload Policy 

5.8.11.2.8. Cloud Workload Preventive Action 

5.8.11.3. Cloud Workload Rules 

5.8.11.3.1. Default (pre-defined) Rules 

5.8.11.3.2. Custom (user-defined) Rules 

5.8.11.3.3. Cloud Workload Rules page 

📝

🟢note

Keep the following caveats in my mind when
working with Rules:
Instance Administrators are able to view all
facets of Rules without restrictions, even if
Scope Based Access Control (SBAC) roles are
in effect. Learn more about SBAC.Manage user
scope

If you've been assigned a custom role with
View/Edit permissions limited by SBAC, you may
not be able...

5.8.11.3.3.1. Filter page results 

5.8.11.3.3.2. Change the layout of the rules table 

5.8.11.3.3.3. Rule details panel 

5.8.11.3.4. Create a new Custom Detection Rule 

📝

🟢note

The custom rule must use the match term (not
deny or others) to function properly.

📝

🟢note

Only users with the following roles can enable
or disable Custom Code Execution:
Account Admin
Instance Administrator
Deployment Admin
Privileged Security Admin

📝

🟢note

Only Custom Detection Rules (not built-in
rules) can be assigned to custom controls.

👀

🟠i…

The custom Python scripts are intended to be
executed exclusively for compliance checks
and validations. To ensure the scripts are used
properly and no security risks or unintended
changes occur, the system implements the
following restrictions and safeguards:
Only a predefined set of Python libraries and
functions required for compliance checks are...

5.8.11.3.5. Use an existing rule to create a new
Custom Detection Rule 🧭 
➡️n…

Posture Management → Rules & Policies →
Rules → Cloud Workload

5.8.11.3.6. Edit a Custom Detection Rule 

5.8.11.3.7. Delete a Custom Detection Rule 

5.8.12. Web and API Security (WAAS) 

🔒 5.8.12.1. Overview 

🟣c…

Requires Cortex XSIAM Premium or any other
XSIAM license with the Cloud Runtime Security
add-on.

5.8.12.2. Personas workflow 

5.8.12.3. Secure your API landscape 

5.8.12.3.1. Gain visibility and assess risk of API
endpoints 

📝

🟢note

Data classification findings are only available
for enabled profiles.

📝

🟢note

Indicates that a JSON Web Token was identified,
but it is unknown how to determine its type
from the given string. It could be a non-
standard JSON Web Token creation algorithm.

📝

🟢note

To link APIs to business applications, the two
prerequisites must be met:
The VM must have XDR agent with WAAS
enabled.
Applications must be defined in Application
Security Posture Management
(ASPM).Application Security Posture
Management (ASPM)

5.8.12.3.2. Monitor and investigate API threats 

5.8.12.3.3. Configure API security from end to
end 

5.8.12.3.3.1. Third-party integrations 

5.8.12.3.3.1.1. Ingest AWS API Gateway 

5.8.12.3.3.1.2. Ingest Azure APIM 

5.8.12.3.3.1.3. Ingest Apigee Proxy 

5.8.12.3.3.1.4. Ingest Kong 

5.8.12.3.3.1.5. Ingest-F5 

5.8.12.3.3.2. Agent-based protection 

📝

🟢note

Web and API Security (WAAS) profiles and
policies are currently a Beta feature.

5.8.12.3.3.2.1. Set up Web and API Security
profiles 

5.8.12.3.3.2.2. Apply Web and API Security
profiles to workloads 

5.8.12.3.3.2.3. Manage Web and API Security
prevention profiles 

5.8.12.3.3.2.4. Add a disable prevention rule for
cloud workloads 

5.8.12.3.3.2.5. Add a support exception rule for
cloud workloads 

5.8.12.3.3.2.6. Add a legacy exception rule for
cloud workloads 

5.8.12.3.3.2.7. Additional workload management
tasks



5.8.12.3.4. API specification inventory 

📝

🟢note

Even if you have already imported the
specification, you can edit the API specification
in Cortex XSIAM and add or update the server
list.

📝 5.8.12.3.4.1. Import API specification 

🟢note

Even if you already imported the file, you can
edit the API asset and add or update the server
list.

5.8.13. Serverless function runtime security 

5.8.13.1. Overview 

5.8.13.2. Set up serverless function protection 

📝 5.8.13.3. Serverless runtime issues 

🟢note

Issues triggered within 24 hours, sharing the
same name and description, will be aggregated
into cases along with issues from the same
function per execution.

5.9. Cortex Advanced Email Security 

5.9.1. Cortex Advanced Email Security module
overview ☑️ 

🟣pr…

The following are prerequisites for using the
Cortex XSIAM Advanced Email Security module.
REQUIREMENT
DESCRIPTION
Setup and Permissions
Ensure Analytics is activated before enabling
the Cortex Advanced Email Security module.
Licenses and Add-ons
Cortex Advanced Email Security add-on.

5.9.2. Cortex Advanced Email Security module
architecture and data flow



5.9.3. Getting started with the Cortex Advanced
Email Security module ☑️ 
🟣pr…

Before you configure the Cortex Advanced
Email Security module, ensure you have the
following:
Admin-level access to the target email platform
Dedicated service account (recommended) for
integration purposes (response actions)
List of domains and mailboxes to be protected
(to be used during the wizard configuration)
Access to an internal phishing...

5.9.4. Deploy and configure the Email Security
module 

5.9.4.1. Integrate Microsoft 365 with the Cortex
Advanced Email Security Module 

🔒

🟣c…

To configure a quick action, you must first
create an application in Microsoft O365.

🧭

➡️n…

After you onboard your domains and configure
the quick actions, Cortex XSIAM manage your
protected domains in Modules → Email
Security → Email Security Configuration

5.9.4.2. Configure the Cortex Advanced Email
Security module 

🔒

🟣c…

Requires the Advanced Email Security module.

📝

🟢note

You can add email indicators to the Allow List
also in Exceptions Configuration → Issue
Exclusions. However, if you add multiple
indicators in a rule using Issue Exclusions under
Exceptions Configuration, you cannot edit the
rule in the Email Security Allow List.

🧭

➡️n…

Modules → Email Security → Email Security
Configuration

5.9.5. Cortex Advanced Email Security threat
detection and issues 

📝

🟢note

Depending on data collection mode and
platform capabilities, not all fields may be
populated for every message. API and export
documentation provides further clarification on
optional vs required fields.

🧭 5.9.5.1. Email Security Analytics Rules 

➡️n…

The Email Security Analytics Rules page is in
Modules → Email Security → Email Security
Detection Rules

5.9.6. Investigate and respond to email security
issues 

🔒

🟣c…

Requires the Cortex Advanced Email Security
module.

🧭

➡️n…

Modules → Email Security → Email Security
Issues

5.9.7. Automate remediation for the Cortex

Advanced Email Security module 

📝

🟢note

For automated actions not yet supported by
the response engine, use the playbooks, scripts,
and commands in the Cortex XSIAM
automation engine. For more information, see
Automation in Cortex XSIAM.

🧭

➡️n…

Define the rules for your email security policy in
Email Remediation Response Rules, located in
Modules → Email Security → Remediation →
Rules

Review all the remediation actions initiated by
your policy in the Email Remediation Action
Center, located in Modules → Email Security →
Remediation → Action Center

5.9.7.1. Email Remediation Response Rules 

📝

🟢note

For automated actions not yet supported by
the response engine, use the playbooks, scripts,
and commands in the Cortex XSIAM
automation engine. For more information, see
Automation in Cortex XSIAM.

📝

🟢note

If you apply a new template, all the
customizations to the previous template you
used will be lost.

🧭

➡️n…

The Email Remediation Response Rules page is
under Modules → Email Security →
Remediation → Rules and displays the following
widgets and the Rules table

5.9.7.2. Email Security Remediation Action Center 

5.9.8. Email Command Center 

🔒

🟣c…

Requires the Cortex Advanced Email Security
module.

📝

🟢note

Adding more data into the Email Security
module will ensure better detection of
complicated email threat vectors.

📝

🟢note

The number of remediated emails and the
number of remediation actions may not always
be equal. This is due to a number of reasons,
including different policies that affect the email
messages or manual actions taken.

5.9.9. Advanced Email Security module security
and compliance 📝 
🟢note

For information about how Cortex handles
personal and private information, see the
Cortex Privacy Datasheet.

5.10. Exposure management 

🔒 5.10.1. Exposure Management 

🟣c…

Requires the Exposure Management add-on.

5.10.2. Get started with Exposure Management 

5.10.2.1. Exposure Management FedRAMP
support 

5.10.3. Exposure Management Command Center 

5.10.4. Security controls 

📝

🟢note

Security controls is currently in Beta and only
available to a select group of users. If this
feature is not yet visible in your console, please
contact your account representative to request
activation for your environment.

📝 5.10.4.1. Automatically detect security controls 

🟢note

Auto-detection of controls is supported when
certain constraints regarding topology and
configuration are met. Learn more about
Network Exposure Detection.

5.10.4.2. Manually attested security control
taxonomy 💡 
🔵tip

Take an inventory of your top 10-15 security
controls, check which ones need to be
manually added into the Cortex Platform and
use the taxonomy to map them into the system.

5.10.4.3. Establish security control roles 

📝

🟢note

Ensure that you have clear visibility into the
controls that are created and implemented, by
periodically reviewing the Audit Logs as part of
your change management process. Audit logs
track the following actions:
Create/Update/Delete Security Controls
Create/Update/Delete Effectiveness Rules
Update an Effectiveness Value in a findings or
issues

💡

🔵tip

Start with a centralized model. This helps a
core team master the new object models,
states, and taxonomies to prevent confusion
and ensure high-quality control creation.

🧭 5.10.4.4. Create a security control 

➡️n…

Vulnerability & Exposure Management →
Exposure Management → Security Controls
and select Create Security Control

🧭 5.10.4.5. Manage security controls 

➡️n…

Alternatively, you can also find Detected
Controls and Detected Controls Coverage on
the Vulnerability Issue (Posture Management →
Vulnerability Management → Vulnerability
Issues page

🧭 5.10.4.6. Set compensating controls 

➡️n…

Posture Management → Vulnerability
Management → Vulnerability Issues and sort
the vulnerabilities listed by their CVRS score or
Compensating Control Effectiveness

5.10.4.7. Improve controls coverage 

5.10.4.8. Create effectiveness rules 

📝

🟢note

Only users with the role Exposure Management
Administrator can create effectiveness rules.

💡

🔵tip

Use All, rather than selecting individual CVEs,
unless you explicitly only want to mark specific
CVEs as Effectively Mitigated.

5.10.4.9. Manage effectiveness rules 

5.10.5. Cortex Network Scanner 

5.10.5.1. Get started with Cortex Network

Scanner 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with an
active Cortex XSIAM NG SIEM and Cortex
XSIAM Enterprise license that has the Exposure
Management add-on.

☑️

🟣pr…

Review the Cortex Network Scanner
deployment recommendations and complete
any prerequisites.
Set up and configure Broker VM

📝

🟢note

The Cortex Network Scanner applet is not
supported in High Availability (HA) cluster
configurations.
The Cortex Network Scanner applet is not
supported for FedRAMP customers.

👀

🟠i…

The Cortex Network Scanner applet is not
supported for FedRAMP customers.
Cortex Network Scanner does not support high
availability (HA) Broker VM configuration.

🧭

➡️n…

Settings → Configurations → Network Scanners
→ Network Scanners and find your new scanner
in the list

🧭 5.10.5.2. Add a network 

➡️n…

Settings → Configurations → Network Scanning
→ Networks and click + Add Network

🧭 5.10.5.3. Define target groups 

➡️n…

Settings → Configurations → Network Scanning
→ Target Group Management

5.10.5.4. Manage credentials 

☑️

🟣pr…

Before initiating an authenticated scan,
complete the following prerequisites on your
target hosts:
Create dedicated service accounts.
We highly recommend creating dedicated
service accounts on your target devices
specifically for the network scanner. Avoid
using existing administrative accounts or
personal user accounts. This practice enhances...

📝

🟢note

For security reasons, you cannot edit saved
credentials, but you can delete them and
create new ones as needed.

🧭

➡️n…

Settings → Configurations → Network Scanners
→ Credential Management

Settings → Configurations → Network Scanning
→ Credential Management

5.10.5.5. Create a scan 

📝

🟢note

Be sure that scanner traffic is allowed from
each selected scanner to its selected targets.
See Deployment recommendations for more
information.

📝

🟢note

Be sure that scanner traffic is allowed from
each selected scanner to its selected targets.
See Deployment recommendations for more
information.

📝

🟢note

Be sure that scanner traffic is allowed from
each selected scanner to its selected targets.
See Deployment recommendations for more
information.

💡

🔵tip

Most use cases can use the default advanced
settings.

💡

🔵tip

Most use cases can use the default advanced
settings.

💡

🔵tip

Most use cases can use the default advanced
settings.

💡

🔵tip

ICMP Ping provides the quickest discovery scan
and is good for initial discovery and scoping,
however in the modern enterprise environment
ICMP response can be blocked by the firewall
or endpoint security rules. Using additional
methods increases the accuracy of the host
discovery, although makes the scan take a
longer time. The best approach is to use...

🧭 5.10.5.6. Manage scans 

➡️n…

Settings → Configurations → Network Scanners
→ Scan Management

5.10.5.7. View issues triggered by network
scanner findings 🧭 
➡️n…

Alternatively, you can also view issues triggered
by the Network Scanner from the Findings page,
Posture Management → Vulnerability
Management → Vulnerability Issues → All
Vulnerability Findings

Settings → Configurations → Network Scanners
→ Scan Management → Rescan History

5.10.6. Service Level Agreements (SLAs) for
issue resolution 

📝

🟢note

These filters support filtering of whole days
only, for example Resolution SLA > 1 filters for
issues that have a Resolution SLA of greater
than one day.

🧭

➡️n…

Settings → Configurations → Object Setup →
Issues

Settings → Configurations → Object Setup →
Issues and select the SLA Rules tab

6. Reference and developer docs 

6.1. Cortex XSIAM XQL 

6.1.1. Get started with XQL 

6.1.1.1. XQL language features 

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion commands and
definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc key.

🧭

➡️n…

You submit XQL queries to Cortex XSIAM using
the Investigation & Response → Search →
Query Builder user interface

6.1.1.2.1. Adding comments in queries  6.1.1.2. XQL Language Structure 

📝 6.1.1.3. Supported operators 

🟢note

In some cases, using an IN or NOT IN operator
combined with a dataset and filter stage can
be a better alternative to using a join stage.

6.1.1.4. Datasets and presets 

📝

🟢note

To set up this Cloud Identity Engine (previously
called Directory Sync Service (DSS)) dataset,
you need to set up a Cloud Identity Engine.
Otherwise, you will not have a pan_dss_raw
dataset. For more information, see Set up Cloud
Identity Engine.

📝

🟢note

INFO issues are not included in this dataset.
This dataset includes issues from the Security
and Health domains. For more information, see
Overview of the Issues page.

📝

🟢note

The fields contained in this dataset are a subset
of the fields in the xdr_data dataset.

📝

🟢note

If the vendor and product are not specified in
the Winlogbeat profile's configuration file,
Cortex XSIAM creates a default dataset called
microsoft_windows_raw.

📝

🟢note

To ensure GlobalProtect access authentication
logs are sent to Cortex XSIAM, verify that your
PANW firewall's Log Settings for GlobalProtect
has the Cortex Data Lake checkbox selected.

📝

🟢note

You must have the Cortex XSIAM Threat Intel
Management (TIM) Add-on to use this dataset.

📝

🟢note

You must have the Cortex XSIAM Threat Intel
Management (TIM) Add-on to use this dataset.

📝

🟢note

The fields contained in this dataset are a subset
of the fields in the xdr_data dataset.

📝

🟢note

Prisma Access firewalls do not send
configuration logs to the Structured Log
Storage (SLS).

📝

🟢note

You can query in XQL for this data and build
widgets based on the xdr_data dataset or using
the preset device_control.
To view in an XQL query these events, the
Device Configuration of the endpoint profile
must be set to Block. Otherwise, the USB events
are not captured. The events are also captured
when a group of device types are blocked on
the...

📝

🟢note

The fields contained in this dataset are a subset
of the fields in the xdr_data dataset.

👀

🟠i…

This dataset will not be updated after June
2024. Use the health_alerts dataset instead.

🧭 6.1.1.5. About examples 

➡️n…

Investigation & Response → Search → Query
Builder → XQL → Query Library

👀 6.1.1.6. JSON functions 

🟠i…

JSON field names are case sensitive, so the key
to field pairing must be identical in an XQL
query for results to be found. For example, if a
field value is "TIMESTAMP" and your query is
defined to look for "timestamp", no results will
be found.

6.1.1.7. How to filter for empty values in the
results table 

6.1.1.8. Understanding string manipulation in XQL 

6.1.2. Build XQL queries 

📝

🟢note

If you have the Cortex Agentic Assistant, you
can use natural language prompts to create
and run XQL queries within the chat interface.
For more information, see Create and run XQL
queries with Agentic Assistant chat.

6.1.2.1. About the Query Builder 

📝

🟢note

Schema changes to datasets may not be
reflected in the autocomplete suggestions and
definitions as you type in real time the XQL
query, and can appear with a slight delay.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion commands and
definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc key.

💡

🔵tip

If you prefer to use the Query Builder in Legacy
mode, switch the toggle in the header. In
Legacy mode, the Query Builder searches
predefined datasets only. To search the full
XDM Data Model, switch to New mode or
select XQL Search.

6.1.2.2. How to build XQL queries 

📝

🟢note

Users with different dataset permissions can
receive different results for the same XQL query.
An administrator or a user with a predefined
user role can create and view queries built with
an unknown dataset that currently does not
exist in Cortex XSIAM. All other users can only
create and view queries built with an existing
dataset.
When you have more...

📝

🟢note

You can build a query that investigates data in
both a cold dataset and a hot dataset in the
same query. In addition, as the hot storage
dataset format is the default option and
represents the fully searchable storage, this
format is used throughout this guide for
investigation and threat hunting. For more
information on hot and cold storage, see...

👀

🟠i…

Forensic datasets are not inlcuded by default in
XQL query results, unless the dataset query is
explicitly defined to use a forensic dataset.

💡 6.1.2.2.1. Get started with XQL queries 

🔵tip

If you are new to creating queries, you can also
try our simple search templates, which can help
you get started in understanding how queries
work. See Query Builder templates.Query
Builder templates

6.1.2.2.2. Useful XQL user interface features 

📝

🟢note

Schema changes to datasets may not be
reflected in the autocomplete suggestions and
definitions as you type in real time the XQL
query and can appear with a slight delay.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

6.1.2.2.3. XQL Query best practices 

6.1.2.2.4. Expected results when querying fields 

6.1.2.2.5. Create XQL query 

📝

🟢note

Whenever the time period is changed in the
query window, the config timeframe is
automatically set to the time period defined for
the entire query, including queries that are part
of the join stage. Yet, this won't be visible as
part of the query. Only if you manually type in
the config timeframe will this be seen in the
query.

These time picker...

📝

🟢note

While datamodel dataset=* is supported in the
query, we recommend that you specify specific
datasets for quicker and more efficient results.

📝

🟢note

Whenever the time period is changed in the
query window, the config timeframe is
automatically set to the time period defined for
the entire query, including queries that are part
of the join stage. Yet, this won't be visible as
part of the query. Only if you manually type in
the config timeframe will this be seen in the
query.

These time picker...

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

💡

🔵tip

While the query is running, you can navigate
away from the page. A notification is sent when
the query has finished. You can also Cancel the
query or run a new query, where you have the
option to Run only new query (cancel previous)
or Run both queries.

💡

🔵tip

When creating XQL queries, you can:
Use the up and down arrow keys to navigate
through the auto-suggestion command
suggestions and definitions.
Select an auto-suggestion command by
pressing either the Enter or Tab key.
Press Shift+Enter to add a new line, and easily
ignore the auto-suggestion output.
Close the auto-suggestion output by pressing
the Esc...

💡

🔵tip

While the query is running, you can navigate
away from the page. A notification is sent when
the query has finished. You can also Cancel the
query or run a new query, where you have the
option to Run only new query (cancel previous)
or Run both queries.

6.1.2.2.6. Review XQL query results 

📝

🟢note

It's also possible to graph the results displayed.
For more information, see Graph query results.

📝

🟢note

Real time query results are available only in the
Query Builder and in free text query.
Real time results are displayed only for queries
run on hot datasets.
The Sort option is available only after all the
data is retrieved.
When you formulate complex queries, the
results will be displayed when the query has
finished running completely, and not in real...

📝

🟢note

Results are received incrementally for the first
100K records, or up to 100MB worth of records,
whichever comes first. After that, the next
update is when the query has finished running
completely.

📝

🟢note

In order for Cortex XSIAM to provide a
histogram for a field, the field must not contain
an array or a JSON object.

👀 6.1.2.2.7. Translate to XQL 

🟠i…

This feature is still in a Beta state and you will
find that not all Splunk queries can be
converted to XQL. This feature will be improved
upon in the upcoming releases to support
greater Splunk query translations to XQL.

📝 6.1.2.2.8. Graph query results 

🟢note

To display the result of as a time duration,
choose the graph type Single Value and enable
Show as Time. You can then select the Time
Unit (millisecond, second, minute, or hour) and
the Display format.

6.1.2.3. Query Builder templates 

💡

🔵tip

To get started with queries, you can run an
empty template query with no values specified.
The query results will include all of the fields in
the template specific fieldset. Based on the
query results, you can run subsequent queries
to narrow down your search.

6.1.2.3.1. Get started with Query Builder
templates 

6.1.2.3.2. Considerations for using Query Builder
templates 

6.1.2.3.3. Create a query from a template 

📝

🟢note

Field names and aliases are listed without their
prefix, for example
xdm.SOURCE.USER.USERNAME is listed as
SOURCE.USER.USERNAME and XDM_ALIAS.ipv4
is listed as ipv4.
Fields that are already included in the query
template are shown as grayed out.
In the Identity and Network templates,
xdm.event.outcome shows as grayed out. In
these templates, the ACTION...

📝

🟢note

This order might change if you include a
filtering field that is listed in the fieldset. In that
case, the field is taken out of the fieldset and
ordered at the top of the list with the other
filtering fields.

6.1.2.3.4. Run a free text query 

📝

🟢note

Free-text search is also available in XQL
queries. You can use the search stage to query
free-text strings in specific datasets, or all of
the datasets in your tenant.

📝

🟢note

Free text search is limited to the last 90 days of
data. Specifying a time frame outside of this
limitation will cause the query to fail.

6.1.2.3.5. Query Builder template examples 

6.1.2.4. Overview of the Query Center 

📝

🟢note

Very short queries might not be listed.
You cannot cancel correlation queries.
The default retention period for historic queries
is aligned with issue retention.

6.1.2.4.1. Edit and run queries in Query Center 

📝

🟢note

If query limits are applied to your tenant, the
number of concurrent running queries is limited
per user. If query usage is reaching the defined
limit, a system message warns you that a high
query load is impacting performance. If you
exceed the limit, new queries are blocked until
query usage drops. You can view all active
queries under Query Center...

📝

🟢note

You can cancel your own queries. To cancel
queries run by other users, you must have
View/Edit permissions for Configurations →
Query Management. By default, Instance
administrators have View/Edit permission.

📝

🟢note

Cancelled queries show a Canceled status. You
can see details of all canceled queries in the
Query History tab.
You cannot cancel correlation rule queries.
If you cancel a scheduled query, only the
current query is cancelled. Future recurrences
of the scheduled query are not affected.

📝 6.1.2.4.1.1. Query Center reference information 

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

6.1.2.5. Manage scheduled queries 

6.1.2.5.1. Scheduled Queries reference

information 📝 
🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

6.1.2.6. Manage your personal query library 

6.1.2.7. Federated Search 

6.1.2.7.1. Federated Search 

📝

🟢note

Federated Search is not enabled by default. To
enable it in your tenant, please contact your
Customer Support Team.

📝

🟢note

Federated search query costs are calculated
according to timeframe, complexity, and any
cross-cloud egress costs that may apply.

📝

🟢note

For optimal results, we recommend the Parquet
format.

📝

🟢note

The list of supported regions may change in the
future.

6.1.2.7.2. Federated Search configuration 

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
An AWS bucket that contains your data sources.
Permissions to modify IAM policies in AWS.

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
A GCS bucket that contains your data sources.
Permissions to modify IAM policies in GCS.

☑️

🟣pr…

Access to Cortex XSIAM communication. For a
list of the authorized IP addresses, see Enable
access to required PANW resources.
An Azure Blob Storage blob with your data
sources.

Permissions to modify IAM policies in Azure
Blob Storage.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema. However, if the
auto-detected schema is incorrect, you can
add, edit or delete fields.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

You can only configure regions that are in the
multi-region of your tenant.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

Copy the Directory (tenant) ID, the Application
(client) ID, and the Object ID. You will use these
in the connection step.

📝

🟢note

You can only configure regions that are in the
multi-region of your tenant.

📝

🟢note

We highly recommend that you don't change
the auto-detected schema. However, you can
add, edit or delete fields.
You can't delete the ds field, which is used for
Hive partitioning.
After you save the schema, you can't delete
any fields you added during setup.

📝

🟢note

When you create, delete, or update an external
dataset, the action is recorded in the
Management Audit Logs under the type
External Datasets.

📝 6.1.2.7.3. Query using Federated Search 

🟢note

The following aren't available in Federated
Search and remain exclusive to fully ingested
data.
Complex, cross-source analytical functions, for
example correlations, widgets, dashboards, and
APIs
search, target and view XQL stages

📝 6.1.2.7.4. Manage external datasets 

🟢note

We highly recommend that you don't change
the auto-detected schema. However, in the Edit
window you can add new fields or delete the
new fields you added in the Edit window. You
can't delete the fields that were configured
during setup.

6.1.2.8. Legacy Query Builder 

📝

🟢note

We recommend using the Query Builder in New
mode to take advantage of the Query Builder
templates and the ability to search the full
Cortex Data Model (XDM).
In Legacy mode, the Query Builder searches
predefined datasets only. To search the full
XDM, switch to New mode or select XQL Search.

6.1.2.8.1. Create authentication query 

6.1.2.8.2. Create event log query 

6.1.2.8.3. Create file query 

6.1.2.8.4. Create image load query 

6.1.2.8.5. Create network connections query 

📝 6.1.2.8.6. Create network query 

🟢note

When you run the query, depending on the
outcome of the results, the value specified in
this field might be displayed in the dst_ip field
in the query results. This occurs if an RDP event
is recorded whereby a user connected from the
source IP to the destination IP.

6.1.2.8.7. Create process query 

👀 6.1.2.8.8. Create registry query 

🟠i…

Ensure the KEY NAME is entered as a real
registry key name, and not as a symbolic link.
Otherwise, the query will not retrieve results.
Instead of
HKEY_LOCAL_MACHINE\System\CurrentControl
Set, which is a symbolic link, use
KEY_LOCAL_MACHINE\System\ControlSet001.
Instead of HKEY_CURRENT_USER, use
HKEY_USERS\<SID>, where SID is either a SID of
the current...

6.1.2.8.9. Query across all entities 

6.1.3. Stages 

6.1.4. Functions 

6.2. Graph Search 

6.2.1. What is Graph Search? 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

6.2.2. Get started with Graph Search queries 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

🧭

➡️n…

Understand your assets and findings data:
Graph Search queries are based on the current
data that has been collected for assets and
findings from the data sources configured and
then sent to the Unified Asset Inventory (UAI),
which is displayed in the All Assets page
(Inventory → Assets → All Assets

6.2.3. How to build Graph Search queries? 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

🧭

➡️n…

You submit Graph Search queries using the
Investigation & Response → Search → Query
Builder → Graph Search built-in query interface

6.2.4. Understand Graph Search query results 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

6.2.5. Create Graph Search query 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

📝

🟢note

For more information about the Query Library,
see Manage the Graph Search Query Library.

💡

🔵tip

After running the query, you can view the
complete query by hovering over the last
THAT... in the Graph Search query interface, and
the query is displayed in a tooltip.
If your query doesn't find any results or you
want to change your query for any reason, you
can always click anywhere in the Graph Search
query interface, where your existing query is...

6.2.6. Graph Search examples 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

6.2.7. Manage the Graph Search Query Library 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

🧭

➡️n…

From Graph Search in the Query Builder Select
Investigation & Response → Search → Query
Builder → Graph Search

Investigation & Response → Search → Query
Builder → Graph Search

Investigation & Response → Search → Query
Center

6.2.8. Edit and run queries in Query Center 

📝

🟢note

If query limits are applied to your tenant, the
number of concurrent running queries is limited
per user. If query usage is reaching the defined
limit, a system message warns you that a high
query load is impacting performance. If you
exceed the limit, new queries are blocked until
query usage drops. You can view all active
queries under Query Center...

📝

🟢note

You can cancel your own queries. To cancel
queries run by other users, you must have
View/Edit permissions for Configurations →
Query Management. By default, Instance
administrators have View/Edit permission.

📝

🟢note

Cancelled queries show a Canceled status. You
can see details of all canceled queries in the
Query History tab.
You cannot cancel correlation rule queries.
If you cancel a scheduled query, only the
current query is cancelled. Future recurrences
of the scheduled query are not affected.

🧭

➡️n…

Investigation & Response → Search → Query
Center → Query History

📝 6.2.8.1. Query Center reference information 

🟢note

Certain fields are exposed and hidden by
default. An asterisk (*) is beside every field that
is exposed by default.

6.2.9. Supported assets and findings 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

6.2.10. FAQ on Graph Search 

🔒

🟣c…

This feature is included with a Cortex XSIAM
Premium license. It is also included with any
other Cortex XSIAM license that has the Cloud
Posture Security or Cloud Runtime Security
add-on.

☑️

🟣pr…

Graph Search requires View or View/Edit RBAC
permissions for Graph Search under
Investigation & Response → Search.

6.3. Cortex CLI 

📝

🟢note

The CLI Read Only Role is not supported for
CWP as the system does not support offline
mode.

6.3.1. Connect Cortex CLI 

☑️

🟣pr…

System requirements:
macOS (Intel Core i7, such as Sequoia): To
ensure all functionalities work correctly, you
must install the vectorscan dependency via
Homebrew, using this command: brew install
vectorscan

RHEL 8.10 and Red Hat UBI9. The following
prerequisites must be met:
Install patchelf
Install zstd
Ubuntu 20 requires the prefetch...

📝

🟢note

The Cortex CLI requires an API key with the
Standard security level.

📝

🟢note

On macOS arm 64 architecture you must
unpack the downloaded file to retrieve the
executable.

📝

🟢note

To add an additional CLI instance, navigate to
Settings → Data Sources → select the menu
for your connected CLI instance → + New
Instance, and repeat the onboarding steps.

📝

🟢note

For more information about CLI usage for CWP,
refer to Cortex CLI for Cloud Workload
Protection

For more information about CLI usage for API
Security, refer to Cortex CLI for API Security
For more information about CLI usage for
Application Security, refer to Cortex CLI usage
for Application Security

6.3.2. Self-service API keys for CLI scans 

6.3.3. Cortex CLI common command line

reference guide 📝 
🟢note

For soft fails, a failed check matches the
defined severity threshold. If multiple soft fail
severities are specified, the highest severity acts
as the threshold for determining a soft fail.
However, a successful scan will always return
an exit code of 0, even if block-level findings
(which might trigger soft fails based on
severity) are present.

6.3.4. Cortex CLI for API Security 

☑️

🟣pr…

Ensure you have the required user permissions.
Refer to Cortex CLI for more information
Onboard and install the Cortex CLI. Refer to
Connect Cortex CLI for more information
Ensure your application exposes APIs and
provides a corresponding OpenAPI
Specification file
Ensure that you have installed Java v 11 and
above

6.3.4.1. Cortex CLI API Security command line
reference guide 

6.3.5. Cortex CLI for Cloud Workload Protection 

☑️

🟣pr…

Ensure you have the required user permissions.
Refer to Cortex CLI for more information
Onboard and install the Cortex CLI. Refer to
Connect Cortex CLI for more information
Verify that Java version 11 and above is
installed: Run java -version in your terminal. If
not, refer to Java SE Development Kit 11.0.25 for
information about installing Java

☑️

🟣pr…

Before you begin, ensure you have sudo
privileges to execute the image scan.

📝

🟢note

CWP does not support container image secret
scanning for systems running on ARM
architecture.

📝

🟢note

For available CWP commands, refer to Cloud
Workload Protection command line reference.

📝

🟢note

--archive: When used with image scan, sets the
scan source to an archive file. When used with
image sbom, indicates the SBOM should be
exported from an archive file
The --archive flag can also be explicitly set as -
-archive=true
--archive-format <value>: The image archive
format (such as docker-archive or oci-archive).
Default: docker-archive.

6.3.5.1. Cloud Workload Protection command
line reference



6.3.6. Cortex CLI for Code Security 

☑️

🟣pr…

For the Cortex CLI binary:
Ensure you have Node.js v22 installed on your
host machine before running any scans with the
Cortex CLI. This is crucial to prevent runtime
errors, as the CLI depends on Node.js for
executing JavaScript analysis
Note

To check your version of Node.js, run node -v
To download Node.js, refer to the official
Node.js...

6.3.6.1. Cortex CLI usage for Application
Security 

6.3.6.2. Cortex CLI Application Security
command line reference



📝

🟢note

The repo-id flag must not end with .config, .log
or .ini. -config is acceptable.
--repo-id foo.config will be blocked
--repo-id foo-config will pass

👀

🟠i…

The Cortex CLI Application Security only
supports single occurrences of each flag. If the
same flag is passed multiple times, only the last
provided value will be used. For example, in the
following command, only TF CloudFormation
will be the scanned framework.
./cortexcli --api-base-url <YOUR_API_URL> --
api-key <YOUR_API_KEY> --auth-id
<YOUR_AUTH_ID>...

6.4. Cortex XSIAM 3.x Documentation 

6.5. Reference 

6.5.1. Cloud service provider permissions 

6.5.2. Microsoft Windows security auditing setup 

6.5.2.1. Enable security auditing event IDs 

📝

🟢note

We recommend you configure security auditing
using Group Policy Object (GPO). Using GPO
simplifies audit management and ensures that
auditing settings are uniformly applied across
your network, reducing the risk of
misconfigurations on individual machines.

6.5.2.1.1. Enable security auditing event IDs with
GPO 

📝

🟢note

We recommend that you configure the Group
Policy Object (GPO) to apply to all endpoints
and not just Domain Controllers. This ensures
comprehensive auditing across your entire
network.

🧭

➡️n…

Server Manager → Tools → Group Policy
Management

Computer Configuration → Policies →
Windows Settings → Security Settings →
Advanced Audit Policy Configuration → Audit
Policies

6.5.2.1.2. Set up local machine security auditing
without GPO 

6.5.2.1.3. Additional setup for Active Directory
Certificate Services (ADCS) events 📝 
🟢note

Enabling auditing for Active Directory
Certificate Services (ADCS) restarts (events
4880 and 4881) can significantly slow down the
service if you have a large database. To prevent
delays:
Clean up the database: Remove any
unnecessary entries to reduce its size.
Skip this audit: If restart speed is critical,
consider not enabling auditing for ADCS...

6.5.2.1.4. Enable auditing access to AD domain
objects - 4662 📝 
🟢note

The Descendant msDS-
DelegatedManagedServiceAccount Objects
configuration is relevant only for Windows
Server 2025.

6.5.2.2. Enable additional event logs using Event
Viewer 🧭 
➡️n…

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows → User
Profile Service, right click Operational and
select Enable Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows →
CAPI2, right click Operational and select Enable
Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows → DNS
Client Events, right click Operational and select
Enable Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows →
DriverFrameworks-UserMode, right click
Operational and select Enable Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows →
PowerShell, right click Operational and select
Enable Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows →
Windows Defender, right click Operational and
select Enable Log

In Event viewer → Application and Services
Logs → Microsoft → Windows →
TerminalServices-ClientActiveXCore →
Microsoft-Windows-TerminalServices-
RDPClient, right click Operational and select
Enable Log

In Event Viewer → Expand Applications and
Services Logs → Microsoft → Windows →
Windows Firewall With Advanced Security →
Firewall, right click Operational and select
Enable Log

6.5.2.3. Enable LDAP server events logging (1644) 

6.5.2.3.1. Enable LDAP server events logging
using RegEdit 

6.5.2.3.2. Enable LDAP server events logging
using GPO 🧭 
➡️n…

Computer Configuration → Preferences →
Windows Settings → Registry

6.5.2.3.3. Validate log collection for LDAP Server
events 

6.5.3. XDM fields for mapping authentication
events 

📝

🟢note

For more information on the entire Cortex Data
model (XDM) schema, see Cortex XSIAM Data
Model Schema.

📝

🟢note

Do not map a static string, list, or empty string.
You must map this field from the raw log field
that best represents the actual source IP used
in the authentication attempt. In cases where
multiple IP fields are available, such as client_ip,
source_ip, and original_client_ip, choose the
field that captures the IP address from which
the user initially...

📝

🟢note

Mapping should be done per event type. The
same system could be an IDP in one event and
an SP in another.

📝

🟢note

For more information on the event outcome
constants in the Cortex Data Model, see
XDM_CONST.OUTCOME.

📝

🟢note

Outcome is based on a conclusive event type
reflecting the true end state of the
authentication flow.Critical for effectiveness of
detection rules. Incorrect derivation can lead to
missed detections or false positives.

📝

🟢note

These are the most common values, but other
logon types also exist. For a complete list, see
XDM_CONST.LOGON_TYPE.

📝

🟢note

For more information, see
XDM_CONST.USER_TYPE.

📝

🟢note

For more information, see
XDM_CONST.PRIVILEGE_LEVEL.

📝

🟢note

For more information, see
XDM_CONST.OS_FAMILY.

📝

🟢note

While xdm.network.session_id aggregates
multiple user actions within a broader session
window. xdm.session.context.id is used to
correlate events that belong to a single
authentication request or transaction.

6.5.4. Cortex Network Scanner OSS 

6.5.5. Fair Usage policy for Cortex XSIAM 