

Data Structures

Recursive Programming

Repeating a Code Segment

- There are two basic methods for repeating a code segment:
 - Loops (do-while, while, for, ...)
 - Recursion
- Recursion:**
 - A function calling itself
 - Simplifies code writing for the solutions of some types of problems.
 - Is an important advanced programmed technique and shortens the code when used appropriately.
 - Downside: The program may take longer to run.

2

ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Recursive Programming

- The basic approach is to define the problem to be solved in terms of simpler subproblems.
- The recursive function can solve the base case and returns the result if there is one.
- If the input problem is not the base case, the problem can be divided into simple parts, and the function calls itself for each part.
- Since recursive program writing is different from the usual style, it takes more practice to learn.

3

ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Example: Computing the Factorial

Definition of the factorial function:

$$n! = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot (n-1) \cdot (n-2) \cdot \dots \cdot 3 \cdot 2 \cdot 1 & \text{if } n \geq 1 \end{cases}$$

$$n! = n \cdot (n-1) \cdot \dots \cdot 3 \cdot 2 \cdot 1$$

$$5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1$$

We could also define the function in terms of itself:

Example: $\text{fact}(5) = 5 \cdot (4 \cdot 3 \cdot 2 \cdot 1) = 5 \cdot \text{fact}(4)$

$$f(n) = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot f(n-1) & \text{else} \end{cases}$$

4

ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Factorial Function

```
int recursiveFactorial(int n){
    int m;
    if (n == 0) return 1; // base case
    else{                // recursion step
        m = recursiveFactorial(n-1);
        return m * recursiveFactorial(n-1);
    }
}
```


Note!

The base case is, at the same time, the termination condition of the function and should not be left out. Otherwise, there will be "infinite" recursion (analogous to the problem of an infinite loop in an iterative solution).

5

ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Exercise



6

ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Is Recursion Always Useful?

- Let us write the same function iteratively:

```
int iterativeFactorial(int n){
    int i,p;
    p=1;
    for(i=2; i<=n; i++)
        p*=i;
    return p;
}
```

- This solution wastes less space in memory and works faster.

7

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

Recursion Types

- Linear**
 - Each time a function (method) is called, it makes at most one recursive call.
- Tail**
 - If there is linear recursion and the last command of the function is a recursive call, tail recursion occurs.
 - These types of methods can be converted from the recursive state to the iterative state.
- Binary**
 - If the function calls itself twice at a time, there is binary recursion.

8

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

Binary Recursion Example

Let us write the function that sums elements of an array.

Algorithm:

BinarySum(A, i, n)

Input: array A, integers i and n

Output: sum of n numbers in array A starting with index i


```
if n = 1 then
    return A[i]
else
    return BinarySum(A, i, ceil(n/2))
           + BinarySum(A, i+ceil(n/2), n-ceil(n/2))
```



9

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

BinarySum() Call Sequence



- Binary recursion is generally used in algorithms designed with the "divide and conquer" method.
- In these types of algorithms, recursion may prove more effective than an iterative solution.

10

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

Calculating the Square of an Integer

- The square of the number x will be calculated using only addition, subtraction, and left shift (multiplication by 2) operations.
- In integer multiplication operations, instead of the much slower direct low-level multiplication command, compilers use addition/subtraction and right/left shift low-level commands.

Solution:

$$\begin{aligned} x^2 &= (x - 1 + 1)^2 \\ &= (x - 1)^2 + 2(x - 1) + 1^2 \\ &= (x - 1)^2 + 2x - 1 \end{aligned}$$

11

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

Squaring an Integer

```
unsigned int square(unsigned int x){
    if (x <= 1)
        return 1;
    else
        return square(x - 1) + (x << 1) - 1;
}
```

12

ITÜ, BL.G221E Data Structures, G. Eryigit, S. Kabadaşlı © 2011

Permutation

- Example: permutations of the set {1,2,3} :
 1 2 3 1 3 2
 2 1 3 2 3 1
 3 1 2 3 2 1
- To generate these permutations, we could use the code below:

```
for (i1 = 1; i1 <= 3; i1++)
  for (i2 = 1; i2 <= 3; i2++)
    if (i2 != i1)
      for (i3 = 1; i3 <= 3; i3++)
        if ((i3 != i1) && (i3 != i2))
          cout << i1 << " " << i2 << " " << i3 << endl;
```

- However, this code can only generate ternary (3-ary) permutations. How do we generate n-ary permutations?

13 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Recursive Solution for Permutation

```
void perm(int *list, int k, int m){
  int i;
  if (k == m){
    for (i = 0; i <= m; i++)
      cout << list[i] << " ";
    cout << endl;
  }
  else
    for (i = k; i <= m; i++){
      swap(&list[k], &list[i]);
      perm(list, k+1, m);
      swap(&list[k], &list[i]);
    }
}
```

list[0..x] -> an array holding the data that can be printed to the screen
 k: starting index
 m: ending index
 First call: perm(list,0,x)

```
void swap(int *a, int *b){
  int temp = *a;
  *a = *b;
  *b = temp;
}
```

14 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Recursive Solution for Permutation

- At each step, a position is held constant and the others are permuted. For example, when writing the permutation of (1 2 3 4), these numbers are placed into the first position in order and the remaining three positions are written as a permutation.

- 1 ... permutations that start with 1
- 2 permutations that start with 2
- 3 ...
- 4 ...

Thus, the problem is divided into subproblems.

15 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Recursive Solution for Permutation

```
for (i = k; i <= m; i++){
  swap(list[k], list[i]);
  perm(list, k+1, m);
  swap(list[k], list[i]);
}
```

k=1, m=3
 1 2 3

First, hold the 1st position constant. Write the permutation of the rest (We do not worry about how to do this for now) next to it.

```
>> 1 2 3
>> 1 3 2
```

Then, swap the number in the 1st position with the number in the 2nd position.


```
2 1 3
```

Now, again holding the first position constant, write the permutation of the rest next to it.

```
>> 2 1 3
>> 2 3 1
Reverse the swap operation
1 2 3
```

16 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Recursive Solution for Permutation



Eight Queens Problem

- A classical problem
- Goal:** Place 8 queens on a 8X8 chessboard such that they cannot attack each other
- Two queens cannot be located on the
 - Same row
 - Same column
 - Same diagonal
- A solution for a 5X5 board is shown on the right.
 - At the top of every column, number of the row where queen is located is shown.

5	3	1	4	2
		q		
				q
	q			
			q	
q				

18 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Solution to the Eight Queens Problem

- The problem has more than one solution.
- Since only one queen may be located on a row, the potential solutions may be found by generating permutations of the row numbers shown on the example board.
 - All permutations may not be solutions.
 - However, all solutions are among these permutations.

4	1	3	5	2
	q			
				q
		q		
q				
			q	

19 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011


Solution to the Eight Queens Problem

- A permutation generator with the addition of "diagonal attack" checks could be used to solve the **n queens problem**.

20 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Towers of Hanoi


- The Towers of Hanoi problem can easily be solved using recursion.



21 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Hanoi Iterative Solution (reminder)

- As long as the move stack is full, we pop a move (n,source,destination) from this stack, and push these moves onto the stack:
 - (n-1, temp, destination)
 - (1, source, destination)
 - (n-1, source, temp) (what has to be done first is at the top of the stack)



22 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Hanoi Recursive Solution

```
void Hanoi_recursive(int n, int source, int destination, int temp){
    if(n>=1){
        Hanoi_recursive(n-1,source,temp,destination);
        s[destination].push(s[source].pop());
        Hanoi_recursive(n-1,temp,destination,source);
    }
}
```

Hanoi_recursive(5,0,2,1);

23 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Finding a Path in a Labyrinth

The path finding in a labyrinth problem, which we had previously solved using a stack, could also be solved by writing a recursive function.


```
int main(){
    char lab[8][8]={{'x','x','x','x','x','x','x','x'},
                    {' ',' ','x','x','x','x',' ','x'},
                    {'x',' ','x','x','x','x',' ','x'},
                    {'x',' ',' ',' ',' ',' ',' ','x'},
                    {'x',' ','x',' ','x','x',' ','x'},
                    {'x',' ','x','x','x',' ','x','x'},
                    {'x',' ','x','x','x','x','x','x'},
                    {'x','x','x','x','x','x','x','x'}};

    if(find_path(lab,entrance.y,entrance.x, LEFT))
        cout<<"PATH found"<<endl;

    printlab(lab);
    return EXIT_SUCCESS;
}
```

24 ITÜ, BLG221E Data Structures, G. Eryigit, S. Kabadayi © 2011

Finding a Path in a Labyrinth



25

İTÜ, BLG221E Data Structures, G. Eryigit, S. Kabadaş © 2011


Recursive Path Finding Function

```
bool find_path(char lab[8][8], int y, int x, int camefrom){
    lab[y][x]='o';
    if(x==exit.x && y==exit.y)
        return true;
    printlab(lab);
    if(x>0 && lab[y][x-1]!='x' && camefrom!=LEFT)
        if(find_path(lab,y,x-1,RIGHT)) //left
            return true;
    if(y<7 && lab[y+1][x]!='x' && camefrom!=DOWN)
        if(find_path(lab,y+1,x,UP)) //down
            return true;
    if(y>0 && lab[y-1][x]!='x' && camefrom!=UP)
        if(find_path(lab,y-1,x,DOWN)) //up
            return true;
    if(x<7 && lab[y][x+1]!='x' && camefrom!=RIGHT)
        if(find_path(lab,y,x+1,LEFT)) //right
            return true;
    lab[y][x]='x'; //incorrect paths deleted
    printlab(lab); //the return path is also viewed
    return false;
}
```

26

İTÜ, BLG221E Data Structures, G. Eryigit, S. Kabadaş © 2011


Finding a Path in a Labyrinth



27

İTÜ, BLG221E Data Structures, G. Eryigit, S. Kabadaş © 2011

Finding a Path in a Labyrinth



28

İTÜ, BLG221E Data Structures, G. Eryigit, S. Kabadaş © 2011

In Recitation: To do

Fibonacci Numbers
Minmax