


MAT 202E - NUMERICAL
METHOD
CRN: 20964
INSTRUCTOR: BERK CANBERK

HOMEWORK-1
DATE: 15.04.2013

TUĞRUL YATAĞAN
040100117


1) With %0.01 relative error finishing condition, these are the plot of relative errors of each method using initial conditions:

Bisection method




Iteration number for Bisection method is 14.

Secant method



Iteration number for Secant method is 7.

Newton-Raphson method



Iteration number for Newton-Raphson method is 6.

According to these plots Newton-Raphson method is the fastest algorithm for this equation.

Matlab codes for these scripts are under the Q1 folder that are bisection.m , secant.m , newtonraphson.m

Scripts executes without input or output parameters.


Example output:

```
>> secant
```


```
Root x for Secant Method = -2.0001 with relative error = 0.0072237
```

2) $f(x) = \sin(x)$ between $[0, 2\pi]$

Lagrange interpolation



Newton's Divided Difference interpolation



Matlab codes for these scripts are under the Q2 folder that are lagrange.m , newton.m


Example output:

```
>> newton
SamplePoints =
Columns 1 through 6
    0    0.3307    0.6614    0.9921    1.3228    1.6535
Columns 7 through 12
    1.9842    2.3149    2.6456    2.9762    3.3069    3.6376
Columns 13 through 18
    3.9683    4.2990    4.6297    4.9604    5.2911    5.6218
Columns 19 through 20
    5.9525    6.2832
Enter X coordinate for interpolation: 0.3307
p(x) points are = 0.3247    0.32471    0.32471    0.32471
```

Program waits for user input for interpolation point. If we choose common point the results will be the same. [2,9,17] members of array (which keeps our sample points) are common in this example.

3)

Number Of Sample And Mean Distance



Matlab codes for this script and function are under the Q3 folder that are meandistance.m , randdistance.m

Main script for this script is meandistance.m, randdistance.m is assistant function. randdistance.m generates random two points and returns their distance between them to the main script.

Example output:

```
>> meandistance  
Enter n iteration number(ex:1000): 1000
```

meandistance.m waits for user input for iteration number.

Approximate mean value of distance converges to 0.9 when large amount of sample calculation.