

Computer Operating Systems, Practice Session 4

Threads

Mustafa Ersen (ersenm@itu.edu.tr)

Istanbul Technical University
34469 Maslak, İstanbul

05 March 2014

Today

Computer Operating Systems, PS 4

Thread Creation and Termination

Joining Threads

Using Global Variables in Threads

Thread Creation

```
#include <pthread.h>
```

```
int pthread_create(pthread_t *thread, const pthread_attr_t *attr, void  
*(*start_routine)(void*), void *arg);
```

pthread_t *thread	: Pointer to the thread to be created
const pthread_attr_t *attr	: Pointer to attributes of the thread to be created
void *(*start_routine)(void*)	: Pointer to the routine that will start the thread
void *arg	: Pointer to the arguments for the start routine

Example Program 1

```
1 #include <pthread.h>
2 #include <stdio.h>
3 #include <stdlib.h>
4
5 void* print_message_function(void *ptr){
6     char *message;
7     // interpreting as char *
8     message = (char *) ptr;
9     printf("\n %s \n", message);
10    // terminating the thread
11    pthread_exit(NULL);
12 }
13
```

Example Program 1

```
14 int main(){
15     pthread_t thread1, thread2, thread3;
16     char *message1 = "Hello";
17     char *message2 = "World";
18     char *message3 = "!...";
19     // creating 3 threads using print_message_function as the start routine
20     // and message1, message2 and message3 as the arguments for the start routine
21     if(pthread_create(&thread1,NULL,print_message_function,(void *)message1)){
22         fprintf(stderr,"pthread_create failure\n");
23         exit(-1);
24     }
25     if(pthread_create(&thread2,NULL,print_message_function,(void *)message2)){
26         fprintf(stderr,"pthread_create failure\n");
27         exit(-1);
28     }
29     if(pthread_create(&thread3,NULL,print_message_function,(void *)message3)){
30         fprintf(stderr,"pthread_create failure\n");
31         exit(-1);
32     }
33     // to block main to support the threads it created until they terminate
34     pthread_exit(NULL);
35 }
```

Compiling a Program Including Thread/s

- ▶ Source File: `source.c`
- ▶ Executable File: `output`
- ▶ These applications should be linked with thread library. Sample, proper compilation:
`gcc -pthread source.c -o output`

Output of the Example Program 1

```
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ gcc -pthread  
Example1.c -o output  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ ./output  
  
!...  
  
World  
  
Hello  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ █
```

Example Program 2

```
1 #include <pthread.h>
2 #include <stdio.h>
3 #include <stdlib.h>
4 #include <math.h>
5 #define NUM_THREADS 4
6
7 void *BusyWork(void *t){
8     int i;
9     long tid;
10    double result=0.0;
11    tid = (long)t;
12    printf("Thread %ld starting...\n", tid);
13    for (i=0; i<1000000; i++){
14        result = result + sin(i) * tan(i);
15    }
16    printf("Thread %ld done. Result = %e\n", tid, result);
17    pthread_exit((void*) t);
18 }
19
```

Barney B. (2013). POSIX Threads Programming. Retrieved March 03, 2014, from <https://computing.lln.gov/tutorials/pthreads/>

Example Program 2

```
20 int main (int argc, char *argv[]){
21     pthread_t thread[NUM_THREADS];
22     pthread_attr_t attr;
23     int rc;
24     long t;
25     void *status;
26     // Initialize and set thread detach state attribute
27     // Only threads that are created as joinable can be joined
28     // If a thread is created as detached(PTHREAD_CREATE_DETACHED), it cannot be joined
29     pthread_attr_init(&attr);
30     pthread_attr_setdetachstate(&attr, PTHREAD_CREATE_JOINABLE);
31     for(t=0; t<NUM_THREADS; t++) {
32         printf("Main: creating thread %ld\n", t);
33         // creating thread t
34         rc = pthread_create(&thread[t], &attr, BusyWork, (void *)t);
35         if (rc) {
36             printf("ERROR; return code from pthread_create() is %d\n", rc);
37             exit(-1);
38         }
39     }
```

Example Program 2

```
40 // Free library resources used by the attribute
41 pthread_attr_destroy(&attr);
42 // Join operation is used for synchronization between threads by blocking the
43 // calling thread until the specified thread (with given threadid) terminates
44 for(t=0; t<NUM_THREADS; t++) {
45     rc = pthread_join(thread[t], &status);
46     if (rc) {
47         printf("ERROR; return code from pthread_join() is %d\n", rc);
48         exit(-1);
49     }
50     printf("Main: completed join with thread %ld having a status of %ld\n",t,(long)status);
51 }
52 printf("Main: program completed. Exiting.\n");
53 // to block main to support the threads it created until they terminate
54 pthread_exit(NULL);
55 }
```

Output of the Example Program 2

```
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ gcc -pthread  
Example2.c -lm -o output  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ ./output  
Main: creating thread 0  
Main: creating thread 1  
Main: creating thread 2  
Main: creating thread 3  
Thread 3 starting...  
Thread 2 starting...  
Thread 1 starting...  
Thread 0 starting...  
Thread 2 done. Result = -3.153838e+06  
Thread 0 done. Result = -3.153838e+06  
Main: completed join with thread 0 having a status of 0  
Thread 3 done. Result = -3.153838e+06  
Thread 1 done. Result = -3.153838e+06  
Main: completed join with thread 1 having a status of 1  
Main: completed join with thread 2 having a status of 2  
Main: completed join with thread 3 having a status of 3  
Main: program completed. Exiting.  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ █
```

Example Program 3

```
1 #include <pthread.h>
2 #include <stdlib.h>
3 #include <stdio.h>
4
5 int myglobal;
6
7 void* thread_function(void *arg){
8     int i,j;
9     // changing the value of myglobal in thread_function
10    for(i=0;i<20;i++){
11        //myglobal++;
12        j=myglobal;
13        j=j+1;
14        myglobal=j;
15        printf(".");
16        // to force writing all user-space buffered data to stdout
17        fflush(stdout);
18        sleep(1);
19    }
20    pthread_exit(NULL);
21 }
22
```

Example Program 3

```
23 int main(void){
24     pthread_t mythread;
25     int i;
26     myglobal=0;
27     // creating a thread using thread_function as the start routine
28     if(pthread_create(&mythread,NULL,thread_function,NULL)){
29         printf("error creating thread");
30         abort();
31     }
32     // changing the value of myglobal in main()
33     for(i=0;i<20;i++){
34         myglobal = myglobal+1;
35         printf("o");
36         // to force writing all user-space buffered data to stdout
37         fflush(stdout);
38         sleep(1);
39     }
40     printf("\nmyglobal equals %d\n",myglobal);
41     // to block main to support the threads it created until they terminate
42     pthread_exit(NULL);
43 }
```

Output of the Example Program 3

```
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ gcc -pthread  
Example3.c -o output  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ ./output  
0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.  
myglobal equals 40  
musty@musty-VirtualBox:/media/sf_virtualbox_shared_folder$ █
```