

Agenda



- 1. Project Management Concepts
- 2. Estimation
- 3. Process Metrics
- 4. Planning and Scheduling

Project Management - 1

1. Project Management Concepts 2. Estimation
3. Process Metrics
4. Planning and Scheduling

Project Management Concepts

80 4.1 63

Software Project Management



- Concerned with activities involved in ensuring that software is delivered on time and on schedule and in accordance with the requirements of the organisations developing and procuring the software.
- Project management is needed because software development is always subject to budget and schedule constraints that are set by the organisation developing the software.

Success Criteria

- Deliver the software to the customer at the agreed time.
- $_{\mbox{\scriptsize 50}}$ Deliver software that meets the customer's expectations.
- Maintain a happy and well-functioning development team.

1.4

4P's



People
 the most important
 element of a successful
 project

t Property of the second secon

3. Process the set of framework activities and software engineering tasks to get the job done



2. Product the software to be built

4. Project
all work required to
make the product a
reality

ect Management - 1 1

Stakeholders



- so Senior managers who define the business issues that often have significant influence on the project.
- Project (technical) managers who must plan, motivate, organize, and control the practitioners who do software work.
- Practitioners who deliver the technical skills that are necessary to engineer a product or application.
- Customers who specify the requirements for the software to be engineered and other stakeholders who have a peripheral interest in the outcome.
- End-users who interact with the software once it is released for production use.

Project Management - 1

Software Teams



- 50 The following factors must be considered when selecting a software project team structure
 - o the difficulty of the problem to be solved
 - o the size of the resultant program(s) in lines of code or function points
 - o the time that the team will stay together (team lifetime)
 - o the degree to which the problem can be modularized
 - $_{\circ}\;$ the required quality and reliability of the system to be built
 - o the rigidity of the delivery date
 - the degree of sociability (communication) required for the project

Avoid Team "Toxicity"



- A frenzied work atmosphere in which team members waste energy and lose focus on the objectives of the work to be performed.
- High frustration caused by personal, business, or technological factors that cause friction among team members.
- "Fragmented or poorly coordinated procedures" or a poorly defined or improperly chosen process model that becomes a roadblock to accomplishment.
- Unclear definition of roles resulting in a lack of accountability and resultant finger-pointing.
- "Continuous and repeated exposure to failure" that leads to a loss of confidence and a lowering of morale.

ect Management - 1

Project Management - 1

1 8

Team Organizations



- Small software engineering groups are usually organised informally without a rigid structure.
- For large projects, there may be a hierarchical structure where different groups are responsible for different sub-projects.
 - Decentralized-control team
 - Centralized-control team
 - Mixed-control team

Decentralized-Control Team



- Decisions are made thru consensus
- Review each other's work
- ∞ Suitable for long-term projects
- not suitable for large teams
- Decentralized control is best when communication among engineers is necessary

Centralized-Control Team



- Chief programmer is responsible for the design and all the technical details of the project
- 50 The chief programmer may be overloaded
- Centralized control is best when the speed of development is the most important goal and the problem is well understood

Mixed-Control Team



- n Hierarchical team
- so Combination of centralized and decentralized teams
- so Attempts to have advantages of both

Project Management -

Example Team Organization Project Manager Business Analyst Tech Lead Programmers Database Analyst Designer Testers

Agile Teams



- 50 Team members must have trust in one another.
- The distribution of skills must be appropriate to the problem.
- Mavericks may have to be excluded from the team, if team cohesiveness is to be maintained.
- nam is "self-organizing"
 - An adaptive team structure
 - Uses elements of Constantine's random, open, and synchronous paradigms
 - Significant autonomy

1.1/

The Project



- Projects get into trouble when ...
 - Software people don't understand their customer's needs.
 - o The product scope is poorly defined.
 - Changes are managed poorly.
 - The chosen technology changes.
 - o Business needs change [or are ill-defined].
 - Deadlines are unrealistic.
 - Users are resistant.
 - Sponsorship is lost [or was never properly obtained].
 - The project team lacks people with appropriate skills.
 - Managers [and practitioners] avoid best practices and lessons learned.

Common-Sense Approach to Projects



- Start on the right foot. This is accomplished by working hard (very hard) to understand the problem that is to be solved and then setting realistic objectives and expectations.
- Maintain momentum. The project manager must provide incentives to keep turnover of personnel to an absolute minimum, the team should emphasize quality in every task it performs, and senior management should do everything possible to stay out of the team's way.
- Track progress. For a software project, progress is tracked as work products (e.g., models, source code, sets of test cases) are produced and approved (using formal technical reviews) as part of a quality assurance activity.
- Make smart decisions. In essence, the decisions of the project manager and the software team should be to "keep it simple."
- Conduct a postmortem analysis. Establish a consistent mechanism for extracting lessons learned for each project.

1.15

Project Management - 1

1.16

Critical Practices



- 50 Formal risk management
- so Empirical cost and schedule estimation
- Metrics-based project management
- Defect tracking against quality targets
- po People aware project management

Project Management Concepts
 Estimation

Process Metrics

4. Planning and Scheduling

Estimation

80 4.2 C3

Project Management

ect Management - 1 1

Estimation



- po Organizations need to make software effort and cost estimates.
- Estimation of resources, cost, and schedule for a software engineering effort requires
 - experience
 - o access to good historical information (metrics
 - the courage to commit to quantitative predictions when qualitative information is all that exists
- so Estimation carries inherent risk and this risk leads to uncertainty.
- 50 There is no simple way to make an accurate estimate of the effort required to develop a software system.
- Initial estimates are usually based on inadequate information about user requirements.

anagement - 1

Coding Testing Analysis and Design

30-40%

15-20%

Management - 1


1.20

Typical Effort Distribution

Analysis and Design 40-50%








21

Estimating the uncertainty!



Estimation Techniques



- Estimation by analogy
 The cost of a new project is estimated by analogy with similar completed projects.
- Expert judgement Several experts on the proposed software application domain are consulted. They each estimate the project cost. The estimation process iterates until an agreed estimate is reached.
- Algorithmic cost modelling
 A model based on historical cost Information that relates some software metric (usually its size) to the project cost is used. COCOMO is an example of algorithmic cost modelling.
- Parkinson's Law
 Parkinson's Law states that work expands to fill the time available. The cost is determined by available resources rather than by objective assessment.
- 5. Pricing to win
 The estimated effort depends on the customer's budget and not on the software functionality.

ect Management - 1 1.

Algorithmic Cost Modelling



- Cost (i.e. Effort) is estimated as a mathematical function of product, project and process attributes whose values are estimated by project managers:
 - Effort = A * (Size)E * EAF

where

- A is an organisation-dependent constant,
- E reflects the disproportionate effort for large projects,
- EAF (Effort Adjustment Factor) is a multiplier reflecting product, process and people attributes.
- The most commonly used product attribute for cost estimation is <u>code</u> <u>size</u>.
- Most models are similar but they use different values for A, E and EAF.

Project Management - 1

Function Points



- 50 Function Point is a measurement estimation method for a software from the <u>functionality perspective</u>.
 - o Functionality as viewed from the user's perspective.
- This estimation method is based on a empirical model which is mainly independent of programming language.
- Function Points can be used for several purposes:
 - $_{\odot}\,$ Estimating the FP of a new planned software.
 - o Assessing the retail value of an existing software.
- Developed by Allan J. Albrecht, and standardized by the "International Function Point User Group". (www.ifpug.org)

FP — Project Types



Project Type	FP Purpose
Development Project	Measures the functions that will be provided to the users in a new application.
Enhancement Project	Measures the modifications to an existing application.
Application Assesment	Measures the functionality provided to users in an existing application.

FP — Counting Steps



- 1. Count Data Functions and Transactional Functions
- 2. Calculate Unadjusted Function Point
- 3. Calculate Value Adjustment Factor (VAF)
- 4. Calculate Adjusted Function Point

FP - Equations



$$VAF = \left(\sum_{i=1}^{14} GSC_i * 0.01\right) + 0.65$$

Adjusted FP = (Unadjusted FP) * VAF

VAF: Value Adjustment Factor
GSC: General System Characteristic factors





- VAF consists of 14 General System Characteristics (GSC) such as data communications, response times, end user efficiency, multiple sites, flexibility,etc.
- ≤ Each GSC can be an integer value between 0 and 5.
- Min VAF = (14*0)*0.01 + 0.65 = 0.65
- Max VAF = (14*5)*0.01 + 0.65 = 1.35
- The overall effect of VAF can vary in range from 0.65 (when all GSCs are low) to 1.35 (when all GSCs are high), so its overall adjustment effect could be ± 35 %.
- Me will study the GSCs and VAF later.

1.29

FP — Calculating Unadjusted Function Points



Type of	Complexity of Components			nts
Component	Low	Average	High	Total
EI	x3	x 4	x6	=
EO	x 4	x 5	x 7	=
EQ	x3	x 4	x 6	=
ILF	x7	x10	x15	=
EIF	x 5	x 7	x10	=

Unadjusted Function Points =

FP — Standard Functions



∞ In counting FPs there are five standard "functions" that you

Data Functions:

- Internal Logical Files (ILF)
- External Interface Files (EIF)

Transactional Functions:

- External Inputs (EI)
- o External Outputs (EO)
- External Inquiries (EQ)

FP — Data Functions



န္ကာ ILF:

- Files controlled by the program.
- Each data file (or database table) is counted.
- Examples
 - · ILF refers to logical group of data files maintained by the application such
 - · Note the inside application data is updated and not any external data.

ച EIF:

- Files controlled by other programs.
- All machine readable interfaces (import/export data file) that are used to transmit information to another system are counted.
- Examples
 - EIF refers to logical group of data referenced but not maintained internally such as an Currency file.

FP - Transactional Functions



El:

- Each user input (screens, forms, dialog boxes, controls etc.) that provides distinct data to the software is counted.


 Individual data items within a data-entry screen are not counted
- Inputs should be distinguished from inquiries, which are counted separately.

- Each user output that provides information to the user is counted.
- In this context, output refers to reports, screens, graphs, error
- Individual data items within a report are not counted separately.

- An inquiry is defined as an on-line input that results in the generation of some immediate software response in the form of an on-line output.
- Each distinct inquiry is counted.

FP — System Example 1








· ILF refers to logical group of data files maintained by the application such as Employee file.

FP — Logical File (ILF) example

Note the inside application data is updated and not any external data.

FP — System Example 2



6

FP — External Interface File (EIF) example



· EIF refers to logical group of data referenced but not maintained internally such as an Currency file.



- The basic EI is from user screens (for data entry / editing).
- · Users should have interface through which they can maintain the data files in ILF through Add, Delete, Update menu selections (transactional functions).
 - Passing control data such as menu selections into the application is considered as EI.



- EO usually refers to reports which contain derived data from the internal files (ILF) such as calculated totals.
 - Formatted data sent out of application with added value.
 - For example, list of students and the calculated grade average in a
- EO can also refer to screens which contain the followings:
 - Displaying derived data from the internal files (ILF).
 - Prefilling a listbox with hardcoded data in the program.
- Outputs sent to external systems are EO.
 - For example, your application generates CSV (comma separated values) files.
 - These files are then used by some external application to update the external application tables (EIF).



- EQ functions will be mainly reports which do not contain derived
- Formatted data sent out of application without added value. (For example, only the list of students in a class)
- · Reports may have input criteria, so that can be another EQ.

Sa Customers

First Name Last Name Address
Howard Anderson 919 Jahr

- Prefilling a listbox from ILF is considered as EQ, because this is an
- · Note EQ functions don't update any ILF or EIF. They only fetch data for display.

FP Example: "Customer" Application



- In this simple example, we will evaluate a Customer GUI (Graphical User Interface) application.
- no The database has only one table, which contains customer
- 50 The GUI program will allow the user add, delete, and update the records.

FP Example :"Customer" Screen



10

(878) 174-3093 (088) 094-8669 (310) 950-1584 (113) 030-9012 (366) 436-7778 (282) 370-7369 (034) 003-0375 (533) 439-3612 (098) 074-9801 (389) 106-3392

7

FP Example: Counting the Functions (1)



- March 1 There is 1 Internal Logical File
 - 1) Customer table

Customer: Table		
	Field Name	Data Type
P	CustID	Number
	LastName	Text
	FirstName	Text
	Address	Text
	City	Text
	State	Text
	Zip	Text
	PhoneNumber	Text

FP Example : Counting the Functions (2





- n There are 3 External Inputs
 - 1) "Customer selection" area in the screen for selecting a customer
 - 2) "Current record" area in the screen for entering/editing customer data
 - 3) All transaction buttons (ADD, UPDATE, DELETE, etc.)


FP Example : Counting the Functions (3)





- n There are 2 External Outputs
 - 1) The output listbox of all customer names and addresses (always read only)
 - "Current record" area in the screen for displaying currently selected customer data (read only in display mode)
- n There is 1 External Query
 - 1) The confirmation dialog boxes for "Delete" and "Save" buttons




















FP - General System Characteristics		
Data Communication ription	Rating	
Distributed data processing No influence	0	
s. Performance Incidental L. Heavily used configuration	1	
5. Transaction rate Moderate	2	
5. Online data entry Average	3	
7. End user efficien ®ignificant	4	
B. Online update Essential	5	
9. Complex processing		
10. Reusability		
11. Installation ease		
12. Operational ease		
13. Multiple sites		
14. Facilitate change		

FP - GSC Definitions (1)

- 1. Data communications: How many communication facilities are there to aid in the transfer or exchange of information with the application or system?
- 2. Distributed data processing: How are distributed data and processing functions handled?
- 3. Performance: Did the user require response time or throughput?
- 4. Heavily used configuration: How heavily used is the current hardware platform where the application will be executed?
- Transaction rate: How frequently are transactions executed; daily, weekly, monthly, etc.?
- 6. On-Line data entry: What percentage of the information is entered On-Line?
- 7. End-user efficiency: Was the application designed for end-user efficiency?

FP - GSC Definitions (2)



- 8. On-Line update: How many ILFs are updated by On-Line transaction?
- 9. Complex processing: Does the application have extensive logical or mathematical processing?
- 10. Reusability: Was the application developed to meet one or many user's needs?
- 11. Installation ease: How difficult is conversion and installation?
- 12. Operational ease: How effective and/or automated are start-up, back up, and recovery procedures?
- 13. Multiple sites: Was the application specifically designed, developed, and supported to be installed at multiple sites for multiple organizations?
- 14. Facilitate change: Was the application specifically designed, developed, and supported to facilitate change?

FP - GSCs for "Customer" Example



	200
GSC	Value (0-5)
1. Data communications	0
2. Distributed data processing	0
3. Performance	3
4. Heavily used configuration	3
5. Transaction rate	4
6. On-Line data entry	5
7. End-user efficiency	4
8. On-Line update	1
9. Complex processing	0
10. Reusability	0
11. Installation ease	0
12. Operational ease	2
13. Multiple sites	0
14. Facilitate change	0

Total =

22



VAF = 0.65 + (Sum of all GSC factors) * 0.01)

= 0.65 + (22 * 0.01)

= 0.87

Adjusted FP = VAF * (Total Unadjusted FP)

= 0.87 * 30

≈ 26

FP - Approximate Estimation of Size and Effort



- Assume the program will be implemented in Visual Basic, which has a standard rate of 50 LOC/FP.
 - $_{\odot}$ The project will be approximately 50 * 26 \approx 1300 lines of code.
 - Assume a programmer works for 5 FP per day.
 - The project will take approximately $26 / 5 \approx 5$ days.

FP - Actual Lines of Code in Visual Basic



Module Name	Total Lines	Effective Coded Lines
frmCustMaint.frm	989	400
modGeneral.bas	65	60
modValidate.bas	246	240
TOTALS =	1300	700

COCOMO 2 Model



- so An empirical model based on project experience.
- Well-documented, 'independent' model which is not tied to a specific software vendor.
- Long history from initial version published in 1981 (COCOMO-81) through various instantiations to COCOMO 2 (2000).
- COCOMO 2 takes into account different approaches to software development, reuse, etc.

COCOMO 2 Submodels




- COCOMO 2 incorporates a range of sub-models that produce increasingly detailed software estimates.
- № The sub-models in COCOMO 2 are:
 - Application composition model. Used when software is composed from existing parts.
 - Early design model. Used when requirements are available but design has not yet started.
 - Reuse model. Used to compute the effort of integrating reusable components.
 - Post-architecture model. Used once the system architecture has been designed and more information about the system is available.

Project Management - 1

1.61

Project Management - 1

1.62



Relative size Application Composition (3 parameters) Early Design (12 parameters) Post-Architecture (22 parameters) Underestimated Application Composition (3 parameters) Post-Architecture (22 parameters) Milestones Acquirements Spec. Spec.

Estimation for 00 Projects - 1



- Develop estimates using effort decomposition, FP analysis, and any other method that is applicable for conventional applications.
- Using object-oriented analysis modeling, develop use-cases and determine a count.
- so From the analysis model, determine the number of key classes
- categorize the type of interface for the application and develop a multiplier for support classes:

Ju	pport orasses.	
	Interface type	Multipli
	No GUI	2.0
	Text-based user interface	2.25
	GUI	2.5
	Complex CIII	2.0

Estimation for 00 Projects - II



- Multiply the number of key classes (step 3) by the multiplier to obtain an estimate for the number of support classes.
- Multiply the total number of classes (key + support) by the average number of work-units per class. Lorenz and Kidd suggest 15 to 20 person-days per class.
- Cross check the class-based estimate by multiplying the average number of work-units per use-case

Project Management - 1

1.65

Project Management - 1


Estimation for Agile Projects



- Each user scenario (a mini-use-case) is considered separately for estimation purpos
- The scenario is decomposed into the set of software engineering tasks that will be required to develop it.
- so Each task is estimated separately. Note: estimation can be based on historical data, an empirical model, or "experience."
 - Alternatively, the 'volume' of the scenario can be estimated in LOC, FP or some other volume oriented measure (e.g., use-case count).
- so Estimates for each task are summed to create an estimate for the scenario.
 - Alternatively, the volume estimate for the scenario is translated into effort using historical
- The effort estimates for all scenarios that are to be implemented for a given software increment are summed to develop the effort estimate for the increment

Estimation Process Metrics 💝 Planning and Scheduling **Process and Project Metrics** 80 4.3 CB

A Good Manager Measures



Why Do We Measure?



- so assess the status of an ongoing project
- n track potential risks
- uncover problem areas before they go "critical,"
- adjust work flow or tasks,

Project Management Concepts

so evaluate the project team's ability to control quality of software work products.

Process Measurement



- Ne measure the efficiency of a software process indirectly.
 - That is, we derive a set of metrics based on the outcomes that can be derived from the process.
 - Outcomes include


 - · defects delivered to and reported by end-users
 - work products delivered (productivity)
 - · human effort expended calendar time expended
 - schedule conformance

 - other measures
- Me also derive process metrics by measuring the characteristics of specific software engineering tasks.

Process Metrics Guidelines



- interpreting metrics data.
- provide regular feedback to the individuals and teams who collect measures and metrics.
- Don't use metrics to appraise individuals
- Nork with practitioners and teams to set clear goals and metrics that will be used to achieve them.
- no Never use metrics to threaten individuals or teams.
- Metrics data that indicate a problem area should not be considered "negative." These data are merely an indicator for process improvement.
- Don't obsess on a single metric to the exclusion of other important metrics.



Metrics

Process Metrics

- Quality-related
- focus on quality of work products and deliverables
- Productivity-related
- Production of work-products related to effort expended

 Statistical SQA data
- error categorization & analysis

 Defect removal efficiency
- propagation of errors from process activity to activity
- Reuse data

 The number of components produced and their degree of reusability

n Project Metrics

- used to minimize the development schedule by making the adjustments necessary to avoid delays and mitigate potential problems and risks
- used to assess product quality on an ongoing basis and, when necessary modify the technical approach to
- every project should measure:
 - · Inputs-measures of the resources (e.g.
 - people, tools) required to do the work.

 outputs—measures of the deliverables or
 work products created during the
 software engineering process.
 - · results-measures that indicate the effectiveness of the deliverables

Typical Project Metrics



- so Effort/time per software engineering task
- so Errors uncovered per review hour
- Scheduled vs. actual milestone dates
- so Changes (number) and their characteristics
- Distribution of effort on software engineering tasks Examples:
- 50 total FP estimation (Function Points)
- total LOC estimation (Lines of Code)
- FP per person-month
- errors or defects per KLOC (thousand LOC)
- pages of documentation per KLOC

Object-Oriented Metrics



- Number of scenario scripts (use-cases)
- Number of support classes (required to implement the system but are not immediately related to the problem domain)
- 🔊 Average number of support classes per key class (analysis class)
- Number of subsystems (an aggregation of classes that support a function that is visible to the end-user of a system)

Web Project Metrics



- Number of static Web pages (the end-user has no control over the content displayed on the page)
- Number of dynamic Web pages (end-user actions result in customized content displayed on the page)
- Number of internal page links (internal page links are pointers that provide a hyperlink to some other Web page within the WebApp)
- number of persistent data objects
- n Number of external systems interfaced
- n Number of static content objects
- » Number of dynamic content objects
- n Number of executable functions

- **Project Management Concepts**
- Estimation
- Process Metrics
- Planning and Scheduling

Planning and Scheduling

80 4.4 CB

Why Are Projects Late?

- n unrealistic deadline established by someone outside the software development group
- so changing customer requirements that are not reflected in schedule changes;
- n honest underestimate of the amount of effort and/or the number of resources that will be required to do the job;
- predictable and/or unpredictable risks that were not considered when the project commenced;
- x technical difficulties that could not have been foreseen in
- » human difficulties that could not have been foreseen in advance;
- miscommunication among project staff that results in delays;
- so a failure by project management to recognize that the project is falling behind schedule and a lack of action to correct the problem

Plan-Driven Development (PDD)



- Plan-driven or plan-based development is an approach to software engineering where the development process is planned in detail.
 - Plan-driven development is based on engineering project management techniques and is the 'traditional' way of managing large software development projects.
- A project plan is created that records the work to be done, who will do it, the development schedule and the work products.
- so Managers use the plan to support project decision making and as a way of measuring progress.

Plan-Driven Development Pros and Cons



- no The arguments in favor of a plan-driven approach are that early planning allows organizational issues (availability of staff, other projects, etc.) to be closely taken into account, and that potential problems and dependencies are discovered before the project starts, rather than once the project is underway.
- no The principal argument against plan-driven development is that many early decisions have to be revised because of changes to the environment in which the software is to be developed and used.


Project Plans



- n a plan-driven development project, a project plan sets out the resources available to the project, the work breakdown and a schedule for carrying out the work.
- » Plan sections
 - o Introduction
 - Project organization
 - Risk analysis
 - o Hardware and software resource requirements
 - Work breakdown
 - Project schedule
 - Monitoring and reporting mechanisms

The project planning process





A Typical Software Project Plan Document



- 1. Introduction
 - A. Purpose of Plan
 B. Project Scope and Objectives
- 2. Project Estimates
- A. Historical Data Used for Estimates
- B. Estimation Techniques
- C. Estimates of Effort, Cost, Duration
- 3. Risks Management Strategy A. Risk Table
- B. Discussion of Risks to be Managed
- C. RMMM Plan 4. Schedule
- A. Project Work Breakdown Structure
- R Task Network
- C. Timeline Chart
- D. Resource Table

- 5. Project Resources
 - A. People
 - B. Hardware and Software C. Special Resources
- 6. Staff Organization
- A. Team Structure
- B. Management Reporting
- 7. Tracking and Control Mechanisms
- A. Quality Assurance and Control
- B. Change Management and Control
- 8. Appendices


Scheduling Principles



- nterdependency—indicate task interrelationship
- so effort validation—be sure resources are available
- so defined responsibilities—people must be assigned
- material defined milestones—review for quality

Effort and Delivery Time





Project Management - 1

1.85

Project Management - 1

1 96

For Scheduling



· PERT Chart:

- Shows the relationships based on tasks or activities
- Defines tasks that can be done concurrently or not and critical path

· Gantt Chart:

Shows schedule (timeline) information for each task as a bar chart

PERT Chart



- $_{\mbox{\scriptsize 50}}$ Project Evaluation and Review Technique
- 🔊 Also known as Task Network Diagram
 - Nodes: activities / tasks and estimated duration
 - Edges: dependencies
- Critical path: Longest path from start to finish. Any slippage on the critical path will cause project delay.

PERT Example : Tasks and Durations



TASKS	WEEKS
1.2 Software Development	11
1.2.1 Requirements Analysis	3
1.2.2 Architectural Design	2
1.2.3 Procedural Design	2.5
1.2.4 Code	3.5
1.3 Testing	7
1.3.1 Unit Test	3
1.3.2 Integration Test	4
1.3.3 Acceptance Test	1
1.4 Operations	5
1.4.1 Packaging	1
1.4.2 Customer Training	5


Management - 1

PERT Chart Underschip Int 100 2: Int 200 2: Int 20

GANTT Chart




- so Also known as timeline chart
- so Shows high level view of whole project
 - Horizontal bars show duration of tasks
 - Triangles show milestones
 - Vertical lines show dependencies



GANTT Chart Example







- Agile methods of software development are iterative approaches where the software is developed and delivered to customers in increments.
- 🔊 Unlike plan-driven approaches, the functionality of these increments is not planned in advance but is decided during the development.
 - The decision on what to include in an increment depends on progress and on the customer's priorities
- no The customer's priorities and requirements change so it makes sense to have a flexible plan that can accommodate these changes.
- Release planning, which looks ahead for several months and decides on the features that should be included in a release of a system.
- so Iteration planning, which has a shorter term outlook, and focuses on planning the next increment of a system. This is typically 2-4 weeks of work for the team.

Schedule Tracking



- so conduct periodic project status meetings in which each team member reports progress and problems.
- so evaluate the results of all reviews conducted throughout the software engineering process.
- so determine whether formal project milestones have been accomplished by the scheduled date.
- so compare actual start-date to planned start-date for each project task listed in the resource table
- meet informally with practitioners to obtain their subjective assessment of progress to date and problems on the horizon.

OOP Project Progress



- Description Technical milestone: 00 analysis
- All classes and the class hierarchy have been defined and reviewed.
 - Class attributes and operations associated with a class have been defined and reviewed.

 Class relationships (Chapter 8) have been established and reviewed.
- A behavioral model (Chapter 8) has been created and reviewed. Reusable classes have been noted. Technical milestone: 00 design
 completed
- - has been defined and reviewed.
 Classes are allocated to subsystems
 and reviewed.
 Task allocation has been established
 and reviewed.
 Responsibilities and collaborations
 (Chapter 9) have been identified.
 Attributes and operations have been
 designed and reviewed.
 - The communication model has been created and reviewed.
 - The set of subsystems (Chapter 9) has been defined and reviewed.
- sted
 The correctness and completeness of OO analysis and design models has been reviewed. A class-responsibility-collaboration network (Chapter 8) has been reviewed in the control of the

programming completed

Each new class has been implemented in code from the design model.

Technical milestone: 00

model.

Extracted classes (from a reuse library) have been implemented.

Prototype or increment has beer prototype or increment with the completed milestone: 00 testing