



wazuh_Scan

Report generated by Tenable Nessus™

Tue, 14 Apr 2026 12:48:55 +03


TABLE OF CONTENTS

Vulnerabilities by Host

- 192.168.50.10.....4

Vulnerabilities by Host

192.168.50.10



Scan Information

Start time: Tue Apr 14 12:32:32 2026

End time: Tue Apr 14 12:48:55 2026

Host Information

IP: 192.168.50.10

MAC Address: 00:0C:29:5B:91:27 00:0C:29:5B:91:31

OS: Linux Kernel 6.8.0-107-generic on Ubuntu 24.04

Vulnerabilities

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/25/smtp

```
The following certificate was at the top of the certificate
chain sent by the remote host, but it is signed by an unknown
certificate authority :
```

```
| -Subject : CN=wazuh
| -Issuer  : CN=wazuh
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/443/www

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=US/L=California/O=Wazuh/OU=Wazuh/CN=wazuh-dashboard  
| -Issuer  : OU=Wazuh/O=Wazuh/L=California
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/1515

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=US/ST=California/CN=Wazuh  
| -Issuer  : C=US/ST=California/CN=Wazuh
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/55000/www

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=US/ST=California/L=San Francisco/O=Wazuh/CN=wazuh.com  
| -Issuer  : C=US/ST=California/L=San Francisco/O=Wazuh/CN=wazuh.com
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/25/smtp

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : CN=wazuh
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/1515

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : C=US/ST=California/CN=Wazuh
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/55000/www

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
| -Subject : C=US/ST=California/L=San Francisco/O=Wazuh/CN=wazuh.com
```

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

TLsv1 is enabled and the server supports at least one cipher.

157288 - TLS Version 1.1 Deprecated Protocol

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://datatracker.ietf.org/doc/html/rfc8996>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2022/04/04, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

TLSv1.1 is enabled and the server supports at least one cipher.

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

31705 - SSL Anonymous Cipher Suites Supported

Synopsis

The remote service supports the use of anonymous SSL ciphers.

Description

The remote host supports the use of anonymous SSL ciphers. While this enables an administrator to set up a service that encrypts traffic without having to generate and configure SSL certificates, it offers no way to verify the remote host's identity and renders the service vulnerable to a man-in-the-middle attack.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?3a040ada>

Solution

Reconfigure the affected application if possible to avoid use of weak ciphers.

Risk Factor

Low

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	28482
CVE	CVE-2007-1858

Plugin Information

Plugin Output

tcp/25/smtp

The following is a list of SSL anonymous ciphers supported by the remote TCP server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DH-AES128-SHA256 SHA256	0x00, 0xA6	DH	None	AES-GCM(128)	
DH-AES256-SHA384 SHA384	0x00, 0xA7	DH	None	AES-GCM(256)	
ADH-AES128-SHA SHA1	0x00, 0x34	DH	None	AES-CBC(128)	
ADH-AES128-SHA256 SHA256	0x00, 0x6C	DH	None	AES-CBC(128)	
ADH-AES256-SHA SHA1	0x00, 0x3A	DH	None	AES-CBC(256)	
ADH-AES256-SHA256 SHA256	0x00, 0x6D	DH	None	AES-CBC(256)	
ADH-CAMELLIA128-SHA SHA1	0x00, 0x46	DH	None	Camellia-CBC(128)	
ADH-CAMELLIA128-SHA256 SHA256	0x00, 0xBF	DH	None	Camellia-CBC(128)	
ADH-CAMELLIA256-SHA SHA1	0x00, 0x89	DH	None	Camellia-CBC(256)	
ADH-CAMELLIA256-SHA256 SHA256	0x00, 0xC5	DH	None	Camellia-CBC(256)	
AECDH-AES128-SHA SHA1	0xC0, 0x18	ECDH	None	AES-CBC(128)	
AECDH-AES256-SHA SHA1	0xC0, 0x19	ECDH	None	AES-CBC(256)	

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

156000 - Apache Log4j Installed (Linux / Unix)

Synopsis

Apache Log4j, a logging API, is installed on the remote Linux / Unix host.

Description

One or more instances of Apache Log4j, a logging API, are installed on the remote Linux / Unix Host.

The plugin timeout can be set to a custom value other than the plugin's default of 45 minutes via the 'timeout.156000' scanner setting in Nessus 8.15.1 or later.

Note, this plugin runs certain commands differently if the scan is configured to use the 'Attempt Least Privilege' option. If enabled, scan times are expected to increase, especially on hosts with many files.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://logging.apache.org/log4j/2.x/>

Solution

n/a

Risk Factor

None

References

XREF IAVA:0001-A-0650

XREF IAVT:0001-T-0941

Plugin Information

Published: 2021/12/10, Modified: 2026/04/13

Plugin Output

tcp/0

```
Nessus detected 3 installs of Apache Log4j:
```

```
Path                : /usr/share/java/libintl-0.21.jar
Version             : unknown
JMSAppender.class association : Not Found
JdbcAppender.class association : Not Found
```

```
JndiLookup.class association : Not Found
Method                      : Embedded string inspection

Path                        : /usr/share/apport/apport.jar
Version                    : unknown
JMSAppender.class association : Not Found
JdbcAppender.class association : Not Found
JndiLookup.class association : Not Found
Method                      : Embedded string inspection

Path                        : /usr/share/apport/testsuite/crash.jar
Version                    : unknown
JMSAppender.class association : Not Found
JdbcAppender.class association : Not Found
JndiLookup.class association : Not Found
Method                      : Embedded string inspection
```

Note: Jar file inspection cannot be performed. No results or cannot list archive contents. If results are present, install an unzip package to resolve this problem.

34098 - BIOS Info (SSH)

Synopsis

BIOS info could be read.

Description

Using SMBIOS and UEFI, it was possible to get BIOS info.

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2008/09/08, Modified: 2024/02/12

Plugin Output

tcp/0

```
Version      : None
Vendor       : VMware, Inc.
Release Date : 11/12/2020
Secure boot  : disabled
```


39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Local checks have been enabled.
```

139918 - ClamAV Installed (Linux)

Synopsis

Checks the packages and file system on the remote Linux host for a ClamAV installation.

Description

ClamAV, an open source anti-virus software package from Cisco, has been detected on the remote Linux host.

See Also

<https://www.clamav.net>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/08/27, Modified: 2026/04/13

Plugin Output

tcp/0

```
Path           : /usr/bin/clamscan (via package manager)
Version        : 1.4.3
Autoupdate     : no
Managed by OS : True
Running        : yes
Signatures version : 27963
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :
```

```
cpe:/o:canonical:ubuntu_linux:24.04.4::~~lts~~~ -> Canonical Ubuntu Linux
```

```
Following application CPE's matched on the remote system :
```

```
cpe:/a:apache:log4j -> Apache Software Foundation log4j
cpe:/a:cisco:clam_antivirus:1.4.3 -> Cisco Clam Antivirus
cpe:/a:gnupg:libgcrypt:1.10.3 -> GnuPG Libgcrypt
cpe:/a:haxx:curl:8.5.0 -> Haxx Curl
cpe:/a:haxx:libcurl:8.5.0 -> Haxx libcurl
cpe:/a:openbsd:openssh:9.6 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:9.6p1 -> OpenBSD OpenSSH
cpe:/a:openssl:openssl:3.0.13 -> OpenSSL Project OpenSSL
cpe:/a:tukaani:xz:5.6.1 -> Tukaani XZ
cpe:/a:vim:vim:9.1 -> Vim
cpe:/a:vmware:open_vm_tools:12.5.0 -> VMware Open VM Tools
```


182774 - Curl Installed (Linux / Unix)

Synopsis

Curl is installed on the remote Linux / Unix host.

Description

Curl (also known as curl and cURL) is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182774' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://curl.se/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
Path          : /usr/bin/curl
Version       : 8.5.0
Associated Package : curl 8.5.0-2ubuntu10.8
Managed by OS : True
```

55472 - Device Hostname

Synopsis

It was possible to determine the remote system hostname.

Description

This plugin reports a device's hostname collected via SSH or WMI.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/06/30, Modified: 2026/04/13

Plugin Output

tcp/0

```
Hostname : wazuh
wazuh (hostname command)
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 100
```

25203 - Enumerate IPv4 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv4 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv4 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable any unused IPv4 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/09/24

Plugin Output

tcp/0

The following IPv4 addresses are set on the remote host :

- 192.168.50.10 (on interface ens33)
- 192.168.3.132 (on interface ens37)
- 127.0.0.1 (on interface lo)

25202 - Enumerate IPv6 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv6 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv6 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable IPv6 if you are not actually using it. Otherwise, disable any unused IPv6 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/09/24

Plugin Output

tcp/0

The following IPv6 interfaces are set on the remote host :

- fe80::20c:29ff:fe5b:9127 (on interface ens33)
- fe80::20c:29ff:fe5b:9131 (on interface ens37)
- fd64:6140:46cf:4f00:20c:29ff:fe5b:9131 (on interface ens37)
- ::1 (on interface lo)

33276 - Enumerate MAC Addresses via SSH

Synopsis

Nessus was able to enumerate MAC addresses on the remote host.

Description

Nessus was able to enumerate MAC addresses by connecting to the remote host via SSH with the supplied credentials.

Solution

Disable any unused interfaces.

Risk Factor

None

Plugin Information

Published: 2008/06/30, Modified: 2022/12/20

Plugin Output

tcp/0

```
The following MAC addresses exist on the remote host :
```

- 00:0c:29:5b:91:27 (interface ens33)
- 00:0c:29:5b:91:31 (interface ens37)

170170 - Enumerate the Network Interface configuration via SSH

Synopsis

Nessus was able to parse the Network Interface data on the remote host.

Description

Nessus was able to parse the Network Interface data on the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/01/19, Modified: 2025/02/11

Plugin Output

tcp/0

```
ens33:
  MAC : 00:0c:29:5b:91:27
  IPv4:
    - Address : 192.168.50.10
      Netmask : 255.255.255.0
      Broadcast : 192.168.50.255
  IPv6:
    - Address : fe80::20c:29ff:fe5b:9127
      Prefixlen : 64
      Scope : link
      ScopeID : 0x20
lo:
  IPv4:
    - Address : 127.0.0.1
      Netmask : 255.0.0.0
  IPv6:
    - Address : ::1
      Prefixlen : 128
      Scope : host
      ScopeID : 0x10
ens37:
  MAC : 00:0c:29:5b:91:31
  IPv4:
    - Address : 192.168.3.132
      Netmask : 255.255.255.0
      Broadcast : 192.168.3.255
  IPv6:
    - Address : fe80::20c:29ff:fe5b:9131
      Prefixlen : 64
      Scope : link
      ScopeID : 0x20
    - Address : fd64:6140:46cf:4f00:20c:29ff:fe5b:9131
```

```
Prefixlen : 64  
Scope : global  
ScopeID : 0x0
```

179200 - Enumerate the Network Routing configuration via SSH

Synopsis

Nessus was able to retrieve network routing information from the remote host.

Description

Nessus was able to retrieve network routing information the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/02, Modified: 2023/08/02

Plugin Output

tcp/0

```
Gateway Routes:
  ens33:
    ipv4_gateways:
      192.168.50.254:
        subnets:
          - 192.168.60.0/24
    ens37:
      ipv4_gateways:
        192.168.3.1:
          subnets:
            - 0.0.0.0/0
      ipv6_gateways:
        fe80::6661:40ff:fe46:cf4f:
          subnets:
            - ::/0
Interface Routes:
  ens33:
    ipv4_subnets:
      - 192.168.50.0/24
    ipv6_subnets:
      - fe80::/64
  ens37:
    ipv4_subnets:
      - 192.168.3.0/24
    ipv6_subnets:
      - fd64:6140:46cf:4f00::/64
      - fe80::/64
```

168980 - Enumerate the PATH Variables

Synopsis

Enumerates the PATH variable of the current scan user.

Description

Enumerates the PATH variables of the current scan user.

Solution

Ensure that directories listed here are in line with corporate policy.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2026/04/13

Plugin Output

tcp/0

```
Nessus has enumerated the path of the current scan user :
```

```
/usr/local/sbin  
/usr/local/bin  
/usr/sbin  
/usr/bin  
/sbin  
/bin  
/snap/bin
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
00:0C:29:5B:91:27 : VMware, Inc.
```

```
00:0C:29:5B:91:31 : VMware, Inc.
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 00:0C:29:5B:91:27  
- 00:0C:29:5B:91:31
```


168982 - Filepaths contain Dangerous characters (Linux)

Synopsis

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential.

Description

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential. Although almost any character is valid for an entry in this kind of filesystem, such as semicolons, use of some of them may lead to problems or security compromise when used in further commands.

This product has chosen in certain plugins to avoid digging within those files and directories for security reasons.

These should be renamed to avoid security compromise.

Solution

Rename these files or folders to not include dangerous characters.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
The following files and directories contain potentially dangerous characters such as brackets,  
ampersand, or semicolon.
```

```
This scanner avoided access to these files when possible for safety:
```

```
/usr/bin/clamscan (via package manager)
```

84502 - HSTS Missing From HTTPS Server

Synopsis

The remote web server is not enforcing HSTS.

Description

The remote HTTPS server is not enforcing HTTP Strict Transport Security (HSTS). HSTS is an optional response header that can be configured on the server to instruct the browser to only communicate via HTTPS. The lack of HSTS allows downgrade attacks, SSL-stripping man-in-the-middle attacks, and weakens cookie-hijacking protections.

See Also

<https://tools.ietf.org/html/rfc6797>

Solution

Configure the remote web server to use HSTS.

Risk Factor

None

Plugin Information

Published: 2015/07/02, Modified: 2024/08/09

Plugin Output

tcp/443/www

```
HTTP/1.1 302 Found
location: /app/login?
osd-name: wazuh
x-frame-options: sameorigin
cache-control: private, no-cache, no-store, must-revalidate
set-cookie: security_authentication=; Max-Age=0; Expires=Thu, 01 Jan 1970 00:00:00 GMT; Secure;
  HttpOnly; Path=/
content-length: 0
Date: Tue, 14 Apr 2026 09:33:49 GMT
Connection: keep-alive
Keep-Alive: timeout=120
```

The remote HTTPS server does not send the HTTP
"Strict-Transport-Security" header.

84502 - HSTS Missing From HTTPS Server

Synopsis

The remote web server is not enforcing HSTS.

Description

The remote HTTPS server is not enforcing HTTP Strict Transport Security (HSTS). HSTS is an optional response header that can be configured on the server to instruct the browser to only communicate via HTTPS. The lack of HSTS allows downgrade attacks, SSL-stripping man-in-the-middle attacks, and weakens cookie-hijacking protections.

See Also

<https://tools.ietf.org/html/rfc6797>

Solution

Configure the remote web server to use HSTS.

Risk Factor

None

Plugin Information

Published: 2015/07/02, Modified: 2024/08/09

Plugin Output

tcp/55000/www

```
HTTP/1.1 401 Unauthorized
Content-Type: application/problem+json; charset=utf-8
Content-Length: 71
Date: Tue, 14 Apr 2026 09:33:49 GMT
Connection: close
```

The remote HTTPS server does not send the HTTP
"Strict-Transport-Security" header.

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/443/www

Based on tests of each method :

- HTTP methods ACL CHECKOUT are allowed on :

/ui/favicons

- HTTP methods ACL CHECKOUT COPY DELETE GET HEAD LOCK MERGE
MKACTIVITY MKCOL MOVE NOTIFY OPTIONS PATCH POST PROPFIND
PROPPATCH PUT REPORT SEARCH SUBSCRIBE TRACE UNLOCK UNSUBSCRIBE
are allowed on :

/

/app

- HTTP methods ACL CHECKOUT COPY DELETE GET LOCK MERGE MKACTIVITY
MKCOL MOVE NOTIFY OPTIONS PATCH POST PROPFIND PROPPATCH PUT
REPORT SEARCH SUBSCRIBE TRACE UNLOCK UNSUBSCRIBE are allowed on :

/ui

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/55000/www

Based on tests of each method :

- HTTP methods ACL CHECKOUT COPY DELETE GET HEAD LOCK MERGE
MKACTIVITY MKCOL MOVE NOTIFY OPTIONS PATCH POST PROPFIND
PROPPATCH PUT REPORT SEARCH SUBSCRIBE TRACE UNLOCK UNSUBSCRIBE
are allowed on :

/

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/443/www

Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : yes

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

location: /app/login?

osd-name: wazuh

x-frame-options: sameorigin

cache-control: private, no-cache, no-store, must-revalidate

set-cookie: security_authentication=; Max-Age=0; Expires=Thu, 01 Jan 1970 00:00:00 GMT; Secure;

HttpOnly; Path=

content-length: 0

Date: Tue, 14 Apr 2026 09:37:04 GMT

Connection: keep-alive

Keep-Alive: timeout=120

Response Body :

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/55000/www

Response Code : HTTP/1.1 429 Too Many Requests

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : yes

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Content-Type: application/problem+json; charset=utf-8

Content-Length: 280

Date: Tue, 14 Apr 2026 09:37:04 GMT

Response Body :

```
{"title": "Too Many Requests", "detail": "Maximum number of requests per minute reached",  
  "remediation": "This limit can be changed in api.yaml file. More information here: https://  
documentation.wazuh.com/4.7/user-manual/api/configuration.html#configuration-file", "error": 6001}
```

91634 - HyperText Transfer Protocol (HTTP) Redirect Information

Synopsis

The remote web server redirects requests to the root directory.

Description

The remote web server issues an HTTP redirect when requesting the root directory of the web server.

This plugin is informational only and does not denote a security problem.

Solution

Analyze the redirect(s) to verify that this is valid operation for your web server and/or application.

Risk Factor

None

Plugin Information

Published: 2016/06/16, Modified: 2025/11/03

Plugin Output

tcp/443/www

```
Request      : https://192.168.50.10/
HTTP response : HTTP/1.1 302 Found
Redirect to   : https://192.168.50.10/app/login?
Redirect type  : 30x redirect

Final page    : https://192.168.50.10/app/login?
HTTP response : HTTP/1.1 200 OK
```

171410 - IP Assignment Method Detection

Synopsis

Enumerates the IP address assignment method(static/dynamic).

Description

Enumerates the IP address assignment method(static/dynamic).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/02/14, Modified: 2026/04/13

Plugin Output

tcp/0

```
+ lo
+ IPv4
  - Address      : 127.0.0.1
    Assign Method : static
+ IPv6
  - Address      : ::1
    Assign Method : static
+ ens33
+ IPv4
  - Address      : 192.168.50.10
    Assign Method : static
+ IPv6
  - Address      : fe80::20c:29ff:fe5b:9127
    Assign Method : static
+ ens37
+ IPv4
  - Address      : 192.168.3.132
    Assign Method : dynamic
+ IPv6
  - Address      : fd64:6140:46cf:4f00:20c:29ff:fe5b:9131
    Assign Method : dynamic
  - Address      : fe80::20c:29ff:fe5b:9131
    Assign Method : static
```

151883 - Libgcrypt Installed (Linux/UNIX)

Synopsis

Libgcrypt is installed on this host.

Description

Libgcrypt, a cryptography library, was found on the remote host.

See Also

<https://gnupg.org/download/index.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/07/21, Modified: 2026/04/13

Plugin Output

tcp/0

Nessus detected 4 installs of Libgcrypt:

Path : /usr/lib/x86_64-linux-gnu/libgcrypt.so.20.4.3
Version : 1.10.3

Path : /usr/lib/x86_64-linux-gnu/libgcrypt.so.20
Version : 1.10.3

Path : /lib/x86_64-linux-gnu/libgcrypt.so.20.4.3
Version : 1.10.3

Path : /lib/x86_64-linux-gnu/libgcrypt.so.20
Version : 1.10.3

Synopsis

Use system commands to obtain the list of mounted devices on the target machine at scan time.

Description

Report the mounted devices information on the target machine at scan time using the following commands.

```
/bin/df -h /bin/lsblk /bin/mount -l
```

This plugin only reports on the tools available on the system and omits any tool that did not return information when the command was ran.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/02/03, Modified: 2023/11/27

Plugin Output

tcp/0

```
$ df -h
Filesystem                Size      Used Avail Use% Mounted on
tmpfs                      335M    1.6M   334M    1% /run
/dev/mapper/ubuntu--vg-ubuntu--lv 14G    9.6G   3.5G   74% /
tmpfs                      1.7G    916K   1.7G    1% /dev/shm
tmpfs                      5.0M         0   5.0M    0% /run/lock
/dev/sda2                  2.0G    200M   1.6G   11% /boot
tmpfs                      335M    12K   335M    1% /run/user/1000

$ lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINTS
sda           8:0    0   30G  0 disk
|-sda1        8:1    0    1M  0 part
|-sda2        8:2    0    2G  0 part /boot
`-sda3        8:3    0   28G  0 part
   `--ubuntu--vg-ubuntu--lv 252:0    0   14G  0 lvm  /
sr0          11:0    1   3.2G  0 rom

$ mount -l
sysfs on /sys type sysfs (rw,nosuid,nodev,noexec,relatime)
proc on /proc type proc (rw,nosuid,nodev,noexec,relatime)
udev on /dev type devtmpfs (rw,nosuid,relatime,size=1672708k,nr_inodes=418177,mode=755,inode64)
devpts on /dev/pts type devpts (rw,nosuid,noexec,relatime,gid=5,mode=620,ptmxmode=000)
```

```
tmpfs on /run type tmpfs (rw,nosuid,nodev,noexec,relatime,size=342892k,mode=755,inode64)
/dev/mapper/ubuntu--vg-ubuntu--lv on / type ext4 (rw,relatime)
securityfs on /sys/kernel/security type securityfs (rw,nosuid,nodev,noexec,relatime)
tmpfs on /dev/shm type tmpfs (rw,nosuid,nodev,inode64)
tmpfs on /run/lock type tmpfs (rw,nosuid,nodev,noexec,relatime,size=5120k,inode64)
cgroup2 on /sys/fs/cgroup type cgroup2
(rw,nosuid,nodev,noexec,relatime,nsdelegate,memory_recursiveprot)
pstore on /sys/fs/pstore type pstore (rw,nosuid,nodev,noexec,relatime)
bpf on /sys/fs/bpf type bpf (rw,nosuid,nodev,noexec,relatime,mode=700)
systemd-1 on /proc/sys/fs/binfmt_misc type autofs
(rw,relatime,fd=32,pgrp=1,timeout=0,minproto=5,maxproto=5,direct,pipe_ino=11232)
hugetlbfs on /dev/hugepages type hugetlbfs (rw,nosuid,nodev,relatime,pagesize=2M)
mqueue on /dev/mqueue type mqueue (rw,nosuid, [...])
```

193143 - Linux Time Zone Information

Synopsis

Nessus was able to collect and report time zone information from the remote host.

Description

Nessus was able to collect time zone information from the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2024/04/10, Modified: 2024/04/10

Plugin Output

tcp/0

```
Via date: UTC +0000
Via timedatectl: Time zone: Etc/UTC (UTC, +0000)
Via /etc/timezone: Etc/UTC
Via /etc/localtime: UTC0
```

Synopsis

Nessus was able to enumerate local users and groups on the remote Linux host.

Description

Using the supplied credentials, Nessus was able to enumerate the local users and groups on the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2016/12/19, Modified: 2025/03/26

Plugin Output

tcp/0

```
----- [ User Accounts ] -----  
  
User       : emin  
Home folder : /home/emin  
Start script : /bin/bash  
Groups     : lxd  
            cdrom  
            sudo  
            emin  
            plugdev  
            dip  
            adm  
  
----- [ System Accounts ] -----  
  
User       : root  
Home folder : /root  
Start script : /bin/bash  
Groups     : root  
  
User       : daemon  
Home folder : /usr/sbin  
Start script : /usr/sbin/nologin  
Groups     : daemon  
  
User       : bin  
Home folder : /bin  
Start script : /usr/sbin/nologin  
Groups     : bin
```



```
User      : sys
Home folder : /dev
Start script : /usr/sbin/nologin
Groups     : sys

User      : sync
Home folder : /bin
Start script : /bin/sync
Groups     : nogroup

User      : games
Home folder : /usr/games
Start script : /usr/sbin/nologin
Groups     : games

User      : man
Home folder : /var/cache/man
Start script : /usr/sbin/nologin
Groups     : man

User      : lp
Home folder : /var/spool/lpd
Start script : /usr/sbin/nologin
Groups     : lp

User      : mail
Home folder : /var/mail
Start script : /usr/sbin/nologin
Groups     : mail

User      : news
Home folder : /var/spool/news
Start script : /usr/sbin/nologin
Groups     : news

User      : uucp
Home folder : /var/spool/uucp
Start script : /usr/sbin/nologin
Groups     : uucp

User      : proxy
Home folder : /bin
Start script : /usr/sbin/nologin
Groups     : proxy

User      : www-data
Home folder : /var/www
Start script : /usr/sbin/nologin
Groups     : www-data

User      : backup
Home folder : /var/backups
Start script : /usr/sbin/nologin
Groups     : backup

User      : list
Home folder : /var/list
Start script : /usr/sbin/nologin
Groups     : list

User      : irc
Home folder : /run/ircd
Start script : /usr/sbin/nologin
Groups     : irc

User      : _apt
Home folder : /nonexistent
Start script : /usr/sbin/nologin
Groups     : nogroup
```

```
User      : nobody  
Home folder : /nonexistent  
Start script : /us [...]
```

50344 - Missing or Permissive Content-Security-Policy frame-ancestors HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive Content-Security-Policy (CSP) frame-ancestors response header or does not set one at all.

The CSP frame-ancestors header has been proposed by the W3C Web Application Security Working Group as a way to mitigate cross-site scripting and clickjacking attacks.

See Also

<http://www.nessus.org/u?55aa8f57>

<http://www.nessus.org/u?07cc2a06>

<https://content-security-policy.com/>

<https://www.w3.org/TR/CSP2/>

Solution

Set a non-permissive Content-Security-Policy frame-ancestors header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/443/www

The following pages do not set a Content-Security-Policy frame-ancestors response header or set a permissive policy:

- <https://192.168.50.10/app/login>

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.11.3
Nessus build : 20047
Plugin feed version : 202604132127
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : wazuh_Scan
```

```
Scan policy used : Advanced Scan
Scanner IP : 192.168.60.10
Port scanner(s) : netstat
Port range : 1-65535
Ping RTT : Unavailable
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : yes, as 'emin' via ssh
Attempt Least Privilege : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : enabled
Web application tests : enabled
Web app tests - Test mode : single
Web app tests - Try all HTTP methods : no
Web app tests - Maximum run time : 5 minutes.
Web app tests - Stop at first flaw : CGI
Max hosts : 100
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/4/14 12:32 +03 (UTC +03:00)
Scan duration : 966 sec
Scan for malware : yes
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

64582 - Netstat Connection Information

Synopsis

Nessus was able to parse the results of the 'netstat' command on the remote host.

Description

The remote host has listening ports or established connections that Nessus was able to extract from the results of the 'netstat' command.

Note: The output for this plugin can be very long, and is not shown by default. To display it, enable verbose reporting in scan settings.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/13, Modified: 2023/05/23

Plugin Output

tcp/0

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/25/smtp

```
Port 25/tcp was found to be open
```


14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/68

```
Port 68/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/443/www

```
Port 443/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/514

```
Port 514/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/546

```
Port 546/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/1514

```
Port 1514/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/1515

```
Port 1515/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/55000/www

```
Port 55000/tcp was found to be open
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.x
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 6.8.0-107-generic
Confidence level : 99
Method : uname
Type : general-purpose
Fingerprint : uname:Linux wazuh 6.8.0-107-generic #107-Ubuntu SMP PREEMPT_DYNAMIC Fri Mar 13 19:51:50 UTC 2026 x86_64 x86_64 x86_64 GNU/Linux

Remote operating system : ArubaOS-CX - R9
Cisco Catalyst 9200 Series Switches
Cisco Catalyst 9300 Series Switches
Cisco Catalyst IE9300 Rugged Series
Nutanix
Confidence level : 59
Method : SinFP
Type :
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff4445414401030307:M1460:
P3:B00000:F0x00:W0:00:M0

P4:191603_7_p=22R

Remote operating system : Linux Kernel 6.8.0-107-generic on Ubuntu 24.04
Confidence level : 100
Method : LinuxDistribution
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :

SSH:!:SSH-2.0-OpenSSH_9.6p1 Ubuntu-3ubuntu13.15
SMTP:!:220 wazuh ESMTF Postfix (Ubuntu)
SSLCert:!:i/O:Wazuhi/OU:Wazuhs/CN:wazuh-dashboards/O:Wazuhs/OU:Wazuh
62d856c27510192b14188d99fdfebcd6486683e2
i/CN:Wazuhs/CN:Wazuh
c208d29fa6896b310cb37f826a5b2ee92ebcc2b7
i/CN:wazuh.comi/O:Wazuhs/CN:wazuh.coms/O:Wazuh
7e881d9e9d97bd7b8a448a56cf389949686aabf3
i/CN:wazuhs/CN:wazuh
862d2751b7f5e4b716b758c7284b807db8139324

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 6.8.0-107-generic on Ubuntu 24.04
Confidence level : 100
Method : LinuxDistribution
```

Not all fingerprints could give a match. If you think that these signatures would help us improve OS fingerprinting, please submit them by visiting <https://www.tenable.com/research/submitsignatures>.

```
SSH:!:SSH-2.0-OpenSSH_9.6p1 Ubuntu-3ubuntu13.15
uname:Linux wazuh 6.8.0-107-generic #107-Ubuntu SMP PREEMPT_DYNAMIC Fri Mar 13 19:51:50 UTC 2026
x86_64 x86_64 x86_64 GNU/Linux
```

SinFP:

```
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff4445414401030307:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191603_7_p=22R
```

```
SMTP:!:220 wazuh ESMTP Postfix (Ubuntu)
SSLcert:!:i/O:Wazuhi/OU:Wazuhs/CN:wazuh-dashboards/O:Wazuhs/OU:Wazuh
62d856c27510192b14188d99fdfebcd6486683e2
i/CN:Wazuhs/CN:Wazuh
c208d29fa6896b310cb37f826a5b2ee92ebcc2b7
i/CN:wazuh.comi/O:Wazuhs/CN:wazuh.coms/O:Wazuh
7e881d9e9d97bd7b8a448a56cf389949686aabf3
i/CN:wazuhs/CN:wazuh
862d2751b7f5e4b716b758c7284b807db8139324
```

The remote host is running Linux Kernel 6.8.0-107-generic on Ubuntu 24.04

97993 - OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)

Synopsis

Information about the remote host can be disclosed via an authenticated session.

Description

Nessus was able to login to the remote host using SSH or local commands and extract the list of installed packages.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/05/30, Modified: 2026/03/30

Plugin Output

tcp/0

```
It was possible to log into the remote host via SSH using 'password' authentication.

The output of "uname -a" is :
Linux wazuh 6.8.0-107-generic #107-Ubuntu SMP PREEMPT_DYNAMIC Fri Mar 13 19:51:50 UTC 2026 x86_64
x86_64 x86_64 GNU/Linux

Local checks have been enabled for this host.
The remote Debian system is :
trixie/sid

This is a Ubuntu system

OS Security Patch Assessment is available for this host.
Runtime : 7.117391 seconds
```

117887 - OS Security Patch Assessment Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials and enumerate OS security patch levels.

Description

Nessus was able to determine OS security patch levels by logging into the remote host and running commands to determine the version of the operating system and its components. The remote host was identified as an operating system or device that Nessus supports for patch and update assessment. The necessary information was obtained to perform these checks.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0516

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
OS Security Patch Assessment is available.
```

```
Account   : emin  
Protocol  : SSH
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/04/13

Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 9.6p1
Banner       : SSH-2.0-OpenSSH_9.6p1 Ubuntu-3ubuntu13.15
backported   : 1
```

50845 - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

tcp/25/smtp

168007 - OpenSSL Installed (Linux)

Synopsis

OpenSSL was detected on the remote Linux host.

Description

OpenSSL was detected on the remote Linux host.

The plugin timeout can be set to a custom value other than the plugin's default of 15 minutes via the 'timeout.168007' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

Note: This plugin leverages the '-maxdepth' find command option, which is a feature implemented by the GNU find binary. If the target does not support this option, such as HP-UX and AIX devices, users will need to enable 'thorough tests' in their scan policy to run the find command without using a '-maxdepth' argument.

See Also

<https://openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/11/21, Modified: 2026/04/13

Plugin Output

tcp/0

Nessus detected 2 installs of OpenSSL:

Path	: /usr/lib/x86_64-linux-gnu/libcrypto.so.3
Version	: 3.0.13
Associated Package	: libssl3t64
Path	: /usr/bin/openssl
Version	: 3.0.13
Associated Package	: openssl 3.0.13-0ubuntu3.9
Managed by OS	: True

We are unable to retrieve version info from the following list of OpenSSL files. However, these installs may include their version within the filename or the filename of the Associated Package.

e.g. libssl.so.3 (OpenSSL 3.x), libssl.so.1.1 (OpenSSL 1.1.x)

/usr/lib/x86_64-linux-gnu/libssl.so.3

179139 - Package Manager Packages Report (nix)

Synopsis

Reports details about packages installed via package managers.

Description

Reports details about packages installed via package managers

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/01, Modified: 2025/05/07

Plugin Output

tcp/0

Successfully retrieved and stored package data.

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/25/smtp

```
The target TLS server offers no post-quantum ciphers.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/443/www

```
The target TLS server offers no post-quantum ciphers.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/1515

```
The target TLS server offers no post-quantum ciphers.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/55000/www

```
The target TLS server offers no post-quantum ciphers.
```

277653 - Remote Services Using Post-Quantum Ciphers

Synopsis

Reports remote services that offer post-quantum ciphers.

Description

This plugin reports network services that offer post-quantum ciphers and enumerates the post-quantum ciphers that they offer. Tenable makes no attempt to determine whether the remote service is actually hardened against a post-quantum attack.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers the following post-quantum ciphers:
```

```
KEX  
sntrup761x25519-sha512@openssh.com
```

10263 - SMTP Server Detection

Synopsis

An SMTP server is listening on the remote port.

Description

The remote host is running a mail (SMTP) server on this port.

Since SMTP servers are the targets of spammers, it is recommended you disable it if you do not use it.

Solution

Disable this service if you do not use it, or filter incoming traffic to this port.

Risk Factor

None

References

XREF IAVT:0001-T-0932

Plugin Information

Published: 1999/10/12, Modified: 2020/09/22

Plugin Output

tcp/25/smtp

```
Remote SMTP server banner :  
220 wazuh ESMTP Postfix (Ubuntu)
```


42088 - SMTP Service STARTTLS Command Support

Synopsis

The remote mail service supports encrypting traffic.

Description

The remote SMTP service supports the use of the 'STARTTLS' command to switch from a cleartext to an encrypted communications channel.

See Also

<https://en.wikipedia.org/wiki/STARTTLS>

<https://tools.ietf.org/html/rfc2487>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/10/09, Modified: 2019/03/20

Plugin Output

tcp/25/smtp

```
Here is the SMTP service's SSL certificate that Nessus was able to
collect after sending a 'STARTTLS' command :
```

```
----- snip -----
Subject Name:

Common Name: wazuh

Issuer Name:

Common Name: wazuh

Serial Number: 1E 1F DC 1D 00 F7 5D A3 04 DE 00 80 E0 3A 06 F7 11 08 6A 57

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Mar 11 07:59:48 2026 GMT
Not Valid After: Mar 08 07:59:48 2036 GMT
```

Public Key Info:

Algorithm: RSA Encryption

Key Length: 2048 bits

Public Key: 00 9D FC 8E 5B FC 34 15 3D C1 7D 27 C2 44 59 5D C3 E9 29 B4
47 4A 7C 43 1C 2F 6B 93 5E 3D 79 23 C7 52 05 24 3C 4D EE 46
26 F0 84 C2 53 09 27 1C 20 32 0E 64 19 7F EB EA 76 A1 85 62
66 1C 3D 77 4D 69 7D CC 01 C4 3D D9 1D 82 1A A2 F9 2F B5 68
7C 67 17 FC 4A 2E 81 7F 0A AF 42 71 31 7D D2 44 73 30 88 1A
0C 20 C3 53 40 7C DB FE BC 94 F8 9A A0 18 FA C2 BF A7 40 50
71 EB 9F B7 19 9F C8 6C 8E E2 32 2C E6 69 00 FD 0E D8 8E 6A
42 7F F1 75 BA C4 7A 6F 57 E0 C6 83 0F 2A BC 76 DC E1 F1 0A
80 80 33 88 99 D8 58 42 5E 1A 4C 80 C9 F8 80 B5 97 8B 88 0F
F3 FB D9 32 FD 7E 99 C0 70 D4 A1 9C 54 03 8F 7F 46 92 65 F7
2C 1E D0 57 31 6A 37 1B C3 CD 20 A9 65 6E 96 DE DA 7A CD 47
32 BC 27 E7 30 AE AD 5B 7D 14 EA BA 4A 4F 75 B0 7A E1 D2 25
CC BE 18 8F 6F AC 87 81 DF 17 68 7B A5 B4 77 EF CF

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 6B 91 86 D2 23 8E E2 F0 84 E5 58 3E CC 6C 25 82 9A 99 C9
A9 A9 6E 92 BD 82 17 8A C3 FA 0F 2C 9B C9 96 7C 3A 58 D0 03
AF F3 F0 1F 1A 14 D8 95 04 50 BF 1D 1F 31 03 AE 1C 7F BF 4E
B4 E3 73 49 B0 7A 73 A7 55 A6 FB 14 CC CA E5 57 DD AE E1 5F
0B AB 72 C5 D0 3B 2F 8E 9B 4A 06 26 EC B4 F5 07 87 C5 62 73
F2 24 33 AA 50 F8 90 8A 1D 1B AD AB 36 ED B8 83 57 56 C2 38
8F 80 78 4F AA 84 3A 95 E7 43 88 54 A8 93 B5 DD 6E 6C 94 82

[...]

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ecdsa-sha2-nistp256
rsa-sha2-256
rsa-sha2-512
ssh-ed25519
```

The server supports the following options for encryption_algorithms_client_to_server :

```
aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com
```

The server supports the following options for mac_algorithms_server_to_client :

```
hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

The server supports the following options for kex_algorithms :

```
curve25519-sha256
curve25519-sha256@libssh.org
diffie-hellman-group-exchange-sha256
diffie-hellman-group14-sha256
diffie-hellman-group16-sha512
diffie-hellman-group18-sha512
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
ext-info-s
kex-strict-s-v00@openssh.com
sntrup761x25519-sha512@openssh.com
```

The server supports the following options for compression_algorithms_client_to_server :

```
none
zlib@openssh.com
```

The server supports the following options for encryption_algorithms_server_to_client :

```
aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com
```

102094 - SSH Commands Require Privilege Escalation

Synopsis

This plugin reports the SSH commands that failed with a response indicating that privilege escalation is required to run them.

Description

This plugin reports the SSH commands that failed with a response indicating that privilege escalation is required to run them. Either privilege escalation credentials were not provided, or the command failed to run with the provided privilege escalation credentials.

NOTE: Due to limitations inherent to the majority of SSH servers, this plugin may falsely report failures for commands containing error output expected by sudo, such as 'incorrect password', 'not in the sudoers file', or 'not allowed to execute'.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0507

Plugin Information

Published: 2017/08/01, Modified: 2020/09/22

Plugin Output

tcp/0

```
Login account : emin
Commands failed due to privilege escalation failure:
- Escalation account : emin
  Escalation method  : sudo
  Plugins :
    - Plugin Filename : bios_get_info_ssh.nasl
      Plugin ID       : 34098
      Plugin Name      : BIOS Info (SSH)
    - Command : "LC_ALL=C dmidecode"
      Response : "# dmidecode 3.5\n/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nScanning /dev/mem for entry point.\nCan't read memory from /dev/mem"
      Error    : ""
    - Command : "LC_ALL=C /usr/sbin/dmidecode"
      Response : "# dmidecode 3.5\n/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nScanning /dev/mem for entry point.\nCan't read memory from /dev/mem"
      Error    : ""
```

```

- Command : "LC_ALL=C /sbin/dmidecode"
  Response : "# dmidecode 3.5\n/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nScanning /dev/mem for entry point.\nCan't read memory from /dev/mem"
  Error : ""
- Plugin Filename : enumerate_aws_ami_nix.nasl
  Plugin ID : 90191
  Plugin Name : Amazon Web Services EC2 Instance Metadata Enumeration (Unix)
- Command : "/usr/sbin/dmidecode -s system-version 2>&1"
  Response : "/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nCan't read memory from /dev/mem"
  Error : ""
- Plugin Filename : enumerate_oci_nix.nasl
  Plugin ID : 154138
  Plugin Name : Oracle Cloud Infrastructure Instance Metadata Enumeration (Linux / Unix)
- Command : "LC_ALL=C dmidecode -s chassis-asset-tag 2>&1"
  Response : "/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nCan't read memory from /dev/mem"
  Error : ""
- Command : "LC_ALL=C /usr/sbin/dmidecode -s chassis-asset-tag 2>&1"
  Response : "/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nCan't read memory from /dev/mem"
  Error : ""
- Command : "LC_ALL=C /sbin/dmidecode -s chassis-asset-tag 2>&1"
  Response : "/sys/firmware/dmi/tables/smbios_entry_point: Permission denied\nCan't read memo
[...]
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the  
SSH protocol :
```

- 1.99
- 2.0

Synopsis

The remote host supports the SCP protocol over SSH.

Description

The remote host supports the Secure Copy (SCP) protocol over SSH.

See Also

https://en.wikipedia.org/wiki/Secure_copy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/04/26, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_9.6p1 Ubuntu-3ubuntu13.15
SSH supported authentication : publickey,password
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/25/smtp

```
This port supports TLSv1.3/TLSv1.0/TLSv1.1/TLSv1.2.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/443/www

```
This port supports TLSv1.3/TLSv1.2.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/1515

```
This port supports TLSv1.2.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/55000/www

```
This port supports TLSv1.2.
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

```
Subject Name:

Common Name: wazuh

Issuer Name:

Common Name: wazuh

Serial Number: 1E 1F DC 1D 00 F7 5D A3 04 DE 00 80 E0 3A 06 F7 11 08 6A 57

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Mar 11 07:59:48 2026 GMT
Not Valid After: Mar 08 07:59:48 2036 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 9D FC 8E 5B FC 34 15 3D C1 7D 27 C2 44 59 5D C3 E9 29 B4
             47 4A 7C 43 1C 2F 6B 93 5E 3D 79 23 C7 52 05 24 3C 4D EE 46
             26 F0 84 C2 53 09 27 1C 20 32 0E 64 19 7F EB EA 76 A1 85 62
             66 1C 3D 77 4D 69 7D CC 01 C4 3D D9 1D 82 1A A2 F9 2F B5 68
             7C 67 17 FC 4A 2E 81 7F 0A AF 42 71 31 7D D2 44 73 30 88 1A
             0C 20 C3 53 40 7C DB FE BC 94 F8 9A A0 18 FA C2 BF A7 40 50
             71 EB 9F B7 19 9F C8 6C 8E E2 32 2C E6 69 00 FD 0E D8 8E 6A
             42 7F F1 75 BA C4 7A 6F 57 E0 C6 83 0F 2A BC 76 DC E1 F1 0A
             80 80 33 88 99 D8 58 42 5E 1A 4C 80 C9 F8 80 B5 97 8B 88 0F
             F3 FB D9 32 FD 7E 99 C0 70 D4 A1 9C 54 03 8F 7F 46 92 65 F7
             2C 1E D0 57 31 6A 37 1B C3 CD 20 A9 65 6E 96 DE DA 7A CD 47
```



```
32 BC 27 E7 30 AE AD 5B 7D 14 EA BA 4A 4F 75 B0 7A E1 D2 25
CC BE 18 8F 6F AC 87 81 DF 17 68 7B A5 B4 77 EF CF
Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits
Signature: 00 6B 91 86 D2 23 8E E2 F0 84 E5 58 3E CC 6C 25 82 9A 99 C9
A9 A9 6E 92 BD 82 17 8A C3 FA 0F 2C 9B C9 96 7C 3A 58 D0 03
AF F3 F0 1F 1A 14 D8 95 04 50 BF 1D 1F 31 03 AE 1C 7F BF 4E
B4 E3 73 49 B0 7A 73 A7 55 A6 FB 14 CC CA E5 57 DD AE E1 5F
0B AB 72 C5 D0 3B 2F 8E 9B 4A 06 26 EC B4 F5 07 87 C5 62 73
F2 24 33 AA 50 F8 90 8A 1D 1B AD AB 36 ED B8 83 57 56 C2 38
8F 80 78 4F AA 84 3A 95 E7 43 88 54 A8 93 B5 DD 6E 6C 94 82
EE 3E A3 2B 43 AC 3C 31 8C 8C B5 91 98 FF 78 AD 03 A5 D8 AA
A5 B6 0F 63 A7 E7 CC 5F 34 4C 60 1E 1C B7 B0 D3 44 9B F5 5C
F5 DE 8D 85 6A CB 91 6A 76 [...]
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/443/www

```
Subject Name:

Country: US
Locality: California
Organization: Wazuh
Organization Unit: Wazuh
Common Name: wazuh-dashboard

Issuer Name:

Organization Unit: Wazuh
Organization: Wazuh
Locality: California

Serial Number: 66 D9 9D 94 D4 FD BD CC A1 82 74 30 47 5D 40 72 51 CF 65 B3

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Mar 10 12:56:34 2026 GMT
Not Valid After: Mar 07 12:56:34 2036 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 BB F9 3A 40 9F B7 41 06 14 D4 F3 65 77 03 BA 82 2B 78 82
             C7 DC A0 50 DD 43 E1 A8 DA 2F F8 1E FA 63 C4 DD 6D D2 A5 33
             91 7B C8 6D DE 33 1A 02 C9 E2 C0 84 36 FB 0C 92 86 B4 AE 7E
             19 64 A6 53 DD AF 50 35 77 46 77 44 D1 82 BF 4E EA 96 93 D0
             C9 18 75 60 8C CA 61 56 C2 BA 25 67 40 D5 56 61 B6 5E CC 08
```

```
36 37 2A C9 B0 67 DE 82 EB D2 18 9A 79 C3 F1 03 16 1D 85 C6
5E A4 0E 7A CC B0 AA 32 F6 42 D1 B3 1C 4B B1 8D 54 CD E3 3A
AC DC CC 93 9E 41 17 DA 37 2A 81 D5 D1 46 53 47 5C C1 0E FE
71 68 C0 EC E0 DC EC A7 64 49 CD B3 EA 16 85 78 23 7F 7E 7F
51 EE 17 1A C2 24 99 D3 A7 C9 E7 E3 5E CB 82 B9 35 82 F2 C0
6F C4 D3 AD 4F 2A 5F 96 EB 95 0E A6 B7 45 C1 11 28 01 1A 9C
E3 61 FF E1 88 FF 71 8D 6B 6F C2 A1 4A 28 A5 56 FE 16 C2 CE
DB 2B 76 46 41 71 FF 25 E8 3D 45 24 1A FD F8 63 C3
```

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 76 69 74 94 EF D8 27 F9 66 C8 B7 B8 1E 59 63 FB A7 F4 4F
1C 4F 2B 06 16 A4 46 C3 41 32 6A 91 16 2A 5C A2 A7 2C D6 E4
DB FE 2B A4 F5 F5 29 DA 9E 6A F5 FC 57 8E 45 27 BD F4 87 FF
06 9D 07 40 C8 50 7F EE 6B EB D7 7F 8C FA 5B 5A 8C B7 20 0C
D6 82 17 2D 92 0C 56 46 E5 2B D7 63 73 04 72 63 2B 45 EB 96
DE FB DE 6E 72 7B 8B 64 DD 68 32 53 F2 CC F0 FA DD 50 41 94
30 76 16 C4 7B 39 10 69 4A 82 AE EC 55 B2 5F 67 5C 5A 5B 4E
7D 4B E5 D0 6A 47 23 F5 B7 D6 84 96 [...]

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/1515

```
Subject Name:

Country: US
State/Province: California
Common Name: Wazuh

Issuer Name:

Country: US
State/Province: California
Common Name: Wazuh

Serial Number: 39 9F 5E E1 70 18 BE 1D E7 9D 81 2F 24 AD 56 1C C1 29 46 01

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Mar 10 12:57:56 2026 GMT
Not Valid After: Mar 10 12:57:56 2027 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 C5 38 C8 D0 6C BF 43 F8 8F 37 FD 7C FD 13 28 76 C7 4B E0
            D5 AF BD 7B 5F AB FB F3 95 B7 48 8D F4 FA 5E 02 EE FA 8B 7C
            9A B5 87 CC FA D4 6E 16 F4 A3 66 06 29 43 EF D7 C1 16 E4 7C
            D1 99 1D 48 EB 8C C6 2C DE 43 43 42 18 96 CA DC 41 3D F6 3F
            D4 01 80 BD 4F BA 54 57 F0 E0 F9 4D 84 8A 22 CF 64 98 EB 9A
            9A 15 1B 41 E0 C0 8F 01 72 CD 36 46 02 73 33 81 44 1E 91 4C
            3F 07 C4 88 2A 99 42 6E 74 37 B8 95 08 BC 30 A9 8C BD 3A 5F
```

```
0E 39 F8 5E 4F 65 AC 50 0E E3 AB 37 44 87 B8 30 67 3B 73 30
05 E7 CF 7A B4 DD 89 F5 C7 F6 E8 BB 5C D4 A4 90 31 89 FC 49
CF E8 4D 12 16 9B 10 3A 02 0E A9 B4 B4 9A 2F B7 46 03 4D F4
3C DF A9 0C 71 D3 AF C9 55 7E 39 88 47 D9 0E 97 FC 61 E0 8C
9B 5A E9 72 00 CA E6 5E 85 C7 95 A7 10 FA A2 D0 BB A0 FC CB
E5 66 E3 91 1C 54 FD 05 A1 E6 02 92 82 5D 10 20 F3
```

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 37 C3 30 C2 B2 6E 01 A8 FF 03 92 40 B0 7C 39 42 84 54 77
64 3A 18 24 BA 64 14 25 D9 CD 95 8F E8 D1 1D 15 9F 65 D4 AF
EC 68 5F 79 3E CC 79 EE 54 30 1C 73 AC B2 B6 83 56 5B D5 14
D3 2C 8A EE 27 09 1B 00 47 A4 24 E4 DC F5 D7 AB 91 56 4E 56
6D ED 92 AC E4 CE 5E D7 F2 F1 DD A5 D3 59 DD 69 73 69 86 9F
E4 CE CC A2 7F 2D B5 4E B9 43 E4 78 BD 82 F1 87 B8 7F BB 2A
FC 30 35 CB AE 38 D4 65 AC CB 76 8B 88 E5 3D 96 E2 85 47 A7
A4 48 55 08 E7 83 E1 F0 83 F8 CA 61 56 52 0F CA D3 E6 06 11
3F 1D 85 1B E0 45 0D [...]

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/55000/www

```
Subject Name:

Country: US
State/Province: California
Locality: San Francisco
Organization: Wazuh
Common Name: wazuh.com

Issuer Name:

Country: US
State/Province: California
Locality: San Francisco
Organization: Wazuh
Common Name: wazuh.com

Serial Number: 75 08 18 94 A0 B6 4C 47 1A 3E 12 FA B5 53 66 9C 1D 5F 94 94

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Mar 10 12:58:22 2026 GMT
Not Valid After: Mar 10 12:58:22 2027 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 AC F3 9A 90 F5 78 7F 11 03 F2 00 C9 97 4E CC 85 FD C8 E1
             FF 64 E8 9D C9 22 78 E5 B0 8F 26 93 66 D2 58 B4 4A 59 82 19
             F2 A1 05 79 F2 70 E9 A7 EF EE 2B BD 9D 5A D6 60 1E AB 61 4C
```

```
FE 10 EE BE C1 2C BA 9E B1 D6 B4 71 20 07 50 FD DC 8C 80 91
D7 CC 96 71 DE 8E C0 D3 85 BE 58 B1 45 14 F0 7D 4C 56 88 F5
6A 53 26 7E C0 6B 5A C4 D8 89 5C 19 54 E8 E6 55 66 0C 63 07
00 71 48 42 5B 59 95 94 1A 6A FB 7A 00 07 0A BE 61 46 54 14
A4 27 32 DA 0E 2B DF 10 E3 BA 2F F3 F2 F1 F6 F2 20 FD BE 93
F4 A8 A3 A0 2C 08 D4 B5 5C 28 DC CC 2F 7E C0 9C 7C 7D F7 0F
58 52 F4 3C E8 11 FC C1 D9 7D 52 A5 D6 14 84 C6 00 B4 C7 5F
B0 41 72 0F D0 8B E7 02 9A 37 08 20 8C 35 4B AC D1 95 51 94
DA 9D 3E F8 FE 46 EF 41 5D 45 10 B6 CF 74 19 27 F0 49 C0 42
E8 6F D0 59 86 F7 BE 45 4A 4F 2D C1 E0 85 8B 27 75
```

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 8A B8 F1 63 5E DB 12 EE 4A E8 67 29 2F FB 33 5C 39 0F F5
1C 0B 93 74 5F A4 60 2E 9A 3E D2 F1 42 5C 6B 6D E1 1A 7F 9A
66 49 0A 68 99 4E 25 A1 F2 33 CD D0 05 DB 84 53 7F B4 0C 20
B0 73 A9 E3 8A 84 2F 97 6B D8 5D C4 64 B1 6B 91 A8 F8 59 E0
37 08 A1 1B 63 FB A9 81 02 45 FF 49 C4 81 8C AB 8A 61 06 EC
6D 6B 26 2E 8A 66 D9 E7 D0 BC E3 60 FB B9 FD D4 EC 4F D9 63
8B 0C 20 34 A6 40 C3 91 DA 48 6A FE BE 60 EA ED 0C 64 82 85

[...]

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

Here is the list of SSL CBC ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-CAMELLIA-CBC-128 SHA256	0xC0, 0x76	ECDHE	RSA	Camellia-CBC(128)	
ECDHE-RSA-CAMELLIA-CBC-256 SHA384	0xC0, 0x77	ECDHE	RSA	Camellia-CBC(256)	
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)	
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)	

DHE-RSA-AES256-SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)
SHA256				
DHE-RSA-CAMELLIA128-SHA	0x00, 0x45	DHE	RSA	Camellia-CBC(128)
SHA1				
DHE-RSA-CAMELLIA128-SHA256	0x00, 0xBE	DHE	RSA	Camellia-CBC(128)
SHA256				
DHE-RSA-CAMELLIA256-SHA	0x00, 0x88	DHE	RSA	Camellia-CBC(256)
SHA1				
DHE-RSA-CAMELLIA256-SHA256	0x00, 0xC4	DHE	RSA	Camellia-CBC(256)
SHA256				
ADH-AES128-SHA	0x00, 0x34	DH	None	AES-CBC(128)
SHA1				
ADH-AES128-SHA256	0x00, 0x6C	DH	None	AES-CBC(128)
SHA256				
ADH-AES256-SHA	0x00, 0x3A	DH	None	AES-CBC(256)
SHA1				
ADH-AES256-SHA256	0x00, 0x6D	DH	None	AES-CBC(256)
SHA256				
ADH-CAMELLIA128-SHA	0x00, 0x46	DH	None	Camellia-CBC(128)
SHA1				
ADH-CAMELLIA128-SHA256	0x00, 0xBF	DH	None	Camellia-CBC(128)
SHA256				
ADH-CAMELLIA256-SHA	0x00, 0x89	DH	None	Camellia-C [...]

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/443/www

Here is the list of SSL CBC ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					

RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/1515

Here is the list of SSL CBC ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					

RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/55000/www

Here is the list of SSL CBC ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					

RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

```
Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1.3
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
TLS_AES_128_GCM_SHA256	0x13, 0x01	-	-	AES-GCM(128)	
SHA256					
TLS_AES_256_GCM_SHA384	0x13, 0x02	-	-	AES-GCM(256)	
SHA384					
TLS_CHACHA20_POLY1305_SHA256	0x13, 0x03	-	-	ChaCha20-Poly1305(256)	
SHA256					

```
SSL Version : TLSv1.2
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES-128-CCM-AEAD	0xC0, 0x9E	DHE	RSA	AES-CCM(128)	
SHA-256					

DHE-RSA-AES-128-CCM8-AEAD SHA-256	0xC0, 0xA2	DHE	RSA	AES-CCM8(128)
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x9E	DHE	RSA	AES-GCM(128)
DHE-RSA-AES-256-CCM-AEAD SHA-384	0xC0, 0x9F	DHE	RSA	AES-CCM(256)
DHE-RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA3	DHE	RSA	AES-CCM8(256)
DHE-RSA-AES256-SHA384 SHA384	0x00, 0x9F	DHE	RSA	AES-GCM(256)
DHE-RSA-CHACHA20-POLY1305 SHA256	0xCC, 0xAA	DHE	RSA	ChaCha20-Poly1305(256)
DH-AES128-SHA256 SHA256	0x00, 0xA6	DH	None	AES-GCM(128)
DH-AES256-SHA384 SHA384	0x00, 0xA7	DH	None	AES-GCM(256)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	E [...]		

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/443/www

```
Here is the list of SSL ciphers supported by the remote server :  
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1.3
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
TLS_AES_128_GCM_SHA256	0x13, 0x01	-	-	AES-GCM(128)	
SHA256					
TLS_AES_256_GCM_SHA384	0x13, 0x02	-	-	AES-GCM(256)	
SHA384					
TLS_CHACHA20_POLY1305_SHA256	0x13, 0x03	-	-	ChaCha20-Poly1305(256)	
SHA256					

```
SSL Version : TLSv1.2
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					

ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)
ECDHE-RSA-CHACHA20-POLY1305 SHA256	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)
RSA-AES-128-CCM-AEAD SHA-256	0xC0, 0x9C	RSA	RSA	AES-CCM(128)
RSA-AES-128-CCM8-AEAD SHA-256	0xC0, 0xA0	RSA	RSA	AES-CCM8(128)
RSA-AES128-SHA256 SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)
RSA-AES-256-CCM-AEAD SHA-384	0xC0, 0x9D	RSA	RSA	AES-CCM(256)
RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA1	RSA	RSA	AES-CCM8(256)
RSA-AES256-SHA384 SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)
ECDHE-RSA-AES128-SHA SHA1	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECD [...]		

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/1515

```
Here is the list of SSL ciphers supported by the remote server :  
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1.2
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-CHACHA20-POLY1305	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)	
SHA256					
RSA-AES-128-CCM-AEAD	0xC0, 0x9C	RSA	RSA	AES-CCM(128)	
SHA-256					
RSA-AES-128-CCM8-AEAD	0xC0, 0xA0	RSA	RSA	AES-CCM8(128)	
SHA-256					
RSA-AES128-SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
SHA256					
RSA-AES-256-CCM-AEAD	0xC0, 0x9D	RSA	RSA	AES-CCM(256)	
SHA-384					

RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA1	RSA	RSA	AES-CCM8(256)
RSA-AES256-SHA384 SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)
ECDHE-RSA-AES128-SHA SHA1	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)
AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC(128)
RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)
RSA-AES256-S [...]				

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/55000/www

```
Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1.2
```

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-CHACHA20-POLY1305	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)	
SHA256					
RSA-AES128-SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
SHA256					
RSA-AES256-SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					

ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)
AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC(128)
RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/25/smtp

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES-128-CCM-AEAD SHA-256	0xC0, 0x9E	DHE	RSA	AES-CCM(128)	
DHE-RSA-AES-128-CCM8-AEAD SHA-256	0xC0, 0xA2	DHE	RSA	AES-CCM8(128)	
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x9E	DHE	RSA	AES-GCM(128)	
DHE-RSA-AES-256-CCM-AEAD SHA-384	0xC0, 0x9F	DHE	RSA	AES-CCM(256)	
DHE-RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA3	DHE	RSA	AES-CCM8(256)	

DHE-RSA-AES256-SHA384 SHA384	0x00, 0x9F	DHE	RSA	AES-GCM(256)
DHE-RSA-CHACHA20-POLY1305 SHA256	0xCC, 0xAA	DHE	RSA	ChaCha20-Poly1305(256)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)
ECDHE-RSA-CAMELLIA-CBC-128 SHA256	0xC0, 0x76	ECDHE	RSA	Camellia-CBC(128)
ECDHE-RSA-CAMELLIA-CBC-256 SHA384	0xC0, 0x77	ECDHE	RSA	Camellia-CBC(256)
ECDHE-RSA-CHACHA20-POLY1305 SHA256	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)
DHE-RSA-AES256-SHA256 SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)
DHE-RSA-CAMELLIA128-SHA	0x00, 0x45	DHE	RSA	[...]

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/443/www

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-CHACHA20-POLY1305	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)	
SHA256					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					

ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/1515

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-CHACHA20-POLY1305	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)	
SHA256					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					

ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)

The fields above are :

{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/55000/www

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-CHACHA20-POLY1305	0xCC, 0xA8	ECDHE	RSA	ChaCha20-Poly1305(256)	
SHA256					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					

ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

94761 - SSL Root Certification Authority Certificate Information

Synopsis

A root Certification Authority certificate was found at the top of the certificate chain.

Description

The remote service uses an SSL certificate chain that contains a self-signed root Certification Authority certificate at the top of the chain.

See Also

[https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2003/cc778623\(v=ws.10\)](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2003/cc778623(v=ws.10))

Solution

Ensure that use of this root Certification Authority certificate complies with your organization's acceptable use and security policies.

Risk Factor

None

Plugin Information

Published: 2016/11/14, Modified: 2018/11/15

Plugin Output

tcp/1515

The following root Certification Authority certificate was found :

```
| -Subject           : C=US/ST=California/CN=Wazuh
| -Issuer            : C=US/ST=California/CN=Wazuh
| -Valid From        : Mar 10 12:57:56 2026 GMT
| -Valid To          : Mar 10 12:57:56 2027 GMT
| -Signature Algorithm : SHA-256 With RSA Encryption
```


156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/25/smtp

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	----	----	-----	----
DHE-RSA-AES-128-CCM-AEAD SHA-256	0xC0, 0x9E	DHE	RSA	AES-CCM(128)	
DHE-RSA-AES-128-CCM8-AEAD SHA-256	0xC0, 0xA2	DHE	RSA	AES-CCM8(128)	
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x9E	DHE	RSA	AES-GCM(128)	
DHE-RSA-AES-256-CCM-AEAD SHA-384	0xC0, 0x9F	DHE	RSA	AES-CCM(256)	
DHE-RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA3	DHE	RSA	AES-CCM8(256)	
DHE-RSA-AES256-SHA384 SHA384	0x00, 0x9F	DHE	RSA	AES-GCM(256)	
DH-AES128-SHA256 SHA256	0x00, 0xA6	DH	None	AES-GCM(128)	
DH-AES256-SHA384 SHA384	0x00, 0xA7	DH	None	AES-GCM(256)	
ECDHE-RSA-CAMELLIA-CBC-128 SHA256	0xC0, 0x76	ECDHE	RSA	Camellia-CBC(128)	
ECDHE-RSA-CAMELLIA-CBC-256 SHA384	0xC0, 0x77	ECDHE	RSA	Camellia-CBC(256)	
RSA-AES-128-CCM-AEAD SHA-256	0xC0, 0x9C	RSA	RSA	AES-CCM(128)	
RSA-AES-128-CCM8-AEAD SHA-256	0xC0, 0xA0	RSA	RSA	AES-CCM8(128)	
RSA-AES128-SHA256 SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
RSA-AES-256-CCM-AEAD SHA-384	0xC0, 0x9D	RSA	RSA	AES-CCM(256)	
RSA-AES-256-CCM8-AEAD SHA-384	0xC0, 0xA1	RSA	RSA	AES-CCM8(256)	
RSA-AES256-SHA384 SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
DHE-RSA-AES128-SHA	[...]				

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/443/www

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	----	----	-----	----
RSA-AES-128-CCM-AEAD	0xC0, 0x9C	RSA	RSA	AES-CCM(128)	
SHA-256					
RSA-AES-128-CCM8-AEAD	0xC0, 0xA0	RSA	RSA	AES-CCM8(128)	
SHA-256					
RSA-AES128-SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
SHA256					
RSA-AES-256-CCM-AEAD	0xC0, 0x9D	RSA	RSA	AES-CCM(256)	
SHA-384					
RSA-AES-256-CCM8-AEAD	0xC0, 0xA1	RSA	RSA	AES-CCM8(256)	
SHA-384					
RSA-AES256-SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
RSA-AES128-SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)	
SHA256					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RSA-AES256-SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)	
SHA256					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/1515

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	----
RSA-AES-128-CCM-AEAD	0xC0, 0x9C	RSA	RSA	AES-CCM(128)	
SHA-256					
RSA-AES-128-CCM8-AEAD	0xC0, 0xA0	RSA	RSA	AES-CCM8(128)	
SHA-256					
RSA-AES128-SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
SHA256					
RSA-AES-256-CCM-AEAD	0xC0, 0x9D	RSA	RSA	AES-CCM(256)	
SHA-384					
RSA-AES-256-CCM8-AEAD	0xC0, 0xA1	RSA	RSA	AES-CCM8(256)	
SHA-384					
RSA-AES256-SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
RSA-AES128-SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)	
SHA256					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RSA-AES256-SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)	
SHA256					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/55000/www

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	----	----	-----	----
RSA-AES128-SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
SHA256					
RSA-AES256-SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
SHA384					
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES128-SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)	
SHA256					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
ECDHE-RSA-AES256-SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)	
SHA384					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
RSA-AES128-SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)	
SHA256					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RSA-AES256-SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)	
SHA256					

The fields above are :

```
{Tenable ciphernam}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```


22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/25/smtp

```
An SMTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/443/www

```
A TLSv1.3 server answered on this port.
```

tcp/443/www

```
A web server is running on this port through TLSv1.3.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/1515

```
A TLSv1.3 server answered on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/55000/www

```
A TLSv1.2 server answered on this port.
```

tcp/55000/www

```
A web server is running on this port through TLSv1.2.
```

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

<http://www.nessus.org/u?54fba2c1>

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The TLS service on port 443/TLSv1.2 offers these ciphers vulnerable to Shor's:
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
```

```
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_128_CCM_8
TLS_RSA_WITH_AES_256_CCM
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
```

The TLS service on port 55000/TLSv1.2 offers these ciphers vulnerable to Shor's:

```
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
```

The TLS service on port 1515/TLSv1.2 offers these ciphers vulnerable to Shor's:

```
TLS_RSA_WITH_AES_256_CCM_8
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_RSA_WITH_AES_128_CCM
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_128_CCM_8
TLS_RSA_WITH_AES_256_CCM
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
```

The SSH service on port 22 offers these ciphers vulnerable to Shor's:

```
diffie-hellman-group-exchange-sha256
curve25519-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.or [...]
```

22869 - Software Enumeration (SSH)

Synopsis

It was possible to enumerate installed software on the remote host via SSH.

Description

Nessus was able to list the software installed on the remote host by calling the appropriate command (e.g., 'rpm -qa' on RPM-based Linux distributions, dpkg, etc.).

Solution

Remove any software that is not in compliance with your organization's acceptable use and security policies.

Risk Factor

None

References

XREF IAVT:0001-T-0502

Plugin Information

Published: 2006/10/15, Modified: 2025/03/26

Plugin Output

tcp/0

Here is the list of packages installed on the remote Debian Linux system :

```
ii  adduser  3.137ubuntu1  all  add and remove users and groups
ii  amd64-microcode  3.20250311.1ubuntu0.24.04.1  amd64  Processor microcode firmware for AMD CPUs
ii  apparmor  4.0.1really4.0.1-0ubuntu0.24.04.5  amd64  user-space parser utility for AppArmor
ii  apport  2.28.1-0ubuntu3.8  all  automatically generate crash reports for debugging
ii  apport-core-dump-handler  2.28.1-0ubuntu3.8  all  Kernel core dump handler for Apport
ii  apport-symptoms  0.25  all  symptom scripts for apport
ii  appstream  1.0.2-1build6  amd64  Software component metadata management
ii  apt  2.8.3  amd64  commandline package manager
ii  apt-transport-https  2.8.3  all  transitional package for https support
ii  apt-utils  2.8.3  amd64  package management related utility programs
ii  base-files  13ubuntu10.4  amd64  Debian base system miscellaneous files
ii  base-passwd  3.6.3build1  amd64  Debian base system master password and group files
ii  bash  5.2.21-2ubuntu4  amd64  GNU Bourne Again SHell
ii  bash-completion  1:2.11-8  all  programmable completion for the bash shell
ii  bc  1.07.1-3ubuntu4  amd64  GNU bc arbitrary precision calculator language
ii  bcache-tools  1.0.8-5build1  amd64  bcache userspace tools
ii  bind9-dnsutils  1:9.18.39-0ubuntu0.24.04.3  amd64  Clients provided with BIND 9
ii  bind9-host  1:9.18.39-0ubuntu0.24.04.3  amd64  DNS Lookup Utility
ii  bind9-libs  1:9.18.39-0ubuntu0.24.04.3  amd64  Shared Libraries used by BIND 9
```



```
ii bolt 0.9.7-1 amd64 system daemon to manage thunderbolt 3 devices
ii bpfcc-tools 0.29.1+ds-1ubuntu7 all tools for BPF Compiler Collection (BCC)
ii bpftrace 0.20.2-1ubuntu4.3 amd64 high-level tracing language for Linux eBPF
ii bsdextrautils 2.39.3-9ubuntu6.5 amd64 extra utilities from 4.4BSD-Lite
ii bsduutils 1:2.39.3-9ubuntu6.5 amd64 basic utilities from 4.4BSD-Lite
ii btrfs-progs 6.6.3-1.1build2 amd64 Checksumming Copy [...]
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

84821 - TLS ALPN Supported Protocol Enumeration

Synopsis

The remote host supports the TLS ALPN extension.

Description

The remote host supports the TLS ALPN extension. This plugin enumerates the protocols the extension supports.

See Also

<https://tools.ietf.org/html/rfc7301>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/07/17, Modified: 2024/09/11

Plugin Output

tcp/443/www

```
http/1.1
```

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

These are the TLS supported groups offered by the remote server :

TLS supported groups :

Name	Code
-----	-----
ffdhe3072	0x0101
ffdhe2048	0x0100
secp256r1	0x0017
x448	0x001e
secp384r1	0x0018
secp521r1	0x0019
x25519	0x001d

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/443/www

These are the TLS supported groups offered by the remote server :

TLS supported groups :

Name	Code
-----	-----
secp256r1	0x0017
x448	0x001e
secp384r1	0x0018
secp521r1	0x0019
x25519	0x001d

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/1515

```
These are the TLS supported groups offered by the remote server :
```

```
TLS supported groups :
```

Name	Code
-----	-----
secp256r1	0x0017
x448	0x001e
secp384r1	0x0018
x25519	0x001d
secp521r1	0x0019

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/55000/www

These are the TLS supported groups offered by the remote server :

TLS supported groups :

Name	Code
-----	-----
secp256r1	0x0017
x448	0x001e
secp384r1	0x0018
secp521r1	0x0019
x25519	0x001d

121010 - TLS Version 1.1 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1.

TLS 1.1 lacks support for current and recommended cipher suites.

Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

None

References

XREF CWE:327

Plugin Information

Published: 2019/01/08, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

```
TLSv1.1 is enabled and the server supports at least one cipher.
```


136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

```
TLSv1.2 is enabled and the server supports at least one cipher.
```

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2026/04/13

Plugin Output

tcp/443/www

```
TLSv1.2 is enabled and the server supports at least one cipher.
```

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2026/04/13

Plugin Output

tcp/1515

```
TLSv1.2 is enabled and the server supports at least one cipher.
```

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2026/04/13

Plugin Output

tcp/55000/www

```
TLSv1.2 is enabled and the server supports at least one cipher.
```

138330 - TLS Version 1.3 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.3.

See Also

<https://tools.ietf.org/html/rfc8446>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/07/09, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

```
TLSv1.3 is enabled and the server supports at least one cipher.
```

138330 - TLS Version 1.3 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.3.

See Also

<https://tools.ietf.org/html/rfc8446>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/07/09, Modified: 2026/04/13

Plugin Output

tcp/443/www

```
TLSv1.3 is enabled and the server supports at least one cipher.
```

110385 - Target Credential Issues by Authentication Protocol - Insufficient Privilege

Synopsis

Nessus was able to log in to the remote host using the provided credentials. The provided credentials were not sufficient to complete all requested checks.

Description

Nessus was able to execute credentialed checks because it was possible to log in to the remote host using provided credentials, however the credentials were not sufficiently privileged to complete all requested checks.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0502

Plugin Information

Published: 2018/06/06, Modified: 2024/03/25

Plugin Output

tcp/22/ssh

Nessus was able to log into the remote host, however this credential did not have sufficient privileges for all planned checks :

User: 'emin'
Port: 22
Proto: SSH
Method: password
Escalation: sudo

See the output of the following plugin for details :

Plugin ID : 102094
Plugin Name : SSH Commands Require Privilege Escalation

141118 - Target Credential Status by Authentication Protocol - Valid Credentials Provided

Synopsis

Valid credentials were provided for an available authentication protocol.

Description

Nessus was able to determine that valid credentials were provided for an authentication protocol available on the remote target because it was able to successfully authenticate directly to the remote target using that authentication protocol at least once. Authentication was successful because the authentication protocol service was available remotely, the service was able to be identified, the authentication protocol was able to be negotiated successfully, and a set of credentials provided in the scan policy for that authentication protocol was accepted by the remote service. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/10/15, Modified: 2024/03/25

Plugin Output

tcp/22/ssh

```
Nessus was able to log in to the remote host via the following :
```

```
User:      'emin'  
Port:      22  
Proto:     SSH  
Method:    password  
Escalation: sudo
```


56468 - Time of Last System Startup

Synopsis

The system has been started.

Description

Using the supplied credentials, Nessus was able to determine when the host was last started.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/10/12, Modified: 2018/06/19

Plugin Output

tcp/0

```
reboot system boot 6.8.0-107-generi Tue Apr 14 09:20 still running
reboot system boot 6.8.0-107-generi Tue Apr 14 08:21 still running
reboot system boot 6.8.0-107-generi Mon Apr 13 19:17 still running
reboot system boot 6.8.0-107-generi Mon Apr 13 07:58 - 08:37 (00:39)
reboot system boot 6.8.0-107-generi Fri Apr 10 12:53 - 08:37 (2+19:44)
reboot system boot 6.8.0-107-generi Fri Apr 10 12:43 - 12:47 (00:04)
reboot system boot 6.8.0-107-generi Fri Apr 10 12:28 - 12:38 (00:10)
reboot system boot 6.8.0-107-generi Thu Apr 9 09:38 - 12:38 (1+03:00)
reboot system boot 6.8.0-107-generi Thu Apr 9 09:29 - 09:37 (00:08)
reboot system boot 6.8.0-107-generi Thu Apr 9 08:03 - 09:37 (01:33)
reboot system boot 6.8.0-107-generi Wed Apr 8 13:37 - 09:37 (19:59)
reboot system boot 6.8.0-107-generi Tue Apr 7 15:55 - 09:37 (1+17:42)
reboot system boot 6.8.0-107-generi Tue Apr 7 07:47 - 09:37 (2+01:50)
reboot system boot 6.8.0-107-generi Mon Apr 6 14:52 - 09:37 (2+18:44)
reboot system boot 6.8.0-107-generi Mon Apr 6 10:43 - 09:37 (2+22:53)
reboot system boot 6.8.0-107-generi Mon Apr 6 07:48 - 09:37 (3+01:49)
reboot system boot 6.8.0-107-generi Sun Apr 5 20:36 - 09:37 (3+13:01)
reboot system boot 6.8.0-107-generi Sun Apr 5 20:27 - 09:37 (3+13:10)
reboot system boot 6.8.0-107-generi Sun Apr 5 20:20 - 09:37 (3+13:17)
reboot system boot 6.8.0-106-generi Sat Apr 4 12:46 - 09:37 (4+20:50)
reboot system boot 6.8.0-106-generi Fri Apr 3 19:24 - 09:37 (5+14:12)
reboot system boot 6.8.0-106-generi Fri Apr 3 19:03 - 09:37 (5+14:34)
reboot system boot 6.8.0-106-generi Fri Apr 3 17:46 - 09:37 (5+15:50)
reboot system boot 6.8.0-106-generi Fri Apr 3 16:55 - 09:37 (5+16:41)
reboot system boot 6.8.0-106-generi Fri Apr 3 16:14 - 09:37 (5+17:22)
reboot system boot 6.8.0-106-generi Fri Apr 3 15:54 - 16:14 (00:19)
reboot system boot 6.8.0-106-generi Fri Apr 3 15:15 - 16:14 (00:58)
reboot [...]
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

```
For your information, here is the traceroute from 192.168.60.10 to 192.168.50.10 :  
192.168.60.10  
192.168.60.254  
192.168.50.10
```

```
Hop Count: 2
```

192709 - Tukaani XZ Utils Installed (Linux / Unix)

Synopsis

Tukaani XZ Utils is installed on the remote Linux / Unix host.

Description

Tukaani XZ Utils is installed on the remote Linux / Unix host.

XZ Utils consists of several components, including:

- liblzma
- xz

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.192709' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://xz.tukaani.org/xz-utils/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/03/29, Modified: 2026/04/13

Plugin Output

tcp/0

```
Nessus detected 2 installs of XZ Utils:

Path           : /usr/bin/xz
Version        : 5.6.1
Associated Package : xz-utils 5.6.1
Confidence     : High
```

```
Managed by OS      : True
Version Source     : Package

Path               : /usr/lib/x86_64-linux-gnu/liblzma.so.5.4.5
Version            : 5.6.1
Associated Package : liblzma5 5.6.1
Confidence         : High
Managed by OS     : True
Version Source     : Package
```

198218 - Ubuntu Pro Subscription Detection

Synopsis

The remote Ubuntu host has an active Ubuntu Pro subscription.

Description

The remote Ubuntu host has an active Ubuntu Pro subscription.

See Also

<https://documentation.ubuntu.com/pro/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/31, Modified: 2024/07/05

Plugin Output

tcp/0

```
This machine is NOT attached to an Ubuntu Pro subscription. However, it may have previously been attached.
```

```
The following details were gathered from /var/lib/ubuntu-advantage/status.json:
```

```
Binary Path      : /var/lib/ubuntu-advantage
Binary Version   : 37.1ubuntu0~24.04
```

110483 - Unix / Linux Running Processes Information

Synopsis

Uses `/bin/ps auxww` command to obtain the list of running processes on the target machine at scan time.

Description

Generated report details the running processes on the target machine at scan time.

This plugin is informative only and could be used for forensic investigation, malware detection, and to confirm that your system processes conform to your system policies.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/06/12, Modified: 2023/11/27

Plugin Output

tcp/0

USER	PID	%CPU	%MEM	VSZ	RSS	TTY	STAT	START	TIME	COMMAND
root	1	0.2	0.3	22140	13512	?	Ss	09:20	0:01	/usr/lib/systemd/systemd --system
--deserialize=79										
root	2	0.0	0.0	0	0	?	S	09:20	0:00	[kthreadd]
root	3	0.0	0.0	0	0	?	S	09:20	0:00	[pool_workqueue_release]
root	4	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/R-rcu_g]
root	5	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/R-rcu_p]
root	6	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/R-slub_]
root	7	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/R-netns]
root	9	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/0:0H-kblockd]
root	11	0.0	0.0	0	0	?	I	09:20	0:00	[kworker/u256:0-ext4-rsv-
conversion]										
root	12	0.0	0.0	0	0	?	I<	09:20	0:00	[kworker/R-mm_pe]
root	13	0.0	0.0	0	0	?	I	09:20	0:00	[rcu_tasks_kthread]
root	14	0.0	0.0	0	0	?	I	09:20	0:00	[rcu_tasks_rude_kthread]
root	15	0.0	0.0	0	0	?	I	09:20	0:00	[rcu_tasks_trace_kthread]
root	16	0.0	0.0	0	0	?	S	09:20	0:00	[ksoftirqd/0]
root	17	0.0	0.0	0	0	?	I	09:20	0:00	[rcu_preempt]
root	18	0.0	0.0	0	0	?	S	09:20	0:00	[migration/0]
root	19	0.0	0.0	0	0	?	S	09:20	0:00	[idle_inject/0]
root	20	0.0	0.0	0	0	?	S	09:20	0:00	[cpuhp/0]
root	21	0.0	0.0	0	0	?	S	09:20	0:00	[cpuhp/1]
root	22	0.0	0.0	0	0	?	S	09:20	0:00	[idle_inject/1]
root	23	0.0	0.0	0	0	?	S	09:20	0:00	[migration/1]
root	24	0.0	0.0	0	0	?	S	09:20	0:00	[ksoftirqd/1]
root	26	0.0	0.0	0	0	?	I<	09:20	0:00	[kw [...]

152743 - Unix Software Discovery Commands Not Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials, but encountered difficulty running commands used to find unmanaged software.

Description

Nessus found problems running commands on the target host which are used to find software that is not managed by the operating system.

Details of the issues encountered are reported by this plugin.

Failure to properly execute commands used to find and characterize unmanaged software on the target host can lead to scans that do not report known vulnerabilities. There may be little in the scan results of unmanaged software plugins to indicate the missing availability of the source commands except audit trail messages.

Commands used to find unmanaged software installations might fail for a variety of reasons, including:

- * Inadequate scan user permissions,
- * Failed privilege escalation,
- * Intermittent network disruption, or
- * Missing or corrupt executables on the target host.

Please address the issues reported here and redo the scan.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/08/23, Modified: 2021/08/23

Plugin Output

tcp/0

```
Failures in commands used to assess Unix software:
```

```
unzip -v      :  
sh: 1: unzip: not found
```

```
Account  : emin  
Protocol : SSH
```


11154 - Unknown Service Detection: Banner Retrieval

Synopsis

There is an unknown service running on the remote host.

Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

Plugin Output

tcp/1515

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 1515
Type      : help
Banner    :
0x00:  45 52 52 4F 52 3A 20 49 6E 76 61 6C 69 64 20 72      ERROR: Invalid r
0x10:  65 71 75 65 73 74 20 66 6F 72 20 6E 65 77 20 61      equest for new a
0x20:  67 65 6E 74 45 52 52 4F 52 3A 20 55 6E 61 62 6C      gentERROR: Unabl
0x30:  65 20 74 6F 20 61 64 64 20 61 67 65 6E 74          e to add agent
```

186361 - VMWare Tools or Open VM Tools Installed (Linux)

Synopsis

VMWare Tools or Open VM Tools were detected on the remote Linux host.

Description

VMWare Tools or Open VM Tools were detected on the remote Linux host.

See Also

<https://kb.vmware.com/s/article/340>

<http://www.nessus.org/u?c0628155>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/11/28, Modified: 2026/04/13

Plugin Output

tcp/0

```
Path      : /usr/bin/vmtoolsd
Version   : 12.5.0
```

20094 - VMware Virtual Machine Detection

Synopsis

The remote host is a VMware virtual machine.

Description

According to the MAC address of its network adapter, the remote host is a VMware virtual machine.

Solution

Since it is physically accessible through the network, ensure that its configuration matches your organization's security policy.

Risk Factor

None

Plugin Information

Published: 2005/10/27, Modified: 2019/12/11

Plugin Output

tcp/0

```
The remote host is a VMware virtual machine.
```

189731 - Vim Installed (Linux)

Synopsis

Vim is installed on the remote Linux host.

Description

Vim is installed on the remote Linux host.

See Also

<https://www.vim.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/01/29, Modified: 2026/04/13

Plugin Output

tcp/0

```
Nessus detected 2 installs of Vim:
```

```
Path      : /usr/bin/vim.tiny
Version   : 9.1
Managed by OS : True
```

```
Path      : /usr/bin/vim.basic
Version   : 9.1
Managed by OS : True
```

100669 - Web Application Cookies Are Expired

Synopsis

HTTP cookies have an 'Expires' attribute that is set with a past date or time.

Description

The remote web application sets various cookies throughout a user's unauthenticated and authenticated session. However, Nessus has detected that one or more of the cookies have an 'Expires' attribute that is set with a past date or time, meaning that these cookies will be removed by the browser.

See Also

<https://tools.ietf.org/html/rfc6265>

Solution

Each cookie should be carefully reviewed to determine if it contains sensitive data or is relied upon for a security decision.

If needed, set an expiration date in the future so the cookie will persist or remove the Expires cookie attribute altogether to convert the cookie to a session cookie.

Risk Factor

None

Plugin Information

Published: 2017/06/07, Modified: 2021/12/20

Plugin Output

tcp/443/www

The following cookie is expired :

```
Name : security_authentication
Path : /
Value :
Domain :
Version :
Expires :
Comment :
Secure : 1
Httponly : 1
Port :
```

100669 - Web Application Cookies Are Expired

Synopsis

HTTP cookies have an 'Expires' attribute that is set with a past date or time.

Description

The remote web application sets various cookies throughout a user's unauthenticated and authenticated session. However, Nessus has detected that one or more of the cookies have an 'Expires' attribute that is set with a past date or time, meaning that these cookies will be removed by the browser.

See Also

<https://tools.ietf.org/html/rfc6265>

Solution

Each cookie should be carefully reviewed to determine if it contains sensitive data or is relied upon for a security decision.

If needed, set an expiration date in the future so the cookie will persist or remove the Expires cookie attribute altogether to convert the cookie to a session cookie.

Risk Factor

None

Plugin Information

Published: 2017/06/07, Modified: 2021/12/20

Plugin Output

tcp/55000/www

The following cookie is expired :

```
Name : security_authentication
Path : /
Value :
Domain :
Version :
Expires :
Comment :
Secure : 1
Httponly : 1
Port :
```

Synopsis

The remote web server hosts linkable content that can be crawled by Nessus.

Description

The remote web server contains linkable content that can be used to gather information about a target.

See Also

<http://www.nessus.org/u?5496c8d9>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2016/06/24

Plugin Output

tcp/443/www

The following sitemap was created from crawling linkable content on the target host :

- <https://192.168.50.10/app/login>
- <https://192.168.50.10/ui/favicons/apple-touch-icon.png>
- <https://192.168.50.10/ui/favicons/favicon-16x16.png>
- <https://192.168.50.10/ui/favicons/favicon-32x32.png>
- <https://192.168.50.10/ui/favicons/favicon.ico>
- <https://192.168.50.10/ui/favicons/manifest.json>
- <https://192.168.50.10/ui/favicons/safari-pinned-tab.svg>

Attached is a copy of the sitemap file.

182848 - libcurl Installed (Linux / Unix)

Synopsis

libcurl is installed on the remote Linux / Unix host.

Description

libcurl is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182848' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://curl.se/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/10, Modified: 2026/04/13

Plugin Output

tcp/0

Nessus detected 2 installs of libcurl:

Path	: /usr/lib/x86_64-linux-gnu/libcurl.so.4.8.0
Version	: 8.5.0
Associated Package	: libcurl4t64
Path	: /usr/lib/x86_64-linux-gnu/libcurl-gnutls.so.4.8.0
Version	: 8.5.0
Associated Package	: libcurl3t64-gnutls