

FUTURA

LA SCUOLA PER L'ITALIA DI DOMANI



Finanziato
dall'Unione europea
NextGenerationEU



Ministero dell'Istruzione
e del Merito



Italiadomani
PIANO NAZIONALE DI RIPRESA E RESILIENZA

DOCENTE	Shadi Lahham
Corso	Web Developer
Unità Formativa	Programmazione - Javascript e Typescript
Argomento	Specificato nel titolo della slide successiva

Intervento realizzato da
ITS
TECNOLOGIE
DELL'INFORMAZIONE
E DELLA COMUNICAZIONE

COESIONE
ITALIA 21-27
PIEMONTE



Cofinanziato
dall'Unione europea



REGIONE
PIEMONTE

Variables, types and operators

Foundation

Shadi Lahham - Web development

Variables

Statements

Each instruction in JS is a "statement", like:

```
console.log('Hello World!');
```

```
document.getElementById("demo").innerHTML = "Hello Dolly.";
```

More details:

[JavaScript Statements](#)

Variables

Use variables to store values

Declare, then initialize in 2 statements:

```
let x;  
x = 5;  
console.log(x);
```

Or declare and initialize in one statement:

```
let y = 2;  
console.log(y);
```

Re-assign the value later:

```
let x = 5;  
x = 1;
```

Primitive Data Types

string: an immutable string of characters:

```
let greeting = 'Hello Kitty';  
let restaurant = "Paul's Place";
```

number: whole (6, -102) or floating point (5.8737):

```
let myAge = 28;  
let pi = 3.14;
```

boolean: Represents logical values true or false:

```
let catsAreBest = true;  
let dogsRule = false;
```

undefined: Represents a value that hasn't been defined.

```
let notDefinedYet;
```

null: Represents an explicitly empty value.

```
let goodPickupLines = null;
```

Strings

A string holds an ordered list of characters:

```
let alphabet = "abcdefghijklmnopqrstuvwxyz";
```

The length property reports the size of the string:

```
console.log(alphabet.length); // 26
```

Each character has an index.

The first character is always at index 0.

The last character is always at index length-1:

```
console.log(alphabet[0]); // 'a'  
console.log(alphabet[1]); // 'b'  
console.log(alphabet[2]); // 'c'  
console.log(alphabet[alphabet.length]); // undefined  
console.log(alphabet[alphabet.length-1]); // 'z'  
console.log(alphabet[alphabet.length-2]); // 'y'
```

Variable Names

- Begin with letters, \$ or _
- Only contain letters, numbers, \$ and _
- Case sensitive
- Avoid reserved words
- Choose clarity and meaning
- Prefer **camelCase** for multiple words (instead of under_score)
- Pick a naming convention and stick with it

[Camel case - MDN](#)

[Camel case - Wikipedia](#)

note: \$ is usually used by libraries such as jQuery so it's best to avoid in variable names

Variable Names

OK:

```
let numPeople, $mainHeader, _num, _Num;
```

Not OK:

```
let 2coolForSchool, soHappy!
```

Meaningful Names in English

// always choose meaningful variable names; code is easier to understand and maintain

let `x` = 100; *// bad*

let `totalPrice` = 100; *// good*

// always use English for variable names, even for values in a different language

let `liczbaProduktow` = 5; *// bad*

let `liczbaProduktow` = 'pięć'; *// bad*

let `nazwaUzytkownika` = 'Jan Kowalski'; *// bad*

Meaningful Names in English

// always choose meaningful variable names; code is easier to understand and maintain

```
let x = 100; // bad
```

```
let totalPrice = 100; // good
```

// always use English for variable names, even for values in a different language

```
let numberOfProducts = 5; // good
```

```
let numberOfProducts = 'pięć'; // good
```

```
let userName = 'Jan Kowalski'; // good
```

Expressions

Variables can also store the result of any "expression":

```
let x = 2 + 2;
let y = x * 3;
let myName = 'Gina';
let greeting = 'Hello ' + myName;
let title = 'Baroness';
let formalGreeting = greeting + ', ' + title
```

Loose Typing

JS figures out the type based on value, and the type can change:

```
let x;  
x = 2;  
x = 'Hi';
```

A variable can only be of one type:

```
let y = 2 + ' cats';  
console.log(typeof y);
```

Operators

Arithmetic Operators

```
let a = 12 + 5;    // 17
let b = 12 - 5;    // 7
let c = 12 * 5;    // 60
let d = 12 / 5;    // 2.4 - division results in floating point numbers.
let e = 12 % 5;    // 2 - the remainder of 12/5 in integer math is 2.
```

```
let a = "1";
let b = a;        // b = "1": a string
let c = +a;       // c = 1: a number
let d = -a;       // d = -1: a number
```

Assignment Operators

Assignment:

```
x = y  
x += y  
x -= y  
x *= y  
x /= y  
x %= y
```

Same as:

```
x = y  
x = x + y  
x = x - y  
x = x * y  
x = x / y  
x = x % y
```

note:

x has to be already declared

Increment Operators

```
let a = 1;  
a = a + 1;  
a += 1;  
a++;  
++a;
```

// increment occurs before a is assigned to b

```
let a = 1;  
let b = ++a; // a = 2, b = 2;
```

// increment occurs to c after c is assigned to d

```
let c = 1;  
let d = c++; // c = 2, d = 1;
```

Comparison Operators

- `==` Is equal to
- `===` Is identical (is equal to and is of the same type)
- `!=` Is not equal to
- `!==` Is not identical
- `>` Greater than
- `>=` Greater than or equal to
- `<` Less than
- `<=` Less than or equal to

```
let x = 5;  
x == 5;    //true  
x === "5"; //false
```

Logical Operators

Operators:

`&&` and
`||` or
`!` not

Examples:

```
(x < 10 && y > 1)
(x === 5 || y === 5)
!(x === y)
```

String Operators

+

+=

Examples:

```
text3 = text1 + text2;
```

```
text1 += text2;
```

Operator Classification

Operator Classification

operator: an entity (such as a symbol or keyword) that performs an action on operands

operand: an entity (such as a variable or value) on which an operator performs an action

// unary (1 operand)

```
let x = 5;
```

```
console.log(++x); // unary operator
```

// binary (2 operands)

```
let y = 5; // binary operator
```

```
let z = 3; // binary operator
```

```
console.log(y + z); // binary operator
```

// ternary (3 operands)

```
let a = 10;
```

```
let b = 5;
```

```
let result = a > b ? 'yes' : 'no'; // ternary operator
```

Operator Precedence

Operator Precedence

// multiplication has higher precedence than addition

```
let result = 10 + 5 * 2;
```

```
console.log(result); // Output: 20
```

// parentheses change the precedence, so addition is done first

```
let result1 = (10 + 5) * 2;
```

```
console.log(result1); // Output: 30
```


Operator Precedence

// addition has higher precedence than assignment

```
let x = 5;  
x *= 2 + 3;  
console.log(x); // Output: 25
```

// Logical AND has Lower precedence than comparison

```
let comparison = 10 > 5 && 5 <= 3;  
console.log(comparison); // Output: false
```

// Logical NOT has higher precedence than both Logical AND and Logical OR

```
let logical = true || false && !false;  
console.log(logical); // Output: true
```

[JavaScript Operator Precedence](#)

[Operator precedence | MDN](#)

Let & const

Let

```
let x = 88;  
console.log('value of x', x);  
  
for (let i = 0; i < 10; i++) {  
  let t = i;  
  console.log('inside i = ', i);  
  console.log('inside t = ', t);  
}  
  
console.log('outside i = ', i); // i not defined  
console.log('outside t = ', t); // t not defined
```

let: Block-scoped

Access restricted to nearest enclosing block

Const

```
let x = 88;  
const y = 77;  
x = 9;  
console.log('x = ', x);  
y = 17; // TypeError: Assignment to constant variable.  
console.log('y = ', y);  
const y = 55; // SyntaxError: Identifier 'y' has already been declared
```

const: Block-scoped, like **let**

Values of const variables cannot be reassignment

Const variables cannot be redeclared

Your turn

1. Tell my fortune

- Store the following into variables: number of children, partner's name, geographic location, job title.
- Output your fortune to the console like so: "You will be a X in Y, and married to Z with N kids."

note: remember to create an `index.html` file and a `main.js` file

Do this for all future exercises

Open your browser's devtools and go to the console

[Open Chrome DevTools](#)

[Open Firefox DevTools](#)

2.Calculate age

- Store your birth year in a variable.
- Store a future year in a variable.
- Calculate your 2 possible ages for that year based on the stored values.
- For example, if you were born in 1988, then in 2026 you'll be either 37 or 38, depending on what month it is in 2026.
- Output them to the console like so: "I will be either NN or NN in YYYY", substituting the values.

3.Free coffee

- Store your current age into a variable.
 - Store a maximum age into a variable.
 - Store the amount of coffee you drink per day (as a number).
 - Calculate how much coffee you would drink for the rest of your life.
-
- Output the result to the console like so: "You will need NN cups of coffee to last you until the ripe old age of X".

Bonus

4.Easy geometry

Calculate properties of a circle, using the definitions here.

- Store a radius into a variable.
- Calculate the circumference based on the radius, and output "The circumference is NN".
- Calculate the area based on the radius, and output "The area is NN".

Reference:

[JavaScript Math Object](#)
[Circles](#)

5.Convert temperature

- Store a celsius temperature into a variable.
- Convert it to fahrenheit and output "NN°C is NN°F".
- Now store a fahrenheit temperature into a variable.
- Convert it to celsius and output "NN°F is NN°C."

References

[JavaScript Operators Reference](#)

[Expressions and operators](#)

[JavaScript data types and data structures](#)

[Values, Types, and Operators](#)

Operator Precedence

[JavaScript Operator Precedence](#)
[Operator precedence | MDN](#)

Javascript validation

Code quality tools

[ESLint](#)

[JSHint](#)

© Copyright & Attribution

Unless otherwise stated, all materials are © 2017–2025 [Shadi Lahham](#)

For personal use only. May not be shared or reproduced without written permission

Brief excerpts may be used with proper attribution

External links and resources are copyrighted by their respective owners