



Prowler Setup and Cloud Security Scan

Prowler is an open-source cloud security assessment tool used to identify vulnerabilities and configuration weaknesses in cloud environments. In this project, it was used to perform a security scan of an **Amazon Web Services** environment in order to detect potential misconfigurations and security risks.


This section demonstrates the installation and configuration of Prowler on a Kali Linux system, as well as the steps taken to run the scan. Screenshots are provided to illustrate the setup process and the results generated from the assessment.

To begin the setup process, a dedicated directory was first created on the Kali machine to organize the installation files.



if you are getting error : unable to locate package prowler...

head to github to get the installer package and paste as instructed below



```
kali@kali: ~/cloudvuln
$ mkdir cloudvuln
$ ls
acdirectory bins.save cloudvuln cloud_vulnerability Desktop Documents Downloads Music phishing_pot PhishMailer Pictures Public Sewing_machines Templates Videos walmart
$ cd cloudvuln
$ ls
$ sudo apt install prowler
[sudo] password for kali:
Error: Unable to locate package prowler

(kali@kali)~/cloudvuln
$ git clone https://github.com/prowler-cloud/prowler.git
Cloning into 'prowler' ...
remote: Counting objects: 100% (370/370), done.
remote: Compressing objects: 100% (270/270), done.
Receiving objects: 2% (3176/158786), 2.33 MiB | 2.30 MiB/s
```

create an IAM user

The screenshot shows the 'Retrieve password' step in the AWS IAM console. A green success banner at the top states 'User created successfully'. On the left, a progress bar shows four steps: 'Specify user details', 'Set permissions', 'Review and create', and 'Retrieve password' (which is the current step). The main content area is titled 'Retrieve password' and includes a sub-section 'Console sign-in details'. This section displays the 'Console sign-in URL' (partially redacted), the 'Console password' (redacted and enclosed in a red box), and a 'Show' button. There are also buttons for 'Email sign-in instructions', 'Cancel', 'Download .csv file', and 'Return to users list'.

The screenshot shows the 'Users' list page in the AWS IAM console. The left sidebar contains navigation links for 'Identity and Access Management (IAM)', 'Access Management', and 'Access reports'. The main content area is titled 'Users (3)' and includes a search bar and a table of users. The table has columns for 'User name', 'Path', 'Groups', 'Last activity', 'MFA', 'Password age', 'Console last sign-in', and 'Access key ID'. Three users are listed: 'blu', 'jason', and 'prowlerscan_user'. The 'prowlerscan_user' row is highlighted with a red box. The URL at the bottom of the browser window is 'https://us-east-1.console.aws.amazon.com/iam/home?region=eu-north-1#/users/details/prowlerscan_user'.

User name	Path	Groups	Last activity	MFA	Password age	Console last sign-in	Access key ID
blu	/	0	Now	Virtual...	19 minutes	Now	-
jason	/	1	1 hour ago	-	90 days	1 hour ago	Active - AKIA Inactive - AKI...
prowlerscan_user	/	0	3 minutes ago	-	2 minutes	3 minutes ago	-

aws IAM > Users > prowlerscan_user

Identity and Access Management (IAM)

Search IAM

Dashboard

Access Management

- User groups
- Users**
- Roles
- Policies
- Identity providers
- Account settings
- Root access management
- Temporary delegation requests

Access reports

- Access Analyzer
- Resource analysis
- Unused access
- Analyzer settings
- Credential report

Permissions

Permissions policies (1)

Permissions are defined by policies attached to the user directly or through groups.

Filter by Type

All types

Policy name	Type	Attached via
☐ IAMUserChangePassword	AWS managed	Directly

Permissions boundary (not set)

Generate policy based on CloudTrail events

You can generate a new policy based on the access activity for this user, then customize, create, and attach it to this role. AWS uses your CloudTrail events to identify the services and actions used and generate a policy. [Learn more](#)

[Generate policy](#)

No requests to generate a policy in the past 7 days.

Remove Add permissions

Add permissions

Create inline policy

1

https://us-east-1.console.aws.amazon.com/iam/home?region=eu-north-1#/users/details/prowlerscan_user/add-permissions

aws

Search

[Alt+S]

Globalgoldmind (3863-9733-2453)blu

IAMUsersprowlerscan_userAdd permissions

0

Step 1

Add permissions

Step 2

Review

Add permissions

Add user to an existing group or create a new one. Using groups is a best-practice way to manage user's permissions by job functions. [Learn more](#)

Permissions options

☐ Add user to group

Add user to an existing group, or create a new group. We recommend using groups to manage user permissions by job function.

☐ Copy permissions

Copy all group memberships, attached managed policies, inline policies, and any existing permissions boundaries from an existing user.

☒ Attach policies directly

Attach a managed policy directly to a user. As a best practice, we recommend attaching policies to a group instead. Then, add the user to the appropriate group.

Permissions policies (1454)

Q Search

Filter by Type

All types

< 1 2 3 4 5 6 7 ... 73 >

☐ Policy name

☐ Access

☐ AccessAnalyzerServiceRolePolicy

☐ AccountManagementFromVercel

☐ AdministratorAccess

☐ AdministratorAccess-Amplify

☐ AdministratorAccess-AmazonKinesisVideo

Type

Customer managed

AWS managed

AWS managed

AWS managed - job function

AWS managed

AWS managed

Attached entities

0

0

0

1

0

0

CloudShellFeedbackConsole Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. PrivacyTermsCookie preferences

aws

Search

[Alt+S]

Globalgoldmind (3863-9733-2453)blu

IAMUsersprowlerscan_userAdd permissions

0

Step 1

Add permissions

Step 2

Review

Add permissions

Add user to an existing group or create a new one. Using groups is a best-practice way to manage user's permissions by job functions. [Learn more](#)

Permissions options

☐ Add user to group

Add user to an existing group, or create a new group. We recommend using groups to manage user permissions by job function.

☐ Copy permissions

Copy all group memberships, attached managed policies, inline policies, and any existing permissions boundaries from an existing user.

☒ Attach policies directly

Attach a managed policy directly to a user. As a best practice, we recommend attaching policies to a group instead. Then, add the user to the appropriate group.

Permissions policies (1454)

Q securityaudit

Filter by Type

All types

1 match

< 1 >

☐ Policy name

☒ SecurityAudit

Type

AWS managed - job function

Attached entities

1

CancelNext

CloudShellFeedbackConsole Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. PrivacyTermsCookie preferences

search for securityAudit and ViewonlyAccess policies

Step 1

Add permissions

Step 2

Review

Add permissions

Add user to an existing group or create a new one. Using groups is a best-practice way to manage user's permissions by job functions. [Learn more](#)

☐ Add user to group

Add user to an existing group, or create a new group. We recommend using groups to manage user permissions by job function.

☐ Copy permissions

Copy all group memberships, attached managed policies, inline policies, and any existing permissions boundaries from an existing user.

☒ Attach policies directly

Attach a managed policy directly to a user. As a best practice, we recommend attaching policies to a group instead. Then, add the user to the appropriate group.

Permissions policies (2/1454)

viewonly

Filter by Type

All types

2 matches

Policy name	Type	Attached entities
☐ AmazonViewOnlyAccessFromVercel	AWS managed	0
☒ ViewOnlyAccess	AWS managed - job function	1

Cancel

Next

CloudShell

Feedback

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences

Search

[Alt+S]

Global

goldmind (3863-9733-2453)

blu

IAM

Users

prowlerscan_user

Add permissions

☐ [AdministratorAccess-AWSElasticBeanstalk](#)

AWS managed

0

☐ [AIOpsAssistantIncidentReportPolicy](#)

AWS managed

0

☐ [AIOpsAssistantPolicy](#)

AWS managed

0

☐ [AIOpsConsoleAdminPolicy](#)

AWS managed

0

☐ [AIOpsOperatorAccess](#)

AWS managed

0

☐ [AIOpsReadOnlyAccess](#)

AWS managed

0

☐ [AlexaForBusinessDeviceSetup](#)

AWS managed

0

☐ [AlexaForBusinessFullAccess](#)

AWS managed

0

☐ [AlexaForBusinessGatewayExecution](#)

AWS managed

0

☐ [AlexaForBusinessLifeSizeDelegatedAccessP...](#)

AWS managed

0

☐ [AlexaForBusinessNetworkProfileServicePol...](#)

AWS managed

0

☐ [AlexaForBusinessPolyDelegatedAccessPolicy](#)

AWS managed

0

☐ [AlexaForBusinessReadOnlyAccess](#)

AWS managed

0

☐ [AmazonAPIGatewayAdministrator](#)

AWS managed

0

☐ [AmazonAPIGatewayInvokeFullAccess](#)

AWS managed

0

Cancel

Next

CloudShell

Feedback



Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences



Now these policies have been added to the dedicated IAM user that will be dedicated to scanning for vulnerabilities

aws IAM > Users > prowlerscan_user

Identity and Access Management (IAM)

2 policies added to prowlerscan_user

prowlerscan_user info Delete

Summary

ARN
arn:aws:iam::386397332453:user/prowlerscan_user

Console access
Enabled without MFA

Created
March 12, 2026, 12:55 (UTC+01:00)

Last console sign-in
Today

Access key 1
Create access key

Permissions Groups Tags Security credentials Last Accessed

Permissions policies (3) Remove Add permissions

Permissions are defined by policies attached to the user directly or through groups.

Filter by Type

Search All types

Policy name	Type	Attached via
☐ IAMUserChangePassword	AWS managed	Directly
☐ SecurityAudit	AWS managed - job function	Directly
☐ ViewOnlyAccess	AWS managed - job function	Directly

CloudShell Feedback Console Mobile App

2 policies added to prowlerscan_user

Access key best practices & alternatives

Build on the basis of your use case to increase key security. Consider the following use cases and alternatives.

Use case

☒ Command Line Interface (CLI)
You plan to use this access key to enable the AWS CLI to access your AWS account.

☐ You plan to use this access key to enable application code in a local development environment to access your AWS account.

☐ Application running on an AWS compute service
You plan to use this access key to enable application code running on an AWS compute service like Amazon EC2, Amazon ECS, or AWS Lambda to access your AWS account.

☐ Third-party service
You plan to use this access key to enable access for a third-party application or service that monitors or manages your AWS resources.

☐ Application running outside AWS
You plan to use this access key to enable application code running in your data center or other infrastructure outside of AWS that needs to access your AWS resources.

☐ Other
Your use case is not listed here.

Alternatives recommended

• Use AWS CloudShell, a browser-based CLI, to run commands. [Learn more](#)

Confirmation

☒ I understand the above recommendation and want to proceed to create an access key.


Next


Now create access key

owler aws --list-compliance – Shows the compliance frameworks supported by Prowler


prowler aws --list-compliance – Shows the compliance frameworks supported by Prowler

aws configure --list-profiles – Lists all AWS CLI configuration profiles available on the system.





save both the access key and
the secret access key



The image displays two screenshots of a Kali Linux terminal window. The top screenshot shows the command `aws configure --profile blu_prowler_user` being executed, with the AWS Access Key ID `386397332453` and the AWS Secret Access Key `FWS+T2aeFIQvYAnb1SiNRES5dI0mCnvDsrOfDZxj` entered. The bottom screenshot shows the same command being executed again, with the same AWS Access Key ID and Secret Access Key entered, and the Default region name `[None]` and Default output format `[None]` also entered. A 'Screenshot taken' notification is visible in the bottom right corner of the terminal window.

```
(kali@kali)-[~/cloudvuln/prowler]
$ aws configure --profile blu_prowler_user
AWS Access Key ID [None]: 386397332453
AWS Secret Access Key [None]: FWS+T2aeFIQvYAnb1SiNRES5dI0mCnvDsrOfDZxj

(kali@kali)-[~/cloudvuln/prowler]
$ aws configure --profile blu_prowler_user
AWS Access Key ID [None]: 386397332453
AWS Secret Access Key [None]: FWS+T2aeFIQvYAnb1SiNRES5dI0mCnvDsrOfDZxj
Default region name [None]:
Default output format [None]:

(kali@kali)-[~/cloudvuln/prowler]
$
```

enter the command keys
and the access keys

```
kali@kali:~/cloudvuln/prowler$ aws configure --profile blu_prowler_user
AWS Access Key ID [None]: 386397332453
AWS Secret Access Key [None]: FWS+T2aeFIQvYAnb1SiNRES5dI0mCnvDsrOf0DZxj
Default region name [None]:
Default output format [None]:

kali@kali:~/cloudvuln/prowler$ ls
AGENTS.md      contrib          docker-compose.yml  kubernetes  permissions  pyproject.toml  skills
api            CONTRIBUTING.md  Dockerfile          LICENSE     poetry.lock  README.md       tests
codecov.yml    dashboard       docs                Makefile    prowler      SECURITY.md      ui
CODE_OF_CONDUCT.md  docker-compose-dev.yml  examples            mcp_server  prowler-cli.py

kali@kali:~/cloudvuln/prowler$ cd permissions

kali@kali:~/cloudvuln/prowler/permissions$ ls
prowler-additions-policy.json  prowler-azure-custom-role.json  templates

kali@kali:~/cloudvuln/prowler/permissions$ mousepad prowler-additions-policy.json
```

folloe these steps to copy the prowler policies
that will be inserted into the AWS platform

```
File Edit Search View Document Help

1 {
2   "Version": "2012-10-17",
3   "Statement": [
4     {
5       "Action": [
6         "account:Get*",
7         "appstream:Describe*",
8         "appstream:List*",
9         "backup:List*",
10        "backup:Get*",
11        "bedrock:List*",
12        "bedrock:Get*",
13        "cloudtrail:GetInsightsSelectors",
14        "codeartifact:List*",
15        "codebuild:BatchGet*",
16        "codebuild:ListReportGroups",
17        "cognito-idp:GetUserPoolMfaConfig",
18        "dlm:Get*",
19        "dms:Describe*",
20        "ds:Get*",
21        "ds:Describe*",
22        "ds:List*",
23        "dynamodb:GetResourcePolicy",
24        "ec2:GetIbsEncryptionByDefault",
25        "ec2:GetSnapshotBlockPublicAccessState",
26        "ec2:GetInstanceMetadataDefaults",
27        "ecr:Describe*",
28        "ecr:GetRegistryScanningConfiguration",
29        "elasticfilesystem:DescribeBackupPolicy",
30        "glue:GetConnections",
31        "glue:GetSecurityConfigurations",
32        "glue:SearchTables",
33        "glue:GetMLTransform",
34        "iam:List*",
35        "logs:FilterLogEvents",
36        "lightail:GetRelationalDatabases",
37        "macie2:GetMacieSession",
38        "macie2:GetAutomatedDiscoveryConfiguration",
39        "s3:GetAccountPublicAccessBlock",
40        "shield:DescribeProtection",
41        "shield:GetSubscriptionState",
42        "securityhub:BatchImportFindings",
43        "securityhub:GetFindings",
44        "servicecatalog:Describe*",
45        "servicediscovery:List*",
46        "ssm:GetDocument",
47        "xray:ListSegments"
```

copy all

Identity and Access Management (IAM)

Dashboard

Access Management

Users

Roles

Policies

Identity providers

Account settings

Root access management

Temporary delegation requests

Access reports

Access Analyzer

Resource analysis

Unused access

Analyzer settings

Credential report

Organization activity

Service control policies

Resource control policies

prowlscan_user

Summary

ARN: `arn:aws:iam:386397332453:user/prowlscan_user`

Created: March 12, 2026, 12:55 (UTC+01:00)

Console access: Enabled without MFA

Last console sign-in: Today

Access key 1: AKIA/TSTYTMP54RHYXPGC - Active

Access key 2: Create access key

Permissions policies (3)

Permissions are defined by policies attached to the user directly or through groups.

Filter by Type: All types

Policy name	Type	Attached via
<code>iam:UserChangePassword</code>	AWS managed	Directly
<code>SecurityAudit</code>	AWS managed - job function	Directly
<code>ViewOnlyAccess</code>	AWS managed - job function	Directly

Permissions boundary (not set)

Generate policy based on CloudTrail events

Step 1: Specify permissions

Step 2: Review and create

Specify permissions

Add permissions by selecting services, actions, resources, and conditions. Build permission statements using the JSON editor.

Visual

JSON

Actions

```
39    "s3:GetAccountPublicAccessBlock",
40    "shield:DescribeProtection",
41    "shield:GetSubscriptionState",
42    "securityhub:BatchReportFindings",
43    "securityhub:GetFindings",
44    "servicecatalog:Describe*",
45    "servicecatalog:List*",
46    "s3n:GetDocument",
47    "s3n:Incidents:List*",
48    "states:listTagsForResource",
49    "support:Describe*",
50    "tag:GetTagKeys",
51    "wellarchitected:List*"
52  },
53  "Resource": "*",
54  "Effect": "Allow",
55  "Sid": "AllowReadOnly"
56  },
57  {
58    "effect": "allow",
59    "Action": [
60      "apigateway:GET"
61    ],
62    "Resource": [
63      "arn:apigateway:*::restapis/*",
64      "arn:apigateway:*::apis/*"
65    ],
66    "Sid": "AllowAPIGatewayReadOnly"
67  }
68  ]
69  }
70  }
```

Select a statement

Select an existing statement in the policy or add a new statement.

+ Add new statement

70.1 JSON

656 of 2048 characters remaining

CloudShell

Feedback

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. Privacy Terms Cookie preferences

aws IAM Users > prowlercan_user Create policy

Policy editor

```
39 "s3:getAccountPublicAccessBlock",
40 "shield:describeProtection",
41 "shield:getSubscriptionData",
42 "securityhub:batchImportFindings",
43 "securityhub:getFindings",
44 "servicecatalog:describe*",
45 "servicecatalog:list*",
46 "ssm:getDocument",
47 "ssm:incidents:list*",
48 "states:listTagsForResource",
49 "support:describe*",
50 "tag:getTags",
51 "wellarchitected:list*"
52 },
53 "Resource": "*",
54 "Effect": "Allow",
55 "Sid": "AllowReadOnlyOnly"
56 },
57 {
58   "Effect": "Allow",
59   "Action": [
60     "apigateway:GET"
61   ],
62   "Resource": [
63     "arn:*:apigateway:*::/restapis/*",
64     "arn:*:apigateway:*::/apis/*"
65   ],
66   "Sid": "AllowAPIGatewayReadOnly"
67 }
68 ]
69 }
70 }
71 }
72 }
```

[+ Add new statement](#)

656 of 2048 characters remaining

Security: 0 Errors: 0 Warnings: 0 Suggestions: 0

[Cancel](#) [Next](#)

insert the json file here

CloudShell Feedback Console Mobile App

aws IAM Users > prowlercan_user Create policy

Step 1 Specify permissions
Step 2 Review and create

Review and create

Review the permissions, specify details, and tags.

Policy details

Policy name

Enter a meaningful name to identify this policy.

prowler_policy

Maximum 128 characters. Use alphanumeric and +, -, @, _ characters.

Permissions defined in this policy


Permissions defined in this policy document specify which actions are allowed or denied. To define permissions for an IAM identity (user, user group, or role), attach a policy to it.

[Search](#)

Allow (32 of 464 services) [Show remaining 432 services](#)


Service	Access level	Resource	Request condition
Account	Full: Read	All resources	None
API Gateway	Full: Read	ResourcePath: string like (/restapis/*, region) string like [All]	None
API Gateway V2	Limited: Read	ResourcePath: string like [/apis/*, region] string like [All]	None
AppStream 2.0	Full: List Limited: Read	All resources	None
Backup	Full: List Limited: Permissions management, Read	All resources	None
Bedrock	Full: List Limited: Read	All resources	None
CloudTrail	Limited: Read	All resources	None

"prowlerr aws --profile blu_prowler_user --region us-east-1" : use this to run the scan. you can decide not to or to add the region



output

get the html file by running
firefox "html file gotten above"



Report Information	
Version:	3.11.3
Parameters used:	aws -profile blu_prowler_user -region us-east-1
Date:	2026-03-12T10:05:23.742994

AWS Assessment Summary	
AWS Account:	386397332453
AWS-CLI Profile:	blu_prowler_user
Audited Regions:	us-east-1

AWS Credentials	
User ID:	AIDAVTSYTMPSPRGNPXCR
Caller Identity ARN:	arn:aws:iam:386397332453:user:prowlerscan_user

Assessment Overview	
Total Findings:	142
Passed:	64
Failed:	78
Total Resources:	41
Search:	

Status	Severity	Service Name	Region	Check ID	Check Title	Resource ID	Tags	Status Extended	Risk	Recommendation	Compliance
FAIL	low	support	us-east-1	trustedadvisor_premium_support_plan_subscribed	Check if a Premium support plan is subscribed	386397332453		Amazon Web Services Premium Support Plan isn't subscribed.	Ensure that the appropriate su read more...	It is recommended that you sub read more...	
FAIL	medium	organizations	us-east-1	organizations_account_part_of_organizations	Check if account is part of an AWS Organizations	AWS Organization		AWS Organizations is not in-use for this AWS Account.	The risk associated with not b read more...	Create or Join an AWS Organiza read more...	•MITRE-ATTACK: T1078, T1087, read more...
FAIL	medium	organizations	us-east-1	organizations_tags_policies_enabled_and_attached	Check if an AWS Organization has tags policies enabled and attached.	AWS Organization		AWS Organizations is not in-use for this AWS Account.	If an AWS Organization tags po read more...	Enable and attach AWS Organiza read more...	•ENS-RD022: op.exp.Laws sys read more...
FAIL	low	organizations	us-east-1	organizations_scp_check_deny_regions	Check if AWS Regions are restricted with SCP policies	AWS Organization		AWS Organizations is not in-use for this AWS Account.	The risk associated with not r read more...	Restrict AWS Regions using SCP read more...	•MITRE-ATTACK: T1078, T1087, read more...
PASS	medium	cloudwatch	us-east-1	cloudwatch_cross_account	Check if CloudWatch has allowed	386397332453		CloudWatch doesn't allow cross-account	Cross-	Grant usage permission on a	•AWS-Well-

blu_prowler_user -region us-east-1

Date: 2026-03-12T10:05:23.742994

Audited Regions: us-east-1

Failed: 78

Total Resources: 41

Filters Active - 0

Clear Filters Collapse All Show All

Status	Severity	Service Name	Region	Check Title
FAIL	critical	accessanalyzer	eu-north-1	Check if a Premium support plan is subscribed
INFO	high	account	us-east-1	Check if account is part of an AWS Organizati...
PASS	low	athena		Check if an AWS Organization has tags polici...
	medium	backup		Check if AWS Regions are restricted with SC...
		cloudtrail		Check if CloudWatch has allowed cross-accou...
		cloudwatch		Check if EBS Default Encryption is activated.

Resource ID	Resource Tags	Risk	Recommendation	Compliance
<root_account>	No data	Access Keys could be lost or stolen. It creates a	Analyze Bucket policy to validate appropriate per	•AWS-Well-Architected-Framework-Security-Pill
386397332453	•floor 1=•floor 1	Account VPC could be linked to other accounts.	Apply Zero Trust approach. Implement a process	•AWS-Well-Architected-Framework-Security-Pill
Access		Allow attackers to gain unauthorized access to r	Apply Zero Trust approach. Implement a process	•AWS-Well-Architected-Framework-Security-Pill
ad-04f964b51a306d12		Allowing public access to CloudTrail log content		•AWS-Well-Architected-Framework-Security-Pill
AdministratorAccess				
AmazonS3FullAccess				

more...

FAIL	medium	ec2	us-east-1	ec2_ebs_default_encryption	Check if EBS Default Encryption is	386397332453	EBS Default Encryption is not activated.	if not enabled. Enable Encryption. Use a	•CSP-21-CFR-Part-11
------	--------	-----	-----------	----------------------------	------------------------------------	--------------	--	--	---------------------

GitHub - prowler-cloudly: Prowler - The Handy Cloud Security Framework

file:///home/kali/cloudvuln/prowler/permissions/output/prowler-output-38639732453-20260312100523.html

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

blu_prowler_user -region us-east-1
Date: 2026-03-12T10:05:23.742594

Audited Regions: us-east-1

Failed: 78
Total Resources: 41

Filters Show 100 entries

Filters Active: 0

Clear Filters Collapse All Show All

Status	Severity	Service Name	Region	Check Title
FAIL	critical	accessanalyzer	eu-north-1	Check if a Premium support plan is subscribed
INFO	high	account	us-east-1	Check if account is part of an AWS Organizati...
PASS	low	athena		Check if an AWS Organization has tags polici...
	medium	backup		Check if AWS Regions are restricted with SC...
		cloudtrail		Check if CloudWatch has allowed cross-accou...
		cloudwatch		Check if EBS Default Encryption is activated.

Resource ID	Resource Tags	Risk	Recommendation	Compliance
<root_account>	No data	Access Keys could be lost or stolen. It creates	Analyze Bucket policy to validate appropriate	AWS-Well-Architected-Framework-Security-Pile
38639732453	floor 1=floor 1	Account VPC could be linked to other accounts.	Apply Zero Trust approach. Implement a process	AWS-Well-Architected-Framework-Security-Pile
Access		Allow attackers to gain unauthorized access to re	Apply Zero Trust approach. Implement a process	AWS-Well-Architected-Framework-Security-Pile
ad-049b04b51a308d12		Allowing public access to CloudTrail log content		AWS-Well-Architected-Framework-Security-Pile
AdministratorAccess				
AmazonS3FullAccess				

more...

FAIL medium ec2 us-east-1 ec2_ebs_default_encryption Check if EBS Default Encryption is 38639732453 EBS Default Encryption is not activated. If not enabled Enable Encryption. Use a <GUP-21-CFR-Pan-11>

Report information

Version: 3.13.3

Parameters used: aws -profile blu_prowler_user -region us-east-1

Date: 2026-03-12T10:05:23.742594

AWS Assessment Summary

AWS Account: 38639732453

AWS-CLI Profile: blu_prowler_user

Audited Regions: us-east-1

AWS Credentials

User ARN: arn:aws:iam::38639732453:user/prowler_user

Caller identity ARN: arn:aws:iam::38639732453:user/prowler_user

Assessment Overview

Total Findings: 142

Passed: 64

Failed: 78

Total Resources: 41

Filters (0) Show 100 entries

Status	Severity	Service Name	Region	Check ID	Check Title	Resource ID	Resource Tags	Status Extended	Risk	Recommendation	Compliance
PASS	critical	iam	us-east-1	iam_root_mfa_enabled	Ensure MFA is enabled for the root account	<root_account>		MFA is enabled for root account.	The root account is the most privileged user in an AWS account. MFA adds an extra layer of protection on top of a user name and password with each login attempt. Enabling MFA on your root account significantly reduces the risk of unauthorized access to your AWS resources. For more information, see AWS IAM User Guide .	Using MFA console sign-in to read more...	<GDPR-Article-25-GDPR-21-CF-read more...
PASS	critical	iam	us-east-1	iam_root_access_key	Ensure no root account access key exists	<root_account>		User <root_account> does not have access keys.	The root account is the most privileged user in an AWS account. MFA adds an extra layer of protection on top of a user name and password with each login attempt. Enabling MFA on your root account significantly reduces the risk of unauthorized access to your AWS resources. For more information, see AWS IAM User Guide .	Use the credentials report to read more...	<GDPR-Article-25-GDPR-21-CF-read more...
PASS	critical	iam	us-east-1	iam_root_hardware_mfa_enabled	Ensure only hardware MFA is enabled for the root account	<root_account>		Root account has a hardware MFA device enabled.	The root account is the most privileged user in an AWS account. MFA adds an extra layer of protection on top of a user name and password with each login attempt. Enabling MFA on your root account significantly reduces the risk of unauthorized access to your AWS resources. For more information, see AWS IAM User Guide .	Using MFA console sign-in to read more...	<GDPR-Article-25-GDPR-21-CF-read more...

	<table> <tr> <td>Report Information</td><td>AWS Assessment Summary</td><td>AWS Credentials</td></tr> <tr> <td>Version: 1.1.3</td><td>AWS Account: 36323131053</td><td>User: M1ADWTSYTMSPRQFWVCR</td></tr> <tr> <td>Parameters used: aws-profile:sh_prowler_user --region us-east-1</td><td>AWS CLI Profile: sh_prowler_user</td><td>Cable identity ARN: arn:iam::36323131053:profile/sh_prowler_user</td></tr> <tr> <td>Date: 2024-09-12T13:05:29.742004</td><td>Audited Regions: us-east-1</td><td></td></tr> </table>	Report Information	AWS Assessment Summary	AWS Credentials	Version: 1.1.3	AWS Account: 36323131053	User: M1ADWTSYTMSPRQFWVCR	Parameters used: aws-profile:sh_prowler_user --region us-east-1	AWS CLI Profile: sh_prowler_user	Cable identity ARN: arn:iam::36323131053:profile/sh_prowler_user	Date: 2024-09-12T13:05:29.742004	Audited Regions: us-east-1				<table> <tr> <td>Assessment Overview</td></tr> <tr> <td>Total Findings: 142</td></tr> <tr> <td>Passed: 54</td></tr> <tr> <td>Failed: 78</td></tr> <tr> <td>Total Resources: 41</td></tr> </table>	Assessment Overview	Total Findings: 142	Passed: 54	Failed: 78	Total Resources: 41
Report Information	AWS Assessment Summary	AWS Credentials																			
Version: 1.1.3	AWS Account: 36323131053	User: M1ADWTSYTMSPRQFWVCR																			
Parameters used: aws-profile:sh_prowler_user --region us-east-1	AWS CLI Profile: sh_prowler_user	Cable identity ARN: arn:iam::36323131053:profile/sh_prowler_user																			
Date: 2024-09-12T13:05:29.742004	Audited Regions: us-east-1																				
Assessment Overview																					
Total Findings: 142																					
Passed: 54																					
Failed: 78																					
Total Resources: 41																					

[illegible]

FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-0d3b697673d65	VPC subnet subnet-0d3b697673d65 assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-0f86a3d7364e16d4	VPC subnet subnet-0f86a3d7364e16d4 assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-057d8038433ba223	VPC subnet subnet-057d8038433ba223 assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-0445765680dc6d44	VPC subnet subnet-0445765680dc6d44 assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-0a483b641d85275	VPC subnet subnet-0a483b641d85275 assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
FAIL	medium	vpc	us-east-1	vpc_subnet_no_public_ip_by_default	Ensure VPC subnets do not assign public IP by default	subnet-0ac9f01308471ef	VPC subnet subnet-0ac9f01308471ef assigns public IP by default	VPC subnet is a part of the VPC having its own rules for traffic. Assigning the public IP to the subnet automatically (on launch) can accidentally expose the instances within this subnet to internet and should be added to the post-creation of the Subnet.	VPC subnets should not allow automatic public IP assignment	Screenshot taken View image
PASS	medium	vpc	us-east-1	vpc_endpoint_service_allowed_principal_trust_boundaries	Find trust boundaries in VPC endpoint services allowed principles	vpc-en-02608a605d3110f	VPC Endpoint Service vpc-en-02608a605d3110f has no allowed principals.	Account VPC could be linked to other accounts	In multi-Account environments identify untrusted links. Check trust chaining and dependencies between accounts	❌ AWS Well-Architected Framework Security Pillar: SEC06-BP01
INFO	medium	account	us-east-1	account_maintain_current_contact_details	Maintain current contact details.	38639732453	Manual check: Login to the AWS Console. Choose your account name on the top right of the window -> My Account -> Contact Information	Ensure contact email and telephone details for AWS accounts are current and map to more than one individual in your organization. An AWS account supports a number of contact details, and users will use these to contact the account owner if actively judged to be in breach of acceptable Use Policy. If an AWS account is observed to be behaving in a prohibited or suspicious manner, AWS will attempt to contact the account owner by email and phone using the	Using the Billing and Cost Management console complete contact details.	<CS-1.4.1.1> <CS-2.0.2.1.1> <CS-1.5.1.1> <AWS Well-Architected Framework Security Pillar: SEC03-BP03, SEC10-BP04, SEC05-BP02> op.ark7.com en 1

[illegible]