



Uniwersytet
Wrocławski



University of Wrocław

Pokor Fanclub

Olaf Surgut, Rafał Mańczyk, Krzysztof Olejnik

AMPPZ 2024

15-17 November

1 Contest

2 Mathematics

3 Data structures

4 Numerical

5 Number theory

6 Combinatorial

7 Graph

8 Geometry

9 Strings

10 Various

Contest (1)

```
template.cpp 38 lines
#pragma GCC optimize("Ofast,unroll-loops")
#pragma GCC target("popcnt,avx,tune=native")
#include <bits/stdc++.h>
using namespace std;
#define int long long
#define ll long long
#define ld long double
#define endl '\n'
#define st first
#define nd second
#define pb push_back
#define eb emplace_back
#define sz(x) (int)(x).size()
#define all(x) (x).begin(), (x).end()
#define FOR(i,l,r) for(int i=(l);i<=(r);i++)
#define ROF(i,r,l) for(int i=(r);i>=(l);i--)
#ifdef DEBUG
auto&operator<<(auto&o,pair<auto,auto>p){return o<<"("
<<p.first<<"", "<<p.second<<"");}
auto operator<<(auto&o,auto x)->decltype(x.end(),o){o<<
"{";int i=0;for(auto e:x)o<<"", "+!i++<<e;return o
<<"");}
#define debug(X...) cerr<<["#X"]": ",[] (auto...$){(cerr
<<$<<"", "...)<<endl;}(X)
#else
#define debug(...){}
#endif
#define rep(i, a, b) for(int i = a; i < (b); ++i)
typedef pair<int, int> pii;
typedef vector<int> vi;
signed main() {
ios::sync_with_stdio(false);
cin.tie(nullptr);
return 0;
}
```

```
pokorrc 8 lines
c() {
g++ $1.cpp -o $1 -std=c++17 -Wall -Wshadow \
-fsanitize=address,undefined -g -DDEBUG -DLOCAL
}
nc() { g++ $1.cpp -o $1 -std=c++17 -O3; }
r() { command time -f "%Us %M KB" ./$1; }
libhash() { cat $1.cpp | cpp -dD -P -fpreprocessed | \
tr -d '[:space:]'| md5sum |cut -c-6; }
```

```
.vimrc 7 lines
syntax on
set nu hls is ts=4 si sw=4
" Select region and then type :Hash to hash your
selection.
" Useful for verifying that there aren't mistypes.
ca Hash w !cpp -dD -P -fpreprocessed \ | tr -d '[:space
:]' \
\ | md5sum \ | cut -c-6
```

```
hash.sh 3 lines
# Hashes a file, ignoring all whitespace and comments.
Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]'| md5sum |
cut -c-6
```

Mathematics (2)

2.1 Equations

20
$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

22 The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by = e &\Rightarrow x = \frac{ed - bf}{ad - bc} \\ cx + dy = f &\Rightarrow y = \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

2.2 Recurrences

If $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$, and r_1, \dots, r_k are distinct roots of $x^k - c_1x^{k-1} - \dots - c_k$, there are d_1, \dots, d_k s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1n + d_2)r^n$.

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$$m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$

2.4.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux


$$F = b^2 + d^2 - a^2 - c^2:$$

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and

$$A = \sqrt{(p - a)(p - b)(p - c)(p - d)}.$$

2.4.3 Spherical coordinates



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \text{acos}(z/\sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \text{atan2}(y, x) \end{aligned}$$

2.5 Derivatives/Integrals

$$\int \sqrt{a^2 + x^2} dx = \frac{x}{2} \sqrt{a^2 + x^2} + \frac{a^2}{2} \ln(x + \sqrt{a^2 + x^2})$$

$$\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{|a|}$$

$$\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{|a|} = -\arccos \frac{x}{|a|}$$

$$\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln(x + \sqrt{a^2 + x^2})$$

Sub $s = \tan(x/2)$ to get: $dx = \frac{2 ds}{1 + s^2}$

$$\sin x = \frac{2s}{1 + s^2}, \cos x = \frac{1 - s^2}{1 + s^2}$$

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

(Integration by parts) $\int \tan ax = -\frac{\ln |\cos ax|}{a}$

$$\int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$

$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x), \int xe^{ax} dx = \frac{e^{ax}}{a^2}(ax - 1)$$

$$\frac{d}{dx} \tan x = 1 + \tan^2 x, \frac{d}{dx} \arctan x = \frac{1}{1 + x^2}$$

Curve length: $\int_a^b \sqrt{1 + (f'(x))^2} dx$

When $X(t), Y(t) : \int_a^b \sqrt{(X'(t))^2 + (Y'(t))^2} dt$

Solid of revolution vol: $\pi \int_a^b (f(x))^2 dx$

Surface area: $2\pi \int_a^b |f(x)| \sqrt{1 + (f'(x))^2} dx$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$1 + 2 + 3 + \dots + n = \frac{n(n + 1)}{2}$$

$$1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n + 1)(n + 1)}{6}$$

$$1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n + 1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30}$$

2.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, \quad (-\infty < x < \infty)$$
$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, \quad (-1 < x \leq 1)$$
$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, \quad (-1 \leq x \leq 1)$$
$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, \quad (-\infty < x < \infty)$$
$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, \quad (-\infty < x < \infty)$$

2.8 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.8.1 Discrete distributions
Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\text{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p .
First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, \quad k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$
$$\mu = \lambda, \sigma^2 = \lambda$$

2.8.2 Continuous distributions
Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$
$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$
$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let X_1, X_2, \dots be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \Pr(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

π is a stationary distribution if $\pi = \pi \mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i . π_j/π_i is the expected number of visits in state j between two visits in state i .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i 's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1).
 $\lim_{k \rightarrow \infty} \mathbf{P}^k = \mathbf{1}\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets \mathbf{A} and \mathbf{G} , such that all states in \mathbf{A} are absorbing ($p_{ii} = 1$), and all states in \mathbf{G} leads to an absorbing state in \mathbf{A} . The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j , is $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is i , is $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$.

Data structures (3)

PBDS.h

```
Description: Policy Based Data Structures 460200, 17 lines
// Order Statistics Tree: Caution: Not a multiset!
#include <bits/extc++.h>
using namespace __gnu_pbds;
template <class T> using Tree = tree<T, null_type, less
<T>, rb_tree_tag,
tree_order_statistics_node_update>;
Tree<int> t, t2;
auto it = t.insert(10).first; // it == t.upper_bound(9)
;
t.order_of_key(10); // # of entries strictly smaller
than key
t.join(t2); // fast only if max(T) < min(T2) or min(T)
> max(T2)
// Hash Table: faster but can lead to MLE (1.5x worse
performance), initial capacity must = 2^k
struct chash { // large odd number for C
    const uint64_t C = 1l(4e18 * acos(0)) | 7l;
    ll operator()(ll x) const { return __builtin_bswap64(
        x * C); }
};
gp_hash_table<ll, int, chash> h({}, {}, {}, {}, {1 <<
16}); // cc_hash_table also exists if needed
```

HashMap.h

```
Description: Hash map with mostly the same API as un-
ordered_map, but ~3x faster. Uses 1.5x memory. Initial ca-
pacity must be a power of 2 (if provided). d77092, 7 lines
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = 1l(4e18 * acos(0)) | 7l;
    ll operator()(ll x) const { return __builtin_bswap64(
        x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{
1<<16});
```

SegmentTree.h

```
Description: Zero-indexed max-tree. Bounds are inclusive to
the left and exclusive to the right. Can be changed by mod-
ifying T, f and unit.
Time: O(log N) 0f4bdb, 19 lines
struct Tree {
    typedef int T;
    static constexpr T unit = INT_MIN;
    T f(T a, T b) { return max(a, b); } // (any
associative fn)
```

```
vector<T> s; int n;
Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
        s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
}
T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2) ra = f(ra, s[b++]);
        if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
}
};
```

LazySegmentTree.h

```
Description: Segment tree with ability to add or set values of
large intervals, and compute max of intervals. Can be changed
to other things. Use with a bump allocator for better perfor-
mance, and SmallPtr or implicit indices to save memory.
Usage: Node* tr = new Node(v, 0, sz(v));
Time: O(log N).
"../various/BumpAllocator.h" 34ecf5, 50 lines
const int inf = 1e9;
struct Node {
    Node *l = 0, *r = 0;
    int lo, hi, mset = inf, madd = 0, val = -inf;
    Node(int lo, int hi) : lo(lo), hi(hi) {} // Large interval
of -inf
    Node(vi& v, int lo, int hi) : lo(lo), hi(hi) {
        if (lo + 1 < hi) {
            int mid = lo + (hi - lo)/2;
            l = new Node(v, lo, mid); r = new Node(v, mid, hi
            );
            val = max(l->val, r->val);
        }
        else val = v[lo];
    }
    int query(int L, int R) {
        if (R <= lo || hi <= L) return -inf;
        if (L <= lo && hi <= R) return val;
        push();
        return max(l->query(L, R), r->query(L, R));
    }
    void set(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) mset = val = x, madd = 0;
        else {
            push(), l->set(L, R, x), r->set(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void add(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) {
            if (mset != inf) mset += x;
            else madd += x;
            val += x;
        }
        else {
            push(), l->add(L, R, x), r->add(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void push() {
        if (!l) {
            int mid = lo + (hi - lo)/2;
            l = new Node(lo, mid); r = new Node(mid, hi);
        }
        if (mset != inf)
            l->set(lo,hi,mset), r->set(lo,hi,mset), mset =
            inf;
        else if (madd)
            l->add(lo,hi,madd), r->add(lo,hi,madd), madd = 0;
    }
};
```


UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().

Usage: int t = uf.time(); ...; uf.rollback(t);

Time: $\mathcal{O}(\log(N))$

```

struct RollbackUF {
    vi e; vector<pii> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
    void rollback(int t) {
        for (int i = time(); i --> t;)
            e[st[i].first] = st[i].second;
        st.resize(t);
    }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        st.push_back({a, e[a]});
        st.push_back({b, e[b]});
        e[a] += e[b]; e[b] = a;
        return true;
    }
};

```

SubMatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).

Usage: SubMatrix<int> m(matrix);

m.sum(0, 0, 2, 2); // top left 4 elements

Time: $\mathcal{O}(N^2 + Q)$

```

template<class T>
struct SubMatrix {
    vector<vector<T>> p;
    SubMatrix(vector<vector<T>>& v) {
        int R = sz(v), C = sz(v[0]);
        p.assign(R+1, vector<T>(C+1));
        rep(r,0,R) rep(c,0,C)
            p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
    }
    T sum(int u, int l, int d, int r) {
        return p[d][r] - p[d][l] - p[u][r] + p[u][l];
    }
};

```

Matrix.h

Description: Basic operations on square matrices.

Usage: Matrix<int, 3> A;

A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};

vector<int> vec = {1,2,3};

vec = (A^N) * vec;

```

template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};
    vector<int> vec = {1,2,3};
    vec = (A^N) * vec;
};

template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][j] += d[i][k]*m.d[k][j];
        return a;
    }
    vector<T> operator*(const vector<T>& vec) const {
        vector<T> ret(N);
        rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator^(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i,0,N) a.d[i][i] = 1;
        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p >>= 1;
        }
    }
};

```

```

}
return a;
}
};

```

LineContainer.h

Description: Container where you can add lines of the form $kx+m$, and query maximum values at points x . Useful for dynamic programming ("convex hull trick").

Time: $\mathcal{O}(\log N)$

```

struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? y->m : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}); y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};

```

Treap.h

Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.

Time: $\mathcal{O}(\log N)$

```

struct Node {
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }
template<class F> void each(Node* n, F f) {
    if (n) { each(n->l, f); f(n->val); each(n->r, f); }
}

pair<Node*, Node*> split(Node* n, int k) {
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for
        lower_bound(k)
        auto pa = split(n->l, k);
        n->l = pa.second;
        n->recalc();
        return {pa.first, n};
    } else {
        auto pa = split(n->r, k - cnt(n->l) - 1); // and
        just "k"
        n->r = pa.first;
        n->recalc();
        return {n, pa.second};
    }
}

Node* merge(Node* l, Node* r) {
    if (!l) return r;
    if (!r) return l;
};

```

```

if (l->y > r->y) {
    l->r = merge(l->r, r);
    l->recalc();
    return l;
} else {
    r->l = merge(l, r->l);
    r->recalc();
    return r;
}
}

Node* ins(Node* t, Node* n, int pos) {
    auto pa = split(t, pos);
    return merge(merge(pa.first, n), pa.second);
}

// Example application: move the range [l, r) to index
// k
void move(Node*& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}

```

LiChao.h

Description: Extended Li Chao tree (segment tree for functions). Let F be a family of functions closed under function addition, such that for every $f \neq g$ from the family F there exists x such that $f(z) \leq g(z)$ for $z \leq x$ else $f(z) \geq g(z)$ or the other way around (intersect at one point). Typically F is the family of linear functions. DS maintains a sequence $c_0, c_1 \dots c_{n-1}$ under operations max, add.

Time: $\mathcal{O}(n \log n)$

```

struct LiChao {
    struct Func {
        ll a, b; // a*x + b
        // Evaluate function in point x
        ll operator()(ll x) const { return a*x+b; }
        Func operator+(Func r) const {
            return {a+r.a, b+r.b};
        } // Sum of two functions
    }; // ID_ADD/MAX neutral elements for add/max
    static constexpr Func ID_ADD{0, 0};
    static constexpr Func ID_MAX{0, ll(-1e9)};
    vector<Func> val, lazy;
    int len;
    // Initialize tree for n elements; time: O(n)
    LiChao(int n = 0) {
        for (len = 1; len < n; len *= 2);
        val.resize(len*2, ID_MAX);
        lazy.resize(len*2, ID_ADD);
    }
    void push(int i) {
        if (i < len) rep(j, 2) {
            lazy[i*2+j] = lazy[i*2+j] + lazy[i];
            val[i*2+j] = val[i*2+j] + lazy[i];
        }
        lazy[i] = ID_ADD;
    } // For each x in [vb;ve)
    // set c[x] = max(c[x], f(x));
    // time: O(log^2 n) in general case,
    // O(log n) if [vb;ve) = [0;len)
    void max(int vb, int ve, Func f,
        int i = 1, int b = 0, int e = -1) {
        if (e < 0) e = len;
        if (vb >= e || b >= ve || i >= len*2)
            return;
        int m = (b+e) / 2;
        push(i);
        if (b >= vb && e <= ve) {
            auto& g = val[i];
            if (g(m) < f(m)) swap(g, f);
            if (g(b) < f(b))
                max(vb, ve, f, i*2, b, m);
            else
                max(vb, ve, f, i*2+1, m, e);
        } else {
            max(vb, ve, f, i*2, b, m);
            max(vb, ve, f, i*2+1, m, e);
        }
    }
};

```

```

} // For each x in [vb;ve)
// set c[x] = c[x] + f(x);
// time: O(log^2 n) in general case,
// O(1) if [vb;ve) = [0;len)
void add(int vb, int ve, Func f,
    int i = 1, int b = 0, int e = -1) {
    if (e < 0) e = len;
    if (vb >= e || b >= ve) return;
    if (b >= vb && e <= ve) {
        lazy[i] = lazy[i] + f;
        val[i] = val[i] + f;
    } else {
        int m = (b+e) / 2;
        push(i);
        max(b, m, val[i], i*2, b, m);
        max(m, e, val[i], i*2+1, m, e);
        val[i] = ID_MAX;
        add(vb, ve, f, i*2, b, m);
        add(vb, ve, f, i*2+1, m, e);
    }
} // Get value of c[x]; time: O(log n)
auto query(int x) {
    int i = x+len;
    auto ret = val[i](x);
    while (i /= 2)
        ret = :max(ret+lazy[i](x), val[i](x));
    return ret; }
};

```

FenwickTree.h

Description: Computes partial sums $a[0] + a[1] + \dots + a[pos - 1]$, and updates single elements $a[i]$, taking the difference between the old and new value.

Time: Both operations are $\mathcal{O}(\log N)$.

```

struct FT {
    vector<ll> s;
    FT(int n) : s(n) {}
    void update(int pos, ll dif) { // a[pos] += dif
        for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
    }
    ll query(int pos) { // sum of values in [0, pos)
        ll res = 0;
        for (; pos > 0; pos &= pos - 1) res += s[pos-1];
        return res;
    }
    int lower_bound(ll sum) { // min pos st sum of [0, pos)
        // sum is .
        // Returns n if no sum is >= sum, or -1 if empty
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << 25; pw; pw >= 1) {
            if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
                pos += pw, sum -= s[pos-1];
        }
        return pos;
    }
};

```

FenwickTree2d.h

Description: Computes sums $a[i,j]$ for all $i < I$, $j < J$, and increases single elements $a[i,j]$. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).

Time: $\mathcal{O}(\log^2 N)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

```

"FenwickTree.h"
157f07, 22 lines

struct FT2 {
    vector<vi> ys; vector<FT> ft;
    FT2(int limx) : ys(limx) {}
    void fakeUpdate(int x, int y) {
        for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
    }
    void init() {
        for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
    }
    int ind(int x, int y) {
};

```

```
        return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
        ft[x].update(ind(x, y), dif);
}
ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
        sum += ft[x-1].query(ind(x-1, y));
    return sum;
}
};
```

WaveletTree.h

Description: Wavelet tree. Supports fast kth order statistics on ranges (no updates).

Time: $\mathcal{O}(\log N)$

587095, 35 lines

```
struct WaveletTree {
    vector<vi> seq, left;
    int len;
    WaveletTree() {}
    // time and space:  $\mathcal{O}((n+maxVal) \log maxVal)$ 
    // Values are expected to be in  $[0;maxVal]$ .
    WaveletTree(const vi& elems, int maxVal) {
        for (len = 1; len < maxVal; len *= 2);
        seq.resize(len*2); left.resize(len*2);
        seq[1] = elems; build(1, 0, len);
    }
    void build(int i, int b, int e) {
        if (i >= len) return;
        int m = (b+e) / 2;
        left[i].pb(0);
        for(auto &x : seq[i]) {
            left[i].pb(left[i].back() + (x < m));
            seq[i*2 + (x >= m)].pb(x);
        }
        build(i*2, b, m); build(i*2+1, m, e);
    } // Find k-th (0 indexed) smallest element in [begin, end)
    int kth(int begin, int end, int k, int i=1) {
        if (i >= len) return seq[i][0];
        int x = left[i][begin], y = left[i][end];
        if (k < y-x) return kth(x, y, k, i*2);
        return kth(begin-x, end-y, k-y+x, i*2+1);
    } // Count number of elements >= vb and < ve
    int count(int begin, int end, int vb, int ve, int i = 1, int b = 0, int e = -1) {
        if (e < 0) e = len;
        if (b >= ve || vb >= e) return 0;
        if (b >= vb && e <= ve) return end-begin;
        int m = (b+e) / 2; int x = left[i][begin], y = left[i][end];
        return count(x, y, vb, ve, i*2, b, m) + count(begin-x, end-y, vb, ve, i*2+1, m, e);
    }
};
```

RMQ.h

Description: Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time.

Usage: RMQ rmq(values);

rmq.query(inclusive, exclusive);

Time: $\mathcal{O}(|V| \log |V| + Q)$

510c32, 16 lines

```
template<class T>
struct RMQ {
    vector<vector<T>> jmp;
    RMQ(const vector<T>& V) : jmp(1, V) {
        for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
            jmp.emplace_back(sz(V) - pw * 2 + 1);
            rep(j,0,sz(jmp[k]))
                jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
        }
    }
    T query(int a, int b) {
```

```
        assert(a < b); // or return inf if a == b
        int dep = 31 - __builtin_clz(b - a);
        return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
    }
};
```

MoQueries.h

Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change step to add/remove the edge (a,c) and remove the initial add call (but keep in).

Time: $\mathcal{O}(N\sqrt{Q})$

a12ef4, 49 lines

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer
vi mo(vector<pii> Q) {
    int L = 0, R = 0, blk = 350; //  $\sim N/\sqrt{Q}$ 
    vi s(sz(Q)), res = s;
    #define K(x) pii(x.first/blk, x.second ^ ~(x.first/blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
    for (int qi : s) {
        pii q = Q[qi];
        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    }
    return res;
}
vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0) {
    int N = sz(ed), pos[2] = {}, blk = 350; //  $\sim N/\sqrt{Q}$ 
    vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
    ;
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    };
    dfs(root, -1, 0, dfs);
    #define K(x) pii(I[x][0] / blk, I[x][1] ^ ~(I[x][0] / blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
    for (int qi : s) rep(end,0,2) {
        int &a = pos[end], b = Q[qi][end], i = 0;
        #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
            else { add(c, end); in[c] = 1; } a = c; }
        while (!L[b] <= L[a] && R[a] <= R[b])
            I[i++] = b, b = par[b];
        while (a != b) step(par[a]);
        while (i--) step(I[i]);
        if (end) res[qi] = calc();
    }
    return res;
}
```

Numerical (4)

4.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
```

```
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val += x) += a[i];
        return val;
    }
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0 +b, b=c;
        a.pop_back();
    }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.

Usage: polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0

Time: $\mathcal{O}(n^2 \log(1/\epsilon))$

"Polynomial.h" b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
    }
    return ret;
}
```

PolyInterpolate.h

Description: Given n points (x[i], y[i]), computes an $n-1$ -degree polynomial p that passes through them: $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.

Time: $\mathcal{O}(n^2)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

BerlekampMassey.h

Description: Recovers any n -order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.

Usage: berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}

Time: $\mathcal{O}(N^2)$

".../number-theory/ModPow.h" 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1;
    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }
    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \geq n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp-Massey.

Usage: linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci number

Time: $\mathcal{O}(n^2 \log k)$

f4e444, 26 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);
    auto combine = [&](Poly a, Poly b) {
        Poly res(n + 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
        res.resize(n + 1);
        return res;
    };
    Poly pol(n + 1), e(pol);
    pol[0] = e[1] = 1;
    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(pol, e);
        e = combine(e, e);
    }
    ll res = 0;
    rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
    return res;
}
```

4.2 Optimization

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4 , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.

```

Usage: double sphereVolume = quad(-1, 1, [](double x)
{
return quad(-1, 1, [&](double y) {
return quad(-1, 1, [&](double z) {
return x*x + y*y + z*z < 1; }));});});
92dd79, 15 lines

typedef double d;
#define S(a,b) ((f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) /
6
template <class F>
d rec(F& f, d a, d b, d eps, d S) {
d c = (a + b) / 2;
d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
if (abs(T - S) <= 15 * eps || b - a < 1e-10)
return T + (T - S) / 15;
return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps /
2, S2);
}

template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
return rec(f, a, b, eps, S(a, b));
}

```

Simplex.h

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b$, $x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.

Usage: vvd A = {{1,-1}, {-1,1}, {-1,-2}};
vvd b = {1,1,-4}, c = {-1,-1}, x;
T val = LPSolver(A, b, c).solve(x);
Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case. aa8530, 68 lines

```

typedef double T; // long double, Rational, double +
mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;
const T eps = 1e-8, inf = 1./0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[
s])) s=j
struct LPSolver {
int m, n;
vi N, B;
vvd D;
LPSolver(const vvd& A, const vd& b, const vd& c) :
m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1]
= b[i];}
rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
N[n] = -1; D[m+1][n] = 1;
}
void pivot(int r, int s) {
T *a = D[r].data(), inv = 1 / a[s];
rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
T *b = D[i].data(), inv2 = b[s] * inv;
rep(j,0,n+2) b[j] -= a[j] * inv2;
b[s] = a[s] * inv2;
}
rep(j,0,n+2) if (j != s) D[r][j] **= inv;
rep(i,0,m+2) if (i != r) D[i][s] **= -inv;
D[r][s] = inv;
swap(B[r], N[s]);
}
bool simplex(int phase) {
int x = m + phase - 1;
for (;;) {
int s = -1;
rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
if (D[x][s] >= -eps) return true;
int r = -1;
rep(i,0,m) {
if (D[i][s] <= eps) continue;

```

```

if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
< MP(D[r][n+1] / D[r][s], B[r])) r
= i;
}
if (r == -1) return false;
pivot(r, s);
}
}
T solve(vd &x) {
int r = 0;
rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
if (D[r][n+1] < -eps) {
pivot(r, n);
if (!simplex(2) || D[m+1][n+1] < -eps) return -
inf;
rep(i,0,m) if (B[i] == -1) {
int s = 0;
rep(j,1,n+1) ltj(D[i]);
pivot(i, s);
}
}
bool ok = simplex(1); x = vd(n);
rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
return ok ? D[m][n+1] : inf;
}
};

```

4.3 Matrices

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.
Time: $\mathcal{O}(N^3)$ bd5cec, 15 lines

```

double det(vector<vector<double>>& a) {
int n = sz(a); double res = 1;
rep(i,0,n) {
int b = i;
rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b =
j;
if (i != b) swap(a[i], a[b]), res *= -1;
res *= a[i][i];
if (res == 0) return 0;
rep(j,i+1,n) {
double v = a[j][i] / a[i][i];
if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
}
}
return res;
}

```

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}(N^3)$ 3313dc, 18 lines

```

const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
int n = sz(a); ll ans = 1;
rep(i,0,n) {
rep(j,i+1,n) {
while (a[j][i] != 0) { // gcd step
ll t = a[i][i] / a[j][i];
if (t) rep(k,i,n)
a[i][k] = (a[i][k] - a[j][k] * t) % mod;
swap(a[i], a[j]);
ans *= -1;
}
}
ans = ans * a[i][i] % mod;
if (!ans) return 0;
}
return (ans + mod) % mod;
}
}

```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.

Time: $\mathcal{O}(n^2 m)$ 44c9ab, 38 lines

```

typedef vector<double> vd;
const double eps = 1e-12;
int solveLinear(vector<vd>& A, vd& b, vd& x) {
int n = sz(A), m = sz(x), rank = 0, br, bc;
if (n) assert(sz(A[0]) == m);
vi col(m); iota(all(col), 0);
rep(i,0,n) {
double v, bv = 0;
rep(r,i,n) rep(c,i,m)
if ((v = fabs(A[r][c])) > bv)
br = r, bc = c, bv = v;
if (bv <= eps) {
rep(j,i,n) if (fabs(b[j]) > eps) return -1;
break;
}
swap(A[i], A[br]);
swap(b[i], b[br]);
swap(col[i], col[bc]);
rep(j,0,n) swap(A[j][i], A[j][bc]);
bv = 1/A[i][i];
rep(j,i+1,n) {
double fac = A[j][i] * bv;
b[j] -= fac * b[i];
rep(k,i+1,m) A[j][k] -= fac*A[i][k];
}
rank++;
}
x.assign(m, 0);
for (int i = rank; i--;) {
b[i] /= A[i][i];
x[col[i]] = b[i];
rep(j,0,i) b[j] -= A[j][i] * b[i];
}
return rank; // (multiple solutions if rank < m)
}

```

SolveLinear2.h

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:

"SolveLinear.h" 08e495, 7 lines

```

rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
x[col[i]] = b[i] / A[i][i];
fail;; }

```

SolveLinearBinary.h

Description: Solves $Ax = b$ over \mathbb{F}_2 . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b .

Time: $\mathcal{O}(n^2 m)$ fa2d7a, 34 lines

```

typedef bitset<1000> bs;
int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
int n = sz(A), rank = 0, br;
assert(m <= sz(x));
vi col(m); iota(all(col), 0);
rep(i,0,n) {
for (br=i; br<n; ++br) if (A[br].any()) break;
if (br == n) {
rep(j,i,n) if(b[j]) return -1;
break;
}
int bc = (int)A[br]._Find_next(i-1);
swap(A[i], A[br]);
swap(b[i], b[br]);
swap(col[i], col[bc]);
rep(j,0,n) if (A[j][i] != A[j][bc]) {
A[j].flip(i); A[j].flip(bc);
}
rep(j,i+1,n) if (A[j][i]) {

```

```

b[j] ^= b[i];
A[j] ^= A[i];
}
rank++;
}
x = bs();
for (int i = rank; i--;) {
if (!b[i]) continue;
x[col[i]] = 1;
rep(j,0,i) b[j] ^= A[j][i];
}
return rank; // (multiple solutions if rank < m)
}

```

MatrixInverse.h

Description: Invert matrix A . Returns rank; result is stored in A unless singular ($\text{rank} < n$). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of $A \pmod p$, and k is doubled in each step.

Time: $\mathcal{O}(n^3)$ ebf6f6, 35 lines

```

int matInv(vector<vector<double>>& A) {
int n = sz(A); vi col(n);
vector<vector<double>> tmp(n, vector<double>(n));
rep(i,0,n) tmp[i][i] = 1, col[i] = i;
rep(i,0,n) {
int r = i, c = i;
rep(j,i,n) rep(k,i,n)
if (fabs(A[j][k]) > fabs(A[r][c]))
r = j, c = k;
if (fabs(A[r][c]) < 1e-12) return i;
A[i].swap(A[r]); tmp[i].swap(tmp[r]);
rep(j,0,n)
swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c
]);
swap(col[i], col[c]);
double v = A[i][i];
rep(j,i+1,n) {
double f = A[j][i] / v;
A[j][i] = 0;
rep(k,i+1,n) A[j][k] -= f*A[i][k];
rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
}
rep(j,i+1,n) A[i][j] /= v;
rep(j,0,n) tmp[i][j] /= v;
A[i][i] = 1;
}
for (int i = n-1; i > 0; --i) rep(j,0,i) {
double v = A[j][i];
rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
}
rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
return n;
}
}

```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d,p,q,b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$$

where a_0, a_{n+1} , b_i , c_i and d_i are known. a can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\})$$

Fails if the solution is not unique.

If $|d_i| > |p_i| + |q_{i-1}|$ for all i , or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.
Time: $\mathcal{O}(N)$

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>&
    super,
    const vector<T>& sub, vector<T> b) {
    int n = sz(b); vi tr(n);
    rep(i,0,n-1) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag
            i /= 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i
                ];
            diag[i+1] = sub[i]; tr[++i] = 1;
        } else {
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        }
    }
    for (int i = n; i--;) {
        if (tr[i]) {
            swap(b[i], b[i-1]);
            diag[i-1] = diag[i];
            b[i] /= super[i-1];
        } else {
            b[i] /= diag[i];
            if (i) b[i-1] -= b[i]*super[i-1];
        }
    }
    return b;
}
```

4.4 Fourier transforms

FastFourierTransform.h

Description: `fft(a)` computes $f(k) = \sum_x a[x] \exp(2\pi i \cdot kx / N)$ for all k . N must be a power of 2. Useful for convolution: $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multi-ply pointwise, divide by n , reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16} ; higher for random inputs). Otherwise, use NTT/FFT-Mod.
Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$)

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (~ 10% faster if
        double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n); rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i
            /2];
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            C z = rt[j+k] * a[i+j+k]; // (85% faster if hand-
                rolled)
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
}
vd conv(const vd& a, const vd& b) {
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);
    int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
    vector<C> in(n), out(n);
    copy(all(a), begin(in));
    rep(i,0,sz(b)) in[i].imag(b[i]);
    fft(in);
```

```
for (C& x : in) x *= x;
rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
fft(out);
rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
return res;
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolu-tions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)
"FastFourierTransform.h" 82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt
        (M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] %
        cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] %
        cut);
    fft(L), fft(R);
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) /
            1i;
    }
    fft(outl), fft(outs);
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])
            +.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5)
            ;
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

NumberTheoreticTransform.h

Description: `ntt(a)` computes $f(k) = \sum_x a[x]g^{xk}$ for all k , where $g = \text{root}^{(\text{mod}-1)/N}$. N must be a power of 2. Use-ful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a . For arbitrary modulo, see FFTMod. $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the in-puts, multiply pointwise, divide by n , reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.

```
Time:  $\mathcal{O}(N \log N)$ 
"../number-theory/ModPow.h" ced03d, 35 lines
const ll mod = (119 << 23) + 1, root = 62; // =
    998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26,
    479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vl rt(2, 1);
    for (static int k = 2, s = 2; k < n; k *= 2, s++) {
        rt.resize(n);
        ll z[] = {1, modpow(root, mod >> s)};
        rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
```

```
        ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i
            + j];
        a[i + j + k] = ai - z + (z > ai ? mod : 0);
        ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    vl L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv %
            mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where \oplus is one of AND, OR, XOR. The size of a must be a power of two.
Time: $\mathcal{O}(N \log N)$

```
void FST(vi& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,i+
            step) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                inv ? pii(v, u - v) : pii(u + v, u); // OR
                pii(u + v, u - v); // XOR
            }
        }
    }
    if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
```

Number theory (5)

5.1 Modular arithmetic

ModInverse.h

Description: Pre-computation of modular inverses. Assumes $\text{LIM} \leq \text{mod}$ and that mod is a prime.

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] %
    mod;
```

ModPow.h

```
const ll mod = 1000000007; // faster if const
ll modpow(ll b, ll e) {
    ll ans = 1;
    for (; e; b = b * b % mod, e /= 2)
        if (e & 1) ans = ans * b % mod;
    return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. `modLog(a,1,m)` can be used to calculate the order of a .

Time: $\mathcal{O}(\sqrt{m})$

```
ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
```

```
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(1,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

ModSum.h

Description: Sums of mod'd arithmetic progressions. $\text{modsum}(\text{to}, c, k, m) = \sum_{i=0}^{\text{to}-1} (ki + c) \% m$. `divsum` is similar but for floored division.
Time: $\log(m)$, with a large constant.

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m-1 - c, m,
        k);
}
ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k,
        m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \pmod c$ (or $a^b \pmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.
Time: $\mathcal{O}(1)$ for `modmul`, $\mathcal{O}(\log b)$ for `modpow`

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2)
        if (e & 1) ans = modmul(ans, b, mod);
    return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solu-tion).

Time: $\mathcal{O}(\log^2 p)$ worst case, $\mathcal{O}(\log p)$ for most p

```
"ModPow.h" 19a793, 24 lines
ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no
        solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8
        == 5
    ll s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0)
        ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    ll x = modpow(a, (s + 1) / 2, p);
    ll b = modpow(a, s, p), g = modpow(n, s, p);
    for (; r = m) {
        ll t = b;
        for (m = 0; m < r && t != 1; ++m)
            t = t * t % p;
        if (m == 0) return x;
        ll gs = modpow(g, 1LL << (r - m - 1), p);
        g = gs * gs % p;
        x = x * gs % p;
        b = b * g % p;
```

```

    }
}

```

5.2 Primality

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.

Time: LIM=1e9 \approx 1.5s

6b2912, 20 lines

```

const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
    const int S = (int)round(sqrt(LIM)), R = LIM / 2;
    vi pr = {2}, sieve(S+1); pr.reserve((int)(LIM/log(LIM)
        *1.1));
    vector<pii> cp;
    for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
        cp.push_back({i, i * i / 2});
        for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
    }
    for (int L = 1; L <= R; L += S) {
        array<bool, S> block{};
        for (auto &[p, idx] : cp)
            for (int i=idx; i < S+L; idx = (i+=p)) block[i-L]
                = 1;
        rep(i,0,min(S, R - L))
            if (!block[i]) pr.push_back((L + i) * 2 + 1);
    }
    for (int i : pr) isPrime[i] = 1;
    return pr;
}

```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.

Time: 7 times the complexity of $a^b \bmod c$.

"ModMulLL.h" 60dcd1, 12 lines

```

bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull a[] = {2, 325, 9375, 28178, 450775, 9780504,
        1795265022},
        s = __builtin_ctzll(n-1), d = n >> s;
    for (ull a : A) { // ^ count trailing zeroes
        ull p = modpow(a%n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = modmul(p, p, n);
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}

```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

Time: $\mathcal{O}(n^{1/4})$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h" d8d98d, 18 lines

```

ull pollard(ull n) {
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](ull x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n)) prd
            = q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}
vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), all(r));
    return l;
}

```

```

}

```

Pell.h

Description: $O(\log n)$, pell(n) oblicza rozwiązanie fundamentalne $x^2 - ny^2 = 1$, zwraca (0,0) jeżeli nie ma.

8b143f, 27 lines

```

pair<LL, LL> pell(LL n) {
    LL s = LL(sqrtl(n));
    if (s * s == n) return {0, 0};
    LL m = 0, d = 1, a = s;
    __int128 num1 = 1, num2 = a, den1 = 0, den2 = 1;
    while (num2 * num2 - n * den2 * den2 != 1) {
        m = d * a - m;
        d = (n - m * m) / d;
        a = (s + m) / d;
        if (num2 > (1ll << 62) / a) return {0, 0};
        tie(num1, num2) = pair(num2, a * num2 + num1);
        tie(den1, den2) = pair(den2, a * den2 + den1);
    }
    return {num2, den2};
}
vector<pair<LL, LL>> all_pell(LL n, LL limit) {
    auto [x0, y0] = pell(n);
    if (!x0) return {};
    vector<pair<LL, LL>> ret;
    __int128 x = x0, y = y0;
    while (x <= limit) {
        ret.emplace_back(x, y);
        if (y0 * y > (1ll << 62) / n) break;
        tie(x, y) = pair(x0 * x + n * y0 * y, x0 * y + y0 *
            x);
    }
    return ret;
}
}

```

FloorSum.h

Description: $O(\log a)$, liczy $\sum_{i=0}^{n-1} \left\lfloor \frac{a \cdot i + b}{c} \right\rfloor$. Działa dla $0 \leq a, b < c$ oraz $1 \leq c, n \leq 10^9$.

78c6f7, 15 lines

```

LL floor_sum(LL n, LL a, LL b, LL c) {
    LL ans = 0;
    if (a >= c) {
        ans += (n - 1) * n * (a / c) / 2;
        a %= c;
    }
    if (b >= c) {
        ans += n * (b / c);
        b %= c;
    }
    LL d = (a * (n - 1) + b) / c;
    if (d == 0) return ans;
    ans += d * (n - 1) - floor_sum(d, c, c - b - 1, a);
    return ans;
}

```

5.3 Divisibility

euclid.h

Description: Finds two integers x and y , such that $ax+by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of a modulo b .

a3b98f, 5 lines

```

ll euclid(ll a, ll b, ll &x, ll &y) {
    if (!b) return x = 1, y = 0, a;
    ll d = euclid(b, a % b, y, x);
    return y -= a/b * x, d;
}

```

CRT.h

Description: Chinese Remainder Theorem.

crt(a, m, b, n) computes x such that $x \equiv a \pmod{m}$, $x \equiv b \pmod{n}$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\log(n)$

"euclid.h" 04d93a, 7 lines

```

ll crt(ll a, ll m, ll b, ll n) {
    if (n > m) swap(a, b), swap(m, n);
    ll x, y, g = euclid(m, n, x, y);
}

```

```

assert((a - b) % g == 0); // else no solution
x = (b - a) % n * x % n / g * m + a;
return x < 0 ? x + m*n/g : x;
}

```

phiFunction.h

Description: Euler's ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} \dots p_r^{k_r}$ then $\phi(n) = (p_1-1)p_1^{k_1-1} \dots (p_r-1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1-1/p)$. $\sum_{d|n} \phi(d) = n$, $\sum_{1 \leq k \leq n, \gcd(k,n)=1} k = n\phi(n)/2$, $n > 1$. Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod{n}$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod{p}, \forall a$

c9f4dd, 8 lines

```

const int LIM = 5000000;
int phi[LIM];
void calculatePhi() {
    rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] /
            i;
}

```

Min25.h

Description: Calculates prefsums of multiplicative function at each floor(N/i). keys[id(N/i)]=N/i. Remember about overflows. See example below.

Time: $\mathcal{O}\left(\frac{n^{3/4}}{\log n}\right)$

f4fd1a, 50 lines

```

vector<ll> global_primes; // global_primes[-1]>sqrt(N)
template<typename T>
struct Min25 {
    ll N;
    vector<ll> keys, primes;
    Min25(ll N_) : N(N_) {
        for (ll l = 1; l <= N; ++l)
            keys.pb(l = N / (N / l));
        for (int i = 0; global_primes[i] * global_primes[i]
            <= N; ++i)
            primes.pb(global_primes[i]);
    }
    ll id(ll x) {
        ll id = x < N / x ? x - 1 : sz(keys) - N / x;
        assert(keys[id] == x);
        return id;
    }
    // f has to be TOTALLY multiplicative
    // pref(x) is regular prefix sum function of f
    vector<T> overPrimes(auto pref) {
        vector<T> dp(sz(keys));
        rep(i, sz(keys))
            dp[i] = pref(keys[i]) - T(1);
        for (ll p : primes) {
            auto fp = dp[p - 1] - dp[p - 2];
            for (int i = sz(keys) - 1; i >= 0 && p * p <=
                keys[i]; --i)
                dp[i] = dp[i] - (dp[id(keys[i] / p)] - dp[p -
                    2]) * fp;
        }
        return dp;
    }
    // dp are prefix sums of f over primes
    // f(p, k, p**k) calculates f on primes powers
    void fullSum(vector<T> &dp, auto f) {
        for (ll p : primes | views::reverse) {
            for (int i = sz(keys) - 1; i >= 0 && p * p <=
                keys[i]; --i) {
                for (ll k = 1, q = p; q * p <= keys[i]; ++k, q
                    *= p)
                    dp[i] = dp[i] + f(p, k + 1, q * p) + f(p, k,
                        q) * (dp[id(keys[i] / q)] - dp[p - 1]);
            }
        }
        for (auto &v : dp) v = v + T(1);
    }
}

```

```

};
vector<ll> exampleUsage(Min25<ll> &m) { // OVERFLOWS!
    auto primeCnt = m.overPrimes([](ll x){return x; });
    auto primeSum = m.overPrimes([](ll x){return x*(x+1)
        /2; });
    vector<ll> phi; rep(i, sz(m.keys))
        phi.pb(primeSum[i] - primeCnt[i]);
    m.fullSum(phi, [](int p,int k,ll pk){return pk-pk/p;
        });
    return phi; }

```

5.4 Pisano period

$\pi(n)$ is a period of Fibonacci sequence modulo n . $\pi(nm) = \pi(n)\pi(m)$ for $n \perp m$, $\pi(p^k) = p^{k-1}\pi(p)$.

$$\pi(p) \begin{cases} = 3 & p = 2 \\ = 20 & p = 5 \\ |p-1 & p \equiv_{10} \pm 1 \\ |2(p+1) & p \equiv_{10} \pm 3 \end{cases}$$

$F_i \equiv_p -F_{i+p+1}$ for $p \equiv_{10} \pm 3$. $\pi(n) \leq 4n$ for $n \neq 2 \cdot 5^r$.

5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \quad b = k \cdot (2mn), \quad c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.6 Pythagorean Tree

Primitive Pythagorean triples form infinite ternary tree, where each triple occurs exactly once. Node is a column vector $(a, b, c = \sqrt{a^2 + b^2})$, root is (3, 4, 5), and each child is given by a product of a parent and one of the:

$$\begin{bmatrix} 1 & -2 & 2 \\ 2 & -1 & 2 \\ 2 & -2 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 2 & 2 \\ 2 & 1 & 2 \\ 2 & 2 & 3 \end{bmatrix}, \begin{bmatrix} -1 & 2 & 2 \\ -2 & 1 & 2 \\ -2 & 2 & 3 \end{bmatrix}$$

5.7 Primes

$p = 962592769$ is such that $2^{21} | p-1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a , except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2a-2}$.

5.8 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.9 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d)g(n/d)$$

Other useful formulas/forms:

$$\sum_{d|n} \mu(d) = [n = 1] \text{ (very useful)}$$
$$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n)g(d)$$

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m)g(\lfloor \frac{n}{m} \rfloor)$$

Define Dirichlet convolution as $f * g(n) = \sum_{d|n} f(d)g(n/d)$. Let $s_f(n) = \sum_{i=1}^n f(i)$. Then $s_f(n)g(1) = s_{f*g}(n) - \sum_{d=2}^n s_f(\lfloor \frac{n}{d} \rfloor)g(d)$.

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	$> \text{DBL_MAX}$		

IntPerm.h
Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.
Time: $\mathcal{O}(n)$

```
int permToInt(vi& v) {
    int use = 0, i = 0, r = 0;
    for(int x:v) r = r * ++i + __builtin_popcount(use &
        -(1<<x)),
        use |= 1 << x; // (note: minus, not ~!)
    return r;
}
```

6.1.2 Cycles

Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then

$$\sum_{n=0}^\infty g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1)+D(n-2)) = nD(n-1)+(-1)^n$$

6.1.4 Burnside's lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k)\phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \quad p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

<i>n</i>	0	1	2	3	4	5	6	7	8	9	20	50	100
<i>p</i> (<i>n</i>)	1	1	1	2	3	5	7	11	15	22	30	627	~2e5 ~2e8

6.2.2 Lucas’ Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_kp^k + \dots + n_1p + n_0$ and $m = m_kp^k + \dots + m_1p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod p$.

6.2.3 Binomials

multinomial.h

Description: Computes $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1!k_2!\dots k_n!}$.

```
ll multinomial(vi& v) {
    ll c = 1, m = v.empty() ? 1 : v[0];
    rep(i, 1, sz(v)) rep(j, 0, v[i])
        c = c * ++m / (j+1);
    return c;
}
```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t-1}$ (FFT-able).
 $B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^\infty f(i) = \int_m^\infty f(x)dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m)$$

$$\approx \left\lfloor \int_m^{\lfloor \frac{n}{k} \rfloor} f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \right\rfloor$$

IntPerm multinomial DeBruijn NimProduct

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n, k) = c(n - 1, k - 1) + (n - 1)c(n - 1, k), \quad c(0, 0) = 1$$
$$\sum_{k=0}^n c(n, k)x^k = x(x + 1) \dots (x + n - 1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$$
$$c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j + 1)$, $k + 1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n - k)E(n - 1, k - 1) + (k + 1)E(n - 1, k)$$

$$E(n, 0) = E(n, n - 1) = 1$$
$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n - 1, k - 1) + kS(n - 1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n + 1) \pmod p$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i : $n_1n_2 \dots n_k n^{k-2}$
with degrees d_i : $(n-2)!/((d_1-1)! \dots (d_n-1)!)$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, \quad C_{n+1} = \frac{2(2n+1)}{n+2} C_n, \quad C_{n+1} = \sum C_i C_{n-i}$$

$$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n + 1$ leaves (0 or 2 children).
- ordered trees with $n + 1$ vertices.
- ways a convex polygon with $n + 2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

6.4 Other

DeBruijn.h

Description: Recursive FKM, given alphabet $[0, k)$ constructs cyclic string of length k^n that contains every length n string as substr.

```
vi dseq(int k, int n) {
    if (k == 1) return {0};
    vi res, aux(n+1);
    function<void(int,int)> gen = [&](int t, int p) {
        if (t > n) { // consider lyndon word of len p
            if (n%p == 0) FOR(i, 1, p+1) res.pb(aux[i]);
        } else {
            aux[t] = aux[t-p]; gen(t+1, p);
            FOR(i, aux[t-p]+1, k) aux[t] = i, gen(t+1, t);
        }
    };
    gen(1, 1); return res;
}
```

NimProduct.h

Description: Nim Product.

```
using ull = uint64_t;
ull _nimProd2[64][64];
ull nimProd2(int i, int j) {
    if (_nimProd2[i][j]) return _nimProd2[i][j];
    if ((i & j) == 0) return _nimProd2[i][j] = 1ull << (i | j);
    int a = (i&j) & ~(i&j);
    return _nimProd2[i][j] = nimProd2(i ^ a, j)
        ^ nimProd2((i ^ a) | (a-1), (j ^ a) | (i & (a-1)));
}
ull nimProd(ull x, ull y) {
    ull res = 0;
    for (int i = 0; (x >> i) && i < 64; i++)
        if ((x >> i) & 1)
            for (int j = 0; (y >> j) && j < 64; j++)
                if ((y >> j) & 1)
                    res ^= nimProd2(i, j);
    return res;
}
```

PermGroup.h

Description: Schreier-Sims lets you add a permutation to a group, count number of permutations in a group, test whether a permutation is a member of a group. Works well for $n \leq 15$, maybe for larger too. Construct PermGroup() and run order() to get order of the group.

Time: $\mathcal{O}(n^6)$ d6edf4, 55 lines

```
vi inv(vi v) { vi V(sz(v)); rep(i,sz(v)) V[v[i]]=i;
    return V; }
vi id(int n) { vi v(n); iota(all(v),0); return v; }
vi operator*(const vi& a, const vi& b) {
    vi c(sz(a)); rep(i,sz(a)) c[i] = a[b[i]];
    return c;
}
struct PermGroup {
    struct Group {
        vi flag;
        vector<vi> gen, sigma;
        // sigma[t][k] = t, sigma[t][x] = x if x > k
        Group(int n, int p) : flag(n), sigma(n) {
            flag[p] = 1; sigma[p] = id(n);
        }
    };
    int n = 0; vector<Group> g;
    PermGroup() {}
    bool check(const vi& cur, int k) {
        if (!k) return 1;
        int t = cur[k];
        return g[k].flag[t] ? check(inv(g[k].sigma[t])*cur,
            k-1) : 0;
    }
    void updateX(const vi& cur, int k) {
        int t = cur[k]; // if flag, fixes k -> k
        if (g[k].flag[t]) ins(inv(g[k].sigma[t])*cur,k-1);
        else {
            g[k].flag[t] = 1, g[k].sigma[t] = cur;
            for(auto x: g[k].gen)
                updateX(x*cur,k);
        }
    }
    void ins(const vi& cur, int k) {
        if (check(cur,k)) return;
        g[k].gen.pb(cur);
        rep(i,n) if (g[k].flag[i]) updateX(cur*g[k].sigma[i],k);
    }
    ll order(vector<vi> gen) {
        if (sz(gen) == 0) return 1;
        n = sz(gen[0]);
        rep(i,n) g.pb(Group(n,i));
        for(auto a: gen)
            ins(a, n-1); // insert perms into group one by
                           one
        ll tot = 1; // watch out for overflows, can be up
                     to n!
        rep(i,n) {
            int cnt = 0;
            rep(j,i+1) cnt += g[i].flag[j];
            tot *= cnt;
        }
        return tot;
    }
};
```

GrayCode.h

Description: Gray code: gray(0), ..., gray($2^n - 1$) - permutation in which each two consecutive (cyclically) numbers. differ in exactly one bit. b4cc82, 6 lines

```
using ull = unsigned long long;
ull gray(ull i) { return i^i>>1; }
ull invg(ull i) { // i=invg(gray(i))=gray(inv g(i))
    i^=i>>1; i^=i>>2; i^=i>>4;
    i^=i>>8; i^=i>>16; i^=i>>32; return i;
}
```

Graph (7)

7.1 Fundamentals

BellmanFord.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max |w_i| < \sim 2^{63}$.

Time: $\mathcal{O}(VE)$ 830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }
};
struct Node { ll dist = inf; int prev = -1; };
void bellmanFord(vector<Node>& nodes, vector<Ed>& eds,
    int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = d;
        }
    }
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m , where $m[i][j] = \text{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j , inf if no path, or -inf if the path goes through a negative-weight cycle.

Time: $\mathcal{O}(N^3)$ 531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
    int n = sz(m);
    rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
    rep(k,0,n) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) {
            auto newDist = max(m[i][k] + m[k][j], -inf);
            m[i][j] = min(m[i][j], newDist);
        }
    rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -
            inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n - nodes reachable from cycles will not be returned.

Time: $\mathcal{O}(|V| + |E|)$ 66a137, 14 lines

```
vi topoSort(const vector<vi>& gr) {
    vi indeg(sz(gr)), ret;
    for (auto& li : gr) for (int x : li) indeg[x]++;
    queue<int> q; // use priority_queue for lexic.
                  largest ans.
    rep(i,0,sz(gr)) if (indeg[i] == 0) q.push(i);
    while (!q.empty()) {
        int i = q.front(); // top() for priority queue
        ret.push_back(i);
        q.pop();
        for (int x : gr[i])
```

```
        if (--indeg[x] == 0) q.push(x);
    }
    return ret;
}
```

Shapes.h

Description: Counts all subgraph shapes with at most 4 edges. No multiedges / loops allowed;

Time: $\mathcal{O}(m\sqrt{m})$ f62c2b, 39 lines

```
struct Shapes {
    ll tri = 0, rect = 0, path3 = 0, path4 = 0, star3 =
        0, p = 0;
    __int128_t y = 0, star4 = 0;
    Shapes(vector<vi>& g) {
        int n = sz(g);
        vector<vi> h(n);
        vector<ll> f(n), c(n), s(n);
        rep(v, n) f[v] = (s[v] = sz(g[v])) * n + v;
        rep(v, n) {
            ll x = 0;
            star3 += s[v] * (s[v] - 1) * (s[v] - 2);
            star4 += __int128_t(s[v] - 1) * s[v] * (s[v] - 2)
                * (s[v] - 3);
            for (auto u : g[v]) {
                path4 += s[u] * x - x; x += s[u] - 1;
                y += (s[v] - 1) * (s[u] - 1) * (s[u] - 2) / 2;
                if (f[u] < f[v]) h[v].pb(u);
            }
        }
        rep(v, n) {
            for (int u : h[v])
                for (int w : g[u]) if (f[v] > f[w])
                    rect += c[w] ++;
            for(int u : h[v]) {
                tri += c[u]; c[u] -= 1;
                path3 += (s[v] - 1) * (s[u] - 1);
                for(int w : g[u])
                    if (c[w] < 0)
                        p += s[v] + s[u] + s[w] - 6, c[w] ++;
                    else if (c[w] > 0)
                        c[w] --;
            }
        }
        path3 -= 3 * tri;
        y -= 2 * p;
        path4 -= 4 * rect + 2 * p + 3 * tri;
        star3 /= 6;
        star4 /= 24;
    }
};
```

SPFA.h

Description: SPFA with subtree erasure heuristic. Returns array of distances or empty array if negative cycle is reachable from source. par[v] = parent in shortest path tree

Time: $\mathcal{O}(VE)$ but fast on random bf4a3f, 33 lines

```
using Edge = pair<int, ll>;
vector<ll> spfa(vector<vector<Edge>>& G,
    vi& par, int src) {
    int n = sz(G); vi que, prv(n+1);
    iota(all(prv), 0); vi nxt = prv;
    vector<ll> dist(n, INT64_MAX);
    par.assign(n, -1);
    auto add = [&](int v, int p, ll d) {
        par[v] = p; dist[v] = d;
        prv[n] = nxt[prv[v] = prv[nxt[v] = n]] = v;
    };
    auto del = [&](int v) {
        nxt[prv[nxt[v]] = prv[v]] = nxt[v];
        prv[v] = nxt[v] = v;
    };
    for (add(src, -2, 0); nxt[n] != n; ) {
        int v = nxt[n]; del(v);
        for (auto e : G[v]) {
            ll alt = dist[v] + e.y;
            if (alt < dist[e.x]) {
                que = {e.x};
```

```
                rep(i, sz(que)) {
                    int w = que[i]; par[w] = -1;
                    del(w);
                    for (auto f : G[w])
                        if (par[f.x] == w) que.pb(f.x);
                }
                if (par[v] == -1) return {};
                add(e.x, v, alt);
            }
        }
    }
    return dist; }
```

7.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(V^2\sqrt{E})$ 0ae1d4, 48 lines

```
struct PushRelabel {
    struct Edge {
        int dest, back;
        ll f, c;
    };
    vector<vector<Edge>> g;
    vector<ll> ec;
    vector<Edge*> cur;
    vector<vi> hs; vi H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(
        n) {}
    void addEdge(int s, int t, ll cap, ll rcap=0) {
        if (s == t) return;
        g[s].push_back({t, sz(g[t]), 0, cap});
        g[t].push_back({s, sz(g[s])-1, 0, rcap});
    }
    void addFlow(Edge& e, ll f) {
        Edge &back = g[e.dest][e.back];
        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.
            dest);
        e.f += f; e.c -= f; ec[e.dest] += f;
        back.f -= f; back.c += f; ec[back.dest] -= f;
    }
    ll calc(int s, int t) {
        int v = sz(g); H[s] = v; ec[t] = 1;
        vi co(2*v); co[0] = v-1;
        rep(i,0,v) cur[i] = g[i].data();
        for (Edge& e : g[s]) addFlow(e, e.c);
        for (int hi = 0;;) {
            while (hs[hi].empty()) if (!hi--) return -ec[s];
            int u = hs[hi].back(); hs[hi].pop_back();
            while (ec[u] > 0) // discharge u
                if (cur[u] == g[u].data() + sz(g[u])) {
                    H[u] = 1e9;
                    for (Edge& e : g[u]) if (e.c && H[u] > H[e.
                        dest]+1)
                        H[u] = H[e.dest]+1, cur[u] = &e;
                    if (++co[H[u]], !--co[hi] && hi < v)
                        rep(i,0,v) if (hi < H[i] && H[i] < v)
                            --co[H[i]], H[i] = v + 1;
                    hi = H[u];
                } else if (cur[u]->c && H[u] == H[cur[u]->dest
                    +1])
                    addFlow(*cur[u], min(ec[u], cur[u]->c));
                else ++cur[u];
            }
        }
        bool leftOfMinCut(int a) { return H[a] >= sz(g); }
    };
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(F \log(V))$ where F is max flow. $\mathcal{O}(V^3E)$ for setpi. 5839eb, 19 lines

```
#include <bits/extc++.h>
const ll INF = numeric_limits<ll>::max() / 4;
```

```

struct MCMF {
    struct edge {
        int from, to, rev;
        ll cap, cost, flow;
    };
    int N;
    vector<vector<edge>> ed;
    vi seen;
    vector<ll> dist, pi;
    vector<edge>> par;
    MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N),
        par(N) {}
    void addEdge(int from, int to, ll cap, ll cost) {
        if (from == to) return;
        ed[from].push_back(edge{ from,to,sz(ed[to]),cap,
            cost,0 });
        ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-
            cost,0 });
    }
    void path(int s) {
        fill(all(seen), 0);
        fill(all(dist), INF);
        dist[s] = 0; ll di;
        __gnu_pbds::priority_queue<pair<ll, int>> q;
        vector<decltype(q)::point_iterator> its(N);
        q.push({ 0, s });
        while (!q.empty()) {
            s = q.top().second; q.pop();
            seen[s] = 1; di = dist[s] + pi[s];
            for (edge& e : ed[s]) if (!seen[e.to]) {
                ll val = di - pi[e.to] + e.cost;
                if (e.cap - e.flow > 0 && val < dist[e.to]) {
                    dist[e.to] = val;
                    par[e.to] = &e;
                    if (its[e.to] == q.end())
                        its[e.to] = q.push({ -dist[e.to], e.to });
                    else
                        q.modify(its[e.to], { -dist[e.to], e.to });
                }
            }
        }
        rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
    }
    pair<ll, ll> maxflow(int s, int t) {
        ll totflow = 0, totcost = 0;
        while (path(s), seen[t]) {
            ll fl = INF;
            for (edge& x = par[t]; x; x = par[x->from])
                fl = min(fl, x->cap - x->flow);
            totflow += fl;
            for (edge& x = par[t]; x; x = par[x->from]) {
                x->flow += fl;
                ed[x->to][x->rev].flow -= fl;
            }
        }
        rep(i,0,N) for (edge& e : ed[i]) totcost += e.cost *
            e.flow;
        return {totflow, totcost/2};
    }
    // If some costs can be negative, call this before
    maxflow:
    void setpi(int s) { // (otherwise, leave this out)
        fill(all(pi), INF); pi[s] = 0;
        int it = N, ch = 1; ll v;
        while (ch-- && it--)
            rep(i,0,N) if (pi[i] != INF)
                for (edge& e : ed[i]) if (e.cap)
                    if ((v = pi[i] + e.cost) < pi[e.to])
                        pi[e.to] = v, ch = 1;
        assert(it >= 0); // negative cost cycle
    }
};

```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $O(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

482fe0, 36 lines

```

template<class T> T edmondsKarp(vector<unordered_map<
    int, T>>&
    graph, int source, int sink) {
    assert(source != sink);
    T flow = 0;
    vi par(sz(graph)), q = par;
    for (,;) {
        fill(all(par), -1);
        par[source] = 0;
        int ptr = 1;
        q[0] = source;
        rep(i,0,ptr) {
            int x = q[i];
            for (auto e : graph[x]) {
                if (par[e.first] == -1 && e.second > 0) {
                    par[e.first] = x;
                    q[ptr++] = e.first;
                    if (e.first == sink) goto out;
                }
            }
        }
        return flow;
    out:
    T inc = numeric_limits<T>::max();
    for (int y = sink; y != source; y = par[y])
        inc = min(inc, graph[par[y]][y]);
    flow += inc;
    for (int y = sink; y != source; y = par[y]) {
        int p = par[y];
        if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
        graph[y][p] += inc;
    }
}

```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s , only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.

Time: $O(V^3)$

8b0e19, 21 lines

```

pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
    rep(i,0,n) co[i] = {i};
    rep(ph,1,n) {
        vi w = mat[0];
        size_t s = 0, t = 0;
        rep(it,0,n-ph) { //  $O(V^2) \rightarrow O(E \log V)$  with prio.
            queue
            w[t] = INT_MIN;
            s = t, t = max_element(all(w)) - w.begin();
            rep(i,0,n) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), all(co[t]));
        rep(i,0,n) mat[s][i] += mat[t][i];
        rep(i,0,n) mat[i][s] = mat[s][i];
        mat[0][t] = INT_MIN;
    }
    return best;
}

```

FlowDemands.h

Description: Flows with demands.

e1c0d0, 52 lines

```

// #include "flow_edmonds_karp.h"
// #include "flow_push_relabel.h" // if you need
// Flow with demands; time:  $O(\text{maxflow})$ 
struct FlowDemands {
    MaxFlow net;
    vector<vector<flow_t>> demands;

```

```

    flow_t total = 0;
    // Initialize for k vertices
    FlowDemands(int k = 0) : net(2) {
        while (k--) addVert();
    }
    // Add new vertex
    int addVert() {
        int v = net.addVert();
        demands.pb({});
        net.addEdge(0, v, 0);
        net.addEdge(v, 1, 0);
        return v-2;
    }
    // Add edge from u to v with demand dem
    // and capacity cap (dem <= flow <= cap).
    // Returns edge index in adjacency list of u.
    int addEdge(int u, int v,
        flow_t dem, flow_t cap) {
        demands[u].pb(dem);
        demands[v].pb(0);
        total += dem;
        net.G[0][v].cap += dem;
        net.G[u+2][1].cap += dem;
        return net.addEdge(u+2, v+2, cap-dem) - 2;
    }
    // Check if there exists a flow with value f
    // for source src and destination dst.
    // For circulation, you can set args to 0.
    bool canFlow(int src, int dst, flow_t f) {
        net.addEdge(dst += 2, src += 2, f);
        f = net.maxFlow(0, 1);
        net.G[src].pop_back();
        net.G[dst].pop_back();
        return f == total;
    }
    // Get flow through e-th edge of vertex v
    flow_t getFlow(int v, int e) {
        return net.getFlow(v+2,e+2)+demands[v][e];
    }
};

```

GomoryHu.h

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.

Time: $O(V)$ Flow Computations

"PushRelabel.h" 0418b3, 13 lines

```

typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
    vi par(N);
    rep(i,1,N) {
        PushRelabel D(N); // Dinic also works
        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2])
            ;
        tree.push_back({i, par[i], D.calc(i, par[i])});
        rep(j,i+1,N)
            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j]
                = i;
    }
    return tree;
}

```

7.3 Flow with demands

Say we want $d(e) \leq f(e) \leq c(e)$ for each edge. To find an arbitrary flow, add s', t' and the following edges:

- $\forall v \in V : c'((s', v)) = \sum_u d((u, v)), \quad c'((v, t')) = \sum_w d((v, w)),$
- $\forall (u, v) \in E : c'((u, v)) = c((u, v)) - d((u, v)),$
- $c'((t, s)) = \infty.$

For min flow, replace ∞ with L and find smallest L such that flow is saturated.

7.4 Matching

hopcroftKarp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched. **Usage:** vi btoa(m, -1); hopcroftKarp(g, btoa);

Time: $O(\sqrt{VE})$

f612e4, 42 lines

```

bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A,
    vi& B) {
    if (A[a] != L) return 0;
    A[a] = -1;
    for (int b : g[a]) if (B[b] == L + 1) {
        B[b] = 0;
        if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A,
            B))
            return btoa[b] = a, 1;
    }
    return 0;
}
int hopcroftKarp(vector<vi>& g, vi& btoa) {
    int res = 0;
    vi A(g.size()), B(btoa.size()), cur, next;
    for (,;) {
        fill(all(A), 0);
        fill(all(B), 0);
        cur.clear();
        for (int a : btoa) if (a != -1) A[a] = -1;
        rep(a,0,sz(g)) if (A[a] == 0) cur.push_back(a);
        for (int lay = 1; lay++ ) {
            bool islast = 0;
            next.clear();
            for (int a : cur) for (int b : g[a]) {
                if (btoa[b] == -1) {
                    B[b] = lay;
                    islast = 1;
                }
            }
            else if (btoa[a] != a && !B[b]) {
                B[b] = lay;
                next.push_back(btoa[b]);
            }
        }
        if (islast) break;
        if (next.empty()) return res;
        for (int a : next) A[a] = lay;
        cur.swap(next);
    }
    rep(a,0,sz(g))
        res += dfs(a, 0, g, btoa, A, B);
}
}

```

DFSMatching.h

Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched. **Usage:** vi btoa(m, -1); dfsMatching(g, btoa);

Time: $O(VE)$

522b98, 22 lines

```

bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
    if (btoa[j] == -1) return 1;
    vis[j] = 1; int di = btoa[j];
    for (int e : g[di])
        if (!vis[e] && find(e, g, btoa, vis)) {
            btoa[e] = di;
            return 1;
        }
    return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
    vi vis;
    rep(i,0,sz(g)) {
        vis.assign(sz(btoa), 0);
        for (int j : g[i])
            if (find(j, g, btoa, vis)) {
                btoa[j] = i;
                break;
            }
    }
}

```

```

    }
}
return sz(btoa) - (int)count(all(btoa), -1);
}

```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

```

"DFSMatching.h" da4196, 20 lines
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = dfsMatching(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    ;
    vi q, cover;
    rep(i,0,n) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1)
            {
                seen[e] = true;
                q.push_back(match[e]);
            }
    }
    rep(i,0,n) if (!lfound[i]) cover.push_back(i);
    rep(i,0,m) if (seen[i]) cover.push_back(n+i);
    assert(sz(cover) == res);
    return cover;
}

```

WeightedMatching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j] and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.

```

Time:  $O(N^2M)$  1e0fe9, 31 lines
pair<int, vi> hungarian(const vector<vi> &a) {
    if (a.empty()) return {0, {}};
    int n = sz(a) + 1, m = sz(a[0]) + 1;
    vi u(n), v(m), p(m), ans(n - 1);
    rep(i,1,n) {
        p[0] = i;
        int j0 = 0; // add "dummy" worker 0
        vi dist(m, INT_MAX), pre(m, -1);
        vector<bool> done(m + 1);
        do { // dijkstra
            done[j0] = true;
            int i0 = p[j0], j1, delta = INT_MAX;
            rep(j,1,m) if (!done[j]) {
                auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
        } while (p[j0]);
        while (j0) { // update alternating path
            int j1 = pre[j0];
            p[j0] = p[j1], j0 = j1;
        }
    }
    rep(j,1,m) if (p[j]) ans[p[j] - 1] = j - 1;
    return {-v[0], ans}; // min cost
}

```

GeneralMatching.h

Description: Matching for general graphs. Fails with probability N/mod .

```

Time:  $O(N^3)$ 
"./numerical/MatrixInverse-mod.h" cb1912, 40 lines
vector<pii> generalMatching(int N, vector<pii>& ed) {
    vector<vector<ll>> mat(N, vector<ll>(N)), A;
    for (pii pa : ed) {
        int a = pa.first, b = pa.second, r = rand() % mod;
        mat[a][b] = r, mat[b][a] = (mod - r) % mod;
    }
    int r = matInv(A = mat), M = 2*N - r, fi, fj;
    assert(r % 2 == 0);
    if (M != N) do {
        mat.resize(M, vector<ll>(M));
        rep(i,0,N) {
            mat[i].resize(M);
            rep(j,N,M) {
                int r = rand() % mod;
                mat[i][j] = r, mat[j][i] = (mod - r) % mod;
            }
        } while (matInv(A = mat) != M);
    } while (matInv(A = mat) != M);
    vi has(M, 1); vector<pii> ret;
    rep(it,0,M/2) {
        rep(i,0,M) if (has[i])
            rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
                fi = i; fj = j; goto done;
            } assert(0); done:
        if (fj < N) ret.emplace_back(fi, fj);
        has[fi] = has[fj] = 0;
        rep(sw,0,2) {
            ll a = modpow(A[fi][fj], mod-2);
            rep(i,0,M) if (has[i] && A[i][fj]) {
                ll b = A[i][fj] * a % mod;
                rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
            }
            swap(fi,fj);
        }
    }
    return ret;
}

```

MatroidIntersection.h

Description: Find largest subset S of [n] such that S is independent in both matroid A and B, given by their oracles, see example implementations below. Returns vector V such that V[i] = 1 iff i-th element is included in found set;

Time: $O(r^2 \cdot (\text{init} + n \cdot \text{add}))$, where r is max independent set.

```

e3ed3b, 152 lines
template<class T, class U>
vector<bool> intersectMatroids(T& A, U& B, int n) {
    vector<bool> ans(n);
    bool ok = 1;
    // NOTE: for weighted matroid intersection find
    // shortest augmenting paths first by weight change,
    // then by length using Bellman-Ford,
    // Speedup trick (only for unweighted):
    A.init(ans); B.init(ans);
    rep(i, n)
        if (A.canAdd(i) && B.canAdd(i))
            ans[i] = 1, A.init(ans), B.init(ans);
    //End of speedup
    while (ok) {
        vector<vi> G(n);
        vector<bool> good(n);
        queue<int> que;
        vi prev(n, -1);
        A.init(ans); B.init(ans); ok = 0;
        rep(i, n) if (!ans[i]) {
            if (A.canAdd(i)) que.push(i), prev[i]=-2;
            good[i] = B.canAdd(i);
        }
        rep(i, n) if (ans[i]) {
            ans[i] = 0;
            A.init(ans); B.init(ans);
        }
    }
}

```

```

rep(j, n) if (i != j && !ans[j]) {
    if (A.canAdd(j)) G[i].pb(j); // -cost[j]
    if (B.canAdd(j)) G[j].pb(i); // cost[i]
}
ans[i] = 1;
}
while (!que.empty()) {
    int i = que.front();
    que.pop();
    if (good[i]) { // best found (unweighted = shortest path)
        ans[i] = 1;
        while (prev[i] >= 0) { // alternate matching
            ans[i] = prev[i] = 0;
            ans[i] = prev[i] = 1;
        }
        ok = 1; break;
    }
    for(auto j: G[i]) if (prev[j] == -1)
        que.push(j), prev[j] = i;
}
}
return ans;
}
// Matroid where each element has color
// and set is independent iff for each color c
// #{elements of color c} <= maxAllowed[c].
struct LimOracle {
    vi color; // color[i] = color of i-th element
    vi maxAllowed; // Limits for colors
    vi tmp;
    // Init oracle for independent set S; O(n)
    void init(vector<bool>& S) {
        tmp = maxAllowed;
        rep(i, sz(S)) tmp[color[i]] -= S[i];
    }
    // Check if S+{k} is independent; time: O(1)
    bool canAdd(int k) { return tmp[color[k]] > 0; }
};
// Graphic matroid - each element is edge,
// set is independent iff subgraph is acyclic.
struct GraphOracle {
    vector<pii> elems; // Ground set: graph edges
    int n; // Number of vertices, indexed [0;n-1]
    vi par;
    int find(int i) {
        return par[i] == -1 ? i : par[i] = find(par[i]);
    }
    // Init oracle for independent set S; ~O(n)
    void init(vector<bool>& S) {
        par.assign(n, -1);
        rep(i, sz(S)) if (S[i])
            par[find(elems[i].st)] = find(elems[i].nd);
    }
    // Check if S+{k} is independent; time: ~O(1)
    bool canAdd(int k) {
        return find(elems[k].st) != find(elems[k].nd);
    }
};
// Co-graphic matroid - each element is edge,
// set is independent iff after removing edges
// from graph number of connected components
// doesn't change.
struct CographOracle {
    vector<pii> elems; // Ground set: graph edges
    int n; // Number of vertices, indexed [0;n-1]
    vector<vi> G;
    vi pre, low;
    int cnt;
    int dfs(int v, int p) {
        pre[v] = low[v] = ++cnt;
        for(auto e: G[v]) if (e != p)
            low[v] = min(low[v], pre[e] ? dfs(e,v));
        return low[v];
    }
    // Init oracle for independent set S; O(n)
    void init(vector<bool>& S) {
        G.assign(n, {});
        pre.assign(n, 0);
    }
}

```

```

low.resize(n);
cnt = 0;
rep(i,sz(S)) if (!S[i]) {
    pii e = elems[i];
    G[e.st].pb(e.nd);
    G[e.nd].pb(e.st);
}
rep(v, n) if (!pre[v]) dfs(v, -1);
}
// Check if S+{k} is independent; time: O(1)
bool canAdd(int k) {
    pii e = elems[k];
    return max(pre[e.st], pre[e.nd]) != max(low[e.st], low[e.nd]);
}
}
// Matroid equivalent to linear space with XOR
struct XorOracle {
    vector<ll> elems; // Ground set: numbers
    vector<ll> base;
    // Init for independent set S; O(n+r^2)
    void init(vector<bool>& S) {
        base.assign(63, 0);
        rep(i, sz(S)) if (S[i]) {
            ll e = elems[i];
            rep(j, sz(base)) if ((e >> j) & 1) {
                if (!base[j]) {
                    base[j] = e;
                    break;
                }
                e ^= base[j];
            }
        }
    }
    // Check if S+{k} is independent; time: O(r)
    bool canAdd(int k) {
        ll e = elems[k];
        rep(i, sz(base)) if ((e >> i) & 1) {
            if (!base[i]) return 1;
            e ^= base[i];
        }
        return 0;
    }
}
}

```

Konig.h

Description: $O(n + \text{matching}(n, m))$ wyznaczenie w grafie dwudzielnym kolejno minimalnego pokrycia krawędziowego (PK), maksymalnego zbioru niezależnych wierzchołków (NW), minimalnego pokrycia wierzchołkowego (PW) korzystając z maksymalnego zbioru niezależnych krawędzi (NK) (tak zwany matching). Z tw. Koniga zachodzi $|NK| = n - |PK| = n - |NW| = |PW|$.

```

"./matching/main.cpp" d37a69, 41 lines
// BEGIN HASH
vector<pair<int, int>> get_min_edge_cover(vector<vector<int>>> graph) {
    vector<int> match = Matching(graph)().second;
    vector<pair<int, int>> ret;
    REP(v, ssize(match))
        if (match[v] != -1 and v < match[v])
            ret.emplace_back(v, match[v]);
    else if (match[v] == -1 and not graph[v].empty())
        ret.emplace_back(v, graph[v].front());
    return ret;
} // END HASH
// BEGIN HASH
array<vector<int>, 2> get_coloring(vector<vector<int>>> graph) {
    int n = ssize(graph);
    vector<int> match = Matching(graph)().second;
    vector<int> color(n, -1);
    function<void (int)> dfs = [&](int v) {
        color[v] = 0;
        for(int u : graph[v])
            if (color[u] == -1) {
                color[u] = true;
                dfs(match[u]);
            }
    };
}

```



```

    }
};
REP(v, n)
    if(match[v] == -1)
        dfs(v);
REP(v, n)
    if(color[v] == -1)
        dfs(v);
array<vector<int>, 2> groups;
REP(v, n)
    groups[color[v]].emplace_back(v);
return groups;
}
vector<int> get_max_independent_set(vector<vector<int>>>
    graph) {
    return get_coloring(graph)[0];
}
vector<int> get_min_vertex_cover(vector<vector<int>>>
    graph) {
    return get_coloring(graph)[1];
} // END HASH

```

7.5 DFS algorithms

SCC.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.

Usage: `scc(graph, [&](vi& v) { ... })` visits all components

in reverse topological order. `comp[i]` holds the component

index of a node (a component only has edges to components with

lower index). `ncmps` will contain the number of components.

Time: $\mathcal{O}(E + V)$ 76b5c9, 24 lines

```

vi val, comp, z, cont;
int Time, ncmps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ? dfs(e, g, f));
    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncmps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncmps++;
    }
    return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncmps = 0;
    rep(i, 0, n) if (comp[i] < 0) dfs(i, g, f);
}

```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two distinct paths between any two nodes. Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.

Usage: `int eid = 0; ed.resize(N);`
for each edge (a,b) {
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++);` }
`bicomps([&](const vi& edgelist) {...});`
Time: $\mathcal{O}(E + V)$ c6b7c7, 32 lines

```

vi num, st;
vector<vector<pii>> ed;
int Time;

```

```

template<class F>
int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, top = me;
    for (auto [y, e] : ed[at]) if (e != par) {
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me)
                st.push_back(e);
        } else {
            int si = sz(st);
            int up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
                f(vi(st.begin() + si, st.end()));
                st.resize(si);
            }
            else if (up < me) st.push_back(e);
            else { /* e is a bridge */ }
        }
    }
    return top;
}
template<class F>
void bicomps(F f) {
    num.assign(sz(ed), 0);
    rep(i, 0, sz(ed)) if (!num[i]) dfs(i, -1, f);
}

```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c, \dots to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(a||c)\&\&(d||b)\&\&\dots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions ($\sim x$).

Usage: `TwoSat ts(number of boolean variables);`
`ts.either(0, ~3);` // Var 0 is true or var 3 is false
`ts.setValue(2);` // Var 2 is true
`ts.atMostOne({0, ~1, 2});` // ≤ 1 of vars 0, ~1 and 2 are true
`ts.solve();` // Returns true iff it is solvable
`ts.values[0..N-1]` holds the assigned values to the vars
Time: $\mathcal{O}(N + E)$, where N is the number of boolean variables, and E is the number of clauses. 5f9706, 56 lines

```

struct TwoSat {
    int N;
    vector<vi> gr;
    vi values; // 0 = false, 1 = true
    TwoSat(int n = 0) : N(n), gr(2*n) {}
    int addVar() { // (optional)
        gr.emplace_back();
        gr.emplace_back();
        return N++;
    }
    void either(int f, int j) {
        f = max(2*f, -1-2*f);
        j = max(2*j, -1-2*j);
        gr[f].push_back(j^1);
        gr[j].push_back(f^1);
    }
    void setValue(int x) { either(x, x); }
    void atMostOne(const vi& li) { // (optional)
        if (sz(li) <= 1) return;
        int cur = ~li[0];
        rep(i, 2, sz(li)) {
            int next = addVar();
            either(cur, ~li[i]);
            either(cur, next);
            either(~li[i], next);
            cur = ~next;
        }
        either(cur, ~li[1]);
    }
    vi val, comp, z; int time = 0;
    int dfs(int i) {
        int low = val[i] = ++time, x; z.push_back(i);
        for(int e : gr[i]) if (!comp[e])
            low = min(low, val[e] ? dfs(e));
    }
}

```

```

    if (low == val[i]) do {
        x = z.back(); z.pop_back();
        comp[x] = low;
        if (values[x]>1) == -1)
            values[x]>1 = x&1;
    } while (x != i);
    return val[i] = low;
}
bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i, 0, 2*N) if (!comp[i]) dfs(i);
    rep(i, 0, N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
}
}

```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$ 780b64, 15 lines

```

vi eulerWalk(vector<vector<pii>>& gr, int nedges, int
    src=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x]
            );
        if (it == end){ ret.push_back(x); s.pop_back();
            continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back(y);
        }
    }
    for (int x : D) if (x < 0 || sz(ret) != nedges+1)
        return {};
    return {ret.rbegin(), ret.rend()};
}

```

Dominators.h

Description: Tarjan's dominators in directed graph Returns tree (as array of parents) of immediate dominators `idom`. `idom[root] = root`, `idom[v] = -1` if v is unreachable from root
Time: $\mathcal{O}(|E|\log|V|)$ 2613e6, 32 lines

```

vi dominators(vector<vi>& G, int root) {
    int n = sz(G); vector<vi> in(n), bucket(n);
    vi pre(n, -1), anc(n, -1), par(n), best(n);
    vi ord, idom(n, -1), sdom(n, n), rdom(n);
    auto dfs = [&](auto f, int v, int p) -> void {
        if (pre[v] == -1) {
            par[v] = p; pre[v] = sz(ord);
            ord.pb(v);
            for (auto e : G[v])
                in[e.pb(v), f(f, e, v)];
        }
    };
    rdom[root] = idom[root] = root;
    iota(all(best), 0); dfs(dfs, root, -1);
    rep(i, sz(ord)) {
        int v = ord[sz(ord)-i-1], b = pre[v];
        for (auto e : in[v])
            b = min(b, pre[e] < pre[v] ? pre[e] :
                sdom[find(find, e).st]);
        for (auto u : bucket[v]) rdom[u] = find(find, u).st;
        sdom[v] = b; anc[v] = par[v];
    }
}

```

```

        bucket[ord[sdom[v]]].pb(v);
    }
    for (auto v : ord) idom[v] = (rdom[v] == v ?
        ord[sdom[v]] : idom[rdom[v]]);
    return idom; }

```

KthShortest.h

Description: Given directed weighted graph with non-negative edge weights gets K -th shortest walk (not necessarily simple) in $\mathcal{O}(\log|E|)$. -1 if no next path (can only happen in DAG). WARNING: USES KLOGM memory and persistent heaps! 2d9393, 57 lines

```

constexpr ll INF = 1e18;
struct Eppstein {
    using T = ll; using Edge = pair<int, T>;
    struct Node { int E[2] = {}, s = 0; Edge x; };
    T shortest; // Shortest path length
    priority_queue<pair<T, int>> Q;
    vector<Node> P[1]; vi h;
    Eppstein(vector<vector<Edge>>& G, int s, int t) {
        int n = sz(G); vector<vector<Edge>> H(n);
        rep(i, n) for(auto &e : G[i])
            H[e.st].pb((i, e.nd));
        vi ord, par(n, -1); vector<T> d(n, -INF);
        Q.push({d[t] = 0, t});
        while (!Q.empty()) {
            auto v = Q.top(); Q.pop();
            if (d[v.nd] == v.st) {
                ord.pb(v.nd);
                for(auto &e : H[v.nd])
                    if (v.st-e.nd > d[e.st]) {
                        Q.push({d[e.st] = v.st-e.nd, e.st});
                        par[e.st] = v.nd;
                    }
            }
        }
        if ((shortest = -d[s]) >= INF) return;
        h.resize(n);
        for(auto &v : ord) {
            int p = par[v]; if (p+1) h[v] = h[p];
            for(auto &e : G[v]) if (d[e.st] > -INF) {
                T k = e.nd - d[e.st] + d[v];
                if (k || e.st != p)
                    h[v] = push(h[v], {e.st, k});
                else p = -1;
            }
        }
        P[0].x.st = s; Q.push({0, 0});
    }
    int push(int t, Edge x) {
        P.pb(P[t]);
        if (!P[t] = sz(P)-1).s || P[t].x.nd >= x.nd)
            swap(x, P[t].x);
        if (P[t].s) {
            int i = P[t].E[0], j = P[t].E[1];
            int d = P[i].s > P[j].s;
            int k = push(d ? j : i, x);
            P[t].E[d] = k; // Don't inline k!
        }
        P[t].s++; return t;
    }
    ll nextPath() { // next length, -1 if no next path
        if (Q.empty()) return -1;
        auto v = Q.top(); Q.pop();
        for (int i : P[v.nd].E) if (i)
            Q.push({v.st-P[i].x.nd+P[v.nd].x.nd, i});
        int t = h[P[v.nd].x.st];
        if (t) Q.push({v.st - P[t].x.nd, t});
        return shortest - v.st; } };

```

PlanarFaces.h

Description: Read desc below. a391b4, 102 lines

```

/*
 * complexity mlogm, assumes that you are given an
 * embedding
 * graph is drawn straightline non-intersecting

```

```

* returns combinatorial embedding (inner face vertices
  clockwise, outer counter clockwise).
* WAZNE czasem trzeba zlaczyc wszystkie sciany
  zewnetrzne (chodzi o kmine do konkretnego
  zadania)
* (ktorych moze byc kilka, gdy jest wiele spojnych) w
  jedna sciane.
* Zewnetrzne sciany moga wygladac jak kaktusy, a
  wewnetrzne zawsze sa niezdegenerowanym
  wielokatem.

*/
struct Edge {
    int e, from, to;
    // face is on the right of "from -> to"
};
ostream& operator<<(ostream &o, Edge e) {
    return o << vector<e.e, e.from, e.to>;
}

struct Face {
    bool is_outside;
    vector<Edge> sorted_edges;
    // edges are sorted clockwise for inside and cc for
    outside faces
};
ostream& operator<<(ostream &o, Face f) {
    return o << pair<f.is_outside, f.sorted_edges>;
}
vector<Face> split_planar_to_faces(vector<pii> coord,
    vector<pii> edges) {
    int n = sz(coord);
    int E = sz(edges);
    vector<vi> graph(n);
    rep(e, E) {
        auto [v, u] = edges[e];
        graph[v].eb(e);
        graph[u].eb(e);
    }
    vi lead(2 * E);
    iota(lead.begin(), lead.end(), 0);
    function<int (int)> find = [&](int v) {
        return lead[v] == v ? v : lead[v] = find(lead[v]);
    };
    auto side_of_edge = [&](int e, int v, bool outward) {
        return 2 * e + ((v != min(edges[e].first, edges[e].
            second)) ^ outward);
    };
    rep(v, n) {
        vector<pair<pii, int>> sorted;
        for(int e : graph[v]) {
            auto p = coord[edges[e].first ^ edges[e].second ^
                v];
            auto center = coord[v];
            sorted.eb(pair<p.first - center.first, p.second -
                center.second>, e);
        }
        sort(all(sorted), [&](pair<pii, int> l0, pair<pii,
            int> r0) {
            auto l = l0.first;
            auto r = r0.first;
            bool half_l = l > pair(0, 0);
            bool half_r = r > pair(0, 0);
            if(half_l != half_r)
                return half_l;
            return l.first * LL(r.second) - l.second * LL(r.
                first) > 0;
        });
        rep(i, sz(sorted)) {
            int e0 = sorted[i].second;
            int e1 = sorted[(i + 1) % sz(sorted)].second;
            int side_e0 = side_of_edge(e0, v, true);
            int side_e1 = side_of_edge(e1, v, false);
            lead[find(side_e0)] = find(side_e1);
        }
    }
    vector<vi> comps(2 * E);
    rep(i, 2 * E)
        comps[find(i)].eb(i);
    vector<Face> polygons;
    vector<vector<pii>> outgoing_for_face(n);

```

```

rep(leader, 2 * E)
    if(sz(comps[leader])) {
        for(int id : comps[leader]) {
            int v = edges[id / 2].first;
            int u = edges[id / 2].second;
            if(v > u)
                swap(v, u);
            if(id % 2 == 1)
                swap(v, u);
            outgoing_for_face[v].eb(u, id / 2);
        }
        vector<Edge> sorted_edges;
        function<void (int)> dfs = [&](int v) {
            while(sz(outgoing_for_face[v])) {
                auto [u, e] = outgoing_for_face[v].back();
                outgoing_for_face[v].pop_back();
                dfs(u);
                sorted_edges.eb(e, v, u);
            }
        };
        dfs(edges[comps[leader].front() / 2].first);
        reverse(all(sorted_edges));
        LL area = 0;
        for(auto edge : sorted_edges) {
            auto l = coord[edge.from];
            auto r = coord[edge.to];
            area += 1.first * LL(r.second) - 1.second * LL(
                r.first);
        }
        polygons.eb(area >= 0, sorted_edges);
    }
    // Remember that there can be multiple outside faces.
    return polygons;
}

```

PlanarityCheck.h

Description: Read desc below.

cc4508, 93 lines

```

/*
 * Opis: O(szybko) ale istnieja przyklady O(n2),
 * przyjmuje graf nieskierowany bez petelek i
 * multikrawedzi.
*/
bool is_planar(vector<vi> g) {
    int n = sz(g), m = 0;
    rep(v, n) m += sz(g[v]);
    m /= 2;
    if(n <= 3) return true;
    if(m > 3 * n - 6) return false;
    vector<vi> up(n), dn(n);
    vi low(n, -1), pre(n);
    rep(start, n)
        if(low[start] == -1) {
            vector<pii> e_up;
            int tm = 0;
            function<void (int, int)> dfs_low = [&](int v,
                int p) {
                low[v] = pre[v] = tm++;
                for(int u : g[v])
                    if(u != p and low[u] == -1) {
                        dn[v].eb(u);
                        dfs_low(u, v);
                        low[v] = min(low[v], low[u]);
                    }
                else if(u != p and pre[u] < pre[v]) {
                    up[v].eb(ssize(e_up));
                    e_up.eb(v, u);
                    low[v] = min(low[v], pre[u]);
                }
            };
            dfs_low(start, -1);
            vector<pair<int, bool>> dsu(sz(e_up));
            rep(v, sz(dsu)) dsu[v].first = v;
            function<pair<int, bool> (int)> find = [&](int v)
                {
                    if(dsu[v].first == v)
                        return pair<v, false>;
                    auto [u, ub] = find(dsu[v].first);
                    return dsu[v] = pair<u, ub ^ dsu[v].second>;
                };

```

```

};
auto onion = [&](int x, int y, bool flip) {
    auto [v, vb] = find(x);
    auto [u, ub] = find(y);
    if(v == u)
        return not (vb ^ ub ^ flip);
    dsu[v] = {u, vb ^ ub ^ flip};
    return true;
};
auto interlace = [&](const vi &ids, int lo) {
    vi ans;
    for(int e : ids)
        if(pre[e_up[e].second] > lo)
            ans.eb(e);
    return ans;
};
auto add_fu = [&](const vi &a, const vi &b) {
    fwd(k, 1, sz(a))
        if(not onion(a[k - 1], a[k], 0))
            return false;
    fwd(k, 1, sz(b))
        if(not onion(b[k - 1], b[k], 0))
            return false;
    return a.empty() or b.empty() or onion(a[0], b
        [0], 1);
};
function<bool (int, int)> dfs_planar = [&](int v,
    int p) {
    for(int u : dn[v])
        if(not dfs_planar(u, v))
            return false;
    rep(i, sz(dn[v])) {
        fwd(j, i + 1, sz(dn[v]))
            if(not add_fu(interlace(up[dn[v][i]], low[
                dn[v][j]]),
                interlace(up[dn[v][j]], low[dn[v][i
                    ]]))
                return false;
        for(int j : up[v]) {
            if(e_up[j].first != v)
                continue;
            if(not add_fu(interlace(up[dn[v][i]], pre[
                e_up[j].second]),
                interlace({j}, low[dn[v][i]])))
                return false;
        }
    }
    for(int u : dn[v]) {
        for(int idx : up[u])
            if(pre[e_up[idx].second] < pre[p])
                up[v].eb(idx);
        exchange(up[u], {});
    }
    return true;
};
if(not dfs_planar(start, -1))
    return false;
}
return true;
}

```

7.6 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $O(NM)$

e210e2, 31 lines

```

vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);

```

```

    int at = u, end = u, d, c = free[u], ind = 0, i =
        0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) !=
        -1)
        loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at
        ][cd])
        swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
        int left = fan[i], right = fan[++i], e = cc[i];
        adj[u][e] = left;
        adj[left][e] = u;
        adj[right][e] = -1;
        free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : fan[0], u, end)
        for (int& z = free[y] = 0; adj[y][z] != -1; z++);
}
rep(i, 0, sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v; ) ++
        ret[i];
return ret;
}

```

ChordalGraph.h

Description: A graph is chordal if any cycle $C \geq 4$ has a chord i.e. an edge (u, v) where u and v is in the cycle but (u, v) is not A perfect elimination ordering (PEO) in a graph is an ordering of the vertices of the graph such that, $\forall v : v$ and its neighbors that occur after v in the order (later) form a clique. A graph is chordal if and only if it has a perfect elimination ordering. Optimal vertex coloring of the graph: first fit: $col[i]$ = smallest color that is not used by any of the neighbours earlier in PEO. Max clique = Chromatic number = $1 + \max$ over number of later neighbours for all vertices. Chromatic polynomial = $(x - d_1)(x - d_2) \dots (x - d_n)$ where d_i = number of neighbors of i later in PEO.

Time: $O(n + m)$

34f560, 38 lines

```

vi perfectEliminationOrder(vector<vi>& g) { // 0-
    indexed, adj list
    int top = 0, n = sz(g);
    vi ord, vis(n), indeg(n);
    vector<vi> bucket(n);
    rep(i, n) bucket[0].pb(i);
    for(int i = 0; i < n; ) {
        while(bucket[top].empty()) --top;
        int u = bucket[top].back();
        bucket[top].pop_back();
        if(vis[u]) continue;
        ord.pb(u);
        vis[u] = 1;
        ++i;
        for(int v : g[u]) {
            if(vis[v]) continue;
            bucket[++indeg[v]].pb(v);
            top = max(top, indeg[v]);
        }
    }
    reverse(all(ord));
    return ord;
}
bool isChordal(vector<vi>& g, vi ord) { //ord =
    perfectEliminationOrder(g)
    int n = sz(g);
    set<pii> edg;
    rep(i, n) for(auto v:g[i]) edg.insert({i,v});
    vi pos(n); rep(i, n) pos[ord[i]] = i;
    rep(u, n) {
        int mn = n;
        for(auto v : g[u]) if(pos[u] < pos[v]) mn = min(mn,
            pos[v]);
        if(mn != n) {
            int p = ord[mn];
            for(auto v : g[u]) if(pos[v] > pos[u] && v != p
                && !edg.count({v, p})) return 0;

```

```
    }
  }
  return 1;
}
```

ChromaticNumber.h

Description: Calculates chromatic number of a graph represented by a vector of bitmasks. Self loops are not allowed.

Usage: chromaticNumber({6, 5, 3}) // 3-clique

Time: $\mathcal{O}(2^n n)$ 688cb2, 20 lines

```
const int MOD = 1000500103; // big prime
int chromaticNumber(vi g) {
    int n = sz(g);
    if (!n) return 0;
    vi ind(1 << n, 1), s(1 << n);
    rep(i, 1 << n) s[i] = __popcount(i) & 1 ? -1 : 1;
    fwd(i, 1, 1 << n) {
        int ctz = __builtin_ctz(i);
        ind[i] = ind[i - (1 << ctz)] + ind[(i - (1 << ctz))
            & ~g[ctz]];
        if (ind[i] >= MOD) ind[i] -= MOD;
    }
    fwd(k, 1, n) {
        ll sum = 0;
        rep(i, 1 << n) {
            s[i] = int((ll)s[i] * ind[i] % MOD);
            sum += s[i];
        }
        if (sum % MOD) return k;
    }
    return n; }
}
```

7.7 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

Time: $\mathcal{O}(3^{n/3})$, much faster for sparse graphs b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B
    R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs. f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, g, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.
            i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d;
            });
        int mxD = r[0].d;
```

```
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    }
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (sz(R)) {
            if (sz(q) + R.back().d <= sz(qmax)) return;
            q.push_back(R.back().i);
            vv T;
            for(auto v:R) if (e[R.back().i][v.i]) T.push_back
                ((v.i));
            if (sz(T)) {
                if (S[lev]++ / ++pk < limit) init(T);
                int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q)
                    + 1, 1);
                C[1].clear(), C[2].clear();
                for (auto v : T) {
                    int k = 1;
                    auto f = [&](int i) { return e[v.i][i]; };
                    while (any_of(all(C[k]), f)) k++;
                    if (k > mxk) mxk = k, C[mxk + 1].clear();
                    if (k < mnk) T[j++].i = v.i;
                    C[k].push_back(v.i);
                }
                if (j > 0) T[j - 1].d = 0;
                rep(k,mnk,mxk + 1) for (int i : C[k])
                    T[j].i = i, T[j++].d = k;
                expand(T, lev + 1);
            } else if (sz(q) > sz(qmax)) qmax = q;
            q.pop_back(), R.pop_back();
        }
    }
    vi maxClique() { init(V), expand(V); return qmax; }
    Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)),
        old(S) {
        rep(i,0,sz(e)) V.push_back({i});
    }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

7.8 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.

Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$ c4e85, 25 lines

```
vector<vi> treeJump(vi& P){
    int on = 1, d = 1;
    while(on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i,1,d) rep(j,0,sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}
int jmp(vector<vi>& tbl, int nod, int steps){
    rep(i,0,sz(tbl))
        if(steps&1<<i) nod = tbl[i][nod];
    return nod;
}
int lca(vector<vi>& tbl, vi& depth, int a, int b) {
    if (depth[a] < depth[b]) swap(a, b);
    a = jmp(tbl, a, depth[a] - depth[b]);
    if (a == b) return a;
    for (int i = sz(tbl); i--;) {
        int c = tbl[i][a], d = tbl[i][b];
        if (c != d) a = c, b = d;
    }
    return tbl[0][a];
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q)$

"../data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
    int T = 0;
    vi time, path, ret;
    RMQ<int> rmq;
    LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1),
        ret)) {}
    void dfs(vector<vi>& C, int v, int par) {
        time[v] = T++;
        for (int y : C[v]) if (y != par) {
            path.push_back(v), ret.push_back(time[v]);
            dfs(C, y, v);
        }
    }
    int lca(int a, int b) {
        if (a == b) return a;
        tie(a, b) = minmax(time[a], time[b]);
        return path[rmq.query(a, b)];
    }
    //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(
        a,b)];}
};
```

LCA2.h

Description: Provides LCA, K-th ancestor and isAncestor queries in log(n) time with O(n) memory. 271bb1, 51 lines

```
struct LCA {
    vi par, jmp, depth, pre, post;
    int cnt = 0; LCA() {}
    LCA(vector<vi>& g, int v = 0) :
        par(sz(g), -1), jmp(sz(g), v),
        depth(sz(g)), pre(sz(g)), post(sz(g)) {
        dfs(g, v);
    }
    void dfs(vector<vi>& g, int v) {
        int j = jmp[v], k = jmp[j], x =
            depth[v]+depth[k] == depth[j]*2 ? k : v;
        pre[v] = ++cnt;
        for (auto e : g[v]) if (!pre[e]) {
            par[e] = v; jmp[e] = x;
            depth[e] = depth[v]+1;
            dfs(g, e);
        }
        post[v] = ++cnt;
    }
    int laq(int v, int d) {
        while (depth[v] > d)
            v = depth[jmp[v]] < d ? par[v] : jmp[v];
        return v;
    } // Lowest Common Ancestor; time: O(lg n)
    int operator()(int a, int b) {
        if (depth[a] > depth[b]) swap(a, b);
        b = laq(b, depth[a]);
        while (a != b) {
            if (jmp[a] == jmp[b])
                a = par[a], b = par[b];
            else
                a = jmp[a], b = jmp[b];
        }
        return a;
    } // Check if a is ancestor of b; time: O(1)
    bool isAncestor(int a, int b) {
        return pre[a] <= pre[b] &&
            post[b] <= post[a];
    } // Get distance from a to b; time: O(lg n)
    int distance(int a, int b) {
        return depth[a] + depth[b] -
            depth[operator()(a, b)]*2;
    } // Get k-th vertex on path from a to b,
        // a is 0, b is last; time: O(lg n)
        // Returns -1 if k > distance(a, b)
    int kthVertex(int a, int b, int k) {
        int c = operator()(a, b);
```

```
        if (depth[a]-k >= depth[c])
            return laq(a, depth[a]-k);
        k += depth[c]*2 - depth[a];
        return (k > depth[b] ? -1 : laq(b, k)); } };
```

CompressTree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most |S| - 1) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$

"LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i,0,m) {
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    }
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i,0,sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i,0,sz(li)-1) {
        int a = li[i], b = li[i+1];
        ret.emplace_back(rev[lca.lca(a, b)], b);
    }
    return ret;
}
```

HLD.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most log(n) light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS_EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.

Time: $\mathcal{O}((\log N)^2)$

"../data-structures/LazySegmentTree.h" 03139d, 46 lines

```
template <bool VALS_EDGES> struct HLD {
    int N, tim = 0;
    vector<vi> adj;
    vi par, siz, rt, pos;
    Node *tree;
    HLD(vector<vi> adj_)
        : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
        rt(N), pos(N), tree(new Node(0, N)) { dfsSz(0);
        dfsHld(0); }
    void dfsSz(int v) {
        if (par[v] != -1) adj[v].erase(find(all(adj[v]),
            par[v]));
        for (int& u : adj[v]) {
            par[u] = v;
            dfsSz(u);
            siz[v] += siz[u];
            if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
        }
    }
    void dfsHld(int v) {
        pos[v] = tim++;
        for (int u : adj[v]) {
            rt[u] = (u == adj[v][0] ? rt[v] : u);
            dfsHld(u);
        }
    }
    template <class B> void process(int u, int v, B op) {
        for (; rt[u] != rt[v]; v = par[rt[v]]) {
            if (pos[rt[u]] > pos[rt[v]]) swap(u, v);
            op(pos[rt[v]], pos[v] + 1);
        }
    }
```

```

    if (pos[u] > pos[v]) swap(u, v);
    op(pos[u] + VALS_EDGES, pos[v] + 1);
}
void modifyPath(int u, int v, int val) {
    process(u, v, [&](int l, int r) { tree->add(l, r, val); });
}
int queryPath(int u, int v) { // Modify depending on problem
    int res = -1e9;
    process(u, v, [&](int l, int r) {
        res = max(res, tree->query(l, r));
    });
    return res;
}
int querySubtree(int v) { // modifySubtree is similar
    return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
}
};

```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

Time: All operations take amortized $\mathcal{O}(\log N)$
 or b462, 90 lines

```

struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
        if (c[1]) c[1]->p = this;
        // (+ update sum of subtree elements etc. if wanted )
    }
    void pushFlip() {
        if (!flip) return;
        flip = 0; swap(c[0], c[1]);
        if (c[0]) c[0]->flip ^= 1;
        if (c[1]) c[1]->flip ^= 1;
    }
    int up() { return p ? p->c[1] == this : -1; }
    void rot(int i, int b) {
        int h = i ^ b;
        Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
        if ((y->p == p) p->c[up()] = y;
        c[i] = z->c[i ^ 1];
        if (b < 2) {
            x->c[h] = y->c[h ^ 1];
            y->c[h ^ 1] = x;
        }
        z->c[i ^ 1] = this;
        fix(); x->fix(); y->fix();
        if (p) p->fix();
        swap(pp, y->pp);
    }
    void splay() {
        for (pushFlip(); p; ) {
            if (p->p) p->p->pushFlip();
            p->pushFlip(); pushFlip();
            int c1 = up(), c2 = p->up();
            if (c2 == -1) p->rot(c1, 2);
            else p->p->rot(c2, c1 != c2);
        }
    }
    Node* first() {
        pushFlip();
        return c[0] ? c[0]->first() : (splay(), this);
    }
};

struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}
    void link(int u, int v) { // add an edge (u, v)
        assert(!connected(u, v));

```

```

        makeRoot(&node[u]);
        node[u].pp = &node[v];
    }
    void cut(int u, int v) { // remove an edge (u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else
            x->c[0] = top->p = 0;
            x->fix();
    }
    bool connected(int u, int v) { // are u, v in the same tree?
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    }
    void makeRoot(Node* u) {
        access(u);
        u->splay();
        if (u->c[0]) {
            u->c[0]->p = 0;
            u->c[0]->flip ^= 1;
            u->c[0]->pp = u;
            u->c[0] = 0;
            u->fix();
        }
    }
    Node* access(Node* u) {
        u->splay();
        while (Node* pp = u->pp) {
            pp->splay(); u->pp = 0;
            if (pp->c[1]) {
                pp->c[1]->p = 0; pp->c[1]->pp = pp; }
            pp->c[1] = u; pp->fix(); u = pp;
        }
        return u;
    }
};

```

DirectedMST.h

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

Time: $\mathcal{O}(E \log V)$
 or b620, 60 lines

```

"../data-structures/UnionFindRollback.h"
struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b : a;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }
pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
    RollbackUF uf(n);
    vector<Node*> heap(n);
    for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node(e));
    ll res = 0;
    vi seen(n, -1), path(n), par(n);
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1,-1}), comp;

```

```

deque<tuple<int, int, vector<Edge>>> cys;
rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
        if (!heap[u]) return {-1,{};};
        Edge e = heap[u]->top();
        heap[u]->delta -= e.w, pop(heap[u]);
        Q[qi] = e, path[qi++] = u, seen[u] = s;
        res += e.w, u = uf.find(e.a);
        if (seen[u] == s) {
            Node* cyc = 0;
            int end = qi, time = uf.time();
            do cyc = merge(cyc, heap[w = path[--qi]]);
            while (uf.join(u, w));
            u = uf.find(u), heap[u] = cyc, seen[u] = -1;
            cys.push_front({u, time, {&Q[qi], &Q[end]}});
        }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
}
for (auto& [u,t,comp] : cys) { // restore sol ( optional )
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
}
rep(i,0,n) par[i] = in[i].a;
return (res, par);
}

```

Centroid.h

Description: Computes centroid tree for a given (0-indexed) tree, memory $\mathcal{O}(n \log n)$ • child[v] = children of v in centroid tree • par[v] = parent of v in centroid tree (-1 for root) • depth[v] = depth of v in centroid tree (0 for root) = sz(ind[v]-1 • size[v] = size of centroid subtree of v • ind[v][i] = index of vertex v in i-th centroid subtree from root, preorder • subtree[v] = list of vertices in centroid subtree of v • dists[v] = distances from v to vertices in its centroid subtree (in the order of subtree[v]) • neigh[v] = neighbours of v in its centroid subtree • dir[v][i] = index of centroid neighbour that is first vertex on path from centroid v to i-th vertex of centroid subtree (-1 for centroid)

Time: $\mathcal{O}(n \log n)$
 5ba6c3, 47 lines

```

struct CentroidTree {
    vector<vi> child, ind, dists, subtree, neigh, dir;
    vi par, depth, size;
    int root; // Root centroid
    CentroidTree() {}
    CentroidTree(vector<vi>& G)
        : child(sz(G)), ind(sz(G)), dists(sz(G)), subtree(sz(G)), neigh(sz(G)), dir(sz(G)), par(sz(G), -2), depth(sz(G)), size(sz(G)))
    { root = decomp(G, 0, 0); }
    void dfs(vector<vi>& G, int v, int p) {
        size[v] = 1;
        for(Auto e: G[v]) if (e != p && par[e] == -2)
            dfs(G, e, v), size[v] += size[e];
    }
    void layer(vector<vi>& G, int v, int p, int c, int d)
    {
        ind[v].pb(sz(subtree[c]));
        subtree[c].pb(v); dists[c].pb(d);
        dir[c].pb(sz(neigh[c])-1); // possibly add extra functionalities here
        for(auto e: G[v]) if (e != p && par[e] == -2) {
            if (v == c) neigh[c].pb(e);
            layer(G, e, v, c, d+1);
        }
    }
    int decomp(vector<vi>& G, int v, int d) {
        dfs(G, v, -1);
        int p = -1, s = size[v];
        loop:
        for(auto e: G[v]) {
            if (e != p && par[e] == -2 && size[e] > s/2) {
                p = v; v = e; goto loop;
            }
        }
    }

```

```

    }
}
par[v] = -1; size[v] = s; depth[v] = d;
layer(G, v, -1, v, 0);
for(auto e: G[v]) if (par[e] == -2) {
    int j = decomp(G, e, d+1);
    child[v].pb(j);
    par[j] = v;
}
return v;
}
};

```

7.9 Math

7.9.1 Number of Spanning Trees

Create an $N \times N$ matrix mat, and for each edge $a \rightarrow b \in G$, do mat[a][b]-, mat[b][b]++ (and mat[b][a]-, mat[a][a]++ if G is undirected).

Remove the i th row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

7.9.2 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \dots \geq d_n$ exists iff $d_1 + \dots + d_n$ is even and for every $k = 1 \dots n$,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)
 47ec0a, 28 lines

```

template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x ,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x ,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist ()=1
    P perp() const { return P(-y, x); } // rotates +90 degrees
    P normal() const { return perp().unit(); }
    // returns point rotated 'a' radians ccw around the origin
    P rotate(double a) const {
        return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
    friend ostream& operator<<(ostream& os, P p) {

```



```
    return os << "(" << p.x << ", " << p.y << ")"; }
};
```

lineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. $a==b$ gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. Uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




```
"Point.h" f6bf6b, 4 lines

template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a) / (b-a).dist();
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.



```
Usage: Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;

"Point.h" 5c88f4, 6 lines

typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.



```
Usage: vector<P> inter = segInter(s1,e1,s2,e2);
if (sz(inter)==1)
cout << "segments intersect at " << inter[0] << endl;

"Point.h", "OnSegment.h" 9d57f2, 13 lines
```

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
    {
        auto oa = c.cross(d, a), ob = c.cross(d, b),
            oc = a.cross(b, c), od = a.cross(b, d);
        // Checks if intersection is single non-endpoint point.
        if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
            return {(a * ob - b * oa) / (ob - oa)};
        set<P> s;
        if (onSegment(c, d, a)) s.insert(a);
        if (onSegment(c, d, b)) s.insert(b);
        if (onSegment(a, b, c)) s.insert(c);
        if (onSegment(a, b, d)) s.insert(d);
        return {all(s)};
    }
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



```
Usage: auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;

"Point.h" a01f81, 8 lines
```

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)};
    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h

Description: Returns where p is as seen from s towards e. $1/0/-1 \Leftrightarrow$ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

```
Usage: bool left = sideOf(p1,p2,q)==1;

"Point.h" 3af81c, 9 lines
```

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}
```

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.

```
"Point.h" c597e8, 3 lines

template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h

Description:
Applies the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.



```
"Point.h" 03a306, 6 lines

typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

LineProjectionReflection.h

Description: Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

```
"Point.h" b5562d, 5 lines

template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

```
Usage: vector<Angle> v = {w[0], w[0].t360() ...}; // sorted
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180())
++j; }
// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices v[i],v[j],v[j+1]
```

```
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }

    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }

    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half(); } }
    Angle t360() const { return {x, y, t + 1}; }
};
```

```
bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
        make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180() ?
        make_pair(a, b) : make_pair(b, a.t360()));
}

Angle operator+(Angle a, Angle b) { // point a + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}
```

```
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}
```

8.2 Circles

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

```
"Point.h" 84d6d3, 11 lines

typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P> && out) {
    if (a == b) { assert(r1 != r2); return false; }
```

```
P vec = b - a;
double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
    p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
if (sum*sum < d2 || dif*dif > d2) return false;
P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
*out = {mid + per, mid - per};
return true;
}
```

CircleTangents.h

Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents - 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0. "Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

CircleLine.h

Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.

```
"Point.h" e0cfba, 9 lines

template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
    P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
    ;
    double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
    ;
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    P h = ab.unit() * sqrt(h2);
    return {p - h, p + h};
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.

```
Time:  $O(n)$ 


".../content/geometry/Point.h" alee63, 19 lines

typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = p + d * t;
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2
            ;
    };
};
```

```
auto sum = 0.0;
rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
return sum;
}
```

circumcircle.h

Description: The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



```
"Point.h" 1caa3a, 9 lines
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist()/
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)
        )/2;
}
```

MinimumEnclosingCircle.h

Description: Computes the minimum circle that encloses a set of points.

Time: expected $\mathcal{O}(n)$

```
"circumcircle.h" 09dd0a, 17 lines
pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
        o = ps[i], r = 0;
        rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
            o = (ps[i] + ps[j]) / 2;
            r = (o - ps[i]).dist();
            rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
                o = ccCenter(ps[i], ps[j], ps[k]);
                r = (o - ps[i]).dist();
            }
        }
    }
    return {o, r};
}
```

CirclesUnionArea.h

Description: Returns the area of the sum of circles.

Time: $\mathcal{O}(n^2 \log n)$

```
"CircleIntersection.h" 8dfc1a, 34 lines
template<typename T> // double or long double
T circlesArea(vector<pair<P, T>> c) {
    const T PI = acos((T)-1);
    sort(all(c)); c.erase(unique(all(c)), c.end());
    T res = 0;
    for(auto &[p, r]: c) {
        int cnt = 0, cover = 0;
        vector<pair<T, int>> eve = {{-PI, 0}};
        for(auto &[q, s]: c) if(make_pair(p, r) !=
            make_pair(q, s)) {
            T dst = (p - q).dist();
            if(r + dst <= s) { cover = 1; break; }
            pair<P, P> inters;
            if(!circleInter(p, q, r, s, &inters)) continue;
            T le = (inters.st - p).angle();
            T re = (inters.nd - p).angle();
            cnt += le > re;
            eve.pb({le, 1}), eve.pb({re, -1});
        }
        if(cover) continue;
    }
```

```
sort(eve.begin() + 1, eve.end());
eve.pb({PI, 0});
T loc = 0;
fwd(i, 1, SZ(eve)) {
    if(!cnt) {
        T a = eve[i-1].st, b = eve[i].st;
        loc += r * (b - a) +
            p.cross(P(cos(b)-cos(a), sin(b)-sin(a)));
    }
    cnt += eve[i].nd;
}
res += r * loc;
return res / 2;
}
```

8.3 Polygons

InsidePolygon.h

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

Usage: vector<P> v = {P(4,4), P(1,2), P(2,1)}; bool in = inPolygon(v, P(3, 3), false); **Time:** $\mathcal{O}(n)$

```
"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = sz(p);
    rep(i,0,n) {
        P q = p[(i + 1) % n];
        if (onSegment(p[i], q, a)) return !strict;
        //or: if (segDist(p[i], q, a) <= eps) return !
            strict;
        cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q)
            ) > 0;
    }
    return cnt;
}
```

PolygonArea.h

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

```
"Point.h" f12300, 6 lines
template<class T>
T polygonArea2(vector<Point<T>>& v) {
    T a = v.back().cross(v[0]);
    rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
    return a;
}
```

PolygonCenter.h

Description: Returns the center of mass for a polygon.

Time: $\mathcal{O}(n)$

```
"Point.h" 9706dc, 9 lines
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

PolygonTangents.h

Description: Polygon tangents from a given point. The polygon must be ccw and have no collinear points. Returns a pair of indices of the given polygon. Should work for a point on border (for a point being polygon vertex returns previous and next one).

Time: $\mathcal{O}(\log n)$

```
"Point.h" 4d1a00, 21 lines
#define pdir(i) (ph ? p - poly[(i)%n] : poly[(i)%n] - p
    )
```

```
#define cmp(i,j) sgn(pdir(i).cross(poly[(i)%n]-poly[(j)
    %n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n)
    < 0
template<class P>
array<int, 2> polygonTangents(vector<P>& poly, P p) {
    auto bs = [&](int ph) {
        int n = sz(poly), lo = 0, hi = n;
        if(extr(0)) return 0;
        while (lo + 1 < hi) {
            int m = (lo + hi) / 2;
            if(extr(m)) return m;
            int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
            (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi:
                lo) = m;
        }
        return lo;
    };
    array<int, 2> res = {bs(0), bs(1)};
    if(res[0] == res[1]) res[0] = (res[0] + 1) % SZ(poly)
        ;
    if(poly[res[0]] == p) res[0] = (res[0] + 1) % SZ(poly)
        );
    return res;
}
```

Minkowski.h

Description: Computes Minkowski sum of two convex polygons in ccw order. Vertices are required to be in ccw order.

Time: $\mathcal{O}(n + m)$

```
"Point.h", "Angle.h" e0df19, 18 lines
P edgeSeq(vector<P> p, vector<P>& edges) {
    int i = 0, n = sz(p);
    rep(j, n) if (tie(p[i].y, p[i].x) > tie(p[j].y, p[j].
        x)) i = j;
    rep(j, n) edges.pb(p[(i+j+1)%n] - p[(i+j)%n]);
    return p[i];
}
vector<P> hullSum(vector<P> A, vector<P> B) {
    vector<P> sum, e1, e2, es(sz(A) + sz(B));
    P pivot = edgeSeq(A, e1) + edgeSeq(B, e2);
    merge(all(e1), all(e2), es.begin(), [&](P a, P b){
        return Angle(a.x, a.y) < Angle(b.x,b.y);
    });
    sum.pb(pivot);
    for(auto e: es) sum.pb(sum.back() + e);
    sum.pop_back();
    return sum; //can have collinear vertices!
}
```

PolygonCut.h

Description: Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.

```
Usage: vector<P> p = ...;
p = polygonCut(p, P(0,0), P(1,0));
"Point.h", "LineIntersection.h" f2b7d4, 13 lines
```

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back()
            ;
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev).second);
        if (side)
            res.push_back(cur);
    }
    return res;
}
```

PolygonUnion.h

Description: Calculates the area of the union of n polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)

Time: $\mathcal{O}(N^2)$, where N is the total number of points

```
"Point.h", "sideOf.h" 3931c6, 33 lines
typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/
    b.y; }
double polyUnion(vector<vector<P>>& poly) {
    double ret = 0;
    rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
        P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])
            ];
        vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
        rep(j,0,sz(poly)) if (i != j) {
            rep(u,0,sz(poly[j])) {
                P C = poly[j][u], D = poly[j][(u + 1) % sz(poly
                    [j])];
                int sc = sideOf(A, B, C), sd = sideOf(A, B, D);
                if (sc != sd) {
                    double sa = C.cross(D, A), sb = C.cross(D, B)
                        ;
                    if (min(sc, sd) < 0)
                        segs.emplace_back(sa / (sa - sb), sgn(sc -
                            sd));
                }
                else if (!sc && !sd && j<i && sgn((B-A).dot(D
                    -C))>0){
                    segs.emplace_back(rat(C - A, B - A), 1);
                    segs.emplace_back(rat(D - A, B - A), -1);
                }
            }
        }
        sort(all(segs));
        for (auto& s : segs) s.first = min(max(s.first,
            0.0), 1.0);
        double sum = 0;
        int cnt = segs[0].second;
        rep(j,1,sz(segs)) {
            if (!cnt) sum += segs[j].first - segs[j - 1].
                first;
            cnt += segs[j].second;
        }
        ret += A.cross(B) * sum;
    }
    return ret / 2;
}
```

ConvexHull.h

Description: Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.

Time: $\mathcal{O}(n \log n)$

```
"Point.h" 310954, 13 lines
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(sz(pts)+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <=
                0) t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] ==
        h[1])};
}
```

ConvexHullOnline.h

Description: Allows online point insertion. If exists, left vertical segment is included; right one is excluded. To get a lower hull add (-x, -y) instead of (x, y).

Time: amortized $\mathcal{O}(\log n)$ per add

```
"Point.h" 10c55b, 16 lines
using P = Point<ll>;
struct UpperHull : set<P> {
    bool rm(auto it) {
        if (it==begin() || it==end() || next(it)==end() ||
            it->cross(*prev(it), *next(it)) > 0)
            return false;
        erase(it); return true;
    }
    bool add(P p) { // true iff added
        auto [it, ok] = emplace(p);
        if (!ok || rm(it)) return false;
        while (rm(next(it)));
        while (it != begin() && rm(prev(it)));
        return true;
    }
};
```

ConvexHullOnline2.h

Description: Fully dynamic upper / lower convex hull, can be used for computing onion layers. All points should be known in advance. Points on the edges are included in the hull. Return indices are the same as in the input.

Time: $\mathcal{O}(\log^2 n)$, as fast as other $\mathcal{O}(\log n)$ hulls

```
"Point.h" 21e548, 70 lines
template<class T>
struct DynHull {
    using P = Point<T>;
    struct Point { int l, r; }; vector<P> ps;
    int n; vi in, id; int s; vector<Node> t; vector<T> m;
    DynHull(vector<P> _ps, bool lower = 0, int start = -1)
        : ps(_ps), n(sz(ps)), in(n), id(n) {
        if(start == -1) start = n;
        s = 1; while(s < n) s *= 2;
        t.resize(s * 2, {-1, -1}); m.resize(s);
        vector<pair<P, int>> pts;
        rep(i, n) pts.pb({ps[i] * (lower ? -1 : 1), i});
        sort(all(pts));
        rep(i, n) {
            tie(ps[i], id[i]) = pts[i]; in[id[i]] = i;
            int p = i + s; while((p & 1) ^ 1) p >>= 1;
            m[p >> 1] = ps[i].x;
        }
        rep(i, start) t[s + in[i]] = {in[i], in[i]};
        for (int i = s - 1; i >= 1; i --) pull(i);
    }
    int go(int v) {
        while(t[v].l < 0) v = v * 2 + t[v].l + 3;
        return v;
    }
    void pull(int v) {
        auto crossNegX = [](P a, P b, P c, P d, T x) {
            // change __int128 if using doubles!
            __int128 p = a.cross(b, c), q = b.cross(a, d);
            return p + q == 0 || (d.x - x) * p + (c.x - x) *
                q <= 0;
        };
        int p = v * 2, q = p + 1;
        if(t[p].l == -1 && t[q].l == -1) t[v] = {-1, -1};
        else if(t[p].l == -1) t[v] = {-2, -2};
        else if(t[q].l == -1) t[v] = {-3, -3};
        else {
            p = go(p), q = go(q);
            while(p < s || q < s) {
                auto [a, b] = t[p]; auto [c, d] = t[q];
                if(a != b && ps[a].cross(ps[b], ps[c]) > 0) {
                    p = go(p * 2); }
                else if(c != d && ps[b].cross(ps[c], ps[d]) >
                    0) {
                    q = go(q * 2 + 1); }
                else if(a == b) q = go(q * 2);
                else if(c == d ||
                    crossNegX(ps[a], ps[b], ps[c], ps[d], m[v]))
                    {
                        p = go(p * 2 + 1); }
            }
        }
    }
};
```

```
        else q = go(q * 2);
    }
    t[v] = {p - s, q - s};
}
void add(int i) {
    i = in[i]; int v = i + s; t[v] = {i, i};
    while(v >= 1) pull(v);
}
void del(int i) {
    i = in[i]; int v = i + s; t[v] = {-1, -1};
    while(v >= 1) {
        if(t[v].l < 0 || t[v].l == i || t[v].r == i) pull
            (v); }
}
void dfs(int v, int l, int r, vi &h) {
    if(v >= s) return h.pb(id[t[v].l]);
    if(l <= t[v].l) dfs(go(v * 2), l, min(t[v].l, r), h
        );
    if(t[v].r <= r) dfs(go(v * 2 + 1), max(t[v].r, l),
        r, h);
}
vi hull() {
    vi h; if(~t[1].l) dfs(go(1), 0, n - 1, h); return h
        ;
}
};
```

HullDiameter.h

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

Time: $\mathcal{O}(n)$

```
"Point.h" c571b8, 12 lines
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
    int n = sz(S), j = n < 2 ? 0 : 1;
    pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
    rep(i, 0, j)
        for (; j = (j + 1) % n) {
            res = max(res, {{S[i] - S[j]}.dist2(), {S[i], S[j]
                }}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]
                )) >= 0)
                break;
        }
    return res.second;
}
```

PointInsideHull.h

Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

Time: $\mathcal{O}(\log N)$

```
"Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines
typedef Point<ll> P;
bool inHull(const vector<P>& l, P p, bool strict = true)
    {
        int a = 1, b = sz(l) - 1, r = !strict;
        if (sz(l) < 3) return r && onSegment(l[0], l.back(),
            p);
        if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
        if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b],
            p) <= -r)
            return false;
        while (abs(a - b) > 1) {
            int c = (a + b) / 2;
            (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
        }
        return sgn(l[a].cross(l[b], p)) < r;
    }
};
```

LineHullIntersection.h

Description: Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet(-1, -1)$ if no collision, $\bullet(i, -1)$ if touching the corner i , $\bullet(i, i)$ if along side $(i, i + 1)$, $\bullet(i, j)$ if crossing sides $(i, i + 1)$ and $(j, j + 1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i, i + 1)$. The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

Time: $\mathcal{O}(\log n)$

```
"Point.h" 7cf45b, 39 lines
#define cmp(i, j) sgn(dir.perp().cross(poly[(i) % n] - poly
    [(j) % n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n)
    < 0
template <class P> int extrVertex(vector<P>& poly, P
    dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi :
            lo) = m;
    }
    return lo;
}
#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i, 0, 2) {
        int lo = endB, hi = endA, n = sz(poly);
        while ((lo + 1) % n != hi) {
            int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
            (cmpL(m) == cmpL(endB) ? lo : hi) = m;
        }
        res[i] = (lo + 1 % cmpL(hi)) % n;
        swap(endA, endB);
    }
    if (res[0] == res[1]) return {res[0], -1};
    if (!cmpL(res[0]) && !cmpL(res[1]))
        switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)
            ) {
            case 0: return {res[0], res[0]};
            case 2: return {res[1], res[1]};
        }
    return res;
}
```

HalfplaneIntersection.h

Description: Online half plane intersection. Works both for ll and long double. Bounding box is optional, but needed for distinguishing bounded vs unbounded. Halfplanes are sorted ccw in HPI.s. Time: $\mathcal{O}(\log n)$ per add.

```
"Point.h" f5db92, 98 lines
using T = ll; // has to fit 2*|pts|**2
using P = Point<T>; // only cross needed
using SuperT = __int128_t; // has to fit 6*|pts|**3
const SuperT EPS = 1e-12; // |pts| <= 10^6 (for T=dbl)
struct Line {
    T a, b, c;
    Line(T a_=0, T b_=0, T c_=0): a(a_), b(b_), c(c_) {}
    //ax + by + c >= 0 (coords <= 10^9)
    Line(P p, P q): a(p.y-q.y), b(q.x-p.x), c(p.cross(q))
        {} //p->q ccw (coords <= 10^6)
    Line operator< () const {return Line(-a, -b, -c); }
    bool up() const {return a?(a<0):(b>0);}
    P v() const {return P(a,b);}
    P vx() {return P(b,c);} P vy() {return P(a,c);}
    T wek(Line p) const {return v().cross(p.v());}
```

```
bool operator<(Line b) const {
    if (up() != b.up()) return up() > b.up();
    return wek(b) > 0;
}
};
bool parallel(Line a, Line b) {return !a.wek(b);}
bool same(Line a, Line b) {
    return parallel(a,b) && !a.vy().cross(b.vy()) && !a.
        vx().cross(b.vx());
}
T weaker(Line a, Line b) {
    if (abs(a.a) > abs(a.b)) return a.c*abs(b.a) - b.c*
        abs(a.a);
    return a.c*abs(b.b) - b.c*abs(a.b);
}
array<SuperT, 3> intersect(Line a, Line b) {
    SuperT det = a.wek(b);
    SuperT x = a.vx().cross(b.vx());
    SuperT y = a.vy().cross(b.vy());
    // if (T=dbl) return {x / det, -y / det, 1.0};
    if (det > 0) return {x, -y, det};
    return {-x, y, -det};
}
struct HPI {
    bool empty=0, pek=0;
    set<Line> s;
    typedef set<Line>::iterator iter;
    iter next(iter it){return ++it == s.end() ? s.begin()
        : it;}
    iter prev(iter it){return it == s.begin() ? --s.end()
        : --it;}
    bool hide(Line a, Line b, Line c) { // do a,b hide c?
        if (parallel(a,b)) {
            if (weaker(a, -b) < 0) empty = 1;
            return 0;
        }
        if (a.wek(b) < 0) swap(a,b);
        auto [rx, ry, rdet] = intersect(a,b);
        auto v = rx*c.a + ry*c.b + rdet*c.c;
        if (a.wek(c) >=0 && c.wek(b) >=0 && v >= -EPS)
            return 1;
        if (a.wek(c) < 0 && c.wek(b) < 0) {
            if (v < -EPS) empty = 1;
            else if (v <= EPS) pek = 1;
        }
        return 0;
    }
    void delAndMove(iter& i, int nxt) {
        iter j = i;
        if(nxt==1) i = next(i);
        else i = prev(i);
        s.erase(j);
    }
    void add(Line l) {
        if (empty) return;
        if (l.a == 0 && l.b == 0) {
            if (l.c < 0) empty = 1;
            return;
        }
        iter it = s.lower_bound(l); //parallel
        if(it != s.end() && parallel(*it, l) && it->up() ==
            l.up()) {
            if (weaker(l, *it)>=0) return;
            delAndMove(it,1);
        }
        if(it == s.end()) it = s.begin(); //*it>p
        while(sz(s) >= 2 && hide(l, *next(it), *it))
            delAndMove(it,1);
        if(sz(s)) it = prev(it); //*it<q
        while(sz(s) >= 2 && hide(l, *prev(it), *it))
            delAndMove(it,0);
        if(sz(s) < 2 || !hide(*it, *next(it), l)) s.insert(
            l);
    }
    int type() { // 0=empty, 1=point, 2=segment,
        if(empty) return 0; // 3=halfline, 4=line,
        if(sz(s) <= 4) { // 5=polygon or unbounded
            vector<Line> r(all(s));
```

```

    if(sz(r) == 2 && parallel(r[0], r[1]) && weaker(r
        [0],-r[1])<0)
        return 0;
    rep(i, sz(r)) rep(j, i) if(same(r[i], r[j])) {
        if(sz(r) == 2) return 4;
        if(sz(r) == 3) return 3;
        if(sz(r) == 4 && same(r[0], r[2]) && same(r[1],
            r[3])) return 1;
        return 2;
    }
    if(sz(r) == 3 && pek) return 1;
    return 5;
}
};

```

HalfplaneIntersection2.h

Description: Weszło na zadaniu gdzie trzeba bylo policzyć pole przeciecia

<bits/stdc++.h> **b05643, 152 lines**

```

using namespace std;
const int N = 100;
typedef long double LD;
const LD inf = 500 + 7;
struct Point {
    LD x, y;
    void read() {
        int xx, yy;
        cin >> xx >> yy;
        x = xx;
        y = yy;
    }
};
Point operator- (const Point& A, const Point& B) {
    return Point(A.x - B.x, A.y - B.y); }
Point operator+ (const Point& A, const Point& B) {
    return Point(A.x + B.x, A.y + B.y); }
Point operator* (const Point& A, const LD& value) {
    return Point(A.x * value, A.y * value); }
int half(const Point& v) {
    if (v.x < 0 && v.y < 0)
        return 1;
    if (v.x >= 0 && v.y < 0)
        return 2;
    if (v.x >= 0 && v.y >= 0)
        return 3;
    if (v.x < 0 && v.y >= 0)
        return 4;
    assert(false);
    return -1;
}
LD dot(const Point& A, const Point& B) { return A.x * B
    .x + A.y * B.y; }
LD det(const Point& A, const Point& B) { return A.x * B
    .y - A.y * B.x; }
LD det(const Point& A, const Point& B, const Point& C)
    { return det(B - A, C - A); }
struct Halfplane {
    Point P, v;
    bool inside(const Point& Q) const {
        return det(v, Q - P) > -1e-9;
    }
    bool operator< (const Halfplane& other) const {
        if (half(v) != half(other.v))
            return half(v) < half(other.v);
        return det(v, other.v) > 0;
    }
};
Point inter(const Halfplane& k, const Halfplane& l) {
    return k.P + k.v * (det(l.P - k.P, l.v) / det(k.v, l
        .v));
}
int n;
Point pts[N][2];
int main() {
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    cout << fixed << setprecision(12);

```

```

    cin >> n;
    for (int i = 0; i < n; i++)
        for (int j : {0, 1})
            pts[i][j].read();
    vector<Halfplane> hps;
    for (int i = 0; i < n; i++) {
        for (int j : {0, 1}) {
            for (int k = 0; k < n; k++) if (i != k) {
                for (int l : {0, 1}) {
                    bool ok = true;
                    for (int m = 0; m < n; m++) if (m != i && m
                        != k) {
                        if (det(pts[i][j], pts[k][l], pts[m][0]) <
                            0 &&
                            det(pts[i][j], pts[k][l], pts[m][1]) < 0)
                            ok = false;
                        break;
                    }
                }
                if (ok) {
                    hps.push_back(Halfplane(pts[i][j], pts[k][l]
                        ] - pts[i][j]));
                }
            }
        }
    }
    const Point box[4] = {
        Point{+inf, +inf},
        Point{+inf, -inf},
        Point{-inf, -inf},
        Point{-inf, +inf}
    };
    for (int i = 0, j = 3; i < 4; j = i++) {
        hps.push_back(Halfplane(box[i], box[j] - box[i]));
    }
    sort(hps.begin(), hps.end());
    deque<Halfplane> dq;
    for (const Halfplane& hp : hps) {
        while (dq.size() >= 2 && !hp.inside(inter(end(dq)
            [-1], end(dq)[-2])))
            dq.pop_back();
        while (dq.size() >= 2 && !hp.inside(inter(dq[0], dq
            [1])))
            dq.pop_front();
        if (dq.size() && fabs1(det(hp.v, dq.back().v)) < 1e
            -9L) {
            if (dot(hp.v, dq.back().v) < 0) {
                cout << 0.0L << '\n';
                return 0;
            }
            if (!hp.inside(dq.back().P)) {
                dq.pop_back();
                dq.push_back(hp);
            }
        }
        else {
            dq.push_back(hp);
        }
    }
    while (dq.size() >= 3 && !dq[0].inside(inter(end(dq)
        [-1], end(dq)[-2])))
        dq.pop_back();
    while (dq.size() >= 3 && !end(dq)[-1].inside(inter(dq
        [0], dq[1])))
        dq.pop_front();
    vector<Point> hull;
    for (int i = 0, j = (int) dq.size() - 1; i < (int) dq
        .size(); j = i++) {
        hull.push_back(inter(dq[j], dq[i]));
    }
    long double ans = 0;
    for (int i = 0, j = (int) hull.size() - 1; i < (int)
        hull.size(); j = i++) {
        ans += det(hull[i], hull[j]);
    }
    ans /= 2;
    cout << fabs1(ans) << '\n';

```

```

    return 0;
}
PointLocation.h
Description: Computes (not necessarily convex) polygon tree
structure. Also for each query point computes its location (in-
cluding boundaries).
Time:  $O(n \log n)$ 
"directedSegment.h" 39f30f, 47 lines
template<class P>
pair<vi,vi> pointLoc(vector<vector<P>> polys, vector<P>
    pts) {
    vector<tuple<P, int, int>> eve; // {point, event_type
        , id}
    vector<pair<dirSeg<P>, int>> segs; // {s, e, poly_id
        }
    rep(i, sz(polys)) rep(j, sz(polys[i])) {
        dirSeg<P> seg(polys[i][j], polys[i][(j+1)%sz(polys[
            i])]);
        eve.pb({seg.s,0,sz(segs)}), eve.pb({seg.e,2,sz(segs
            )});
        segs.pb({seg, i});
    }
    rep(i, sz(pts)) eve.pb({pts[i], 1, i});
    sort(all(eve));
    vi par(sz(polys), -2), ans(sz(pts), -1);
    auto cmp = [](auto a, auto b) {
        return make_pair(a.st.cmp(b.st), a.nd) < make_pair
            (0, b.nd);
    };
    set<pair<dirSeg<P>, int>, decltype(cmp)> s(cmp);
    for(auto &[_ , eve_tp, id]: eve) {
        if(eve_tp == 1) { // point query
            P p = pts[id];
            auto it = s.lower_bound({dirSeg(p, p), 0});
            if(it != s.begin()) { // on vertical segment?
                auto prv = prev(it);
                if(!sgn(p.cross(prv->st.s, prv->st.e))) it--;
            }
            if(it == s.end()) ans[id] = -1;
            else {
                auto [seg, seg_id] = *it;
                int poly_id = segs[seg_id].nd; // strictness
                    there!
                ans[id] = !seg.rev && sgn(p.cross(seg.s, seg.e)
                    )
                    ? par[poly_id] : poly_id;
            }
        }
        if(eve_tp == 0) { // add segment
            auto it = next(s.insert({segs[id].st, id}).st);
            int poly_id = segs[id].nd;
            if(par[poly_id] == -2) {
                if(it == s.end()) par[poly_id] = -1;
                else {
                    int up_rev = it->st.rev, up_id = segs[it->nd
                        ].nd;
                    par[poly_id] = !up_rev ? par[up_id] : up_id;
                }
            }
        }
        if(eve_tp == 2) s.erase({segs[id].st, id}); // del
            segment
    }
    return {par, ans};
}

```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.

Time: $O(n \log n)$

"Point.h" **ac41a6, 17 lines**

```

typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(all(v), [](P a, P b) { return a.y < b.y; });
    pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};

```

```

    int j = 0;
    for (P p : v) {
        P d(1 + (1ll)sqrt(ret.first), 0);
        while (v[j].y <= p.y - d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi = S.upper_bound(
            p + d);
        for (; lo != hi; ++lo)
            ret = min(ret, {(lo - p).dist2(), {lo, p}});
        S.insert(p);
    }
    return ret.second;
}

```

FurthestPair.h

Description: assumes $n \geq 2$, $O(n)$.

Time: $O(n^2)$

"../convex-hull/main.cpp" **d59d33, 12 lines**

```

pair<P, P> furthest_pair(vector<P> in) {
    in = hull(in);
    int n = ssize(in), j = 1;
    pair<D, pair<P, P>> ret;
    REP(i, j)
        for(; j = (j + 1) % n) {
            ret = max(ret, {dist(in[i], in[j]), {in[i], in[j]
                }}});
            if (sign(cross(in[(j + 1) % n] - in[j], in[i + 1]
                - in[i])) <= 0)
                break;
        }
    return ret.second;
}

```

ManhattanMST.h

Description: Given N points, returns up to $4*N$ edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights $w(p, q) = |p.x - q.x| + |p.y - q.y|$. Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST.

Time: $O(N \log N)$

"Point.h" **df6f59, 23 lines**

```

typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
    vi id(sz(ps));
    iota(all(id), 0);
    vector<array<int, 3>> edges;
    rep(k,0,4) {
        sort(all(id), [&](int i, int j) {
            return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;});
        map<int, int> sweep;
        for (int i : id) {
            for (auto it = sweep.lower_bound(-ps[i].y);
                it != sweep.end(); sweep.erase(it++)) {
                int j = it->second;
                P d = ps[i] - ps[j];
                if (d.y > d.x) break;
                edges.push_back({d.y + d.x, i, j});
            }
            sweep[-ps[i].y] = i;
        }
        for (P& p : ps) if (k & 1) p.x = -p.x; else swap(p
            .x, p.y);
    }
    return edges;
}

```

kdTree.h

Description: KD-tree (2d, can be extended to 3d)

"Point.h" **bac5b0, 63 lines**

```

typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();
bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }
struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds

```



```
Node *first = 0, *second = 0;
T distance(const P& p) { // min squared distance to a point
    T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
    T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
    return (P(x,y) - p).dist2();
}
Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
        x0 = min(x0, p.x); x1 = max(x1, p.x);
        y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
        // split on x if width >= height (not ideal...)
        sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
        // divide by taking half the array for each child
        (not
         // best performance with many duplicates in the middle)
         int half = sz(vp)/2;
         first = new Node({vp.begin(), vp.begin() + half});
         ;
         second = new Node({vp.begin() + half, vp.end()});
    }
};
struct KDTree {
    Node* root;
    KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}
    pair<T, P> search(Node *node, const P& p) {
        if (!node->first) {
            // uncomment if we should not find the point itself:
            // if (p == node->pt) return {INF, P()};
            return make_pair((p - node->pt).dist2(), node->pt);
        }
        Node *f = node->first, *s = node->second;
        T bfirst = f->distance(p), bsec = s->distance(p);
        if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);
        // search closest side first, other side if needed
        auto best = search(f, p);
        if (bsec < best.first)
            best = min(best, search(s, p));
        return best;
    }
    // find nearest point to a point, and its squared distance
    // (requires an arbitrary operator< for Point)
    pair<T, P> nearest(const P& p) {
        return search(root, p);
    }
};
```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ... }, all counter-clockwise.

```
Time:  $\mathcal{O}(n \log n)$ 
"Point.h" eefdf5, 88 lines
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t lll; // (can be ll if coords are < 2^64)
P arb(LLONG_MAX, LLONG_MAX); // not equal to any other point
struct Quad {
    Q rot, o; P p = arb; bool mark;
    P& F() { return r()->p; }
    P& r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return r()->prev(); }
} *H;
```

```
bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
    lll p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
    Q r = H ? H : new Quad(new Quad(new Quad{0}));
    };
    H = r->o; r->r()->r() = r;
    rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
    r->p = orig; r->F() = dest;
    return r;
}
void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}
pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }
    #define H(e) e->F(), e->p
    #define valid(e) (e->F().cross(H(base)) > 0)
    Q A, B, ra, rb;
    int half = sz(s) / 2;
    tie(ra, A) = rec({all(s) - half});
    tie(B, rb) = rec({sz(s) - half + all(s)});
    while ((B->p.cross(H(A)) < 0 && (A = A->next()) || (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
    Q base = connect(B->r(), A);
    if (A->p == ra->p) ra = base->r();
    if (B->p == rb->p) rb = base;
    #define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
        while (circ(e->dir->F(), H(base), e->F())) { \
            Q t = e->dir; \
            splice(e, e->prev()); \
            splice(e->r(), e->r()->prev()); \
            e->o = H; H = e; e = t; \
        }
    for (;;) {
        DEL(LC, base->r(), o); DEL(RC, base, prev());
        if (!valid(LC) && !valid(RC)) break;
        if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
            base = connect(RC, base->r());
        else
            base = connect(base->r(), LC->r());
    }
    return { ra, rb };
}
vector<P> triangulate(vector<P> pts) {
    sort(all(pts)); assert(unique(all(pts)) == pts.end());
    if (sz(pts) < 2) return {};
    Q e = rec(pts).first;
    vector<Q> q = {e};
    int qi = 0;
    while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
    #define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
        q.push_back(c->r()); c = c->next(); } while (c != e); }
    ADD;
    pts.clear();
}
```

```
while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
return pts;
}
8.5 3D
PolyhedronVolume.h
Description: Magic formula for the volume of a polyhedron. Faces should point outwards.
3058c3, 6 lines
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

Point3D.h

```
Description: Class to handle points in 3D space. T can be e.g. double or long long.
8058ae, 32 lines
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
    bool operator<(R p) const { return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const { return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const { return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x); }
    T dist2() const { return x*x + y*y + z*z; }
    double dist() const { return sqrt((double)dist2()); }
    //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
    double phi() const { return atan2(y, x); }
    //Zenith angle (latitude) to the z-axis in interval [0, pi]
    double theta() const { return atan2(sqrt(x*x+y*y),z); }
    P unit() const { return *this/(T)dist(); } //makes dist()==1
    //returns unit vector normal to *this and p
    P normal(P p) const { return cross(p).unit(); }
    //returns point rotated 'angle' radians ccw around axis
    P rotate(double angle, P axis) const {
        double s = sin(angle), c = cos(angle); P u = axis.unit();
        return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
    }
};
```

3dHull.h

```
Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.
Time:  $\mathcal{O}(n^2)$ 
"Point3D.h" 5b45fc, 49 lines
typedef Point3D<double> P3;
struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};
struct F { P3 q; int a, b, c; };
```

```
vector<F> hull3d(const vector<P3>& A) {
    assert(sz(A) >= 4);
    vector<vector<PR>> E(sz(A), vector<PR>{sz(A), {-1, -1}}));
    #define E(x,y) E[f.x][f.y]
    vector<F> FS;
    auto mf = [&](int i, int j, int k, int l) {
        P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
        if (q.dot(A[l]) > q.dot(A[i]))
            q = q * -1;
        F f(q, i, j, k);
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.push_back(f);
    };
    rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
        mf(i, j, k, 6 - i - j - k);
    rep(i,4,sz(A)) {
        rep(j,0,sz(FS)) {
            F f = FS[j];
            if (f.q.dot(A[i]) > f.q.dot(A[f.a])) {
                E(a,b).rem(f.c);
                E(a,c).rem(f.b);
                E(b,c).rem(f.a);
                swap(FS[j--], FS.back());
                FS.pop_back();
            }
        }
        int nw = sz(FS);
        rep(j,0,nw) {
            F f = FS[j];
            #define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
            C(a, b, c); C(a, c, b); C(b, c, a);
        }
    }
    for (F& it : FS) if ((A[it.b] - A[it.a]).cross(A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
    return FS;
};
```

sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 (ϕ_1) and f2 (ϕ_2) from x axis and zenith angles (latitude) t1 (θ_1) and t2 (θ_2) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points.

```
double sphericalDistance(double f1, double t1, double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

Strings (9)

KMP.h

Description: pi[x] computes the length of the longest prefix of s that ends at x, other than s[0..x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string. **Time:** $\mathcal{O}(n)$

```
d4375c, 16 lines
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}
vi match(const string& s, const string& pat) {
```

```

vi p = pi(pat + '\0' + s), res;
rep(i,sz(p)-sz(s),sz(p))
    if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
    ;
return res;
}

```

Zfunc.h

Description: $z[i]$ computes the length of the longest common prefix of $s[i:]$ and s , except $z[0] = 0$. (abacaba -> 0010301)
Time: $\mathcal{O}(n)$

ee09e2, 12 lines

```

vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
            z[i]++;
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    return z;
}

```

Manacher.h

Description: For each position in a string, computes $p[0][i]$ = half length of longest even palindrome around pos i , $p[1][i]$ = longest odd (half rounded down).
Time: $\mathcal{O}(N)$

e7ad79, 13 lines

```

array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}

```

MainLorentz.h

Description: Main-Lorentz algorithm for finding all squares in given word; Results are in compressed form: (b, e, l) means that for each $b \leq i \leq e$ there is square at position i of size $2l$. Each square is present in only one interval.

Time: $\mathcal{O}(nlgn)$

46fbbc, 46 lines

```

struct Sqr {
    int begin, end, len;
};
vector<Sqr> lorentz(const string &s) {
    vector<Sqr> ans;
    vi pos(sz(s) / 2 + 2, -1);
    fwd(mid, 1, sz(s)) {
        int part = mid & ~(mid - 1), off = mid - part;
        int end = min(mid + part, sz(s));
        auto a = s.substr(off, part);
        auto b = s.substr(mid, end - mid);
        string ra(a.rbegin(), a.rend());
        string rb(b.rbegin(), b.rend());
        rep(j, 2) {
            // Set # to some unused character!
            vi z1 = Z(ra, true);
            vi z2 = Z(b + "##" + a, true);
            z1.pb(0);
            z2.pb(0);
            rep(c, sz(a)) {
                int l = sz(a) - c;
                int x = c - min(l - 1, z1[l]);
                int y = c - max(l - z2[sz(b) + c + 1], j);
                if (x > y)
                    continue;
                int sb = (j ? end - y - 1 * 2 : off + x);

```

```

        int se = (j ? end - x - 1 * 2 + 1 : off + y + 1);
        int &p = pos[l];
        if (p != -1 && ans[p].end == sb)
            ans[p].end = se;
        else
            p = sz(ans), ans.pb({sb, se, l});
    }
    a.swap(rb);
    b.swap(ra);
}
}
return ans;
}

```

Lyndon.h

Description: Compute Lyndon factorization for s ; Word is simple iff it's strictly smaller than any of it's nontrivial suffixes. Lyndon factorization is division of string into non-increasing simple words. It is unique.

Time: $\mathcal{O}(n)$

688c1c, 12 lines

```

vector<string> duval(const string &s) {
    int n = sz(s), i = 0;
    vector<string> ret;
    while (i < n) {
        int j = i + 1, k = i;
        while (j < n && s[k] <= s[j])
            k = (s[k] < s[j] ? i : k + 1), j++;
        while (i <= k)
            ret.pb(s.substr(i, j - k)), i += j - k;
    }
    return ret;
}

```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.

Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());

Time: $\mathcal{O}(N)$

d07a42, 8 lines

```

int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1);
            break;}
        if (s[a+k] > s[b+k]) {a = b; break;}
    }
    return a;
}

```

SuffixArray.h

Description: Builds suffix array for a string. $sa[i]$ is the starting index of the suffix which is i 'th in the sorted suffix array. The returned vector is of size $n + 1$, and $sa[0] = n$. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: $lcp[i] = lcp(sa[i], sa[i-1])$, $lcp[0] = 0$. The input string must not contain any zero bytes.

Time: $\mathcal{O}(n \log n)$

769289, 23 lines

```

struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string& s, int lim=256) { // or
        basic_string<int>
        int n = sz(s) + 1, k = 0, a, b;
        vi x(all(s)), y(n), ws(max(n, lim)), rank(n);
        x.push_back(0), sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2),
            lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =

```

```

        (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
    }
    rep(i,1,n) rank[sa[i]] = i;
    for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
        for (k && k--, j = sa[rank[i] - 1];
            s[i + k] == s[j + k]; k++);
}
};

```

SuffixTree.h

Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices $[l, r]$ into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining $[l, r]$ substrings. The root is 0 (has $l = -1$, $r = 0$), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substrng matching, though).

Time: $\mathcal{O}(26N)$

aae0b8, 50 lines

```

struct SuffixTree {
    enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALPHA], l[N], r[N], p[N], s[N], v=0, q=0, m=2;
    void ukkadd(int i, int c) { suff:
        if (r[v]<=q) {
            if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
                p[m++]=v; v=s[v]; q=r[v]; goto suff; }
            v=t[v][c]; q=l[v];
        }
        if (q==-1 || c==toi(a[q])) q++; else {
            l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
            p[m]=p[v]; t[m][c]=m+1; t[m][toi(a[q])]=v;
            l[v]=q; p[v]=m; t[p[m]][toi(a[l[m]])]=m;
            v=s[p[m]]; q=l[m];
            while (q<r[m]) { v=t[v][toi(a[q])]; q+=r[v]-l[v]; }
            if (q==r[m]) s[m]=v; else s[m]=m+2;
            q=r[v]-(q-r[m]); m+=2; goto suff;
        }
    }
    SuffixTree(string a) : a(a) {
        fill(r,r+N,sz(a));
        memset(s, 0, sizeof s);
        memset(t, -1, sizeof t);
        fill(t[1],t[1]+ALPHA,0);
        s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
        rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
    }
    // example: find longest common substring (uses ALPHA = 28)
}

```

```

pii best;
int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]
        ) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
        mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
        best = max(best, {len, r[node] - len});
    return mask;
}
static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z'
        + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
}
}

```

Hashing.h

Description: Self-explanatory methods for string hashing

f35a6f, 44 lines

```

// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and
// more

```

```

// code, but works on evil test data (e.g. Thue-Morse,
// where
// ABBA... and BAAB... of length 2^10 hash the same mod
// 2^64).
// "typedef ull H;" instead if you think test data is
// random,
// or work mod 10^9+7 if the Birthday paradox is not a
// problem.
typedef uint64_t ull;
struct H {
    ull x; H(ull x=0) : x(x) {}
    H operator+(H o) { return x + o.x + (x + o.x < x); }
    H operator-(H o) { return *this + ~o.x; }
    H operator*(H o) { auto m = (__uint128_t)x * o.x;
        return H((ull)m) + (ull)(m >> 64); }
    ull get() const { return x + !~x; }
    bool operator==(H o) const { return get() == o.get(); }
    bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (1ll)1e11+3; // (order ~ 3e9; random
// also ok)
struct HashInterval {
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
};
vector<H> getHashes(string& str, int length) {
    if (sz(str) < length) return {};
    H h = 0, pw = 1;
    rep(i,0,length)
        h = h * C + str[i], pw = pw * C;
    vector<H> ret = {h};
    rep(i,length,sz(str)) {
        ret.push_back(h = h * C + str[i] - pw * str[i-
            length]);
    }
    return ret;
}
H hashString(string& s){H h{}; for(char c:s) h=h*C+c;
    return h;}

```

AhoCorasick.h

Description: Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(–, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.

Time: construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.

f35677, 66 lines

```

struct AhoCorasick {
    enum {alpha = 26, first = 'A'}; // change this!
    struct Node {
        // (nmatches is optional)
        int back, next[alpha], start = -1, end = -1,
            nmatches = 0;
        Node(int v) { memset(next, v, sizeof(next)); }
    };
    vector<Node> N;
    vi backp;
    void insert(string& s, int j) {
        assert(!s.empty());
        int n = 0;
        for (char c : s) {
            int& m = N[n].next[c - first];

```

```

    if (m == -1) { n = m = sz(N); N.emplace_back(-1);
    }
    else n = m;
}
if (N[n].end == -1) N[n].start = j;
backp.push_back(N[n].end);
N[n].end = j;
N[n].nmatches++;
}
AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i, 0, sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);
    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
        int n = q.front(), prev = N[n].back;
        rep(i, 0, alpha) {
            int &ed = N[n].next[i], y = N[prev].next[i];
            if (ed == -1) ed = y;
            else {
                N[ed].back = y;
                (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
                    = N[y].end;
                N[ed].nmatches += N[y].nmatches;
                q.push(ed);
            }
        }
    }
}
vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
        n = N[n].next[c - first];
        res.push_back(N[n].end);
        // count += N[n].nmatches;
    }
    return res;
}
vector<vi> findAll(vector<string>& pat, string word)
{
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i, 0, sz(word)) {
        int ind = r[i];
        while (ind != -1) {
            res[i - sz(pat[ind]) + 1].push_back(ind);
            ind = backp[ind];
        }
    }
    return res;
}
};

```

ALCS.h

Description: All-substrings common sequences algorithm. Given strings A and B, algorithm computes: $C(i, j, k) = |LCS(A[1:i], B[j:k])|$ in compressed form; To describe the compression, note that: 1. $C(i, j, k-1) \leq C(i, j, k) \leq C(i, j, k-1) + 1$ 2. If $j < k$ and $C(i, j, k) = C(i, j, k-1) + 1$, then $C(i, j+1, k) = C(i, j+1, k-1) + 1$ 3. If $j \geq k$, then $C(i, j, k) = 0$ This allows us to store just the following: $ih(i, k) = \min j$ s.t. $C(i, j, k-1) < C(i, j, k)$

Time: $\mathcal{O}(nm)$

Saadab, 58 lines

```

struct ALCS {
    string A, B;
    vector<vi> ih;
    // Precompute compressed matrix; time: O(nm)
    ALCS(string s, string t) : A(s), B(t) {
        int n = sz(A), m = sz(B);
        ih.resize(n + 1, vi(m + 1));
        iota(all(ih[0]), 0);
        fwd(1, 1, n + 1) {
            int iv = 0;
            fwd(j, 1, m + 1) {
                if (A[l - 1] != B[j - 1]) {
                    ih[l][j] = max(ih[l - 1][j], iv);

```

```

                    iv = min(ih[l - 1][j], iv);
                } else {
                    ih[l][j] = iv;
                    iv = ih[l - 1][j];
                }
            }
        }
    }
    // Compute |LCS(A[1:i], B[j:k])|; time: O(k-j)
    // Note: You can precompute data structure
    // to answer these queries in O(log n)
    // or compute all answers for fixed 'i'.
    int operator()(int i, int j, int k) {
        int ret = 0;
        fwd(q, j, k) ret += (ih[i][q + 1] <= j);
        return ret;
    }
    // Compute subsequence LCS(A[1:i], B[j:k]);
    // time: O(k-j)
    string recover(int i, int j, int k) {
        string ret;
        while (i > 0 && j < k) {
            if (ih[i][k-1] <= j) {
                ret.pb(B[k]);
                while (A[--i] != B[k])
                    ;
            }
        }
        reverse(all(ret));
        return ret;
    }
    // Compute LCS'es of given prefix of A,
    // and all prefixes of given suffix of B.
    // Returns vector L of length |B|+1 s.t.
    // L[k] = |LCS(A[1:i], B[j:k])|; time: O(|B|)
    vi row(int i, int j) {
        vi ret(sz(B) + 1);
        fwd(k, j + 1, sz(ret)) ret[k] = ret[k - 1] + (ih[i][k] <= j);
        return ret;
    }
}
};

```

PalindromicTree.h

Description: Computes plaindromic tree: for each end position in the string we store longest palindrome ending in that position. link is the suffix palindrome links, eg ababa -> aba. Can be used to compute shortest decomposition of strings to palindromes in $\mathcal{O}(n \log n)$ time - use [DP] lines.

Time: $\mathcal{O}(N)$

eb3607, 38 lines

```

constexpr int ALPHA = 26;
struct PalTree {
    vi txt; //; Node 0=empty pal (root of even), 1="-1"
    pal (of odd)
    vi len(0, -1); // Lengths of palindromes
    vi link(1, 0); // Suffix palindrome links, eg [ababa]
    //> [aba]
    vector<array<int, ALPHA>> to({}, {}); // egdes, ex:
    // aba -> cabac
    int last(0); // Current node (max suffix pal)
    vi diff(0, 0); // [DP] len[i]-len[link[i]]
    vi slink(0, 0); // [DP] like link but to having
    // different 'diff'
    vi series(0, 0); // [DP] dp for series (groups of pals
    // with =diff)
    vi ans(0); // [DP] ans for prefix
    int ext(int i) {
        while (len[i]+2>sz(txt) || txt[sz(txt)-len[i]-2] !=
            txt.back())
            i = link[i];
        return i;
    }
    void add(int x) { // x in [0, ALPHA], time O(1) or O(lg
        n) for DP
        txt.pb(x); last = ext(last);
        if (!to[last][x]) {
            len.pb(len[last] + 2);
            link.pb(to[ext(link[last])][x]);

```

```

        to[last][x] = sz(to);
        to.pb({});
        diff.pb(len.back() - len[link.back()]); // [DP]
        slink.pb(diff.back() == diff[link.back()] ? slink
            [link.back()] : link.back()); // [DP]
        series.pb(0); // [DP]
    }
    last = to[last][x];
    ans.pb(INT_MAX); // [DP]
    for (int i = last; len[i] > 0; i = slink[i]) { // [DP]
        series[i] = ans[sz(ans) - len[slink[i]] - diff[i]
            - 1]; // [DP]
        if (diff[i] == diff[link[i]]) // [DP]
            series[i] = min(series[i], series[link[i]]); //
            [DP]
        // For even only palindromes set ans only for even
        sz(txt) // [DP]
        ans.back() = min(ans.back(), series[i] + 1); // [
            DP]
    }
}
};

```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).

Time: $\mathcal{O}(\log N)$

edce47, 23 lines

```

set<pii>::iterator addInterval(set<pii>& is, int L, int
    R) {
    R) {
        if (L == R) return is.end();
        auto it = is.lower_bound((L, R)), before = it;
        while (it != is.end() && it->first <= R) {
            R = max(R, it->second);
            before = it = is.erase(it);
        }
        if (it != is.begin() && (--it)->second >= L) {
            L = min(L, it->first);
            R = max(R, it->second);
            is.erase(it);
        }
        return is.insert(before, {L, R});
    }
}
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}

```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).

Time: $\mathcal{O}(N \log N)$

9e9d8d, 19 lines

```

template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
    sort(all(S), [&](int a, int b) { return I[a] < I[b];
        });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at < sz(I) && I[S[at]].first <= cur) {
            mx = max(mx, make_pair(I[S[at]].second, S[at]));
            at++;

```

```

        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}

```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.

Usage: constantIntervals(0, sz(v), [&](int x) {return v[x];}, [&](int lo, int hi, T val) {...});

Time: $\mathcal{O}(k \log \frac{n}{k})$

753a4c, 19 lines

```

template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T
    q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}

```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \dots < f(i) \geq \dots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f , change it to >, also at (B).

Usage: int ind = ternSearch(0, n-1, [&](int i) {return a[i];});

Time: $\mathcal{O}(\log(b-a))$

9155b4, 11 lines

```

template<class F>
int ternSearch(int a, int b, F f) {
    assert(a <= b);
    while (b - a >= 5) {
        int mid = (a + b) / 2;
        if (f(mid) < f(mid+1)) a = mid; // (A)
        else b = mid+1;
    }
    rep(i, a+1, b+1) if (f(a) < f(i)) a = i; // (B)
    return a;
}

```

LIS.h

Description: Compute indices for the longest increasing subsequence.

Time: $\mathcal{O}(N \log N)$

2932a0, 17 lines

```

template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i, 0, sz(S)) {
        // change 0 -> i for longest non-decreasing
        // subsequence
        auto it = lower_bound(all(res), p(S[i], 0));
        if (it == res.end()) res.emplace_back(), it = res.
            end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
}

```

```
int L = sz(res), cur = res.back().second;
vi ans(L);
while (L-->) ans[L] = cur, cur = prev[cur];
return ans;
}
```

FastKnapsack.h

Description: Given N non-negative integer weights w and a non-negative target t , computes the maximum $S \leq t$ such that S is the sum of some subset of the weights.

Time: $\mathcal{O}(N \max(w_i))$ b20ccc, 16 lines

```
int knapsack(vi w, int t) {
    int a = 0, b = 0, x;
    while (b < sz(w) && a + w[b] <= t) a += w[b++];
    if (b == sz(w)) return a;
    int m = *max_element(all(w));
    vi u, v(2*m, -1);
    v[a+m-t] = b;
    rep(i,b,sz(w)) {
        u = v;
        rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
        for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
            v[x-w[j]] = max(v[x-w[j]], j);
    }
    for (a = t; v[a+m-t] < 0; a--);
    return a;
}
```

HilbertMO.h

Description: Packing. 7646cf, 35 lines

// Modified MO's queries sorting algorithm,
// slightly better results than standard.
// Allows to process q queries in $\mathcal{O}(n \sqrt{q})$

```
struct Query {
    int begin, end;
};
// Get point index on Hilbert curve
ll hilbert(int x, int y, int s, ll c = 0) {
    if (s <= 1) return c;
    s /= 2; c *= 4;
    if (y < s)
        return hilbert(x&(s-1), y, s, c+(x>=s)+1);
    if (x < s)
        return hilbert(2*s-y-1, s-x-1, s, c);
    return hilbert(y-s, x-s, s, c+3);
}
// Get good order of queries; time:  $\mathcal{O}(n \lg n)$ 
vi moOrder(vector<Query>& queries, int maxN) {
    int s = 1;
    while (s < maxN) s *= 2;
    vector<ll> ord;
    for( auto &q : queries)
        ord.pb(hilbert(q.begin, q.end, s));
    vi ret(sz(ord));
    iota(all(ret), 0);
    sort(all(ret), [&s](int l, int r) {
        return ord[l] < ord[r];
    });
    return ret;
}
```

Packing.h

Description: Packing. 03b70d, 50 lines

```
// Utilities for packing precomputed tables.
// Encodes 13 bits using two characters.
// Writer out; out.ints(-123, 8);
// out.done(); cout << out.buf;
struct Writer {
    string buf;
    int cur = 0, has = 0;
    void done() {
        buf.pb(char(cur%91 + 35));
        buf.pb(char(cur/91 + 35));
        cur = has = 0;
    } // Write unsigned b-bit integer.
    void intu(uint64_t v, int b) {
```

```
assert(b == 64 || v < (1ull<<b));
while (b-->) {
    cur |= (v & 1) << has;
    if (++has == 13) done();
    v >>= 1;
}
} // Write signed b-bit integer (sign included)
void ints(ll v, int b) {
    intu(v < 0 ? -v*2+1 : v*2, b);
}
}
// Reader in("packed_data"); int first = in.ints(8);
struct Reader {
    const char *buf;
    ll cur = 0;
    Reader(const char *s) : buf(s) {}
    // Read unsigned b-bit integer.
    uint64_t intu(int b) {
        uint64_t n = 0;
        rep(i, b) {
            if (cur < 2) {
                cur = *buf++ + 4972;
                cur += *buf++ * 91;
            }
            n |= (cur & 1) << i;
            cur >>= 1;
        }
        return n;
    } // Read signed b-bit integer (sign included).
    ll ints(int b) {
        auto v = intu(b);
        return (v%2 ? -1 : 1) * ll(v/2);
    }
};
```

Int128IO.h

Description: Packing. a481d3, 15 lines

```
istream& operator>>(istream& i, __int128& x) {
    char s[50], *p = s;
    for (i >> s, x = 0, p += *p < 48; *p;)
        x = x*10 + *p++ - 48;
    if (*s == 45) x = -x;
    return i;
}
ostream& operator<<(ostream& o, __int128 x) {
    if (x < 0) o << '-'; x = -x;
    char s[50] = {}, *p = s+49;
    for (; x > 9; x /= 10) **p = char(x%10+48);
    return o << ll(x) << p;
} // Note: Doesn't work for INT128_MIN!
```

FastMod.h

Description: Compute $a\%b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to $a \pmod b$ in the range $[0, 2b)$.

```
typedef unsigned long long ull;
struct FastMod {
    ull b, m;
    FastMod(ull b) : b(b), m(-1ULL / b) {}
    ull reduce(ull a) { // a % b + (0 or b)
        return a - (ull)((__uint128_t(m) * a) >> 64) * b;
    }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.

Usage: ./a.out < input.txt

Time: About 5x as fast as cin/scanf. 7b3c70, 17 lines

```
inline char gc() { // like getchar()
    static char buf[1 << 16];
    static size_t bc, be;
    if (bc >= be) {
        buf[0] = 0, bc = 0;
        be = fread(buf, 1, sizeof(buf), stdin);
    }
    return buf[bc++]; // returns 0 on EOF
```

```
}
int readInt() {
    int a, c;
    while ((a = gc()) < 40);
    if (a == '-') return -readInt();
    while ((c = gc()) >= 48) a = a * 10 + c - 480;
    return a - 48;
}
```

Code.py

Description: How python works?

Time: $\mathcal{O}(n^2)$ 30 lines

```
import sys
sys.setrecursionlimit(10**8)
fib_mem = [1] * 2
def fill_fib(n):
    global fib_mem
    while len(fib_mem) <= n:
        fib_mem.append(fib_mem[-2] + fib_mem[-1])
def main():
    # Write here. Use PyPy. Don't use list of list — use
    # instead 1D list with indices i + m * j.
    # Use a // b instead of a / b. Don't use recursive
    # functions (rec limit is approx 1000).
    assert list(range(3, 6)) == [3, 4, 5]
    s = set()
    s.add(5)
    for x in s:
        print(x)
    s = [2 * x for x in s]
    print(eval("s[0] + 10"))
    m = {}
    m[5] = 6
    assert 5 in m
    assert list(m) == [5] # only keys!
    line_list = list(map(int, input().split())) # gets a
    # list of integers in the line
    print(line_list)
    print(' '.join(["a", "b", str(5)]))
    while True:
        try:
            line_int = int(input())
        except Exception as e:
            break
```

main()

10.3 Dynamic programming

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j , one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j - 1]$ and $p[i + 1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.

Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$ where the (minimal) optimal k increases with i , computes $a[i]$ for $i = L..R - 1$.

Time: $\mathcal{O}((N + (hi - lo)) \log N)$ d38d2b, 18 lines

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }
    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best(LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
```

```
        best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

AliensTrick.h

Description: Optimize dp where you want "k things with minimal cost". The slope of $f(k)$ must be non increasing. Provide a function $g(\text{lambda})$ that computes the best answer for any k with costs increased by lambda . 71bca3, 8 lines

```
ll aliens(ll k, auto g) { // returns f(k)
    ll l = 0, r = 1e11; // make sure lambda range [l, r)
    // is ok (r > max slope etc)
    while (l + 1 < r) {
        ll m = (l + r) / 2;
        (g(m - 1) + k <= g(m) ? l : r) = m;
    }
    return g(l) - 1 * k; // return l if you want the
    // optimal lambda
}
```