

# Network Configuration Report

## Router Configurations

Explanation and details about router configurations.

### Router 1 Configurations

network: 172.168.1.0 0.0.0.31

network: 192.168.2.0 0.0.0.3

network: 192.168.10.1 0.0.0.255

network: 192.168.20.1 0.0.0.255

Interface: lo0, IP: 192.168.10.1 255.255.255.0

Interface: lo1, IP: 192.168.20.1 255.255.255.0

## Network Configuration Report

### Prompt for Router 1

Requirements: Strictly adhere to the following explicitly stated requirements; Write a simple Ansible playbook with separate tasks for each protocol and interface configurations with the following details; hosts: R1 Do not worry about the inventory file; Never provide explanations for the generated playbook; Do not use variables and templates to generate the playbooks; Ensure all generated playbooks adhere to yaml's rule of always starting a playbook with `---` and ending the playbook with a new line containing `...`; Always use ios\_config module and ensure unsupported parameters are not generated;; Use `parents` argument to implement stanzas; when configuring interfaces, ensure you generate codes for only provided interfaces and always implement 'No Shutdown' for each interface; when configuring routing protocols, ensure you generate codes for only provided protocols and that the protocol is initialized only under the parents argument using the format `router protocol-type xx`. Also, DO NOT configure router id; set `replace` argument to block. `replace` argument should always be child to `ios\_config`; Protocol: ospf OSPF Area: 1, Process ID: 1, Number of networks to advertise: 4 network1: 172.168.1.0 0.0.0.31 network2: 192.168.2.0 0.0.0.3 network3: 192.168.10.1 0.0.0.255 network4: 192.168.20.1 0.0.0.255 Interface: lo0, IP: 192.168.10.1 255.255.255.0 Interface: lo1, IP: 192.168.20.1 255.255.255.0

## Network Configuration Report

### Generated Playbook for Router 1

---

- hosts: R1

gather\_facts: no

tasks:

- name: Configure Loopback interface lo0

ios\_config:

parents: interface lo0

lines:

- ip address 192.168.10.1 255.255.255.0

- no shutdown

replace: block

- name: Configure Loopback interface lo1

ios\_config:

parents: interface lo1

lines:

- ip address 192.168.20.1 255.255.255.0

- no shutdown

replace: block

- name: Configure OSPF

ios\_config:

parents: router ospf 1

lines:

## Network Configuration Report

- network 172.168.1.0 0.0.0.31 area 1
- network 192.168.2.0 0.0.0.3 area 1
- network 192.168.10.1 0.0.0.255 area 1
- network 192.168.20.1 0.0.0.255 area 1

replace: block

...

### Router 2 Configurations

network: 192.168.2.0 0.0.0.3

network: 192.168.30.1 0.0.0.255

network: 192.168.4.0 0.0.0.3

network: 192.168.40.1 0.0.0.255

Interface: lo0, IP: 192.168.30.1 255.255.255.0

Interface: lo1, IP: 192.168.40.1 255.255.255.0

## Network Configuration Report

### Prompt for Router 2

Requirements: Strictly adhere to the following explicitly stated requirements; Write a simple Ansible playbook with separate tasks for each protocol and interface configurations with the following details; hosts: R2 Do not worry about the inventory file; Never provide explanations for the generated playbook; Do not use variables and templates to generate the playbooks; Ensure all generated playbooks adhere to yaml's rule of always starting a playbook with `---` and ending the playbook with a new line containing `...`; Always use ios\_config module and ensure unsupported parameters are not generated;; Use `parents` argument to implement stanzas; when configuring interfaces, ensure you generate codes for only provided interfaces and always implement 'No Shutdown' for each interface; when configuring routing protocols, ensure you generate codes for only provided protocols and that the protocol is initialized only under the parents argument using the format `router protocol-type xx`. Also, DO NOT configure router id; set `replace` argument to block. `replace` argument should always be child to `ios\_config`; Protocol: ospf OSPF Area: 1, Process ID: 1, Number of networks to advertise: 2 network1: 192.168.2.0 0.0.0.3 network2: 192.168.30.1 0.0.0.255 Protocol: eigrp EIGRP AS Number: 10, Number of networks to advertise: 2 network1: 192.168.4.0 0.0.0.3 network2: 192.168.40.1 0.0.0.255; Using dedicated tasks, Please redistribute the routing protocols using 'redistribute ospf 1 metric 1000 33 255 1 1500' for redistributing OSPF into EIGRP and 'redistribute eigrp 10 subnets' for redistributing EIGRP into OSPF; The redistribution tasks, should be generated after the routing protocol configuration tasks have been generated; Interface: lo0, IP: 192.168.30.1 255.255.255.0 Interface: lo1, IP: 192.168.40.1 255.255.255.0

## Network Configuration Report

### Generated Playbook for Router 2

---

- hosts: R2

gather\_facts: no

tasks:

- name: Configure lo0

ios\_config:

lines:

- description Loopback 0
- no shutdown
- ip address 192.168.30.1 255.255.255.0

parents: interface lo0

- name: Configure lo1

ios\_config:

lines:

- description Loopback 1
- no shutdown
- ip address 192.168.40.1 255.255.255.0

parents: interface lo1

- name: Configure OSPF

ios\_config:

lines:

## Network Configuration Report

- network 192.168.2.0 0.0.0.3 area 1
- network 192.168.30.1 0.0.0.255 area 1

parents: router ospf 1

replace: block

- name: Configure EIGRP

ios\_config:

lines:

- network 192.168.4.0 0.0.0.3
- network 192.168.40.1 0.0.0.255

parents: router eigrp 10

replace: block

- name: Redistribute OSPF into EIGRP

ios\_config:

lines:

- redistribute ospf 1 metric 1000 33 255 1 1500

parents: router eigrp 10

replace: block

- name: Redistribute EIGRP into OSPF

ios\_config:

lines:

- redistribute eigrp 10 subnets

parents: router ospf 1

replace: block

## Network Configuration Report

...

### Router 3 Configurations

network: 192.168.4.0 0.0.0.3

network: 192.168.50.1 0.0.0.255

network: 192.168.6.0 0.0.0.3

network: 192.168.60.1 0.0.0.255

Interface: lo0, IP: 192.168.50.1 255.255.255.0

Interface: lo1, IP: 192.168.60.1 255.255.255.0



## Network Configuration Report

### Prompt for Router 3

Requirements: Strictly adhere to the following explicitly stated requirements; Write a simple Ansible playbook with separate tasks for each protocol and interface configurations with the following details; hosts: R3 Do not worry about the inventory file; Never provide explanations for the generated playbook; Do not use variables and templates to generate the playbooks; Ensure all generated playbooks adhere to yaml's rule of always starting a playbook with `---` and ending the playbook with a new line containing `...`; Always use ios\_config module and ensure unsupported parameters are not generated;; Use `parents` argument to implement stanzas; when configuring interfaces, ensure you generate codes for only provided interfaces and always implement 'No Shutdown' for each interface; when configuring routing protocols, ensure you generate codes for only provided protocols and that the protocol is initialized only under the parents argument using the format `router protocol-type xx`. Also, DO NOT configure router id; set `replace` argument to block. `replace` argument should always be child to `ios\_config`; Protocol: eigrp EIGRP AS Number: 10, Number of networks to advertise: 2 network1: 192.168.4.0 0.0.0.3 network2: 192.168.50.1 0.0.0.255 Protocol: ospf OSPF Area: 100, Process ID: 1, Number of networks to advertise: 2 network1: 192.168.6.0 0.0.0.3 network2: 192.168.60.1 0.0.0.255; Using dedicated tasks, Please redistribute the routing protocols using 'redistribute ospf 1 metric 1000 33 255 1 1500' for redistributing OSPF into EIGRP and 'redistribute eigrp 10 subnets' for redistributing EIGRP into OSPF; The redistribution tasks, should be generated after the routing protocol configuration tasks have been generated; Interface: lo0, IP: 192.168.50.1 255.255.255.0 Interface: lo1, IP: 192.168.60.1 255.255.255.0

## Network Configuration Report

### Generated Playbook for Router 3

---

- name: Configure Router

hosts: R3

gather\_facts: no

tasks:

- name: Configure loopback interface lo0

ios\_config:

lines:

- ip address 192.168.50.1 255.255.255.0

- no shutdown

parents:

- interface lo0

replace: block

- name: Configure loopback interface lo1

ios\_config:

lines:

- ip address 192.168.60.1 255.255.255.0

- no shutdown

parents:

- interface lo1

replace: block

## Network Configuration Report

- name: Configure EIGRP

ios\_config:

lines:

- network 192.168.4.0 0.0.0.3
- network 192.168.50.1 0.0.0.255

parents:

- router eigrp 10

replace: block

- name: Configure OSPF

ios\_config:

lines:

- network 192.168.6.0 0.0.0.3 area 100
- network 192.168.60.1 0.0.0.255 area 100

parents:

- router ospf 1

replace: block

- name: Redistribute OSPF into EIGRP

ios\_config:

lines:

- redistribute ospf 1 metric 1000 33 255 1 1500

parents:

- router eigrp 10

replace: block

## Network Configuration Report

- name: Redistribute EIGRP into OSPF

ios\_config:

lines:

- redistribute eigrp 10 subnets

parents:

- router ospf 1

replace: block

...

### Router 4 Configurations

network: 192.168.6.0 0.0.0.3

network: 192.168.70.1 0.0.0.255

network: 192.168.80.1 0.0.0.255

Interface: lo0, IP: 192.168.70.1 255.255.255.0

Interface: lo1, IP: 192.168.80.1 255.255.255.0

## Network Configuration Report

### Prompt for Router 4

Requirements: Strictly adhere to the following explicitly stated requirements; Write a simple Ansible playbook with separate tasks for each protocol and interface configurations with the following details; hosts: R4 Do not worry about the inventory file; Never provide explanations for the generated playbook; Do not use variables and templates to generate the playbooks; Ensure all generated playbooks adhere to yaml's rule of always starting a playbook with `---` and ending the playbook with a new line containing `...`; Always use ios\_config module and ensure unsupported parameters are not generated;; Use `parents` argument to implement stanzas; when configuring interfaces, ensure you generate codes for only provided interfaces and always implement 'No Shutdown' for each interface; when configuring routing protocols, ensure you generate codes for only provided protocols and that the protocol is initialized only under the parents argument using the format `router protocol-type xx`. Also, DO NOT configure router id; set `replace` argument to block. `replace` argument should always be child to `ios\_config`; Protocol: ospf OSPF Area: 100, Process ID: 1, Number of networks to advertise: 3 network1: 192.168.6.0 0.0.0.3 network2: 192.168.70.1 0.0.0.255 network3: 192.168.80.1 0.0.0.255 Interface: lo0, IP: 192.168.70.1 255.255.255.0 Interface: lo1, IP: 192.168.80.1 255.255.255.0

## Network Configuration Report

### Generated Playbook for Router 4

---

- hosts: R4

gather\_facts: no

tasks:

- name: Configure loopback interface lo0

ios\_config:

lines:

- description lo0
- ip address 192.168.70.1 255.255.255.0
- no shutdown

parents: interface lo0

replace: block

- name: Configure loopback interface lo1

ios\_config:

lines:

- description lo1
- ip address 192.168.80.1 255.255.255.0
- no shutdown

parents: interface lo1

replace: block

- name: Configure ospf

ios\_config:

## Network Configuration Report

lines:

- network 192.168.6.0 0.0.0.3 area 100
- network 192.168.70.1 0.0.0.255 area 100
- network 192.168.80.1 0.0.0.255 area 100

parents: router ospf 1

replace: block

...