Chart record information

by Glen Stampoultzis

1. Introduction

This document is intended as a work in progress for describing our current understanding of how the chart records are are written to produce a valid chart.

2. Bar chart

The following records detail the records written for a 'simple' bar chart.

```
______
rectype = 0xec, recsize = 0xc8
-BEGIN DUMP-----
00000000 0F 00 02 F0 C0 00 00 10 00 08 F0 08 00 00 00 .......
00000010 02 00 00 00 02 04 00 00 0F 00 03 F0 A8 00 00 00 .........
00000020 0F 00 04 F0 28 00 00 00 01 00 09 F0 10 00 00 00 ....(.........
00000040 02 00 0A F0 08 00 00 00 04 00 00 05 00 00 00 .........
00000050 0F 00 04 F0 70 00 00 00 92 0C 0A F0 08 00 00 00 ....p........
00000070 7F 00 04 01 04 01 BF 00 08 00 08 00 81 01 4E 00 .......................
00000080 00 08 83 01 4D 00 00 08 BF 01 10 00 11 00 CO 01 ....M........
00000090 4D 00 00 08 FF 01 08 00 08 00 3F 02 00 00 02 00 M.....?....
000000A0 BF 03 00 00 08 00 00 10 F0 12 00 00 00 00 ........
000000B0 04 00 C0 02 0A 00 F4 00 0E 00 66 01 20 00 E9 00 ......f. ...
000000C0 00 00 11 F0 00 00 00 00
-END DUMP-----
recordid = 0 \times c, size = 200
[UNKNOWN RECORD:ec]
   .id = ec
[/UNKNOWN RECORD]
______
rectype = 0x5d, recsize = 0x1a
-BEGIN DUMP-----
00000000 15 00 12 00 05 00 02 00 11 60 00 00 00 08 03 ..........
00000010 87 03 00 00 00 00 00 00 00 00
-END DUMP-
recordid = 0x5d, size = 26
[UNKNOWN RECORD:5d]
```

```
id = 5d
[/UNKNOWN RECORD]
______
rectype = 0x809, recsize = 0x10
-BEGIN DUMP-
-END DUMP----
          ------
recordid = 0x809, size =16
[BOF RECORD]
  .version
             = 600
  .requiredversion = 106
[/BOF RECORD]
rectype = 0x14, recsize = 0x0
-BEGIN DUMP-
**NO RECORD DATA**
-END DUMP-----
recordid = 0x14, size =0
[HEADER]
  .length = 0
.header = null
[/HEADER]
rectype = 0x15, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP----
recordid = 0x15, size =0
[FOOTER]
  \begin{array}{ll} . \text{footerlen} & = 0 \\ . \text{footer} & = \text{null} \end{array}
[/FOOTER]
_____
rectype = 0x83, recsize = 0x2
-BEGIN DUMP-----
00000000 00 00
-END DUMP-----
recordid = 0x83, size =2
[HCENTER]
  .hcenter = false
[/HCENTER]
_____
rectype = 0x84, recsize = 0x2
-BEGIN DUMP-----
0000000 00 00
```

```
-END DUMP-----
recordid = 0x84, size =2
[VCENTER]
   .vcenter = false
[/VCENTER]
_____
rectype = 0xa1, recsize = 0x22
-BEGIN DUMP-----
00000000 00 00 12 00 01 00 01 00 01 00 04 00 00 B8 03 .......
00000010 00 00 00 00 00 00 E0 3F 00 00 00 00 00 E0 3F .....?.....?
00000020 OF 00
-END DUMP---
recordid = 0xa1, size =34
[PRINTSETUP]
               = 0
   .papersize
   .scale
               = 18
  = 1
...twidth = 1
.fitheight = 1
.options = 4
.ltor = f
                = false
      .landscape = false
.valid = true
.mono = false
      .draft = false
.notes = false
      .noOrientat = false
   .usepage = false
.hresolution = 0
.vresolution = 952
   .headermargin = 0.5
   .footermargin = 0.5
               = 15
   .copies
[/PRINTSETUP]
______
rectype = 0x33, recsize = 0x2
-BEGIN DUMP-----
00000000 03 00
-END DUMP--
recordid = 0x33, size =2
[UNKNOWN RECORD:33]
   .id
[/UNKNOWN RECORD]
_____
rectype = 0x1060, recsize = 0xa
-BEGIN DUMP-----
00000000 A0 23 08 16 C8 00 00 00 05 00
                                                .#......
-END DUMP-----
recordid = 0x1060, size =10
[FBI]
```

```
.xBasis
                 = 0x23A0 (9120)
   .yBasis
                   = 0x1608 (5640)
   .heightBasis
                   = 0 \times 00008 (200)
                    = 0 \times 0000 (0)
   .scale
   .indexToFontTable
                   = 0 \times 0005 (5)
[/FBI]
______
rectype = 0x1060, recsize = 0xa
-BEGIN DUMP-----
00000000 A0 23 08 16 C8 00 01 00 06 00
                                              .#......
-END DUMP--
recordid = 0x1060, size =10
[FBI]
                     = 0x23A0 (9120)
   .xBasis
   .yBasis
                    = 0x1608 (5640)
   .heightBasis
                   = 0 \times 00008 (200)
   .scale
                    = 0 \times 0001 (1)
   .indexToFontTable
                   = 0 \times 0006 (6)
[/FBI]
_____
rectype = 0x12, recsize = 0x2
-BEGIN DUMP-----
00000000 00 00
-END DUMP-----
recordid = 0x12, size =2
[PROTECT]
   .rowheight = 0
[/PROTECT]
_____
Offset 0xf22 (3874)
rectype = 0x1001, recsize = 0x2
-BEGIN DUMP-----
00000000 00 00
-END DUMP-----
recordid = 0x1001, size =2
[UNITS]
   .units
                   = 0 \times 0000 (0)
[/UNITS]
______
Offset 0xf28 (3880)
rectype = 0x1002, recsize = 0x10
-BEGIN DUMP-----
00000000 00 00 00 00 00 00 00 00 58 66 D0 01 40 66 22 01 .........xf..@f".
-END DUMP--
recordid = 0x1002, size =16
[CHART]
                     = 0 \times 00000000 (0)
   .x
                     = 0 \times 00000000 (0)
   •У
                     = 0 \times 01 D06658 (30434904)
   .width
                   = 0 \times 01226640 (19031616)
   .height
```

```
[/CHART]
_____
Offset 0xf3c (3900)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0xf40 (3904)
rectype = 0xa0, recsize = 0x4
-BEGIN DUMP-----
00000000 01 00 01 00
-END DUMP-----
recordid = 0xa0, size =4
                   = 0x0001 (1)
   .numerator
   .denominator
                  = 0 \times 0001 (1)
[/SCL]
_____
Offset 0xf48 (3912)
rectype = 0x1064, recsize = 0x8
-BEGIN DUMP-----
00000000 00 00 01 00 00 00 01 00
                                           . . . . . . . .
-END DUMP-----
recordid = 0x1064, size =8
[PLOTGROWTH]
   .horizontalScale = 0x00010000 (65536 )
.verticalScale = 0x00010000 (65536 )
[/PLOTGROWTH]
______
Offset 0xf54 (3924)
rectype = 0x1032, recsize = 0x4
-BEGIN DUMP-----
00000000 00 00 02 00
                                           . . . .
-END DUMP-----
recordid = 0x1032, size =4
[FRAME]
      derType = 0x0000 (0)
ions = 0x0002 (2)
.autoSize = fa
   .borderType
   .options
                        = false
      .autoPosition
                          = true
[/FRAME]
_____
Offset 0xf5c (3932)
rectype = 0x1033, recsize = 0x0
```

```
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
______
Offset 0xf60 (3936)
rectype = 0x1007, recsize = 0xc
-BEGIN DUMP-----
00000000 00 00 00 00 00 00 FF FF 09 00 4D 00
                                           ....M.
-END DUMP--
recordid = 0x1007, size =12
[LINEFORMAT]
                   = 0 \times 000000000 (0)
   .lineColor
                  = 0 \times 0000 (0)
   .linePattern
  .weight
                   = 0xFFFF (-1)
                   = 0 \times 0009 (9)
   .format
      .auto
                          = true
      .drawTicks
                          = false
      .unknown
                          = false
   .colourPaletteIndex = 0 \times 0.04D (77)
[/LINEFORMAT]
_____
Offset 0xf70 (3952)
rectype = 0x100a, recsize = 0x10
-BEGIN DUMP-----
-END DUMP-----
recordid = 0x100a, size =16
[AREAFORMAT]
   .foregroundColor = 0x00FFFFFFF (16777215)
.backgroundColor = 0x00000000 (0)
.pattern = 0x0001 (1)
.formatFlags = 0x0001 (1)
      .automatic
                          = true
                          = false
       .invert
   .forecolorIndex
                  = 0 \times 004 E (78)
   .backcolorIndex
                  = 0 \times 004 D (77)
[/AREAFORMAT]
Offset 0xf84 (3972)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
______
```

```
Offset 0xf88 (3976)
rectype = 0x1003, recsize = 0xc
-BEGIN DUMP-----
00000000 01 00 01 00 20 00 1F 00 01 00 00 00
-END DUMP--
recordid = 0x1003, size =12
[SERIES]
   .categoryDataType = 0x0001 (1 )
.valuesDataType = 0x0001 (1 )
.numCategories = 0x0020 (32 )
.numValues = 0x001F (31 )
.bubbleSeriesType = 0x0001 (1 )
.numBubbleValues = 0x0000 (0 )
[/SERIES]
______
Offset 0xf98 (3992)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP--
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
______
Offset 0xf9c (3996)
rectype = 0x1051, recsize = 0x8
-BEGIN DUMP-----
00000000 00 01 00 00 00 00 00 00
-END DUMP-----
recordid = 0x1051, size =8
[AI]
   .linkType - 0x01 (1)

.referenceType = 0x01 (1)

= 0x0000 (0)
   .linkType
                      = 0x00 (0)
       .customNumberFormat = false
   .indexNumberFmtRecord = 0x0000 (0 )
                   = (org.apache.poi.hssf.record.LinkedDataFormulaField@1ee
   .formulaOfLink
[/AI]
______
Offset Oxfa8 (4008)
rectype = 0x1051, recsize = 0x13
-BEGIN DUMP-----
00000000 01 02 00 00 00 00 0B 00 3B 00 00 00 1E 00 01 .....;.....
00000010 00 01 00
-END DUMP-----
recordid = 0x1051, size =19
[AI]
   .linkType
                       = 0x01 (1)
                      = 0x02 (2)
   .referenceType
                     = 0 \times 0000 (0)
   .options
```

```
.customNumberFormat = false
   .indexNumberFmtRecord = 0x0000 (0)
   .formulaOfLink = (org.apache.poi.hssf.record.LinkedDataFormulaField@e58
[/AI]
______
Offset Oxfbf (4031)
rectype = 0x1051, recsize = 0x13
-BEGIN DUMP-----
00000000 02 02 00 00 69 01 0B 00 3B 00 00 00 1F 00 00 ....i...;.....
00000010 00 00 00
-END DUMP--
recordid = 0x1051, size =19
[AI]
   .linkType
                      = 0x02 (2)
                      = 0x02 (2)
   .referenceType
   .options
                      = 0 \times 0000 (0)
       .customNumberFormat
                          = false
   .indexNumberFmtRecord = 0x0169 (361 )
   .formulaOfLink = (org.apache.poi.hssf.record.LinkedDataFormulaField@95f
[/AI]
______
Offset 0xfd6 (4054)
rectype = 0x1051, recsize = 0x8
-BEGIN DUMP----
00000000 03 01 00 00 00 00 00 00
                                                  . . . . . . . .
-END DUMP--
recordid = 0x1051, size =8
[AI]
                      = 0x03 (3)
   .linkType
                     = 0x01 (1)
   .referenceType
                     = 0 \times 0000 (0)
        .customNumberFormat
                          = false
   .indexNumberFmtRecord = 0x0000 (0)
                  = (org.apache.poi.hssf.record.LinkedDataFormulaField@11b
   .formulaOfLink
[/AI]
______
Offset Oxfe2 (4066)
rectype = 0x1006, recsize = 0x8
-BEGIN DUMP--
00000000 FF FF 00 00 00 00 00 00
-END DUMP-----
recordid = 0x1006, size =8
[DATAFORMAT]
   .pointNumber
                     = 0 \times FFFF (-1)
   .seriesIndex
                     = 0 \times 0000 (0)
   .seriesNumber = 0x0000 (0 )
.seriesNumber = 0x0000 (0 )
= fa
       .useExcel4Colors
                              = false
[/DATAFORMAT]
______
```

```
Offset Oxfee (4078)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset Oxff2 (4082)
rectype = 0x105f, recsize = 0x2
-BEGIN DUMP-----
00000000 00 00
-END DUMP-----
recordid = 0x105f, size =2
[UNKNOWN RECORD]
  .id = 105f
[/UNKNOWN RECORD]
_____
Offset 0xff8 (4088)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
                  -----
recordid = 0x1034, size =0
[END]
[/END]
______
Offset Oxffc (4092)
rectype = 0x1045, recsize = 0x2
-BEGIN DUMP-
00000000 00 00
-END DUMP-----
recordid = 0x1045, size =2
[SeriesToChartGroup]
  .chartGroupIndex
                 = 0 \times 0000 (0)
[/SeriesToChartGroup]
______
Offset 0x1002 (4098)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP----
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x1006 (4102)
rectype = 0x1044, recsize = 0x4
```

```
-BEGIN DUMP-----
00 00 00 A0 0000000
-END DUMP-----
recordid = 0x1044, size =4
[SHTPROPS]
   .flags
                      = 0x000A (10)
        .chartTypeManuallyFormatted = false
        .plotVisibleOnly = true
.doNotSizeWithWindow = false
.defaultPlotDimonsions = true
        .defaultPlotDimensions
                              = true
        .autoPlotArea
                              = false
                 = 0 \times 00 (0)
   .empty
[/SHTPROPS]
_____
Offset 0x100e (4110)
rectype = 0x1024, recsize = 0x2
-BEGIN DUMP-----
00000000 02 00
-END DUMP-----
recordid = 0x1024, size =2
[DEFAULTTEXT]
   .categoryDataType = 0x0002 (2)
[/DEFAULTTEXT]
_____
Offset 0x1014 (4116)
rectype = 0x1025, recsize = 0x20
-BEGIN DUMP-----
00000000 02 02 01 00 00 00 00 DB FF FF FF C4 FF FF FF .......
-END DUMP----
recordid = 0x1025, size = 32
[TEXT]
   .horizontalAlignment = 0x02 (2)
   .verticalAlignment = 0x02(2)
.displayMode = 0x0001(1)
   .displayMode = 0x0001 (1 )
.rgbColor = 0x00000000 (0 )
- 0xFFFFFFDB (-37
       ght = 0x00000000 (0 )

= 0x00000000 (0 )

= 0x00000000 (0 )

= 0x00000000 (177 )

autoColor

.showKey
                     = 0xFFFFFFDB (-37)
   .x
   •У
                     = 0 \times FFFFFFC4 (-60)
   .width
   .height
   .options1
                              = false
        .showValue
                              = false
        .vertical
        .autoGeneratedText
                             = true
        .generated
                              = true
                             = false
        .autoLabelDeleted
        .autoBackground
                              = true
        .rotation
        .showCategoryLabelAsPercentage
                                     = false
       .showValueAsPercentage = false
```

```
.showBubbleSizes = false
.showLabel = false
   .showLabel = false
.indexOfColorValue = 0x004D (77 )
.options2 = 0x2B50 (11088 )
      .dataLabelPlacement = 0
   .textRotation = 0x0000 (0)
[/TEXT]
_____
Offset 0x1038 (4152)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
______
Offset 0x103c (4156)
rectype = 0x104f, recsize = 0x14
-BEGIN DUMP-----
00000010 00 00 00 00
-END DUMP--
                 ______
recordid = 0x104f, size =20
[UNKNOWN RECORD]
   .id = 104f
[/UNKNOWN RECORD]
_____
Offset 0x1054 (4180)
rectype = 0x1026, recsize = 0x2
-BEGIN DUMP-----
00000000 05 00
-END DUMP-----
recordid = 0x1026, size =2
[FONTX]
            = 0 \times 0005 (5)
  .fontIndex
[/FONTX]
______
Offset 0x105a (4186)
rectype = 0x1051, recsize = 0x8
-BEGIN DUMP-----
00000000 00 01 00 00 00 00 00 00
-END DUMP---
recordid = 0x1051, size =8
[AI]
   .linkType = 0x00 (0)
.referenceType = 0x01 (1)
.options = 0x0000 (0)
   .linkType
   .customNumberFormat = false
```

```
.indexNumberFmtRecord = 0x0000 (0)
   .formulaOfLink = (org.apache.poi.hssf.record.LinkedDataFormulaField@913
[/AI]
______
Offset 0x1066 (4198)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x106a (4202)
rectype = 0x1024, recsize = 0x2
-BEGIN DUMP-----
00000000 03 00
-END DUMP-----
recordid = 0x1024, size =2
[DEFAULTTEXT]
   .categoryDataType = 0x0003 (3)
[/DEFAULTTEXT]
_____
Offset 0x1070 (4208)
rectype = 0x1025, recsize = 0x20
-BEGIN DUMP-----
00000000 02 02 01 00 00 00 00 00 DB FF FF FF C4 FF FF FF ........
-END DUMP----
recordid = 0x1025, size = 32
[TEXT]
   .horizontalAlignment = 0x02 (2)
   .verticalAlignment = 0x02(2)
.displayMode = 0x0001(1)
   .displayMode = 0x0001 (1 )
.rgbColor = 0x00000000 (0 )
                   = 0xFFFFFFDB (-37)
   .X
                   = 0 \times FFFFFFC4 (-60)
   •У
   .width
                   = 0 \times 00000000 (0)
                   = 0 \times 00000000 (0)
   .height
   .options1
                   = 0x00B1 (177)
       .autoColor
                           = true
                           = false
       .showKey
                           = false
       .showValue
                           = false
       .vertical
       .autoGeneratedText
                          = true
       .generated
                          = true
                          = false
       .autoLabelDeleted
                           = true
       .autoBackground
       .rotation
       .showCategoryLabelAsPercentage
                                 = false
      .showValueAsPercentage = false
```

```
.showBubbleSizes = false
   .showLabel = false
.indexOfColorValue = 0x004D (77 )
options2 = 0x2B50 (11088 )
      .dataLabelPlacement = 0
   .textRotation = 0x0000 (0)
[/TEXT]
_____
Offset 0x1094 (4244)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
______
Offset 0x1098 (4248)
rectype = 0x104f, recsize = 0x14
-BEGIN DUMP----
00000010 00 00 00 00
-END DUMP-----
recordid = 0x104f, size = 20
[UNKNOWN RECORD]
   .id
           = 104f
[/UNKNOWN RECORD]
______
Offset 0x10b0 (4272)
rectype = 0x1026, recsize = 0x2
-BEGIN DUMP--
00000000 06 00
-END DUMP-----
recordid = 0x1026, size =2
[FONTX]
   .fontIndex
                   = 0 \times 0006 (6)
[/FONTX]
______
Offset 0x10b6 (4278)
rectype = 0x1051, recsize = 0x8
-BEGIN DUMP-----
00000000 00 01 00 00 00 00 00 00
                                            . . . . . . . .
-END DUMP----
recordid = 0x1051, size =8
[AI]
                   = 0x00 (0)
   .linkType
   .referenceType = 0x01 (1)
.options = 0x0000 (0)
      .customNumberFormat = false
   .indexNumberFmtRecord = 0 \times 0000 (0 )
```

```
.formulaOfLink = (org.apache.poi.hssf.record.LinkedDataFormulaField@1f9
[/AI]
______
Offset 0x10c2 (4290)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x10c6 (4294)
rectype = 0x1046, recsize = 0x2
-BEGIN DUMP-----
00000000 01 00
-END DUMP---
recordid = 0x1046, size =2
[AXISUSED]
  .numAxis
                 = 0 \times 0001 (1)
[/AXISUSED]
______
Offset 0x10cc (4300)
rectype = 0x1041, recsize = 0x12
-BEGIN DUMP---
00000010 00 00
-END DUMP-----
recordid = 0x1041, size =18
[AXISPARENT]
                 = 0 \times 0000 (0)
  .axisType
  .x
                 = 0 \times 000001 DF (479)
  •У
                 = 0 \times 000000DD (221)
                 = 0x00000BB3 (2995)
   .width
   .height
                 = 0x00000B56 (2902)
[/AXISPARENT]
_____
Offset 0x10e2 (4322)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x10e6 (4326)
rectype = 0x104f, recsize = 0x14
-BEGIN DUMP-----
```

```
00000000 02 00 02 00 3A 00 00 05 5E 00 00 00 58 0D 00 00 ....:...^...X...
00000010 E5 0E 00 00
-END DUMP-----
recordid = 0x104f, size =20
[UNKNOWN RECORD]
  .id = 104f
[/UNKNOWN RECORD]
______
Offset 0x10fe (4350)
rectype = 0x101d, recsize = 0x12
-BEGIN DUMP---
00000010 00 00
-END DUMP-----
recordid = 0x101d, size =18
[AXIS]
   .axisType
                    = 0 \times 0000 (0)
   .reserved1
.reserved2
.reserved3
.reserved4
                    = 0 \times 00000000 (0)
                    = 0 \times 00000000 (0)
                     = 0 \times 00000000 (0)
                     = 0 \times 00000000 (0)
[/AXIS]
_____
Offset 0x1114 (4372)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x1118 (4376)
rectype = 0x1020, recsize = 0x8
-BEGIN DUMP-----
00000000 01 00 01 00 01 00 01 00
-END DUMP-
recordid = 0x1020, size =8
[CATSERRANGE]
   .crossingPoint = 0x0001 (1 )
.labelFrequency = 0x0001 (1 )
.tickMarkFrequency = 0x0001 (1 )
.options = 0x0001 (1 )
       .valueAxisCrossing = true
.crossesFarRight = false
       .reversed
                            = false
[/CATSERRANGE]
_____
Offset 0x1124 (4388)
rectype = 0x1062, recsize = 0x12
```

```
-BEGIN DUMP-----
00000000 1C 90 39 90 02 00 00 00 01 00 00 00 00 1C 90 ..9.......
00000010 FF 00
-END DUMP-----
recordid = 0x1062, size =18
[AXCEXT]
   .minorUnit = 0x0000 (0 )
.baseUnit = 0x0000 (0 )
.crossingPoint = 0x901C (-28644 )
.options = 0x00FF (255 )
.defaultMinimum = true
       .defaultMaximum
                             = true
        .defaultMajor
                             = true
        .defaultMinorUnit
                             = true
        .isDate
                              = true
        .defaultBase
        .defaultCross
        .defaultDateSettings
                              = true
[/AXCEXT]
_____
Offset 0x113a (4410)
rectype = 0x101e, recsize = 0x1e
-BEGIN DUMP------
00000010 00 00 00 00 00 00 00 23 00 4D 00 2D 00 .....#.M.-.
-END DUMP----
recordid = 0x101e, size = 30
[TICK]
   .majorTickType = 0x02 (2 )

.minorTickType = 0x00 (0 )

.labelPosition = 0x03 (3 )

.background = 0x01 (1 )
   .labelColorRgb
                     = 0 \times 00000000 (0)
   .zero1
.zero2
                     = 0 \times 0000 (0)
   .2e102
.options
       autoTextColor autoTextD
                     = 0 \times 0000 (0)
       .autoTextBackground = true
.rotation = 0
.autorotate
       .rotation = 0
.autorotate = true
   .tickColor
                     = 0 \times 004 D (77)
                     = 0 \times 002D (45)
   .zero3
[/TICK]
_____
Offset 0x115c (4444)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
```

```
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x1160 (4448)
rectype = 0x101d, recsize = 0x12
-BEGIN DUMP-----
00000010 00 00
-END DUMP----
recordid = 0x101d, size =18
[AXIS]
  .reserved1
.reserved2
.reserved3
.reserved4
   .axisType
                    = 0 \times 0001 (1)
                    = 0 \times 000000000 (0)
                    = 0 \times 00000000 (0)
                   = 0 \times 00000000 (0)
                    = 0 \times 00000000 (0)
[/AXIS]
______
Offset 0x1176 (4470)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x117a (4474)
rectype = 0x101f, recsize = 0x2a
-BEGIN DUMP----
00000020 00 00 00 00 00 00 00 1F 01
-END DUMP-
recordid = 0 \times 101 f, size = 42
[VALUERANGE]
   .minimumAxisValue = (0.0)
.maximumAxisValue = (0.0)
.majorIncrement = (0.0)
.minorIncrement = (0.0)
.categoryAxisCross = (0.0)
.options = 0x011F (287)
       .automaticMinimum = true
       .automaticMaximum
.automaticMajor
.automaticMinor
                           = true
                            = true
                            = true
       .automaticCategoryCrossing = true
```

```
.crossCategoryAxisAtMaximum = false
       .reserved
                  = true
[/VALUERANGE]
_____
Offset 0x11a8 (4520)
rectype = 0x101e, recsize = 0x1e
-BEGIN DUMP-----
00000010 00 00 00 00 00 00 00 00 23 00 4D 00 00 00 .....#.M...
-END DUMP--
recordid = 0x101e, size = 30
[TICK]
  .zero1
.zero2
.options
                   = 0 \times 0000 (0)
                   = 0 \times 0000 (0)
                   = 0 \times 0023 (35)
      .autoTextColor
                          = true
      .autoTextBackground
                         = true
      .rotation
                         = 0
   .autorotate = true
.tickColor = 0x004D (77 )
                          = true
   .zero3
                   = 0 \times 0000 (0)
[/TICK]
_____
Offset 0x11ca (4554)
rectype = 0x1021, recsize = 0x2
-BEGIN DUMP-----
00000000 01 00
                                           . .
-END DUMP-----
recordid = 0x1021, size =2
recordid - UAIULI.
[AXISLINEFORMAT] = 0x0001 (1 )
[/AXISLINEFORMAT]
______
Offset 0x11d0 (4560)
rectype = 0x1007, recsize = 0xc
-BEGIN DUMP-----
00000000 00 00 00 00 00 FF FF 09 00 4D 00
                                           . . . . . . . . . . . M .
recordid = 0x1007, size =12
[LINEFORMAT]
                   = 0 \times 00000000 (0)
  .lineColor
   .linePattern
.weight
                   = 0 \times 0000 (0)
                   = 0 \times FFFF (-1)
                  = 0 \times 0009 (9)
  .format
```

```
.auto
                        = true
      .drawTicks
                        = false
      .unknown
                        = false
   .colourPaletteIndex = 0x004D (77)
[/LINEFORMAT]
_____
Offset 0x11e0 (4576)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP--
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x11e4 (4580)
rectype = 0x1035, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1035, size =0
[PLOTAREA]
[/PLOTAREA]
_____
Offset 0x11e8 (4584)
rectype = 0x1032, recsize = 0x4
-BEGIN DUMP-----
00000000 00 00 03 00
-END DUMP-----
recordid = 0x1032, size =4
[FRAME]
  .borderType
                = 0 \times 0000 (0)
              = 0 \times 0003 (3)
  .options
      .autoSize
                        = true
      .autoPosition
                        = true
[/FRAME]
_____
Offset 0x11f0 (4592)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x11f4 (4596)
rectype = 0x1007, recsize = 0xc
-BEGIN DUMP-----
```

```
00000000 80 80 80 00 00 00 00 00 00 17 00
-END DUMP-----
recordid = 0x1007, size =12
[LINEFORMAT]
                     = 0 \times 00808080  (8421504)
   .lineColor
                    = 0 \times 0000 (0)
= 0 \times 0000 (0)
   .linePattern
   .weight
                     = 0 \times 0000 (0)
   .format
       .auto
                             = false
       .drawTicks
                             = false
       .unknown
                             = false
   .colourPaletteIndex = 0x0017 (23)
[/LINEFORMAT]
_____
Offset 0x1204 (4612)
rectype = 0x100a, recsize = 0x10
-BEGIN DUMP-----
00000000 C0 C0 C0 00 00 00 00 00 01 00 00 16 00 4F 00 .............
-END DUMP---
recordid = 0x100a, size =16
[AREAFORMAT]
   .foregroundColor = 0x00C0C0C0 (12632256 )
.backgroundColor = 0x00000000 (0 )
.pattern = 0x0001 (1 )
.formatFlags = 0x0000 (0 )
.automatic = false
       .invert
                             = false
   .forecolorIndex = 0x0016 (22)
.backcolorIndex = 0x004F (79)
[/AREAFORMAT]
_____
Offset 0x1218 (4632)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
______
Offset 0x121c (4636)
rectype = 0x1014, recsize = 0x14
-BEGIN DUMP-----
00000010 00 00 00 00
-END DUMP-----
recordid = 0x1014, size = 20
[CHARTFORMAT]
   .xPosition
                 = 0
                 = 0
   .yPosition
  .width
               = 0
```

```
= 0
   .height
                = 0
   .arBit
[/CHARTFORMAT]
______
Offset 0x1234 (4660)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x1238 (4664)
rectype = 0x1017, recsize = 0x6
-BEGIN DUMP-----
00000000 00 00 96 00 00 00
                                                . . . . . .
-END DUMP--
recordid = 0x1017, size =6
[BAR]
   .barSpace = UXUUUU (U /
.categorySpace = 0x0096 (150 )
.formatFlags = 0x0000 (0 )
= fals
                     = 0x0000 (0)
       .horizontal
                             = false
                            = false
       .stacked
       .displayAsPercentage = false
       .shadow
                             = false
[/BAR]
_____
Offset 0x1242 (4674)
rectype = 0x1022, recsize = 0xa
-BEGIN DUMP-----
00000000 00 00 00 00 00 00 00 0F 00
                                                . . . . . . . . . .
-END DUMP-----
recordid = 0x1022, size =10
[UNKNOWN RECORD]
   .id = 1022
[/UNKNOWN RECORD]
______
Offset 0x1250 (4688)
rectype = 0x1015, recsize = 0x14
-BEGIN DUMP-----
00000000 D6 0D 00 00 1E 06 00 00 B5 01 00 00 D5 00 00 00 ........
00000010 03 01 1F 00
-END DUMP-----
recordid = 0x1015, size = 20
[LEGEND]
   .xAxisUpperLeft = 0x00000DD6 (3542 )

.yAxisUpperLeft = 0x0000061E (1566 )

.xSize = 0x000001B5 (437 )
  .xSize
```

```
.ySize
                     = 0 \times 00000005 (213)
                    = 0x03 (3)
   .type
   .spacing
                    = 0x01 (1)
                    = 0 \times 001 F (31)
   .options
       .autoPosition
                           = true
       .autoSeries
                            = true
       .autoXPositioning
                            = true
                           = true
       .autoYPositioning
       .vertical
                            = true
       .dataTable
                            = false
[/LEGEND]
_____
Offset 0x1268 (4712)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
______
Offset 0x126c (4716)
rectype = 0x104f, recsize = 0x14
-BEGIN DUMP-----
00000000 05 00 02 00 D6 0D 00 00 1E 06 00 00 00 00 00 00 ........
00000010 00 00 00 00
-END DUMP-----
recordid = 0x104f, size =20
[UNKNOWN RECORD]
   .id
           = 104f
[/UNKNOWN RECORD]
_____
Offset 0x1284 (4740)
rectype = 0x1025, recsize = 0x20
-BEGIN DUMP-----
00000000 02 02 01 00 00 00 00 DB FF FF FF C4 FF FF FF .......
-END DUMP-
recordid = 0x1025, size = 32
[TEXT]
   .horizontalAlignment = 0x02 (2)
   .verticalAlignment = 0x02 (2 )
.displayMode = 0x0001 (1 )
   .displayMode
                    = 0 \times 000000000 (0)
   .rgbColor
                    = 0xFFFFFDB (-37)
   .X
                    = 0 \times FFFFFFC4 (-60)
   •У
   .width
                    = 0 \times 00000000 (0)
                    = 0 \times 00000000 (0)
   .height
   .options1
                    = 0 \times 00B1 (177)
       .autoColor
                            = true
                            = false
       .showKey
```

```
= false
       .showValue
                         = false
      .vertical
                         = true
      .autoGeneratedText
       .generated
                          = true
                         = false
       .autoLabelDeleted
       .autoBackground
                          = true
       .rotation
       .showCategoryLabelAsPercentage
                                = false
       .showValueAsPercentage = false
       .showBubbleSizes
                          = false
       .showLabel
                          = false
   .indexOfColorValue = 0x004D (77 )
.options2 = 0x3770 (14192 )
      .dataLabelPlacement = 0
   .textRotation = 0x0000 (0)
[/TEXT]
_____
Offset 0x12a8 (4776)
rectype = 0x1033, recsize = 0x0
-BEGIN DUMP--
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1033, size =0
[BEGIN]
[/BEGIN]
_____
Offset 0x12ac (4780)
rectype = 0x104f, recsize = 0x14
-BEGIN DUMP-----
00000010 00 00 00 00
-END DUMP--
recordid = 0x104f, size =20
[UNKNOWN RECORD]
   .id
           = 104f
[/UNKNOWN RECORD]
_____
Offset 0x12c4 (4804)
rectype = 0x1051, recsize = 0x8
-BEGIN DUMP-----
00000000 00 01 00 00 00 00 00 00
                                            . . . . . . . .
-END DUMP-----
recordid = 0x1051, size =8
[AI]
   .linkType
                   = 0x00 (0)
   .referenceType
                  = 0x01 (1)
   .options
                  = 0 \times 0000 (0)
      .customNumberFormat = false
   .indexNumberFmtRecord = 0x0000 (0)
   .formulaOfLink = (org.apache.poi.hssf.record.LinkedDataFormulaField@1d0
[/AI]
```

```
_____
Offset 0x12d0 (4816)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP---
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x12d4 (4820)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
______
Offset 0x12d8 (4824)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP---
recordid = 0x1034, size =0
[END]
[/END]
_____
Offset 0x12dc (4828)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP----
**NO RECORD DATA**
-END DUMP-----
recordid = 0x1034, size =0
[END]
[/END]
______
Offset 0x12e0 (4832)
rectype = 0x1034, recsize = 0x0
-BEGIN DUMP----
**NO RECORD DATA**
-END DUMP----
                 ______
recordid = 0x1034, size =0
[END]
[/END]
______
rectype = 0x200, recsize = 0xe
```

```
-BEGIN DUMP-----
00000000 00 00 00 1F 00 00 00 00 01 00 00 00 ......
-END DUMP-----
recordid = 0x200, size =14
[DIMENSIONS]
   .firstrow
            = 1f
   .lastrow
            = 0
   .firstcol
  .lastcol
            = 1
            = 0
   .zero
[/DIMENSIONS]
_____
rectype = 0x1065, recsize = 0x2
-BEGIN DUMP-----
00000000 02 00
-END DUMP-----
recordid = 0x1065, size =2
[SINDEX]
  .index
                 = 0 \times 0002 (2)
[/SINDEX]
______
rectype = 0x1065, recsize = 0x2
-BEGIN DUMP-----
00000000 01 00
-END DUMP--
recordid = 0x1065, size =2
[SINDEX]
   .index
                = 0 \times 0001 (1)
[/SINDEX]
_____
rectype = 0x1065, recsize = 0x2
-BEGIN DUMP-----
00000000 03 00
                                       . .
-END DUMP-----
recordid = 0x1065, size =2
[SINDEX]
                 = 0 \times 0003 (3)
  .index
[/SINDEX]
______
rectype = 0xa, recsize = 0x0
-BEGIN DUMP-----
**NO RECORD DATA**
-END DUMP----
recordid = 0xa, size =0
[EOF]
[/EOF]
```

The next section breaks those records down into an easier to read format:

```
[UNKNOWN RECORD:ec]
[UNKNOWN RECORD:5d]
[BOF RECORD]
    [HEADER]
    [FOOTER]
    [HCENTER]
    [VCENTER]
    [PRINTSETUP]
    [UNKNOWN RECORD:33]
    [FBI]
    [FBI]
    [PROTECT]
    [UNITS]
    [CHART]
    [BEGIN]
                               // zoom magnification
        [SCL]
        [PLOTGROWTH]
                               // font scaling
                               // border around text
        [FRAME]
        [BEGIN]
                               // default line and area format
            [LINEFORMAT]
            [AREAFORMAT]
        [END]
        [SERIES]
                               // start of series
        [BEGIN]
            [AI]
                               // LINK_TYPE_TITLE_OR_TEXT
                               // LINK_TYPE_VALUES
// LINK_TYPE_CATEGORIES
            [AI]
            [AI]
                               // ??
// Formatting applies to series?
            [AI]
            [DATAFORMAT]
                               // ??
            [BEGIN]
                 [UNKNOWN RECORD]
            [SeriesToChartGroup] // Used to support > 1 chart?
        [END]
        [SHTPROPS]
                               // Some defaults for how chart is displayed.
        [DEFAULTTEXT]
                               // Describes the characteristics of the next
                               // record
                               // Details of the text that follows in the
        [TEXT]
                               // next section
        [BEGIN]
            [UNKNOWN RECORD] // POS record... looks like I missed this one.
                               // docs seem to indicate it's better to use
                               // defaults...
// index to font record.
            [FONTX]
                               // link to text? seems to be linking to nothing
            [AI]
        [END]
        [DEFAULTTEXT]
                               // contains a category type of 3 which is not
                               // documented (sigh).
        [TEXT]
                               // defines position, color etc for text on chart.
        [BEGIN]
            [UNKNOWN RECORD] // Another pos record
```

```
[FONTX]
                              // font
                              // reference type is DIRECT (not sure what this
            [AI]
                               // means)
        [END]
        [AXISUSED]
                               // number of axis on the chart.
                              // axis size and location
// beginning of axis details
        [AXISPARENT]
        [BEGIN]
            [UNKNOWN RECORD]
                                     // Another pos record.
                                     // Category axis
            [AXIS]
            [BEGIN]
                [CATSERRANGE]
                                    // defines tick marks and other stuff
                [AXCEXT]
                                     // unit information
                [TICK]
                                     // tick formating characteristics
            [END]
            [AXIS]
                                    // Value axis
            [BEGIN]
                IN |
[VALUERANGE]
                                    // defines tick marks and other stuff
                [TICK]
                                    // tick formating characteristics
                [AXISLINEFORMAT] // major grid line axis format
                [LINEFORMAT]
                                     // what do the lines look like?
            [END]
            [PLOTAREA]
                                     // marks that the frame following belongs
                                     // to the frame.
                                     // border
            [FRAME]
            [BEGIN]
                                    // border line
                [LINEFORMAT]
                                    // border area
                [AREAFORMAT]
            [END]
            [CHARTFORMAT]
                                    // marks a chart group
            [BEGIN]
                                     // indicates a bar chart
                [BAR]
                [UNKNOWN RECORD] // apparently this record is ignoreable
                [LEGEND]
                                     // positioning for the legend
                [BEGIN]
                     [UNKNOWN RECORD] // another position record.
                                         // details of the text that follows
// in the next section
                     [TEXT]
                     [BEGIN]
                         [UNKNOWN RECORD] // yet another pos record
                                           // another link (of type direct)
                     [END]
                [END]
            [END]
        [END]
    [END]
    [DIMENSIONS]
    [SINDEX]
    [SINDEX]
    [SINDEX]
[EOF]
```

Just a quick note on some of the unknown records:

EC: MSODRAWING - A Microsoft drawing record. (Need to track down where this is

documented).

- 5D: OBJ: Description of a drawing object. (This is going to be a PITA to implement).
- 33: Not documented. :-(
- 105f: Not documented. :-(
- 104f: POS: Position record (should be able to safely leave this out).
- 1022: CHARTFORMATLINK: Can be left out.

It is currently suspected that many of those records could be left out when generating a bar chart from scratch. The way we will be proceeding with this is to write code that generates most of these records and then start removing them to see how this effects the chart in excel.

3. Inserting the Chart into the Workbook

• Unknown record (sid=00eb) is inserted before the SST record.

- Any extra font records are inserted as needed
- Chart records inserted after DBCell records.