

RISC-V赛道性能用例与开发板对应关系																		重测规则
开发板	开发板对应ip																	1. 每个开发板绑定若干性能用例。 2. 在每个开发版上依次运行所有队伍的代码。 3. 运行三次，取中值作为性能成绩。
riscv-1	192.168.140.100	2024-0ZE-13	2024-1WO-11	2024-2KM-21	2024-7UJ-12	2024-8NL-18	2024-931-6											
riscv-2	192.168.140.102	2024-C64-14	2024-CH6-24	2024-DCV-7	2024-FAF-19	2024-FVJ-15	2024-H17-1	2024-I4W-2										
riscv-3	192.168.140.105	2024-JVU-10	2024-K0I-17	2024-KVV-20	2024-LN4-9	2024-MXP-16	2024-NCY-23	2024-NKK-22										
riscv-4	192.168.140.108	2024-1RK-26	2024-2D0-22	2024-51P-30	2024-NT1-4	2024-PKP-8	2024-U03-25	2024-VTF-5										
riscv-5	192.168.140.109	2024-5HA-8	2024-5NG-2	2024-84M-11	2024-AZ7-32	2024-BE3-31	2024-BJV-10	2024-CH1-5										
riscv-6	192.168.140.110	2024-ETJ-33	2024-FI8-9	2024-FQX-25	2024-I9Y-15	2024-IG5-12	2024-JR2-21	2024-K22-4										
riscv-7	192.168.140.111	2024-LW8-7	2024-OBF-29	2024-PAF-17	2024-PCT-14	2024-QV9-34	2024-T6G-27	2024-TBR-19										
riscv-8	192.168.140.112	2024-U7D-6	2024-U7W-16	2024-V6O-23	2024-VGH-20	2024-VRT-1	2024-X7M-3	2024-XRB-24	2024-XU5-13	2024-Y60-18	2024-Z3A-28							
ARM赛道性能用例与开发板对应关系																		
开发板	开发板对应ip																	
arm-1	192.168.140.67	2024-0ZE-13	2024-1WO-11	2024-2KM-21	2024-7UJ-12	2024-8NL-18	2024-931-6	2024-BAV-3	2024-C64-14	2024-CH6-24	2024-DCV-7	2024-FAF-19	2024-FVJ-15	2024-H17-1	2024-I4W-2	2024-JVU-10		
arm-2	192.168.140.65	2024-1RK-26	2024-2D0-22	2024-51P-30	2024-5HA-8	2024-5NG-2	2024-K0I-17	2024-KVV-20	2024-LN4-9	2024-MXP-16	2024-NCY-23	2024-NKK-22	2024-NT1-4	2024-PKP-8	2024-U03-25	2024-VTF-5		
arm-3	192.168.140.68	2024-84M-11	2024-AZ7-32	2024-BE3-31	2024-BJV-10	2024-CH1-5	2024-ETJ-33	2024-FI8-9	2024-FQX-25	2024-I9Y-15	2024-IG5-12	2024-JR2-21	2024-K22-4	2024-LW8-7	2024-OBF-29	2024-PAF-17		
arm-4	192.168.140.69	2024-PCT-14	2024-QV9-34	2024-T6G-27	2024-TBR-19	2024-U7D-6	2024-U7W-16	2024-V6O-23	2024-VGH-20	2024-VRT-1	2024-X7M-3	2024-XRB-24	2024-XU5-13	2024-Y60-18	2024-Z3A-28			