

Syntax

The ENGPREFIX2 function takes a numeric **input_value** and returns the number scaled to the appropriate engineering prefix value as text and appends it with the associated SI engineering prefix.

ENGPREFIX2(input_value, [unit_chr], [cap_mode], [skip_milli],
[μF_blank], space_separator], [round_digits])

Argument	Description
input_value Required	Number to have engineering SI prefix assigned.
unit_chr Optional	Characters of SI Unit to follow SI prefix as in "F" for Farads, "H" for Henry, Greek letter omega "Ω" for Ohms, and etc. Default is "".
cap_mode Optional	Option to not return prefix "nano" for capacitors. 0 - normal - return nano [default] 1 - skip nano and go from μF to pF below 0.001μF 2 - skip nano and go from μF to pF below 0.01μF 3 - skip nano and go from μF to pF below 0.1μF

skip_milli Optional	TRUE – Does not return prefix "milli" for capacitors. Goes from μ F to F. Default is FALSE.
μF_blank Optional	TRUE – If prefix μ is calculated, μ is not displayed. Use when schematics indicate, "All capacitors are in microfarads unless otherwise noted". Default is FALSE.
space_separator Optional	TRUE - Adds a space between the number and the prefix. Default is FALSE.
round_digits Optional	Rounds the result to a specified number of digits. -1 is no rounding [default] 0 returns the integer of the output value (no decimals) 1 and up is number of decimals to round...2, 3, and etc.

Example

ENGPREFIX2(input_value, [unit_chr], [cap_mode], [skip_milli],
[μF_blank], space_separator, [round_digits])

Formula	Description	Result
=ENGPREFIX2(5628)	Returns text of the input_value scaled to SI prefix level, and prefix added	5.628k
=ENGPREFIX2(5628,"Ω")	Returns text of the input_value scaled to SI prefix, with prefix and unit_chr Ω added	5.628kΩ
=ENGPREFIX2(1.0E-09,"F",1)	Capacitor values >= 0.001μF returns μF	0.001μF
=ENGPREFIX2(8.20E-10,"F",1)	Capacitor values >= 0.001μF returns μF, below in pF	820pF
=ENGPREFIX2(0.1,"F",1,TRUE)	μ used instead of milli	100000μF
=ENGPREFIX2(1E-08,"F",2,TRUE,TRUE)	μ not returned	0.01

Formula	Description	Result
=ENGPREFIX2(6.8E-06,"H",1,FALSE,FALSE,TRUE)	Space between value and prefix	6.8 mH
=ENGPREFIX2(6.561E-09,"W",1,FALSE,FALSE,TRUE,1)	Round to 1 decimal place	6.6 GW