QA AI base: project cheat sheet

IN USE · DRAFT / NOT RUN · UNVERIFIED · NOT USED

Cheat sheet 2 of 6. PLACEHOLDER: fill in when the setup is finished. Facts below are from CLAUDE.md; blanks are UNKNOWN until Discovery.

Where things live

`CLAUDE.md` Always-on rules, skill table	DRAFT
`.claude/rules/` security, QA, AI + web and mobile rules	DRAFT
`.claude/skills/` Copies of plugins/qabase/skills	DRAFT
`.claude/hooks/` Hook specs and scripts	NOT ACTIVE
`.claude/settings.draft.json` Permissions draft	NOT ACTIVE
`.mcp.json` Approved MCP servers	EMPTY
`evals/` Acceptance checks	NOT RUN
`automation/web` Playwright (optional)	OPTIONAL
`automation/mobile` WebdriverIO + Appium (optional)	OPTIONAL
`automation/api` The project's choice (optional)	OPTIONAL

The chain: Claude, human, deterministic

C Claude with a skill · **H human gate** · D no AI

- C `analyze-requirements + brief`
- **H** approve the brief
- C `create-test-cases`
- **H** review cases, save to TMS
- C `automation-readiness`
- **H** approve candidate
- C `create + review test`
- **H** review diff, merge
- D CI run, results, evidence
- **H** release decision

Manual testing runs in parallel and feeds the release decision.
Source: docs/schemes/08-mvp-chain.md (working draft).

Fill in (UNKNOWN until Discovery)

Environment to test on (DEV or SIT)	UNKNOWN
Test management and defect tracker	UNKNOWN
CI/CD tool and who can see runs	UNKNOWN
Test accounts and test data	UNKNOWN
Devices and builds for mobile	UNKNOWN
Who approves changes (AI QA Process Lead)	UNKNOWN
Where to send feedback	UNKNOWN

Rules to keep in view

- DEV or approved non-production only. Production is prohibited.
- A mobile build can open on PROD by default. Switch to test and confirm first.
- A bug gets a failing test first (Iron Law).
- Say which device or emulator produced the evidence.