Contents

1 Measuring the variable of interest **1**

2 Cross-tabs and categorical variables **1**

3 Estimation **2**

4 Regression/Classification **2**

5 Discussion topics **2**

1 Measuring the variable of interest

In most cases, you will have one variable of interest to measure,e.g. Grade or Crash. It can be continuous or binary. For simplicity, assume that continuous variables are Gaussian and discrete are Bernoulli.

At the first step, generate data from your simulator for both of the two hypotheses, and see what the Bernoulli or Gaussian parameters would be, ignoring all the other variables. For example, for the Crash variable, you would be estimating the percentage of crashes in the population. For Grade, you would be estimating the overall grade distribution.

2 Cross-tabs and categorical variables

In voting, for example, you see polls that report for different subsets of people, breaking down the voting patterns on gender, race, education, income etc. You can see this as estimating a different parameter θ_C for each category of people C.

As a running example, I will use voting for left or right (0, 1) and variables age, gender, smoking, exercise.

Look at your features, and create bins that correspond into categories C, so that every person is in exactly one category. If your features are discrete, e.g. taking m values, then you naturally have m bins. For continuous features, you can choose how many bins you have. The more features and bins, the more the possible categories. For example, if you split age in [18, 25), [25, 45), [45, 65), [65,∞) then you have 4 bins. If we split smoking in yes/no and exercise in 0, (0,30], (30,60], (60, ∞), then we end up with $2 \times 4 \times 2 \times 4 = 64$ categories.

3 Estimation

Generate data for both of your hypotheses. For now, fix an arbitrary amount of data.

Now, estimate θ_C for every possible category using both ML and MAP. Assume all variables are observable for simplicity.

- Some categories will be empty! That is, maybe there is no person who is 70-80 years old, smokes, and exercises 60-90 minutes/day. What should θ_C be in this case in the MAP and ML estimation?
- Now, vary the amount of data you generate (try 10x more and 10x less). If you have a small amount of data, some categories are more likely to have nobody. Your estimates will also be more noisy. The more categories and the fewer data, the more noisy it is going to be. How does your θ_C estimate get influenced by the amount of data?
- Decide on an **algorithm** for choosing one of the two hypotheses, based on your θ_C estimates. How often does the algorithm get it wrong, when H_0 or H_1 is true? How does it depend on the amount of data?

4 Regression/Classification

Is there some way you could run a similar analysis using standard regression or classification algorithms?

5 Discussion topics

For this submission, you are *encouraged* to submit your **Chatbot prompts and responses**, as well as topics of **group discussion**, relating to this week's *lecture* and the *assignment*. This will **not** be taken into account for your grade, but we would like to understand:

- which concepts you found difficult,
- which questions you asked,
- whether the responses were helpful, confusing, or incorrect,
- and what eventually helped you understand the material.

Feel free to include both successful and unsuccessful interactions with fellow students and chatbots alike.