api.mon.declarant.by — API Overview

Nov 11, 2026 · @Aleh Ladyka

There is no public documentation or Swagger for `api.mon.declarant.by`. The bare `/api` path returns 404, so the API was mapped by running its only known client, the monitoring app at mon.declarant.by (linked from declarant.by under "Мониторинг событий"), and recording every call it made across all six sections.

General

- **Base URL:** `https://api.mon.declarant.by/api/`
- **Format:** JSON request bodies and responses.
- **Pagination:** list endpoints return Laravel-style pages with these fields: `current_page`, `data[]`, `per_page`, `total`, `last_page`, `next_page_url`, `prev_page_url`, `links`.
- **Auth:** the app sends `X-Api-Key`, `X-Api-Token` and `X-Api-Word` headers. Test calls without them still returned 200, but those were made from the app's own site, so the headers may be required for other callers.
- **Waiting-zone data is a separate host.** The "ЗО" section calls `belarusborder.by/info/...`, not this API.

Endpoints on api.mon.declarant.by

Examples are illustrative and shortened. IDs 56, 9103 and the office names were seen in live responses; `…` marks values left out.

Method	Path	Description	Inputs	Returns	Example request	Example response
POST	`/customs-place`	Lists customs offices and their checkpoints of one kind (ВПТО or СВХ). Feeds the office/checkpoint lists on the ВПТО and СВХ pages.	body: `place_kind` (2 = СВХ; the ВПТО page uses another value, likely 1)	Customs offices, each with `places[]`: `id`, `place_code`, `disp_name`, `disp_address`, `disp_work_time`, `disp_phones`, `ptocode`, `isActive`, `updated`	`POST /api/customs-place` body `{"place_kind":2}`	`[{"id":"06","disp_name":"Минская региональная таможня","sortIndex":5,"places":[{"id":56,"place_code":"BA-0603/0000230","ptocode":"06649","isActive":1,…}]},…]`

Method	Path	Description	Inputs	Returns	Example request	Example response
GET	`/customs-place/{id}`	Gets one checkpoint's card: name, address, working hours, phones and codes. Shown as the header of a ВПТО or СВХ detail page.	path id	One place's details (same fields, plus `svh_place_code`)	`GET /api/customs-place/56`	`{"id":56,"place_code":"BA-0603/0000230","disp_name":"СВХ ТЛЦ Минск-Белтаможсервис","disp_address":"Минский р-н, 17-й км автодороги Минск-Дзержинск","customs":"06","ptocode":"06649","place_kind":2}`
POST	`/vpto`	Searches customs declarations processed at a ВПТО checkpoint and shows each one's clearance stage (registered, released, refused, etc.). Filter by status, document type or registration number.	body: `place_id`, `declStatus`, `docTypes`, `regNumber`	Paginated declarations: `regNumber`, `regDate`, `declType`, `declMode`, `declOwner`, `declStatus`, `accNumber` / `accDate`, `requirementText`, `refusalReason`, `referenceNumber`, `wrkPoint`	`POST /api/vpto` body `{"place_id":2,"declStatus":null,"docTypes":[],"regNumber":""}`	`{"current_page":1,"data":[{"id":…,"place_id":2,"regNumber":"…","regDate":"2026-11-11 10:15:00","declStatus":…,…}],"last_page":…,"total":…}`
POST	`/svh`	Searches goods and vehicles placed in a temporary storage warehouse (СВХ): arrival, documents and release. Filter by item number, arrival date, transport or registration number.	body: `place_id`, `numItem`, `dateIn`, `transport`, `regNum`	Paginated warehouse (СВХ) entries: `dateIn` / `dateOut`, `docId`, `numItem`, `transport`, `regNum`, `vhNum`, `prevNum`, `sender`, `receiver`, `documents`	`POST /api/svh` body `{"place_id":56,"numItem":"","dateIn":"","transport":"","regNum":""}`	`{"current_page":1,"data":[{"id":…,"place_id":56,"dateIn":"2026-11-11 09:40:00","transport":"…","regNum":"…","dateOut":null,"documents":[…]}],"total":…}`
GET	`/rpto`	Lists customs offices and their regional clearance points (РПТО). Feeds the РПТО page list.	none	Customs offices with their РПТО `places[]`	`GET /api/rpto`	`[{"customs_id":"09","name":"Брестская таможня","places":[{"id":9103,"address":"г. Брест, п/п Козловичи",…}]},…]`
GET	`/rpto/{id}`	Gets one РПТО's card: name, address, working hours and phones.	path id	РПТО details: `name`, `address`, `timework`, `phones`, `customs_id`	`GET /api/rpto/9103`	`{"id":9103,"name":"…","address":"г. Брест, п/п Козловичи","timework":"…","phones":"…","customs_id":"09","updated":"…"}`
POST	`/rpto/vehicles`	Shows the queue of vehicles at one РПТО with their timestamps and status. `search` filters by vehicle number.	body: `id`, `search`	Paginated vehicle queue: `number`, `tsnumber`, `rdatetime`, `tdatetime`, `edatetime`, `status`	`POST /api/rpto/vehicles` body `{"id":9103,"search":""}`	`{"current_page":1,"data":[{"number":1,"tsnumber":"…","rdatetime":"…","tdatetime":"…","edatetime":null,"status":"…"}],"total":…}`
POST	`/vehicle`	Finds passenger cars imported by individuals that are currently in a customs control zone (ЗТК). Search by VIN, optionally limited to one ПТО.	body: `search` (VIN), `ptoCode`	Paginated passenger cars in customs control zones: `vin`, `description`, `dateIn`, `timeIn`, `DOCID`, `ptoCode`	`POST /api/vehicle` body `{"search":"WBA","ptoCode":""}`	`{"current_page":1,"data":[{"id":…,"vin":"WBA…","description":"…","dateIn":"…","timeIn":"…","ptoCode":"…"}],"total":…}`

Method	Path	Description	Inputs	Returns	Example request	Example response
GET	`/container`	Looks up the status of a container with goods for several recipients at TLC Минск-Белтаможсервис-2.	query: `id` (container number)	Container status; returns `{}` if not found	`GET /api/container?id=MSKU1234567`	`{}` (no match for this number)

Waiting-zone endpoints (belarusborder.by)

All three take a `token` query parameter.

Method	Path	Description	Inputs	Returns	Example request	Example response
GET	`/info/checkpoint`	Lists border waiting zones (ЗО) with how many vehicles of each type are queued, booked, prioritised or already passed.	`token`	`result[]` of zones: `id` (UUID), `name`, `address`, `phone`, and queue counts (`countAll`, `countCar`, `countTruck`, `countBus`, `countMotorcycle`, `countLiveQueue`, `countBookings`, `countPriority`, `countPassedSCC`)	`GET https://belarusborder.by/info/checkpoint?token=<token>`	`{"result":[{"id":"53d94097-2b34-11ec-8467-ac1f6bf889c0","name":"…","address":"…","countAll":…,"countTruck":…,"countCar":…,…},…]}`
GET	`/info/monitoring-new`	Returns the live electronic queue for one waiting zone, split by vehicle type and queue kind (live, priority, regular).	`token`, `checkpointId`	Live queues by vehicle type (`truckLiveQueue`, `truckPriority`, `truckGpk`, `bus*`, `car*`, `motorcycle*`) plus `info`	`GET https://belarusborder.by/info/monitoring-new?token=<token>&checkpointId=53d94097-2b34-11ec-8467-ac1f6bf889c0`	`{"info":{…},"truckLiveQueue":[…],"truckPriority":[…],"carLiveQueue":[…],"busLiveQueue":[…],…}`
GET	`/info/monitoring/statistics`	Returns queue statistics for one waiting zone, used for the zone page's summary.	`token`, `checkpointId`	Non-JSON statistics payload	`GET https://belarusborder.by/info/monitoring/statistics?token=<token>&checkpointId=53d94097-…`	Non-JSON body (not decoded)

How the app pages map to the API

Page	Calls
`#/vpto`	`customs-place`, then `customs-place/{id}` and `vpto`
`#/svh`	`customs-place`, then `customs-place/{id}` and `svh`

Page	Calls
`#/rpto`	`rpto`, then `rpto/{id}` and `rpto/vehicles`
`#/cars`	`vehicle`
`#/container`	`container`
`#/zone`	belarusborder.by endpoints

Caveats

This is reverse-engineered from the live app, not official documentation, so it's undocumented and may change without notice. The key values embedded in the app's code were not copied. Before building anything on it, check with Белтаможсервис's software support (declarant.by/ru/software/support/) about permitted use.