
IMPROVING SOLAR PANEL EFFICIENCY USING PEROVSKITE–SILICON TANDEM SOLAR CELLS

Olga-Dimitra Stoura • Mechanical Engineering • University of Massachusetts Amherst

INTRODUCTION & ENGINEERING PROBLEM

Commercial silicon solar panels typically convert about 20–23% of incoming sunlight into electricity. Efficiency is limited by heat generation, low-energy photons that pass through the cell, reflection, and electrical losses. Improving conversion efficiency is therefore a major engineering challenge in renewable energy.

HOW THE TANDEM CELL WORKS




A perovskite top cell absorbs higher-energy portions of sunlight while the silicon bottom cell absorbs lower-energy photons. Using two complementary absorbers reduces losses compared with a single silicon junction.

WHY THIS APPROACH?


Tandem architecture can increase conversion efficiency while retaining silicon as the structural/manufacturing foundation.

EVIDENCE FROM ENGINEERING RESEARCH



Messmer et al. found that tandem concepts can offset added perovskite costs through higher power output; module cost per watt depends strongly on the silicon bottom-cell design.

ADAPTED FROM MESSMER ET AL. (2021), FIG. 5B



Outdoor testing of a full-size bifacial tandem module showed that spectral conditions and backside irradiance affect measured module performance.

SIMPLIFIED FROM CHOJNIAK ET AL. (2024), FIG. 5

ENGINEERING BENEFITS

Higher efficiency	Different layers absorb different portions of the solar spectrum.
Better use of area	Higher output per unit area can reduce area-dependent system costs.
Compatibility with silicon	Existing silicon technology can serve as the bottom-cell platform.

CURRENT ENGINEERING CHALLENGES

- Long-term stability of perovskite materials
- Moisture sensitivity and material degradation
- Large-scale manufacturing and process compatibility
- Environmental impacts and recycling of hazardous materials

ENVIRONMENTAL CONSIDERATION

Rodriguez-Garcia et al. report that PST systems can be more efficient than standard PVs, but life-cycle toxicity and end-of-life management remain important engineering concerns. They suggest mainly to improve recycling for this issue.

KEY SOURCES | Messmer et al., 2021, Progress in Photovoltaics, 29, 744–759 • Rodriguez-Garcia et al., 2024, ACS Sustainable Chemistry & Engineering, 12, 17523–17530 • Chojniak et al., 2024, Progress in Photovoltaics, 32, 219–231