

# Approximate Binary Trees in External Memory Models

by

Oliver Grant

A thesis  
presented to the University of Waterloo  
in fulfillment of the  
thesis requirement for the degree of  
Master of Mathematics  
in  
Computer Science

Waterloo, Ontario, Canada, 2016

I hereby declare that I am the sole author of this thesis. This is a true copy of the thesis, including any required final revisions, as accepted by my examiners.

I understand that my thesis may be made electronically available to the public.

## Abstract

We examine the classic binary search tree problem of Knuth [28]. First, we quickly re-examine a solution of Güttler, Melhorn and Schneider [18] which was shown to have a worst case bound of  $c * H + 2$  where  $c \geq 1/H(1/3, 2/3) \approx 1.08$ . We give a new worst case bound on the heuristic of  $H + 4$ . In the remainder of the work, we examine the problem under various models of external memory. First, we use the Hierarchical Memory Model (HMM) of Aggarwal et al. [2] and propose several approximate solutions. We find that the expected cost of search is at most  $\frac{W_{HMM}(P)}{\lceil \lg(s_{min}) \rceil} * (H + 1)$  where  $W_{HMM}(P)$  is a well-defined function of the probability distribution,  $s_{min} = \min(\min_{i \in \{1, \dots, n\}}(p_i), \min_{j \in \{0, \dots, n\}}(q_j))$ , and  $H$  is the entropy of the distribution. Using this, we improve a bound given in Thite's 2001 thesis for the HMM<sub>2</sub> model in the approximate setting. We also examine the problem in the Hierarchical Memory with Block Transfer Model [3] and find approximate solutions. Similarly, we find the expected cost is at most  $\frac{W_{HMBTM}(P)}{\lceil \lg(s_{min}) \rceil} * (H + 1)$  where  $W_{HMBTM}(P)$  is a well-defined function of the probability distribution and  $s_{min}$  and  $H$  are as before.

## **Acknowledgements**

I would like to thank all the little people who made this possible.

## **Dedication**

This is dedicated to the one I love.

# Table of Contents

<b>List of Tables</b>	<b>viii</b>
<b>List of Figures</b>	<b>ix</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Binary Search Trees . . . . .	1
1.2 The Optimum Binary Search Tree Problem . . . . .	1
1.3 Why Study Binary Search Trees . . . . .	2
1.4 Overview . . . . .	2
<b>2 Background and Related Work</b>	<b>4</b>
2.1 Binary Search Trees . . . . .	4
2.2 Alphabetic Trees . . . . .	5
2.3 Multiway Trees . . . . .	6
2.4 Memory Models . . . . .	7
<b>3 An Improved Bound for the Modified Minimum Entropy Heuristic</b>	<b>8</b>
3.1 Preliminaries . . . . .	8
3.2 The Modified Minimum Entropy Heuristic . . . . .	8
3.3 ME is within 4 of Entropy . . . . .	9

<b>4</b>	<b>Approximate Binary Search in the Hierarchical Memory Model</b>	<b>12</b>
4.1	The Hierarchical Memory Model . . . . .	12
4.2	Thite's Optimum Binary Search Trees on the HMM Model . . . . .	13
4.3	Efficient Near-Optimal Multiway Trees of Bose and Douïeb . . . . .	13
4.4	Algorithm ApproxMWPaging . . . . .	14
4.5	Expected Cost ApproxMWPaging . . . . .	16
4.6	Approximate Binary Search Trees of De Prisco and De Santis with Extensions by Bose and Douïeb . . . . .	19
4.7	Algorithm ApproxBSTPaging . . . . .	20
4.8	Expected Cost ApproxBSTPaging . . . . .	21
4.9	Improvements over Thite in the HMM <sub>2</sub> Model . . . . .	22
<b>5</b>	<b>Approximate Binary Search in the Hierarchical Memory with Block Transfer Model</b>	<b>25</b>
5.1	Hierarchical Memory with Block Transfer Model . . . . .	25
5.2	ApproxMWPaging with BT . . . . .	26
5.3	ApproxMWPaging with BT Running Time . . . . .	28
5.4	Search with ApproxMWPaging with BT . . . . .	31
5.5	Expected Cost ApproxMWPaging with BT . . . . .	32
5.6	ApproxBSTPaging with BT . . . . .	32
5.7	Expected Cost ApproxBSTPaging with BT . . . . .	32
<b>6</b>	<b>Conclusion and Open Problems</b>	<b>33</b>
6.1	Discussion . . . . .	33
6.2	Conclusion . . . . .	33
	<b>APPENDICES</b>	<b>34</b>
	<b>A PDF Plots From Matlab</b>	<b>35</b>
	<b>References</b>	<b>36</b>

# List of Tables



# List of Figures

# Chapter 1

## Introduction

### 1.1 Binary Search Trees

A binary search tree is simple structure used to store key-value pairs. It was invented in the late 1950s and early 1960s and is generally attributed to the combined efforts of Windley, Booth, Colin and Hibbard [34] [9] [19]. In general, the trees allow for quick binary searches through the data in search of a specific key. Each node has a key over which there is a total-ordering (a number, a string, etc.), as well as some value (generally the important information). Each tree node has at most two children generally labelled as the *left* and *right*. All nodes in the subtree of the *left* child of a specific node have a key strictly less than the key of the node in question. Similarly, nodes in the subtree of the *right* child of a specific node have a key strictly greater than the key of the node in question. A pointer is typically stored to a root node. Search begins from this root node and is done by recursively searching in either the *left* or *right* child of root node, or stopping if the root being searched has the correct key.

### 1.2 The Optimum Binary Search Tree Problem

Knuth first proposed the optimum binary search tree problem in 1971 [28]. We are given a set of  $n$  words  $B_1, B_2, \dots, B_n$  and  $2n + 1$  frequencies,  $p_1, p_2, \dots, p_n, q_0, q_1, \dots, q_n$  representing the probabilities of searching for each given word and the probabilities of searching for strings between (and outside of) these words. We have that  $q_0 + \sum_{i=1}^n p_i + q_i = 1$ . We also

assume that without loss of generality  $q_i + p_i + q_{i+1} \neq 0$  for any  $i$ . The words (and gaps between) are used as keys and the lexicographical ordering of them provides our order over the keys. Our goal is to construct a binary tree such that the expected cost of search is minimized. The names make up the leaves of the tree while, gaps make up the internal nodes. The weighted path length of the tree is:

$$P = \sum_{i=1}^n p_i(b_i + 1) + \sum_{j=1}^n q_j(a_j)$$

Where  $b_i$  and  $a_j$  represent the depth of nodes representing the  $i^{th}$  word and  $j^{th}$  gap respectively. The optimal solution of Knuth requires  $O(n^2)$  time, and  $O(n^2)$  space. This solution is both time and space intensive. We will later examine an approximate solution to this problem of Güttler, Mehlhorn and Schneider which uses  $O(n^2)$  time but  $O(n)$  space and improve its worst-case bound. However, these problems were examined under the RAM model which is an inadequate model for many situations. We examine the problem in more realistic models and look at approximate solutions under these settings.

## 1.3 Why Study Binary Search Trees

Binary search trees are ubiquitous throughout computer science with numerous applications. The basic binary search tree has been built upon in many ways. AVL trees (named after creators AdelsonVelskii and Landis) were the first form of self-balancing binary search trees introduced [1]. The trees invented by the pair in 1963 and maintain a height of  $O(\lg(n))$  where  $n$  is the number of nodes in the tree during insertions and deletions (both of which take  $O(\lg(n))$  time). Improved self-balancing binary search trees followed in the form of red-black trees by Bayer in 1972 and splay trees by Sleator and Tarjan in 1985 [6] [31]. Tango trees were invented in 2007 by Demaine et al. and provided the first  $O(\lg \lg n)$  competitive binary tree [12]. Here,  $O(\lg \lg n)$  competitive means that the tango tree does at most  $O(\lg \lg n)$  times more work (pointer movements and rotations) than an optimal offline tree. B trees are among the most commonly used binary tree variant and were invented in 1970 by Bayer and McCreight [5].

Binary space partition Binary Tries in routers Hash Trees Heaps - PQ Huffman Code - compression Syntax tree expression evaluation

## 1.4 Overview

In Chapter 2 I review previous work done in the areas of binary search trees, multiway trees, alphabetic trees and various models of external memory. In Chapter 3, I re-examine

the Modified Entropy Rule (ME) of Güttler, Mehlhorn and Schneider [18]. This is a  $O(n)$  time algorithm for approximating the optimum binary search tree problem in the RAM model. The method worked very well in practice, and the group had great experimental results, but unfortunately they could not bound the worst case expected cost of the as they would have hoped. While simpler solutions like the *Min-max* and *Weight Balanced* techniques of Bayer [4] had worst case costs of at most  $H + 2$ , the trio's ME technique had a worst case expected search cost of  $c * H + 2$  where  $c \approx 1.08$ . I provide a new argument of its worst case expected search cost and show that it is within a constant of entropy: at worst  $H + 4$ . In Chapter 4, I move on to external memory models, examining the optimum binary search tree problem under the hierarchical memory model as was done in Thite's thesis [32]. I provide TWO?  $O(n * lg(m_1))$  time algorithm which has a worst case expected cost of TODO FIX  $C \leq (\lceil lg(m_1) \rceil * (\lfloor log_{m_1}(\frac{2}{min_{p,q}}) \rfloor + 1)) * W * (H + 1)$  WHERE TODO. The solution provided also gives a direct improvement over the solution Thite provided in the same work for HMM<sub>2</sub>. In Chapter 5, I extend my solutions to examine a more realistic model for external memory, the hierarchical memory with block transfers model (HMBTM). I use similar algorithms which run in TODO and give worst case expected search costs of TODO. In Chapter 6 I summarize my findings and discuss several problems which remain open.

# Chapter 2

## Background and Related Work

### 2.1 Binary Search Trees

After Knuth's initial examination of the optimum binary search tree problem in 1971 [28], several others have examined the approximate version of the problem. Knuth's optimal solution requires  $O(n^2)$  time and space which is too costly in many situations. While unable to bound an approximate algorithm within a constant of the optimal solution, many authors have been able to bound the cost based on the entropy of the distribution of probabilities,  $H$ . Specifically,  $H = \sum_{i=1}^n p_i * \log_2(\frac{1}{p_i}) + \sum_{j=0}^n q_i * \lg(\frac{1}{q_j})$ . In 1975, Bayer showed that  $H - \lg H - (\lg e - 1) \leq C_{Opt}$ ,  $C_{Opt} \leq C_{WB} \leq H + 2$  and  $C_{Opt} \leq C_{MM} \leq H + 2$  where  $C_{Opt}$ ,  $C_{WB}$ , and  $C_{MM}$  are costs for the optimal solution, as well as weight-balanced and min-max heuristic methods respectively [4]. Weight-balanced and min-max costs heuristics are greedy and require both  $O(n)$  time and  $O(n)$  space to run. In 1980, Güttler, Mehlhorn and Schneider presented a new heuristic, the Modified Entropy Rule (ME) [18] which built upon the ideas of Horibe [20]. Güttler, Mehlhorn AND Schneider gave empirical evidence that the heuristic out-performed others [18]. While the heuristic took  $O(n^2)$  time, it only required  $O(n)$  space, a huge savings over the optimal solution. However, they were unable to prove that  $C_{ME} \leq H + 2$  (like previous weight-balanced and min-max heuristics) and settled with  $C_{ME} \leq c_1 * H + 2$  where  $c_1 = \frac{1}{H(\frac{1}{3}, \frac{2}{3})} \approx 1.08$ . In 1993, De Prisco and De Santis presented a new heuristic for constructing a near-optimum binary search tree [11]. The method is discussed in more detail in section 4.6 and has an upper bounded cost of at most  $H + 1 - q_0 - q_n + q_{max}$  where  $q_{max}$  is the maximum weight leaf node. This method was later updated by Bose and Douieb to have a worst case cost of

$$\frac{H}{\lg(2k-1)} \leq P_{OPT} \leq P_T \leq \frac{H}{\lg k} + 1 + \sum_{i=0}^n q_i - q_0 - q_n - \sum_{i=0}^m q_{rank[i]} \quad [10]$$

Here,  $H$  is the entropy of the probability distribution,  $P_{OPT}$  is the average path-length in the optimal tree,  $P_T$  is the average path length of the tree built using their algorithm and  $m = \max(n - 3P, P) - 1 \geq \frac{n}{4} - 1$ .  $P$  is the number of increasing or decreasing sequences in a left-to-right read of the access probabilities of the leaves. Moreover,  $q_{rank[i]}$  is the  $i^{th}$  smallest access probability among all leaves except  $q_0$  and  $q_n$ .

## 2.2 Alphabetic Trees

Given a set of  $n$  keys with various probabilities, the problem is to build a binary search tree where every internal node has two children, leaves have no children, and the  $n$  keys described are the leaves with minimum expected search cost. Here, the expected search cost is  $\sum p_i * l_i$  where  $p_i$  is the probability of searching for leaf/key  $i$  and  $l_i$  is the leaf's level in the tree. The alphabetic ordering of the leaves must be maintained. This is the same as the binary search tree problem with all internal node weights zero.

In 1952, Huffman famously developed the Huffman tree, which solved the same problem without a left-to-right ordering constraint on leaves [25]. Gilbert and Moore examined the problem with the added alphabetic constraint and developed a  $O(n^3)$  algorithm which solved the problem optimally [16]. Hu and Tucker gave a  $O(n^2)$  time and space algorithm in 1971 [24] which was improved by Knuth to take only  $O(n \lg n)$  time and  $O(n)$  space in 1973 [27]. The original proof of Hu and Tucker was extremely complicated, but was fortunately later simplified by Hu [21] and Hu et al. [23]. Garsia and Wachs gave an independent  $O(n \lg n)$  time,  $O(n)$  space algorithm in 1977 [15]. This was shown to be equivalent to the Hu and Tucker algorithm in 1982 by Hu [22] and also went through a proof simplification [26] by Kingston in 1988.

In 1991, Yeung proposed an approximate solution which solved the problem in  $O(n)$  time and space [35]. The algorithm produced a tree with worst case cost  $H + 2 - q_1 - q_n$ . This was later improved by De Prisco and De Santis who created an  $O(n)$  time algorithm which had a worst case cost of  $H + 1 - q_0 - q_n + q_{max}$  [11]. The method was improved one more time by Bose and Douieb who improved upon Yeung's method by decreasing the bound by  $\sum_{i=0}^m q_{rank[i]}$  where  $m = \max(n - 3P, P) - 1 \geq \frac{n}{4} - 1$ ,  $P$  is the number of increasing or decreasing sequences in a left-to-right read of the access probabilities of the leaves and  $q_{rank[i]}$  is the  $i^{th}$  smallest access probability among all leaves except  $q_0$  and  $q_n$  [10]. De Prisco and De Santis used Yeung's method within their own, so this improvement

to Yeung's method gave an overall tighter bound of  $H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^m q_{rank[i]}$ .  
CHECK THIS OUT TODO

## 2.3 Multiway Trees

This static k-ary or multiway search tree problem is similar to optimum binary search tree problem with the added constraint that up to  $k$  keys can be placed into a single node, and cost of search within a node is constant. Multiway search trees maintain an ordering property similar to that of traditional binary search trees. Each key in every page in the subtree rooted at a specific location in a page  $g$  (i.e. between two keys  $k$  and  $l$ ) must have its key lie between  $k$  and  $l$ . Each internal node of the k-ary tree contains at least one and at most  $k - 1$  keys while a leaf node contains no keys. Successful searches end in an internal while unsuccessful searches end in one of the  $n + 1$  leaves of the tree. The cost of search is the average path depth is defined as :

$$\sum_{i=1}^n p_i(d_T(x_i) + 1) + \sum_{j=0}^n q_j(d_T(x_{i-1}, x_i))$$

where  $x_i$ 's represent successful search keys, pairs  $(x_{i-1}, x_i)$  represent unsuccessful search "keys" and  $d_T(x_i)$  or  $d_T(x_{i-1}, x_i)$  represent the depth of a specific successful or unsuccessful search respectively.

Vishnavi et al. [33], and Gotlieb [17] in 1980 and 1981 respectively independently solved the problem optimally in  $O(k * n^3)$  time. In a slightly modified B-tree model (every leaf has same depth, every internal node is at least half full), Becker's 1994 work gave a  $O(kn^\alpha)$  time algorithm where  $\alpha = 2 + \log_k 2$  [7]. Moreover, in 1997 Becker proposed an  $O(Dkn)$  time algorithm where  $D$  is the height of the resulting tree[8]. The algorithm did not produce an optimal tree but was thought to be empirically close despite having no strong upper bound. In 2009, Bose and Douieb gave both an upper and lower bound on the optimal search tree in terms of the entropy of the probability distribution as well as an  $O(n)$  time algorithm to build a near-optimal tree [10]. There bounds of:

$$\frac{H}{\lg(2k-1)} \leq P_{OPT} \leq P_T \leq \frac{H}{\lg k} + 1 + \sum_{i=0}^n q_i - q_0 - q_n - \sum_{i=0}^m q_{rank[i]}$$

will be discussed in more detail in section BLAH TODO of this paper.

## 2.4 Memory Models

HMM HMM BT Other Stuff Cache Oblivious Look at what Thite wrote about TODO -  
LOOK @ SURVEY ON MEMORY MODELS



# Chapter 3

## An Improved Bound for the Modified Minimum Entropy Heuristic

### 3.1 Preliminaries

Recall that  $H = \sum_{i=1}^n p_i * \lg(\frac{1}{p_i}) + \sum_{j=0}^n q_j * \lg(\frac{1}{q_j})$ . We also use  $H(x_1, x_2, \dots, x_n)$  to describe the entropy of probability distribution  $(x_1, x_2, \dots, x_n)$ . For sub tree  $t$ , we let  $p_t$  be its total probability.  $P_L(p_i)$  and  $P_R(p_i)$  are probabilities of searching for a word lexicographically before or after (respectively) word  $B_i$ .  $P_{L_t}(p_i) = \frac{P_L(p_i)}{p_t}$  and  $P_{R_t}(p_i) = \frac{P_R(p_i)}{p_t}$  are these same probabilities normalized for sub tree  $t$ . Similarly,  $P_{L_t}(q_j)$  and  $P_{R_t}(q_j)$  describe the normalized probabilities of searching for a word before or after (respectively) the lexicographic gap between words  $B_j$  and  $B_{j+1}$ . We let  $E_t = H(P_{L_t}(p_i), \frac{p_i}{p_t}, P_{R_t}(p_i))$  be the local entropy of a sub tree  $t$  rooted at word  $B_i$ .

### 3.2 The Modified Minimum Entropy Heuristic

As described in [18], the heuristic greedily chooses the word  $B_i$  as the root such that  $H(P_{L_t}(p_i), \frac{p_i}{p_t}, P_{R_t}(p_i))$  is maximized. There are two exceptions to this rule. First, if there exists  $p_i$  such that  $\frac{p_i}{p_t} > \max(P_{L_t}(p_i), P_{R_t}(p_i))$  we always select  $B_i$  as the root. Moreover, if there exists  $q_j$  such that  $\frac{q_j}{p_t} > \max(P_{L_t}(q_j), P_{R_t}(q_j))$  then we select the root from among  $B_j$  and  $B_{j+1}$ .  $B_j$  is chosen if  $P_{L_t}(q_j) > P_{R_t}(q_j)$  and  $B_{j+1}$  is chosen otherwise. Since it takes linear time and constant space to find the all of the optimal local entropy splits in each

level of the tree, the algorithm takes  $O(n^2)$  time and  $O(n)$  space.

### 3.3 ME is within 4 of Entropy

**Lemma 3.3.1.** *When using the ME Rule to choose the root  $B_r$  of a binary search tree  $t$  with total probability  $p_t$ , one of the following three cases must occur:*

- 1)  $E_t \geq 1 - 2\frac{p_r}{p_t}$
- 2) *There exists  $q_i$  such that  $\frac{q_i}{p_t} > \max(P_{L_t}(q_i), P_{R_t}(q_i))$*
- 3)  $\max(P_{L_t}(p_r), P_{R_t}(p_r)) < \frac{4}{5}p_t$

*Proof.* Suppose there exists some  $p_i$  such that  $\frac{p_i}{p_t} > \max(P_{L_t}(p_i), P_{R_t}(p_i))$ . By the ME Rule, it must be selected as the root and thus  $p_r = p_i$ . Moreover, both  $P_{L_t}(p_i)$  and  $P_{R_t}(p_i)$  must be less than one half. As shown in [14]  $H(x, 1-x) \geq 2x$  when  $x < \frac{1}{2}$ . Thus we have:

$$\begin{aligned}
E_t &\geq H(\max(P_{L_t}(p_i), P_{R_t}(p_i)), 1 - \max(P_{L_t}(p_i), P_{R_t}(p_i))) \\
&\geq 2 * \max(P_{L_t}(p_i), P_{R_t}(p_i)) \\
&\geq 1 - \frac{p_i}{p_t} \\
&\geq 1 - 2\frac{p_i}{p_t} \geq 1 - 2\frac{p_r}{p_t} \\
&\text{as required.}
\end{aligned}$$

If we do not have some  $p_i$  such that  $\frac{p_i}{p_t} > \max(P_{L_t}(p_i), P_{R_t}(p_i))$  but do have some  $p_i$  such that  $P_{L_t}(p_i) \leq \frac{1}{2}p_t$  and  $P_{R_t}(p_i) \leq \frac{1}{2}p_t$  then we have:

$E_t \geq H(P_{L_t}(p_i), \frac{p_i}{p_t}, P_{R_t}(p_i))$  where  $0 \leq P_{L_t}(p_i) \leq 0.5$ ,  $0 \leq \frac{p_i}{p_t} \leq 0.5$  and  $0 \leq P_{R_t}(p_i) \leq 0.5$  and we know that

$H(P_{L_t}(p_i), \frac{p_i}{p_t}, P_{R_t}(p_i)) \geq H(1/2, 1/2) = 1$  in this case. Thus,  $E_t \geq 1 - 2p_r$  as required.

Otherwise, we must have some  $q_i$  spanning the middle of the data set (i.e.  $P_{L_t}(q_i) < \frac{1}{2}p_t$  and  $P_{R_t}(q_i) < \frac{1}{2}p_t$ ). Suppose that case 2) does not occur: there does not exist a  $q_i$  such that  $\frac{q_i}{p_t} > \max(P_{L_t}(q_i), P_{R_t}(q_i))$ . Then, we have that

$$\max(P_{L_t}(p_i), P_{R_t}(p_i)) \geq \min(P_{L_t}(p_i), P_{R_t}(p_i)) \text{ and}$$

$$\max(P_{L_t}(p_i), P_{R_t}(p_i)) \geq q_i$$

Thus,  $\max(P_{L_t}(p_i), P_{R_t}(p_i)) \geq 1/3$  and by our assumption  $\max(P_{L_t}(p_i), P_{R_t}(p_i)) < \frac{1}{2}$ .

So, as in the proof of table 3 (5.3) in [18]

$$E_t \geq H(1/3, 2/3) \approx 0.92.$$

Now also suppose that case 1) does not occur.  $\implies E_t < 1 - 2\frac{p_r}{q_t}$   
 $\implies \frac{p_r}{q_t} < \frac{1-H(\frac{1}{3}, \frac{2}{3})}{2} \approx 0.04$

Suppose that  $\max(P_{L_t}(p_r), P_{R_t}(p_r)) \geq \frac{4}{5}p_t$  then we have

$$E_t \leq H(\frac{4}{5}, \frac{1-H(\frac{1}{3}, \frac{2}{3})}{2}, \frac{1}{5} - \frac{1-H(\frac{1}{3}, \frac{2}{3})}{2}) \approx 0.87 < H(\frac{1}{3}, \frac{2}{3}) \geq E_t$$

a contradiction.

Thus, if we do not have case 1) or 2), we must have case 3). Since this is our last remaining case, this completes the proof. □

**Theorem 3.3.2.**  $C_{ME} \leq H + 4$

*Proof.* This uses a similar style to the proof of theorem 4.4 in [4]. We will bind each  $E_t$  for each sub tree of our BST on a case by case basis using the cases of **Lemma 3.3.1**.

If case 1 occurs, we obviously have that

$$E_t \geq 1 - 2\frac{p_r}{p_t}$$

Note that this can only happen once for each word (a word can only be root once).

While it wasn't explicitly stated, in **Lemma 3.3.1** it was shown that if some  $p_i$  spans in the middle of the data set,  $P_{L_t}(p_i) \leq \frac{1}{2}p_t$  and  $P_{R_t}(p_i) \leq \frac{1}{2}p_t$ , then regardless of whether or not  $\frac{p_i}{p_t} > \max(P_{L_t}(p_i), P_{R_t}(p_i))$ , we can still show that case 1 occurs. Suppose for the remainder of the proof that there is no such middle-spanning  $p_i$ .

Let  $q_m$  be the unique middle gap (i.e.  $P_{L_t}(q_m) < \frac{1}{2}p_t$  and  $P_{R_t}(q_m) < \frac{1}{2}p_t$ ) when case 2 or 3 occurs. When case 2 occurs we have that:

$$E_t \geq H(\frac{1}{2} - \frac{1}{2}\frac{q_m}{p_t}, \frac{1}{2} + \frac{1}{2}\frac{q_m}{p_t}) \geq 2(\frac{1}{2} - \frac{1}{2}\frac{q_m}{p_t}) = 1 - \frac{q_m}{p_t}.$$

Note that by the definition of the ME Rule, when this occurs,  $q_m$  must be a leaf of depth at most 2. Thus, this condition can only happen twice for each  $q_m$ .

When case 2 does not occur (and we have a  $q_m$  spanning the middle) we must have case 3. This gives us:

$$E_t \geq H(\frac{1}{2} - \frac{1}{2}\frac{q_m}{p_t}, \frac{1}{2} + \frac{1}{2}\frac{q_m}{p_t}) \geq 1 - \frac{4}{5}(\frac{q_m}{p_t})^2 \text{ when } \frac{q_m}{p_t} < \frac{1}{2} \text{ (which must be true since case 2 did not occur).}$$

As in [4] we define a  $b_t$  for each sub tree  $t$  as follows:

let  $b_t = 2p_r$  for case 1.

let  $b_t = 2q_m$  for case 2.

let  $b_t = \frac{q_m^2}{p_t}$  for case 3.

Note that, in 1975 Bayer showed that:

$C = \sum_{t \in S_T} p_t$  and  $H = \sum_{t \in S_T} P_t E_t$  Where  $S_T$  is the set of all sub trees of our tree (**Lemma 2.3** [4]). Thus, we have

$$H = \sum_{t \in S_T} P_t E_t \geq \sum_{t \in S_T} P_t - \sum b_t = C - \sum b_t$$

$$\implies C \leq H + \sum b_t$$

As mentioned above, cases 1 and 2 can only occur once and twice respectively. Case 3 however, can occur many times, but each time it occurs,  $\frac{q_m}{p_t}$  must decrease by a factor of  $\frac{5}{4}$  since  $\max(P_{L_t}(p_r), P_{R_t}(p_r)) < \frac{4}{5}p_t$  (we recursively examine a smaller sub tree). Moreover, if  $\frac{q_m}{p_t} > \frac{1}{2}$  then we will have case 2. Let  $S_m$  be the set of all sub trees  $t$  for which  $q_m$  is the middle gap and case 3 only applies. We have that

$$C \leq H + \sum b_t = H + 2 \sum_{r=1}^n p_r + 2 \sum_{m=0}^n q_m + \sum_{m=0}^n \sum_{t \in S_m} \frac{4}{5} \frac{q_m^2}{p_t}$$

By factoring out  $q_m$  and examining only cases up to  $\frac{q_m}{p_t} = \frac{1}{2}$  we get:

$$\implies C \leq H + 2 + \sum_{m=0}^n \frac{4}{5} q_m \sum_{x=0}^{\infty} \frac{1}{2} * \left(\frac{4}{5}\right)^x$$

$$\implies C \leq H + 2 + \sum_{m=0}^n \frac{4}{5} q_m \left(\frac{1}{2} * \frac{1}{1-\frac{4}{5}}\right) \text{ (geometric series)}$$

$$\implies C \leq H + 4$$

□

# Chapter 4

## Approximate Binary Search in the Hierarchical Memory Model

### 4.1 The Hierarchical Memory Model

The Hierarchical Memory Model (HMM) was proposed in 1987 by Aggarwal et al. as an alternative to the classic RAM model [2]. It was intended to better model the multiple levels of the memory hierarchy. The model has an unlimited number of registers,  $R_1, R_2, \dots$  each with its own location in memory (positive integer). In the first version of the model, accessing a register at memory location  $x_i$  takes  $\lceil \lg(x_i) \rceil$  time. Thus, computing  $f(a_1, a_2, \dots, a_n)$  takes time  $\sum_{i=1}^n \lceil \lg(\text{location}(a_i)) \rceil$ . The original paper also considered arbitrary cost functions  $f(x)$ . We will use the cost function as was explained in Thite's thesis [32]. Here,  $\mu(a)$  is the cost of accessing memory location  $a$ . We have a series of memory sizes  $m_1, m_2, \dots, m_h$  where  $m_l$  has infinite size each with an associated cost  $c_1, c_2, \dots, c_h$ . We assume that  $c_1 < c_2 < \dots < c_h$ .

$$\mu(a) = c_i \text{ if } \sum_{j=1}^{i-1} m_j < a \leq \sum_{j=1}^i m_j.$$

While Thite notes that typical memory hierarchies have increasing sizes for slower memory levels, we explicitly assume that successive memory sizes divide one another evenly:

$$m_1 < m_2 < \dots < m_h \text{ and}$$

$$\forall i \in \{1, 2, \dots, h\}, m_i \mid m_{i+1}.$$

## 4.2 Thite's Optimum Binary Search Trees on the HMM Model

Thite's thesis provided solutions to several problems in the HMM and a related model [32]. He first provided an optimal solution to the following problem (known as **Problem 5** in the work):

**Problem [Optimum BST Under HMM].** Suppose we are given a set of  $n$  ordered keys  $x_1, x_2, \dots, x_n$  with associated probabilities of search  $p_1, p_2, \dots, p_n$ , as well as  $n + 1$  ranges  $(-\infty, x_1), (x_1, x_2), \dots, (x_{n-1}, x_n), (x_n, \infty)$  with associated probabilities of search  $q_0, q_1, \dots, q_n$ . The problem is to construct a binary search tree  $T$  over the set of keys and compute a memory assignment function  $\phi : V(T) \rightarrow 1, 2, \dots, n$  that assigns nodes of  $T$  to memory locations such that the expected cost of a search is minimized under the HMM model.

He provided three separate optimum solutions; **Parts**, **Trunks**, and **Split**. These algorithms have various use cases, running in times  $O(\frac{2^{h-1}}{(h-1)!} * n^{2h+1})$ ,  $O(\frac{2^{n-m_h} * (n-m_h+h)^{n-m_h} * n^3}{(h-2)!})$  and  $O(2^n)$  respectively. In the following sections, I will provide an approximate solution to this problem that runs in time  $O(n * \lg(m_1))$  and an upper bound on its expected search cost.

Thite also considered the same problem under the related HMM<sub>2</sub> model. This model assumes there are simply two levels of memory of size  $m_1$  and  $m_2$  with costs of access  $c_1$  and  $c_2$  where  $c_1 < c_2$ . Thite provided an optimal solution to this problem (named **TwoLevel**) which ran in time  $O(n^5)$ ,  $o(n^5)$  if  $m_1 \in o(n)$ , and  $O(n^4)$  if  $m_1 \in O(1)$ . He also gave an  $O(n \lg n)$  time approximate solution with an upper bounded expected search cost of  $c_2(H + 1)$ . The solution I provide which approximates the optimum tree under the HMM model also provides a strict improvement over Thite's approximate algorithm in both running time and expected cost under the HMM<sub>2</sub> model.

## 4.3 Efficient Near-Optimal Multiway Trees of Bose and Douïeb

In 2009, Bose and Douïeb's 2009 work provided a new construction method with linear running time (independent of the size of a node in tree) with the best expected cost to

date [10]. The group was able to prove that:

$$\frac{H}{\lg(2k-1)} \leq P_{OPT} \leq P_T \leq \frac{H}{\lg k} + 1 + \sum_{i=0}^n q_i - q_0 - q_n - \sum_{i=0}^m q_{rank[i]}$$

Here,  $H$  is the entropy of the probability distribution,  $P_{OPT}$  is the average path-length in the optimal tree,  $P_T$  is the average path length of the tree built using their algorithm and  $m = \max(n - 3P, P) - 1 \geq \frac{n}{4} - 1$ .  $P$  is the number of increasing or decreasing sequences in a left-to-right read of the access probabilities of the leaves. Moreover,  $q_{rank[i]}$  is the  $i^{th}$  smallest access probability among all leaves except  $q_0$  and  $q_n$ .

As described in the subsection TODO, we are given  $n$  ordered keys with weights  $p_0, \dots, p_n$  as well as  $n + 1$  weights of unsuccessful searches  $q_0, \dots, q_n$ . We often refer to "keys" representing the gaps as  $(x_{i-1}, x_i)$  to mean the "key" associated with a search between key  $x_{i-1}$  and  $x_i$ .

The algorithm occurs in three steps. First, a new distribution is created by distributing all leaf weight to internal nodes. The peaks and valleys of the probability distribution of the leaf weights is used to do this assignment. After this, the new probability distribution is made into a  $k$ -ary tree using a greedy recursive algorithm. The algorithm essentially chooses the  $l \leq k$  elements to go in the root node such that each child's subtree will have probability of access of at most  $1/k$ . They then reattach leaves to this internal key tree they have created. Their algorithm's design allows them to bound the depth of keys and leaves which ultimately allows them to achieve the bounds they have described.

## 4.4 Algorithm ApproxMWPaging

First, we need a lemma about converting a multiway search tree to a binary search tree. For the sake of clarity, we will call what are typically known as *nodes* of the multiway tree *pages*. This represents how various items of our search tree will fit onto pages. We maintain the notion of calling individual items *keys*.

**Lemma 4.4.1.** *Given a multiway tree  $T'$  with page size  $k$  and  $n$  keys, where keys are associated with a probability distribution of successful and unsuccessful searches as in Knuth's original optimum binary search tree problem, we can create a BST  $T$  where each key in a given page  $g$  of  $T'$  forms a connected component in  $T$  in  $O(n \lg(k))$  time.*

*Proof.* For each page  $g$ , we sort its keys and create a complete BST  $B$  over the keys. We create an ordering over all potential locations where keys could be added to the tree from

left to right. All keys in all descendant pages of a page in a specific subtree rooted at a child of  $g$  will lie in a specific range. There are at most  $k + 1$  of these ranges (since our page has at most  $k$  keys). These ranges will precisely correspond to the at most  $k + 1$  locations where a new child key could be added to  $B$ . We note that we cannot add new children to keys which correspond to unsuccessful searches. We order these locations from left to right and attach root keys from the newly created BST's of each of the ordered (left to right) children of  $g$ . These will all be valid connections since each child of  $g$  has keys in these correct ranges, and combining BST's in this fashion produces a valid BST. We perform a sort of  $O(k)$  items (in time  $O(k \lg(k))$ )  $O(n/k)$  times, and make  $O(n)$  new parent child connections, giving us total time  $O(n \lg(k))$ .  $\square$

In order to approximately solve the optimum BST problem under the HMM model, we will do the following:

1) First, we create a Multiway Tree  $T'$  using the algorithm of Bose and Douïeb. This takes  $O(n)$  time with our node size equal to  $m_1$ , the smallest level of our memory hierarchy [10].

2) Inside each page (node of the multiway tree), we create a balanced binary search tree (ignoring weights). We call each of these  $T'_k$  for  $k \in 1, \dots, \lceil n/m_1 \rceil$ . This takes  $O(m_1)$  time per page, of which there are at most  $O(n/m_1)$  giving us  $O(n)$  time total.

3) In order to make this into a proper binary search tree, we must connect the  $O(n/m_1)$  BST's we have made as described in the previous Lemma. This takes  $O(n \lg(m_1))$  time.

4) We pack things into memory in a breadth first search order in  $T$  starting from the root. This takes  $O(n)$  time.

*THIS IS THE OLD WAY. I THINK ITS NEEDED FOR TH BETTER MODEL BUT NOT FOR THIS. We pack things into memory in a breadth first search order in  $T'$  starting from the root. We do not leave gaps if pages are not full. The individual items of the pages of size at most  $m_1$  are stored in breadth first search order based on the trees made in step 2. This takes  $O(n/m_1)$  for the breadth first search of  $T'$ , and  $O(m_1)$  per page, of which there are  $O(n/m_1)$ , giving us  $O(n)$  time.*



We are left with a binary search tree which has been properly packed into our memory in total time  $O(nlg(m_1))$ .

## 4.5 Expected Cost ApproxMWPaging

First, we bound the depth of nodes in our BST  $T$ . The depth of a key  $x_i$  (denoted  $(x_{i-1}, x_i)$  for unsuccessful searches) is defined as  $d_T(x_i)$  ( $d_T(x_{i-1}, x_i)$ ).

**Lemma 4.5.1.** *For a key  $x_i$ ,*

$$d_T(x_i) \leq \lceil lg(m_1) \rceil * \lfloor log_{m_1}(\frac{1}{p_i}) \rfloor.$$

*For a key  $(x_{i-1}, x_i)$ ,*

$$d_T(x_{i-1}, x_i) \leq \lceil lg(m_1) \rceil * (\lfloor log_{m_1}(\frac{2}{q_i}) \rfloor + 1).$$

*Proof.* First we note that in the tree  $T'$  we build using Bose and Douïeb's multiway tree algorithm, the maximum depth of keys (call this  $d'_T(x_i), d'_T(x_{i-1}, x_i)$ ) for a page size  $m_1$  is [10]:

$$d_T(x_i) \leq \lfloor log_{m_1}(\frac{1}{p_i}) \rfloor.$$

$$d_T(x_{i-1}, x_i) \leq \lfloor log_{m_1}(\frac{2}{q_i}) \rfloor + 1.$$

As explained in the paper, these follow from Lemmas 1 and 2 of Bose and Douïeb [10].

Within a page, we make a balanced (ignoring weight) BST, so each key has a depth *within* a page of at most  $\lceil lg(m_1) \rceil$ .

Since our algorithm always connects the root of the BST made for page to a key in the BST made for the page's parent, a key  $x_i$  has a depth of at most  $\lfloor log_{m_1}(\frac{1}{p_i}) \rfloor$  in terms of pages accessed ( $\lfloor log_{m_1}(\frac{2}{q_i}) \rfloor + 1$  pages for keys  $((x_{i-1}, x_i))$ ). Within a page, we will examine at most  $\lceil lg(m_1) \rceil$  keys. Thus, a key's depth is at most the bound described.  $\square$

We now describe the cost of searching for a key located at deepest part of tree  $T$ :  $W$ . Let  $m'_j = \sum_{k \leq j} m_k$ . We define  $m'_0 = 0$ . Let  $l$  be the smallest  $j$  such that  $m'_j > n$ .  $l$  represents how many levels of memory will be required for storing our tree. Let  $H(T)$  represent the height of our tree.

**Lemma 4.5.2.**  $W \leq \sum_{k=1}^{l-1} (\lfloor \lg(m'_k + 1) \rfloor - \lfloor \lg(m'_{k-1} + 1) \rfloor) * c_k + (H(T) - \lfloor \lg(m'_{l-1} + 1) \rfloor) * c_l$

*Proof.* Consider the accessing each key along the path from the root to the deepest key in  $T$ . Note that we will have to examine  $H(T)$  keys in order to access the deepest leaf in the tree. We will access one key at depth 0, one key at depth 1 and so on. Because the tree is packed into memory in BFS order, a key at depth  $i$  will be at memory location at most  $2^i - 1$ . Now, consider how many levels of the binary search tree  $T$  will fit inside of  $m_1$ , the fastest memory. In order for all keys of depth  $i$  (and higher) to be in  $m_1$  we need:

$$2^i - 1 \leq m_1 \implies i \leq \lg(m_1 + 1).$$

Thus, at least  $\lfloor \lg(m_1 + 1) \rfloor$  levels of  $T$  fit on  $m_1$ . Next we examine how many fit on  $m_j$  for  $1 < j < l$ . The last level to completely fit on  $m_j$  or higher memories is the maximum  $i$  such that:

$$2^{i+1} - 1 \leq m'_j \implies i \leq \lg(m'_j + 1).$$

Thus, at least  $\lfloor \lg(m'_j + 1) \rfloor$  levels of  $T$  fit on  $m_j$  or higher levels of memory.

Thus, on our search for the deepest key in the tree, we will make at least  $\lfloor \lg(m_1 + 1) \rfloor$  checks for elements located at memory  $m_1$ . This will cost a total of

$$\lfloor \lg(m_1 + 1) \rfloor * c_1.$$

For each memory level  $m_j$  for  $1 < j < l$ , we will make at least  $\lfloor \lg(m'_j + 1) \rfloor$  checks in  $m_j$  or higher memories. Of these checks, at least  $\lfloor \lg(m'_{j-1} + 1) \rfloor$  will be in memory levels strictly higher up in the memory hierarchy than  $j$ . Since  $c_j > c_i$  for  $j > i$ , an upper bound on the cost of searching for all elements in memory level  $j$  on the path from the root to the deepest element of the tree is:

$$(\lfloor \lg(m_1 + 1) \rfloor - \lfloor \lg(m'_{j-1} + 1) \rfloor) * c_j.$$

Finally, we can upper bound the cost by assuming that all remaining searches take place at  $c_l$ . The searches at level  $l$  will cost at most:

$$(\lg(H(T) - \lfloor \lg(m'_{l-1} + 1) \rfloor)) * c_l.$$

Combining the above three equations gives the desired bound.

□

Next, we note that the cost of search for a key at some depth  $i$  is at most  $\frac{i}{H(T)} * W$ .

**Lemma 4.5.3.** *The cost of searching for a keys  $x_i$  and  $(x_{i-1}, x_i)$  ( $C(x_i)$  and  $C(x_{i-1}, x_i)$  respectively) can be bounded as follows:*

$$C(x_i) \leq \frac{\lceil \lg(m_1) \rceil * \frac{\lg(\frac{1}{p_i})}{\lg(m_1)}}{\lceil \lg(2n+2) \rceil} * W$$

$$C(x_{i-1}, x_i) \leq \frac{\lceil \lg(m_1) \rceil * \lceil \log_{m_1}(\frac{2}{q_i}) \rceil}{\lceil \lg(2n+2) \rceil} * W$$

*Proof.* From Lemma 4.5.1 we have a bound on the depth of keys  $x_i$  and  $(x_{i-1}, x_i)$ . Moreover, we know that since there are  $2n + 1$  keys in our tree, our tree must have a height of at least:

$$\lceil \lg(2n + 2) \rceil.$$

Note that since our tree is stored in BFS order in memory, whenever we examine a key's child, it will be at a memory location of at least the same, if not higher cost (by being in the same or a deeper page). Thus, the path from the root to a specific key can be upper bounded by the cost of searching for the deepest element in the tree, multiplied by the fraction of the way down the tree  $x_i$  or  $(x_{i-1}, x_i)$  are. Note that when searching for keys, we must search along the entire path from root to the key in question, while we need only examine the path from the root to the parent of a key for unsuccessful  $(x_{i-1}, x_i)$  searches. Combining 4.5.1 and 4.5.4 with the minimum height of our tree gives:

$$\begin{aligned} C(x_i) &\leq \frac{\lceil \lg(m_1) \rceil * \lceil \log_{m_1}(\frac{1}{p_i}) \rceil}{\lceil \lg(2n+2) \rceil} * W \\ \implies C(x_i) &\leq \frac{\lceil \lg(m_1) \rceil * \frac{\lg(\frac{1}{p_i})}{\lg(m_1)}}{\lceil \lg(2n+2) \rceil} * W \end{aligned}$$

$$\begin{aligned} \text{Similarly,} \\ C(x_{i-1}, x_i) &\leq \frac{\lceil \lg(m_1) \rceil * \lceil \log_{m_1}(\frac{2}{q_i} + 1 - 1) \rceil}{\lceil \lg(2n+2) \rceil} * W \\ C(x_{i-1}, x_i) &\leq \frac{\lceil \lg(m_1) \rceil * \frac{\lg(\frac{2}{q_i})}{\lg(m_1)}}{\lceil \lg(2n+2) \rceil} * W. \end{aligned}$$

This completes the proof. □

We can now bound the expected cost of search using the bounds for each key.

**Theorem 4.5.4.**  $C \leq (\frac{\lceil \lg(m_1) \rceil}{\lceil \lg(2n+2) \rceil * \lg(m_1)} * W) * (H + 1)$

*Proof.* The total expected cost of search is simply the sum of the weighted cost of search for all keys. Given our last lemma, we have that:

$$C \leq \sum_{i=1}^n p_i * C(x_i) + \sum_{j=1}^{n+1} q_j * C(x_{i-1}, x_i)$$

$$\implies C \leq \sum_{i=1}^n p_i * \frac{\lceil \lg(m_1) \rceil * \lg(\frac{1}{p_i})}{\lceil \lg(2n+2) \rceil} * W + \sum_{j=1}^{n+1} q_j * \frac{\lceil \lg(m_1) \rceil * \lg(\frac{2}{q_j})}{\lceil \lg(2n+2) \rceil} * W$$

$$\implies C \leq (\frac{\lceil \lg(m_1) \rceil}{\lceil \lg(2n+2) \rceil * \lg(m_1)} * W) * (\sum_{i=1}^n p_i * \lg(\frac{1}{p_i}) + \sum_{j=1}^{n+1} (q_j * \lg(\frac{2}{q_j})))$$

$$\implies C \leq (\frac{\lceil \lg(m_1) \rceil}{\lceil \lg(2n+2) \rceil * \lg(m_1)} * W) * (\sum_{i=1}^n p_i * \lg(\frac{1}{p_i}) + \sum_{j=1}^{n+1} (q_j * \lg(\frac{1}{q_j})) + 1)$$

$$\implies C \leq (\frac{\lceil \lg(m_1) \rceil}{\lceil \lg(2n+2) \rceil * \lg(m_1)} * W) * (H + 1). \quad \square$$

## 4.6 Approximate Binary Search Trees of De Prisco and De Santis with Extensions by Bose and Douïeb

As in the classic Knuth problem, we are given a set of  $n$  probabilities of searching for words  $(p_1, p_2, \dots, p_n)$ , as well as  $n + 1$  probabilities of unsuccessful searches  $(q_0, q_1, \dots, q_n)$ . The duo provides an algorithm which constructs a binary search tree in  $O(n)$  time with an expected cost of at most [11]

$$H + 1 - q_0 - q_n + q_{max}$$

where  $q_{max}$  is the maximum probability of an unsuccessful search. This was later modified by Bose and Douïeb (the same paper described in section TODO) to have an improved bound [10]

$$P_T \leq H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} p q_{rank[i]}$$

$P_T$  is the average path length of the tree built using their algorithm and  $m' = \max(2n - 3P, P) - 1 \geq \frac{n}{2} - 1$ .  $P$  is the number of increasing or decreasing sequences in a left-to-right read of the access probabilities of the leaves. Moreover,  $p_{q_{rank}[i]}$  is the  $i^{th}$  smallest access probability among all keys and leaves except  $q_0$  and  $q_n$ .

First, I explain the algorithm of De Prisco and De Santis and then explain the extensions of Bose and Douïeb. De Prisco and De Santis' algorithm occurs in three phases.

In **Phase 1**, an auxiliary probability distribution is created using  $2n$  zero probabilities, along with the  $2n + 1$  successful and unsuccessful search probabilities. Yeung's linear time alphabetic search tree algorithm is used with the  $2n + 1$  successful and unsuccessful search probabilities used as leaves of the new tree created. This is referred to as the *starting tree*.

In **Phase 2** what's known as the *redundant tree* is created by moving  $p_i$  keys up the *starting tree* to the lowest common ancestor of keys  $q_{i-1}$  and  $q_i$ . The keys which used to be called  $p_i$  are relabelled to *old.p<sub>i</sub>*.

In **Phase 3** the *derived tree* is constructed from the *redundant tree* by removing redundant edges. Edges to and from nodes which represented zero probability keys are deleted. This derived tree is a binary search tree with the expected search cost described.

In Bose and Douïeb's work, they explain how they can substitute their algorithm for Yeung's linear time alphabetic search tree algorithm which results in a better bound (as described above). We use the updated version (by Bose and Douïeb) of De Prisco and De Santis' algorithm as a subroutine in the sections to follow.

## 4.7 Algorithm ApproxBSTPaging

Our second solution to create an approximately optimum BST under the HMM model works as follows:

1) First, we create an approximately optimal BST  $T$  using the algorithm of De Prisco and De Santis [11] (as updated by Bose and Douïeb [10]). This takes  $O(n)$  time.

2) In a similar fashion to step 4) of *ApproxMWPaging*, we pack things into memory in a breadth first search order of  $T$  starting from the root. This relative simple traversal also takes  $O(n)$  time.

We are left with a binary search tree which has been properly packed into our memory in total time  $O(n)$ .

## 4.8 Expected Cost ApproxBSTPaging

As explained in the Bose and Douïeb paper, the average path length search cost of the tree created by their algorithm is at most:

$$[10] P_T \leq H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]}$$

Similar to the previous section, if we can bound the cost of search for a given path length, then we can form a bound on the average cost of search in the HMM model. Consider  $min_{p,q}$  for our probability distribution. It is implicitly shown in the work of Bose and Douïeb that:

As before, we can describe the cost of searching for a key located at deepest part of tree  $T$ :  $W$ . Recall,  $m'_j = \sum_{k \leq j} m_k$ ,  $m'_0 = 0$  and let  $l$  be the smallest  $j$  such that  $m'_j > n$ .

**Lemma 4.8.1.**

$$W \leq \sum_{k=1}^{l-1} ([lg(m'_k + 1)] - [lg(m'_{k-1} + 1)]) * c_k \\ + (H(T) - [lg(m'_l + 1)]) * c_l$$

*Proof.* Since we are simply putting things into memory in BFS order, and all we use is the height of the tree and the memory hierarchy, the proof is identical to that of **Lemma 4.5.3**.  $\square$

Next, we note that the cost of search for a key at some depth  $i$  is at most  $\frac{i}{H(T)} * W$ . This must be true because the cost of examining nodes can only increase as we move down the tree because of the increasing property of the cost of access of our various levels of memory and our BFS packing algorithm. Since, we also know the expected path length of our tree we can show that:

**Theorem 4.8.2.**  $C \leq (\frac{W}{H(T)}) * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]})$

*Proof.* Bose and Douieb show that after using their algorithm for Phase 1 of De Prisco and De Santis algorithm, every leaf of the *starting tree* (all keys representing successful and unsuccessful searches) are at depth at most  $\lfloor \lg(\frac{1}{p}) \rfloor + 1$  for at least  $\{2n - 3P, P\} - 1$  of  $p \in \{\{p_1, p_2, \dots, p_n\} \cup \{q_0, q_1, \dots, q_n\}\}$  and  $\lfloor \lg(\frac{1}{p}) \rfloor + 2$  for all others. Recall that  $P$  is the number of peaks in the probability distribution  $q_0, p_1, q_1, \dots, p_n, q_n$ . Moreover, after phases two and three of the algorithm, each key has its depth decrease by 2, and all leaves (except one) move up the tree by one. Now, let  $C_d(i)$  represent the cost of accessing a node at depth  $i$ . As mentioned above, this is at most  $\frac{i}{H(T)} * W$ . Using this, we can derive the following equation an upper bound on the expected cost of search:

$$\begin{aligned} C &\leq \sum_{i=1}^n (p_i * \frac{depth(p_i)}{H(T)} * W) + \sum_{i=0}^n (q_i * \frac{(depth(q_i)-1)}{H(T)} * W) \\ \implies C &\leq \frac{W}{H(T)} (\sum_{i=1}^n (p_i * depth(p_i)) + \sum_{i=0}^n (q_i * (depth(q_i) - 1))) \\ \implies C &\leq \frac{W}{H(T)} (\sum_{i=1}^n (p_i * depth(p_i)) + \sum_{i=0}^n (q_i * (depth(q_i) - 1))) \\ \implies C &\leq \frac{W}{H(T)} (\sum_{i=1}^n (p_i * \lfloor \lg(\frac{1}{p_i}) \rfloor) + \sum_{i=0}^n (q_i * \lfloor \lg(\frac{1}{q_i}) \rfloor - 1 + 1)) \end{aligned}$$

Note that the expected cost is equal to the expected path length for each key, multiplied by the cost of search for each key. Since we have an upper bound on the cost of search for an element at some depth  $i$ , and an upper bound on the expected path length TODO  $\square$

IS IT DEPTH + 1 FOR THE KEYS? SHOULD WE BE DOING AN EXTRA ACCESS FOR LEAVES RELATIVE TO HOW THEY DID IT BEFORE.

## 4.9 Improvements over Thite in the HMM<sub>2</sub> Model

The HMM<sub>2</sub> model is the same as the general HMM model with the added constraint that there are only two types of memory (slow and fast). In Thite's thesis, he proposed both an optimal solution to the problem, as well as an approximate solution that runs in time  $O(n \lg(n))$  [32]. I show that my solution is at least as good, and may be better in certain situations. First I give an alternate bound to my expected cost which is similar to the one presented in Thite's work.

**Lemma 4.9.1.** Let  $m'_j = \sum_{k \leq j} m_k$ . We define  $m'_0 = 0$ . Let  $l$  be the smallest  $j$  such that  $m'_j > n$ . Then the cost of search:

$$C \leq c_l * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]}).$$

*Proof.* By using the ApproxBSTPaging algorithm, we can simply assume all key accesses happen in the most expensive type of memory ( $m_l$ ). Thus, our expected cost can be bounded by an upper bound on the average path length, multiplied by this upper bound on our cost of accessing each item.  $\square$

Moreover, for both ApproxMWPaging and ApproxBSTPaging:

**Lemma 4.9.2.** Suppose  $\sum_{k=1}^{l-1} (c_{i+1} - c_i) * (\lfloor \lg(m'_i + 1) \rfloor) > \lfloor \lg(m'_1 + 1) \rfloor * c_1$ . Then  $W < c_l * H(T)$ .

$$\begin{aligned} \text{Proof. } W &\leq \sum_{k=1}^{l-1} (\lfloor \lg(m'_k + 1) \rfloor - \lfloor \lg(m'_{k-1} + 1) \rfloor) * c_i \\ &+ (\text{height}(T) - 1 - \lfloor \lg(m'_{k-1} + 1) - 1 \rfloor) * c_l \end{aligned}$$

Rearranging the formula gives:

$$\implies W \leq H(T) * c_l + \lfloor \lg(m'_1 + 1) \rfloor - \sum_{k=1}^{l-1} (c_{k+1} - c_k) \lfloor \lg(m'_k + 1) \rfloor$$

Thus, as long as  $\sum_{k=1}^{l-1} (c_{k+1} - c_k) \lfloor \lg(m'_k + 1) \rfloor > \lfloor \lg(m'_1 + 1) \rfloor$  then we will get our desired result.  $\square$

Note that our assumption will generally be true since  $c_l > c_{l-1} > \dots > c_1$  and  $m_l > m_{l-1} > \dots > m_1$ . Finally, we can see that:

**Theorem 4.9.3.** Suppose  $\sum_{k=1}^{l-1} (c_{i+1} - c_i) * (\lfloor \lg(m'_i + 1) \rfloor) > \lfloor \lg(m'_1 + 1) \rfloor * c_1$ . Then  $C < c_l * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]})$

*Proof.*  $C \leq (\frac{W}{H(T)}) * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]})$  Assuming  $\sum_{k=1}^{l-1} (c_{i+1} - c_i) * (\lfloor \lg(m'_i + 1) \rfloor) > \lfloor \lg(m'_1 + 1) \rfloor * c_1$  and using **Lemma 4.9.2** gives:

$$\implies C < (\frac{c_l * H(T)}{H(T)}) * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]})$$

$$\implies C < c_l * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]}) \quad \square$$



TODO UNDERSTAND WHY THIS ISN'T A DIRECT IMPROVEMENT. I'M CONFUSED

Subbing our assumption into the HMM<sub>2</sub> model gives:  $(c_2 - c_1) * (\lfloor \lg(m_1 + 1) \rfloor) > \lfloor \lg(m_1 + 1) \rfloor * c_1$   
 $\implies c_2 > 2 * c_1$

which is a valid assumption in many types of memory hierarchies.

**Corollary.**  $C < c_2 * (H + 1 - q_0 - q_n + q_{max} - \sum_{i=0}^{m'} pq_{rank[i]})$   
*whenever  $c_2 > 2 * c_1$*

In many types of memory hierarchies, this will provide an improvement over Thite's bound of:

$$C < c_2 * (H + 1)$$

especially in the case where  $c_2 \gg c_1$ .

# Chapter 5

## Approximate Binary Search in the Hierarchical Memory with Block Transfer Model

### 5.1 Hierarchical Memory with Block Transfer Model

This model (HMBTM for short) was proposed by Aggarwal, Chandra, and Snir as an improvement over the HMM model [2] discussed previously [3]. The model with block transfer still has a memory hierarchy with increasing costs of access, but allows for any contiguous block of memory to be copied from one location to another with constant unit time per element after the initial access. This provides a better model for standard computers which can copy many words from one type of memory to another after accessing a single word. Like the HMM model, we have an unlimited number of registers (numbered 1, 2, , .. etc.) and we will still use the cost function as was explained in Thite's thesis [32]. Here,  $\mu(a)$  is the cost of accessing memory location  $a$ . We have a series of memory sizes  $m_1, m_2, \dots, m_h$  where  $m_l$  has infinite size each with an associated cost  $c_1, c_2, \dots, c_h$ . We assume that  $c_1 < c_2 < \dots < c_h$ .

$$\mu(a) = c_i \text{ if } \sum_{j=1}^{i-1} m_j < a \leq \sum_{j=1}^i m_j.$$

We explicitly assume that successive memory sizes divide one another evenly:

$$m_1 < m_2 < \dots < m_h \text{ and}$$

$$\forall i \in \{1, 2, \dots, h\}, m_i \mid m_{i+1}.$$

In this new model, we are given the additional operational opportunity to move a block from one location to another. Specifically, a block copy operation is defined as:

$$[x - l, x] \rightarrow [y - l, y].$$

The contents of  $\mu(x - i)$  are copied to  $\mu(y - i)$  for  $i \in \{0, \dots, l\}$ . This is valid if the two intervals are disjoint. This copy operation costs  $\max(f(x, y)) + l$ .

I provide fast but approximate solutions to the optimum BST problem under new model in the following sections.

## 5.2 ApproxMWPaging with BT

The first algorithm I provide is very similar to ApproxMWPaging. The first three steps of the algorithm are in fact identical. To review, we create a Multiway Tree  $T'$  using the algorithm of Bose and Douieb, form balanced BST's within each page of  $T'$ , and then connect these balanced BSTs from  $T'$  to form a valid BST  $T$ . This is done in  $O(n \lg(m_1))$  time.

To decide packing order, we will do a modified BFS of  $T'$ . We will always pack individual pages of  $T'$  into memory in a BFS of the balanced BST formed from the page.

BT-Range-Pack packs the tree  $T$  using  $r\_q$  as roots from memory location  $loc$ . It packs recursively into pages of size  $m_i$  (or smaller if necessary) until  $m_{i+1}$  nodes have been packed or we run out of roots to pack from in  $r\_q[]$ . If  $i = 0$  then we only pack  $amt$  nodes (so we can fill memory levels appropriately). Note that we only remove the top root from  $r\_q$  if the root has been completely used i.e. it has been packed into a page of size  $\leq m_1$ . We always return a pair, the updated  $r\_q$  which contains new roots to search packed from (added in BFS order from leaves of  $m_1$  or smaller packed "pages") and the current location in memory where we should pack into next.

We call BT-Pack() in order to pack nodes into the tree. Essentially, this function attempts to pack each level of the memory hierarchy independently from  $m_1$  to  $m_l$ . Within each memory level  $i$ , we attempt to pack it from a single source (the next available node in BFS order of our tree) in blocks of size  $m_{i-1}$  which are recursively packed in blocks of size  $m_{i-2}$ . If we cannot fill a memory level, or a specific block within the packing of a memory

level, we will pack whatever we can starting again from a new root (still in BFS order) passing into our BT-Range-Pack function the biggest  $i$  possible such that  $m_i$  will still fit in the page we are trying to pack.

We are left with a binary search tree which has been properly packed into our memory in total time  $O(n * l)$ .

---

**Algorithm 1** ApproxPaging with BT Packing

---

```

1: procedure BT-RANGE-PACK( $r\_q[], i, loc, amt$ )
2:   if  $i = 0$  then
3:     Create largest BFS tree  $T$  possible from  $r\_q[0]$  with at  $\min(m_1, amt)$  nodes
4:     Push  $T$  in BFS order into memory starting from memory location  $loc$ 
5:      $loc += size(T)$ 
6:      $r\_q.pop()$ 
7:     for each leaf  $l$  in  $T$  in BFS order do
8:       Push all children of  $l$  onto  $r\_q$ 
9:     end for
10:    return ( $r\_q[], loc$ )
11:  else
12:     $total = 0$ 
13:    while  $total < m_{i+1}$  and  $\neg(empty? r)$  do
14:       $old\_loc = loc$ 
15:       $i = \max_{0, \dots, j+1}(i : m_i + total < m_{j+1})$ 
16:       $(loc, new\_r\_q) = \text{AMWBT-Range-Pack}(r\_q[0, \dots, 0], i - 1, loc, m_i)$ 
17:      for each node  $r$  in  $new\_r\_q$  do
18:         $r\_q.push(r)$ 
19:      end for
20:       $total += loc - old\_loc$ 
21:    end while
22:    return ( $r\_q[], loc$ )
23:  end if
24: end procedure

```

---

---

**Algorithm 2** ApproxPaging with BT Packing

---

```
1: procedure BT-PACK
2:    $r\_q = \text{empty}$ 
3:    $r\_q.\text{push\_back}(\text{root})$ 
4:    $loc = 0$ 
5:   for  $j = 0$  to  $l - 1$  do
6:     while  $loc < m_{j+1}$  and  $\neg(\text{empty?}r\_q)$  do
7:       if  $loc + m_1 < m_{j+1}$  then
8:          $i = \max_{0, \dots, j+1}(i : m_i + \text{total} < m_{j+1})$ 
9:          $(loc, \text{new\_}r\_q) = \text{AMWBT-Range-Pack}([r\_q[0]], i - 1, loc, m_i)$ 
10:      else
11:         $(loc, \text{new\_}r\_q) = \text{AMWBT-Range-Pack}([r\_q[0]], 0, loc, m_i)$ 
12:      end if
13:       $r\_q.\text{pop}()$ 
14:      for each node  $r$  in  $\text{new\_}r\_q$  do
15:         $r\_q.\text{push}(r)$ 
16:      end for
17:    end while
18:  end for
19: end procedure
```

---

### 5.3 ApproxMW Paging with BT Running Time

First, we examine the runtime of  $\text{BT-Range-Pack}(r\_q[], i, loc, amt)$ .

**Lemma 5.3.1.** *BT-Range-Pack( $r\_q[], i, loc, amt$ ) returns an updated location, call it  $\text{new\_loc}$  in time at most  $O((i+1) * (\text{new\_loc} - loc))$  time and packs  $(\text{new\_loc} - loc)$  nodes into memory.*

*Proof.* I will prove this by induction on  $i$ . In the base case ( $i = 0$ ) we simply do a BFS from the given root, packing as many of  $\min(m_1, amt)$  into memory as possible, we return an updated  $loc$  which is exactly equal to the size of the BFS tree we have created. We also push all children of all leaves of this BFS tree onto our  $r\_q$ . This all takes time  $(\text{new\_loc} - loc) \in O(1 * (\text{new\_loc} - loc))$  as required.

Suppose  $\text{BT-Range-Pack}(r\_q[], i, loc, amt)$  returns  $new\_loc$  in time at most  $O(l * (new\_loc - loc))$  and packs  $(new\_loc - loc)$  nodes into memory for all  $i < k$ . Consider  $\text{BT-Range-Pack}(r\_q[], k, loc, amt)$ . Since  $i \neq 0$  we enter the else case on line 11. Now, we may call  $\text{BT-Range-Pack}$  a number of times, but the sum of  $loc$  updates will be at most  $m_{i+1}$ . By our induction hypothesis, we know each  $\text{BT-Range-Pack}(r\_q[], i, loc, amt)$  for  $i < k$  packs sum number  $(new\_loc - loc)$  of nodes into memory in time  $O((i + 1) * (new\_loc - loc))$ . Moreover, other than the recursive calls, all lines take  $O(1)$  except line 15 which takes  $O(i)$  and lines 17-18 which take  $(new\_loc - loc)$  time since only a linear amount of children can be pushed onto  $r\_q$  for each item packed into memory (and each child can only be pushed to  $r\_q$  once, by its single parent). Let  $S$  be the set of all calls  $q$   $\text{BT-Range-Pack}(r\_q[], q_i, loc, amt)$  is called directly from our original  $\text{BT-Range-Pack}(r\_q[], k, loc, amt)$  call and packs  $q\_amt$  items into memory. Let  $T_{RP}(i, new\_loc - loc)$  be the cost of  $\text{BT-Range-Pack}(r\_q[], i, loc, amt)$  which packs  $new\_loc - loc$  items into memory. Then we have that:

$$\begin{aligned}
T_{RP}(k, new\_loc - loc) &= O(new\_loc - loc) + O(i) + \sum_{q \in S} T_{RP}(q_i, q\_amt) \\
\text{By our induction hypothesis we have that:} \\
\implies T_{RP}(k, new\_loc - loc) &\in O(new\_loc - loc) + O(i) + \sum_{q \in S} O(q_i * q\_amt) \\
\text{Since } q_i \text{ is at most } i \text{ we have:} \\
\implies T_{RP}(k, new\_loc - loc) &\in O(new\_loc - loc) + O(i) + i * \sum_{q \in S} q\_amt \\
\text{Finally, since } new\_loc - loc &= \sum_{q \in S} q\_amt: \\
\implies T_{RP}(k, new\_loc - loc) &\in O(new\_loc - loc) + O(i) + i * (new\_loc - loc) \\
\implies T_{RP}(k, new\_loc - loc) &\in O((new\_loc - loc) * (i + 1)) \text{ as required.} \quad \square
\end{aligned}$$

This leads us to our runtime for  $\text{BT-Pack}()$ .

**Lemma 5.3.2.** *BT-Pack packs all nodes in our tree  $T$  into memory in time  $O(n * l)$ .*

*Proof.* First note that, as in  $\text{BT-Range-Pack}$ , we always update  $loc$  to be the new location where should pack nodes into memory. Lines 5 – 18 loop through each memory level. For a given level, we pack as much as can into it, using as large  $\text{BT-Range-Pack}$ 's as possible. Specifically, line 8 takes  $O(l)$  and lines 14 – 15 take  $(new\_loc - loc)$  time since only a linear amount of children can be pushed onto  $r\_q$  for each item packed into memory (and each child can only be pushed to  $r\_q$  once, by its single parent). Let  $S_h$  be the set of all calls  $q$   $\text{BT-Range-Pack}(r\_q[], q_i, loc, amt)$  called from our  $\text{BT-Pack}$  when  $j = h$  (these each pack  $q\_amt$  of nodes into memory). Let  $packed\_amt$  be the amount packed by a call to  $\text{BT-Range-Pack}$  in lines 9 or 11. By our previous proof, these take time  $O((packed\_amt) * (i))$ . Since  $i$  is at most  $l$  and  $sumpacked\_amt = n$  (we never pack

anything twice) we have that the time required for BT-Pack  $T_P$  is:

$$\begin{aligned}
T_P &\in \sum_{j=0}^{l-1} \text{sum}_{q \in S_j} O(q\_amt * j) \\
\implies T_P &\in o(l) * \sum_{j=0}^{l-1} \text{sum}_{q \in S_j} O(q\_amt) \\
\implies T_P &\in O(n * l) \text{ as required.}
\end{aligned}$$

□

## 5.4 Search with ApproxMWPaging with BT

---

### Algorithm 3 ApproxMWPaging with BT Search

---

```

1: procedure AMWBT-SEARCH(mem, key, prev_moved_s, offset_s)
2:   if ( $\neg(\text{empty?prev\_moved\_s})$  and ( $\text{mem} \geq \text{prev\_moved\_s.top}()$ )) or ( $\text{mem} \geq m_1$ ) then
3:     if ( $\neg(\text{empty?prev\_moved\_s})$  and ( $\text{mem} \geq \text{prev\_moved\_s.top}()$ )) then
4:        $\text{mem}+ = \text{offset\_s.top}()$ 
5:        $\text{offset\_s.pop}()$ 
6:        $\text{prev\_moved\_s.pop}()$ 
7:       if  $\text{neq}(\text{empty?offset\_s})$  then
8:          $\text{mem}- = \text{offset\_s.top}()$ 
9:       end if
10:    end if
11:     $\text{offset\_s.push}(\text{mem})$ 
12:     $i = \min_{m'_i: m'_i > \text{mem}}$ 
13:     $\text{amt\_move} = m'_i - \text{mem}$ 
14:     $\text{prev\_moved\_s.push}(\text{amt\_move})$ 
15:     $[\text{mem}, \text{mem} + \text{amt\_move} - 1] \rightarrow [0, \text{amt\_move} - 1]$ 
16:    AMWBT-Search(0, key, prev_moved_s, offset_s)
17:  else
18:     $\text{offset} = 0$ 
19:    if  $\neg(\text{empty?prev\_s\_moved})$  and ( $\text{mem} \geq \text{prev\_moved\_s.top}()$ ) then
20:       $\text{offset} = \text{offset\_s.top}()$ 
21:    end if
22:    if  $\text{key} = \text{mem.key}$  then
23:      return  $\text{mem.value}$ 
24:    else if  $\text{key} < \text{mem.key}$  then
25:      if mem has no left child then
26:        return mem
27:      else
28:        AMWBT-Search( $\text{mem.left\_child} - \text{offset}$ , key, prev_moved_s, offset_s)
29:      end if
30:    else
31:      if mem has no right child then
32:        return mem
33:      else
34:        AMWBT-Search( $\text{mem.right\_child} - \text{offset}$ , key, prev_moved_s, offset_s)
35:      end if
36:    end if
37:  end if
38: end procedure

```

---



To run we call `AMWBT-Search(0, key, empty, empty)` since the memory location of the root should be 0.

## 5.5 Expected Cost ApproxMWPaging with BT

How a path has cost What cost is similar arg to ApproxMWPaging

## 5.6 ApproxBSTPaging with BT

Given what we have already shown, this algorithm is extremely simple to explain. We first create a BST  $T$  using the algorithm of De Prisco and De Santis [11] (as updated by Bose and Douieb [10]) in  $O(n)$  time (as was the first step in ApproxBSTPaging). We then simply call `BT-Pack()` in order to pack the tree into memory as described in the ApproxMWPaging with BT sections.

## 5.7 Expected Cost ApproxBSTPaging with BT

How a path has cost What cost is similar arg to ApproxMWPaging

## Chapter 6

# Conclusion and Open Problems

### 6.1 Discussion

### 6.2 Conclusion

# APPENDICES

# Appendix A

## Matlab Code for Making a PDF Plot

# References

- [1] M AdelsonVelskii and Evgenii Mikhailovich Landis. An algorithm for the organization of information. Technical report, DTIC Document, 1963.
- [2] Alok Aggarwal, Bowen Alpern, Ashok Chandra, and Marc Snir. A model for hierarchical memory. In *Proceedings of the nineteenth annual ACM symposium on Theory of computing*, pages 305–314. ACM, 1987.
- [3] Alok Aggarwal, Ashok K Chandra, and Marc Snir. Hierarchical memory with block transfer. In *Foundations of Computer Science, 1987., 28th Annual Symposium on*, pages 204–216. IEEE, 1987.
- [4] Paul Joseph Bayer. *Improved bounds on the costs of optimal and balanced binary search trees*. Massachusetts Institute of Technology, Project MAC, 1975.
- [5] R Bayer and E McCreight. Organization and maintenance of large ordered indices. In *Proceedings of the 1970 ACM SIGFIDET (now SIGMOD) Workshop on Data Description, Access and Control*, pages 107–141. ACM, 1970.
- [6] Rudolf Bayer. Symmetric binary b-trees: Data structure and maintenance algorithms. *Acta informatica*, 1(4):290–306, 1972.
- [7] Peter Becker. A new algorithm for the construction of optimal b-trees. *Algorithm Theory SWAT’94*, pages 49–60, 1994.
- [8] Peter Becker. Construction of nearly optimal multiway trees. In *Computing and Combinatorics*, pages 294–303. Springer, 1997.
- [9] Andrew Donald Booth and Andrew JT Colin. On the efficiency of a new method of dictionary construction. *Information and Control*, 3(4):327–334, 1960.

- [10] Prosenjit Bose and Karim Douïeb. Efficient construction of near-optimal binary and multiway search trees. In *Algorithms and Data Structures*, pages 230–241. Springer, 2009.
- [11] Roberto De Prisco and Alfredo De Santis. On binary search trees. *Information Processing Letters*, 45(5):249–253, 1993.
- [12] Erik D Demaine, Dion Harmon, John Iacono, and Mihai Patrascu. Dynamic optimality-almost. *SIAM Journal on Computing*, 37(1):240–251, 2007.
- [13] E Knuth Donald. The art of computer programming. *Sorting and searching*, 3:426–458, 1999.
- [14] Robert G Gallager. *Information theory and reliable communication*, volume 2. Springer, 1968.
- [15] Adriano M Garsia and Michelle L Wachs. A new algorithm for minimum cost binary trees. *SIAM Journal on Computing*, 6(4):622–642, 1977.
- [16] Edgar N Gilbert and Edward F Moore. Variable-length binary encodings. *Bell System Technical Journal*, 38(4):933–967, 1959.
- [17] Leo Gotlieb. Optimal multi-way search trees. *SIAM Journal on Computing*, 10(3):422–433, 1981.
- [18] Reiner Güttler, Kurt Mehlhorn, and Wolfgang Schneider. Binary search trees: Average and worst case behavior. *Elektronische Informationsverarbeitung und Kybernetik*, 16:41–61, 1980.
- [19] Thomas N Hibbard. Some combinatorial properties of certain trees with applications to searching and sorting. *Journal of the ACM (JACM)*, 9(1):13–28, 1962.
- [20] Yasuichi Horibe. An improved bound for weight-balanced tree. *Information and Control*, 34(2):148–151, 1977.
- [21] TC Hu. A new proof of the tc algorithm. *SIAM Journal on Applied Mathematics*, 25(1):83–94, 1973.
- [22] T.C. Hu. *Combinatorial Algorithms*. Addison-Wesley, MA, 1982.
- [23] TC Hu, Daniel J Kleitman, and Jeanne K Tamaki. Binary trees optimum under various criteria. *SIAM Journal on Applied Mathematics*, 37(2):246–256, 1979.

- [24] Te C Hu and Alan C Tucker. Optimal computer search trees and variable-length alphabetical codes. *SIAM Journal on Applied Mathematics*, 21(4):514–532, 1971.
- [25] David A Huffman et al. A method for the construction of minimum redundancy codes. *Proceedings of the IRE*, 40(9):1098–1101, 1952.
- [26] Feffrey H Kingston. A new proof of the garsia-wachs algorithm. *Journal of Algorithms*, 9(1):129–136, 1988.
- [27] DE Knuth. Sorting and searching.(the art of computer programming, vol. 3) addison-wesley. *Reading, MA*, pages 551–575, 1973.
- [28] Donald E. Knuth. Optimum binary search trees. *Acta informatica*, 1(1):14–25, 1971.
- [29] James F Korsh. Greedy binary search trees are nearly optimal. *Information Processing Letters*, 13(1):16–19, 1981.
- [30] James F Korsh. Growing nearly optimal binary search trees. *Information Processing Letters*, 14(3):139–143, 1982.
- [31] Daniel Dominic Sleator and Robert Endre Tarjan. Self-adjusting binary search trees. *Journal of the ACM (JACM)*, 32(3):652–686, 1985.
- [32] Shripad Thite. Optimum binary search trees on the hierarchical memory model. *arXiv preprint arXiv:0804.0940*, 2008.
- [33] Vijay K. Vaishnavi, Hans-Peter Kriegel, and Derick Wood. Optimum multiway search trees. *Acta Informatica*, 14(2):119–133, 1980.
- [34] Peter F Windley. Trees, forests and rearranging. *The Computer Journal*, 3(2):84–88, 1960.
- [35] Raymond W Yeung. Alphabetic codes revisited. *Information Theory, IEEE Transactions on*, 37(3):564–572, 1991.