

FREQUENTLY ASKED QUESTION

Customizing List Bullets and Numbers

I'd like the numbers in my numbered lists to be bold and red instead of boring old black. How do I customize bullets and numbers?

CSS gives you a few ways to customize the markers that appear before list items. For bullets, you can use your own graphics, as described previously. The cool, "I'm so CSS-savvy" way is to use what's called *generated content*. Basically, generated content is just stuff that isn't actually typed on the page but is added by the web browser when it displays the page. A good example is bullets themselves. You don't type bullet characters when you create a list; the browser adds them for you. With CSS, you can have a browser add content, and even style that content, before each `<li>` tag. You read about generated content on page 57, but just so you have the code at hand if you want to make regular bullets next to the list items red, add this CSS to your style sheet:

```
ul li {  
    list-style-type: none;
```

```
}  
ul li:before {  
    content: counter(item, disc) " ";  
    color: red;  
}
```

And, if you wanted to make the items in a numbered list red, you can add this CSS:

```
ol li {  
    list-style-type: none;  
    counter-increment: item;  
}  
ol li:before {  
    content: counter(item) ". ";  
    color: red;  
}
```

For a more in-depth explanation of styling numbered lists visit <http://blog.teamtreehouse.com/customize-ordered-lists-pseudo-element>.

■ Tutorial: Text Formatting in Action

In this tutorial, you'll gussy up headlines, lists, and paragraphs of text, using CSS's powerful formatting options.

To get started, you need to download the tutorial files from https://github.com/sawmac/css_mm_4e. Click the tutorial link and download the files. All of the files are enclosed in a zip archive, so you'll need to unzip them first. The files for this tutorial are contained inside the folder named 06.

Setting Up the Page

First, you'll get your style sheet started, add the `@font-face` directive to load some web fonts, and add styles to format the body text.

1. Launch your web browser and open the file 06→text.html (see Figure 6-19).

It's not much to look at—just a collection of headlines, paragraphs and a lone bulleted list—but you'll turn it into something far better looking.

2. Open the file *text.html* in your favorite text editor.

You'll use a Google font as well as your own font files for this project. Start by adding a link to a Google font.

CSS The Missing Manual

Exploring Typographic Possibilities

november 30 Rod Dibble

- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea

Esse quam nulla

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur? Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

Quis autem vel eum

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur? Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

FIGURE 6-19

The page begins with nothing but basic, drab, HTML.

3. In the `<head>` of the web page, click directly after the closing `</title>` tag. Hit Enter (Return), and then type:

```
<link href="http://fonts.googleapis.com/css?family=Slabo+27px"
rel="stylesheet">
```

This line tells Google to send you a font named Slabo 27px—a serif display font. Next, you'll link to an external style sheet that will hold the styles for this tutorial.

4. After the `<link>` tag you just added, type the following line of code:

```
<link href="css/styles.css" rel="stylesheet">
```

You've linked to an external style sheet in a folder named `css`. That folder holds an external style sheet and your web fonts.

5. Open the file `css→styles.css`. This style sheet has a basic set of reset styles (see page 109).

If you preview the *text.html* file in a web browser now, you'll see that all of the text on the page (headlines, paragraphs, and so on) looks nearly the same—in other words, all the basic HTML formatting the browser applied has been removed, so you can start with a clean slate.

Next, you'll add the necessary `@font-face` directives to load four web fonts. Actually, they are all the same font—PTSans—but include the bold, italic, and bold-italic variants.

6. Add the following code to the top of the *styles.css* file (before the reset styles). (If you'd rather not type all this code, you can open the *at-font-face.css* file in the tutorial folder and just copy and paste that code into the *styles.css* file.)

```
@font-face {
  font-family: 'PTSans';
  src: url('fonts/PTSansRegular.woff2') format('woff2'),
       url('fonts/PTSansRegular.woff') format('woff');
  font-weight: normal;
  font-style: normal;
}
```

```
@font-face {
  font-family: 'PTSans';
  src: url('fonts/PTSansItalic.woff2') format('woff2'),
       url('fonts/PTSansItalic.woff') format('woff');
  font-weight: normal;
  font-style: italic;
}
```

```
@font-face {
  font-family: 'PTSans';
  src: url('fonts/PTSansBold.woff2') format('woff2'),
       url('fonts/PTSansBold.woff') format('woff');
  font-weight: bold;
  font-style: normal;
}
```

```
@font-face {
  font-family: 'PTSans';
  src: url('fonts/PTSansBoldItalic.woff2') format('woff2'),
       url('fonts/PTSansBoldItalic.woff') format('woff');
  font-weight: bold;
  font-style: italic;
}
```

In a nutshell, you've created a new font family named PTSans. You'll be able to use it in any new styles you create. You're using the method described on page 136 to add the bold-italic variants of the font. This method means that whenever you apply a normal bolded tag to text (like a headline, or the `<strong>` tag), the browser will automatically swap in the bold version of the font.

You placed the `@font-face` directive at the beginning of the external style sheet. That's not a requirement, though—it just feels neater to put all the fonts at the top and all of the regular styles after.

Next, you'll create a style that defines some general properties for all text on the page.

7. **At the bottom of the style sheet, after the reset styles, add a new line and type** `html {`.

This is a basic tag selector that applies to the `<html>` tag. As discussed in Chapter 4, other tags inherit the properties of this tag. You can set up some basic text characteristics like font, color, and font size for later tags to use as their starting point.

8. **Press Enter again, and then add the following two properties:**

```
font-family: PTSans, Arial, sans-serif;
font-size: 62.5%;
```

These two instructions set the font to PTSans (or Arial if the browser can't download PTSans), and the font size to 62.5 percent.

NOTE

Why set the page's base font to 62.5 percent? It just so happens that 62.5 percent times 16 pixels (the normal size of text in most web browsers) equals 10 pixels. With 10 pixels as a starting point, it's easy to compute what other text sizes will look like on the screen. For example, 1.5em would be 1.5 x 10 or 15 pixels. 2em is 20 pixels, and so on—easy multiples of ten. You can also use the `rem` unit (see page 155), which is similar to the `em`, but avoids the problem associated with nested inherited `em` units.

9. **Complete this style by pressing Enter and typing a closing bracket to mark the end of the style.**

At this point, your completed style should look like this:

```
html {
  font-family: PTSans, Arial, sans-serif;
  font-size: 62.5%;
}
```

Your style sheet is complete.

10. **Save the `styles.css` file, and open the `text.html` file in a web browser to preview your work.**

The text on the page changes font...it also gets really small. Don't worry, that's the 62.5 percent font size you set in step 8. That's just the starting point for all text, and you'll easily increase the size of text by defining `em` sizes for the other tags.

Formatting the Headings and Paragraphs

Now that the basic text formatting is done, it's time to refine the presentation of the headlines and paragraphs.

1. **Return to your text editor and the `styles.css` file. Click at the end of the closing brace of the HTML tag selector, add a new line, and then type** `.main h1 {`.

This is a *descendant selector* (page 50). It provides more specific direction than a basic HTML tag selector. In this case, the selector tells the web browser “apply the following formatting to any `<h1>` tag inside another tag with the class

name main." If you look at the page's HTML, you'll see that there's a `<div>` tag with a class of main (`<div class="main">`). As you'll learn later, it's very common in CSS-based designs to group HTML tags inside of `<div>` tags. You can then position individual `<div>` tags to create columns and other complex page layouts. It's also common to use descendant selectors like this one to pinpoint your formatting choices by affecting just the tags in certain areas of the page.

2. Hit Enter, and then type these three CSS properties:

```
color: rgb(249,212,120);  
font-family: "Arial Black", Arial, Helvetica, sans-serif;  
font-size: 4em;
```

You've just changed the color of the `<h1>` tag as well as the font. This time, instead of using a web font, you're specifying a font that visitors must have installed on their computers. Many computers have Arial Black, but if the one visiting this page doesn't, it will fall back to Arial or Helvetica or just a generic sans serif. You've also set the font size to 4em, which for most browsers (unless the visitor has tweaked his browser's font settings) comes out to 40 pixels tall. That's all thanks to the 62.5% size you set for the body back at step 7. That smooth move made the base font size 10 pixels tall, so 4×10 comes out to 40 pixels. Next you'll add a text shadow to the headline.

3. Complete this style by hitting Enter, adding the code in bold below (don't forget the closing brace):

```
.main h1 {  
  color: rgb(249,212,120);  
  font-family: "Arial Black", Arial, Helvetica, sans-serif;  
  font-size: 4em;  
  text-shadow: 4px 4px 6px rgba(0,0,0,.75);  
}
```

Here, you've added a text shadow (page 160), which is offset 4 pixels to the right, 4 pixels below, and is feathered out 6 pixels. In addition, you're using the RGBA color (page 149) to set the shadow to black with 75 percent transparency.

4. Save the file and preview the *text.html* file in a web browser.

Next, spruce up the appearance of the other headings and paragraphs.

NOTE

Once a browser opens a file, it saves it in a type of easily accessible storage called a *cache*. If the browser needs that same file again, it plucks the cached version instead of wasting time downloading the file a second time. However, the cache can be a pain when designing locally. The browser may load the old version of your external style sheet from the cache instead of loading the one with your new changes. If the web page doesn't seem to get updated when you update an external style sheet, pressing F5 or Ctrl-Shift-R (⌘-Shift-R) will usually force the browser to load the new version of the file.

5. **Return to your text editor and the `styles.css` file. Click after the closing brace of the `.main h1` tag, hit Enter, and add the following style:**

```
.main h2 {  
  font: normal 3.5em "Slabo 27px", Garamond, Times, serif;  
  color: rgb(37,76,143);  
  border-bottom: 1px solid rgb(200,200,200);  
  margin-top: 25px;  
}
```

Here you have another descendant selector that only applies to `<h2>` tags inside another tag with the class `main` (you're probably getting the hang of these now). The `font` property used here is shorthand that combines the more long-winded `font-weight`, `font-size`, and `font-family` (see the box on page 165). In other words, this one line makes the headline bold, 3.5ems tall, and specifies the Google font you linked to earlier.

In addition, this style adds a decorative border below the headline and a bit of space between the headline and the tag above it (in other words, it adds some space between the "CSS The Missing Manual" and the "Exploring Typographic Possibilities" headlines). You'll read more about borders and margins in the next chapter.

Time to tackle more headlines.

6. **Add another style below the one you added in the last step:**

```
.main h3 {  
  color: rgb(241,47,6);  
  font-size: 1.9em;  
  font-weight: bold;  
  text-transform: uppercase;  
  margin-top: 25px;  
  margin-bottom: 10px;  
}
```

This style dishes out some of the usual formatting—color, size, boldness—and also uses the `text-transform` property (page 157) to make all of the text in the `<h3>` headlines uppercase. Finally, it adds a bit of space above and below the headlines by using the margin properties.

Next, you'll improve the look of the paragraphs.

7. **Add one more style to the page:**

```
.main p {  
  font-size: 1.8em;  
  line-height: 1.5;  
  margin-left: 150px;  
  margin-right: 50px;  
  margin-bottom: 10px;  
}
```


This style introduces the `line-height` property, which sets the spacing between lines. The number 1.5 is a multiplier: It calculates the line height by multiplying the font size (1.75em) and 1.5. Basically, it sets the line height to 1.5x or 150 percent of the font size. This adds a little more space between lines in a paragraph than you'd normally see in a web browser. This extra breathing room gives the text a lighter, airier quality and makes the sentences a little easier to read (but only if you speak Latin).

The style also increases the font size to 1.8em (18 pixels for most browsers) and indents the paragraph from the left and right edges of the page. You'll notice that there's a lot of typing going on for the margin properties—fortunately, as you'll read on page 189 in the next chapter, there's a margin shortcut property that requires much less typing to control the four margins of an element.

Time to try out a more advanced selector type.

8. Add the following style to your style sheet:

```
.main p::first-line {  
  font-weight: bold;  
  color: rgb(153,153,153);  
}
```

The `::first-line` pseudo-element (page 56) affects just the first line of a paragraph. In this case, just the first line of text for each of the paragraphs inside the main div will be bold and gray.

9. Save the *styles.css* file and open the *text.html* file in a web browser to preview your work.

At this point, the page should look like Figure 6-20.

Formatting Lists

This page has a single bulleted list. The plan is to move the list over to the right edge of the page and have the text following it wrap around it. CSS makes this little trick easy.

1. Return to your text editor and the *styles.css* file. Add the following style at the end of the style sheet:

```
.main ul {  
  margin: 50px 0 25px 50px;  
  width: 25%;  
  float: right;  
}
```

When formatting lists, you'll usually create styles for two different elements: the list itself (either the `<ul>` tag for bulleted lists or the `<ol>` tag for numbered lists) and the individual list items (the `<li>` tag). This style controls the entire list.

CSS The Missing Manual

Exploring Typographic Possibilities

november 30 Rod Dibble

- Lorem ipsum
- Reprehenderit qui in ea
- Lorem ipsum
- Reprehenderit qui in ea
- Lorem ipsum
- Reprehenderit qui in ea

ESSE QUAM NULLA

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? *Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?* Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

QUIS AUTEM VEL EUM

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? **Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?** Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

FIGURE 6-20

The page is starting to come together. The headlines, paragraphs, and basic text settings are in place. Depending on which fonts you have on your computer, you may notice slight differences between your design and the one pictured here. For example, if your computer doesn't have Arial Black, the headline, *CSS The Missing Manual*, might not be as bold as is pictured here.

There are a few things happening in this style. First, the *margin* property uses the shorthand method. This one line sets all four margins around the list, replacing the four individual margin properties (*margin-top*, *margin-right*, and so on). The four values are ordered like this: top, right, bottom, left. So for this style, 50 pixels of space get added above the list, 0 space on the right, 25 pixels on the bottom, and 50 pixels on the left.

The width property (discussed in detail on page 204) makes the entire list 25% the width of the browser window. If any particular list item has more text than will fit within that space, it wraps to another line. The *float* property is the real magic—in this case, *float: right* means “move the list over to the right edge of the page.” This property also causes the text following the list to wrap around the left side of the list. It's a cool trick, and you'll learn a lot more about floats on page 210.

You'll control the look of the individual list items next.

2. Add one more style to the style sheet:

```
.main li {  
  color: rgb(32,126,191);  
  font-size: 1.5em;  
  margin-bottom: 7px;  
}
```

Nothing new here: just changing the color and size and adding space below each list item. Time to check out your progress.

NOTE If you want to add space between list items, you need to add top or bottom margins to the `<li>` tag. Adding margins to the `<ul>` or `<ol>` tags simply adds space around the entire list.

3. Save the page and preview it in a web browser.

The page should now look like Figure 6-21.

CSS The Missing Manual

Exploring Typographic Possibilities

november 30 Rod Dibble

ESSE QUAM NULLA

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? *Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?* Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea

QUIS AUTEM VEL EUM

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? **Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?** Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

FIGURE 6-21

The float property gives you some interesting design options. In this case, the bulleted list is floated to the right edge of the page. In fact, the float property is so useful, you'll see that it's the main ingredient of CSS-based layouts, like the ones you'll learn about in Chapter 12.

Fine-Tuning with Classes

Sometimes you want even more control over how a style is applied. For example, while you might want most paragraphs in one section of the page to look the same, you might also want one or two paragraphs to have their own unique look. In this tutorial, the paragraph of text near the top of the page—"November 30 Rod Dibble"—contains some unique information: a publication date and author. You want it to stand out from the other paragraphs, so you'll add a class to the HTML and create a class style.

1. **Open the `text.html` file in your text editor. Locate the HTML for that paragraph—`<p>november 30 <strong>Rod Dibble</strong></p>`—and add `class="byline"` to the opening `<p>` tag. The HTML should look like this:**

```
<p class="byline">november 30 <strong>Rod Dibble</strong></p>
```

Now it's a simple matter of creating a class style that overrides the generic formatting of the other paragraphs on the page.

2. **Open the `styles.css` file in your text editor. At the bottom of the style sheet, add a style for that paragraph:**

```
.main .byline {  
  font-size: 1.6em;  
  margin: 5px 0 25px 50px;  
}
```

This style tweaks the size and placement of just that one paragraph. Note that if you'd just named that style `.byline`—a basic class selector—it wouldn't work. Thanks to the rules of the cascade described in the last chapter, `.byline` is less specific (less powerful) than the `.main p` style you created in step 7 on page 177, so it wouldn't be able to override the size and margins specified by `.main p`. However, `.main .byline` is more specific.

That paragraph still needs some work. It would be great if the name stood out more. The HTML in this case provides just the hook you need.

3. **Add another style to the style sheet:**

```
.main .byline strong {  
  color: rgb(32,126,191);  
  text-transform: uppercase;  
  margin-left: 11px;  
}
```

If you look at the HTML in step 1 above, you'll see that the name—Rod Dibble—is inside a `<strong>` tag. The `<strong>` tag is used to emphasize text and mark it as important. But that doesn't mean you have to let it be bold, the way web browsers normally display that tag. Instead, this descendant selector targets the `<strong>` tag, but only when it appears inside another tag with the class

.byline, and only if all of that is inside yet another tag with the class main—whew, that’s pretty specific.

This style turns the text blue, makes it uppercase, and adds a bit of space on the left side (nudging the name over just a bit from the “November 30” text).

Adding the Finishing Touches

For the last bit of design, you’ll incorporate a few design touches that format the page and that main div so they both look better. Then you’ll finish up with a cool bit of text formatting.

1. Return to your text editor and the *styles.css* file.

First, you’ll add a background color and image to the page.

2. Locate the `html` style in the external style sheet—the first style that appears after the CSS reset rules—and add one new property so that it looks like this (changes are in bold):

```
html {  
    font-family: PTSans, Arial, sans-serif;  
    font-size: 62.5%;  
    background: rgb(225,238,253) url(../images/bg_body.png) repeat-x;  
}
```

The background property is a powerful tool for any web designer. You’ve already used it a couple of times in earlier tutorials; it lets you add color and insert and control the placement of an image to the background of any tag. You’ll learn the ins and outs of this property on page 231, but for now this line changes the background color of the page to light blue and adds a dark blue stripe to the top of the page.

Next you’ll spruce up the main div.

3. Add another style in between the `html` style and the `.main h1` style:

```
.main {  
    max-width: 740px;  
    margin: 0 auto;  
    padding: 0 10px;  
    border: 4px solid white;  
    background: transparent url(../images/bg_banner.jpg) no-repeat;  
}
```

In other words, click after the closing `}` for the `html` style, hit Enter, and type the code above. You don’t necessarily have to put the style in that spot for it to work, but for organizational purposes, putting the style that controls the div before the other styles that format tags inside that div makes sense.

The `max-width` property sets a maximum overall width for this div. That is, the div could shrink to be smaller—great if a visitor is using a screen that’s less than

740 pixels wide—but it will never stretch wider than 740 pixels. The margin property values—0 auto—put 0 pixels of space above and below the div and set the left and right margins to auto, which centers the div in the middle of the browser window. The padding property adds space inside the box, pushing content inside the div away from the border line. Finally, you’ve placed an image into the background of the div.

Those last two styles didn’t have anything to do with text formatting, but if you preview the page, you’ll see that they make it look a lot better...except for those two top headlines. The first headline isn’t bold enough, and the second should fall below the newly added graphic.

4. Add one last style right after the .main h1 style:

```
.main h1 strong {  
  font-size: 150px;  
  color: white;  
  line-height: 1;  
  margin-right: -.5em;  
}
```

The HTML for the headline looks like this:

```
<h1><strong>CSS</strong> The Missing Manual</h1>
```

The “CSS” is enclosed inside tags, so this descendant selector formats only that text (in that sense, it’s like the style you added in step 3 on page 181 that took advantage of a tag embedded within a paragraph). The text size is pumped way up, its color is changed, and the line height is adjusted so that it fits inside the top of the page. You’ll notice that the line height is set to 1, so in this case, the line height will translate to 150 pixels—that’s 1 times the font size of this style.

The one cool trick is the margin-right property, which is set to a negative value: -.5em. Since a positive margin pushes elements away, a negative margin actually pulls elements on top of each other. In this case, the rest of the text in the headline—“The Missing Manual”—is scooted over .5 em, which is .5 times the font size (150 pixels), on top of the “CSS” text.

NOTE Negative margins are perfectly legal (although tricky) CSS.

5. Save the *styles.css* file and preview the *text.html* file in a web browser.

It should look like Figure 6-22. You can compare your work to the finished *text.html* page located in the *06_finished* folder.

Congratulations! You’ve explored many of the text formatting properties offered by CSS and turned ho-hum HTML into an attractive, attention-getting design. In the

next chapter, you'll explore graphics, borders, margins, and other powerful CSS design options offered by CSS.

CSS

The Missing Manual

Exploring Typographic Possibilities

november 30 ROD DIBBLE

ESSE QUAM NULLA

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? *Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla*

pariatur? Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea
- Lorem Ipsum
- Reprehenderit qui in ea

QUIS AUTEM VEL EUM

Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? **Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?** Ut enim ad minima veniam, quis nostrum exercitationem ullam corporis suscipit laboriosam, nisi ut aliquid ex ea commodi consequatur? Quis autem vel eum iure reprehenderit qui in ea voluptate velit esse quam nihil molestiae consequatur, vel illum qui dolorem eum fugiat quo voluptas nulla pariatur?

FIGURE 6-22

With a little CSS, you can turn plain text into a powerful design statement that helps guide readers through the information on your site.