



Neural Networks

Oliver Temple

March 8, 2022





What a Neural Network Is




Figure: Representation of a neural network



Types of Neural Network

- Perceptron
- Feed Forward Neural Network
- Multi-layer Perceptron



Types of Neural Network

Perceptron

$$\mathbf{y} = \sigma(\mathbf{W} \cdot \mathbf{x} + b) \quad (1)$$

Where \mathbf{y} is the output, \mathbf{W} is a vector of the weights, \mathbf{x} is a vector of the inputs, b is the bias and σ is the activation function.




Figure: Perceptron



Types of Neural Network

Feed Forward Neural Network

$$\mathbf{y}_n = \sigma(\mathbf{W}_n \cdot \mathbf{y}_{n-1} + \mathbf{b}_n) \quad (2)$$

Where \mathbf{y}_n is the output vector of the n th layer, \mathbf{W}_n is the weight matrix of the n th layer, \mathbf{y}_{n-1} is the output vector of the previous layer, \mathbf{b}_n is the bias vector of the n th layer, and σ is the activation function.




Figure: Feed Forward Neural Network



Types of Neural Network

Multi-layer Perceptron

$$\mathbf{y}_n = \sigma(\mathbf{W}_n \cdot \mathbf{y}_{n-1} + \mathbf{b}_n) \quad (3)$$

Where \mathbf{y}_n is the output vector of the n th layer, \mathbf{W}_n is the weight matrix of the n th layer, \mathbf{y}_{n-1} is the output vector of the previous layer, \mathbf{b}_n is the bias vector of the n th layer, and σ is the activation function.



How Neural Networks Work

- Collection of interconnected neurons
- Each neuron has a bias
- Each connection has a weight



How Neural Networks Work

Structure

- Input Layer
- Output Layer
- Hidden Layers



How Neural Networks Work

Forward Propagation


- Inputs are passed through the network to get a prediction
- $\mathbf{y}_n = \sigma(\mathbf{W}_n \cdot \mathbf{y}_{n-1} + \mathbf{b}_n)$
- Where \mathbf{y}_n is the output vector of the nth layer, \mathbf{W}_n is the weight matrix of the nth layer, \mathbf{y}_{n-1} is the output vector of the previous layer, \mathbf{b}_n is the bias vector of the nth layer, and σ is the activation function.



How Neural Networks Work


Activation Functions

Sigmoid




$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

tanh



$$\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}}$$

ReLU



$$\text{ReLU}(x) = \max(0, x)$$



How Neural Networks Work

Loss Functions

$$(MSE) = \frac{1}{n} \sum_{i=1}^n (\hat{y}_i - y_i)^2$$

$$(CEL) = -\frac{1}{n} \sum_{i=1}^n (y_i \times \log(\hat{y}_i))$$


Where n is the number of sample, y_i is the desired output of the network and \hat{y}_i is the actual output of the network.



How Neural Networks Work

Backpropagation

- Data moves backwards through the network
- Weights and biases adjusted
- Loss must be calculated
- Weights and biases can be changed proportionally to the gradient
- Process is repeated





How Neural Networks Work

Training

- Forward Propagation
- Backpropagation
- Repeat



Coding a Neural Network

- Data
- Defining the Model
- Training the Model
- Testing the Model



Coding a Neural Network

Data

- Data is very important
- MNIST dataset
- Dataset must be split into 'test' and 'train' subsets
- 50000 images in the 'train' subset
- 10000 images in the 'test' subset




Figure: MNIST Example



Defining the Model

Layers

- 784 input neurons
- 350 hidden neurons
- 10 output neurons



Defining the Model

Loss Function

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n (\hat{y}_i - y_i)^2 \quad (4)$$



Defining the Model

Activation Function

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad (5)$$

$$2\sigma'(x) = x(1 - x) \quad (6)$$



Coding a Neural Network

Training the Model

- Split the data into equal sized batches
- Forward Propagation for the whole epoch
- Backpropagation after each epoch




Figure: Loss over epochs



Coding a Neural Network

Testing the Model

- Test the model on unseen data
- Run the test dataset through the model
- Calculate accuracy by keeping track of how many correct predictions were made
- 95.32% accuracy



Coding a Neural Network

Testing the Model

- Input labels: 8, 5, 8, 9, 1, 9, 7, 2, 8
- predictions: 5, 5, 8, 9, 1, 9, 7, 2, 8
- 88% accuracy



Figure: Inputs for example predictions



Conclusion

- Complex models used for many different tasks
- Easier and quicker to use a library
- I have gained knowledge of neural networks