

# EECS402 Lecture 01

Andrew M. Morgan

Savitch Ch. 2  
C++ Basics  
Flow Of Control

- Names of variables, constants, user-defined functions, etc
- Valid identifiers
  - Must start with letter or underscore
  - Contains only letters, digits, or underscore
  - Can not be C/C++ reserved word
- Note: C/C++ identifiers are *case sensitive*
- Valid identifier examples
  - i, val, Val, VAL, \_internal, my\_var, myVar, twoNums, x54
- Invalid identifier examples
  - 2nums, my-var, class, file.name

- All variables must have a name and a type
- C++ is a strongly-typed language
- Variable names are any valid C++ identifier
- The type of a variable describes what kind of data it holds
- Values of variables can change throughout a program
- Following are some of the C++ data types
  - int: Integer data (-6, 0, 741, -1024)
  - float/double: Floating point data (6.5, 8.0, -97.21204, 0.0081)
  - char: Character data ('a', 'q', '5', '\n')
  - bool: Boolean values (true, false)

- Before any variable can be used, it must be declared
- Gives the variable a type and sets aside memory
  - int counter; //Declares an integer variable called counter
  - float average; //Declares a float called average
  - char grade; //Declares a character to represent a grade
- Assignment – setting a variables value
  - counter = 10;
  - average = 88.25;
  - grade = 'B';
- Initialization can be done during declaration
  - char modif = '+'; //Modifier to be appended to grade
  - int sumOfValues = 0; //Some of input values
  - float initialBudget = 135.50; //Initial budget for week
- If not initialized, the value of the variable is undefined
  - Note: it will most likely NOT be 0
- Style: Variable names in lower case, except first letters of non-first words

- Constants must have a name and a type
- The value of a constant *must* be initialized at declaration time
- The value is not allowed to change during program execution
- Used to avoid "magic numbers" – literal values in a program
  - Seeing the value 12 in a program is not very meaningful – it could represent the number of quiz scores, the number of hours in a half-day...
- Begin declaration with C++ keyword "const"
  - const float PI = 3.1415;
  - const int NUM\_SCORES = 12;
  - const char BEST\_GRADE = 'A';
- Style: Constant names in ALL CAPS to differentiate from variables

- Operators are used on variables and/or literals to compute a new value.
  - = Assignment operator (not equality)
  - +, -, \*, / Add, subtract, multiply, divide
  - % Modulus (remainder)
  - ==, != Equality, inequality
  - ++, -- Increment, decrement
  - +=, -=, \*=, /= Add/assign, etc
    - i -= 4 is equivalent to i = i - 4
  - >, <, >=, <= Greater than, less than, greater or equal, less or equal
  - && Logical AND, returns true when both operands are true
  - || Logical OR, returns true when >= 1 operand is true
  - ! Local NOT, returns true when operand is false

# Expressions

EECS 402

- Expression: a sequence of tokens that can be evaluated to a numerical quantity
- Expressions result in some value
- Example expressions
  - 5 (value: 5)
  - 5 + 10 (value: 15)
  - a < 15 (value: depends on value of a)
  - (intvar >= 15 && intvar <= 30) (value: depends on value of intvar)
  - 2 \* y - i / 2 (value: depends on values of i and y)
  - x = 17 (value: 17)

EECS 402
Andrew M Morgan
7

# Statements

EECS 402

- Statement: a sequence of tokens terminated with a semicolon that can be recognized by the compiler
- A statement does not have a value
- Example statements
  - x = 5;
  - cout << "Hello world!" << endl;
  - a = 14.8 + fvar;
  - i++;

EECS 402
Andrew M Morgan
8

# Comments

EECS 402

- Comments can be included in your program's source code
- They are *ignored completely* by the language
- Typically included to clarify / explain what your code is doing
- Two types of comments in C++:
  - Single-line comments start with `//`
    - Any characters from the `//` to the end of line are ignored
  - Multi-line comments start with `/*` and end with `*/`
    - These comments can span multiple lines or even use only part of a line

```
//Compute a weighted average for total grade..
gradePerc = projAvg * 0.85 + quizAvg * 0.15; //85% projects...

/* All of this text is ignored in your code.. You can even comment
out a chunk of code in the middle of a line this way.. */
val = someData * 3 /* + 7 */ - exampleItem; //val = someData * 3 - exampleItem
```

EECS 402
Andrew M Morgan
9

# General Program Template

EECS 402

- Most C++ programs have the following general layout

```
#include <iostream>
//other #includes
using namespace std;

//Program Header - Name, purpose, date, etc...

int main(void)
{
    //Variable declarations / initializations

    //Program statements

    return (0);
}
```
- Style: Every program you write will include comment block with a "program header", including at a minimum your name, date, and a brief purpose description
  - For space reasons, my programs in lecture slides will not always include these header comments...

EECS 402
Andrew M Morgan
10

# Output To Screen

EECS 402

- Use object `cout`, and operator `<<`, defined in library `<iostream>`
- No conversion specifications needed as in C (`%d`, `%f`, etc)

```
#include <iostream> //Req'd for cout
using namespace std;

//Programmer: Andrew M. Morgan
//Date: January 2018
//Purpose: To demonstrate a simple program that outputs some
//         data to the screen
int main(void)
{
    int x = 5; //Integer for test
    char c = 'p';
    cout << "Welcome!" << endl;
    cout << "int: " << x << " char: " << c << endl;
    return (0);
}
```

Welcome!
int: 5 char: p

EECS 402
Andrew M Morgan
11

# Division In C++

EECS 402

- C++ has two kinds of division
- Integer division
  - Performed when both operands are integers
  - Result is an *integer*
  - 1/3 = 0, 32/15 = 2
- Floating point division
  - Performed when *at least one* operand is a floating point value
  - Result in a floating point value
  - 1/3.0 = 0.33333, 32.0 / 15.0 = 2.13333
- Result of "var1 / var2" depends on variable data types!
- Combined Example
  - 31 / 2 / 2.0 = 7.5 (Integer division done first 31/2 = 15)
  - 31.0 / 2 / 2.0 = 7.75 (All divisions are floating point divisions)

EECS 402
Andrew M Morgan
12

## Type Casting In C++

- A variable's type can be changed temporarily in a statement
- This is called "type casting"
- Type is only changed for the instance on which the cast is applied
- Syntax: `static_cast< newtype >(variable)`

```
int main()
{
    int val = 31;

    cout << "1. Value is: ";
    cout << val / 2 / 2.0 << endl;

    cout << "2. Value is: ";
    cout << static_cast< double >(val) / 2 / 2.0 << endl;

    cout << "3. Value is: ";
    cout << val / 2 / 2.0 << endl;

    return (0);
}
```

Temporarily casts val to type double

1. Value is: 7.5  
 2. Value is: 7.75  
 3. Value is: 7.5

EECS 402
Andrew M Morgan
13

## More On Type Casting

- Sometimes, type casting happens automatically
  - 31 / 2.0, converts 31 to 31.0 automatically without use of `static_cast`
- C-Style casts, used in older C programs
  - Syntax: `(newtype)variable`
  - Example: `(double)31 / 2 / 2.0` results in value of 7.75
- C++ "function style" casts, used in older C++ programs
  - Syntax: `newtype(variable)`
  - Example: `double(31) / 2 / 2.0` results in value of 7.75

EECS 402
Andrew M Morgan
14

## Compound Statements

- Syntax of many C++ constructs allows only one single statement to be used
- Compound statements allow multiple statements to be combined into one statement.
- Multiple statements enclosed in `{ }` result in a compound statement

```
x = 5;
a = 14.8 + fvar;
i++;
```

3 Statements

```
{
    x = 5;
    a = 14.8 + fvar;
    i++;
}
```

1 Statement  
(1 Compound Statement containing 3 statements)

EECS 402
Andrew M Morgan
15

## Input From Keyboard

- Use object `cin`, and operator `>>`, defined in library `<iostream>`
- No conversion specifications needed as in C (`%d`, `%f`, etc)

```
#include <iostream> //Req'd for cin
using namespace std;

int main(void)
{
    int x;
    char c;

    cout << "Enter an int: "; //Prompt
    cin >> x;
    cout << "Enter a char: "; //Prompt
    cin >> c;
    cout << "int: " << x << " char: " << c << endl;
    return (0);
}
```

Enter an int: 5  
 Enter a char: p  
 int: 5 char: p

EECS 402
Andrew M Morgan
16

## If-Else Statement

- Used for conditional branching
- If-else syntax
 

```
if (expression)
    statement
else
    statement
```
- Each statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of an if or else.

```
int x = 4;
if (x == 4)
{
    cout << "x was 4!!" << endl;
}
else
{
    cout << "x was not 4!!" << endl;
    cout << "It was: " << x << endl;
}
```

EECS 402
Andrew M Morgan

x was 4!!

17

## Nested If-Else Example

```
int main(void)
{
    int x = 4;
    if (x == 3)
    {
        cout << "x was 3!!" << endl;
    }
    else
    {
        if (x == 4)
        {
            cout << "x was 4!!" << endl;
        }
        else
        {
            cout << "x not 3 or 4!!" << endl;
        }
    }
    return 0;
}
```

This is ONE if statement. Any single statement can be used in the body of an if-else construct.

```
int main(void)
{
    int x = 4;
    if (x == 3)
    {
        cout << "x was 3!!" << endl;
    }
    else if (x == 4)
    {
        cout << "x was 4!!" << endl;
    }
    else
    {
        cout << "x not 3 or 4!!" << endl;
    }
    return 0;
}
```

By simply rearranging the way it is written, we end up with an "if-else if-else".

EECS 402
Andrew M Morgan

x was 4!!

18

# C++ "switch" Statement

EECS 402

- Used for jumping to a certain branch of code
- switch syntax:

```

switch (discreteExpression)
{
    case value1:
        statement(s)
    case value2:
        statement(s)
    ...
    default:
        statement(s)
}

```

Note: Unlike most other C++ control structures, the statements can contain multiple statements without the use of a compound statement.

EECS 402

Andrew M Morgan

19

# C++ "switch" Statement, Continued

EECS 402

- A "discrete expression" is an expression that results in discrete values
  - Integers, characters, enumerated types, etc
  - NOT floats, doubles, etc
- Statements "fall through" from one case to the next (unless otherwise specified)
- Use of "break" keyword prevents this (usually) unwanted behavior
- The "default" case is optional, and is used when no other case matches the expressions value

EECS 402

Andrew M Morgan

20

# C++ "switch" Example

EECS 402

```

int x;
int i;

cout << "Enter a value: ";
cin >> x;
switch (x)
{
    case 3:
        cout << "3" << endl;
        break;
    case 4:
        cout << "4" << endl;
        break;
    case 5:
        cout << "5" << endl;
        break;
    default:
        cout << "other" << endl;
}

```

Enter a value: 3

Enter a value: 4

Enter a value: 7

EECS 402

Andrew M Morgan

21

# Duplicated Code = Bad

EECS 402

- Duplicating code is bad style

Bad

```

switch (month)
{
    case 1:
        cout << "Winter Semester";
        break;
    case 2:
        cout << "Winter Semester";
        break;
    case 3:
        cout << "Winter Semester";
        break;
    case 4:
        cout << "Winter Semester";
        break;
    case 5:
        cout << "Winter Semester";
        break;
    case 6:
        cout << "Winter Semester";
        break;
    case 7:
        cout << "Winter Semester";
        break;
    case 8:
        cout << "Winter Semester";
        break;
    case 9:
        cout << "Fall Semester";
        break;
    case 10:
        cout << "Fall Semester";
        break;
    case 11:
        cout << "Fall Semester";
        break;
    case 12:
        cout << "Fall Semester";
        break;
    default:
        cout << "Neither";
}

```

Better

```

switch (month)
{
    case 1:
    case 2:
    case 3:
    case 4:
    case 5:
    case 6:
    case 7:
    case 8:
        cout << "Winter Semester";
        break;
    case 9:
    case 10:
    case 11:
    case 12:
        cout << "Fall Semester";
        break;
    default:
        cout << "Neither";
}

```

Best

```

if (month >= 1 && month <= 8)
{
    cout << "Winter Semester";
}
else if (month >= 9 && month <= 12)
{
    cout << "Fall Semester";
}
else
{
    cout << "Neither";
}

```

This is a case where the "usually unwanted" behavior of "falling through" is exactly what you want.

What if you had to change "Semester" to "Term"?

The "if" version is best (in my opinion) just because its much clearer... Not because its shorter...

EECS 402

Andrew M Morgan

22

# While Loop

EECS 402

- Used to iterate until a condition is no longer met
- While loop syntax

```

while (expression)
    statement

```
- The statement should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a while loop.

EECS 402

Andrew M Morgan

23

# While Loop, Example

EECS 402

```

int main(void)
{
    int num = 1; //Loop condition value
    int fact = 1; //Factorial

    while (num <= 5)
    {
        fact *= num;
        num++; //Don't forget to modify num!
    }
    cout << "5 factorial is: " << fact << endl;

    return (0);
}

```

One single (compound) statement.

5 factorial is: 120

EECS 402

Andrew M Morgan

24

# Do-While Loop

EECS 402

- Used to iterate until a condition is no longer met
- Loop body always executed at least once
- Do-While loop syntax

```
do
    statement
while (expression);
```
- The statement should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a do-while loop.

EECS 402
Andrew M Morgan
25

# Do-While Loop, Example

EECS 402

```
int main(void)
{
    int num = 1; //Loop condition value
    int fact = 1; //Factorial

    do
    {
        fact *= num;
        num++;
    }
    while (num <= 5);
    cout << "5 factorial is: " << fact << endl;

    return 0;
}
```

One single (compound) statement.

5 factorial is: 120

EECS 402
Andrew M Morgan
26

# For Loop

EECS 402

- Used to iterate until a condition is no longer met
- Usually used for count-controlled loops ("do this 15 times")
- Initialization, expression, and update are part of for loop
- For loop syntax

```
for (initialization; expression; update)
    statement
```
- The update should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a for loop.

EECS 402
Andrew M Morgan
27

# For Loop, Example

EECS 402

```
int main(void)
{
    int num; //Loop variable - no need to initialize
    int fact = 1; //Factorial

    for (num = 1; num <= 5; num++)
    {
        fact *= num;
    }
    cout << "5 factorial is: " << fact << endl;

    return 0;
}
```

One single (compound) statement.

5 factorial is: 120

EECS 402
Andrew M Morgan
28

# Additional Reference Material

EECS 402

EECS 402

# Output Formatting

EECS 402

- C++ will output values as it sees appropriate if you don't specify
- To specify fixed format (as opposed to scientific notation):

```
- cout.setf(ios::fixed);
```
- To specify floating point numbers should always contain a decimal point character when output:

```
- cout.setf(ios::showpoint);
```
- To specify number of digits after the decimal point to be output:

```
- cout.precision(integerValue);
- cout.precision(4); //outputs 4 digits of prec
```
- To specify justification:

```
- cout.setf(ios::left);
- cout.setf(ios::right);
```

EECS 402
Andrew M Morgan
30



## Output Formatting, Example

EECS  
402

```
double dVal = 1.0 / 3.0;
double dVal2 = 1;

cout << "1. dVal is: " << dVal << endl;
cout << "1. dVal2 is: " << dVal2 << endl;

cout.setf(ios::fixed);
cout.setf(ios::showpoint);
cout.precision(2);

cout << "2. dVal is: " << dVal << endl;
cout << "2. dVal2 is: " << dVal2 << endl;
```

```
1. dVal is: 0.333333
1. dVal2 is: 1
2. dVal is: 0.33
2. dVal2 is: 1.00
```

EECS  
402

Andrew M Morgan

31



## Output Format Manipulators

EECS  
402

- Modifying formats can be done via inline manipulators as well
- Must `#include <iomanip>`
- To set precision with manipulator:
  - `cout << setprecision(intValue);`
  - Note: change in precision is permanent
- To set width (number of characters output) with manipulator:
  - `cout << setw(intValue);`
  - Note: change in width is for the immediately following value ONLY!!!

EECS  
402

Andrew M Morgan

32



## Output Manipulators, Example

EECS  
402

```
double dVal = 1.0 / 3.0;
double dVal2 = 1;

cout << "1. dVal is: " << dVal << endl;
cout << "1. dVal2 is: " << dVal2 << endl;

cout.setf(ios::fixed);
cout.setf(ios::showpoint);
cout.precision(2);

cout << "2. dVal is: " << dVal << endl;
cout << "2. dVal2 is: " << dVal2 << endl;

cout.setf(ios::left);
cout << "3. dVal is: " << setprecision(4) << dVal << endl;
cout << "3. dVal2 is: " << setw(8) << dVal2 << endl;

cout.setf(ios::right);
cout << "4. dVal is: " << dVal << endl;
cout << "4. dVal2 is: " << setw(8) << dVal2 << endl;
```

```
1. dVal is: 0.333333
1. dVal2 is: 1
2. dVal is: 0.33
2. dVal2 is: 1.00
3. dVal is: 0.3333
3. dVal2 is: 1.0000
4. dVal is: 0.3333
4. dVal2 is: 1.0000
```

Note: Two spaces

EECS  
402

Andrew M Morgan

33

