

# EECS402 Lecture 01

Andrew M. Morgan

Savitch Ch. 2  
C++ Basics  
Flow Of Control



## Identifiers

EECS  
402

- Names of variables, constants, user-defined functions, etc
- Valid identifiers
  - Must start with letter or underscore
  - Contains only letters, digits, or underscore
  - Can not be C/C++ reserved word
- Note: C/C++ identifiers are *case sensitive*
- Valid identifier examples
  - i, val, Val, VAL, \_internal, my\_var, myVar, twoNums, x54
- Invalid identifier examples
  - 2nums, my-var, class, file.name





## Variables

EECS  
402

- All variables must have a name and a type
- C++ is a strongly-typed language
- Variable names are any valid C++ identifier
- The type of a variable describes what kind of data it holds
- Values of variables can change throughout a program
- Following are some of the C++ data types
  - int: Integer data (-6, 0, 741, -1024)
  - float/double: Floating point data (6.5, 8.0, -97.21204, 0.0081)
  - char: Character data ('a', 'q', '5', '\n')
  - bool: Boolean values (true, false)

EECS  
402

Andrew M Morgan

3



## Using Variables

EECS  
402

- Before any variable can be used, it must be declared
- Gives the variable a type and sets aside memory
  - `int counter; //Declares an integer variable called counter`
  - `float average; //Declares a float called average`
  - `char grade; //Declares a character to represent a grade`
- Assignment – setting a variables value
  - `counter = 10;`
  - `average = 88.25;`
  - `grade = 'B';`
- Initialization can be done during declaration
  - `char modif = '+'; //Modifer to be appended to grade`
  - `int sumOfValues = 0; //Some of input values`
  - `float initialBudget = 135.50; //Initial budget for week`
- If not initialized, the value of the variable is undefined
  - Note: It will most likely NOT be 0
- Style: Variable names in lower case, except first letters of non-first words

EECS  
402

Andrew M Morgan

4





## Declaring Constants

EECS  
402

- Constants must have a name and a type
- The value of a constant *must* be initialized at declaration time
- The value is not allowed to change during program execution
- Used to avoid "magic numbers" – literal values in a program
  - Seeing the value 12 in a program is not very meaningful – it could represent the number of quiz scores, the number of hours in a half-day...
- Begin declaration with C++ keyword "const"
  - `const float PI = 3.1415;`
  - `const int NUM_SCORES = 12;`
  - `const char BEST_GRADE = 'A';`
- Style: Constant names in ALL CAPS to differentiate from variables

EECS  
402

Andrew M Morgan

5



## Some C++ Operators

EECS  
402

- Operators are used on variables and/or literals to compute a new value.
  - `=` Assignment operator (not equality)
  - `+`, `-`, `*`, `/` Add, subtract, multiply, divide
  - `%` Modulus (remainder)
  - `==`, `!=` Equality, inequality
  - `++`, `--` Increment, decrement
  - `+=`, `-=`, `*=`, `/=` Add/assign, etc
    - `i -= 4` is equivalent to `i = i - 4`
  - `>`, `<`, `>=`, `<=` Greater than, less than, greater or equal, less or equal
  - `&&` Logical AND, returns true when both operands are true
  - `||` Logical OR, returns true when  $\geq 1$  operand is true
  - `!` Local NOT, returns true when operand is false

EECS  
402

Andrew M Morgan

6





## Expressions

EECS  
402

- Expression: a sequence of tokens that can be evaluated to a numerical quantity
- Expressions result in some value
- Example expressions
  - 5 (value: 5)
  - 5 + 10 (value: 15)
  - a < 15 (value: depends on value of a)
  - (intvar >= 15 && intvar <= 30) (value: depends on value of intvar)
  - 2 \* y - i / 2 (value: depends on values of i and y)
  - x = 17 (value: 17)

EECS  
402

Andrew M Morgan

7



## Statements

EECS  
402

- Statement: a sequence of tokens terminated with a semicolon that can be recognized by the compiler
- A statement does not have a value
- Example statements
  - x = 5;
  - cout << "Hello world!" << endl;
  - a = 14.8 + fvar;
  - i++;

EECS  
402

Andrew M Morgan

8





## Comments

EECS  
402

- Comments can be included in your program's source code
- They are *ignored completely* by the language
- Typically included to clarify / explain what your code is doing
- Two types of comments in C++:
  - Single-line comments start with `//`
    - Any characters from the `//` to the end of line are ignored
  - Multi-line comments start with `/*` and end with `*/`
    - These comments can span multiple lines or even use only part of a line

```
//Compute a weighted average for total grade..  
gradePerc = projAvg * 0.85 + quizAvg * 0.15; //85% projects..  
  
/* All of this text is ignored in your code.. You can even comment  
   out a chunk of code in the middle of a line this way.. */  
val = someData * 3 /* + 7 */ - exampleItem; //val = someData * 3 - exampleItem
```

EECS  
402

Andrew M Morgan

9



## General Program Template

EECS  
402

- Most C++ programs have the following general layout

```
#include <iostream>  
//other #includes  
using namespace std;  
  
//Program Header - Name, purpose, date, etc..  
  
int main(void)  
{  
    //Variable declarations / initializations  
  
    //Program statements  
  
    return (0);  
}
```

- Style: Every program you write will include comment block with a “program header”, including at a minimum your name, date, and a brief purpose description
  - For space reasons, my programs in lecture slides will not always include these header comments...

EECS  
402

Andrew M Morgan

10





## Output To Screen

EECS  
402

- Use object `cout`, and operator `<<`, defined in library `<iostream>`
- No conversion specifications needed as in C (`%d`, `%f`, etc)

```
#include <iostream> //Req'd for cout
using namespace std;

//Programmer: Andrew M. Morgan
//Date: January 2018
//Purpose: To demonstrate a simple program that outputs some
//         data to the screen
int main(void)
{
    int x = 5; //Integer for test
    char c = 'p';
    cout << "Welcome!" << endl;
    cout << "int: " << x << " char: " << c << endl;
    return (0);
}
```

Welcome!  
int: 5 char: p

EECS  
402

Andrew M Morgan

11



## Division In C++

EECS  
402

- C++ has two kinds of division
- Integer division
  - Performed when both operands are integers
  - Result is *an integer*
  - $1/3 = 0$ ,  $32/15 = 2$
- Floating point division
  - Performed when *at least one* operand is a floating point value
  - Result in a floating point value
  - $1/3.0 = 0.33333$ ,  $32.0 / 15.0 = 2.13333$
- Result of "`var1 / var2`" depends on variable data types!
- Combined Example
  - $31 / 2 / 2.0 = 7.5$  (Integer division done first  $31/2 = 15$ )
  - $31.0 / 2 / 2.0 = 7.75$  (All divisions are floating point divisions)

EECS  
402

Andrew M Morgan

12





## Type Casting In C++

EECS  
402

- A variable's type can be changed temporarily in a statement
- This is called "type casting"
- Type is only changed for the instance on which the cast is applied
- **Syntax:** `static_cast< newtype >(variable)`

```
int main()
{
    int val = 31;

    cout << "1. Value is: ";
    cout << val / 2 / 2.0 << endl;

    cout << "2. Value is: ";
    cout << static_cast< double >(val) / 2 / 2.0 << endl;

    cout << "3. Value is: ";
    cout << val / 2 / 2.0 << endl;

    return (0);
}
```

Temporarily casts val to type double

1. Value is: 7.5  
2. Value is: 7.75  
3. Value is: 7.5

EECS  
402

Andrew M Morgan

13



## More On Type Casting

EECS  
402

- Sometimes, type casting happens automatically
  - `31 / 2.0`, converts 31 to 31.0 automatically without use of `static_cast`
- C-Style casts, used in older C programs
  - Syntax: `(newtype)variable`
  - Example: `(double)31 / 2 / 2.0` results in value of 7.75
- C++ "function style" casts, used in older C++ programs
  - Syntax: `newtype(variable)`
  - Example: `double(31) / 2 / 2.0` results in value of 7.75

EECS  
402

Andrew M Morgan

14





## Compound Statements

EECS  
402

- Syntax of many C++ constructs allows only one single statement to be used
- Compound statements allow multiple statements to be combined into one statement.
- Multiple statements enclosed in { } result in a compound statement

```
x = 5;  
a = 14.8 + fvar;  
i++;
```

3 Statements

```
{  
    x = 5;  
    a = 14.8 + fvar;  
    i++;  
}
```

1 Statement  
(1 Compound Statement  
containing 3 statements)

EECS  
402

Andrew M Morgan

15



## Input From Keyboard

EECS  
402

- Use object cin, and operator >>, defined in library <iostream>
- No conversion specifications needed as in C (%d, %f, etc)

```
#include <iostream> //Req'd for cin  
using namespace std;  
  
int main(void)  
{  
    int x;  
    char c;  
  
    cout << "Enter an int: "; //Prompt  
    cin >> x;  
    cout << "Enter a char: "; //Prompt  
    cin >> c;  
    cout << "int: " << x << " char: " << c << endl;  
    return (0);  
}
```

Enter an int: **5**  
Enter a char: **p**  
int: 5 char: p

EECS  
402

Andrew M Morgan

16







## If-Else Statement

EECS  
402

- Used for conditional branching
- If-else syntax
 

```
if (expression)
    statement
else
    statement
```
- Each statement can only be *one* single statement
- Could use a compound statement to put multiple statements in the body of an if or else.

```
int x = 4;
if (x == 4)
{
    cout << "x was 4!!" << endl;
}
else
{
    cout << "x was not 4!!" << endl;
    cout << "It was: " << x << endl;
}
```

Single statement only.  
(Used compound statement)

Single statement only.  
(Used compound statement)

EECS  
402

Andrew M Morgan

x was 4!!

17



## Nested If-Else Example

EECS  
402

```
int main(void)
{
    int x = 4;
    if (x == 3)
    {
        cout << "x was 3!!" << endl;
    }
    else
    {
        if (x == 4)
        {
            cout << "x was 4!!" << endl;
        }
        else
        {
            cout << "x not 3 or 4!" << endl;
        }
    }
    return 0;
}
```

x was 4!!

This is ONE if statement. Any single statement can be used in the body of an if-else construct.

```
int main(void)
{
    int x = 4;
    if (x == 3)
    {
        cout << "x was 3!!" << endl;
    }
    else if (x == 4)
    {
        cout << "x was 4!!" << endl;
    }
    else
    {
        cout << "x not 3 or 4!" << endl;
    }
    return 0;
}
```

x was 4!!

By simply rearranging the way it is written, we end up with an "if-else if-else".

EECS  
402

Andrew M Morgan

18





## C++ “switch” Statement

EECS  
402

- Used for jumping to a certain branch of code
- switch syntax:

```
switch (discreteExpression)
{
    case value1:
        statement(s)
    case value2:
        statement(s)
    ...
    default:
        statement(s)
}
```

Note: Unlike most other C++ control structures, the statements can contain multiple statements without the use of a compound statement.

EECS  
402

Andrew M Morgan

19



## C++ “switch” Statement, Cot’d

EECS  
402

- A “discrete expression” is an expression that results in discrete values
  - Integers, characters, enumerated types, etc
  - NOT floats, doubles, etc
- Statements “fall though” from one case to the next (unless otherwise specified)
- Use of “break” keyword prevents this (usually) unwanted behavior
- The “default” case is optional, and is used when no other case matches the expressions value

EECS  
402

Andrew M Morgan

20





## C++ “switch” Example

EECS  
402

```
int x;
int i;

cout << "Enter a value: ";
cin >> x;
switch (x)
{
    case 3:
        cout << "3" << endl;
        break;
    case 4:
        cout << "4" << endl;
    case 5:
        cout << "5" << endl;
        break;
    default:
        cout << "other" << endl;
}
```

Enter a value: **3**  
3

Enter a value: **4**  
4  
5

Enter a value: **7**  
other

EECS  
402

Andrew M Morgan

21



## Duplicated Code = Bad

EECS  
402

- Duplicating code is bad style

### Bad


```
switch (month)
{
    case 1:
        cout << "Winter Semester";
        break;
    case 2:
        cout << "Winter Semester";
        break;
    case 3:
        cout << "Winter Semester";
        break;
    case 4:
        cout << "Winter Semester";
        break;
    case 9:
        cout << "Fall Semester";
        break;
    case 10:
        cout << "Fall Semester";
        break;
    case 11:
        cout << "Fall Semester";
        break;
    case 12:
        cout << "Fall Semester";
        break;
    default:
        cout << "Neither";
}
```

### Better

```
switch (month)
{
    case 1:
    case 2:
    case 3:
    case 4:
        cout << "Winter Semester";
        break;
    case 9:
    case 10:
    case 11:
    case 12:
        cout << "Fall Semester";
        break;
    default:
        cout << "Neither";
}
```

### Best

```
if (month >= 1 && month <= 4)
{
    cout << "Winter Semester";
}
else if (month >= 9 && month <= 12)
{
    cout << "Fall Semester";
}
else
{
    cout << "Neither";
}
```

 This is a case where the "usually unwanted" behavior of "falling through" is exactly what you want..

What if you had to change "Semester" to "Term"?

The "if" version is best (in my opinion) just because its much clearer... Not because its shorter...

EECS  
402

Andrew M Morgan

22





## While Loop

EECS  
402

- Used to iterate until a condition is no longer met
- While loop syntax

```
while (expression)
    statement
```

- The statement should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a while loop.

EECS  
402

Andrew M Morgan

23



## While Loop, Example

EECS  
402

```
int main(void)
{
    int num = 1; //Loop condition value
    int fact = 1; //Factorial

    while (num <= 5)
    {
        fact *= num;
        num++; //Don't forget to modify num!
    }
    cout << "5 factorial is: " << fact << endl;

    return (0);
}
```

} One single (compound) statement.

5 factorial is: 120

EECS  
402

Andrew M Morgan

24





## Do-While Loop

EECS  
402

- Used to iterate until a condition is no longer met
- Loop body always executed at least once
- Do-While loop syntax

```
do
    statement
while (expression);
```

- The statement should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a do-while loop.

EECS  
402

Andrew M Morgan

25



## Do-While Loop, Example

EECS  
402

```
int main(void)
{
    int num = 1; //Loop condition value
    int fact = 1; //Factorial

    do
    {
        fact *= num;
        num++;
    }
    while (num <= 5);
    cout << "5 factorial is: " << fact << endl;

    return 0;
}
```

} One single (compound) statement.

5 factorial is: 120

EECS  
402

Andrew M Morgan

26





## For Loop

EECS  
402

- Used to iterate until a condition is no longer met
- Usually used for count-controlled loops ("do this 15 times")
- Initialization, expression, and update are part of for loop
- For loop syntax

```
for (initialization; expression; update)
    statement
```

- The update should modify the values in expression to be sure the expression is eventually 0 to prevent infinite loops
- The statement can only be one single statement
- Could use a compound statement to put multiple statements in the body of a for loop.

EECS  
402

Andrew M Morgan

27



## For Loop, Example

EECS  
402

```
int main(void)
{
    int num; //Loop variable - no need to initialize
    int fact = 1; //Factorial

    for (num = 1; num <= 5; num++)
    {
        fact *= num;
    }
    cout << "5 factorial is: " << fact << endl;

    return 0;
}
```

} One single  
(compound)  
statement.

5 factorial is: 120

EECS  
402

Andrew M Morgan

28





## Additional Reference Material



## Output Formatting

- C++ will output values as it sees appropriate if you don't specify
- To specify fixed format (as opposed to scientific notation):
  - `cout.setf(ios::fixed);`
- To specify floating point numbers should always contain a decimal point character when output:
  - `cout.setf(ios::showpoint);`
- To specify number of digits after the decimal point to be output:
  - `cout.precision(integerValue);`
  - `cout.precision(4); //outputs 4 digits of prec`
- To specify justification:
  - `cout.setf(ios::left);`
  - `cout.setf(ios::right);`





## Output Formatting, Example

EECS  
402

```
double dVal = 1.0 / 3.0;
double dVal2 = 1;

cout << "1. dVal is: " << dVal << endl;
cout << "1. dVal2 is: " << dVal2 << endl;

cout.setf(ios::fixed);
cout.setf(ios::showpoint);
cout.precision(2);

cout << "2. dVal is: " << dVal << endl;
cout << "2. dVal2 is: " << dVal2 << endl;
```

```
1. dVal is: 0.333333
1. dVal2 is: 1
2. dVal is: 0.33
2. dVal2 is: 1.00
```

EECS  
402

Andrew M Morgan

31



## Output Format Manipulators

EECS  
402

- Modifying formats can be done via inline manipulators as well
- Must `#include <iomanip>`
- To set precision with manipulator:
  - `cout << setprecision(intValue);`
  - Note: change in precision is permanent
- To set width (number of characters output) with manipulator:
  - `cout << setw(intValue);`
  - Note: change in width is for the immediately following value ONLY!!!

EECS  
402

Andrew M Morgan

32







## Output Manipulators, Example

EECS  
402

```
double dVal = 1.0 / 3.0;
double dVal2 = 1;

cout << "1. dVal is: " << dVal << endl;
cout << "1. dVal2 is: " << dVal2 << endl;

cout.setf(ios::fixed);
cout.setf(ios::showpoint);
cout.precision(2);

cout << "2. dVal is: " << dVal << endl;
cout << "2. dVal2 is: " << dVal2 << endl;

cout.setf(ios::left);
cout << "3. dVal is: " << setprecision(4) << dVal << endl;
cout << "3. dVal2 is: " << setw(8) << dVal2 << endl;

cout.setf(ios::right);
cout << "4. dVal is: " << dVal << endl;
cout << "4. dVal2 is: " << setw(8) << dVal2 << endl;
```

1. dVal is: 0.333333  
1. dVal2 is: 1  
2. dVal is: 0.33  
2. dVal2 is: 1.00  
3. dVal is: 0.3333  
3. dVal2 is: 1.0000  
4. dVal is: 0.3333  
4. dVal2 is: 1.0000

Note: Two spaces

EECS  
402

Andrew M Morgan

33

