

Installing Bioconductor

Kasper D. Hansen

- [Installing Bioconductor](#)
- [Other Resources](#)
- [Corrections](#)

Installing Bioconductor

The one true way to install Bioconductor is by using the `biocLite` script. You get access to this script by sourcing it from the Bioconductor website

```
source("http://www.bioconductor.org/biocLite.R")
```

The first time you run the script without arguments, it will install a core set of Bioconductor packages.

```
biocLite()
```

When you run this script, it will autodetect if any of your installed packages are out of date; it will aggressively ask you to update your packages.

Because of this, the way you update a Bioconductor installation, is just by running `biocLite()` without any argument.

You can check if your installation is fully up-to-date, by running `biocvalid()`; it will return `TRUE` if everything is current.

You install a new package by using `biocLite` with the package name, for example

```
biocLite("limma")
```

The reason why you want to use `biocLite` - and only this function - to install and update Bioconductor, is because one of the top problems users have is when they mix and match Bioconductor packages from different releases. Using `biocLite` ensures that everything is synchronized.

The way you update Bioconductor itself when a new release comes out, is by updating R itself and then run `biocLite`.

Other Resources

- Installation instructions from the [Bioconductor site](#).

Corrections

Improvements and corrections to this document can be submitted on its [GitHub](#) in its [repository](#).