Basic perception

Olivier Aycard
Professor
Grenoble INP - PHELMA
GIPSA Lab
https://www.gipsa-lab.grenoble-inp.fr/user/olivier.aycard
olivier.aycard@grenoble-inp.fr

Lab on basic perception

- To be sure, you have the last release of the code, download it on git:
  1. Cd ~/catkin_ws/src
  2. \rm –r follow_me
  3. Git clone https://gricad-gitlab.univ-grenoble-alpes.fr/aycardol/follow_me.git

Lab on basic perception

- We will implement and test:
  1. The detection of motion algorithm described during the lecture on DATMO;
  2. The clustering of objects algorithm described during the lecture on DATMO.

Detection of motion

1. Edit and modify *datmo.cpp* in *~/catkin_ws/src/follow_me*;
   1. You should implement and understantd the functions « store_background », « reset_motion » and « detect_current_motion »
   2. You should implement the function « detect_motion » and complete what robair should do in the 4 different cases ;
2. Edit datmo.h to see the data structure and prototypes of functions
3. Edit *detection_node.cpp* in *~/catkin_ws/src/follow_me*;
   - You should have a look on the source file;
   - This is the main node that will be used to detect a moving person ;
4. Check the results in a terminal and rviz

Tests(1/3)

- Open 5 terminals:
  1. Roscore: the ROS master;
  2. Rosbag play *data_file*.bag: to play a saved file;
  3. Rosrun follow_me *detection_node*;
  4. Rosrun follow_me *robot_moving_node*;
     - The laser data are only processed when the robot does not move;
     - This is automatically taken into account by the node *robot_moving_node*;
     - You do not have to take care about this issue.
  5. Rviz: the vizualization tool of ROS.
     - To have a graphical display of the processing;
     - See screenshots on next slides

Tests(2/3)


RViz*
Move Camera
Select
Focus Camera
Measure
2D Pose Estimate
2D Nav Goal
Publish Point
Displays
Global Options
Fixed Frame
laser
Background Color
48; 48; 48
Frame Rate
30
Default Light
Global Status: Ok
Fixed Frame
OK
Grid
LaserScan
rviz
Create visualization
By display type
By topic
rviz
Axes
Camera
DepthCloud
Effort
FluidPressure
Grid
GridCells
Group
Illuminance
Image
InteractiveMarkers
LaserScan
Map
Marker
MarkerArray
Odometry
Path
Description:
Display Name
Cancel
OK
LaserScan
Displays the data from a sensor_msgs::LaserScan message as points in the world, drawn as points, billboards, or cubes. More Information.
Add
Duplicate
Remove
Rename
Time
ROS Time: 1547891831.74
ROS Elapsed: 831.17
Wall Time: 1547891831.77
Wall Elapsed: 831.10
Experimental
Reset
Left-Click: Rotate. Middle-Click: Move X/Y. Right-Click/Mouse Wheel:: Zoom. Shift: More options.
31 fps

Tests(3/3)


RViz*
File Panels Help
Interact Move Camera Select Focus Camera Measure 2D Pose Estimate 2D Nav Goal Publish Point
Displays
Global Options
Fixed Frame laser
Background Color 48; 48; 48
Frame Rate 30
Default Light
Global Status: Ok
Fixed Frame OK
Grid
Map
LaserScan
Status: Ok
Topic /scan
Unreliable
Selectable
Style Flat Squares
Size (m) 0,01
Alpha 1
Decay Time 0
Position Transformer XYZ
Color Transformer FlatColor
Queue Size 10
Color 255; 255; 255
LaserScan
Odometry
Marker
Status: Ok
Marker Topic /datmo
Queue Size 100
Marker Topic
visualization_msgs::Marker topic to subscribe to. _array will also automatically be subscribed with type visualization_msgs::MarkerArray.
Add Duplicate Remove Rename
Reset
31 fps

Lab on basic perception

- We will implement and test:
  1. The detection of motion algorithm described during the lecture on DATMO;
  2. The clustering of objects algorithm described during the lecture on DATMO.

Clustering

1. Edit and modify *datmo.cpp* in *~/catkin_ws/src/follow_me*;
    1. You should implement the function « perform_basic_clustering »
2. Edit datmo.h to see the data structure and prototypes of functions
3. Check the results in a terminal and rviz

Tests(1/3)

- Open 4 terminals:
  1. Roscore: the ROS master;
  2. Rosbag play *data_file*.bag: to play a saved file;
  3. Rosrun follow_me *perform_clustering_node*;
  4. Rviz: the vizualization tool of ROS.
     - To have a graphical display of the processing;
     - See screenshots on next slides

Tests(2/3)


RViz*
Move Camera
Select
Focus Camera
Measure
2D Pose Estimate
2D Nav Goal
Publish Point
Displays
Global Options
Fixed Frame
laser
Background Color
48; 48; 48
Frame Rate
30
Default Light
Global Status: Ok
Fixed Frame
OK
Grid
LaserScan
rviz
Create visualization
By display type
By topic
rviz
Axes
Camera
DepthCloud
Effort
FluidPressure
Grid
GridCells
Group
Illuminance
Image
InteractiveMarkers
LaserScan
Map
Marker
Odometry
Path
Description:
Display Name
Cancel
OK
LaserScan
Displays the data from a sensor_msgs::LaserScan message as points in the world, drawn as points, billboards, or cubes. More Information.
Add
Duplicate
Remove
Rename
ROS Time: 1547891831.74
ROS Elapsed: 831.17
Wall Time: 1547891831.77
Wall Elapsed: 831.10
Experimental
Reset
Left-Click: Rotate. Middle-Click: Move X/Y. Right-Click/Mouse Wheel:: Zoom. Shift: More options.
31 fps

Tests(3/3)


RViz*
File Panels Help
Interact Move Camera Select Focus Camera Measure 2D Pose Estimate 2D Nav Goal Publish Point
Displays
Global Options
Fixed Frame laser
Background Color 48; 48; 48
Frame Rate 30
Default Light
Global Status: Ok
Fixed Frame OK
Grid
Map
LaserScan
Status: Ok
Topic /scan
Unreliable
Selectable
Style Flat Squares
Size (m) 0,01
Alpha 1
Decay Time 0
Position Transformer XYZ
Color Transformer FlatColor
Queue Size 10
Color 255; 255; 255
LaserScan
Odometry
Marker
Status: Ok
Marker Topic /datmo
Queue Size 100
Marker Topic
visualization_msgs::Marker topic to subscribe to. _array will also automatically be subscribed with type visualization_msgs::MarkerArray.
Add Duplicate Remove Rename
Reset
31 fps