Introduction to Mobile Robotics

Olivier Aycard
Professor
Grenoble INP - PHELMA
GIPSA Lab
https://www.gipsa-lab.grenoble-inp.fr/user/olivier.aycard
olivier.aycard@grenoble-inp.fr

What is a robot ?

Robot = *mechatronic system with perception, decision and action skills,* capable of carrying out *different tasks in the real world, in an autonomous way.*

olivier.aycard@grenoble-inp.fr

The robot of the day



- 1 raspberry pi3:
  - ubuntu + ROS
- Sensors
  - 1 laserscanner
- Actuators
  - 2 wheels driven by 2 motors + encoders

- 1 PC Ubuntu + ROS
  - In charge of sensor data acquisition, processing & visualization;
  - In charge of controlling actuators.

olivier.aycard@grenoble-inp.fr

Outline

1. Sensors and actuators
2. ROS
3. Perception
4. Decision
5. Action
6. Examples of applications
7. Conclusion

Sensor (1/3)

- **A sensor** is an instrument measuring a physical property of the environment;
- Sensors are imprecise and limited;
- The environment of a robot is generally complex, changing, unpredictable and uncertain;
- Understanding the world in which a robot evolves remains a challenge.



Courtesy of sick

Sensor (1/3)

- **A sensor** is an instrument measuring a physical property of the environment;
- Sensc
- The e
  unpre
- Under
  challe



Courtesy of sick

Sensor (2/3)

- **Robair** is equipped with a 2D laser scanner (UST-15LX);
- The laser scanner has:
  - a range of about 6 to 15 meters;
  - a field of view of 270 degrees;
  - an angular resolution of 0.25 degrees *(configurable to 0.125)*.
- **Output**: a table with 1080 elements (r, Θ)
- Laser data are acquired in the trigonometric way
- Polar to cartesian:
  - X = r cos (Θ);
  - Y = r sin (Θ).
- Quality of data depends on distance, angle…
- The frequency of acquisition is 40 Hz
- The laser scanner costs about 1500 euros.

olivier.aycard@grenoble-inp.fr

Sensor (3/3)


Polar space:
(r[i], theta[i]) with i in [0..1080]
Cartesian space:
(x[i], y[i]) with i in [0..1080]
0 radian
Field Of View
(FOV)
r[540], theta[540]
x[540], y[540]
x
y
+π/2 radians
-π/2 radians
+ 2π/3
radians
- 2π/3
radians
r[1080], theta[1080]
x[1080], y[1080]
+π radians = -π radians
r[0], theta[0]
x[0], y[0]

Actuators of a mobile robot

- An **actuator** is a component of a machine that is responsible for moving or controlling a mechanism or system;
- An actuator controls a **degree of freedom** (rotation, translation);





- Actuators could be complex**.**



Courtesy of Thierry Fraichard

Actuators of robair (1/3)

- **Robair** has 2 wheels controlled by 2 motors;
- Robair is a differential drive robot;
- Simplest and most used kinematic model of robot.



- **A monocycle** describes a virtual circle of radius R;
- We have $V = R\,\omega$

Actuators of robair (2/3)

- **Robair** has 2 wheels controlled by 2 motors;



- We have $V = R\,\omega$
- We have $V_r = (R + w/2)\,\omega$
- We have $V_l = (R - w/2)\,\omega$

- We find:

$$R = \frac{W}{2}\frac{V_l + V_r}{V_r - V_l}$$

Actuators of robair (3/3)

- Finally, we have the direct kinematic model:

$$\dot{\omega} = \frac{V_r - V_l}{w} \quad (1) \qquad \dot{V} = \frac{V_l + V_r}{2} \quad (2)$$

- Controlling (V_l, V_r), we can determine (V, ω)

$$V_r = V + \frac{w}{2}\omega \qquad V_l = V - \frac{w}{2}\omega$$

- To simplify the control (at the beginning), we will perform translation OR rotation in place

Estimation of motion: encoder

- While Robair is moving in its environment, we would like to know its position in this environment;
- Its position is determined by its position (x, y) in the environment + its orientation θ: (x, y, θ)
- X-axis is aligned with the angle 0 of the laser



- On each wheel, there is a system (named encoder) able to estimate the distance traveled by each wheel over a short time Δt

Estimation of position: odometry (1/7)

- We call d_l and d_r the distance traveled by each wheel over

$d = \frac{d_r + d_l}{2}$ using (2) $\theta = \frac{d_r - d_l}{w}$ using (1)

- $x_t = x_{t-1} + d\cos(\theta)$
- $y_t = y_{t-1} + d\sin(\theta)$
- $\theta_t = \theta_{t-1} + \theta$

Estimation of position: odometry (2/7)

- When we start robair, odometry is (x=0m, y=0m,



Estimation of position: odometry (3/7)

- When we start robair, odometry is (x=0m, y=0m,



Estimation of position: odometry (4/7)

- When we start robair, odometry is (x=0m, y=0m,



Estimation of position: odometry (5/7)

- When we start robair, odometry is (x=0m, y=0m,



Estimation of position: odometry (6/7)

- When we start robair, odometry is (x=0m, y=0m,



Estimation of position: odometry (7/7)

- When we start robair, odometry is (x=0m, y=0m,



Outline

1. Sensors and actuators
2. ROS
3. Perception
4. Decision
5. Action
6. Examples of applications
7. Conclusion

ROS in a nutshell

- **ROS (Robot Operating System)** is a middleware for controlling robotic components from a PC: robots.ros.org;
- ROS is open source and a standard for software architecture development in robotics;

- ROS is based on 2 important concepts:
  1. A number of independent nodes;
  2. Messages (or topics) that are published by some nodes and subscribed by some nodes;
     => Messages are used to exchange information between nodes;

ROS in a nutshell

- **ROS (Robot Operating System)** is a middleware for controlling robotic components from a PC;
- ROS is open source and a standard for software architecture development in robotics;

- ROS is based on 2 important concepts:
  1. A number of independent nodes;
  2. Messages (or topics) that are published by some nodes and subscribed by some nodes;

- Next slides introducing ROS are based on 89-685: Introduction to Robotics (biu.ac.il) (lecture 1, slide 8-11)

Robots using ROS

- http://wiki.ros.org/Robots


Fraunhofer IPA Care-O-bot


Videre Erratic


TurtleBot


Aldebaran Nao


Lego NXT


Shadow Hand


Willow Garage PR2


iRobot Roomba

Robotnik Guardian


Merlin miabotPro


AscTec Quadrotor


CoroWare Corobot

Clearpath Robotics Husky

Clearpath Robotics Kingfisher


Festo Didactic Robotino

ROS nodes

- Single-purposed executable programs
  - e.g. sensor driver(s), actuator driver(s), mapper, planner, UI, etc.
- Individually compiled, executed, and managed
- Nodes are written using a ROS **client library**
  - C++ client library
  - python client library (not provided in this course)
- Nodes can publish or subscribe to a Topic

(C)2016 Roi Yehoshua

ROS topics

- A topic is a name for a stream of messages with a defined type
  - e.g., data from a laser range-finder might be sent on a topic called scan, with a message type of LaserScan
- Nodes communicate with each other by publishing messages to topics
- Publish/Subscribe model

(C)2016 Roi Yehoshua

ROS on robair (2/5)



When a node starts, it “advertises” itself on the network, making it visible to other nodes on the same machine or different machines.

ROS on robair (3/5)



When we start nodes on our laptop - such as teleoperation or rviz node - they will advertise themselves, and see the nodes and topics running on RobAIR.

ROS on robair (4/5)



Rviz will subscribe to /scan and /odom

ROS on robair (5/5)



Teleoperation node will publish /cmd_vel (ie, rotation and translation)

Outline

1. Sensors and actuators
2. ROS
3. Perception
4. Decision
5. Action
6. Examples of applications
7. Conclusion

Perception

Goal

- Robot perception in dynami environments
- **Laser scanner**
- Speed and robustness



Present Focus: interpretation of raw and noisy sensor data

- Identify static and dynamic part of sensor data
- Modeling dynamic part of the environment
  - Detection And Tracking of Moving Objects (DATMO)
- Modeling static part of the environment
  - Simultaneous Localization And Mapping (SLAM)

olivier.aycard@grenoble-inp.fr

Outline

1. Sensors and actuators
2. ROS
3. Perception
4. Decision
5. Action
6. Examples of applications
7. Conclusion

Decision/Plan of future actions

- Most of the time, a mobile robot has to move in its environment:
  - It needs to plan its future actions
- The mobile robot has a map and it knows where it is in the map (position A for instance);
- It should reach an other position in the map (position B for instance)
- **Question**: How to get there ?
- Answer: sequence of actions to go from A to B that is feasible and without collisic





West, South, East (12 times), North (6 times), West (twice)

Outline

1. Sensors and actuators
2. ROS
3. Perception
4. Decision
5. Action
6. Examples of applications
7. Conclusion

Action/control/navigation

- The mobile robot has a sequence of actions to execute, to reach its goal: it has to execute this sequence of actions:
  - Typical action in our case: “move to (x, y)”;
  - Monitoring of execution: we monitor what happen and react if needed.
    - We need to be able to estimate actions/motions of the mobile robot;
  - Collision detection/avoidance: the mobile robot should be able to detect (and avoid) collision.

Examples of applications(1/3)

- Advanced driver assistant system (ADAS) or autonomous vehicles

Darpa Urban Challenge 2007

Google car

IP Prevent 2008

Google car 2016

Examples of applications(2/3)

- Service robotics

Roomba

Robomow

Dyia One



Baxter

Staubli

Examples of applications(3/3)

- Companion robots

Paro

Aibo

Buddy

Nao

Pepper

Conclusion

- A mobile robot is equipped with 2 kind of sensors:
  - **Exteroceptive sensors** that give information about the environment (ie, laser scanner);
  - **Proprioceptive sensors** that give information about the internal state of the robot (ie, odometer);
- A mobile robot is equipped with some actuators characterized by their degree of freedom;
  - Robair is a differential drive robot;
- Sensors and actuators are imprecise and limited;
- The environment of a robot is generally complex, changing, unpredictable and uncertain.

Follow me behavior (1/2)

- We design, implement and test a simple “follow me” behavior in the next weeks in 2 steps



- 1st release of “follow me” behavior

Follow me behavior (2/2)

- We design, implement and test a simple “follow me” behavior in the next weeks in 2 steps



- 2nd release of “follow me” behavior