

Argumentative recommenders: a new kind of recommendation systems

Olivier Cailloux and Florian Yger

Université Paris-Dauphine, PSL Research University, CNRS, LAMSADE, 75016
PARIS, FRANCE
olivier.cailloux@dauphine.fr

January 2, 2019

Recommender systems aim at recommending some item as most appropriate for the user. This article introduces a new way of measuring appropriateness for the user: an item is among the most appropriate ones if it is among the preferred items of the user when considering all arguments in favor or against all possible items. We describe precisely this goal and describe what a recommender system aiming for that goal could look like, called an Argumentative Recommender. We also provide a way of testing whether a recommender system has achieved the goal, which can be used to compare such recommender systems, and outline a way of building such a system.

1 Introduction

In a situation where a user has to choose an item among a set of possible items, recommender systems aim at recommending some item as most appropriate for the user. In the collaborative learning community, this is usually taken to mean: recommend an item

among the most preferred for the user. In this article, we want to propose another goal for recommender systems. We keep the global aim of recommending some item as most appropriate for a given user, but propose a different understanding of appropriateness. The goal we propose is to recommend an item among those that are in the Deliberated Preference (DP) of the user, and to prove that it does. The DP of the user captures what she prefers when considering all arguments in favor or against all possible items. This differs from her intuitive preference in that the latter does not consider arguments. Thus, the goal we propose is appropriate when one is interested to help the user form a deliberated judgment about which item is best, rather than predict which item the user intuitively prefers. Because this will be done using systems that argue, we call the kind of system we define here an AR. Further motivations for this new goal are described in section 2, and it is precisely defined in section 3.

Together with this new goal, it is necessary to propose a corresponding measure of the performance of the recommender system (done in section 4). In the classical approach, measuring the performance of the system amounts to compare its claims (the items it proposes as preferred) to reality (the preference of the user). Because the DP of the user is not directly observable, this direct check of correspondance becomes non applicable. However, as will be showed, the problem of evaluating the quality of an AR can be framed as a prediction problem (although involving different objects), thereby recovering the possibility of empirical validation by confrontation between claims of the system and reality.

Section 5 relates our proposal to the literature. Sections 6 and 7 then sketch one possible way of undertaking this task, applicable in specific contexts: recommend on the basis of explicit principles coming from decision theory.

This article is an extended version of Cailloux [2018].

2 Motivation

This article discusses a notion of preference that possibly changes when confronted to arguments. That is, we assume that the user's knowledge of which item is best for him is not necessarily fixed a priori, and in particular, that the user may change his mind

when presented with arguments in favor of, or counter-arguments against, various items.

By contrast, the notion of preference considered by classical recommender systems (usually left implicit) is that the user intuitively knows what he prefers, and that this is the right basis for him to decide. This notion can be related to the conception of preference put forth by von Neumann and Morgenstern [1944, p. 16] in their seminal work (cited by Fishburn [1989]). They write that “It is clear that every measurement – or rather every claim of measurability – must ultimately be based on some immediate sensation (...). In the case of utility the immediate sensation of preference (...) provides this basis.” When applied to collaborative filtering, this view suggests that the user does not need help for comparing pairs of item: the job of the system is merely to relieve the user from having to search through the whole set. The user, when presented with a pair of items, knows which one he prefers by introspection, possibly after having tried them both. Similarly, when the user has already provided some comparisons of preference, this is the final word about those pairs.

This notion of preference as “intuitive” preference is not always the best basis to ground recommendation. Indeed, the user might be unwilling to judge what is best for her on the sole basis of her unaided intuition. First, there are cases where the user can’t easily try out the items. An example is a non repeatable choice, such as choosing a university to study in. Second, the best choice might be the result of a complex thought process that should better ensure, as much as possible, that all relevant arguments have been considered, rather than purely rely on intuition. Consider the decision of which smartphone, or which house, to buy. This is also easily the case when a notion of fairness is involved, for example when determining who will receive a prize, or how to best distribute revenue in a society, or to which cause I should donate money. Third, the user might appreciate being pointed to some non-salient feature of the items under comparison; for example, a user might feel an intuitive attraction to the plane alternative when choosing a transportation means for holidays, seeing that the flight time is only one hour compared to three hours by train, but change her mind when being reminded that the total travel time should be taken into account. Finally, an argument coming from psychology is that unaided intuition is known to be sensible, in some contexts, to framing

effects that would perhaps not be considered relevant (by the user himself) when considering arguments and counter-arguments [Kahneman, 2013]. An example that involves several kinds of the just enumerated concerns is obtaining a decision procedure for credit requests in a bank: the user probably wants to involve fairness considerations in order to avoid (possibly unconscious) appearance of unjust discriminations; and even if only profit considerations are to bear, the user might want the procedure to go beyond reflecting the bare intuition of an expert.

3 Definition of deliberated preference

This section describes the new understanding of preference I propose, called the DP of the user (it is a simplification of the recently proposed concept of deliberated judgment [Cailloux and Meinard, 2018]).

I consider given a set of items \mathcal{J} among which a user i wants to choose. I also consider given a set S^* containing arguments that may possibly help i form a deliberated opinion about which item is best for her. Elements of S^* are not detailed and can be conceived as strings in a natural language. An example of an argument is $s =$ “Item j is better than item j' because j has a good performance on criteria ‘price’ and ‘speed’ while item j' has a good performance only on criterion ‘aspect’, which you do not consider important”.

The DP of i is defined as the subset of items that are considered by i as having no item strictly preferred to them, considering all arguments in S^* . To define this properly, we assume we can observe the reaction of i to arguments, as follows.

Define \triangleright as a binary relation over $\mathcal{J} \times S^*$, representing the results of the following experiments. Present (j, s) and (j', s') to i and let her decide, considering the arguments s and s' , which item among j and j' she prefers, if any. Define $(j, s) \triangleright (j', s')$ iff i strictly prefers j to j' , given s and s' . Note that if no strict preference holds, \triangleright does not relate these two pairs (thus $(j, s) \not\triangleright (j', s')$ and $(j', s') \not\triangleright (j, s)$). If the answer of the individual changes when asked several times the same question, we consider that no strict preference holds, as we are interested in the stable part of the individual’s judgement. The relation \triangleright plays here the role of the basic observable von Neumann and Morgenstern talk about (see section 2).

The DP $J_i \subseteq \mathcal{J}$ of i in that situation contains an item j iff $\forall (j', s') \in \mathcal{J} \times S^*, \exists s \in S^* \mid (j', s') \not\triangleright (j, s)$.

4 Prediction of deliberated preference

An AR should be able, given a user, to single out some items as being in his DP, and some items as being not in his DP, and to defend its claims by arguing correspondingly. Formally, an AR η has a *scope* I , representing a set of users it claims to be able to predict the DP of, and gives, for a user $i \in I$, a tuple $(J_\eta, f_\eta^{\text{def}}, R_\eta, f_\eta^{\text{att}})$, where $J_\eta \subseteq \mathcal{J}$ is a set of items that η claims are among the DP of i , $f_\eta^{\text{def}} : J_\eta \times \mathcal{J} \rightarrow S^*$ is an argumentation strategy used to defend items in J_η , $R_\eta \subseteq \mathcal{J} \times \mathcal{J}$ is a binary relation that contains pairs of items (j, j') such that η claims that i deliberately prefers j to j' , and $f_\eta^{\text{att}} : R_\eta \rightarrow S^*$ is an argumentation strategy used to support the claims represented by R_η . (Elements of this tuple depend on i , though this is omitted from the notation.)

An AR is valid if its functions f_η^{def} and f_η^{att} indeed justify its claims. Informally, it is required of f_η^{def} that, when given an item j' and given an item $j \in J_\eta$ considered by η as being in the DP of i , f_η^{def} produces an argument that successfully defends j , whatever the argument given in favor of j' . More precisely and completely, an AR η is said to be *correct* about a user i iff $\forall j \in J_\eta, j' \in \mathcal{J}, s' \in S^* : (j', s') \not\triangleright (j, f_\eta^{\text{def}}(j, j'))$ and $\forall (j, j') \in R_\eta, s' \in S^* : (j, f_\eta^{\text{att}}(j, j')) \triangleright (j', s')$. An AR is *valid* iff it is correct about all users in its scope.

Importantly, validity implies the correctness of the claims concerning the DP of i . This fact is stated formally below, with $J_\eta^\downarrow = R_\eta(\mathcal{J}) = \{j' \in \mathcal{J} \mid (j, j') \in R_\eta \text{ for some } j \in \mathcal{J}\}$. (The proof is omitted.)

Theorem 1 *If an AR η is valid, then $\forall i \in I : J_\eta \subseteq J_i$ and $J_\eta^\downarrow \subseteq \mathcal{J} \setminus J_i$.* \square

This notion of validity cannot be used to definitely prove that a recommender system has correctly captured i 's DP. But it can be used to *compare* ARs, in the following way. Consider two ARs η and η' dealing with the same set of items \mathcal{J} and having overlapping scopes (so that the intersection of the users in their scopes is not null). Such ARs could for example have been built

by different research teams studying the same recommendation setting. Considering a user i in both their scopes, obtain two tuples, $(J_\eta, f_\eta^{\text{def}}, R_\eta, f_\eta^{\text{att}})$ and $(J_{\eta'}, f_{\eta'}^{\text{def}}, R_{\eta'}, f_{\eta'}^{\text{att}})$. Assume they strongly disagree on the prediction of the DP of i , meaning that for some item $j \in \mathcal{J}$, the first system claims that j is in the DP of i , thus $j \in J_\eta$, and the second system claims it is not, thus $\exists j' \mid (j', j) \in R_{\eta'}$. Suffices now to let the two systems play against each other and use i as a judge. That is, we obtain an argument from the first system in defense of its claim, $s = f_\eta^{\text{def}}(j, j')$, and an argument from the second system, $s' = f_{\eta'}^{\text{att}}(j', j)$. We present (j, s) and (j', s') to i and accordingly obtain $(j', s') \triangleright (j, s)$ or $(j', s') \not\triangleright (j, s)$. In the first case, the first system is invalidated, in the second one, the second system is invalidated.

5 Relation to existing literature

Approaches exist which propose to estimate a decision-theoretic model that best approximates a user’s observed behavior [Greco et al., 2010, Sobrie et al., 2018]. Furthermore, numerous approaches have been proposed for modeling preferences using machine learning methods [Fürnkranz and Hüllermeier, 2010]. Several recent articles in particular use active learning approaches to build a preference model of a user in a recommendation setting [Teso et al., 2016, 2017, Dragone et al., 2018b, Erculiani et al., 2018, Dragone et al., 2018a]. Yet other approaches propose to use argumentation theory to enhance recommender systems [Chesñevar et al., 2009, Rago et al., 2018]. These trends constitute promising areas of investigation for building ARs. Such articles typically are focused towards producing recommender systems on the basis of some principles chosen by the authors. By comparison, this article proposes a precise definition of a new goal for similar argumentative systems (which may or may not be similar to the goal the authors of the cited articles have in mind), and a way of comparing ARs experimentally when their predictions disagree.

The idea of using a human as a judge to compare argumentative systems also appears in the paper of Irving et al. [2018]. There are also articles that are interested in using collaborative filtering on the basis of implicit feedback [Rendle et al., 2009, Hu et al., 2008], an idea somewhat related to ours in the sense that the observed

data is not directly the one the model tries to predict. Also somewhat related are articles interested in collecting preference data for improving the learning [Sepiarskaia et al., 2018]. Chen et al. [2018] review techniques that make use of supplementary data in collaborative filtering tasks. Johnson [2014] uses logits for matrix factorization. [OC: Should we say one word about this?] An important literature analyzes necessary and sufficient conditions for the existence of various decision-theoretic models [Krantz et al., 1971, Gonzales, 1996, Bouyssou and Pirlot, 2015], this will be important in conjunction with the approach for building ARs on the basis of such models as exposed in section 6.

Finally, this proposal is intimately related to the important literature on explainable AI [Zhang and Chen, 2018].

6 Recommend on the basis of explicit principles

Section 3 described a new kind of recommender system, that consider the recommendation task under a different light, and section 4 described how to evaluate such ARs. But such ARs do not exist yet. One way of building such systems consists in adapting existing works (related references are given in section 5). Another way is to design an AR from the ground up specifically for tackling the goal described here. Although it is not the main point of this conceptual article, roughly sketching a possible way of doing this could help make this proposal more concrete. This section first briefly describes such a possible way in the context of collaborative settings, then indicates some conditions on the context that must be fulfilled in order to make the proposed approach applicable. The next section more concretely sketches a way of learning such a model and of studying its performances with numerical experiments.

Consider a collaborative learning setting, where we have collected ratings from users on items, assumed to represent their intuitive rather than deliberated preference. A simple approach to build a proof-of-concept AR in such a context is to represent the DP of i as a weak order $\succeq \subseteq \mathcal{J} \times \mathcal{J}$, and to consider this weak order as representable by a decision theoretic model.

The weak order \succeq corresponds to R_η and its maximal elements

correspond to J_η (though the definition tolerates other possibilities). Decision theory has proposed models to represent preferences of decision makers. Even though decision theory does not explicitly use the concept of deliberated preferences as defined here, because its models are conceived for grounding decisions in sound principles, they might be adequate to model deliberated preferences. The model adopted for this article is Multiple Attribute Value Theory (MAVT) [Keeney and Raiffa, 1993], a set of principles for choice well-known in decision theory.

Existing works [Carenini and Moore, 2006, Labreuche, 2011] describe how to generate arguments in natural language that explain, on the basis of an MAVT model, why an alternative is preferred to another one. This provides a starting point for the step of generating arguments. More generally, by picking functions supported by well-studied decision principles, it is made possible to build arguments on the basis of those same principles, and it might be considered that such arguments will have a fighting chance against counter-arguments.

Finally, assume the intuitive behavior of the user is a noisy version of her DP. (More elaborated developments could incorporate knowledge from experimental psychology about differences between the usual behavior of users and the one dictated by decision-theoretic models [Kahneman, 2013].) Then, our task becomes close to one of classical collaborative learning, as MAVT defines the class of functions among which to select an optimal one during learning. The next section draws on this approach to effectively propose an MAVT-based AR.

The principles on which MAVT rests are applicable in specific contexts: those in which the items (among which the user aims to choose) can be exhaustively described by a set of objective descriptors of the items, known a priori, and which each evaluate the desirability of the items on some aspect. Such aspects are called criteria. Exhaustively described means that the user considers nothing else than the performance of the items on the criteria as relevant for the recommendation. Thus, consider a set of criteria \mathcal{C} is known, together with corresponding scales $X^c, c \in \mathcal{C}$, and descriptors $b^c : \mathcal{J} \rightarrow X^c, c \in \mathcal{C}$, that each describe the items on a specific criterion c . Here we use superscripts for criteria indices because we will need subscripts for user indices; these superscripts do not represent exponentiation.

In such a context, an MAVT model representing \succeq is a set of functions $v^c : X^c \rightarrow \mathbb{R}$ (one for each criterion) such that $j \succeq j'$ iff $\sum_{c \in C} v^c(b^c(j)) \geq \sum_{c \in C} v^c(b^c(j'))$.

Consider as an example the choice of an apartment to rent for holidays. The set of criteria might be: surface of the living room, number of beds, distance to city center, modernity of equipment, presence of a washing machine, price. Other examples where building an AR on the basis of an MAVT model may be appropriate include: buying a smartphone, buying a computer, choosing a flight to reach a given place, choosing who to give a “best student” award among a given classroom, locating a new factory, or choosing a university to study at.

By contrast, a recommendation task is not suitable for the approach proposed in this section if no set of criteria is known that fully describe the desirability of an item. For example, a choice of movie to watch this evening.

7 Estimating an MAVT model

We are finally left with the concrete task of learning MAVT models that represent the users’ DPs in a collaborative learning setting.

Assume we have a set of users I of size $m \in \mathbb{N}$, a set of items J of size $n \in \mathbb{N}$, a set of observed pairs $O \subseteq I \times J$ and a relation r mapping those observed pairs $(i, j) \in O$ to some rating r_{ij} , an integer in $\llbracket 1, 5 \rrbracket$ (this notation designates intervals in the integers). We also assume known the set of criteria \mathcal{C} of interest to the user (see section 6). Each criterion $c \in \mathcal{C}$ is associated to a (known) descriptor $b^c : J \rightarrow [0, 1]$ which represents the performances of the items on the given criterion. Thus, the scales X^c used for measuring the objective performances of the criteria are here all supposed to be $[0, 1]$, for simplicity.

7.1 MAVT with logits

In order to learn an MAVT model per user, we choose here to learn partial value functions that have the same shape for all users, and let the weights of these partial functions vary individually. This assumes that users appreciate trade-offs within a criterion in a similar way, but are differentiated by the importance they give to different

criteria. The partial value functions are represented by parameterized logit functions, defined as $\sigma(\alpha, \beta, x) = \frac{1}{1 + \alpha e^{-\beta x}}$. Thus, the parameters are α^c, β^c , for each criterion c , used for representing the partial value functions shapes; and w_i^c , for each criterion c and user i .

Let L denote a loss function that compares the ratings r_{ij} to our approximations of the ratings, for $(i, j) \in O$; let λ denote a real number used to ponder our two objectives, one aiming for a best fit, another aiming for regularized weights; and let $\|\cdot\|_2^2$ denote the squared L2 norm [OC: Problem below, we should apply the norm to a vector, I suppose].

We want to find $\{w_i^c, i \in I, c \in \mathcal{C}\}, \{\alpha^c, c \in \mathcal{C}\}, \{\beta^c, c \in \mathcal{C}\}$ that optimize the following objective:

$$\min_{w, \alpha, \beta} \sum_{(i, j) \in O} L(r_{ij}, \sum_{c \in \mathcal{C}} w_i^c \sigma(\alpha^c, \beta^c, b^c(j))) + \lambda \sum_{i \in I, c \in \mathcal{C}} \|w_i^c\|_2^2.$$

We force w_i^c and α^c positive to respect the preference direction: we assume the data is encoded so that higher $b^c(j)$ means preferred performance.

This is now a classical learning task that can be achieved by classical means. [OC: Florian: perhaps say (in one sentence?) what we do here, with a reference if appropriate?]

We define the partial value functions v_i^c and aggregated value function v_i representing our estimation of the deliberated preferences of user i as $v_i^c(j) = \sigma(\alpha^c, \beta^c, b^c(j))$ and $v_i(j) = \sum_{c \in \mathcal{C}} w_i^c v_i^c(j)$.

7.2 Learning an absolutely-scaled version of MAVT

The foregoing approach must be slightly adapted before being usable in the context we postulated. The ratings $r_{ij} \in \llbracket 1, 5 \rrbracket$ that we observe are given on an absolute scale: the lowest point (1) is meaningful, and the unit is fixed. On the contrary, the evaluations given by a classical MAVT model have no zero and no unit: given a value function v representing the user's preferences, the value function $v' = \alpha + \beta v$ represents it equally well, for any constant α and positive constant β .

To bridge this discrepancy, we add a fictitious criterion d and extend the set of criteria to $D = \mathcal{C} \cup \{d\}$. The learned aggregated value function thus becomes $v_i = \sum_{c \in D} w_i^c v_i^c$. The partial value function v_i^d associated to that added criterion is constant, equal

to one for its whole domain. The associated weight w_i^d , which is learned together with the other parameters, is used to indicate the “bias” of the user i . It is interpreted as the value of the “zero” item: if an item has all zero performances, its rating is w_i^d . If an item fares better than the zero item, v_i will increase its rating. A consequence of this choice is that the whole range of the scale is not used, which might correspond to the rating behavior of real users. Furthermore, the learned weights are not normalized, and are designed to be interpreted in an absolute sense: w_i^c represents the number of stars added by the corresponding criterion when the item is perfect on that criterion, from the point of view of user i .

Our final learning task becomes:

$$\min_{w, \alpha, \beta} \sum_{(i,j) \in O} L(r_{ij}, \sum_{c \in \mathcal{C}} w_i^c \sigma(\alpha^c, \beta^c, b^c(j)) + w_i^d) + \lambda \sum_{i \in I, c \in D} \|w_i^c\|_2^2.$$

7.3 Testing with empirical data

The obtained model can be tested in two very different ways. One would involve treating it properly as an AR, and confronting its propositions to the judgements of real users, by comparing its propositions to the ones of another AR, as indicated in section 4. This is however not yet applicable here, as our model does not produce arguments: we only sketched a first step, aimed at learning MAVT models, which should be included in a strategy similar to the one proposed in section 6 to obtain a full-fledged AR.

Another way to test the obtained model, simpler but less satisfactory, is the more familiar comparison of the predictions of the model to a pre-existing database of (intuitive) preference data. Although the goal of an AR is not to merely predict intuitive preferences (but rather to predict deliberated preferences), it can still be instructive to see how the obtained AR performs with this task. However, because the learning goal we propose is new, it is difficult to find suitable empirical datasets to achieve this comparison. Such dataset should include items that can be objectively described on a set of criteria (such as hotels or smartphones), together with their descriptions, as explained in section 6, and with ratings given by several users, as in a collaborative setting. Such datasets certainly exist within databases of web vendors, or probably could be created by combining several sources of information, but we have not found ready-made publicly available ones. We observe that this

is a common problem within recent research involving elaborated preference models, for example, Teso et al. [2016] also use artificial data to test their proposal.

For illustrative purposes, we describe here the Sushi dataset [Kamishima, 2003]. It is not fully appropriate for our task because it has very few objective descriptors, and because the task of appreciating sushis probably does not mandate much deliberation. But it is formally applicable in our setting as it contains several users evaluating a set of items whose objective description is (unfortunately only partially) known. [OC : Je crois que la description n’apporte rien. On ferait peut-être mieux de citer simplement ce jeu de données, et de s’arrêter là, en attendant d’en faire vraiment quelque chose. Si on la garde, il faut décider si on supprime les descriptions des données qu’on n’utilise pas, tel que $>_i^{\text{top}}$. En fait, plus j’y pense, et plus je trouve qu’on ferait mieux de le laisser tomber complètement, car il n’est vraiment pas approprié pour nous (on ne sait même pas si la description “frequency”, par exemple, représente vraiment qqch. d’objectif et d’où elle vient). Je propose donc de supprimer ce § et ce qui suit.]

In this dataset, J is a set of 100 sushi types. The original authors collected the sushi from the menu of 25 restaurants, computed the frequency of each sushi type occurring on a menu, and took the 100 most frequent. Write P_J the frequency (thus a multiple of $1/25$).

Write $J_{\text{top}} \subset J$ the 10 most frequent sushi types.

The set I has cardinal $m = 5000$. The authors drew randomly a set of 10 sushi types among J , for each user i , according to the distribution P_J . Let us denote this by $J_i \subset J$.

The authors obtained, for each user i in I , three preferential informations, defined as strict partial orders (transitive, asymmetric binary relations). First, they collected a preference ordering over the sushi types from J_{top} from most to least preferred, with no tie allowed. Let $>_i^{\text{top}}$ denote that preference ordering (“top” designates the fact that the ordering is over the 10 most frequent sushi types). Second, they collected a rating, in $\llbracket 1, 5 \rrbracket$, for each sushi type in J_i . Define O as the set of pairs (i, j) such that $j \in J_i$, and let r_{ij} denote that rating. Third, after two supplementary questions asking how oily the user thinks each sushi type is and how frequently they eat them, they collected a preference ordering over J_i , that we write $>_i^{\text{indiv}}$ (“indiv” designates the fact that this relation orders a set of sushi that has been drawn specifically for that user).

Users are described in a space A comprising the attributes

{gender, age category, origin-prefecture, origin-region, origin-east/west (binary), current-region, current-east/west (binary), origin-prefecture}. Items are described in a space B comprising the attributes {group, heaviness/oiliness in taste (in $[0, 4]$), frequency of eating (in $[0, 3]$), normalized price (in $[0, 1]$), $P_J(j)$ }.

7.4 Testing with artificial data

The model can be tested with artificial data, in order to see how robust it is facing perturbations in the data we learn from. This section describes how such data could be generated.

Let us consider that users share a personally-scaled and noisy version of an additive value representation. Let $l(x^1, x^2)$, with $x^1, x^2 \in [0, 1], x^1 < x^2$, denote the piecewise linear partial value function $f : [0, 1] \rightarrow [0, 1]$, with discontinuity points at x^1 and x^2 and $f(0) = 0, f(x^1) = 1/3, f(x^2) = 2/3, f(1) = 1$.

We define partial value functions for each user and criteria so that the average v^c (over all users) is $l(x^{c,1}, x^{c,2})$, with $x^{c,1}$ drawn from a $t(0, 1/2)$ distribution, where $t(a, b)$ denotes the symmetric triangular distribution with extreme points a and b , and $x^{c,2}$ drawn from a $t(1/2, 1)$ distribution. For each user i and criterion c , we draw the perturbation parameters $\alpha_i^{c,1}$ from $t(-0.5x^{c,1}, 1/2x^{c,1})$ and $\alpha_i^{c,2}$ from $t(-0.5(1 - x^{c,2}), 1/2(1 - x^{c,2}))$, and define $v_i^c = l(x^{c,1} + \alpha_i^{c,1}, x^{c,2} + \alpha_i^{c,2})$.

We draw the weights of the user i (for each i) by drawing ω_i^c , for each criterion, from $tN(1/2, 0.1)$, where tN denotes a normal distribution truncated at zero and one. Then we define w_i as the normalization of ω_i (so that $\sum_c w_i^c = 1$).

These parameters define together the value functions of each individual: given an item j , $v_i(j) = \sum_c w_i^c v_i^c(b_j^c)$. This number is between 0 and 1, with 1 representing an ideal item. Furthermore, for each invocation of v_i , we draw an error term ϵ from $N(0, 0.1)$, representing the noise, where N denotes a normal distribution, and use effectively $v_i' = v_i + \epsilon$.

We draw randomly the performances of a set of items \mathcal{J} . For each $j \in \mathcal{J}$ and criterion $c \in \mathcal{C}$, b_j^c is drawn from $tN(0.5, 1)$. Because it is known that users do not tend to use the full range of the scale offered to them when rating items, we assume a non linear relation from v_i' to the rating. We draw, for each user i , a number z_i from a $N(2, 1)$ distribution truncated at zero, scale v_i

with $s_i = 5 - z_i$ so that the best item gets five stars, and define $r_{ij} = [s_i v'_i(j) + z_i]$, where the brackets designate the operation of rounding to the closest integer.

8 Conclusion

The main goal of this article is to propose a new goal for recommendation systems. Such systems argue for their propositions, and are appropriate when the user does not a priori know which item to choose, not just because of the difficulty of exploring the set of items to choose from, but because of the difficulty of forming a coherent preference. Thus, such systems are appropriate when the user desires some help for choosing in a systematic or principled way by taking all relevant arguments into account. The article presented the idea generally and abstractly in sections 1 to 5.

A second goal of this article is to sketch a way of building such ARs. To this aim, the next two sections became progressively more concrete and less general. Section 6 proposed a way of building an AR by learning models as proposed in decision theory. The intuition is that, first, such models are particularly appropriate to help a user deliberate; second, such models can be learned reasonably easily using techniques known in machine learning; third, such models can “reasonably easily” be used to generate textual arguments understandable by a decision maker thanks to the already existing works in this direction in artificial intelligence and the axiomatic works in decision theory. Section 7 illustrated the second point by describing a way of learning an MAVT model in a collaborative learning setting.

It is important to realize that the general part of this article (sections 2 to 4) is not conceptually dependent on its most concrete parts (sections 6 and 7). ARs could be built on different basis than decision-theoretic models. For example, gathering existing arguments in textual forms on various sources on the web and displaying them as-is to the user, or using natural language processing techniques. Similarly, the concept could be applied to settings different than collaborative learning, or using learning techniques different than the one section 7 investigates.

This article has only began to explore the difficulties that need to be overcome in order to build a complete AR, let alone a work-

ing ecosystem of ARs. The concrete approach presented in the later part of this article may be judged naïve, and is incomplete as it does not indicate how to generate arguments from the models learned. Furthermore, methodological issues are to be explored, a work that is also only beginning [Cailloux and Meinard, 2018, Meinard and Cailloux, 2018]: it needs to be guaranteed that ARs are not used as propagandist devices to convince users to do what the conceiver of a particular AR desires; on the contrary, a proper debating environment has to be set up (section 4 describes how to let two ARs “debate”), where sufficiently diverse sources of opinions produce ARs, thereby producing the conditions for making reasonably sure that the user’s deliberated judgement has been reached. Only in such conditions will this environment be able to help the user legitimately.

References

- D. Bouyssou and M. Pirlot. A consolidated approach to the axiomatization of outranking relations: a survey and new results. *Annals of Operations Research*, 229(1):159–212, 2015. ISSN 0254-5330. doi:10.1007/s10479-015-1803-y.
- O. Cailloux. Learning argumentative recommenders. Nov. 2018. URL <https://da2pl.cs.put.poznan.pl/programme/detailed-programme>. In DA2PL: From Decision Aiding to Preference Learning.
- O. Cailloux and Y. Meinard. A formal framework for deliberated judgment. *arXiv:1801.05644 [cs]*, Jan. 2018. URL <http://arxiv.org/abs/1801.05644>.
- G. Carenini and J. D. Moore. Generating and evaluating evaluative arguments. *Artificial Intelligence*, 170(11):925–952, 2006. ISSN 0004-3702. doi:10.1016/j.artint.2006.05.003.
- W.-H. Chen, C.-C. Hsu, Y.-A. Lai, V. Liu, M.-Y. Yeh, and S.-D. Lin. Attribute-aware Collaborative Filtering: Survey and Classification. *arXiv:1810.08765 [cs, stat]*, Oct. 2018. URL <http://arxiv.org/abs/1810.08765>. arXiv: 1810.08765.

- C. Chesñevar, A. G. Maguitman, and M. P. González. Empowering Recommendation Technologies Through Argumentation. In G. Simari and I. Rahwan, editors, *Argumentation in Artificial Intelligence*, pages 403–422. Springer US, Jan. 2009. URL https://doi.org/10.1007/978-0-387-98197-0_20.
- P. Dragone, G. Pellegrini, M. Vescovi, K. Tentori, and A. Passerini. No More Ready-made Deals: Constructive Recommendation for Telco Service Bundling. In *RecSys 2018: Proceedings of the Twelfth ACM Conference on Recommender Systems*, pages 163–171. ACM, Oct. 2018a. URL <http://disi.unitn.it/~passerini/papers/recsys18.pdf>.
- P. Dragone, S. Teso, and A. Passerini. Constructive Preference Elicitation over Hybrid Combinatorial Spaces. In *Proceedings of the 32nd Conference on Artificial Intelligence (AAAI)*, 2018b. URL http://disi.unitn.it/~passerini/papers/aaai18_store.pdf.
- L. Erculiani, P. Dragone, S. Teso, and A. Passerini. Automating Layout Synthesis with Constructive Preference Elicitation. In *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD 2018)*, 2018. URL <http://disi.unitn.it/~passerini/papers/ecmlpkdd18.pdf>.
- P. C. Fishburn. Retrospective on the utility theory of von Neumann and Morgenstern. *Journal of Risk and Uncertainty*, 2(2):127–157, June 1989. doi:10.1007/BF00056134.
- J. Fürnkranz and E. Hüllermeier, editors. *Preference Learning*. Springer, Oct. 2010. ISBN 3-642-14124-2. URL <http://doi.org/10.1007/978-3-642-14125-6>.
- C. Gonzales. Additive Utilities When Some Components Are Solvable and Others Are Not. *Journal of Mathematical Psychology*, 40(2):141–151, June 1996. ISSN 0022-2496. doi:10.1006/jmps.1996.0013.
- S. Greco, M. Ehrgott, and J. R. Figueira, editors. *Trends in Multiple Criteria Decision Analysis*. Springer US, 2010.

ISBN 978-1-4419-5903-4. URL <https://doi.org/10.1007/978-1-4419-5904-1>.

- Y. Hu, Y. Koren, and C. Volinsky. Collaborative Filtering for Implicit Feedback Datasets. In *Proceedings of the Eighth IEEE International Conference on Data Mining*, pages 263–272, Dec. 2008. doi:10.1109/ICDM.2008.22.
- G. Irving, P. Christiano, and D. Amodei. AI safety via debate. *arXiv:1805.00899 [cs, stat]*, May 2018. URL <http://arxiv.org/abs/1805.00899>.
- C. C. Johnson. Logistic Matrix Factorization for Implicit Feedback Data, 2014. URL <https://web.stanford.edu/~rezab/nips2014workshop/>. NIPS 2014 Workshop on Distributed Machine Learning and Matrix Computations.
- D. Kahneman. *Thinking, fast and slow*. Farrar, Straus and Giroux, New York, 2013. ISBN 978-0-374-53355-7.
- T. Kamishima. Nantonac Collaborative Filtering: Recommendation Based on Order Responses. In *Proceedings of the Ninth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '03, pages 583–588, New York, NY, USA, 2003. ACM. ISBN 978-1-58113-737-8. doi:10.1145/956750.956823.
- R. L. Keeney and H. Raiffa. *Decisions with Multiple Objectives: Preferences and Value Tradeoffs*. Cambridge University Press, 2nd edition, Aug. 1993. ISBN 978-0-521-43883-4.
- D. Krantz, R. Luce, P. Suppes, and A. Tversky. *Foundations of measurement*, volume 1: Additive and polynomial representations. Academic Press, New York, 1971.
- C. Labreuche. A general framework for explaining the results of a multi-attribute preference model. *Artificial Intelligence*, 175(7–8):1410 – 1448, 2011. ISSN 0004-3702. doi:10.1016/j.artint.2010.11.008.
- Y. Meinard and O. Cailloux. Justification and decision analysis, 2018. Submitted.

- A. Rago, O. Cocarascu, and F. Toni. Argumentation-Based Recommendations: Fantastic Explanations and How to Find Them. *Electronic proceedings of IJCAI 2018*, pages 1949–1955, 2018. doi:10.24963/ijcai.2018/269.
- S. Rendle, C. Freudenthaler, Z. Gantner, and L. Schmidt-Thieme. BPR: Bayesian Personalized Ranking from Implicit Feedback. In *Proceedings of the 25th Conference on Uncertainty in Artificial Intelligence, UAI '09*, pages 452–461. AUAI Press, 2009. ISBN 978-0-9749039-5-8. URL <http://dl.acm.org/citation.cfm?id=1795114.1795167>.
- A. Sepiliarskaia, J. Kiseleva, F. Radlinski, and M. de Rijke. Preference elicitation as an optimization problem. In *RecSys 2018: Proceedings of the Twelveth ACM Conference on Recommender Systems*. ACM, Oct. 2018.
- O. Sobrie, V. Mousseau, and M. Pirlot. Learning monotone preferences using a majority rule sorting model. *International Transactions in Operational Research*, 2018. ISSN 1475-3995. doi:10.1111/itor.12512. In press.
- S. Teso, A. Passerini, and P. Viappiani. Constructive Preference Elicitation by Setwise Max-Margin Learning. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence, IJCAI 2016, New York, NY, USA, 9-15 July 2016*, pages 2067–2073, 2016. URL <http://disi.unitn.it/~passerini/papers/ijcai16.pdf>.
- S. Teso, P. Dragone, and A. Passerini. Coactive Critiquing: Elicitation of Preferences and Features. In *Proceedings of the 31st Conference on Artificial Intelligence (AAAI)*, 2017. URL <http://disi.unitn.it/~passerini/papers/aaai2017.pdf>.
- J. von Neumann and O. Morgenstern. *Theory of games and economic behavior*. Princeton university press, 1944.
- Y. Zhang and X. Chen. Explainable recommendation: A survey and new perspectives. *CoRR*, abs/1804.11192, 2018. URL <http://arxiv.org/abs/1804.11192>.