

# Linear Time Membership in a Class of Regular Expressions with Counting, Interleaving and Unordered Concatenation

Dario Colazzo

joint work with Giorgio Ghelli and Carlo Sartiani

appeared in ACM TODS

April 18, 2019 - JDL

# Regular expressions

- ▶ Ubiquitous in database and programming languages
  - ▶ data extraction from text
  - ▶ path expressions in query languages over tree- and graph-shaped data

# Regular expressions

- ▶ Ubiquitous in database and programming languages
  - ▶ data extraction from text
  - ▶ path expressions in query languages over tree- and graph-shaped data
- ▶ Standard REs:

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T^*$$

- ▶ Example
  - ▶  $T = a \cdot (c + d)^* \cdot (f + \epsilon)$
  - ▶  $L(T) = \llbracket T \rrbracket = \{a, af, acf, acb, acbf, acbb, acbbf, \dots\}$

# Regular expressions

- ▶ Ubiquitous in database and programming languages
  - ▶ data extraction from text
  - ▶ path expressions in query languages over tree- and graph-shaped data
- ▶ Standard REs:

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T^*$$

- ▶ Example
  - ▶  $T = a \cdot (c + d)^* \cdot (f + \epsilon)$
  - ▶  $L(T) = \llbracket T \rrbracket = \{a, af, acf, acb, acbf, acbb, acbbf, \dots\}$
- ▶ **Membership checking**: does  $w \in L(T)$  hold?

# Regular expressions

- ▶ Ubiquitous in database and programming languages
  - ▶ data extraction from text
  - ▶ path expressions in query languages over tree- and graph-shaped data
- ▶ Standard REs:

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T^*$$

- ▶ Example
  - ▶  $T = a \cdot (c + d)^* \cdot (f + \epsilon)$
  - ▶  $L(T) = \llbracket T \rrbracket = \{a, af, acf, acb, acbf, acbb, acbbf, \dots\}$
- ▶ **Membership checking**: does  $w \in L(T)$  hold?
- ▶ Polynomial for standard REs [[J.E. Hopcroft and J.D. Ullman1979](#)]

## Adding counting # and shuffle &

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T[n..m] \mid T \& T \mid$$

- ▶ Attracted research interest in recent years, useful for XML/JSON schema languages

## Adding counting # and shuffle &

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T[n..m] \mid T \& T \mid$$

- ▶ Attracted research interest in recent years, useful for XML/JSON schema languages
- ▶ Counting
  - ▶  $T = a \cdot (b + c) [2..3]$
  - ▶  $\llbracket T \rrbracket = \{a, acc, abc, abb, abc, accc, abcc, abbc, abcc, accb, abcb, abbb, abcb\}$

## Adding counting # and shuffle &

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T[n..m] \mid T \& T \mid$$

- ▶ Attracted research interest in recent years, useful for XML/JSON schema languages
- ▶ Counting
  - ▶  $T = a \cdot (b + c) [2..3]$
  - ▶  $\llbracket T \rrbracket = \{a, acc, abc, abb, abc, accc, abcc, abbc, abcc, accb, abcb, abbb, abcb\}$
- ▶ Shuffle
  - ▶  $T = (a \cdot b) \& (X \cdot Y)$
  - ▶  $\llbracket T \rrbracket = \{abXY, aXbY, aXYb, XabY, XaYb, XYab\}$



## Adding counting # and shuffle &

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T[n..m] \mid T \& T \mid$$

- ▶ Attracted research interest in recent years, useful for XML/JSON schema languages
- ▶ Counting
  - ▶  $T = a \cdot (b + c) [2..3]$
  - ▶  $\llbracket T \rrbracket = \{a, acc, abc, abb, abc, accc, abcc, abbc, abcc, accb, abcb, abbb, abcb\}$
- ▶ Shuffle
  - ▶  $T = (a \cdot b) \& (X \cdot Y)$
  - ▶  $\llbracket T \rrbracket = \{abXY, aXbY, aXYb, XabY, XaYb, XYab\}$
- ▶ Membership is NP-hard for RE(&) [[Mayer and Stockmeyer1994](#)]

## Adding counting # and shuffle &

$$T ::= \epsilon \mid a \mid T + T \mid T \cdot T \mid T[n..m] \mid T \& T \mid$$

- ▶ Attracted research interest in recent years, useful for XML/JSON schema languages
- ▶ Counting
  - ▶  $T = a \cdot (b + c) [2..3]$
  - ▶  $\llbracket T \rrbracket = \{a, acc, abc, abb, abc, accc, abcc, abbc, abcc, accb, abcb, abbb, abcb\}$
- ▶ Shuffle
  - ▶  $T = (a \cdot b) \& (X \cdot Y)$
  - ▶  $\llbracket T \rrbracket = \{abXY, aXbY, aXYb, XabY, XaYb, XYab\}$
- ▶ Membership is NP-hard for  $\text{RE}(\&)$  [[Mayer and Stockmeyer1994](#)]
- ▶ But is polynomial for  $\text{RE}(\#)$  [[Kilpeläinen and Tuhkanen2003](#)]

## Our results

- ▶ Polynomial membership checking for a class of REs including  $\&$  and  $\#$ , obtained by means of mild restrictions
- ▶ More precisely
  - ▶ Quadratic membership-checking algorithm based on *constraints* for REs
  - ▶ Characterisation of a stability property, and its use for the design of linear membership algorithms
  - ▶ Extension of n-ary REs enriched with unordered concatenation, application to XML schema
  - ▶ Extensive experiments

# The conflict-free restriction

- ▶ Conflict-free REs

- ▶ *counting restricted to symbols:*

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T$$

- ▶ *single occurrence:* for any  $a[m..n]$  and  $a'[m'..n']$  in  $T$ ,  $a$  is different from  $a'$ .

# The conflict-free restriction

- Conflict-free REs

- *counting restricted to symbols:*

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T$$

- *single occurrence:* for any  $a[m..n]$  and  $a'[m'..n']$  in  $T$ ,  $a$  is different from  $a'$ .

- Used very often in practice, especially in the setting of XML schemas  
[Barbosa et al.2006, Choi2002].

- Example:

$$T = (a[1..3] \cdot b[2..2]) + c[1..*]$$

- Counterexamples

$$T' = (a[1..3] \cdot b[2..2])[3..4] + c[1..*]$$

$$T'' = (a[1..3] \cdot b[2..2]) + a[5..*]$$

# The conflict-free restriction

- Conflict-free REs

- *counting restricted to symbols:*

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T$$

- *single occurrence:* for any  $a[m..n]$  and  $a'[m'..n']$  in  $T$ ,  $a$  is different from  $a'$ .

- Used very often in practice, especially in the setting of XML schemas  
[Barbosa et al.2006, Choi2002].

- Example:

$$T = (a[1..3] \cdot b[2..2]) + c[1..*]$$

- Counterexamples

$$T' = (a[1..3] \cdot b[2..2])[3..4] + c[1..*]$$

$$T'' = (a[1..3] \cdot b[2..2]) + a[5..*]$$

- Benefits:

- inclusion  $T \leq U$  over CF-REs can be decided in polynomial time [Colazzo et al.2009b]

- even in the mixed case  $T \leq U$  where only  $U$  is CF  
[Colazzo et al.2009a, Colazzo et al.2013b, Colazzo et al.2013a].

- Quasi linear membership [Ghelli et al.2008] - extended abstract of this paper.

# The conflict-free restriction

- Conflict-free REs

- *counting restricted to symbols:*

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T$$

- *single occurrence:* for any  $a[m..n]$  and  $a'[m'..n']$  in  $T$ ,  $a$  is different from  $a'$ .

- Used very often in practice, especially in the setting of XML schemas  
[Barbosa et al.2006, Choi2002].

- Example:

$$T = (a[1..3] \cdot b[2..2]) + c[1..*]$$

- Counterexamples

$$T' = (a[1..3] \cdot b[2..2])[3..4] + c[1..*]$$

$$T'' = (a[1..3] \cdot b[2..2]) + a[5..*]$$

- Benefits:

- inclusion  $T \leq U$  over CF-REs can be decided in polynomial time [Colazzo et al.2009b]

- even in the mixed case  $T \leq U$  where only  $U$  is CF  
[Colazzo et al.2009a, Colazzo et al.2013b, Colazzo et al.2013a].

- Quasi linear membership [Ghelli et al.2008] - extended abstract of this paper.

- Main ingredient of our approaches: constraint-based characterisation of CF expressions [Colazzo et al.2009b].

# The constraints

- ▶ To illustrate the intuition behind our constraints, consider again

$$T = ((a [1..3] \cdot b [2..2]) + c [1..*])$$

- ▶ It can be fully represented by the *conjunction* of the following constraints:
- ▶ Flat constraints  $\mathcal{FC}(T)$  :
  - ▶ Lower-bound:  $abc^+$
  - ▶ Upper-bound:  $\text{upper}(abc)$
  - ▶ Cardinality:  $a?[1..3] \wedge b?[2..2] \wedge c?[1..*]$
- ▶ Nested constraints  $\mathcal{NC}(T)$  :
  - ▶ Co-occurrence :  $a^+ \Leftrightarrow b^+ \wedge b^+ \Leftrightarrow a^+$
  - ▶ Order:  $a \prec b$
  - ▶ Mutual exclusion:  $(a \prec c \wedge c \prec a) \wedge (b \prec c \wedge c \prec b)$



# Syntax and semantics

$$F ::= A^+ \mid A^+ \Rightarrow B^+ \mid a?[m..n] \mid \text{upper}(A) \mid a \prec b \mid F \wedge F' \mid \mathbf{true}$$

$$\begin{aligned} w \models A^+ &\Leftrightarrow (S(w) \cap A) \neq \emptyset, \text{ i.e., some } a \in A \text{ appears in } w \\ w \models A^+ \Rightarrow B^+ &\Leftrightarrow w \not\models A^+ \text{ or } w \models B^+ \\ w \models a?[m..*] &\Leftrightarrow \text{if } a \text{ appears in } w, \text{ then it appears at least } m \text{ times} \\ w \models a?[m..n] &\Leftrightarrow \text{if } a \text{ appears in } w, \text{ then it appears at least } m \text{ times} \\ &\quad (n \neq *) \text{ and at most } n \text{ times} \\ w \models a \prec b &\Leftrightarrow \text{there is no occurrence of } a \text{ in } w \text{ that follows an occurrence} \\ &\quad \text{of } b \text{ in } w \text{ (hence, both } a \text{ and } b \text{ may be missing)} \\ w \models \text{upper}(A) &\Leftrightarrow S(w) \subseteq A \\ w \models F_1 \wedge F_2 &\Leftrightarrow w \models F_1 \text{ and } w \models F_2 \\ w \models \mathbf{true} &\Leftrightarrow \text{always} \end{aligned}$$

# Abbreviations

$$\begin{array}{lll} A^+ \Leftrightarrow B^+ & =_{def} & A^+ \Rightarrow B^+ \wedge B^+ \Rightarrow A^+ \\ a \prec\succ b & =_{def} & (a \prec b) \wedge (b \prec a) \\ A \prec B & =_{def} & \bigwedge_{a \in A, b \in B} a \prec b \\ A \prec\succ B & =_{def} & \bigwedge_{a \in A, b \in B} a \prec\succ b \\ \mathbf{false} & =_{def} & \emptyset^+ \\ A^- & =_{def} & A^+ \Rightarrow \emptyset^+ \end{array}$$

## Constraint extraction

- ▶ Quadratic time extraction, soundness and completeness [Colazzo et al.2009b]:

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{NC}(T)$$

- ▶ An expression  $T$  is nullable, noted as  $N(T)$ , iff  $\epsilon \in \llbracket T \rrbracket$
- ▶ To illustrate, consider  $T = ((a + \epsilon) \& b [1..5]) \cdot (c + d [1..*])$ , note that  $N(a + \epsilon)$

- ▶ CC:  $a^+ \Rightarrow b^+ \wedge ab^+ \Leftrightarrow cd^+$

- ▶ OC:  $c \prec\succ d \wedge ab \prec cd$

- ▶ Flat:

$abcd^+ \wedge$	Lower-bound
$a?[1..1] \wedge b?[1..5] \wedge c?[1..1] \wedge d?[1..*] \wedge$	Cardinality
$\text{upper}(abcd)$	Upper-bound

## Constraint residuation

- $F \xrightarrow{a} F'$  means that  $F$  is transformed (or residuated) into  $F'$  by parsing the symbol  $a$
- Main cases:

Computing the residual of a nested co-occurrence constraint.

Condition	$a \in A$	$a \in B$	$a \in A$	$a \in B$	$a \in A$
$F$	$A^+ \models B^+$	$A^+ \models B^+$	$A^+ \Leftrightarrow B^+$	$A^+ \Leftrightarrow B^+$	$A^+$
$F'$	$B^+$	<b>true</b>	$B^+$	$A^+$	<b>true</b>

Computing the residual of a nested order constraint.

Condition	$a \in A$	$a \in B$	$a \in A$	$a \in B$	$a \in A$
$F$	$A \prec B$	$A \prec B$	$A \prec \succ B$	$A \prec \succ B$	$A^-$
$F'$	$A \prec B$	$A^-$	$B^-$	$A^-$	<b>false</b>

# Word membership checking

- ▶ Residuation is shifted to words  $F \xrightarrow{w}* F'$  in the obvious way:

$$\begin{array}{l} F \xrightarrow{\epsilon}* F \\ F \xrightarrow{aw}* F'' \quad \Leftrightarrow_{\text{def}} \quad F \xrightarrow{a} F' \wedge F' \xrightarrow{w}* F'' \end{array}$$

- ▶ Corresponds to constraint semantics

$$w \models F \Leftrightarrow F \downarrow^w \mathbf{true}$$


- ▶ Example of residuation:

$$ab^+ \Leftrightarrow cd^+ \xrightarrow{b} cd^+ \xrightarrow{a} cd^+ \xrightarrow{c} \mathbf{true}$$

- ▶ In order to check  $w \in \llbracket T \rrbracket$  we can residuate  $\mathcal{NC}(T)$
- ▶ Complexity:  $O(|w| * |\mathcal{NC}(T)|)$ :
  - ▶ given  $w$ , for each constraint  $F$  in  $\mathcal{NC}(T)$ , we need to eventually parse the whole  $w$  in order to evaluate  $F \downarrow^w G$ .

## We can do much better


- Keep constraints/residuals implicit in a tree-shaped data structure with size  $O(|T|)$
- For  $T = ((a + \epsilon) \& b [1..5]) \cdot (c + d^+)$  we have:



- The two nullable nodes have double line in the picture.


## Residuation algorithm

- For each character  $a$  from the input word  $w$ :
  - it scans the ancestors of  $a[m..n]$  in the constraint tree,
  - residuates all the constraints in this branch, and keeps track of all the resulting  $A^+$  constraints.




## Residuation algorithm

- ▶ For each character  $a$  from the input word  $w$ :
  - ▶ it scans the ancestors of  $a[m..n]$  in the constraint tree,
  - ▶ residuates all the constraints in this branch, and keeps track of all the resulting  $A^+$  constraints.
- ▶ At the end of  $w$ , it checks that all the  $A^+$  constraints have been further residuated into **true** – the generation of a **false** causes an immediate failure.
- ▶ Flat constraints can be trivially checked in constant time for each symbol.







## Optimising tree representation



Evolution of the tree while parsing  $bbac$  for  
 $T = ((a + \epsilon) \& b [1..5]) \cdot (c + d^+)$




Initial tree




after  $\underline{b}$  and after  $b\underline{b}$

$a^+ \Rightarrow b^+ \xrightarrow{b} \mathbf{true} \xrightarrow{b} \mathbf{true}$      $ab^+ \Leftrightarrow cd^+ \xrightarrow{b} cd^+ \xrightarrow{b} cd^+$

# Evolution of the tree while parsing $bbac$ for $T = ((a + \epsilon) \& b [1..5]) \cdot (c + d^+)$




Initial tree



after  $\underline{b}$  and after  $b\underline{b}$


$$a^+ \Rightarrow b^+ \xrightarrow{b} \mathbf{true} \xrightarrow{b} \mathbf{true} \quad ab^+ \Leftrightarrow cd^+ \xrightarrow{b} cd^+ \xrightarrow{b} cd^+$$




after  $bba$

constraints unchanged

Evolution of the tree while parsing  $bbac$  for  
 $T = ((a + \epsilon) \& b [1..5]) \cdot (c + d^+)$




Initial tree




after  $\underline{b}$  and after  $b\underline{b}$

$a^+ \Rightarrow b^+ \xrightarrow{b} \mathbf{true} \xrightarrow{b} \mathbf{true} \quad ab^+ \Leftrightarrow cd^+ \xrightarrow{b} cd^+ \xrightarrow{b} cd^+$



after  $bba$

constraints unchanged



after  $bbac$

$cd^+ \xrightarrow{c} \mathbf{true} \quad ab \prec cd \xrightarrow{c} ab^-$

## Soundness and completeness, complexity

- ▶  $Member(w, T)$  yields *true* iff  $w \in \llbracket T \rrbracket$ 
  - ▶ Follows from the fact the algorithm checks both nested and flat constraints of  $T$ .
- ▶  $Member(w, T)$  runs in time  $O(|T| + |w| * depth(T))$ 
  - ▶ The constraint tree can be built in time  $O(|T|)$ .
  - ▶ For every symbol  $a$  in  $w$ , only visit the path from the leaf node  $a$  to the root.
  - ▶ For each node in this path, a constant number of unit time operations is executed.
  - ▶ The final check on CC constraints scans at most  $|T|$  nodes, while flat constraints can be checked in linear time.

## Linear membership via stability

- ▶ The MEMBER algorithm visits all ancestors of an  $a$ -leaf every time  $a$  is found in  $w$ , which is redundant.
- ▶ We can avoid redundant operations, by relying on the fact that some constraints become stable after residuation (already seen in the example).

## Linear membership via stability

- ▶ The MEMBER algorithm visits all ancestors of an  $a$ -leaf every time  $a$  is found in  $w$ , which is redundant.
- ▶ We can avoid redundant operations, by relying on the fact that some constraints become stable after residuation (already seen in the example).
- ▶ Crucial observation: whenever a node constraint has been residuated because a symbol of  $A_L$  has been met, there is *almost* no reason to visit the node again because of a symbol from  $A_L$  (and the same holds for  $A_R$ )

## Linear membership via stability

- ▶ More precisely, given the first  $a \in A_1$ 
  - ▶  $A_1^+$  becomes **true**
  - ▶  $A_1^+ \models A_2^+$  or  $A_1^+ \Leftrightarrow A_2^+$  becomes  $A_2^+$ .
  - ▶  $A_1 \prec\triangleright A_2$  becomes  $A_2^-$ .



## Linear membership via stability

- ▶ More precisely, given the first  $a \in A_1$ 
  - ▶  $A_1^+$  becomes **true**
  - ▶  $A_1^+ \models A_2^+$  or  $A_1^+ \Leftrightarrow A_2^+$  becomes  $A_2^+$ .
  - ▶  $A_1 \prec\succ A_2$  becomes  $A_2^-$ .
- ▶ None of the obtained constraints can be affected by a second symbol from  $A_1$ .
- ▶ There is only one exception, for the constraint  $A_1 \prec A_2$


## Linear membership via stability

- ▶ More precisely, given the first  $a \in A_1$ 
  - ▶  $A_1^+$  becomes **true**
  - ▶  $A_1^+ \models A_2^+$  or  $A_1^+ \Leftrightarrow A_2^+$  becomes  $A_2^+$ .
  - ▶  $A_1 \prec\succ A_2$  becomes  $A_2^-$ .
- ▶ None of the obtained constraints can be affected by a second symbol from  $A_1$ .
- ▶ There is only one exception, for the constraint  $A_1 \prec A_2$ 
  - ▶ the first  $a \in A_1$  does not residue it
  - ▶ but a subsequent symbol in  $A_2$  residues it into  $A_1^-$
  - ▶ so another  $a' \in A_1$  cannot be ignored, as it will cause the algorithm to *end* and yield “false”.


## Linear mebership

- ▶ Our algorithm MEMBERSTAB exploits stability and has  $O(|T| + |w|)$  complexity.
- ▶ In a nutshell, it ‘deactivates’ the edges along the paths that are visited, since they do not need to be visited again, unless an  $A_1 \prec A_2$  node is residuated to  $A_1^-$
- ▶ In this last case the paths below  $A_1$  are eventually re-activated, but this is done at most once: as soon as one of the re-activated paths is traversed the algorithm stops, and the checking fails.
- ▶ So, in MEMBERSTAB each edge is traversed at most three times for any word  $w$ , and this yields linearity.
- ▶ Let’s see un example.

# MemberStab example, $T = a \cdot (b \cdot c)$ and $w = bbc b$




Initial tree



After b: residuation and edge discarding

After bb: no action



After bbc: the (4,3) edge is restored

After bbcb: return **false**

## Also in the paper

- ▶ Extension with unordered concatenation
- ▶ Extension to n-ary types (still linear)
- ▶ Extensive experiments.

Thank you !

## Adding unordered concatenation

$$w \in \llbracket T_1 \% T_2 \% \dots \% T_n \rrbracket \iff \exists \pi \in S_n. w \in \llbracket T_{\pi(1)} \cdot T_{\pi(2)} \cdot \dots \cdot T_{\pi(n)} \rrbracket$$

- ▶ Not associative
- ▶ So we have considered n-ary expressions of the form

$$T_1 \otimes \dots \otimes T_n$$

with  $\otimes$  ranging over  $\{\cdot, \&, \%\}$

- ▶ Needed to switch to flat-constraints

$$F ::= \% \{A_1, \dots, A_n\} \mid A_1 \prec \dots \prec A_n \mid A_0^+ \models \{A_1^+, \dots, A_n^+\} \mid \dots$$

- ▶ Residuation for  $\%$  constraints generates hybrid constraints including  $\prec$ -constraints.
- ▶ To illustrate, let  $a \in A_2$

$$\% \{A_1, A_2, A_3\} \xrightarrow{a} A_2 \prec \% \{A_1, A_3\}$$

## MemberFlat and MemberFlatStab

- ▶ MemberFlat is a generalisation of Member to n-ary expressions/constraints
- ▶ Complexity is  $O(|T| + |w| * flatdepth(T))$  where  $flatdepth(T)$  is the depth of the type after all operators have been flattened.
- ▶ Quasi linear as  $flatdepth(T)$  has in practice  $flatdepth(T) < 4$
- ▶ We have proved that stability transposes to the n-ary case, thus obtaining MemberFlatStab
- ▶ Linear complexity  $O(|T| + |w|)$
- ▶ Also in the paper: multiword checking and application to XML schema membership




## Performance and scalability

- ▶ We implemented our algorithms in Java
- ▶ To perform experimental analysis we performed comparisons with a baseline approach based on Brzowski derivatives - as we did not find any competitor.
- ▶ Brzowski derivatives are widely used to check membership, and to define finite state automata for REs.
- ▶ Examples:
  - ▶  $d_a(a[2..4]) = a[1..3]$
  - ▶  $d_a(d_a(a[2..4])) = a[0..2]$
  - ▶  $d_a(a[0..0]) = \emptyset$
  - ▶  $d_a(a[2..4] + b[1..3]) = d_a(a[2..4])$
  - ▶  $d_a((b[1..3] + \epsilon) \cdot a[2..4]) = d_a(a[2..4])$
- ▶ Complete formalisation in the paper.
- ▶ Soundness and completeness:  $w \in \llbracket T \rrbracket \Leftrightarrow \epsilon \in \llbracket d_w(T) \rrbracket$
- ▶ Complexity of the baseline algorithm is  $O(|w| * |T|^2)$ .

## Performance and scalability


- ▶ We implemented a generator of synthetic expressions ensuring that operators have same probability of being generated
- ▶ For adopted types binary depth is 15 while flat depth is 4.
- ▶ We generated both positive and negative sets of words for each expression.
- ▶ The data generation algorithm guarantees that the expression is *equally covered* by the words.
- ▶ For each generated  $T$  we generated 30000 positive/negative words having from 1000 to 5000 symbols each

# Positive experiments



Positive experiments for  $\text{cf-RE}(\#, \&)$ : logarithmic scale.

## Positive experiments



Positive experiments for cf-RE( $\#$ ,  $\&$ ): binary and flat algorithms.

# Positive experiments




Figure: Positive experiments for cf-RE( $\#$ ,  $\&$ ,  $\%$ ): logarithmic scale.

# Negative experiments




Figure: Negative experiments for cf-RE( $\#$ ,  $\&$ ): logarithmic scale on y-axis.

# Negative experiments




Figure: Negative experiments for cf-RE(#, &, %).

# Negative experiments




Figure: Negative experiments for  $\text{cf-RE}(\#, \&)$ : random words.



# Negative experiments










Figure: Negative experiments for cf-RE( $\#$ ,  $\&$ ,  $\%$ ): random words.

## Related works and conclusion


- ▶ Regular expressions have been extensively studied in the past (see the paper for an overview).
- ▶ Past studies [[Gelade et al.2009](#), [Hovland2012](#)] have focused on extended REs, but no linear algorithm has been provided for a significative restriction.
- ▶ We have shown how restrictions and constraints can help in separating main properties that have to be checked during membership checking.
- ▶ This has enabled us to devise optimisations for specific aspects like order co-occurrence and order constraints.
- ▶ Experiments have validated complexity analysis on positive data sets.
- ▶ Surprisingly enough, experiments on negative data sets revealed that in this setting even a baseline algorithm can be competitive.


-  Carlos Buil Aranda, Marcelo Arenas, Óscar Corcho, and Axel Polleres. 2013. Federating queries in SPARQL 1.1: Syntax, semantics and evaluation. *J. Web Sem.* 18, 1 (2013), 1–17.
-  Andrey Balmin, Yannis Papakonstantinou, and Victor Vianu. 2004. Incremental validation of XML documents. *ACM Trans. Database Syst.* 29, 4 (2004), 710–751.
-  Denilson Barbosa, Gregory Leighton, and Andrew Smith. 2006. Efficient Incremental Validation of XML Documents After Composite Updates. In *XSym (LNCS)*, Vol. 4156. Springer, 107–121.
-  Denilson Barbosa, Alberto O. Mendelzon, Leonid Libkin, Laurent Mignet, and Marcelo Arenas. 2004. Efficient Incremental Validation of XML Documents.. In *Proceedings of the 20th International Conference on Data Engineering, ICDE 2004*. IEEE Computer Society, 671–682.
-  Geert Jan Bex, Frank Neven, and Jan Van den Bussche. 2004.





DTDs versus XML Schema: A Practical Study. In *Proceedings of the Seventh International Workshop on the Web and Databases, WebDB 2004, June 17-18, 2004, Colocated with ACM SIGMOD/PODS 2004*. 79–84.






 Geert Jan Bex, Frank Neven, Thomas Schwentick, and Stijn Vansummeren. 2010. Inference of concise regular expressions and DTDs. *ACM Trans. Database Syst.* 35, 2 (2010), 11:1–11:47.






 Geert Jan Bex, Frank Neven, and Stijn Vansummeren. 2007. Inferring XML Schema Definitions from XML Data. In *VLDB*. 998–1009.

 Henrik Björklund, Wim Martens, and Thomas Timm. 2015. Efficient Incremental Evaluation of Succinct Regular Expressions. In *Proceedings of the 24th ACM International on Conference on Information and Knowledge Management, CIKM 2015*. ACM, 1541–1550.

 Iovka Boneva, Radu Ciucanu, and Slawek Staworko. 2013. Simple Schemas for Unordered XML. In *Proceedings of the 16th International Workshop on the Web and Databases 2013, WebDB 2013*. 13–18.

-  Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, François Yergeau, and John Cowan. 2006.  
*Extensible Markup Language (XML) 1.1 (Second Edition)*.  
Technical Report. World Wide Web Consortium.  
W3C Recommendation.
-  Anne Brüggemann-Klein. 1993.  
Unambiguity of Extended Regular Expressions in SGML Document Grammars. In *Algorithms - ESA '93, First Annual European Symposium, Bad Honnef, Germany, September 30 - October 2, 1993, Proceedings (Lecture Notes in Computer Science)*, Vol. 726. Springer, 73–84.
-  Anne Brüggemann-Klein and Derick Wood. 1992.  
Deterministic Regular Languages. In *STACS 92, 9th Annual Symposium on Theoretical Aspects of Computer Science, Cachan, France, February 13-15, 1992, Proceedings (Lecture Notes in Computer Science)*, Vol. 577. Springer, 173–184.
-  Anne Brüggemann-Klein and Derick Wood. 1998.  
One-Unambiguous Regular Languages.  
*Inf. Comput.* 142, 2 (1998), 182–206.

-  Janusz A. Brzozowski. 1964.  
Derivatives of Regular Expressions.  
*J. ACM* 11, 4 (1964), 481–494.
-  Byron Choi. 2002.  
What are real DTDs like?. In *WebDB*. 43–48.
-  Dario Colazzo, Giorgio Ghelli, Luca Pardini, and Carlo Sartiani. 2009c.  
Linear inclusion for XML regular expression types. In *Proceedings of the 18th ACM Conference on Information and Knowledge Management, CIKM 2009, Hong Kong, China, November 2-6, 2009*. ACM, 137–146.
-  Dario Colazzo, Giorgio Ghelli, Luca Pardini, and Carlo Sartiani. 2013a.  
Almost-linear inclusion for XML regular expression types.  
*ACM Trans. Database Syst.* 38, 3 (2013), 15.
-  Dario Colazzo, Giorgio Ghelli, Luca Pardini, and Carlo Sartiani. 2013b.  
Efficient asymmetric inclusion of regular expressions with interleaving and counting for XML type-checking.  
*Theor. Comput. Sci.* 492 (2013), 88–116.

-  [Dario Colazzo, Giorgio Ghelli, and Carlo Sartiani. 2009a.](#)  
Efficient asymmetric inclusion between regular expression types. In *ICDT (ACM International Conference Proceeding Series)*, Ronald Fagin (Ed.), Vol. 361. ACM, 174–182.
-  [Dario Colazzo, Giorgio Ghelli, and Carlo Sartiani. 2009b.](#)  
Efficient inclusion for a class of XML types with interleaving and counting. *Inf. Syst.* 34, 7 (2009), 643–656.
-  [Silvano Dal-Zilio and Denis Lugiez. 2003.](#)  
XML Schema, Tree Logic and Sheaves Automata. In *Rewriting Techniques and Applications, 14th International Conference, RTA 2003, Valencia, Spain, June 9-11, 2003, Proceedings (Lecture Notes in Computer Science)*, Vol. 2706. Springer, 246–263.
-  [David C. Fallside and Priscilla Walmsley. 2004.](#)  
XML Schema Part 0: Primer – Second Edition.  
(Oct 2004).  
[W3C Recommendation.](#)
-  [Wouter Gelade, Marc Gyssens, and Wim Martens. 2012.](#)

Regular Expressions with Counting: Weak versus Strong Determinism.

*SIAM J. Comput.* 41, 1 (2012), 160–190.



Wouter Gelade, Wim Martens, and Frank Neven. 2009.

Optimizing Schema Languages for XML: Numerical Constraints and Interleaving.

*SIAM J. Comput.* 38, 5 (2009), 2021–2043.



Giorgio Ghelli, Dario Colazzo, and Carlo Sartiani. 2007.

Efficient Inclusion for a Class of XML Types with Interleaving and Counting. In *Database Programming Languages, 11th International Symposium, DBPL 2007, Vienna, Austria, September 23-24, 2007, Revised Selected Papers (Lecture Notes in Computer Science)*, Marcelo Arenas and Michael I. Schwartzbach (Eds.), Vol. 4797. Springer, 231–245.



Giorgio Ghelli, Dario Colazzo, and Carlo Sartiani. 2008.

Linear time membership in a class of regular expressions with interleaving and counting. In *Proceedings of the 17th ACM Conference on Information and Knowledge Management, CIKM 2008, Napa Valley, California, USA, October 26-30, 2008*. ACM, 389–398.



V M Glushkov. 1961.



The Abstract Theory of Automata.

*Russian Mathematical Surveys* 16, 5 (1961), 1.



Charles F. Goldfarb. 1990.

*SGML handbook*.

Clarendon Press.



Steve Harris and Andy Seaborne. 2013.

*SPARQL 1.1 Query Language*.

Technical Report. World Wide Web Consortium.

W3C Recommendation.



Dag Hovland. 2012.





The Membership Problem for Regular Expressions with Unordered Concatenation and Numerical Constraints. In *Language and Automata Theory and Applications - 6th International Conference, LATA 2012, A Coruña, Spain, March 5-9, 2012*.






*Proceedings (Lecture Notes in Computer Science)*, Adrian Horia Dediu and Carlos Martín-Vide (Eds.), Vol. 7183. Springer, 313–324.



J.E. Hopcroft and J.D. Ullman. 1979.

*Introduction to Automata Theory, Languages and Computation*.

-  [Pekka Kilpeläinen and Rauno Tuhkanen. 2003.](#)  
Regular Expressions with Numerical Occurrence Indicators - preliminary results. In *Proceedings of the Eighth Symposium on Programming Languages and Software Tools, SPLST'03, Kuopio, Finland, June 17-18, 2003*, Pekka Kilpeläinen and Niina Päivinen (Eds.). University of Kuopio, Department of Computer Science, 163–173.
-  [Pekka Kilpeläinen and Rauno Tuhkanen. 2004.](#)  
Towards efficient implementation of XML schema content models. In *Proceedings of the 2004 ACM Symposium on Document Engineering, Milwaukee, Wisconsin, USA, October 28-30, 2004*. ACM, 239–241.
-  [Leonid Libkin, Wim Martens, and Domagoj Vrgoc. 2016.](#)  
Querying Graphs with Data.  
*J. ACM* 63, 2 (2016), 14.
-  [Anthony Mansfield. 1983.](#)  
On the computational complexity of a merge recognition problem.  
*Discrete Applied Mathematics* 5, 1 (1983), 119 – 122.

-  Alain J. Mayer and Larry J. Stockmeyer. 1994.  
Word Problems — This Time with Interleaving.  
*Inf. Comput.* 115, 2 (1994), 293–311.
-  Anders Møller. 2010.  
dk.brics.automaton – Finite-State Automata and Regular Expressions for Java.  
(2010).  
<http://www.brics.dk/automaton/>.
-  Manizheh Montazerian, Peter T. Wood, and Seyed R. Mousavi. 2007.  
XPath Query Satisfiability is in PTIME for Real-World DTDs. In *XSym (LNCS)*,  
Vol. 4704. Springer, 17–30.
-  Sushant Patnaik and Neil Immerman. 1997.  
Dyn-FO: A Parallel, Dynamic Complexity Class.  
*J. Comput. Syst. Sci.* 55, 2 (1997), 199–209.
-  Randy Smith, Cristian Estan, Somesh Jha, and Shijin Kong. 2008.  
Deflating the big bang: fast and scalable deep packet inspection with extended finite  
automata. In *Proceedings of the ACM SIGCOMM 2008 Conference on Applications*,

*Technologies, Architectures, and Protocols for Computer Communications*, Seattle, WA, USA, August 17-22, 2008. ACM, 207–218.



C. M. Sperberg-McQueen. 2004.

*Notes on finite state automata with counters.*

Technical Report.

Available at <http://www.w3.org/XML/2004/05/msm-cfa.html>.



C. M. Sperberg-McQueen. 2005.

Applications of Brzozowski derivatives to XML Schema processing. In *Proceedings of the Extreme Markup Languages® 2005 Conference*.



Henry S. Thompson, David Beech, Murray Maloney, and Noah Mendelsohn. 2004.

*XML Schema Part 1: Structures Second Edition.*

Technical Report. World Wide Web Consortium.

W3C Recommendation.



Manfred K. Warmuth and David Haussler. 1984.

On the Complexity of Iterated Shuffle.

*J. Comput. Syst. Sci.* 28, 3 (1984), 345–358.



Peter T. Wood. 2003.

Containment for XPath Fragments under DTD Constraints. In *Proceedings of the 9th International Conference on Database Theory - ICDT 2003, Siena, Italy, January 8-10, 2003 (Lecture Notes in Computer Science)*, Vol. 2572. Springer, 297–311.