



## 3D localization from omnidirectional video



## Matching 2D image edges with 3D model line segments




R: camera rotation  
T: camera translation  
 $e_i$ : image line  
 $l_j$ : model line segment  
 $\alpha$ : error angle

Minimize:

$$\xi(R, T) = \frac{1}{n} \cdot \sum_{i=1}^n \alpha(e_i, R, T, l_i)^2$$


Correspondence = 1 model line + 1 image edge

Number of correspondences needed varies with conditions.




## The three-line alignment algorithm


Aligning three 2D image edges (i,j,k) onto three 3D model line segments (r,s,t)




## System Overview




## Maintenance: robust edge-line matching



Correspondence update  
Each correspondence is updated using a hue-based and an angle-based matching function.





Random sample consensus  
We draw a number of random correspondence sets, score them and keep the best one. Inliers are promoted in the state machine. Outliers are demoted.




Correspondence state machine  
Each correspondence is assigned a state that changes over time.



## Initialization Algorithm



For each pair of image edges (r,s) and 3D model lines (i,j), score by comparing angles. Process all pairs and update scoring table.




## Visibility computation using OpenGL



Face visibility computation using OpenGL. Each face in the model is rendered using a unique color.

## Real Datasets

	lab	corridor	handheld
Number of frames	1,500	7,800	1,900
Frame rate (fps)	5	5	15
Excursion duration (min)	5	26	2
Excursion length (m)	120	936	33
Total # of 3D segments	3,000	7,400	3,000
Total surface area (m <sup>2</sup> )	450	7,000	450



## Future Work

- Signature-based initialization
- Better accuracy (sensor fusion)
- Better performance (> 1Hz)
- Online update of the 3D model

## Acknowledgments

We gratefully acknowledge the support of Draper Laboratory's University Independent Research and Development Program.

## References

- A. Ansar and K. Daniilidis. Linear pose estimation from points or lines. In Proc. ECCV, volume 4, pages 282–296, New York, May 2002.
- A. Bartoli and P. Sturm. Structure from motion using lines: Representation, triangulation and bundle adjustment. CVIU, 100(3):416–441, Dec. 2005.
- S. Coorg and S. Teller. Matching and pose refinement with camera pose estimates. Technical Report MIT/LCS/TM-561, MIT, 1996.
- T. Drummond and R. Cipolla. Real-time visual tracking of complex structures. IEEE Trans. PAMI, 24(7):932–946, 2002.
- E. Rosten and T. Drummond. Fusing points and lines for high performance tracking. In IEEE ICCV, volume 2, pages 1508–1515, Beijing, China, 2005.