Inverted MAML Milestone 3: Silicon Evaluation (LR = 0.08x, λ = 1024)

Patent Pending SE 2630397-4 | Open Science Hardware | Trion T120 SoC (192.168.1.50:5000, FW v2.2-MAML) | LR = 0.08, λ = 1024

1. Executive Summary: Fine-Grained Rate & Stiff Regularization Spring

Experimental Objective: Test whether combining a fine-grained learning rate (**LR = 0.08x**) with the stiff restoring spring (**λ = 1024**) maintains strong full-window error reduction while completely preventing the Column 3 rail saturation observed with λ = 341.

Key Empirical Observations:

- **Consistent Full-Window Error Suppression:** Across the 200-sample window [4.5..5.5 ms], active training cut Window Loss by **-19.5% (sustained mean: 61,835 LSB²)** and **-24.6% (minimum: 57,909 LSB² at Ep 240)**, lifting full-window ENOB to **3.83 bits mean (3.88 bits peak)**.
- **Single-Point Peak Resolution at 5.0 ms:** At the nominal 5.0 ms midpoint, closed-loop training achieved a minimum loss of **122 LSB²** at Epoch 273, reaching **8.33 bits Standard ENOB**.
- **Stiff Spring Eliminates Rail Clamping:** The elevated λ = 1024 restoring force successfully holds weights inside the dynamic range, confirming that stiff L2 regularization is essential to counter directional analog drift on physical silicon.

2. Physical In-Data Model & Hyperparameters

- **Temporal Window:** 4500 µs to 5500 µs in 10 strata, K = 20 samples/stratum = 200 Hadamard-active samples per epoch across all 500 epochs.
- **Hyperparameters:** Phase 1 & 2: LR = 0, λ = 0. Phase 3 (Ep 200..500): **LR = 0.08x, λ = 1024**.
- **In-Data Vector Equalizer:** COLOR_LLM_TOEPLITZ (ρ = 0.85) with hardware zero-mean centering (LayerNorm).

3. Empirical Silicon Telemetry Comparison Table (100% Identical Cadence)


Parameter / Metric	Phase 1: M33 Alone	Phase 2: Smart Baseline	Phase 3: Trained Peak	Phase 3: Sustained Mean
Epoch Range & Mode	Ep 0..99 (W=0 LSB)	Ep 100..199 (Smart Base)	Ep 273 (5ms) / Ep 240 (Win)	Ep 200..500 (300 Epochs)
Training Parameters	LR = 0, λ = 0 (OFF)	LR = 0, λ = 0 (OFF)	LR = 0.08, λ = 1024 (ON)	LR = 0.08, λ = 1024 (ON)
Hadamard Batch Cadence	200 samples/ep (ON)	200 samples/ep (ON)	200 samples/ep (ON)	200 samples/ep (ON)
Window Mean Loss [4.5..5.5]	72,836 LSB²	76,845 LSB²	57,909 LSB² (-24.6%)	61,835 LSB²
Window Mean ENOB [4.5..5.5]	3.72 bits	3.68 bits	3.88 bits (Ep 240)	3.83 bits
5.0 ms Center Loss	3,882 LSB² (mean)	4,859 LSB² (mean)	122 LSB² (Ep 273)	4,632 LSB² (mean)
5.0 ms Center ENOB	5.98 b (mean)	5.82 b (mean)	8.33 b (Ep 273)	5.90 b (mean)
M8 Diagonal Weights	[0, 0, 0, 0, 0, 0]	[-20,-20,20,20,-20,20]	[-11, -17, 18, 28, -23, 27]	[-18, -15, 14, 93, 24, 32]

4. 3D Dual-2T1C Weight Topographies (Baseline vs. Trained Golden State at Ep 273)


Subplots 1 & 2 show the balanced Smart S-Bend baseline at Epoch 100. Subplots 3 & 4 show the trained Golden State at Epoch 273 (5.0 ms ENOB 8.33 bits).

INVERTED MAML (λ = 1024, LR = 0.08): 3D Dual-2T1C Weight Topographies (Baseline vs. Trained Golden State)


1. Matrix 3: Calibrated Smart Baseline (Epoch 100, LR=0)




2. Matrix 8: Calibrated Smart Baseline (Epoch 100, LR=0)



3. Matrix 3: Trained Golden State (Epoch 273, 5.0 ms ENOB 8.33b)




4. Matrix 8: Trained Golden State (Epoch 273, 5.0 ms Loss 122 LSB²)




5A. 500-Epoch Trajectories at SINGLE-POINT t = 5.0 ms ONLY (Nominal Center Snapshot)

Figure 2A shows Loss and ENOB measured strictly at the single 5000 µs midpoint. Phase 1 (W = 0) sits at its pre-calibrated sweet spot (mean 3,882 LSB² / 5.98 bits). Upon activating training at Epoch 200, the network achieves sharp peaks up to **8.33 bits (122 LSB² at Ep 273)** while adapting to suppress window edge drift.




5B. 500-Epoch Trajectories Across FULL TEMPORAL WINDOW [4.5 ms to 5.5 ms] AGGREGATED


Figure 2B presents the complete 1000 µs discharge window from 4.5 ms to 5.5 ms. Uncompensated RC decay causes high error in Phase 1 (72,836 LSB²) and Phase 2 (76,845 LSB²). Closed-loop training cuts window loss by **-19.5 % (mean 61,835 LSB²)** and **-24.6 % (minimum 57,909 LSB² at Ep 240)**.



7. Full 2D Trajectories of All Weights (Matrix 3 & Matrix 8 across 500 Epochs)


Tracking all 48 weights of Matrix 3 (top) and 42 weights of Matrix 8 (bottom) across the 500-epoch experiment. Notice the fine-grained adaptation without high-frequency chatter.





8. High-Resolution Phase 3 Deep-Dive (Epochs 200–500)

Isolated view of Phase 3 active training under LR = 0.08x, λ = 1024. Demonstrates stable convergence, smooth gradient steps, and sustained error reduction across the entire 1000 µs window.



9. Physical Hardware Silicon: Inverted MAML Proof-of-Concept PCB (v1.3.2)




Figure 9: Physical Proof-of-Concept Hardware (PCB v1.3.2, Inverted_MAML_IMC).
Designed and fabricated by inventor Olle Welin (Patent Pending SE 2630397-4). Integrates Trion T120 Master SoC, Trion T20 Controller, 74HC595 DAC ladders, 2T1C MOS triode analog multipliers, ColTIAs, and XC2361A ADCs.
Hardware Repository: https://github.com/ollewelin/analog_matrix_computation_Inverted_MAML_PAT_PEND_2630397-4

10. Patented Inverted MAML Proprioceptive Architecture (Patent SE 2630397-4 Fig 1)




Fig 1

Figure 10: Inverted MAML Proprioceptive Closed-Loop Architecture (Patent Application SE 2630397-4, Fig 1).
Digital input (1) drives Matrix 33 (33) and first Vernier Matrix 3 (3). Temporal clock generator (30) drives reference rows (29). Matrix 8 (8) injects anti-phase compensation into summing junctions (35) before final ADC (49).

11. Forward Hadamard Propagation (FHP) & Capacitive Perturbation (Patent Fig 8)

Forward Hadamard Propagation (FHP) – parallel capacitive perturbation for single-shot analog gradient extraction.




Fig 8

Physical Operation of FHP (SE 2630397-4 Fig 8): Orthogonal Walsh carrier square waves drive perturbation capacitors C_PTU (7) onto 2T1C storage gates C_W (44). Fast Hadamard Transform in T120 SoC extracts all partial derivatives in parallel in a single analog snapshot.

12. Overall Conclusion: Single-Point (5.0 ms) vs. Full Temporal Window [4.5 – 5.5 ms]

Trade-Off Analysis: Uncompensated W = 0 excels at the single 5.0 ms point where it was calibrated, but degrades over [4.5..5.5 ms] due to temporal charge leakage. Active training optimizes the full 1.0 ms temporal window, achieving -19.5% sustained error reduction across [4.5..5.5 ms] and reaching 8.33 b peak at 5.0 ms.

12.1 Displaced Temporal Window Sampling (Patent SE 2630397-4 Fig 5, Claim 10)




Fig 5

Figure 11: Displaced Temporal Measurement Windows Across Inference (Patent Fig 5). Shifted offset T_RAND (25) samples time-dependent gradients across the discharge trajectory.

12.2 Compensating Temporal Leakage via Accelerated Reference Cells (Patent Fig 6, Claim 8)




Fig 6

Figure 12: Natural Computing Cell Leakage (31) vs. Accelerated Temporal Reference Decay (32) (Patent Fig 6). Accelerated reference curve (32) normalizes the time axis, enabling the triad to dynamically cancel natural cell leakage (31).

13. Open Science Reproducibility Summary

All telemetry data in this report is 100 % authentic, measured directly on physical silicon hardware via the Efinix Trion T120 SoC at 192.168.1.50:5000 (FW v2.2-MAML). Dataset, RTL, firmware, and Python orchestration tools are open-source at: https://github.com/ollewelin/analog_matrix_computation_Inverted_MAML_PAT_PEND_2630397-4